

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384283
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	You; Jung Sang et al.

Seat for vehicles

Abstract

A seat for vehicles has an assembly structure configured such that a cushion assembly may be mounted on and separated from a seat base through a locking device, and thus allows a cover member configured to cover the cushion assembly to be easily replaced so as to prevent contamination of the cushion assembly and the seat base and damage thereto, such as rust generation, due to contaminants on the cover member.

Inventors: You; Jung Sang (Hwaseong-si, KR), Yoo; Han Su (Hwaseong-si, KR), Park; Guk Mu (Seoul, KR), Jeong; Dong Woo (Gwacheon-si, KR), Kim; Myung Hoe (Seoul, KR), Kim; Eun Sue (Hwaseong-si, KR), Lee; Dae Hee (Incheon, KR), Cho; Jae Hoon (Hwaseong-si, KR), Park; Han Kyung (Hwaseong-si, KR), Shin; Jae Sung (Hwaseong-si, KR), Kwak; Hae Dong (Hwaseong-si, KR), Bok; Kwon Hwa (Hwaseong-si, KR), Hwang; Jun sik (Hwaseong-si, KR)

Applicant: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR); HYUNDAI TRANSYS INC. (Seosan-si, KR)

Family ID: 89170149

Assignee: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR); HYUNDAI TRANSYS INC. (Seosan-si, KR)

Appl. No.: 17/983697

Filed: November 09, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230406179 A1	Dec. 21, 2023

Foreign Application Priority Data

KR	10-2022-0073567	Jun. 16, 2022
----	-----------------	---------------

Publication Classification

Int. Cl.: B60N2/70 (20060101); B60N2/68 (20060101)

U.S. Cl.:

CPC B60N2/7035 (20130101); B60N2/68 (20130101);

Field of Classification Search

CPC: B60N (2/68); B60N (2/7035)

USPC: 297/440.22

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3924892	12/1974	Geier	297/440.22	B60N 2/7035
4065182	12/1976	Braniff	297/440.22 X	B60N 2/7005
4583782	12/1985	Mikuniya	297/440.22	B60N 2/015
5649783	12/1996	Ichikawa	297/440.22 X	B60N 2/015
6761411	12/2003	Boehmer	297/440.22	B60N 2/7005

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2010-0122580	12/2009	KR	N/A

Primary Examiner: Barfield; Anthony D

Attorney, Agent or Firm: MCDONNELL BOEHNEN HULBERT & BERGHOFF LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application claims priority from Korean Patent Application No. 10-2022-0073567, filed on Jun. 16, 2022, in the Korean Intellectual Property Office, the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND

1. Field

(2) The present disclosure relates to a seat for vehicles, and more particularly, to a seat for vehicles provided with a cushion assembly having an assembly structure configured such that the cushion assembly may be mounted on and detached from a seat base.

2. Description of the Related Art

(3) Seats on which passengers sit are provided in a vehicle.

(4) In general, a seat for vehicles is configured such that a cushion part is coupled to a seat base forming the frame of the seat, and the surface of the cushion part is covered with a cover member so as to be protected.

(5) In the conventional seat for vehicles, in which the seat base and the cushion part are coupled to each other so as to be integrated, it is difficult to remove only the cushion part from the seat base, and thereby, it is difficult to replace the cover member with a new one and thus, contaminants on the cover member may contaminate the cushion part and the seat base and damage the cushion part and the seat base, i.e., generate rust thereon.

(6) The above information disclosed in the Background section is only for enhancement of understanding of the background of the disclosure and should not be interpreted as conventional technology that is already known to those skilled in the art.

SUMMARY

(7) Therefore, the present disclosure has been made in view of the above problems, and it is an object of the present disclosure to provide a seat for vehicles provided with a cushion assembly having an assembly structure configured such that the cushion assembly may be mounted on and detached from a seat base, and thus allows a cover member configured to cover the cushion assembly to be easily replaced so as to prevent contamination of the cushion assembly and the seat base and damage thereto, such as rust generation, due to contaminants on the cover member.

(8) In accordance with an aspect of the present disclosure, the above and other objects can be accomplished by the provision of a seat for vehicles including a seat base, a cushion assembly coupled to and assembled with the seat base so as to be separable therefrom, and a locking device configured to couple and separate the cushion assembly to and from the seat base.

(9) The seat base may include seat frames configured to form a frame of the seat for vehicles, and formed of steel, and a frame cover coupled to the seat frames so as to cover the seat frames, and formed of plastic.

(10) The cushion assembly may include a cushion panel having a designated size, a cushion pad configured to surround the cushion panel, and a cover member configured to surround and cover the cushion pad.

(11) The cushion panel may be formed by insert injection molding, and may be coupled to the cushion pad so as to be surrounded by the cushion pad.

(12) The locking device may include a locking button provided on the seat base and pressed by a user to be operated, a locking plate connected to the locking button and having a locking hole formed therethrough, and a locking hook provided on the cushion assembly so as to be inserted into the locking hole, and coupled to or separated from the locking plate depending on whether or not the locking button is operated.

(13) The locking device may further include return springs installed such that both ends thereof are supported by the seat base and the locking button so as to supply restoring force to the locking button.

(14) A button recess opened upwards may be formed in the seat base, and the locking button may be installed to be supported by the return springs inserted into the button recess so as to be movable upwards and downwards.

(15) Button flanges may protrude outwards from the locking button, flange holes configured such that the button flanges are inserted thereinto may be formed in the button recess, and, when the locking button is returned to an original position thereof by spring force of the return springs, the button flanges may be caught by upper ends of the flange holes and may thus fixed, and an initial position of the locking button may be determined.

(16) When a user does not press the locking button, an upper surface of the locking button may be located below an upper surface of the seat base so that the locking button maintains a state of being inserted into the button recess.

(17) The locking plate may be provided to extend downwards from the locking button, guide parts configured to extend downwards from the button recess may be provided in the seat base, and left and right sides of the locking plate may be inserted into the guide parts so as to be movable upwards and downwards along the guide parts.

(18) The locking hook may protrude rearwards from a rear end of the cushion assembly toward the locking plate, a hook groove may be formed in a rear end of the locking hook, and, when the locking plate is inserted into the hook groove, the cushion assembly may be in a locked state, and, when the locking plate is released from the hook groove, the cushion assembly may be in an unlocked state.

(19) In the locked state of the cushion assembly, the rear end of the cushion assembly may be compressed due to contact with the seat base, and may accumulate elastic force therein, and, in the unlocked state of the cushion assembly, a shape of the rear end of the compressed cushion assembly may be restored, and the cushion assembly may be moved forwards to a designated distance with respect to the seat base while restoring the shape of the rear end of the compressed cushion assembly.

(20) Front hooks may be provided at positions of the cushion assembly spaced forwards apart from the locking hook, and, when the cushion assembly is in the locked state due to coupling between the locking hook and the locking plate, the front hooks may be assembled with the seat base.

(21) In accordance with another aspect of the present disclosure, there is provided a seat for vehicles, wherein a cushion assembly is separably coupled to a seat base, the cushion assembly includes a cushion pad formed of a cushioning material and a cover member configured to cover the cushion pad, and the cover member is replaced by separating the cushion assembly from the seat base and then separating the cover member from the cushion pad.

(22) When a user presses a locking button installed in the seat base, coupling between the locking button and a locking hook provided on the cushion assembly may be released, and, when coupling between the locking button and the locking hook is released, the cushion assembly may be in a state of being separable from the seat base.

(23) When the locking button and the locking hook are coupled to each other, the seat base and the cushion assembly may be coupled to each other, and the cushion assembly may be placed on the seat base and be assembled therewith.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) The above and other objects, features and other advantages of the present disclosure will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a perspective view of a seat for vehicles according to the present disclosure;

(3) FIG. 2 is a view showing the state in which a cushion assembly is removed from the seat for vehicles shown in FIG. 1;

(4) FIG. 3 is a perspective view of a seat base;

(5) FIG. 4 is a view showing the state in which an upper cover is removed from the seat base shown in FIG. 3;

(6) FIGS. 5, 6, and 7 are perspective views illustrating the cushion assembly, a cushion panel, and a locking device, respectively;

(7) FIG. 8 is a bottom perspective view of FIG. 7;

(8) FIG. 9 is a side view of a portion of the cushion assembly to which a locking hook is coupled;

(9) FIG. 10 is a bottom perspective view showing a button recess to which the locking device is coupled;

(10) FIGS. 11 and 12 are views illustrating the locked state of the cushion assembly;

(11) FIG. 13 is a view of a portion of the cushion assembly to which a front hook is coupled; and

(12) FIGS. 14 and 15 are views illustrating the unlocked state of the cushion assembly.

DETAILED DESCRIPTION

(13) Reference will now be made in detail to exemplary embodiments of the present disclosure, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts, and a redundant description thereof will be omitted.

(14) In the following description of the embodiments, suffixes, such as “module”, “part” and “unit”, are provided or used interchangeably merely in consideration of ease in statement of the specification, and do not have meanings or functions distinguished from one another.

(15) In the following description of the embodiments of the present disclosure, a detailed description of known functions and configurations incorporated herein will be omitted when it may make the subject matter of the present disclosure rather unclear.

(16) Further, the accompanying drawings will be exemplarily given to describe the embodiments of the present disclosure, and should not be construed as being limited to the embodiments set forth herein, and it will be understood that the embodiments of the present disclosure are provided only to completely disclose the disclosure and cover modifications, equivalents or alternatives which come within the scope and technical range of the disclosure.

(17) In the following description of the embodiments, terms, such as “first” and “second”, are used only to describe various elements, and these elements should not be construed as being limited by these terms. These terms are used only to distinguish one element from other elements.

(18) When an element or layer is referred to as being “connected to” or “coupled to” another element or layer, it may be directly connected or coupled to the other element or layer, or intervening elements or layers may be present.

(19) In contrast, when an element or layer is referred to as being “directly connected to” or “directly coupled to” another element or layer, there may be no intervening elements or layers present.

(20) As used herein, singular forms may be intended to include plural forms as well, unless the context clearly indicates otherwise.

(21) In the following description of the embodiments, the terms “comprises,” “comprising,” “including,” and “having” are inclusive and therefore specify the presence of stated features, integers, steps, operations, elements, components, and/or combinations thereof, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or combinations thereof.

(22) Further, “unit” or “control unit” included in “motor control unit (MCU)”, “hybrid control unit (HCU)”, etc. is widely used to name a controller configured to control a specific function of a vehicle, and does not indicate a generic functional unit.

(23) A controller may include a communication device configured to communicate with other controllers or sensors so as to control an assigned function, a memory configured to store an operating system, logic commands, input and output information, etc., and at least one processor configured to perform determination, calculation, judgement, etc. necessary to control the assigned function.

(24) Hereinafter, a seat for vehicles according to an exemplary embodiment of the present disclosure will be described with reference to the accompanying drawings.

(25) The seat for vehicles according to the present disclosure includes, as shown in FIGS. **1** to **15**, a seat base **100**, a cushion assembly **200** coupled to and assembled with the seat base **100** so as to be separable therefrom, and a locking device **300** configured to couple and separate the cushion assembly **200** to and from the seat base **100**.

(26) The seat for vehicles according to the present disclosure may be assembled by coupling the seat base **100** and the cushion assembly **200** to each other, or may be disassembled by separating the seat base **100** and the cushion assembly **200** from each other, through operation of the locking device **300**.

(27) The seat for vehicles according to the present disclosure may further include a back assembly

400 and a headrest **500**.

(28) The back assembly **400** may be coupled to and assembled with the seat base **100** so as to be separable therefrom by a locking device, in the same manner as the cushion assembly **200**.

(29) A back part of the seat base **100**, to which the back assembly **400** is coupled, may be rotated in the forward and rearward directions about a cushion part of the seat base **100**, to which the cushion assembly **200** is coupled, and thus, the angle of the back part of the seat base **100** may be adjusted.

(30) The headrest **500** may be coupled to the seat base **100** so as to be separable therefrom, and may be coupled to the seat base **100** such that the height of the headrest **500** from the seat base **100** is adjustable, as needed.

(31) The seat base **100** includes a plurality of seat frames **110** configured to form the frame of the seat for vehicles, and a frame cover **120** coupled to the seat frames **110** so as to cover the seat frames **110**.

(32) The seat frames **110** are formed of steel, the frame cover **120** is formed of plastic, and the seat frames **110** are located inside the frame cover **120**.

(33) In order to facilitate assembly of the seat frames **110** and the frame cover **120**, the frame cover **120** is provided as an assembly of an upper cover **121** and a lower cover **122**, and the seat frames **110** are located between the upper cover **121** and the lower cover **122**.

(34) Multiple points of the front parts of the seat frames **110** and multiple points of the rear parts of the seat frames **110** are firmly assembled with the upper cover **121** and the lower cover **122** by screws.

(35) The cushion assembly **200** includes a cushion panel **210** having a designated size, a cushion pad **220** configured to surround the cushion panel **210**, and a cover member **230** configured to surround and cover the cushion pad **220**.

(36) The cushion panel **210** is formed to have a rectangular shape, and is formed of plastic so as to increase stiffness of the cushion assembly **200**.

(37) The cushion pad **220** is a foam pad formed of a cushioning material, and the cushion panel **210** is formed by insert injection molding and is coupled to the cushion pad **220** so as to be surrounded by the cushion pad **220**.

(38) The cover member **230** surrounds the cushion pad **220** so as to protect the cushion pad **220** from foreign substances, and may be formed of fabric or leather.

(39) Since the cover member **230** is coupled to the cushion pad **220** so as to be separable therefrom, when the cover member **230** is contaminated with foreign substances, a worker may separate the cushion assembly **200** from the seat base **100** by operating the locking device **300**, may separate the contaminated cover member **230** from the cushion pad **220**, and may then replace the contaminated cover member **230** with a new clean cover member **230**.

(40) The locking device **300** includes a locking button **310** provided on the seat base **100** and pressed by a user to be operated, a locking plate **320** connected to the locking button **310** and having a locking hole **321** formed therethrough, a locking hook **330** provided on the cushion assembly **200** so as to be inserted into the locking hole **321**, and coupled to or separated from the locking plate **320** depending on whether or not the locking button **310** is operated, and return springs **340** installed such that both ends thereof are supported by the seat base **100** and the locking button **310** so as to supply restoring force to the locking button **310**.

(41) A button recess **130** which is opened upwards is formed in the seat base **100**, and the locking button **310** is installed to be inserted into the button recess **130**.

(42) The button recess **130** is formed in the rear portion of the upper cover **121** of the frame cover **120** of the seat base **100** so as to be opened upwards, and the locking button **310** is installed in the button recess **130** so as to be movable upwards and downwards.

(43) The locking plate **320** may be formed integrally with the locking button **310** so as to extend downwards from the locking button **310**, and the locking hole **321** is formed through the locking plate **320** in the forward and rearward directions.

(44) When the locking button **310** is installed in the button recess **130**, the locking plate **320** penetrates the button recess **130** and protrudes downwards from the button recess **130**, and the locking hole **321** is located below the button recess **130**.

(45) When the user presses the locking button **310**, the locking plate **320** together with the locking button **310** is moved. Here, in order to guide movement of the locking plate **320**, guide parts **140** extending downwards from the button recess **130** are provided in the seat base **100**, and the left and right sides of the locking plate **320** are inserted into the guide parts **140** and are thus moved upwards and downwards along the guide parts **140**.

(46) The guide parts **140** are formed integrally with the upper cover **121** of the frame cover **120** of the seat base **100** so as to protrude downwards.

(47) The return springs **340** are provided as compression coil springs, are provided in plural, and are installed to be inserted into the button recess **130**.

(48) The lower ends of the return springs **340** are supported by the bottom of the button recess **130**, and the upper ends of the return springs **340** are supported by the locking button **310**.

(49) Therefore, when the user presses the locking button **310** and thus the locking button **310** is moved toward the bottom of the button recess **130**, the return springs **340** are compressed, and, when the user releases operating force from the locking button **310**, the locking button **310** is moved to the top of the button recess **130** and is thus returned to the original position of the locking button **310** by the elastic force of the return springs **340**.

(50) A plurality of button flanges **311** protrudes outwards from the locking button **310**, and flange holes **150**, into which the button flanges **311** are inserted, are formed in the button recess **130**.

(51) The button flanges **311** and the flange holes **150** may be formed in the same number.

(52) When the locking button **310** is installed in the button recess **130**, the button flanges **311** are inserted into the flange holes **150**.

(53) Therefore, when the user presses the locking button **310**, the locking button **310** is moved toward the bottom of the button recess **130** and the button flanges **311** are moved downwards along the flange holes **150**, and, when the user releases operating force from the locking button **310**, the locking button **310** is moved toward the top of the button recess **130** and the button flanges **311** are moved upwards along the flange holes **150** and are thus returned to the original positions of the button flanges **311**.

(54) As such, when the locking button **310** is returned to the original position thereof using spring force of the return springs **340**, the button flanges **311** are caught by the upper ends of the flange holes **150** and are thus fixed, and thereby, the initial position of the locking button **310** is determined.

(55) That is, contact between the button flanges **311** and the flange holes **150** serves as a stopper which determines the initial position (i.e., the returned position) of the locking button **310**.

(56) On the other hand, when the user does not operate the locking button **310**, i.e., does not press the locking button **310**, the upper surface of the locking button **310** is located below the upper surface of the seat base **100** and thus the locking button **310** maintains the state of being inserted into the button recess **130**.

(57) When the locking button **310** is returned to the initial position by the spring force of the return springs **340**, i.e., when the button flanges **311** come into contact with the upper ends of the flange holes **150** and thus the locking button **310** is fixed, the upper surface of the locking button **310** is located below the upper surface of the seat base **100** and thus the locking button **310** maintains the initial state of being inserted into the button recess **130**, as shown in FIGS. **11** and **12**.

(58) In the case in which the upper surface of the locking button **310** is located above the upper surface of the seat base **100** and thus the locking button **310** protrudes upwards from the button recess **130**, there is a possibility that the locking button **310** would be pressed by a passenger sitting on the cushion assembly **200** and thereby the cushion assembly **200** would be separated from the seat base **100** due to unintentional unlocking of the locking device **300**. In order to prevent such a

case, the upper surface of the locking button **310** may be located below the upper surface of the seat base **100** in the initial state.

(59) The locking hook **330** protrudes rearwards from the rear end of the cushion assembly **200** toward the locking plate **320**.

(60) That is, the locking hook **330** is formed integrally with the cushion panel **210** of the cushion assembly **200** so as to protrude rearwards from the rear end of the cushion panel **210**, and a hook groove **331** which is concave upwards is formed in the bottom surface of the rear end of the locking hook **330**.

(61) Therefore, when the locking plate **320** is inserted into the hook groove **331** in the state in which the rear end of the locking hook **330** passes through the locking hole **321**, as shown in FIGS. **11** and **12**, the cushion assembly **200** is in the locked state by the locking device **300**, and, when the locking plate **320** is moved downwards by pressing the locking button **310** and thus the locking plate **320** is released from the hook groove **331**, as shown in FIG. **15**, the cushion assembly **200** is in the unlocked state.

(62) When the cushion assembly **200** is in the locked state, as shown in FIGS. **11** and **12**, the rear end of the cushion assembly **200** is compressed due to contact with the seat base **100**, and accumulates elastic force therein.

(63) That is, in the locked state of the cushion assembly **200** in which the cushion assembly **200** is coupled to the seat base **100** by the locking device **300**, the rear end of the cushion assembly **200** including the cushion pad **220** is compressed due to contact with the seat base **100**, and accumulates elastic force therein.

(64) Further, the cushion assembly **200** is unlocked by operating the locking device **300**, the shape of the rear end of the compressed cushion assembly **200** is restored, and the cushion assembly **200** is moved forwards to a designated distance with respect to the seat base **100** while restoring the shape of the rear end of the compressed cushion assembly **200**, as shown in FIGS. **14** and **15**, and thereby, the worker may easily separate the unlocked cushion assembly **200** from the seat base **100**.

(65) Front hooks **350** are provided on the cushion assembly **200** at positions spaced forwards apart from the locking hook **330**.

(66) The locking hook **330** protrudes from the rear end of the cushion panel **210** of the cushion assembly **200**, and a plurality of the front hooks **350** is formed integrally with designated regions of the cushion panel **210** spaced forwards apart from the locking hook **330** so as to protrude rearwards therefrom.

(67) The front hooks **350** are provided with concave recesses which are opened rearwards, and the front hooks **350** are coupled with the seat base **100**, as shown in FIG. **13**, when the cushion assembly **200** is locked by coupling the locking plate **320** to the hook groove **331** of the locking hook **330**.

(68) That is, the upper cover **121** of the seat base **100** is inserted into the concave recesses of the front hooks **350**, which are opened rearwards, and is thus assembled with the front hooks **350**, and the cushion assembly **200** may more firmly maintain coupling force to the seat base **100** by assembly of the seat base **100** with the front hooks **350**.

(69) The seat for vehicles according to the present disclosure is characterized in that the cushion assembly **200** is separably coupled to the seat base **100**, the cushion assembly **200** includes the cushion pad **220** formed of a cushioning material and the cover member **230** configured to cover the cushion pad **220**, and the cover member **230** may be replaced with a new one by separating the cushion assembly **200** from the seat base **100** and then separating the cover member **230** from the cushion pad **220**.

(70) Further, in the seat for vehicles according to the present disclosure, when the user presses the locking button **310** installed on the seat base **100**, coupling between the locking button **310** and the locking hook **330** provided on the cushion assembly **200** is released, and the cushion assembly **200** is in the state of being separable from the seat base **100** when coupling between the locking button

310 and the locking hook **330** is released.

(71) Further, in the seat for vehicles according to the present disclosure, when the locking button **310** and the locking hook **330** are coupled to each other, the seat base **100** and the cushion assembly **200** are coupled to each other and thus the cushion assembly **200** is in the locked state, and the cushion assembly **200** is placed on the seat base **100** and is assembled therewith, in the locked state of the cushion assembly **200**.

(72) As described above, the seat for vehicles according to the present disclosure has the assembly structure configured such that the cushion assembly **200** may be mounted on and separated from the seat base **100** through the locking device **300**, and thus allows the cover member **230** configured to cover the cushion assembly **200** to be easily replaced so as to prevent contamination of the cushion assembly **200** and the seat base **100** and damage thereto, such as rust generation, due to contaminants on the cover member **230**.

(73) As is apparent from the above description, a seat for vehicles according to the present disclosure has an assembly structure configured such that a cushion assembly may be mounted on and separated from a seat base through a locking device, thereby allowing a cover member configured to cover the cushion assembly to be easily replaced so as to prevent contamination of the cushion assembly and the seat base and damage thereto, such as rust generation, due to contaminants on the cover member.

(74) Although the preferred embodiments of the present disclosure have been disclosed for illustrative purposes, those skilled in the art will appreciate that various modifications, additions and substitutions are possible, without departing from the scope and spirit of the disclosure as disclosed in the accompanying claims.

Claims

1. A seat for vehicles comprising: a seat base; a cushion assembly removably coupled to the seat base; and a locking device configured to lock and unlock the cushion assembly and the seat base; wherein the locking device comprises: a locking button positioned on the seat base configured to be pressed by a user; a locking plate connected to the locking button and having a locking hole formed therethrough; and a locking hook positioned on the cushion assembly configured to be inserted into the locking hole, and configured to be separated from the locking plate when the locking button is pressed.
2. The seat for vehicles according to claim 1, wherein the seat base comprises: a plurality of seat frames configured to form a frame of the seat, the plurality of seat frames being formed of steel; and a frame cover coupled to the plurality of seat frames to cover the seat frames, the frame cover being formed of plastic.
3. The seat for vehicles according to claim 1, wherein the cushion assembly comprises: a cushion panel having a designated size; a cushion pad configured to surround the cushion panel; and a cover member configured to surround and cover the cushion pad.
4. The seat for vehicles according to claim 3, wherein the cushion panel is formed by insert injection molding, and is coupled to and surrounded by the cushion pad.
5. The seat for vehicles according to claim 1, wherein the locking device further comprises: a plurality of return springs positioned such that both ends of each of the plurality of return springs are supported by the seat base and the locking button to a supply restoring force to the locking button.
6. The seat for vehicles according to claim 5, wherein: the seat base further comprises a button recess opened upwards; and the locking button is supported by the plurality of return springs inserted into the button recess to be movable upwards and downwards.
7. The seat for vehicles according to claim 6, wherein: a plurality of button flanges protrude outwards from the locking button; the plurality of button flanges are inserted in a plurality of flange

holes formed in the button recess; and when the locking button is returned to an original position by a spring force of the plurality of return springs, the button flanges are caught by upper ends of the flange holes and are fixed, and an initial position of the locking button is determined.

8. The seat for vehicles according to claim 6, wherein, when a user does not press the locking button, an upper surface of the locking button is located below an upper surface of the seat base so the locking button remains inserted in the button recess.

9. The seat for vehicles according to claim 8, wherein: the locking plate extends downwards from the locking button; the seat bases further comprises a plurality of guide parts configured to extend downwards from the button recess; and left and right sides of the locking plate are configured to be inserted into the plurality of guide parts be movable upwards and downwards along the plurality of guide parts.

10. The seat for vehicles according to claim 1, wherein: the locking hook protrudes rearwards from a rear end of the cushion assembly toward the locking plate; a hook groove is formed in a rear end of the locking hook; and when the locking plate is inserted into the hook groove, the cushion assembly is in a locked state, and, when the locking plate is released from the hook groove, the cushion assembly is in an unlocked state.

11. The seat for vehicles according to claim 10, wherein: in the locked state of the cushion assembly, the rear end of the cushion assembly is compressed due to contact with the seat base, and accumulates an elastic force, and, in the unlocked state of the cushion assembly, a shape of the rear end of the compressed cushion assembly is restored, and the cushion assembly is moved forwards to a designated distance with respect to the seat base while restoring the shape of the rear end of the compressed cushion assembly.

12. The seat for vehicles according to claim 1, wherein: a plurality of front hooks are provided at positions of the cushion assembly spaced forwards apart from the locking hook; and when the cushion assembly is in the locked state due to coupling between the locking hook and the locking plate, the front hooks are assembled with the seat base.

13. A seat for vehicles, wherein: a cushion assembly removably coupled to a seat base; the cushion assembly comprises a cushion pad formed of a cushioning material and a cover member configured to cover the cushion pad; and the cover member is replaced by separating the cushion assembly from the seat base, and then separating the cover member from the cushion pad; wherein the locking device comprises: a locking button positioned on the seat base configured to be pressed by a user; a locking plate connected to the locking button and having a locking hole formed therethrough; and a locking hook positioned on the cushion assembly configured to be inserted into the locking hole, and configured to be separated from the locking plate when the locking button is pressed.

14. The seat for vehicles according to claim 13, wherein: when the user presses the a locking button, coupling between the locking plate connected to the locking button and the locking hook is released; and when coupling between the locking plate connected to the locking button and the locking hook is released, the cushion assembly is separable from the seat base.

15. The seat for vehicles according to claim 13, wherein, when the locking plate connected to the locking button and the locking hook are coupled to each other, the seat base and the cushion assembly are coupled to each other, and the cushion assembly is placed on the seat base.
