

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415653
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Septien Rojas; Jose Manuel et al.

Reclosable bag having a repulpable zipper

Abstract

A zipper for a reclosable bag includes a first interlocking element, and a second interlocking element. The first interlocking element and the second interlocking element are configured to cooperate to selectively open and close the zipper. One or both of the first interlocking element and the second interlocking element are formed of at least 85% repulpable material.

Inventors: Septien Rojas; Jose Manuel (Naperville, IL), Plourde; Eric (Frankfort, IL), Olechowski; Kevin (Bourbonnais, IL), Johnson; Marion (Hoffman Estates, IL), Howell; Clifton (Elburn, IL), Wihlborg; Lars (Stratford, CT), Galley; David (Manteno, IL)

Applicant: Illinois Tool Works Inc. (Glenview, IL)

Family ID: 1000008818477

Assignee: ILLINOIS TOOL WORKS INC. (Glenview, IL)

Appl. No.: 17/965581

Filed: October 13, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230128908 A1	Apr. 27, 2023

Related U.S. Application Data

us-provisional-application US 63330268 20220412
us-provisional-application US 63271928 20211026

Publication Classification

Int. Cl.: B65D33/25 (20060101); **B65D65/38** (20060101)

U.S. Cl.:

CPC **B65D33/2541** (20130101); **B65D33/2589** (20200501); **B65D65/38** (20130101);
B65D2565/386 (20130101)

Field of Classification Search

CPC: B65D (33/25); B65D (33/2508); B65D (33/2516); B65D (33/2525); B65D (33/2533);
B65D (33/2541); B65D (33/255); B65D (33/2558); B65D (33/2566); B65D (33/2575);
B65D (33/2583); B65D (33/2584); B65D (33/2585); B65D (33/2586); B65D (33/25865);
B65D (33/2587); B65D (33/2588); B65D (33/2589); B65D (33/259); B65D (33/2591)

USPC: 383/61.1; 383/63; 383/64; 383/65

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5121997	12/1991	La Pierre	383/203	B29C 48/155
5200035	12/1992	Bhat et al.	N/A	N/A
5520463	12/1995	Tilman	N/A	N/A
6063224	12/1999	Tomic	24/DIG.49	B29C 48/21
6846573	12/2004	Seydel	N/A	N/A
7067581	12/2005	Husemann et al.	N/A	N/A
7244509	12/2006	Seydel	N/A	N/A
7465265	12/2007	Hinesley	493/215	B31B 50/8125
8597733	12/2012	Vonfelden	N/A	N/A
9637866	12/2016	Tilton	N/A	N/A
10309061	12/2018	Chtourou et al.	N/A	N/A
11214427	12/2021	Collison et al.	N/A	N/A
2004/0048061	12/2003	Weissgerber et al.	N/A	N/A
2009/0123736	12/2008	Green	N/A	N/A
2010/0008603	12/2009	Smith et al.	N/A	N/A
2011/0138753	12/2010	Justice et al.	N/A	N/A
2013/0174386	12/2012	Koenigkramer	N/A	N/A
2020/0283959	12/2019	Flynn et al.	N/A	N/A
2021/0284396	12/2020	Plourde	N/A	C08L 1/286

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2013044933	12/2012	WO	N/A
2015171034	12/2014	WO	N/A
2021183629	12/2020	WO	N/A

OTHER PUBLICATIONS

“Voluntary Standard For Repulping and Recycling Corrugated Fiberboard Treated to Improve Its Performance in the Presence of Water and Water Vapor”, Revised Aug. 16, 2013, 23 pages. cited by

applicant

International Preliminary Report on Patentability mailed May 10, 2024 for corresponding International Application No. PCT/US2022/046665 (11 pages). cited by applicant
International Search Report and Written Opinion mailed Apr. 6, 2023 for corresponding International Application No. PCT/US2022/046665 (18 pages). cited by applicant

Primary Examiner: Newhouse; Nathan J

Assistant Examiner: Attel; Nina K

Attorney, Agent or Firm: The Small Patent Law Group LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to U.S. Provisional Application No. 63/271,928 (filed 26 Oct. 2021) and U.S. Provisional Application No. 63/330,268 (filed 12 Apr. 2022), the entire contents of which are incorporated herein by reference.

BACKGROUND

Technical Field

(1) The subject matter described herein relates to reclosable bags, and more particularly to zippers of reclosable bags.

Discussion of Art

(2) It is well known that there is an increasing amount of plastic waste in the world. It is further well known that plastic waste in landfills or similar environments is very slow to biodegrade.

(3) Plastic bags are used to contain various products, and typically include one or more films used to form an enclosure. While the film of a plastic bag has a thickness of only a few thousandths of an inch, the typical plastic polyethylene bag degrades very slowly, with essentially no degradation in thicker laminates.

(4) Additionally, many known plastic bags include a zipper having flanges. However, the addition of a zipper with flanges poses additional problems in relation to degradation. For example, a zipper is typically much thicker than a film, and therefore degrades much slower than the film. Bioresins (that is, resins using biomass organic materials instead of traditional petroleum feedstock) can be used to facilitate degradation. However, further improvements in relation to degradation are sought, particularly such that maintain certain desired qualities.

BRIEF DESCRIPTION

(5) A need exists for a reclosable bag having a zipper exhibiting increased repulpability, biodegradability, recyclability, and the like.

(6) With that need in mind, certain embodiments of the present disclosure provide a zipper for a reclosable bag. The zipper includes a first interlocking element, and a second interlocking element. The first interlocking element and the second interlocking element are configured to cooperate to selectively open and close the zipper. One or both of the first interlocking element and the second interlocking element are formed of a material including air cavities.

(7) In at least one embodiment, both the first interlocking element and the second interlocking element are formed of the material.

(8) In at least one embodiment, the air cavities are formed through foaming.

(9) In at least one embodiment, the material further includes filler. As an example, the filler includes cellulose.

- (10) In at least one embodiment, the zipper also includes a first flange extending from the first interlocking element, and a second flange extending from the second interlocking element. One or both of the first flange or the second flange can also be formed of the material. As a further example, the first flange and the second flange are both formed of the material.
- (11) As an example, a slider is operatively coupled to the zipper. The slider can also be formed of the material.
- (12) Certain embodiments of the present disclosure provide a method of forming a zipper for a reclosable bag. The method includes forming one or more air cavities within a material; and using the material to form one or both of a first interlocking element or a second interlocking element of the zipper, wherein the first interlocking element and the second interlocking element are configured to cooperate to selectively open and close the zipper.
- (13) In at least one embodiment, said forming includes foaming the air cavities within the material.
- (14) In at least one embodiment, said forming includes providing filler within the material.
- (15) In accordance with one example or aspect, a reclosable package is provided that includes a flexible sheet material having side walls. The side walls may be positioned to close an interior portion of the reclosable package. First and second mounting webs are coupled to upper areas of the side walls. A zipper assembly includes a first interlocking portion coupled to the first mounting web and a second interlocking portion coupled to the second mounting web. The first interlocking portion and the second interlocking portion mate with each other to close the zipper assembly and may separate from each other to open the zipper assembly. The first mounting web and the second mounting web are formed at least in part from a repulpable material.
- (16) In accordance with one example or aspect, a zipper assembly is provided that includes flanges having opposite interior and exterior surfaces. The exterior surfaces of the flanges are positioned to be coupled with one or more side walls of the enclosure. The flanges include interlocking members protruding from the flanges. The interlocking members are positioned to mate with each other and to close the enclosure and to separate from each other to open the enclosure. The flanges are formed at least in part from a repulpable material.
- (17) In accordance with one example or aspect, a method is provided that includes coupling a first mounting portion with one or more panels. The first mounting portion and the one or more panels are formed at least in part from a repulpable material. The method includes coupling a second mounting portion with one or more panels. The second mounting portion is formed at least in part of a repulpable material. A first interlocking portion of a zipper assembly is coupled to the first mounting portion. A second interlocking portion of the zipper assembly is coupled to the second mounting portion.
- (18) In accordance with one example or aspect, a method is provided that includes coupling a zipper assembly onto a mounting portion. The mounting portion is formed at least in part from a repulpable material. The zipper assembly and mounting portion are coupled to a panel of an enclosure. The zipper assembly is openable to open and close the enclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The inventive subject matter may be understood from reading the following description of non-limiting embodiments, with reference to the attached drawings, wherein below:
- (2) FIG. 1 illustrates a front view of reclosable bag, according to an embodiment of the present disclosure;
- (3) FIG. 2 illustrates a cross-sectional view of a zipper of the reclosable bag along line 2-2 of FIG. 1;
- (4) FIG. 3 illustrates a cross-sectional view of a zipper according to an embodiment of the present

disclosure;

(5) FIG. 4 illustrates a flow chart of a method of forming a zipper, according to an embodiment of the present disclosure;

(6) FIG. 5 illustrates a front view of a reclosable enclosure, according to an embodiment;

(7) FIG. 6 disclosure illustrates a cross-sectional view of one example of a reclosable assembly; and

(8) FIG. 7 illustrates a cross-sectional view of a zipper assembly of the reclosable enclosure of FIG. 1 or FIG. 5.

DETAILED DESCRIPTION

(9) Certain embodiments of the present disclosure provide a zipper for a reclosable container, such as a bag. The zipper is formed of a dissolvable material. In at least one embodiment, the zipper is formed of a dissolvable material containing air cavities, which increase solubility. In at least one embodiment, the dissolvable material also contains a filler, such as wood fiber, to limit or otherwise control the formation of the air cavities. Filler, like air cavities, also reduces an amount of polymeric binder used to form the zipper and/or the container. As an example, the filler can be formed, at least in part, of cellulose.

(10) Foaming can be used to form the air cavities. For example, foaming has been used in extruded polyethylene zippers, as disclosed in U.S. Pat. No. 5,520,463, entitled “Foamed Zipper” issued May 28, 1996, which is hereby incorporated by reference in its entirety. United States Patent Application Publication No. 2013/0174386, entitled “More Sustainable Biodegradable Foamed Zipper,” published Jul. 11, 2013, which is hereby incorporated by reference in its entirety, also discloses forming a zipper through foaming. In at least one example, the air cavities can be formed using a foaming process, such as described in U.S. Pat. No. 5,520,463, or United States Patent Application Publication No. 2013/0174386.

(11) It has been found that a zipper having air cavities formed through foaming, and also including a cellulose-based filler may aid in meeting standards and requirements as promulgated by the Flexible Box Associations.

(12) If filler is used in the zipper, a ratio of air cavities and filler content can be adjusted, as desired, to affect certain mechanical properties of the zipper. For example, increased air cavities increases flexibility, while the filler can increase stiffness.

(13) The zipper may or may not include flanges. The presence of air cavities and filler can be present in an entirety of the zipper, or in less than an entirety of the zipper. Further, a slider and/or a clip used in relation to the zipper can also be formed of the same material as the zipper.

(14) FIG. 1 illustrates a front view of reclosable bag **100**, according to an embodiment of the present disclosure. The bag **100** includes a container **101** including a front wall **102** that is coextensive with a rear wall **104**. The front wall **102** and the rear wall **104** can be joined to each other by side seals **106**, **108**, and a bottom seal **110** (or optionally a fold). Upper edges **111** define a mouth **112**, which is reclosable by a zipper **120**.

(15) In at least one embodiment, the container **101** is formed of a biodegradable material. For example, the container **101** can be formed of paper, which may or may not be coated. Alternatively, the container **101** can be formed of a polymeric material.

(16) FIG. 2 illustrates a cross-sectional view of the zipper **120** of the reclosable bag **100** along line 2-2 of FIG. 1. The zipper **120** includes a first profile **122** and a second profile **124** opposite from the first profile **122**. The first profile **122** and the second profile **124** including cooperating interlocking elements. In particular, the first profile **122** includes a first or male interlocking element **126** and a first flange **128** (such as extending from or otherwise coupled to the male interlocking element **126**), and the second profile **124** includes a second or female interlocking element **130** and a second flange **132** (such as extending from or otherwise coupled to the female interlocking element **130**). It is to be understood that the terms “first,” “second,” and the like are merely used to denote a number of items. For example, the female interlocking element **130** can be

considered the first interlocking element, and the male interlocking element **126** can be considered the second interlocking element.

(17) Referring to FIGS. **1** and **2**, the first profile **122** is sealed to the front wall **102** while second profile **124** is sealed to the rear wall **104**. In the closed or interlocked position, the male interlocking element **126** is received and engaged with the female interlocking element **130**. In the open position, the male interlocking element **126** and the female interlocking elements **130** are free of engagement with each other.

(18) In at least one embodiment, the slider **140** may also be used in relation to the zipper **120**. That is, the slider **140** can be operatively coupled to the zipper **120**. The slider **140** can be moved in an opening direction to separate the male interlocking element **126** from the female interlocking elements **130**. Conversely, the slider can be moved in a closing direction to interlock the male interlocking element **126** and the female interlocking element **130**. Optionally, the bag **100** may not include the slider **140**.

(19) FIG. **3** illustrates a cross-sectional view of the zipper **120** according to an embodiment of the present disclosure. At least a portion of the zipper **120** is formed of a material **200** having a plurality of air cavities **202**. The material **200** can also include filler **204** dispersed therethrough. A remainder or substrate **205** of the material **200** (other than the air cavities **202** and the filler **204**) can be formed of a plastic, for example.

(20) An entirety of the zipper **120** can be formed of the material **200**. For example, the male interlocking element **126**, the female interlocking element **130**, the first flange **128**, and the second flange **132** can all be formed of the material **200**. In at least one embodiment, the zipper **120** does not include one or both of the first flange **128** or the second flange **132**.

(21) As another example, less than an entirety of the zipper **120** can be formed of the material **200**. For example, only the male interlocking element **126** and/or the female interlocking element **130** can be formed of the material **200**, while the remaining portions (such as the first flange **128** and the second flange **132**) may be formed of a different material (for example, a plastic that does not include the air cavities **202** and/or the filler **204**). Forming less than entirety of the zipper **120** from the material **200** may be desired, such as if certain standards allow for a certain amount of the zipper (such as 15%) to not exceed biodegradability and/or repulpability requirements.

(22) Referring to FIGS. **1** and **3**, the slider **140** can also be formed of the material **200**. Optionally, the slider **140** may not be formed of the material **200**. As noted, the bag **100** may or may not include the slider **140**.

(23) As shown, one or more sealing areas **220** can be coupled to outer surfaces of the first flange **128** and/or the second flange **132**. Referring to FIGS. **1** and **3**, the sealing areas **220** sealingly engage interior surfaces of the container **101** proximate to the mouth **112**. The seals **220** may or may not be formed, at least in part, of the material **200**. In at least one example, instead of being formed of the material **200**, the sealing areas **220** can be formed of a sealant and/or adhesive.

(24) The material **200** is dissolvable. The air cavities **202** increase the solubility of the material **200**. In at least one example, the air cavities **202** are formed through foaming. For example, foaming agents form the air cavities **202**. The air cavities **202** reduce the overall amount and weight of the zipper **120**, while increasing surface area. The increased surface area provides increased area for compostability, for example, thereby reducing the time for such process.

(25) In at least one embodiment, the filler **204** is a cellulose-based material. For example, the filler **204** is formed, at least in part, of cellulose. As an example, the filler **204** can be wood fiber. The filler **204** limits or otherwise controls the formation of the air cavities **202**. The filler **204**, like the air cavities **202**, also reduces an amount of polymeric binder used to form the zipper **120** and/or the container **101**.

(26) The ratio of the air cavities **202** to the filler **204** within the material **200** can be 1:1. Optionally, the ratio of the air cavities **202** to the filler **204** can be 2:1, 3:1, or the like. Notably, increasing the percentage of the air cavities **202** within the material **200** increases the flexibility of the zipper **120**.

Conversely, the ratio of the air cavities **202** to the filler **204** can be 1:2, 1:3, or the like. Increasing the percentage of the filler **204** within the material **200** increases the stiffness and rigidity of the zipper **120**. As such, the amount of the air cavities **202** and the filler **204** can be adjusted depending on a desired amount of flexibility and stiffness. Alternatively, the material **200** may not include the filler **204**.

(27) It has been found that the zipper **120** having the air cavities **202** formed through foaming, and also including the filler **204**, which can be cellulose-based, may aid in meeting standards and requirements as promulgated by the Flexible Box Associations.

(28) By forming at least a portion of the zipper **120** from the material **200**, the zipper **120** is more biodegradable, repulpable, recyclable, and compostable in comparison to known zippers. The material **200** can be dissolvable.

(29) As described herein, the zipper **120** for a reclosable bag **100** includes a first interlocking element **126** or **130**, and a second interlocking element (the other of **126** or **130**). The first interlocking element and the second interlocking element are configured to cooperate to selectively open and close the zipper **120**. One or both of the first interlocking element and the second interlocking element are formed of the material **200** including air cavities **202**. The air cavities **202** can be formed through foaming. In at least one example, both the first interlocking element and the second interlocking element are formed of the material **200**. In at least one example, the material **200** also includes the filler **204**. As an example, the filler **204** includes cellulose.

(30) FIG. **4** illustrates a flow chart of a method of forming a zipper, according to an embodiment of the present disclosure. Referring to FIGS. **3** and **4**, at **300**, air cavities **202** are formed within the material **200**. At **302**, the amount of air cavities **202** within the material **200** are controlled by a filler **204** (that is, the addition of the filler **204** into the material **200**). Optionally, the amount of air cavities **202** can be independent of the filler **204**. At **304**, the material **200** is then used to form at least part of the zipper **120**.

(31) In one example, a zipper for a reclosable bag is provided. The zipper may include a first interlocking element and a second interlocking element. The first interlocking element and the second interlocking element are configured to cooperate to selectively open and close the zipper. One or both of the first interlocking element and the second interlocking element may be formed of a material including air cavities.

(32) Optionally, both the first interlocking element and the second interlocking element may be formed of the material that includes the air cavities. The air cavities may be formed through foaming. The material may also include filler, such as cellulose. The zipper also may include a first flange extending from the first interlocking element, and a second flange extending from the second interlocking element. One or both of the first flange or the second flange also may be formed of the material. A slider may be operatively coupled to the zipper. The slider also may be formed of the material.

(33) In another example, a method of forming a zipper for a reclosable bag is provided. The method may include forming one or more air cavities within a material, and using the material to form one or both of a first interlocking element or a second interlocking element of the zipper. The first interlocking element and the second interlocking element may cooperate to selectively open and close the zipper.

(34) The material may be used to form both the first interlocking element and the second interlocking element. Air cavities may be formed within the material. The forming operation may include providing filler within the material, such as cellulose.

(35) The material may be used to form one or both of the first flange or a second flange of the zipper. The material also may be used to form a slider configured to operatively couple to the zipper.

(36) In another example, a zipper for a reclosable bag is provided. The zipper may include a first interlocking element and a second interlocking element. The first interlocking element and the

second interlocking element may cooperate to selectively open and close the zipper. The first interlocking element and the second interlocking element may be formed of a material including air cavities and filler, where the air cavities are formed through foaming.

(37) The filler may include cellulose. The zipper also may include a first flange extending from the first interlocking element, and a second flange extending from the second interlocking element. The first flange and the second flange also may be formed of the material.

(38) As described herein, embodiments of the present disclosure provide a zipper for a reclosable bag exhibiting increased repulpability, biodegradability, recyclability, and the like.

(39) Certain embodiments of the present disclosure provide a reclosable enclosure having a zipper assembly, such as a bag. The zipper assembly may be formed at least in part of a repulpable material. The zipper assembly may be coupled to the reclosable container using a mounting web that is formed at least in part of a repulpable material.

(40) FIG. 5 illustrates a front view of one example of a reclosable enclosure **500**. The enclosure may include a flexible sheet material with one or more side walls **502**. The one or more side walls **502** may be arranged to close an interior portion of the enclosure **500**. A zipper assembly **504** may be coupled to the side walls **502** at or near an opening area **506** of the enclosure **500**. A first mounting web may be coupled to a first side wall and a second mounting web may be coupled to a second side wall, opposite the first side wall. The zipper assembly **504** may be coupled to the first mounting wall and the second mounting wall, allowing the zipper assembly **504** to open and close the enclosure **500**. In the embodiment illustrated in FIG. 5, the opening area **506** may be covered by a removable portion **508**. The removable portion **508** may include perforations **510** and a tear bead area that may assist a user in removing the removable portion **508**. The zipper assembly **504** may attach to itself to allow the user to repeatedly open and close the enclosure **500**. In one embodiment, the zipper assembly **504** is heat sealed directly to the side walls **502**.

(41) In at least one embodiment, the reclosable enclosure **500** is formed of a repulpable material. For example, the reclosable enclosure **500** can be formed of paper, which may or may not be coated. The repulpable material may be cellulose-based material, wood fiber, or the like.

(42) FIG. 6 illustrates a cross-sectional view of one example of a reclosable assembly **600**. The reclosable assembly **600** includes a zipper assembly **604** and a mounting web portion **614**. The zipper assembly **604** is coupled to the mounting web portion **614**. In the illustrated embodiment, the zipper assembly **604** is coupled to the mounting web portion **614** by a base portion **640**. The base portion **640** may be extrusion coated or may be an uncoated material. The zipper assembly **604** may include a first interlocking portion **630** and a second interlocking portion **632** that are positioned to cooperate to selectively open and close the zipper assembly **604**. In one embodiment, the first interlocking portion **630** is coupled to a first side wall and the second interlocking portion **632** is coupled to an opposite second side wall. The first mounting web and the second mounting web may be formed at least in part from a repulpable material. In the embodiment illustrated in FIG. 6, the reclosable assembly **600** may be covered by a removable portion **608**. The removable portion **608** may include perforations **610** and a tear bead area **612** that may assist a user in removing the removable portion **608**. The reclosable assembly **600** may be coupled to a reclosable enclosure, such as one or more of the enclosures described and/or shown herein. In the illustrated embodiment, the reclosable assembly **600** includes a strip **650** that is positioned to be coupled with the reclosable enclosure. The strip **650** may be polyethylene, an adhesive, or the like. Coupling the reclosable assembly **600** to the enclosure **500** may allow the zipper assembly **604** to attach to itself to allow the user to repeatedly open and close the enclosure **500**.

(43) In at least one embodiment, the mounting web portion **614** is formed of a repulpable material. For example, the mounting web portion **614** can be formed of paper, which may or may not be coated. The repulpable material may be cellulose-based material, wood fiber, or the like.

(44) FIG. 7 illustrates one example of a zipper assembly **700**. The zipper assembly **700** can be incorporated into the enclosures shown in FIG. 1 and/or FIG. 5. The zipper assembly **700** may

include opposing flanges **702** having outer surfaces **704** that face away from each other. These outer surfaces **704** may be coupled (e.g., via heat sealing, an adhesive, or the like) to the mounting webs (shown in FIG. 5) of the enclosure (also shown in FIG. 5). Opposite inner surfaces **706** of the flanges **702** can face each other. The inner surfaces **706** of the flanges **702** include interlocking or locking elements **712** that protrude from the inner surfaces **706** toward the other flange **702**. These locking elements **712** may mate with each other to close the zipper assembly **700** (and enclosure). The interlocking elements **712** may be pulled apart (e.g., by a consumer pulling on opposite sides of the side walls and/or the flanges **702**) to open the enclosure **500**. In the illustrated example, one flange **702** includes male interlocking elements **714** and the other flange **702** includes female interlocking elements **716**. As shown, the female interlocking elements **716** may be receptacles shaped to receive and secure outer ends of the male interlocking elements **714** (to keep the enclosure **500** closed). Pulling the flanges **702** and/or side walls apart may remove the male interlocking elements **714** from the female interlocking elements **716** to open the enclosure **500**. In one example, a slider may be used that moves along the length of the zipper assembly **700** (e.g., into and out of the plane of FIG. 7) to open or close the zipper assembly **700** and enclosure **500**. Alternatively, the zipper assembly **700** may be opened or closed without the slider.

(45) The body of the zipper assembly **700** may incorporate repulpable material. For example, the entirety of the flanges **702** may be formed from repulpable material or a combination of repulpable material and another material, such as a polymer. In one embodiment, the zipper assembly **700** may be formed at least in part from a water-soluble polymer material. In one embodiment, the zipper assembly **700** may be formed at least in part from a polyethylene material, polyvinyl alcohol (PVOH), or the like.

(46) In the closed or interlocked position, the male interlocking element **714** is received and engaged with the female interlocking element **716**. In the open position, the male interlocking element **714** and the female interlocking elements **716** are free of engagement with each other.

(47) In at least one embodiment, a slider may also be used in relation to the zipper assembly. That is, the slider can be operatively coupled to the zipper assembly. The slider can be moved in an opening direction to separate the male interlocking element from the female interlocking element. Conversely, the slider can be moved in a closing direction to interlock the male locking element and the female interlocking element. Optionally, the reclosable enclosure may not include the slider.

(48) As described herein, embodiments of the present disclosure provide a zipper assembly for a reclosable enclosure exhibiting increased repulpability, biodegradability, recyclability, and the like.

(49) In one embodiment, a method is described for manufacturing reclosable enclosures and zipper assemblies of reclosable enclosures. The method may be used in the manufacturing of the reclosable enclosure **100** shown in FIG. 1. It should be noted that the particular arrangement of components (e.g., the number, types, placement, or the like) described may be modified in various alternate embodiments. The method includes coupling a first mounting portion and a second mounting portion with one or more panels forming a reclosable enclosure. The first and second mounting portions and the panels may be formed at least in part from a repulpable material. The mounting portions may include a sealant layer. A first interlocking portion and a second interlocking portion of a zipper assembly are then coupled to the first and second mounting portions, respectively. In one embodiment, the interlocking portions are extruded directly onto the mounting portions. In one embodiment, the zipper assembly may be heat sealed to the mounting portion.

(50) In another embodiment, a method is described for manufacturing reclosable enclosures and zipper assemblies of reclosable enclosures that includes coupling a zipper assembly onto a mounting portion. The mounting portion may be formed at least in part from a repulpable material. The zipper assembly and mounting portion may be coupled to a panel of an enclosure. The zipper assembly is arranged to open and close an interior of the enclosure.

(51) The amount of repulpable material that is incorporated into one or more components of the enclosures described herein may be at least a threshold amount. For example, there may be at least 85% (but less than 100%) of repulpable material in the panels, zipper assemblies, flanges, interlocking elements, flanges, tear bands, mounting webs, sheets, etc. by weight and/or by volume (with the remainder being material that is not repulpable). Alternatively, there may be at least 80%, at least 70%, or the like (but less than 100%) of repulpable material in the panels, zipper assemblies, flanges, interlocking elements, flanges, tear bands, mounting webs, sheets, etc. by weight and/or by volume (with the remainder being material that is not repulpable). The amount of repulpable material may be expressed or measured as a fiber yield on weight per the Fibre Box Association repulpability test dated 16 Aug. 2013, the contents of which are incorporated herein by reference without limiting the scope of any embodiment described herein (unless currently or subsequently expressly limited by the applicant).

(52) The singular forms “a”, “an”, and “the” include plural references unless the context clearly dictates otherwise. “Optional” or “optionally” means that the subsequently described event or circumstance may or may not occur, and that the description may include instances where the event occurs and instances where it does not. Approximating language, as used herein throughout the specification and claims, may be applied to modify any quantitative representation that could permissibly vary without resulting in a change in the basic function to which it may be related. Accordingly, a value modified by a term or terms, such as “about,” “substantially,” and “approximately,” may be not to be limited to the precise value specified. In at least some instances, the approximating language may correspond to the precision of an instrument for measuring the value. Here and throughout the specification and claims, range limitations may be combined and/or interchanged, such ranges may be identified and include all the sub-ranges contained therein unless context or language indicates otherwise.

(53) This written description uses examples to disclose the embodiments, including the best mode, and to enable a person of ordinary skill in the art to practice the embodiments, including making and using any devices or systems and performing any incorporated methods. The claims define the patentable scope of the disclosure, and include other examples that occur to those of ordinary skill in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal language of the claims.

Claims

1. A reclosable bag comprising: walls forming an enclosure; a mounting web coupled with the walls, the mounting web formed from a first material; a base portion coupled with the mounting web, the base portion formed from a second material; and interlocking elements coupled with the base portion, the interlocking elements configured to engage each other to hold the enclosure closed and release from each other to open the enclosure, the interlocking elements formed from a third material, wherein at least one of the first material, the second material, and the third material is formed from at least 85% of a repulpable material, and wherein two of the first material, the second material, and the third material are different materials.
2. The reclosable bag of claim 1, wherein the third material that forms the interlocking elements includes the at least 85% of the repulpable material and includes air cavities.
3. The reclosable bag of claim 2, wherein the third material that forms the interlocking elements also includes cellulose filler.
4. The reclosable bag of claim 1, further comprising: a slider formed from cellulose filler and air cavities.
5. The reclosable bag of claim 1, wherein the mounting web includes a sealant layer that adheres the mounting web to the walls.

6. The reclosable bag of claim 1, wherein the interlocking elements are heat sealed to the base portion.
 7. The reclosable bag of claim 1, wherein the interlocking elements are extruded directly onto the base portion before the mounting web is coupled to an upper area of the walls.
 8. The reclosable bag of claim 1, further comprising: polyethylene or adhesive strips coupling the mounting web to the walls.
 9. A method comprising: obtaining walls configured to form an enclosure; coupling a mounting web formed from a first material to the walls; coupling a base portion with the mounting web, the base portion formed from a second material; and coupling interlocking elements with the base portion, the interlocking elements engaging each other to hold the enclosure closed and releasing from each other to open the enclosure, the interlocking elements formed from a third material, wherein at least one of the first material, the second material, and the third material is formed from at least 85% of a repulpable material, and wherein two of the first material, the second material, and the third material are different materials.
 10. The method of claim 9, wherein the third material that forms the interlocking elements includes the at least 85% of the repulpable material and includes air cavities.
 11. The method of claim 10, wherein the third material that forms the interlocking elements also includes cellulose filler.
 12. The method of claim 9, further comprising: forming a slider from cellulose filler and air cavities, the slider configured to slide along the interlocking elements to engage the interlocking elements with each other and to release the interlocking elements from each other.
 13. The method of claim 9, further comprising applying a sealant layer between the mounting web and the walls.
 14. The method of claim 9, further comprising heat sealing the interlocking elements to the base portion.
 15. The method of claim 9, wherein the interlocking elements are formed by directly extruding the interlocking elements onto the base portion before the mounting web is coupled to an upper area of the walls.
 16. The method of claim 9, wherein coupling the mounting web to the walls includes coupling the mounting web to the walls with polyethylene or adhesive strips.
 17. A reclosable bag comprising: walls forming an enclosure; a mounting web at least partially formed from a repulpable material and coupled with the walls; a base portion coupled with the mounting web, the base portion formed from a material other than the repulpable material; and interlocking elements coupled with the base portion, the interlocking elements configured to engage each other to hold the enclosure closed and to release from each other to open the enclosure, wherein the interlocking elements are formed from at least 85% of the repulpable material.
 18. The reclosable bag of claim 17, further comprising: polyethylene or adhesive strips coupling the mounting web to the walls.
-