

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417891
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Choi; Hong Soo et al.

Emitter, field emission assembly and electromagnetic wave generator including the same

Abstract

An emitter, a field emission assembly, and an electromagnetic wave generator are provided, and the emitter is an emitter for emitting electrons in an electromagnetic wave generator and is in the form of a sheet in which a plurality of yarns including carbon nanotube (CNT) fibers are weaved.

Inventors: Choi; Hong Soo (Seoul, KR), Kim; Young Bae (Anyang-si, KR), Cho; Hyeongu (Yongin-si, KR), Lee; Namkyu (Hwaseong-si, KR), Jeong; Keunsoo (Seoul, KR), Gihm; Se Hoon (Seongnam-si, KR), Choi; Jiwon (Ansan-si, KR)

Applicant: AweXome Ray, Inc. (Anyang-si, KR)

Family ID: 1000008818509

Assignee: LG Display Co., Ltd. (Seoul, KR)

Appl. No.: 18/070197

Filed: November 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240136142 A1	Apr. 25, 2024
US 20240234074 A9	Jul. 11, 2024

Foreign Application Priority Data

KR	10-2022-0136580	Oct. 21, 2022
----	-----------------	---------------

Publication Classification

Int. Cl.: **H01J9/02** (20060101); **H01J1/304** (20060101); **H01J35/06** (20060101); **H01J35/08** (20060101); **H01J35/14** (20060101)

U.S. Cl.:

CPC **H01J35/065** (20130101); **H01J1/304** (20130101); **H01J35/08** (20130101); **H01J35/14** (20130101); H01J2201/30469 (20130101); H01J2235/06 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7741232	12/2009	Yokoh et al.	N/A	N/A
8395309	12/2012	Wei et al.	N/A	N/A
8588372	12/2012	Zou	378/138	H01J 35/065
10643816	12/2019	Choi et al.	N/A	N/A
11373833	12/2021	Hoff et al.	N/A	N/A
11600462	12/2022	Gihm et al.	N/A	N/A
2004/0053780	12/2003	Jiang et al.	N/A	N/A
2007/0117488	12/2006	Yokoh et al.	N/A	N/A
2008/0143906	12/2007	Allemand et al.	N/A	N/A
2008/0170982	12/2007	Zhang et al.	N/A	N/A
2010/0181896	12/2009	Lee et al.	N/A	N/A
2011/0181170	12/2010	Gamo et al.	N/A	N/A
2012/0085970	12/2011	Zhang et al.	N/A	N/A
2012/0133266	12/2011	Wei et al.	N/A	N/A
2015/0380199	12/2014	Liu	313/311	H01J 23/04
2018/0194950	12/2017	Antoinette	N/A	C08K 5/0066
2019/0287753	12/2018	Weber	N/A	N/A
2022/0392730	12/2021	Gihm et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2004-107196	12/2003	JP	N/A
2004-149996	12/2003	JP	N/A
2006-107932	12/2005	JP	N/A
2008-523254	12/2007	JP	N/A
2012119296	12/2011	JP	N/A
7020627	12/2021	JP	N/A
20110060236	12/2010	KR	N/A
10-1384100	12/2013	KR	N/A
10-1387700	12/2013	KR	N/A
202029256	12/2019	TW	N/A
202038280	12/2019	TW	N/A
WO 2005001180	12/2004	WO	N/A
WO 2012074319	12/2011	WO	N/A

Primary Examiner: Song; Hoon K

Attorney, Agent or Firm: Seed Intellectual Property Law Group LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims the benefit of Korean Patent Application No. 10-2022-0136580, filed on Oct. 21, 2022, in the Korean Intellectual Property Office, the disclosure of which is incorporated

herein by reference.

BACKGROUND

Technical Field

(2) The present disclosure relates to an emitter, a field emission assembly, and an electromagnetic wave generator including the same, and more particularly, to a field emission assembly capable of uniformizing a field emission characteristic through a structure of an emitter, and an electromagnetic wave generator including the same.

Description of the Related Art

(3) Recently, with the development of a carbon nanotube (CNT)-related technology, a technology in which a cathode of the existing X-ray tube which emits hot electrons using the existing filament is replaced with a cold cathode using CNTs, which is capable of emitting electrons due to an electric field, is being developed.

(4) Generally, a carbon nanotube-based X-ray tube includes a cathode including CNTs, a gate for inducing electron emission, a focusing part for improving electron focusing performance, and an anode for generating electromagnetic waves (specifically, X-rays) due to collision of the emitted electrons.

(5) In X-rays, an amount of emitted electrons, a collision speed, and a focal point size are determined according to a voltage, a geometric shape, and a position of each part, and these are factors which determine resolution and quality of a radiographic image. In particular, in the case of an emitter which is an emission source of electrons based on CNTs, uniformity and performance of field emission may depend on a shape or a bonding structure of the emitter.

(6) The emitter may be formed into a variety of structures depending on the use of the electromagnetic wave generator in which the emitter is included. For example, electromagnetic wave generators used for breast cancer detection may require large amounts of X-rays, whereas in other specific cases, a less intense X-ray emission may be required. This is because, when the intensity of X-rays is increased, the X-rays pass through even a target to be detected and thus the target may not be detected.

(7) In one example, many electrons are emitted from an emitter, and the emitter may be required that the electrons are uniformly emitted in a wide area rather than being concentrated and emitted at any one point of the emitter. In an electromagnetic wave generator in the related art, in order to derive such an electron emission pattern, an emitter in the form of a sheet is used sometimes.

BRIEF SUMMARY

(8) Among emitters in the form of a sheet in the related art, there are an anisotropic two-dimensional (2D) sheet emitter in which carbon nanotubes (CNTs) are formed to be disposed with directionality, and a non-woven 2D sheet emitter in which CNTs are formed to be entangled without directionality.

(9) However, in the former case, a field emission characteristic is varied according to an installation direction of the emitter, and in the latter case, electron emission points are non-uniformly formed within the sheet so that the sheet emitters in the related art have limitation in which uniformity of the field emission characteristics of the emitters is degraded.

(10) In addition, as the uniformity of field emission is degraded, there is a limitation in precisely controlling a generation amount or intensity of electromagnetic waves.

(11) In addition, the former emitter is easily torn in a direction perpendicular to the arrangement direction, and the latter emitter has the same property as a non-woven fabric to be easily torn in a specific direction so that there is a problem durability of the emitters is sharply degraded, and thus a lifetime of each emitter is varied.

(12) One or more embodiments of the present disclosure addresses the various technical problems in the related art including the problems identified above.

(13) An aspect of the present disclosure is to provide an emitter capable of improving uniformity of a field emission characteristic, a field emission assembly and a lifetime of an electromagnetic wave

generator, and an electromagnetic wave generator including the same.

(14) Another aspect also provides an emitter capable of more precisely controlling a generation amount or intensity of electromagnetic waves, a field emission assembly, and an electromagnetic wave generator including the same.

(15) Still another aspect also provides an emitter with improved durability and a consistent lifetime, a field emission assembly, and an electromagnetic wave generator including the same.

(16) According to an aspect, there is provided an emitter for emitting electrons in an electromagnetic wave generator. The emitter may be in the form of a sheet in which a plurality of yarns including carbon nanotube (CNT) fibers are weaved.

(17) In this way, it is possible to improve uniformity of a field emission characteristic in the emitter.

(18) In addition, due to the uniformity of the field emission, controlling of a generation amount or an intensity of electromagnetic waves may be more precisely performed.

(19) In addition, durability of the emitter may be improved, and thus the emitter, a field emission assembly, and an electromagnetic wave generator including the same may each have a consistent lifetime.

(20) In addition, the plurality of yarns may be braided yarns.

(21) In addition, the braided yarn may be formed by braiding a plurality of the primary twisted yarns, and the primary twisted yarn may be formed by twisting a plurality of CNT fibers.

(22) In addition, the braided yarn may be formed by braiding a plurality of secondary twisted yarns, the secondary twisted yarn may be formed by twisting a plurality of primary twisted yarns, and the primary twisted yarn may be formed by twisting a plurality of CNT fibers.

(23) In addition, each of the plurality of yarns may be a twisted yarn.

(24) In addition, the twisted yarn may be the primary twisted yarn formed by twisting a plurality of CNT fibers.

(25) In addition, the twisted yarn may be the secondary twisted yarn formed by twisting primary twisted yarns with each other, and the primary twisted yarn may be formed by twisting a plurality of CNT fibers.

(26) According to another aspect, there is provided a field emission assembly including an emitter configured to emit electrons, and a holder configured to fix the emitter. The emitter may be in the form of a sheet in which a plurality of yarns including carbon nanotube (CNT) fibers are weaved.

(27) In addition, the emitter may include an electron emission portion which is a region spread on a plane perpendicular to an electron emission direction.

(28) In addition, the holder may include a seating part on which the emitter is seated and fixing parts disposed on both sides of the seating part, the emitter may include the electron emission portion which is a region spread on a plane perpendicular to the electron emission direction and side portions formed on both sides of the electron emission portion, the electron emission portion may be seated on a front surface of the seating part in the electron emission direction, and the side portions may be disposed in gaps formed between the seating part and the fixing parts while surrounding the seating part.

(29) In addition, the front surface of the seating part in the electron emission direction may be perpendicular to the electron emission direction.

(30) In addition, the field emission assembly may further include coupling members configured to pass through the fixing parts in a lateral direction, and the emitter may be fixed to the holder by pressurizing the side portions by the coupling members and side surfaces of the seating part.

(31) According to still another aspect, there is provided an electromagnetic wave generator including a field emission assembly including an emitter configured to emit electrons and a holder configured to fix the emitter, and an anode in which electrons emitted from the field emission assembly collide to generate electromagnetic waves. The emitter may be in the form of a sheet in which a plurality of yarns including carbon nanotube (CNT) fibers are weaved.

- (32) In addition, the emitter may include an electron emission portion extending on a plane perpendicular to a direction toward the anode.
- (33) In addition, the electromagnetic wave may have a wavelength ranging from 0.001 nm to 10 nm.
- (34) Additional aspects of example embodiments will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the disclosure.
-

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

- (1) These and/or other aspects, features, and advantages of the disclosure will become apparent and more readily appreciated from the following description of example embodiments, taken in conjunction with the accompanying drawings of which:
- (2) FIG. 1 is a conceptual diagram illustrating an electromagnetic wave generator including a field emission assembly according to one example embodiment of the present disclosure;
- (3) FIG. 2 is an exploded perspective view illustrating the field emission assembly according to one example embodiment of the present disclosure;
- (4) FIG. 3 is a cross-sectional view illustrating the field emission assembly according to one example embodiment of the present disclosure;
- (5) FIGS. 4 and 5 are enlarged views illustrating portion S of FIG. 2;
- (6) FIGS. 6A and 6B shows photographs capturing a linear emitter of the field emission assembly according to one example embodiment of the present disclosure;
- (7) FIGS. 7A to 7D is a diagram illustrating a formation process of an emitter of the field emission assembly according to one example embodiment of the present disclosure;
- (8) FIGS. 8A to 8D is a diagram illustrating a mechanical property according to a type of a yarn constituting the emitter;
- (9) FIG. 9 is a graph illustrating electrical properties when an emitter is formed of a twisted yarn and when the emitter is formed of a braided yarn; and
- (10) FIG. 10 is a graph illustrating linear densities when an emitter is formed of a twisted yarn and when the emitter is formed of a braided yarn.

DETAILED DESCRIPTION

- (11) The terms used in the example embodiments are selected, as much as possible, from general terms that are widely used at present while taking into consideration the functions obtained in accordance with the present disclosure, but these terms may be replaced by other terms based on intentions of those skilled in the art, customs, emergence of new technologies, or the like. Also, in a particular case, terms that are arbitrarily selected by the applicant of the present disclosure may be used. In this case, the meanings of these terms may be described in corresponding description parts of the disclosure. Accordingly, it should be noted that the terms used herein should be construed based on practical meanings thereof and the whole content of this specification, rather than being simply construed based on names of the terms.
- (12) As used herein, suffixes “module” and “portion” for a component of the present disclosure are used or interchangeably used solely for ease of preparation of the specification, and do not have different meanings and each of them does not function by itself. Further, regarding the description of the example embodiments of the present disclosure, the detailed description of the related known technologies may be omitted when such description is determined to possibly confuse the essence of the example embodiments included in the present disclosure. Further, the accompanying drawings are merely to make it easier to understand the example embodiments included in the present disclosure and the technical idea of the present disclosure is not limited thereto, and they

should be construed to include all of modification, equivalence and replacement involved in the idea and the technical scope of the present disclosure.

(13) The terms including ordinal numbers such as “first” and “second” may be used to describe different constituent elements, which are not limited thereto. The terms are used only for the purpose of distinguishing one component from another component.

(14) When a component is referred to as being “connected” or “coupled” to another component, the component may be directly connected or coupled to another component, but it should be understood that still another component may be present between the component and another component. On the contrary, when a component is referred to as being “directly connected” or “directly coupled” to another, it should be understood that still another component may not be present between the component and another component.

(15) Unless the context clearly dictates otherwise, the singular form includes the plural form.

(16) As used herein, the term “comprising” or “having” is intended to indicate that there may be the features, numbers, steps, operations, components, parts or a combination thereof, disclosed in this disclosure, but should not be understood as excluding the case that there is one or more of other features, numbers, steps, operations, components, parts or a combination thereof, or the possibility of adding the same.

(17) The expression “at least one of A, B, and C” may include the following meanings: A alone; B alone; C alone; both A and B together; both A and C together; both B and C together; and all three of A, B, and C together.

(18) Example embodiments of the present disclosure will be fully described in a detail below which is suitable for implementation by those skilled in the art with reference to the accompanying drawings. However, the present disclosure may be implemented in various different forms, and thus it is not limited to example embodiments to be described herein.

(19) Hereinafter, example embodiments of the present disclosure will be described in detail with reference to the accompanying drawings.

(20) FIG. 1 is a conceptual diagram illustrating an electromagnetic wave generator including a field emission assembly according to one example embodiment of the present disclosure.

(21) An electromagnetic wave generator **100** according to a first example embodiment of the present disclosure may include a housing **110**, a field emission assembly **120**, a gate electrode **130**, a focusing part **140**, and an anode **150**. However, some of these components may be omitted and implemented, and additional components are not excluded.

(22) Hereinafter, an electron emission direction **x** may be understood as a direction from the field emission assembly **120** toward the anode **150**, that is, an upward direction based on FIGS. 1 to 3.

(23) Referring to FIG. 1, the electromagnetic wave generator **100** may include the housing **110**. The housing **110** may accommodate components such as the field emission assembly **120**, the gate electrode **130**, and the anode **150**. An interior of the housing **110** may be maintained in a vacuum state or may be maintained close to a vacuum state.

(24) An irradiation part **111** may be provided in the housing **110**. Electromagnetic waves generated from the anode **150** may be emitted to the outside of the housing **110** through the irradiation part **111**. However, alternatively, the housing **110** may be entirely formed of a transparent material such as glass so that electromagnetic waves generated from the anode **150** may pass therethrough. In this case, a separate irradiation part **111** may not be provided. In addition, when an intensity of the generated electromagnetic waves is strong, since the electromagnetic waves may pass through the opaque material, the housing **110** may be formed of an opaque material without providing the irradiation part **111**.

(25) The electromagnetic wave generator **100** may include the field emission assembly **120**. The field emission assembly **120** may be a portion from which electrons are emitted due to an electric field. The field emission assembly **120** may serve as a cathode to which a positive voltage is applied.

(26) The field emission assembly **120** may include an emitter **121** for emitting electrons, and a holder **122** for fixing the emitter **121**. A detailed structure of the field emission assembly **120** will be described in detail below with reference to FIGS. **2** to **5**.

(27) The field emission assembly **120** of the electromagnetic wave generator **100** according to one example embodiment of the present disclosure may be a cold cathode. Specifically, in the electromagnetic wave generator **100** according to one example embodiment of the present disclosure, electrons included in the emitter **121** may be emitted by a voltage applied between the field emission assembly **120** and the gate electrode **130** without separately applying heat to the emitter **121**.

(28) The electromagnetic wave generator **100** may include the gate electrode **130**. The gate electrode **130** may be disposed between the emitter **121** and the anode **150**. More specifically, the gate electrode **130** may be disposed in a region between the emitter **121** and the anode **150** to be closer to the emitter **121**.

(29) The gate electrode **130** may induce electron emission from the emitter **121**. Electrons included in the emitter **121** may be emitted due to a voltage applied between the gate electrode **130** and the emitter **121**. In some embodiments, the gate electrode **130** may preferentially serve to withdraw electrons from the emitter **121**.

(30) However, the present disclosure is not limited thereto, and the electromagnetic wave generator **100** may not include the gate electrode **130**. In this case, electrons included in the emitter **121** may be emitted due to a voltage applied between the focusing part **140**, which will be described below, or the anode **150** and the field emission assembly **120**.

(31) The electromagnetic wave generator **100** may include the focusing part **140**. The focusing part **140** may be disposed between the gate electrode **130** and the anode **150** or between the field emission assembly **120** and the anode **150**.

(32) As a voltage is applied, the focusing part **140** may focus an electron beam passing through the gate electrode **130**. The focusing part **140** may be referred to as a lens. In addition, the focusing part **140** may further accelerate the electron beam passing through the gate electrode **130**. Specifically, when a voltage is applied between the focusing part **140** and the gate electrode **130**, the electrons passing through the gate electrode **130** may be accelerated due to an electric field formed by the voltage applied between the focusing part **140** and the gate electrode **130**. As described above, the type of the electromagnetic wave generator **100** provided with the focusing part **140** may be understood as a triode type generator.

(33) However, the present disclosure is not limited thereto, and when the focusing performance of the gate electrode **130** itself is good or excellent, the focusing part **140** may not be provided. As described above, the type of the electromagnetic wave generator **100** not provided with the focusing part **140** may be understood as a diode type generator.

(34) The electromagnetic wave generator **100** may include the anode **150**. The anode **150** may be disposed at a side opposite to the field emission assembly **120**. The anode **150** may be disposed behind the gate electrode **130** and/or the focusing part **140** in a propagation direction of the electron beam. The anode **150** is a portion to which a higher voltage is applied when compared to the cathode including the gate electrode **130** and/or the field emission assembly **120** and may be referred to as an anode or referred to as a target in the sense that an electron beam collides.

(35) Electromagnetic waves may be formed in the anode **150**. Specifically, after the electron beam emitted from the emitter **121** is accelerated while passing through the gate electrode **130** and/or the focusing part **140**, the electron beam may collide with the anode **150**, and in this case, the electron beam may generate electromagnetic waves such that a material constituting the anode **150** is excited by the electron beam and then returned to its original state.

(36) The electromagnetic wave emitted from the electromagnetic wave generator **100** may have a wavelength ranging from 0.001 nm to 10 nm. For example, the electromagnetic wave generator **100** may emit X-ray having a wavelength ranging from 0.001 nm to 10 nm. More specifically, the

electromagnetic wave generator **100** may emit X-ray having a wavelength ranging from 0.01 nm to 10 nm.

(37) FIG. 2 is an exploded perspective view illustrating the field emission assembly according to one example embodiment of the present disclosure. FIG. 3 is a cross-sectional view illustrating the field emission assembly according to one example embodiment of the present disclosure. FIGS. 4 and 5 are enlarged views illustrating portion S of FIG. 2.

(38) The field emission assembly **120** according to one embodiment of the present disclosure may include the emitter **121** and the holder **122**, but may be implemented except for some of them, and does not exclude additional components.

(39) Referring to FIGS. 2 and 5, the field emission assembly **120** may include the emitter **121**. The emitter **121** may be fixed to the holder **122**. The emitter **121** may be electrically conducted by coming into contact with the holder **122**. When an electric field is applied to the electromagnetic wave generator **100**, electrons may move to the emitter **121** through the holder **122** and then may be emitted from the emitter **121**. The emitter **121** may include CNT fibers through which electrons may easily move. However, the present disclosure is not limited thereto, and the emitter **121** may be formed of various materials capable of emitting electrons.

(40) The emitter **121** may be in the form of a sheet. Since the emitter **121** is formed in the form of a sheet, a plurality of electron emission points P may be formed so that a large amount of electromagnetic waves may be generated. In addition, since the emitter **121** is formed in the form of a sheet, the electron emission points P may be widely distributed so that electrons may not be concentrated and emitted at any one point of the emitter **121** and may be evenly emitted in a wide area. In this way, electromagnetic waves having weak intensities may be generated. In summary, a large amount of electromagnetic waves having weak intensities may be generated through the emitter **121** in the form of a sheet. The emitter **121** in the form of a sheet may be used in a specific field, such as breast cancer detection, requiring a large amount of electromagnetic waves having weak intensities.

(41) Referring to FIG. 5, the emitter **121** may include a plurality of yarns **121a**. Specifically, the emitter **121** may be formed of a plurality of yarns **121a** including CNT fibers. The yarn **121a** may be a linear material formed by gathering CNT fibers. A formation method of the yarn **121a** will be described in detail with reference to FIGS. 6A, 6B and 7A to 7D.

(42) Referring to FIGS. 4 and 5, the emitter **121** may be formed by weaving a plurality of yarns **121a**. Specifically, the emitter **121** may be in the form of a sheet in which a plurality of yarns **121a**, which are linearly formed, are weaved to each other. In this way, uniformity of electrical and mechanical properties of the emitter **121** may be improved, and further, the electrical and mechanical properties may be strengthened.

(43) Specifically, when the plurality of yarns **121a** are weaved, the emitter **121** in the form of a sheet may have a constant texture, and thus electron emission points P may be uniformly distributed on the sheet so that uniformity of the field emission characteristics may be improved.

(44) In addition, the electron emission point P may be formed in a portion where the linear yarns **121a** intersect with each other. Since the plurality of yarns **121a** are provided in the form of a regularly weaved sheet, it is possible to remove an element overlapping the electron emission point P to hinder electron emission in the electron emission direction x. That is, since the plurality of yarns **121a** are regularly weaved, all the electron emission points P, which are portions where the linear yarns **121a** intersect with each other, may be exposed to a front side in the electron emission direction x. In this way, the electron emission may be performed more smoothly so that the field emission characteristic may be enhanced.

(45) In addition, when the plurality of yarns **121a** are weaved, structural unity may be secured between the manufactured emitters **121** so that uniformity of mechanical properties of the emitters **121** may be improved. In this way, consistency in the lifetimes of the field emission assembly **120** and the electromagnetic wave generator **100** may be secured. In addition, when manufacturing the

field emission assembly **120**, since errors due to differences in the mechanical properties may be reduced, the uniformity of the field emission characteristics may also be improved.

(46) In addition, when the plurality of yarns **121a** are weaved, a structure of the emitter **121** may be strengthened so that the durability of the emitter **121**, the field emission assembly **120**, and the electromagnetic wave generator **100** may be improved.

(47) The emitter **121** may be weaved in a variety of ways. For example, the emitter **121** may be weaved in various methods, such as plain weaving, twill weaving, and satin weaving. That is, the emitter **121** may be formed without being limited to any specific weaving method as long as a regular texture may be formed. The emitter **121** formed by weaving may have the form of a thin and wide sheet, and rigidity thereof may slightly varied according to the weaving method.

(48) Weaving may mean that a tissue structure of the plurality of yarns **121a** itself may have the form of a sheet without the addition of an additional material or physical/chemical processing. However, through the addition of an additional material or physical/chemical processing, as necessary, the sheet structure may be further strengthened.

(49) Due to the feature of weaving formation, the emitter **121** may include a point or region disposed relatively forward based on the electron emission direction x and a point or region disposed backward based on the electron emission direction x . The point or region disposed relatively forward may include a peak, and the point or region disposed relatively backward may include a valley. The peak and the valley may be formed at portions where the yarns **121a** intersect with each other. An electron emission point P may be formed at a portion where the yarns **121a** intersect with each other, and the electron emission point P may be understood to correspond to the peak. The portions where the peak and the valley are formed may be formed to be thicker than other portions so that many electrons may be concentrated, and electron emission may be facilitated through a shape of the peak. The plurality of yarns **121a** are weaved in a regular texture, and thus a plurality of peaks and valleys have a regular distribution so that uniformity of the field emission characteristics may be improved.

(50) Referring to FIGS. **2** and **3**, the emitter **121** may include an electron emission portion **1211**. The electron emission portion **1211** may refer to a direct region emitting electrons in a width direction of the emitter **121** and may be a central region of the emitter **121** in a state of being mainly spread out in a plane. The electron emission portion **1211** is not defined only with the emitter **121** and may be specified in a state of being coupled to the holder **122**. The electron emission portion **1211** may be disposed on a front surface of a seating part **1221** of the holder **122** the electron emission direction x . When the emitter **121** is fixed to the holder **122**, the electron emission portion **1211** may be exposed to the outside of the holder **122**. When an electric field is applied to the electron emission portion **1211**, electrons may be emitted from the electron emission portion **1211**.

(51) The electron emission portion **1211** may be a region spread out on a plane in the emitter **121** perpendicular to the electron emission direction x . That is, based on FIG. **1**, the electron emission portion **1211** may be a portion spread out on a plane of the emitter **121** perpendicular to a direction toward the anode **150** shown in FIG. **1**. The electron emission portion **1211** may be a portion disposed on the front surface of the seating part **1221** the electron emission direction x , which is formed on a plane perpendicular to the electron emission direction x . When an electric field is applied to an interior of the electromagnetic wave generator **100**, a potential may be formed on the electron emission portion **1211** of the emitter **121**. In this case, when the electron emission portion **1211** is formed on a plane perpendicular to the electron emission direction x , potentials applied to the electron emission points P formed in the electron emission portion **1211** may be the same, and accordingly, it is possible to prevent the electrons from being emitted by being focused on any one portion of the emitter **121**.

(52) The emitter **121** may include side portions **1212**. The side portions **1212** may be formed on both sides of the electron emission portion **1211**. The side portions **1212** may be portions extending

from the both sides of the electron emission portion **1211**. When the emitter **121** is fixed to the holder **122**, the side portions **1212** may be portions not exposed to the outside. The emitter **121** may be fixed to the holder **122** by the side portions **1212**.

(53) The side portions **1212** may be disposed in gaps formed between the seating part **1221** and fixing parts **1222** while surrounding the seating part **1221** of the holder **122**. When the emitter **121** is fixed to the holder **122**, the side portions **1212** may be understood as portions extending in a direction opposite to the electron emission direction x from edges of the both sides of the electron emission portion **1211**. The side portions **1212** may extend to at least a region laterally overlapping coupling holes **1223** formed in the fixing parts **1222**. The emitter **121** may be fixed to the holder **122** by being pressurized by side surfaces of the seating part **1221** and coupling members **123** to which the side portions **1212** pass through the coupling holes **1223** to be coupled.

(54) Referring to FIG. 5, an electron emission point P may be formed in the emitter **121**. The electron emission point P may be a portion where linear yarns **121a** intersect with each other in the emitter **121** in which a plurality of yarns **121a** are weaved. Specifically, a portion where the yarns **121a** intersect may be formed to be thicker than a portion where the yarns **121a** do not intersect, and accordingly, when an electric field is applied to the emitter **121**, electrons may be easily concentrated in the portion where the yarns **121a** intersect. In addition, a peak may be formed in the portion where the yarns **121a** intersect with each other, and electron emission may be facilitated through a shape of the peak. In this way, electrons may be easily concentrated in the portion where the yarns **121a** intersect and be easily emitted so that the portion where the yarns **121a** intersect may become the electron emission point P . A peak of one of the two intersecting yarns **121** may be formed due to a relative arrangement with a valley of the other yarn **121** disposed backward in the electron emission direction x .

(55) Since the emitter **121** is formed by weaving a plurality of yarns **121a**, the electron emission points P may be formed at a constant density. Through the above structure, electrons may be uniformly formed in the entire region of the electron emission portion **1211** so that the uniformity of the field emission characteristics may be improved.

(56) Referring to FIGS. 2 and 3, the field emission assembly **120** may include the holder **122**. The holder **122** may fix the emitter **121**.

(57) The holder **122** may be formed of an electrically conductive material capable of conducting electricity. Specifically, the holder **122** may be made of a material having electrical conductivity and mechanical strength that is not deformed by repulsive forces of electrons accumulated in the field emission assembly **120**. For example, the holder **122** may be made of one or more materials selected from the group consisting of tungsten, zinc, nickel, copper, silver, aluminum, gold, platinum, tin, stainless steel, and conductive ceramic. When an electric field is applied to the field emission assembly **120**, electrons may move to the emitter **121** through the holder **122** formed of an electrically conductive material and then may be emitted to the outside of the emitter **121**.

(58) The holder **122** may include the seating part **1221**. The emitter **121** may be seated on the seating part **1221**. Specifically, the electron emission portion **1211** of the emitter **121** may be disposed on the front surface of the seating part **1221** in the electron emission direction x , and the side portions **1212** of the emitter **121** may be disposed to surround the seating part **1221**. In this case, the side portions **1212** of the emitter **121** may be disposed inside the gaps formed between the seating part **1221** and the fixing parts **1222**.

(59) The front surface of the seating part **1221** in the electron emission direction x may be perpendicular to the electron emission direction x . Since the electron emission portion **1211** in the form of a sheet is disposed in close contact with the front surface of the seating part **1221** in the electron emission direction x , the electron emission portion **1211** may also be perpendicular to the electron emission direction x . In this way, when an electric field is applied to the electromagnetic wave generator **100**, a uniform electric potential may be formed in the electron emission portion **1211** so that the uniformity of the field emission characteristics may be improved.

(60) The holder **122** may include the fixing parts **1222**. The fixing parts **1222** may be disposed on both sides of the seating part **1221**. Gaps may be formed between the seating part **1221** and the fixing parts **1222**, and the side portions **1212** of the emitter **121** may be disposed inside the gaps.

(61) The fixing parts **1222** may include the coupling holes **1223**. The coupling holes **1223** may be formed to pass through side surfaces of the fixing parts **1222** in a lateral direction. The coupling members **123** may be coupled to the coupling holes **1223**.

(62) The field emission assembly **120** may include the coupling members **123**. The coupling members **123** may be coupled by passing through the coupling holes **1223** formed in the fixing parts **1222**. The coupling members **123** may fix the emitter **121** to the holder **122**. For example, screw threads may be formed on inner surfaces of the coupling holes **1223** and outer surfaces of the coupling members **123**, respectively, and the coupling members **123** may be screw-coupled to the coupling holes **1223**.

(63) Specifically, when the coupling members **123** are coupled to the coupling holes **1223** formed in the fixing parts **1222**, ends of the coupling members **123** may pressurize the side surfaces of the seating part **1221**. In this case, the side portions **1212** of the emitter **121** may be disposed between the ends of the coupling members **123** and the side surfaces of the seating part **1221** to be fixed to the holder **122** in such a way of being pressurized by the ends of the coupling members **123** and the side surfaces of the seating part **1221**.

(64) Alternatively, the emitter **121** may be fixed to the holder **122** in a variety of ways. For example, the side portions **1212** of the emitter **121** may be directly pressurized and fixed by the seating part **1221** and the fixing parts **1222**. Specifically, instead of the ends of the coupling members **123** being terminated on the side surfaces of the seating part **1221**, coupling grooves are also formed on the side surfaces of the seating part **1221** so that the coupling members **123** may be fastened to the seating part **1221** after passing through the fixing parts **1222**. In this case, when the coupling members **123** are tightened, a width of each gap may be reduced as a distance between the seating part **1221** and the fixing parts **1222** is decreased. When the coupling members **123** are tightened in a state in which the side portions **1212** of the emitter **121** are disposed inside the gaps, the side portions **1212** of the emitter **121** may be pressurized and fixed by the side surfaces of the seating part **1221** and the side surfaces of the fixing parts **1222**.

(65) Alternatively, the holder **122** does not include the fixing parts **1222**, and the coupling members **123** may be directly coupled to the side surfaces of the seating part **1221**. In this case, in a state in which the side portions **1212** of the emitter **121** are disposed on the side surfaces of the seating part **1221**, when the coupling members **123** pass through the side portions **1212** of the emitter **121** to be coupled to the side surfaces of the seating part **1221**, the emitter **121** may be fixed to the holder **122**.

(66) The seating part **1221** and the fixing parts **1222** of the holder **122** may be formed as separate members. In this case, since the seating part **1221** and the fixing parts **1222** may each be manufactured in the form of a box, it may be easy to manufacture each member. Alternatively, the seating part **1221** and the fixing parts **1222** of the holder **122** may be integrally formed. In this case, since a separate process of aligning the fixing parts **1222** with respect to the seating part **1221** may not be necessary, the process of fixing the emitter **121** to the holder **122** may be facilitated.

(67) As long as the electron emission portion **1211** of the emitter **121** may be disposed along a plane perpendicular to the electron emission direction x , the present disclosure is not limited to the above-described structure of the holder **122**, and the emitter **121** may be formed in a variety of ways. For example, the emitter **121** may be coupled to the holder **122** through a separate mechanical mechanism, may be attached to the holder **122** through an adhesive, or may be fixed to the holder **122** through a welding method.

(68) FIGS. **6A** and **6B** shows photographs capturing a linear emitter of the field emission assembly according to one example embodiment of the present disclosure. FIGS. **7A** to **7D** is a diagram illustrating a formation process of an emitter of the field emission assembly according to one

example embodiment of the present disclosure.

(69) Referring to FIGS. 6A and 6B, the emitter **121** may be formed by weaving a plurality of linear yarns formed of a CNT material. Referring to FIG. 6A, each of the plurality of yarns **121a** constituting the emitter **121** may be a twisted yarn. In this case, since the yarn **121aa** may be manufactured more easily, manufacturing efficiency may be improved. In addition, referring to FIG. 6B, each of the plurality of yarns **121a** constituting the emitter **121** may be a braided yarn. In this case, since mechanical and electrical properties of the yarn **121a** may be improved, a field emission characteristic may also be improved. The physical properties of the twisted yarn and the braided yarn will be described below in detail with reference to FIGS. 8A to 8D, 9 and 10.

(70) FIGS. 7A to 7D shows in detail a process of forming the emitter **121** of the field emission assembly **120** according to one embodiment of the present disclosure.

(71) Referring to FIGS. 7A and 7B, each of the plurality of yarns **121a** constituting the emitter **121** may be a twisted yarn. In this case, referring to FIG. 7A, the twisted yarn constituting the yarn **121a** may be a primary twisted yarn formed by twisting a plurality of CNT fibers. In addition, referring to FIG. 7B, the twisted yarn constituting yarn **121a** may be a secondary twisted yarn formed by twisting the primary twisted yarns with each other. In this case, the primary twisted yarn may be formed by twisting a plurality of CNT fibers.

(72) Meanwhile, referring to FIGS. 7C and 7D, each of the plurality of yarns **121a** constituting the emitter **121** may be a braided yarn. In this case, referring to FIG. 7C, the braided yarn constituting the yarn **121a** may be formed by braiding a plurality of the primary twisted yarns, and the primary twisted yarn may be formed by twisting a plurality of CNT fibers. In addition, referring to FIG. 7D, the braided yarn constituting the yarn **121a** may be formed by braiding the secondary twisted yarns with each other. In this case, the secondary twisted yarn may be formed by twisting a plurality of the primary twisted yarns, and the primary twisted yarn may be formed by twisting a plurality of CNT fibers.

(73) However, when it is possible to form the linear yarn **121a** capable of forming the emitter **121** in the form of a sheet by weaving, the method of forming the yarn **121a** constituting the emitter **121** is not limited to the method described in FIGS. 7A to 7D, and the emitter **121** may be formed according to a required field emission characteristic in various combinations of the methods shown in FIG. 7A to 7D or may be formed in a method not described in FIGS. 7A to 7D.

(74) FIGS. 8A to 8D is a diagram illustrating a mechanical property according to a type of a yarn constituting the emitter

(75) FIGS. 8A to 8D show a strain-stress curve according to a type of a yarn constituting the emitter and illustrate data after an experiment was performed a plurality of times for each case. FIG. 8A shows a case in which a strain is applied to a yarn (Non-Twisted Yarn_64 Fiber) in which 64 CNT fibers were simply collected, FIG. 8B shows a case in which a strain is applied to a twisted yarn (75 Twisted Yarn 64 Fiber) formed by twisting 64 CNT fibers 75 times, FIG. 8C shows a case in which a strain is applied to a twisted yarn (150 Twisted Yarn_64 Fiber) formed by twisting 64 CNT fibers 150 times, and FIG. 8D shows a case in which a strain is applied to a braided yarn (Braided Yarn 64 Fiber) formed by braiding 64 CNT fibers.

(76) Referring to FIGS. 8A to 8C, when the strain was applied to the simply collected CNT fibers (the non-twisted yarn) and to the twisted yarn formed by twisting CNT fibers, it can be seen that a different stress characteristic exhibited at each experiment. On the other hand, referring to FIG. 8D, when the strain was applied to the braided yarn formed by braiding CNT fibers, it can be seen that there is almost no difference in the stress characteristic at each experiment.

(77) The following Table 1 shows the numerical representation of mechanical properties according to the types of yarns constituting the above-described emitter.

(78) TABLE-US-00001

TABLE 1	Strain (%)	Stress (MPa)	Modulus (GPa)
Non-Twisted Yarn	7.62 ± 1.47	901.5 ± 227.0	9.16 ± 2.05
75 Twisted Yarn	11.94 ± 1.06	1177.0 ± 130.1	6.15 ± 1.35
150 Twisted Yarn	13.51 ± 3.07	1163.9 ± 116.2	5.34 ± 2.43
Braided Yarn	9.67 ± 0.36	$935.8 \pm$	

26.5 9.55 ± 1.06

(79) Referring to Table 1, it can be seen that the deviation value of strain and stress were significantly lower in a case in which the yarn constituting the emitter was formed of the braided yarn than other cases. In addition, even when looking at the value of a change ratio (Modulus) of stress according to strain, it can be confirmed that a case in which the yarn constituting the emitter was formed of the (braided yarn has the smallest deviation value when compared to other cases.

(80) Referring to FIGS. 8A to 8D and Table 1, when the yarn constituting the emitter was formed of the braided yarn, the uniformity of mechanical properties may be improved when compared to the simply collected CNT fibers (the non-twisted yarn) or to the yarn formed of the twisted yarn. In this way, since errors due to differences in the mechanical properties of the emitter may be reduced in the process of forming the field emission assembly, the uniformity of the field emission characteristics may also be improved.

(81) FIG. 9 is a graph illustrating electrical properties when an emitter is formed of a twisted yarn and when the emitter is formed of a braided yarn.

(82) Specifically, FIG. 9 shows electrical conductivity according to the type of yarn constituting the emitter.

(83) The following Table 2 numerically expresses average values (avg) and population standard deviation values (std.p) of the electrical properties of emitters when the emitter is formed of the twisted yarn and when the emitter is formed of the braided yarn.

(84) TABLE-US-00002 TABLE 2 Electrical conductivity (S/cm) avg std.p Twisted Yarn 1670.8 53.6 Braided Yarn 1855.3 27.8

(85) Referring to FIG. 9 and Table 2, when the emitter is formed of braided yarn, it can be seen that the avg of the electric conductivity characteristic was higher, and the std.p thereof was smaller when compared to a case in which the emitter is formed of the twisted yarn. That is, when the emitter is formed based on the braided yarn, the uniformity of electrical conductivity may be further improved so that the uniformity of the field emission characteristic of the emitter may also be improved.

(86) FIG. 10 is a graph illustrating a linear density when an emitter is formed of a twisted yarn and when the emitter is formed of a braided yarn.

(87) The following Table 3 numerically expresses average values (avg) and population standard deviation values (std.p) of the linear densities of emitters when the emitter is formed of the twisted yarn and when the emitter is formed of the braided yarn.

(88) TABLE-US-00003 TABLE 3 Linear density (Tex) avg std.p Twisted Yarn 15.67 2.9 Braided Yarn 16.11 0.68

(89) Referring to FIG. 10 and Table 3, when the emitter is formed of the braided yarn, it can be confirmed that the std.p of the linear density is smaller than that of the twisted yarn. Since an amount of a current flowing through the emitter or resistance of the emitter may be varied when the linear density is changed, it can be understood that the more uniform the linear density, the more uniform the electrical characteristic. That is, when the emitter is formed of the braided yarn, the uniformity of the linear density is excellent, and thus the electrical property may also be uniform so that the uniformity of the field emission property may also be improved.

(90) In accordance with the present disclosure, it is possible to improve the uniformity of a field emission characteristic in an emitter.

(91) In addition, due to the uniformity of the field emission, controlling of a generation amount or an intensity of electromagnetic waves can be more precisely performed.

(92) In addition, durability of the emitter may be improved, and thus an emitter, a field emission assembly, and an electromagnetic wave generator including the same may each have a consistent lifetime.

(93) Any or other example embodiments of the present disclosure described above are not mutually exclusive or distinct. Any of the above-described example embodiments or other example

embodiments of the present disclosure may be mixed or combined in each configuration or each function.

(94) For example, it means that a configuration A described in a specific embodiment and/or drawings may be combined with a configuration B described in other embodiments and/or drawings. That is, even when a coupling between components is not directly described, it means that the coupling is possible except for a case in which it is described that the coupling is impossible.

(95) The above detailed description should not be construed as restrictive in all respects and should be considered as illustrative. The scope of the present disclosure should be determined by a reasonable interpretation of the appended claims, and all modifications within the equivalent scope of the present specification are included in the scope of the present disclosure.

(96) The various embodiments described above can be combined to provide further embodiments. All of the U.S. patents, U.S. patent application publications, U.S. patent applications, foreign patents, foreign patent applications and non-patent publications referred to in this specification and/or listed in the Application Data Sheet are incorporated herein by reference, in their entirety. Aspects of the embodiments can be modified, if necessary to employ concepts of the various patents, applications and publications to provide yet further embodiments.

(97) These and other changes can be made to the embodiments in light of the above-detailed description. In general, in the following claims, the terms used should not be construed to limit the claims to the specific embodiments disclosed in the specification and the claims, but should be construed to include all possible embodiments along with the full scope of equivalents to which such claims are entitled. Accordingly, the claims are not limited by the disclosure.

Claims

1. A field emission assembly, comprising an emitter configured to emit electrons; and a holder configured to fix the emitter, wherein the emitter is in the form of a sheet in which a plurality of yarns including carbon nanotube (CNT) fibers are weaved, wherein the emitter includes an electron emission portion which is a region spread on a plane perpendicular to the electron emission direction, and side portions formed on both sides of the electron emission portion, wherein the holder includes a seating part on which the emitter is seated, and fixing parts disposed on both sides of the seating part, wherein the electron emission portion is seated on a front surface of the seating part in the electron emission direction, and wherein the side portions are disposed in gaps formed between the seating part and the fixing parts while surrounding the seating part.
2. The field emission assembly of claim 1, wherein each of the plurality of yarns is a braided yarn.
3. The field emission assembly of claim 2, wherein: the braided yarn is formed by braiding a plurality of primary twisted yarns; and the primary twisted yarn is formed by twisting a plurality of CNT fibers.
4. The field emission assembly of claim 2, wherein: the braided yarn is formed by braiding a plurality of secondary twisted yarns; the secondary twisted yarn is formed by twisting a plurality of primary twisted yarns, and the primary twisted yarn is formed by twisting a plurality of CNT fibers.
5. The field emission assembly of claim 1, wherein each of the plurality of yarns is a twisted yarn.
6. The field emission assembly of claim 5, wherein the twisted yarn is the primary twisted yarn formed by twisting a plurality of CNT fibers.
7. The field emission assembly of claim 5, wherein: the twisted yarn is the secondary twisted yarn formed by twisting primary twisted yarns with each other; and the primary twisted yarn is formed by twisting a plurality of CNT fibers.
8. The field emission assembly of claim 1, wherein the front surface of the seating part in the electron emission direction is perpendicular to the electron emission direction.
9. The field emission assembly of claim 1, further comprising: coupling members configured to

pass through the fixing parts in a lateral direction, wherein the emitter is fixed to the holder by pressurizing the side portions by the coupling members and side surfaces of the seating part.

10. An electromagnetic wave generator, comprising a field emission assembly including an emitter configured to emit electrons and a holder configured to fix the emitter; and an anode in which electrons emitted from the field emission assembly collide to generate electromagnetic waves, wherein the emitter is in the form of a sheet in which a plurality of yarns including carbon nanotube (CNT) fibers are weaved, wherein the emitter includes an electron emission portion which is a region spread on a plane perpendicular to the electron emission direction, and side portions formed on both sides of the electron emission portion, wherein the holder includes a seating part on which the emitter is seated, and fixing parts disposed on both sides of the seating part, wherein the electron emission portion is seated on a front surface of the seating part in the electron emission direction, and wherein the side portions are disposed in gaps formed between the seating part and the fixing parts while surrounding the seating part.

11. The electromagnetic wave generator of claim 10, wherein the emitter includes an electron emission portion extending on a plane perpendicular to a direction toward the anode.

12. The electromagnetic wave generator of claim 10, wherein the electromagnetic wave has a wavelength ranging from 0.001 nm to 10 nm.

13. The electromagnetic wave generator of claim 10, wherein each of the plurality of yarns is a braided yarn.

14. The electromagnetic wave generator of claim 13, wherein: the braided yarn is formed by braiding a plurality of primary twisted yarns; and the primary twisted yarn is formed by twisting a plurality of CNT fibers.

15. The electromagnetic wave generator of claim 13, wherein: the braided yarn is formed by braiding a plurality of secondary twisted yarns; the secondary twisted yarn is formed by twisting a plurality of primary twisted yarns, and the primary twisted yarn is formed by twisting a plurality of CNT fibers.

16. The electromagnetic wave generator of claim 10, wherein each of the plurality of yarns is a twisted yarn.

17. The electromagnetic wave generator of claim 16, wherein the twisted yarn is the primary twisted yarn formed by twisting a plurality of CNT fibers.

18. The electromagnetic wave generator of claim 16, wherein: the twisted yarn is the secondary twisted yarn formed by twisting primary twisted yarns with each other; and the primary twisted yarn is formed by twisting a plurality of CNT fibers.

19. The electromagnetic wave generator of claim 10, wherein the front surface of the seating part in the electron emission direction is perpendicular to the electron emission direction.

20. The electromagnetic wave generator of claim 10, further comprising: coupling members configured to pass through the fixing parts in a lateral direction, wherein the emitter is fixed to the holder by pressurizing the side portions by the coupling members and side surfaces of the seating part.
