

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418960
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Talebi Fard; Peyman et al.

Group communication service request

Abstract

An access and mobility management function (AMF) receives from a first wireless device a non-access stratum (NAS) message comprising an identifier (ID) of a group communication session. The AMF receives from a session management function (SMF) a message comprising a list of one or more second wireless devices associated with the group communication session and a list of one or more packet data unit (PDU) sessions. The AMF determines, based on a state of the one or more second wireless devices, to page the one or more second wireless devices. The AMF receives from the one or more second wireless devices one or more service request messages.

Inventors: Talebi Fard; Peyman (Vienna, VA), Dinan; Esmael Hejazi (McLean, VA), Ryu; Jinsook (Oakton, VA), Park; Kyungmin (Vienna, VA), Qiao; Weihua (Herndon, VA)

Applicant: Peninsula Technologies, LLC (Allen, TX)

Family ID: 1000008818546

Assignee: Peninsula Technologies, LLC (Allen, TX)

Appl. No.: 18/516154

Filed: November 21, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240090079 A1	Mar. 14, 2024

Related U.S. Application Data

continuation parent-doc US 16865556 20200504 US 11832341 child-doc US 18516154
us-provisional-application US 62843110 20190503

Publication Classification

Int. Cl.: H04W76/40 (20180101); H04W68/00 (20090101)

U.S. Cl.:

CPC H04W76/40 (20180201); H04W68/00 (20130101);

Field of Classification Search

CPC: H04W (76/40); H04W (68/00); H04W (68/005); H04W (76/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9445243	12/2015	Yu et al.	N/A	N/A
9693205	12/2016	Vaidya et al.	N/A	N/A
2017/0142560	12/2016	Ryu et al.	N/A	N/A
2018/0198867	12/2017	Dao et al.	N/A	N/A
2018/0279400	12/2017	Faccin	N/A	H04W 68/005
2018/0352416	12/2017	Ryu et al.	N/A	N/A
2019/0007500	12/2018	Kim et al.	N/A	N/A
2019/0007992	12/2018	Kim	N/A	H04W 76/27
2019/0116003	12/2018	Moisanen et al.	N/A	N/A
2019/0166467	12/2018	Livanos	N/A	H04W 8/186
2019/0261260	12/2018	Dao	N/A	H04W 48/00
2020/0015195	12/2019	Chong	N/A	H04W 68/06
2020/0252785	12/2019	Wu	N/A	H04W 28/06
2020/0280948	12/2019	Youn et al.	N/A	N/A
2020/0336964	12/2019	Kawasaki et al.	N/A	N/A
2020/0344823	12/2019	Lu	N/A	H04W 4/12
2021/0153265	12/2020	Liu	N/A	H04W 48/16
2022/0386228	12/2021	Dao	N/A	H04W 36/0009

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2018/175974	12/2017	WO	N/A
2018/194971	12/2017	WO	N/A
2019/032779	12/2018	WO	N/A
2019/062754	12/2018	WO	N/A

OTHER PUBLICATIONS

3GPP TS 29.244 V15.5.0 (Mar. 2019); Technical Specification; 3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; Interface between the Control Plane and the User Plane Nodes; Stage 3; (Release 15). cited by applicant
S2-1900597; 3GPP TSG-SA WG2 Meeting #130; Jan. 21-25, 2019, Kochi, India; CR-Form-v11.2; Change Request; 23.502 CR 0965 rev—Current version: 15.4.1; Title: Support one to many communication for 5GLAN. cited by applicant

S2-1901359; 3GPP TSG-SA WG2 Meeting #130; Jan. 21-25, 2019, Kochi, India; CR-Form-v11.2.1; Change Request; 23.502 CR 0987 rev 2 Current version: 15.4.1; Title: 5GLAN group management procedures. cited by applicant

S2-1901554; SA WG2 Meeting #131; Feb. 25-Mar. 1, 2019, Santa Cruz-Tenerife, Spain; CR-Form-v11.4; Change Request; 23.502 CR 1018 rev Current version: 15.4.1; Title: Clarification for 5GLAN Nx tunnel management. cited by applicant

S2-1902005; 3GPP TSG-SA WG2 Meeting #131; Feb. 25-Mar. 1, 2019, Santa Cruz, Tenerife, ES; CR-Form-v11.2.1; Change Request; 23.501 CR 1000 rev—Current version: 15.4.0; Title: 5GLAN communication. cited by applicant

S2-1902006; 3GPP TSG-SA WG2 Meeting #131; Feb. 25-Mar. 1, 2019, Santa Cruz, Tenerife, ES; CR-Form-v11.2.1; Change Request; 23.502 CR 1096 rev—Current version: 15.4.1; Title: 5GLAN communication. cited by applicant

S2-1902007; 3GPP TSG-SA WG2 Meeting #131; Santa Cruz, Spain, Feb. 25-Mar. 1, 2019; (revision of S2-1901337, 01208); CR-Form-v11.4; Change Request; 23.501 CR 0747 rev 6 Current version: 15.4.0; Title: Support for 5G LAN. cited by applicant

S2-1903220; 3GPP TSG-SA WG2 Meeting #132; Apr. 8-12, 2019, Xi'an, China; CR-Form-v11.4; Change Request; 23.502 CR 1159 rev Current version: 16.0.0; Title: Adding 5GLAN Nx tunnel management. cited by applicant

S2-1903221; 3GPP TSG-SA WG2 Meeting #132; Apr. 8-12, 2019, Xi'an, China; CR-Form-v11.4; Change Request; 23.501 CR 1077 rev Current version: 16.0.2; Title: Data forwarding for 5G-LAN multicast. cited by applicant

S2-1903312; SA WG2 Meeting #132; Feb. 8-12, 2019, Xian, P.R. China; (revision of S2-1903312); Source:Nokia, Nokia Shanghai Bell; Title: 5G LAN group communication with UPF autonomous traffic forwarding; Document for: Discussion. cited by applicant

S2-19xxxxx; 3GPP TSG-SA WG2 Meeting #132; Apr. 8-12, 2019, Xi'an, China; CR-Form-v11.4; Change Request; 23.501 CR xxx rev Current version: 16.0.2; Title: 5G-LAN Service continuity. cited by applicant

S2-1903723; 3GPP TSG-SA WG2 Meeting #132 Apr. 8-12, 2019, Xian, P.R.China; (revision of S2-19xxxx); Source: Huawei, HiSilicon; Title: IPTV solution update; Document for: Approval. cited by applicant

S2-1903854; 3GPP TSG-SA2 Meeting #132; Xi'An, China, Apr. 8-Apr. 12; CR-Form-v11.4; Change Request; 23.501 CR 1267 rev—Current version: 16.0.0; Title: Proposal of 1:N 5GLAN DNN and 5GLAN group mapping. cited by applicant

S2-1903856; 3GPP TSG-SA WG2 Meeting #132; Xi'an, China, Apr. 8-Apr. 12, 2019; (revision of S2-19xxxxx); CR-Form-v11.4; Change Request; 23.501 CR 1268 rev—Current version: 16.0.0; Title: Proposal of supporting 1:N mapping relation between DNN and 5GLAN group. cited by applicant

S2-1903858; 3GPP TSG-SA WG2 Meeting #131; Xi'an, China, Apr. 8-Apr. 12, 2019; (revision of S2-19xxxx); CR-Form-v11.4; Change Request; 23.501 CR 1269 rev—Current version: 16.0.0; Title: 5GLAN AF Provisioning. cited by applicant

S2-1903859; 3GPP TSG-SA WG2 Meeting #131; Xi'an, China, Apr. 8-Apr. 12, 2019; (revision of S2-19xxxx); CR-Form-v11.4; Change Request; 23.501 CR 1270 rev—Current version: 16.0.0; Title: 5GLAN UPF selection. cited by applicant

S2-1904604; 3GPP TSG-SA WG2 Meeting #132; Apr. 8-12, 2019, Xi'an, China; (was S2-1903634); CR-Form-v11.4; Change Request; 23.501 CR 1207 rev 1 Current version: 16.0.2; Title: 5G-LAN Service continuity. cited by applicant

S2-1904607; 3GPP TSG-SA2 Meeting #132; Xi'An, China, Apr. 8-Apr. 12; CR-Form-v11.4; Change Request; 23.501 CR 1267 rev 1 Current version: 16.0.0; Title: Proposal of 1:N 5GLAN DNN and 5GLAN group mapping. cited by applicant

S2-1904615; 3GPP TSG-SA WG2 Meeting #131; Xi'an, China, Apr. 8-Apr. 12, 2019; (revision of

S2-194615); CR-Form-v11.4; Change Request; 23.501 CR 1269 rev 1 Current version: 16.0.0; Title: 5GLAN AF Provisioning. cited by applicant
S2-1904775; 3GPP TSG-SA WG2 Meeting #132; Xi'an, China, Apr. 8-12, 2019; (revision of S2-1904602); CR-Form-v11.4; Change Request; 23.501 CR 1052 rev 2 Current version: 16.0.0; Title: Further detailing of 5G LAN group management. cited by applicant
S2-1904776; 3GPP TSG-SA WG2 Meeting #132; Apr. 8-12, 2019, Xi'an, China; (was S2-1904601); CR-Form-v11.4; Change Request; 23.501 CR 1202 rev 2 Current version: 16.0.2; Title: Clarification on PDU Session management for 5G-LAN multicast. cited by applicant
S2-1904777; 3GPP TSG-SA WG2 Meeting #132; Apr. 8-12, 2019, Xi'an, China; (was S2-1904604); CR-Form-v11.4; Change Request; 23.501 CR 1207 rev 2 Current version: 16.0.2; Title: 5G-LAN Service continuity. cited by applicant
S2-1904785; 3GPP TSG-SA WG2 Meeting #132; Apr. 8-12, 2019, Xi'an, China; (was S2-1904604); CR-Form-v11.4; Change Request; 23.501 CR 1207 rev 3 Current version: 16.0.2; Title: 5G-LAN Service continuity. cited by applicant

Primary Examiner: Ahmed; Atique

Attorney, Agent or Firm: Ascenda Law Group, PC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/865,556, filed May 4, 2020, which claims the benefit of U.S. Provisional Application No. 62/843,110, filed May 3, 2019, all of which are hereby incorporated by reference in their entireties.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

- (1) Examples of several of the various embodiments of the present invention are described herein with reference to the drawings.
- (2) FIG. 1 is a diagram of an example 5G system architecture as per an aspect of an embodiment of the present disclosure.
- (3) FIG. 2 is a diagram of an example 5G System architecture as per an aspect of an embodiment of the present disclosure.
- (4) FIG. 3 is a system diagram of an example wireless device and a network node in a 5G system as per an aspect of an embodiment of the present disclosure.
- (5) FIG. 4 is a system diagram of an example network node as per an aspect of an embodiment of the present disclosure.
- (6) FIG. 5A and FIG. 5B depict two registration management state models in UE **100** and AMF **155** as per an aspect of embodiments of the present disclosure.
- (7) FIG. 6A and FIG. 6B depict two connection management state models in UE **100** and AMF **155** as per an aspect of embodiments of the present disclosure.
- (8) FIG. 7 is diagram for classification and marking traffic as per an aspect of an embodiment of the present disclosure.
- (9) FIG. 8 is an example call flow as per an aspect of an embodiment of the present disclosure.
- (10) FIG. 9 is an example call flow as per an aspect of an embodiment of the present disclosure.
- (11) FIG. 10 is an example call flow as per an aspect of an embodiment of the present disclosure.
- (12) FIG. 11 is an example call flow as per an aspect of an embodiment of the present disclosure.
- (13) FIG. 12 is an example call flow as per an aspect of an embodiment of the present disclosure.
- (14) FIG. 13 is an example call flow as per an aspect of an embodiment of the present disclosure.

(15) FIG. 14 is an example diagram as per an aspect of an embodiment of the present disclosure.
(16) FIG. 15 is an example diagram as per an aspect of an embodiment of the present disclosure.
(17) FIG. 16 is an example call flow as per an aspect of an embodiment of the present disclosure.
(18) FIG. 17 is an example call flow as per an aspect of an embodiment of the present disclosure.
(19) FIG. 18 is an example call flow as per an aspect of an embodiment of the present disclosure.
(20) FIG. 19 is an example call flow as per an aspect of an embodiment of the present disclosure.
(21) FIG. 20 is an example call flow as per an aspect of an embodiment of the present disclosure.
(22) FIG. 21 is an example diagram as per an aspect of an embodiment of the present disclosure.
(23) FIG. 22 is an example diagram as per an aspect of an embodiment of the present disclosure.
(24) FIG. 23 is an example call flow as per an aspect of an embodiment of the present disclosure.
(25) FIG. 24 is an example diagram as per an aspect of an embodiment of the present disclosure.
(26) FIG. 25 is an example diagram as per an aspect of an embodiment of the present disclosure.
(27) FIG. 26 is an example diagram as per an aspect of an embodiment of the present disclosure.
(28) FIG. 27 is an example call flow as per an aspect of an embodiment of the present disclosure.
(29) FIG. 28 is an example call flow as per an aspect of an embodiment of the present disclosure.
(30) FIG. 29 is an example call flow as per an aspect of an embodiment of the present disclosure.
(31) FIG. 30 is an example call flow as per an aspect of an embodiment of the present disclosure.
(32) FIG. 31 is an example call flow as per an aspect of an embodiment of the present disclosure.
(33) FIG. 32 is an example diagram as per an aspect of an embodiment of the present disclosure.
(34) FIG. 33 is an example diagram as per an aspect of an embodiment of the present disclosure.
(35) FIG. 34 is an example diagram as per an aspect of an embodiment of the present disclosure.
(36) FIG. 35 is an example diagram as per an aspect of an embodiment of the present disclosure.
(37) FIG. 36 is a flow diagram of an aspect of an example embodiment of the present disclosure.

Description

DETAILED DESCRIPTION OF EMBODIMENTS

(1) Example embodiments of the present invention enable implementation of enhanced features and functionalities in 5G systems. Embodiments of the technology disclosed herein may be employed in the technical field of 5G systems and network slicing for communication systems. More particularly, the embodiments of the technology disclosed herein may relate to 5G core network and 5G systems for network slicing in communication systems. Throughout the present disclosure, UE, wireless device, and mobile device are used interchangeably. The following acronyms are used throughout the present disclosure: 5G 5th generation mobile networks 5GC 5G Core Network 5GS 5G System 5G-AN 5G Access Network 5QI 5G QoS Indicator AF Application Function AMF Access and Mobility Management Function AN Access Network CDR Charging Data Record CCNF Common Control Network Functions CIoT Cellular IoT CN Core Network CP Control Plane DDN Downlink Data Notification DL Downlink DN Data Network DNN Data Network Name F-TEID Fully Qualified TEID GPSI Generic Public Subscription Identifier GTP GPRS Tunneling Protocol GUTI Globally Unique Temporary Identifier IMSI International Mobile Subscriber Identity LADN Local Area Data Network LI Lawful Intercept MEI Mobile Equipment Identifier MICO Mobile Initiated Connection Only MME Mobility Management Entity MO Mobile Originated MSISDN Mobile Subscriber ISDN MT Mobile Terminating N3IWF Non-3GPP InterWorking Function NAI Network Access Identifier NAS Non-Access Stratum NB-IoT Narrow Band IoT NEF Network Exposure Function NF Network Function NGAP Next Generation Application Protocol NR New Radio NRF Network Repository Function NSI Network Slice Instance NSSAI Network Slice Selection Assistance Information NSSF Network Slice Selection Function OCS Online Charging System OFCS Offline Charging System PCF Policy Control Function PDU Packet/Protocol Data Unit PEI Permanent Equipment Identifier PLMN Public Land

Mobile Network RAN Radio Access Network QFI QoS Flow Identity RM Registration Management S1-AP S1 Application Protocol SBA Service Based Architecture SEA Security Anchor Function SCM Security Context Management SMF Session Management Function SMSF SMS Function S-NSSAI Single Network Slice Selection Assistance information SUCI Served User Correlation ID SUPI Subscriber Permanent Identifier TEID Tunnel Endpoint Identifier TSN Time Sensitive Networking UE User Equipment UL Uplink UL CL Uplink Classifier UPF User Plane Function

(2) Example FIG. 1 and FIG. 2 depict a 5G system comprising of access networks and 5G core network. An example 5G access network may comprise an access network connecting to a 5G core network. An access network may comprise an NG-RAN **105** and/or non-3GPP AN **165**. An example 5G core network may connect to one or more 5G access networks 5G-AN and/or NG-RANs. 5G core network may comprise functional elements or network functions as in example FIG. 1 and example FIG. 2 where interfaces may be employed for communication among the functional elements and/or network elements.

(3) In an example, a network function may be a processing function in a network, which may have a functional behavior and/or interfaces. A network function may be implemented either as a network element on a dedicated hardware, and/or a network node as depicted in FIG. 3 and FIG. 4, or as a software instance running on a dedicated hardware and/or shared hardware, or as a virtualized function instantiated on an appropriate platform.

(4) In an example, access and mobility management function, AMF **155**, may include the following functionalities (some of the AMF **155** functionalities may be supported in a single instance of an AMF **155**): termination of RAN **105** CP interface (N2), termination of NAS (N1), NAS ciphering and integrity protection, registration management, connection management, reachability management, mobility management, lawful intercept (for AMF **155** events and interface to LI system), provide transport for session management, SM messages between UE **100** and SMF **160**, transparent proxy for routing SM messages, access authentication, access authorization, provide transport for SMS messages between UE **100** and SMSF, security anchor function, SEA, interaction with the AUSF **150** and the UE **100**, receiving the intermediate key established as a result of the UE **100** authentication process, security context management, SCM, that receives a key from the SEA that it uses to derive access network specific keys, and/or the like.

(5) In an example, the AMF **155** may support non-3GPP access networks through N2 interface with N3IWF **170**, NAS signaling with a UE **100** over N3IWF **170**, authentication of UEs connected over N3IWF **170**, management of mobility, authentication, and separate security context state(s) of a UE **100** connected via non-3GPP access **165** or connected via 3GPP access **105** and non-3GPP access **165** simultaneously, support of a coordinated RM context valid over 3GPP access **105** and non-3GPP access **165**, support of CM management contexts for the UE **100** for connectivity over non-3GPP access, and/or the like.

(6) In an example, an AMF **155** region may comprise one or multiple AMF **155** sets. The AMF **155** set may comprise some AMF **155** that serve a given area and/or network slice(s). In an example, multiple AMF **155** sets may be per AMF **155** region and/or network slice(s). Application identifier may be an identifier that may be mapped to a specific application traffic detection rule. Configured NSSAI may be an NSSAI that may be provisioned in a UE **100**. DN **115** access identifier (DNAI), for a DNN, may be an identifier of a user plane access to a DN **115**. Initial registration may be related to a UE **100** registration in RM-DEREGISTERED **500**, **520** states. N2AP UE **100** association may be a logical per UE **100** association between a 5G AN node and an AMF **155**. N2AP UE-TNLA-binding may be a binding between a N2AP UE **100** association and a specific transport network layer, TNL association for a given UE **100**.

(7) In an example, session management function, SMF **160**, may include one or more of the following functionalities (one or more of the SMF **160** functionalities may be supported in a single instance of a SMF **160**): session management (e.g. session establishment, modify and release,

including tunnel maintain between UPF **110** and AN **105** node), UE **100** IP address allocation & management (including optional authorization), selection and control of UP function(s), configuration of traffic steering at UPF **110** to route traffic to proper destination, termination of interfaces towards policy control functions, control part of policy enforcement and QoS. lawful intercept (for SM events and interface to LI System), termination of SM parts of NAS messages, downlink data notification, initiation of AN specific SM information, sent via AMF **155** over N2 to (R)AN **105**, determination of SSC mode of a session, roaming functionality, handling local enforcement to apply QoS SLAs (VPLMN), charging data collection and charging interface (VPLMN), lawful intercept (in VPLMN for SM events and interface to LI System), support for interaction with external DN **115** for transport of signaling for PDU session authorization/authentication by external DN **115**, and/or the like.

(8) In an example, a user plane function, UPF **110**, may include one or more of the following functionalities (some of the UPF **110** functionalities may be supported in a single instance of a UPF **110**): anchor point for Intra-/Inter-RAT mobility (when applicable), external PDU session point of interconnect to DN **115**, packet routing & forwarding, packet inspection and user plane part of policy rule enforcement, lawful intercept (UP collection), traffic usage reporting, uplink classifier to support routing traffic flows to a data network, branching point to support multi-homed PDU session(s), QoS handling for user plane, uplink traffic verification (SDF to QoS flow mapping), transport level packet marking in the uplink and downlink, downlink packet buffering, downlink data notification triggering, and/or the like.

(9) In an example, the UE **100** IP address management may include allocation and release of the UE **100** IP address and/or renewal of the allocated IP address. The UE **100** may set a requested PDU type during a PDU session establishment procedure based on its IP stack capabilities and/or configuration. In an example, the SMF **160** may select PDU type of a PDU session. In an example, if the SMF **160** receives a request with PDU type set to IP, the SMF **160** may select PDU type IPv4 or IPv6 based on DNN configuration and/or operator policies. In an example, the SMF **160** may provide a cause value to the UE **100** to indicate whether the other IP version is supported on the DNN. In an example, if the SMF **160** receives a request for PDU type IPv4 or IPv6 and the requested IP version is supported by the DNN the SMF **160** may select the requested PDU type.

(10) In an example embodiment, the 5GC elements and UE **100** may support the following mechanisms: during a PDU session establishment procedure, the SMF **160** may send the IP address to the UE **100** via SM NAS signaling. The IPv4 address allocation and/or IPv4 parameter configuration via DHCPv4 may be employed once PDU session may be established. IPv6 prefix allocation may be supported via IPv6 stateless autoconfiguration, if IPv6 is supported. In an example, 5GC network elements may support IPv6 parameter configuration via stateless DHCPv6.

(11) The 5GC may support the allocation of a static IPv4 address and/or a static IPv6 prefix based on subscription information in a UDM **140** and/or based on the configuration on a per-subscriber, per-DNN basis.

(12) User plane function(s) (UPF **110**) may handle the user plane path of PDU sessions. A UPF **110** that provides the interface to a data network may support functionality of a PDU session anchor.

(13) In an example, a policy control function, PCF **135**, may support unified policy framework to govern network behavior, provide policy rules to control plane function(s) to enforce policy rules, implement a front end to access subscription information relevant for policy decisions in a user data repository (UDR), and/or the like.

(14) A network exposure function, NEF **125**, may provide means to securely expose the services and capabilities provided by the 3GPP network functions, translate between information exchanged with the AF **145** and information exchanged with the internal network functions, receive information from other network functions, and/or the like.

(15) In an example, an network repository function, NRF **130** may support service discovery function that may receive NF discovery request from NF instance, provide information about the

discovered NF instances (be discovered) to the NF instance, and maintain information about available NF instances and their supported services, and/or the like.

(16) In an example, an NSSF **120** may select a set of network slice instances serving the UE **100**, may determine allowed NSSAI. In an example, the NSSF **120** may determine the AMF **155** set to be employed to serve the UE **100**, and/or, based on configuration, determine a list of candidate AMF **155(s)** **155** by querying the NRF **130**.

(17) In an example, stored data in a UDR may include at least user subscription data, including at least subscription identifiers, security credentials, access and mobility related subscription data, session related subscription data, policy data, and/or the like.

(18) In an example, an AUSF **150** may support authentication server function (AUSF **150**).

(19) In an example, an application function, AF **145**, may interact with the 3GPP core network to provide services. In an example, based on operator deployment, application functions may be trusted by the operator to interact directly with relevant network functions. Application functions not allowed by the operator to access directly the network functions may use an external exposure framework (e.g., via the NEF **125**) to interact with relevant network functions.

(20) In an example, control plane interface between the (R)AN **105** and the 5G core may support connection of multiple different kinds of AN(s) (e.g. 3GPP RAN **105**, N3IWF **170** for Un-trusted access **165**) to the 5GC via a control plane protocol. In an example, an N2 AP protocol may be employed for both the 3GPP access **105** and non-3GPP access **165**. In an example, control plane interface between the (R)AN **105** and the 5G core may support decoupling between AMF **155** and other functions such as SMF **160** that may need to control the services supported by AN(s) (e.g. control of the UP resources in the AN **105** for a PDU session).

(21) In an example, the 5GC may provide policy information from the PCF **135** to the UE **100**. In an example, the policy information may comprise: access network discovery and selection policy, UE **100** route selection policy (URSP), SSC mode selection policy (SSCMSP), network slice selection policy (NSSP), DNN selection policy, non-seamless offload policy, and/or the like.

(22) In an example, as depicted in example FIG. 5A and FIG. 5B, the registration management, RM may be employed to register or de-register a UE/user **100** with the network, and establish the user context in the network. Connection management may be employed to establish and release the signaling connection between the UE **100** and the AMF **155**.

(23) In an example, a UE **100** may register with the network to receive services that require registration. In an example, the UE **100** may update its registration with the network periodically in order to remain reachable (periodic registration update), or upon mobility (e.g., mobility registration update), or to update its capabilities or to re-negotiate protocol parameters.

(24) In an example, an initial registration procedure as depicted in example FIG. 8 and FIG. 9 may involve execution of network access control functions (e.g. user authentication and access authorization based on subscription profiles in UDM **140**). Example FIG. 9 is a continuation of the initial registration procedure depicted in FIG. 8. As a result of the initial registration procedure, the identity of the serving AMF **155** may be registered in a UDM **140**.

(25) In an example, the registration management, RM procedures may be applicable over both 3GPP access **105** and non 3GPP access **165**.

(26) An example FIG. 5A may depict the RM states of a UE **100** as observed by the UE **100** and AMF **155**. In an example embodiment, two RM states may be employed in the UE **100** and the AMF **155** that may reflect the registration status of the UE **100** in the selected PLMN: RM-DEREGISTERED **500**, and RM-REGISTERED **510**. In an example, in the RM DEREGISTERED state **500**, the UE **100** may not be registered with the network. The UE **100** context in the AMF **155** may not hold valid location or routing information for the UE **100** so the UE **100** may not be reachable by the AMF **155**. In an example, the UE **100** context may be stored in the UE **100** and the AMF **155**. In an example, in the RM REGISTERED state **510**, the UE **100** may be registered with the network. In the RM-REGISTERED **510** state, the UE **100** may receive services that may

require registration with the network.

(27) In an example embodiment, two RM states may be employed in AMF **155** for the UE **100** that may reflect the registration status of the UE **100** in the selected PLMN: RM-DEREGISTERED **520**, and RM-REGISTERED **530**.

(28) As depicted in example FIG. **6A** and FIG. **6B**, connection management, CM, may comprise establishing and releasing a signaling connection between a UE **100** and an AMF **155** over N1 interface. The signaling connection may be employed to enable NAS signaling exchange between the UE **100** and the core network. The signaling connection between the UE **100** and the AMF **155** may comprise both the AN signaling connection between the UE **100** and the (R)AN **105** (e.g. RRC connection over 3GPP access) and the N2 connection for the UE **100** between the AN and the AMF **155**.

(29) As depicted in example FIG. **6A** and FIG. **6B**, two CM states may be employed for the NAS signaling connectivity of the UE **100** with the AMF **155**, CM-IDLE **600**, **620** and CM-CONNECTED **610**, **630**. A UE **100** in CM-IDLE **600** state may be in RM-REGISTERED **510** state and may have no NAS signaling connection established with the AMF **155** over N1. The UE **100** may perform cell selection, cell reselection, PLMN selection, and/or the like. A UE **100** in CM-CONNECTED **610** state may have a NAS signaling connection with the AMF **155** over N1.

(30) In an example embodiment two CM states may be employed for the UE **100** at the AMF **155**, CM-IDLE **620** and CM-CONNECTED **630**.

(31) In an example, an RRC inactive state may apply to NG-RAN (e.g. it may apply to NR and E-UTRA connected to 5G CN). The AMF **155**, based on network configuration, may provide assistance information to the NG RAN **105**, to assist the NG RAN's **105** decision whether the UE **100** may be sent to RRC inactive state. When a UE **100** is CM-CONNECTED **610** with RRC inactive state, the UE **100** may resume the RRC connection due to uplink data pending, mobile initiated signaling procedure, as a response to RAN **105** paging, to notify the network that it has left the RAN **105** notification area, and/or the like.

(32) In an example, a NAS signaling connection management may include establishing and releasing a NAS signaling connection. A NAS signaling connection establishment function may be provided by the UE **100** and the AMF **155** to establish the NAS signaling connection for the UE **100** in CM-IDLE **600** state. The procedure of releasing the NAS signaling connection may be initiated by the 5G (R)AN **105** node or the AMF **155**.

(33) In an example, reachability management of a UE **100** may detect whether the UE **100** is reachable and may provide the UE **100** location (e.g. access node) to the network to reach the UE **100**. Reachability management may be done by paging the UE **100** and the UE **100** location tracking. The UE **100** location tracking may include both UE **100** registration area tracking and UE **100** reachability tracking. The UE **100** and the AMF **155** may negotiate UE **100** reachability characteristics in CM-IDLE **600**, **620** state during registration and registration update procedures.

(34) In an example, two UE **100** reachability categories may be negotiated between a UE **100** and an AMF **155** for CM-IDLE **600**, **620** state. 1) UE **100** reachability allowing mobile device terminated data while the UE **100** is CM-IDLE **600** mode. 2) Mobile initiated connection only (MICO) mode. The 5GC may support a PDU connectivity service that provides exchange of PDUs between the UE **100** and a data network identified by a DNN. The PDU connectivity service may be supported via PDU sessions that are established upon request from the UE **100**.

(35) In an example, a PDU session may support one or more PDU session types. PDU sessions may be established (e.g. upon UE **100** request), modified (e.g. upon UE **100** and 5GC request) and/or released (e.g. upon UE **100** and 5GC request) using NAS SM signaling exchanged over N1 between the UE **100** and the SMF **160**. Upon request from an application server, the 5GC may be able to trigger a specific application in the UE **100**. When receiving the trigger, the UE **100** may send it to the identified application in the UE **100**. The identified application in the UE **100** may establish a PDU session to a specific DNN.

(36) In an example, the 5G QoS model may support a QoS flow based framework as depicted in example FIG. 7. The 5G QoS model may support both QoS flows that require a guaranteed flow bit rate and QoS flows that may not require a guaranteed flow bit rate. In an example, the 5G QoS model may support reflective QoS. The QoS model may comprise flow mapping or packet marking at the UPF **110** (CN_UP) **110**, AN **105** and/or the UE **100**. In an example, packets may arrive from and/or destined to the application/service layer **730** of UE **100**, UPF **110** (CN_UP) **110**, and/or the AF **145**.

(37) In an example, the QoS flow may be a granularity of QoS differentiation in a PDU session. A QoS flow ID, QFI, may be employed to identify the QoS flow in the 5G system. In an example, user plane traffic with the same QFI within a PDU session may receive the same traffic forwarding treatment. The QFI may be carried in an encapsulation header on N3 and/or N9 (e.g. without any changes to the end-to-end packet header). In an example, the QFI may be applied to PDUs with different types of payload. The QFI may be unique within a PDU session.

(38) In an example, the QoS parameters of a QoS flow may be provided to the (R)AN **105** as a QoS profile over N2 at PDU session establishment, QoS flow establishment, or when NG-RAN is used at every time the user plane is activated. In an example, a default QoS rule may be required for every PDU session. The SMF **160** may allocate the QFI for a QoS flow and may derive QoS parameters from the information provided by the PCF **135**. In an example, the SMF **160** may provide the QFI together with the QoS profile containing the QoS parameters of a QoS flow to the (R)AN **105**.

(39) In an example, 5G QoS flow may be a granularity for QoS forwarding treatment in the 5G system. Traffic mapped to the same 5G QoS flow may receive the same forwarding treatment (e.g. scheduling policy, queue management policy, rate shaping policy, RLC configuration, and/or the like). In an example, providing different QoS forwarding treatment may require separate 5G QoS flows.

(40) In an example, a 5G QoS indicator may be a scalar that may be employed as a reference to a specific QoS forwarding behavior (e.g. packet loss rate, packet delay budget) to be provided to a 5G QoS flow. In an example, the 5G QoS indicator may be implemented in the access network by the 5QI referencing node specific parameters that may control the QoS forwarding treatment (e.g. scheduling weights, admission thresholds, queue management thresholds, link layer protocol configuration, and/or the like).

(41) In an example, 5GC may support edge computing and may enable operator(s) and 3rd party services to be hosted close to the UE's access point of attachment. The 5G core network may select a UPF **110** close to the UE **100** and may execute the traffic steering from the UPF **110** to the local data network via a N6 interface. In an example, the selection and traffic steering may be based on the UE's **100** subscription data, UE **100** location, the information from application function AF **145**, policy, other related traffic rules, and/or the like. In an example, the 5G core network may expose network information and capabilities to an edge computing application function. The functionality support for edge computing may include local routing where the 5G core network may select a UPF **110** to route the user traffic to the local data network, traffic steering where the 5G core network may select the traffic to be routed to the applications in the local data network, session and service continuity to enable UE **100** and application mobility, user plane selection and reselection, e.g. based on input from application function, network capability exposure where 5G core network and application function may provide information to each other via NEf **125**, QoS and charging where PCF **135** may provide rules for QoS control and charging for the traffic routed to the local data network, support of local area data network where 5G core network may provide support to connect to the LADN in a certain area where the applications are deployed, and/or the like.

(42) An example 5G system may be a 3GPP system comprising of 5G access network **105**, 5G core network and a UE **100**, and/or the like. Allowed NSSAI may be an NSSAI provided by a serving PLMN during e.g. a registration procedure, indicating the NSSAI allowed by the network for the

UE **100** in the serving PLMN for the current registration area.

(43) In an example, a PDU connectivity service may provide exchange of PDUs between a UE **100** and a data network. A PDU session may be an association between the UE **100** and the data network, DN **115**, that may provide the PDU connectivity service. The type of association may be IP, Ethernet and/or unstructured.

(44) Establishment of user plane connectivity to a data network via network slice instance(s) may comprise the following: performing a RM procedure to select an AMF **155** that supports the required network slices, and establishing one or more PDU session(s) to the required data network via the network slice instance(s).

(45) In an example, the set of network slices for a UE **100** may be changed at any time while the UE **100** may be registered with the network, and may be initiated by the network, or the UE **100**.

(46) In an example, a periodic registration update may be UE **100** re-registration at expiry of a periodic registration timer. A requested NSSAI may be a NSSAI that the UE **100** may provide to the network.

(47) In an example, a service based interface may represent how a set of services may be provided/exposed by a given NF.

(48) In an example, a service continuity may be an uninterrupted user experience of a service, including the cases where the IP address and/or anchoring point may change. In an example, a session continuity may refer to continuity of a PDU session. For PDU session of IP type session continuity may imply that the IP address is preserved for the lifetime of the PDU session. An uplink classifier may be a UPF **110** functionality that aims at diverting uplink traffic, based on filter rules provided by the SMF **160**, towards data network, DN **115**.

(49) In an example, the 5G system architecture may support data connectivity and services enabling deployments to use techniques such as e.g. network function virtualization and/or software defined networking. The 5G system architecture may leverage service-based interactions between control plane (CP) network functions where identified. In 5G system architecture, separation of the user plane (UP) functions from the control plane functions may be considered. A 5G system may enable a network function to interact with other NF(s) directly if required.

(50) In an example, the 5G system may reduce dependencies between the access network (AN) and the core network (CN). The architecture may comprise a converged access-agnostic core network with a common AN-CN interface which may integrate different 3GPP and non-3GPP access types.

(51) In an example, the 5G system may support a unified authentication framework, stateless NFs, where the compute resource is decoupled from the storage resource, capability exposure, and concurrent access to local and centralized services. To support low latency services and access to local data networks, UP functions may be deployed close to the access network.

(52) In an example, the 5G system may support roaming with home routed traffic and/or local breakout traffic in the visited PLMN. An example 5G architecture may be service-based and the interaction between network functions may be represented in two ways. (1) As service-based representation (depicted in example FIG. 1), where network functions within the control plane, may enable other authorized network functions to access their services. This representation may also include point-to-point reference points where necessary. (2) Reference point representation, showing the interaction between the NF services in the network functions described by point-to-point reference point (e.g. N11) between any two network functions.

(53) In an example, a network slice may comprise the core network control plane and user plane network functions, the 5G Radio Access Network; the N3IWF functions to the non-3GPP Access Network, and/or the like. Network slices may differ for supported features and network function implementation. The operator may deploy multiple network slice instances delivering the same features but for different groups of UEs, e.g. as they deliver a different committed service and/or because they may be dedicated to a customer. The NSSF **120** may store the mapping information between slice instance ID and NF ID (or NF address).

- (54) In an example, a UE **100** may simultaneously be served by one or more network slice instances via a 5G-AN. In an example, the UE **100** may be served by k network slices (e.g. k=8, 16, etc.) at a time. An AMF **155** instance serving the UE **100** logically may belong to a network slice instance serving the UE **100**.
- (55) In an example, a PDU session may belong to one specific network slice instance per PLMN. In an example, different network slice instances may not share a PDU session. Different slices may have slice-specific PDU sessions using the same DNN.
- (56) An S-NSSAI (Single Network Slice Selection Assistance information) may identify a network slice. An S-NSSAI may comprise a slice/service type (SST), which may refer to the expected network slice behavior in terms of features and services; and/or a slice differentiator (SD). A slice differentiator may be optional information that may complement the slice/service type(s) to allow further differentiation for selecting a network slice instance from potentially multiple network slice instances that comply with the indicated slice/service type. In an example, the same network slice instance may be selected employing different S-NSSAIs. The CN part of a network slice instance(s) serving a UE **100** may be selected by CN.
- (57) In an example, subscription data may include the S-NSSAI(s) of the network slices that the UE **100** subscribes to. One or more S-NSSAIs may be marked as default S-NSSAI. In an example, k S-NSSAI may be marked default S-NSSAI (e.g. k=8, 16, etc.). In an example, the UE **100** may subscribe to more than 8 S-NSSAIs.
- (58) In an example, a UE **100** may be configured by the HPLMN with a configured NSSAI per PLMN. Upon successful completion of a UE's registration procedure, the UE **100** may obtain from the AMF **155** an Allowed NSSAI for this PLMN, which may include one or more S-NSSAIs.
- (59) In an example, the Allowed NSSAI may take precedence over the configured NSSAI for a PLMN. The UE **100** may use the S-NSSAIs in the allowed NSSAI corresponding to a network slice for the subsequent network slice selection related procedures in the serving PLMN.
- (60) In an example, the establishment of user plane connectivity to a data network via a network slice instance(s) may comprise: performing a RM procedure to select an AMF **155** that may support the required network slices, establishing one or more PDU sessions to the required data network via the network slice instance(s), and/or the like.
- (61) In an example, when a UE **100** registers with a PLMN, if the UE **100** for the PLMN has a configured NSSAI or an allowed NSSAI, the UE **100** may provide to the network in RRC and NAS layer a requested NSSAI comprising the S-NSSAI(s) corresponding to the slice(s) to which the UE **100** attempts to register, a temporary user ID if one was assigned to the UE, and/or the like. The requested NSSAI may be configured-NSSAI, allowed-NSSAI, and/or the like.
- (62) In an example, when a UE **100** registers with a PLMN, if for the PLMN the UE **100** has no configured NSSAI or allowed NSSAI, the RAN **105** may route NAS signaling from/to the UE **100** to/from a default AMF **155**.
- (63) In an example, the network, based on local policies, subscription changes and/or UE **100** mobility, may change the set of permitted network slice(s) to which the UE **100** is registered. In an example, the network may perform the change during a registration procedure or trigger a notification towards the UE **100** of the change of the supported network slices using an RM procedure (which may trigger a registration procedure). The network may provide the UE **100** with a new allowed NSSAI and tracking area list.
- (64) In an example, during a registration procedure in a PLMN, in case the network decides that the UE **100** may be served by a different AMF **155** based on network slice(s) aspects, the AMF **155** that first received the registration request may redirect the registration request to another AMF **155** via the RAN **105** or via direct signaling between the initial AMF **155** and the target AMF **155**.
- (65) In an example, the network operator may provision the UE **100** with network slice selection policy (NSSP). The NSSP may comprise one or more NSSP rules.
- (66) In an example, if a UE **100** has one or more PDU sessions established corresponding to a

specific S-NSSAI, the UE **100** may route the user data of the application in one of the PDU sessions, unless other conditions in the UE **100** may prohibit the use of the PDU sessions. If the application provides a DNN, then the UE **100** may consider the DNN to determine which PDU session to use. In an example, if the UE **100** does not have a PDU session established with the specific S-NSSAI, the UE **100** may request a new PDU session corresponding to the S-NSSAI and with the DNN that may be provided by the application. In an example, in order for the RAN **105** to select a proper resource for supporting network slicing in the RAN **105**, the RAN **105** may be aware of the network slices used by the UE **100**.

(67) In an example, an AMF **155** may select an SMF **160** in a network slice instance based on S-NSSAI, DNN and/or other information e.g. UE **100** subscription and local operator policies, and/or the like, when the UE **100** triggers the establishment of a PDU session. The selected SMF **160** may establish the PDU session based on S-NSSAI and DNN.

(68) In an example, in order to support network-controlled privacy of slice information for the slices the UE **100** may access, when the UE **100** is aware or configured that privacy considerations may apply to NSSAI, the UE **100** may not include NSSAI in NAS signaling unless the UE **100** has a NAS security context and the UE **100** may not include NSSAI in unprotected RRC signaling.

(69) In an example, for roaming scenarios, the network slice specific network functions in VPLMN and HPLMN may be selected based on the S-NSSAI provided by the UE **100** during PDU connection establishment. If a standardized S-NSSAI is used, selection of slice specific NF instances may be done by one or more PLMN(s) based on the provided S-NSSAI. In an example, the VPLMN may map the S-NSSAI of HPLMN to a S-NSSAI of VPLMN based on roaming agreement (e.g., including mapping to a default S-NSSAI of VPLMN). In an example, the selection of slice specific NF instance in VPLMN may be done based on the S-NSSAI of VPLMN. In an example, the selection of any slice specific NF instance in HPLMN may be based on the S-NSSAI of HPLMN.

(70) As depicted in example FIG. **8** and FIG. **9**, a registration procedure may be performed by the UE **100** to get authorized to receive services, to enable mobility tracking, to enable reachability, and/or the like.

(71) In an example, the UE **100** may send to the (R)AN **105** an AN message **805** (comprising AN parameters, RM-NAS registration request (registration type, SUCI or SUPI or 5G-GUTI, last visited TAI (if available), security parameters, requested NSSAI, mapping of requested NSSAI, UE **100** 5GC capability, PDU session status, PDU session(s) to be re-activated, Follow on request, MICO mode preference, and/or the like), and/or the like). In an example, in case of NG-RAN, the AN parameters may include e.g. SUCI or SUPI or the 5G-GUTI, the Selected PLMN ID and requested NSSAI, and/or the like. In an example, the AN parameters may comprise establishment cause. The establishment cause may provide the reason for requesting the establishment of an RRC connection. In an example, the registration type may indicate if the UE **100** wants to perform an initial registration (i.e. the UE **100** is in RM-DEREGISTERED state), a mobility registration update (e.g., the UE **100** is in RM-REGISTERED state and initiates a registration procedure due to mobility), a periodic registration update (e.g., the UE **100** is in RM-REGISTERED state and may initiate a registration procedure due to the periodic registration update timer expiry) or an emergency registration (e.g., the UE **100** is in limited service state). In an example, if the UE **100** performing an initial registration (i.e., the UE **100** is in RM-DEREGISTERED state) to a PLMN for which the UE **100** does not already have a 5G-GUTI, the UE **100** may include its SUCI or SUPI in the registration request. The SUCI may be included if the home network has provisioned the public key to protect SUPI in the UE. If the UE **100** received a UE **100** configuration update command indicating that the UE **100** needs to re-register and the 5G-GUTI is invalid, the UE **100** may perform an initial registration and may include the SUPI in the registration request message. For an emergency registration, the SUPI may be included if the UE **100** does not have a valid 5G-GUTI available; the PEI may be included when the UE **100** has no SUPI and no valid 5G-GUTI. In

other cases, the 5G-GUTI may be included and it may indicate the last serving AMF **155**. If the UE **100** is already registered via a non-3GPP access in a PLMN different from the new PLMN (e.g., not the registered PLMN or an equivalent PLMN of the registered PLMN) of the 3GPP access, the UE **100** may not provide over the 3GPP access the 5G-GUTI allocated by the AMF **155** during the registration procedure over the non-3GPP access. If the UE **100** is already registered via a 3GPP access in a PLMN (e.g., the registered PLMN), different from the new PLMN (i.e. not the registered PLMN or an equivalent PLMN of the registered PLMN) of the non-3GPP access, the UE **100** may not provide over the non-3GPP access the 5G-GUTI allocated by the AMF **155** during the registration procedure over the 3GPP access. The UE **100** may provide the UE's usage setting based on its configuration. In case of initial registration or mobility registration update, the UE **100** may include the mapping of requested NSSAI, which may be the mapping of one or more S-NSSAI of the requested NSSAI to the S-NSSAIs of the configured NSSAI for the HPLMN, to ensure that the network is able to verify whether the S-NSSAI(s) in the requested NSSAI are permitted based on the subscribed S-NSSAIs. If available, the last visited TAI may be included in order to help the AMF **155** produce registration area for the UE. In an example, the security parameters may be used for authentication and integrity protection. requested NSSAI may indicate the network slice selection assistance information. The PDU session status may indicate the previously established PDU sessions in the UE. When the UE **100** is connected to the two AMF **155** belonging to different PLMN via 3GPP access and non-3GPP access then the PDU session status may indicate the established PDU session of the current PLMN in the UE. The PDU session(s) to be re-activated may be included to indicate the PDU session(s) for which the UE **100** may intend to activate UP connections. A PDU session corresponding to a LADN may not be included in the PDU session(s) to be re-activated when the UE **100** is outside the area of availability of the LADN. The follow on request may be included when the UE **100** may have pending uplink signaling and the UE **100** may not include PDU session(s) to be re-activated, or the registration type may indicate the UE **100** may want to perform an emergency registration.

(72) In an example, if a SUPI is included or the 5G-GUTI does not indicate a valid AMF **155**, the (R)AN **105**, based on (R)AT and requested NSSAI, if available, may select **808** an AMF **155**. If UE **100** is in CM-CONNECTED state, the (R)AN **105** may forward the registration request message to the AMF **155** based on the N2 connection of the UE. If the (R)AN **105** may not select an appropriate AMF **155**, it may forward the registration request to an AMF **155** which has been configured, in (R)AN **105**, to perform AMF **155** selection **808**.

(73) In an example, the (R)AN **105** may send to the new AMF **155** an N2 message **810** (comprising: N2 parameters, RM-NAS registration request (registration type, SUPI or 5G-GUTI, last visited TAI (if available), security parameters, requested NSSAI, mapping of requested NSSAI, UE **100** 5GC capability, PDU session status, PDU session(s) to be re-activated, follow on request, and MICO mode preference), and/or the like). In an example, when NG-RAN is used, the N2 parameters may comprise the selected PLMN ID, location information, cell identity and the RAT type related to the cell in which the UE **100** is camping. In an example, when NG-RAN is used, the N2 parameters may include the establishment cause.

(74) In an example, the new AMF **155** may send to the old AMF **155** a Namf_Communication_UEContextTransfer (complete registration request) **815**. In an example, if the UE's 5G-GUTI was included in the registration request and the serving AMF **155** has changed since last registration procedure, the new AMF **155** may invoke the Namf_Communication_UEContextTransfer service operation **815** on the old AMF **155** including the complete registration request IE, which may be integrity protected, to request the UE's SUPI and MM Context. The old AMF **155** may use the integrity protected complete registration request IE to verify if the context transfer service operation invocation corresponds to the UE **100** requested. In an example, the old AMF **155** may transfer the event subscriptions information by one or more NF consumer, for the UE, to the new AMF **155**. In an example, if the UE **100**

identifies itself with PEI, the SUPI request may be skipped.

(75) In an example, the old AMF **155** may send to new AMF **155** a response **815** to `Namf_Communication_UEContextTransfer` (SUPI, MM context, SMF **160** information, PCF ID). In an example, the old AMF **155** may respond to the new AMF **155** for the `Namf_Communication_UEContextTransfer` invocation by including the UE's SUPI and MM context. In an example, if old AMF **155** holds information about established PDU sessions, the old AMF **155** may include SMF **160** information including S-NSSAI(s), SMF **160** identities and PDU session ID. In an example, if old AMF **155** holds information about active NGAP UE-TNLA bindings to N3IWF, the old AMF **155** may include information about the NGAP UE-TNLA bindings.

(76) In an example, if the SUPI is not provided by the UE **100** nor retrieved from the old AMF **155** the identity request procedure **820** may be initiated by the AMF **155** sending an identity request message to the UE **100** requesting the SUCI.

(77) In an example, the UE **100** may respond with an identity response message **820** including the SUCI. The UE **100** may derive the SUCI by using the provisioned public key of the HPLMN.

(78) In an example, the AMF **155** may decide to initiate UE **100** authentication **825** by invoking an AUSF **150**. The AMF **155** may select an AUSF **150** based on SUPI or SUCI. In an example, if the AMF **155** is configured to support emergency registration for unauthenticated SUPIs and the UE **100** indicated registration type emergency registration the AMF **155** may skip the authentication and security setup or the AMF **155** may accept that the authentication may fail and may continue the registration procedure.

(79) In an example, the authentication **830** may be performed by `Nudm_UEAuthenticate_Get` operation. The AUSF **150** may discover a UDM **140**. In case the AMF **155** provided a SUCI to AUSF **150**, the AUSF **150** may return the SUPI to AMF **155** after the authentication is successful. In an example, if network slicing is used, the AMF **155** may decide if the registration request needs to be rerouted where the initial AMF **155** refers to the AMF **155**. In an example, the AMF **155** may initiate NAS security functions. In an example, upon completion of NAS security function setup, the AMF **155** may initiate NGAP procedure to enable 5G-AN use it for securing procedures with the UE. In an example, the 5G-AN may store the security context and may acknowledge to the AMF **155**. The 5G-AN may use the security context to protect the messages exchanged with the UE.

(80) In an example, new AMF **155** may send to the old AMF **155** `Namf_Communication_RegistrationCompleteNotify` **835**. If the AMF **155** has changed, the new AMF **155** may notify the old AMF **155** that the registration of the UE **100** in the new AMF **155** may be completed by invoking the `Namf_Communication_RegistrationCompleteNotify` service operation. If the authentication/security procedure fails, then the registration may be rejected, and the new AMF **155** may invoke the `Namf_Communication_RegistrationCompleteNotify` service operation with a reject indication reason code towards the old AMF **155**. The old AMF **155** may continue as if the UE **100** context transfer service operation was never received. If one or more of the S-NSSAIs used in the old registration area may not be served in the target registration area, the new AMF **155** may determine which PDU session may not be supported in the new registration area. The new AMF **155** may invoke the `Namf_Communication_RegistrationCompleteNotify` service operation including the rejected PDU session ID and a reject cause (e.g. the S-NSSAI becomes no longer available) towards the old AMF **155**. The new AMF **155** may modify the PDU session status correspondingly. The old AMF **155** may inform the corresponding SMF **160**(s) to locally release the UE's SM context by invoking the `Nsmf_PDUSession_ReleaseSMContext` service operation.

(81) In an example, the new AMF **155** may send to the UE **100** an identity request/response **840** (e.g., PEI). If the PEI was not provided by the UE **100** nor retrieved from the old AMF **155**, the identity request procedure may be initiated by AMF **155** sending an identity request message to the

UE **100** to retrieve the PEI. The PEI may be transferred encrypted unless the UE **100** performs emergency registration and may not be authenticated. For an emergency registration, the UE **100** may have included the PEI in the registration request.

(82) In an example, the new AMF **155** may initiate ME identity check **845** by invoking the N5g-eir_EquipmentIdentityCheck_Get service operation **845**.

(83) In an example, the new AMF **155**, based on the SUPI, may select **905** a UDM **140**. The UDM **140** may select a UDR instance. In an example, the AMF **155** may select a UDM **140**.

(84) In an example, if the AMF **155** has changed since the last registration procedure, or if the UE **100** provides a SUPI which may not refer to a valid context in the AMF **155**, or if the UE **100** registers to the same AMF **155** it has already registered to a non-3GPP access (e.g., the UE **100** is registered over a non-3GPP access and may initiate the registration procedure to add a 3GPP access), the new AMF **155** may register with the UDM **140** using Nudm_UECM_Registration **910** and may subscribe to be notified when the UDM **140** may deregister the AMF **155**. The UDM **140** may store the AMF **155** identity associated to the access type and may not remove the AMF **155** identity associated to the other access type. The UDM **140** may store information provided at registration in UDR, by Nudr_UDM_Update. In an example, the AMF **155** may retrieve the access and mobility subscription data and SMF **160** selection subscription data using Nudm_SDM_Get **915**. The UDM **140** may retrieve this information from UDR by Nudr_UDM_Query (access and mobility subscription data). After a successful response is received, the AMF **155** may subscribe to be notified using Nudm_SDM_Subscribe **920** when the data requested may be modified. The UDM **140** may subscribe to UDR by Nudr_UDM_Subscribe. The GPSI may be provided to the AMF **155** in the subscription data from the UDM **140** if the GPSI is available in the UE **100** subscription data. In an example, the new AMF **155** may provide the access type it serves for the UE **100** to the UDM **140** and the access type may be set to 3GPP access. The UDM **140** may store the associated access type together with the serving AMF **155** in UDR by Nudr_UDM_Update. The new AMF **155** may create an MM context for the UE **100** after getting the mobility subscription data from the UDM **140**. In an example, when the UDM **140** stores the associated access type together with the serving AMF **155**, the UDM **140** may initiate a Nudm_UECM_DeregistrationNotification **921** to the old AMF **155** corresponding to 3GPP access. The old AMF **155** may remove the MM context of the UE. If the serving NF removal reason indicated by the UDM **140** is initial registration, then the old AMF **155** may invoke the Namf_EventExposure_Notify service operation towards all the associated SMF **160**s of the UE **100** to notify that the UE **100** is deregistered from old AMF **155**. The SMF **160** may release the PDU session(s) on getting this notification. In an example, the old AMF **155** may unsubscribe with the UDM **140** for subscription data using Nudm_SDM_unsubscribe **922**.

(85) In an example, if the AMF **155** decides to initiate PCF **135** communication, e.g. the AMF **155** has not yet obtained access and mobility policy for the UE **100** or if the access and mobility policy in the AMF **155** are no longer valid, the AMF **155** may select **925** a PCF **135**. If the new AMF **155** receives a PCF ID from the old AMF **155** and successfully contacts the PCF **135** identified by the PCF ID, the AMF **155** may select the (V-)PCF identified by the PCF ID. If the PCF **135** identified by the PCF ID may not be used (e.g. no response from the PCF **135**) or if there is no PCF ID received from the old AMF **155**, the AMF **155** may select **925** a PCF **135**.

(86) In an example, the new AMF **155** may perform a policy association establishment **930** during registration procedure. If the new AMF **155** contacts the PCF **135** identified by the (V-)PCF ID received during inter-AMF **155** mobility, the new AMF **155** may include the PCF-ID in the Npcf_AMPolicyControl Get operation. If the AMF **155** notifies the mobility restrictions (e.g. UE **100** location) to the PCF **135** for adjustment, or if the PCF **135** updates the mobility restrictions itself due to some conditions (e.g. application in use, time and date), the PCF **135** may provide the updated mobility restrictions to the AMF **155**.

(87) In an example, the PCF **135** may invoke Namf_EventExposure_Subscribe service operation

935 for UE **100** event subscription.

(88) In an example, the AMF **155** may send to the SMF **160** an Nsmf_PDUSession_UpdateSMContext **936**. In an example, the AMF **155** may invoke the Nsmf_PDUSession_UpdateSMContext if the PDU session(s) to be re-activated is included in the registration request. The AMF **155** may send Nsmf_PDUSession_UpdateSMContext request to SMF **160**(s) associated with the PDU session(s) to activate user plane connections of the PDU session(s). The SMF **160** may decide to trigger e.g. the intermediate UPF **110** insertion, removal or change of PSA. In the case that the intermediate UPF **110** insertion, removal, or relocation is performed for the PDU session(s) not included in PDU session(s) to be re-activated, the procedure may be performed without N11 and N2 interactions to update the N3 user plane between (R)AN **105** and 5GC. The AMF **155** may invoke the Nsmf_PDUSession_ReleaseSMContext service operation towards the SMF **160** if any PDU session status indicates that it is released at the UE **100**. The AMF **155** may invoke the Nsmf_PDUSession_ReleaseSMContext service operation towards the SMF **160** in order to release any network resources related to the PDU session.

(89) In an example, the new AMF **155** may send to a N3IWF an N2 AMF **155** mobility request **940**. If the AMF **155** has changed, the new AMF **155** may create an NGAP UE **100** association towards the N3IWF to which the UE **100** is connected. In an example, the N3IWF may respond to the new AMF **155** with an N2 AMF **155** mobility response **940**.

(90) In an example, the new AMF **155** may send to the UE **100** a registration accept **955** (comprising: 5G-GUTI, registration area, mobility restrictions, PDU session status, allowed NSSAI, [mapping of allowed NSSAI], periodic registration update timer, LADN information and accepted MICO mode, IMS voice over PS session supported indication, emergency service support indicator, and/or the like). In an example, the AMF **155** may send the registration accept message to the UE **100** indicating that the registration request has been accepted. 5G-GUTI may be included if the AMF **155** allocates a new 5G-GUTI. If the AMF **155** allocates a new registration area, it may send the registration area to the UE **100** via registration accept message **955**. If there is no registration area included in the registration accept message, the UE **100** may consider the old registration area as valid. In an example, mobility restrictions may be included in case mobility restrictions may apply for the UE **100** and registration type may not be emergency registration. The AMF **155** may indicate the established PDU sessions to the UE **100** in the PDU session status. The UE **100** may remove locally any internal resources related to PDU sessions that are not marked as established in the received PDU session status. In an example, when the UE **100** is connected to the two AMF **155** belonging to different PLMN via 3GPP access and non-3GPP access then the UE **100** may remove locally any internal resources related to the PDU session of the current PLMN that are not marked as established in received PDU session status. If the PDU session status information was in the registration request, the AMF **155** may indicate the PDU session status to the UE. The mapping of allowed NSSAI may be the mapping of one or more S-NSSAI of the allowed NSSAI to the S-NSSAIs of the configured NSSAI for the HPLMN. The AMF **155** may include in the registration accept message **955** the LADN information for LADNs that are available within the registration area determined by the AMF **155** for the UE. If the UE **100** included MICO mode in the request, then AMF **155** may respond whether MICO mode may be used. The AMF **155** may set the IMS voice over PS session supported Indication. In an example, in order to set the IMS voice over PS session supported indication, the AMF **155** may perform a UE/RAN radio information and compatibility request procedure to check the compatibility of the UE **100** and RAN radio capabilities related to IMS voice over PS. In an example, the emergency service support indicator may inform the UE **100** that emergency services are supported, e.g., the UE **100** may request PDU session for emergency services. In an example, the handover restriction list and UE-AMBR may be provided to NG-RAN by the AMF **155**.

(91) In an example, the UE **100** may send to the new AMF **155** a registration complete **960** message. In an example, the UE **100** may send the registration complete message **960** to the AMF

155 to acknowledge that a new 5G-GUTI may be assigned. In an example, when information about the PDU session(s) to be re-activated is not included in the registration request, the AMF **155** may release the signaling connection with the UE **100**. In an example, when the follow-on request is included in the registration request, the AMF **155** may not release the signaling connection after the completion of the registration procedure. In an example, if the AMF **155** is aware that some signaling is pending in the AMF **155** or between the UE **100** and the 5GC, the AMF **155** may not release the signaling connection after the completion of the registration procedure.

(92) As depicted in example FIG. **10** and FIG. **11**, a service request procedure e.g., a UE **100** triggered service request procedure may be used by a UE **100** in CM-IDLE state to request the establishment of a secure connection to an AMF **155**. FIG. **11** is continuation of FIG. **10** depicting the service request procedure. The service request procedure may be used to activate a user plane connection for an established PDU session. The service request procedure may be triggered by the UE **100** or the 5GC, and may be used when the UE **100** is in CM-IDLE and/or in CM-CONNECTED and may allow selectively to activate user plane connections for some of the established PDU sessions.

(93) In an example, a UE **100** in CM IDLE state may initiate the service request procedure to send uplink signaling messages, user data, and/or the like, as a response to a network paging request, and/or the like. In an example, after receiving the service request message, the AMF **155** may perform authentication. In an example, after the establishment of signaling connection to the AMF **155**, the UE **100** or network may send signaling messages, e.g. PDU session establishment from the UE **100** to a SMF **160**, via the AMF **155**.

(94) In an example, for any service request, the AMF **155** may respond with a service accept message to synchronize PDU session status between the UE **100** and network. The AMF **155** may respond with a service reject message to the UE **100**, if the service request may not be accepted by the network. The service reject message may include an indication or cause code requesting the UE **100** to perform a registration update procedure. In an example, for service request due to user data, network may take further actions if user plane connection activation may not be successful. In an example FIG. **10** and FIG. **11**, more than one UPF, e.g., old UPF **110-2** and PDU session Anchor PSA UPF **110-3** may be involved.

(95) In an example, the UE **100** may send to a (R)AN **105** an AN message comprising AN parameters, mobility management, MM NAS service request **1005** (e.g., list of PDU sessions to be activated, list of allowed PDU sessions, security parameters, PDU session status, and/or the like), and/or the like. In an example, the UE **100** may provide the list of PDU sessions to be activated when the UE **100** may re-activate the PDU session(s). The list of allowed PDU sessions may be provided by the UE **100** when the service request may be a response of a paging or a NAS notification, and may identify the PDU sessions that may be transferred or associated to the access on which the service request may be sent. In an example, for the case of NG-RAN, the AN parameters may include selected PLMN ID, and an establishment cause. The establishment cause may provide the reason for requesting the establishment of an RRC connection. The UE **100** may send NAS service request message towards the AMF **155** encapsulated in an RRC message to the RAN **105**.

(96) In an example, if the service request may be triggered for user data, the UE **100** may identify, using the list of PDU sessions to be activated, the PDU session(s) for which the UP connections are to be activated in the NAS service request message. If the service request may be triggered for signaling, the UE **100** may not identify any PDU session(s). If this procedure may be triggered for paging response, and/or the UE **100** may have at the same time user data to be transferred, the UE **100** may identify the PDU session(s) whose UP connections may be activated in MM NAS service request message, by the list of PDU sessions to be activated.

(97) In an example, if the service request over 3GPP access may be triggered in response to a paging indicating non-3GPP access, the NAS service request message may identify in the list of

allowed PDU sessions the list of PDU sessions associated with the non-3GPP access that may be re-activated over 3GPP. In an example, the PDU session status may indicate the PDU sessions available in the UE **100**. In an example, the UE **100** may not trigger the service request procedure for a PDU session corresponding to a LADN when the UE **100** may be outside the area of availability of the LADN. The UE **100** may not identify such PDU session(s) in the list of PDU sessions to be activated, if the service request may be triggered for other reasons.

(98) In an example, the (R)AN **105** may send to AMF **155** an N2 Message **1010** (e.g., a service request) comprising N2 parameters, MM NAS service request, and/or the like. The AMF **155** may reject the N2 message if it may not be able to handle the service request. In an example, if NG-RAN may be used, the N2 parameters may include the 5G-GUTI, selected PLMN ID, location information, RAT type, establishment cause, and/or the like. In an example, the 5G-GUTI may be obtained in RRC procedure and the (R)AN **105** may select the AMF **155** according to the 5G-GUTI. In an example, the location information and RAT type may relate to the cell in which the UE **100** may be camping. In an example, based on the PDU session status, the AMF **155** may initiate PDU session release procedure in the network for the PDU sessions whose PDU session ID(s) may be indicated by the UE **100** as not available.

(99) In an example, if the service request was not sent integrity protected or integrity protection verification failed, the AMF **155** may initiate a NAS authentication/security procedure **1015**.

(100) In an example, if the UE **100** triggers the service request to establish a signaling connection, upon successful establishment of the signaling connection, the UE **100** and the network may exchange NAS signaling.

(101) In an example the AMF **155** may send to the SMF **160** a PDU session update context request **1020** e.g., Nsmf_PDUSession_UpdateSMContext request comprising PDU session ID(s), Cause(s), UE **100** location information, access type, and/or the like.

(102) In an example, the Nsmf_PDUSession_UpdateSMContext request may be invoked by the AMF **155** if the UE **100** may identify PDU session(s) to be activated in the NAS service request message. In an example, the Nsmf_PDUSession_UpdateSMContext request may be triggered by the SMF **160** wherein the PDU session(s) identified by the UE **100** may correlate to other PDU session ID(s) than the one triggering the procedure. In an example, the Nsmf_PDUSession_UpdateSMContext request may be triggered by the SMF **160** wherein the current UE **100** location may be outside the area of validity for the N2 information provided by the SMF **160** during a network triggered service request procedure. The AMF **155** may not send the N2 information provided by the SMF **160** during the network triggered service request procedure.

(103) In an example, the AMF **155** may determine the PDU session(s) to be activated and may send an Nsmf_PDUSession_UpdateSMContext request to SMF **160**(s) associated with the PDU session(s) with cause set to indicate establishment of user plane resources for the PDU session(s).

(104) In an example, if the procedure may be triggered in response to paging indicating non-3GPP access, and the list of allowed PDU sessions provided by the UE **100** may not include the PDU session for which the UE **100** was paged, the AMF **155** may notify the SMF **160** that the user plane for the PDU session may not be re-activated. The service request procedure may succeed without re-activating the user plane of any PDU sessions, and the AMF **155** may notify the UE **100**.

(105) In an example, if the PDU session ID may correspond to a LADN and the SMF **160** may determine that the UE **100** may be outside the area of availability of the LADN based on the UE **100** location reporting from the AMF **155**, the SMF **160** may decide to (based on local policies) keep the PDU session, may reject the activation of user plane connection for the PDU session and may inform the AMF **155**. In an example, if the procedure may be triggered by a network triggered service request, the SMF **160** may notify the UPF **110** that originated the data notification to discard downlink data for the PDU sessions and/or to not provide further data notification messages. The SMF **160** may respond to the AMF **155** with an appropriate reject cause and the user plane activation of PDU session may be stopped.

(106) In an example, if the PDU session ID may correspond to a LADN and the SMF **160** may determine that the UE **100** may be outside the area of availability of the LADN based on the UE **100** location reporting from the AMF **155**, the SMF **160** may decide to (based on local policies) release the PDU session. The SMF **160** may locally release the PDU session and may inform the AMF **155** that the PDU session may be released. The SMF **160** may respond to the AMF **155** with an appropriate reject cause and the user plane Activation of PDU session may be stopped.

(107) In an example, if the UP activation of the PDU session may be accepted by the SMF **160**, based on the location info received from the AMF **155**, the SMF **160** may check the UPF **110** Selection **1025** Criteria (e.g., slice isolation requirements, slice coexistence requirements, UPF's **110** dynamic load, UPF's **110** relative static capacity among UPFs supporting the same DNN, UPF **110** location available at the SMF **160**, UE **100** location information, Capability of the UPF **110** and the functionality required for the particular UE **100** session. In an example, an appropriate UPF **110** may be selected by matching the functionality and features required for a UE **100**, DNN, PDU session type (i.e. IPv4, IPv6, ethernet type or unstructured type) and if applicable, the static IP address/prefix, SSC mode selected for the PDU session, UE **100** subscription profile in UDM **140**, DNAI as included in the PCC rules, local operator policies, S-NSSAI, access technology being used by the UE **100**, UPF **110** logical topology, and/or the like), and may determine to perform one or more of the following: continue using the current UPF(s); may select a new intermediate UPF **110** (or add/remove an intermediate UPF **110**), if the UE **100** has moved out of the service area of the UPF **110** that was previously connecting to the (R)AN **105**, while maintaining the UPF(s) acting as PDU session anchor; may trigger re-establishment of the PDU session to perform relocation/reallocation of the UPF **110** acting as PDU session anchor, e.g. the UE **100** has moved out of the service area of the anchor UPF **110** which is connecting to RAN **105**.

(108) In an example, the SMF **160** may send to the UPF **110** (e.g., new intermediate UPF **110**) an N4 session establishment request **1030**. In an example, if the SMF **160** may select a new UPF **110** to act as intermediate UPF **110-2** for the PDU session, or if the SMF **160** may select to insert an intermediate UPF **110** for a PDU session which may not have an intermediate UPF **110-2**, an N4 session establishment request **1030** message may be sent to the new UPF **110**, providing packet detection, data forwarding, enforcement and reporting rules to be installed on the new intermediate UPF. The PDU session anchor addressing information (on N9) for this PDU session may be provided to the intermediate UPF **110-2**.

(109) In an example, if a new UPF **110** is selected by the SMF **160** to replace the old (intermediate) UPF **110-2**, the SMF **160** may include a data forwarding indication. The data forwarding indication may indicate to the UPF **110** that a second tunnel endpoint may be reserved for buffered DL data from the old I-UPF.

(110) In an example, the new UPF **110** (intermediate) may send to SMF **160** an N4 session establishment response message **1030**. In case the UPF **110** may allocate CN tunnel info, the UPF **110** may provide DL CN tunnel info for the UPF **110** acting as PDU session anchor and UL CN tunnel info (e.g., CN N3 tunnel info) to the SMF **160**. If the data forwarding indication may be received, the new (intermediate) UPF **110** acting as N3 terminating point may send DL CN tunnel info for the old (intermediate) UPF **110-2** to the SMF **160**. The SMF **160** may start a timer, to release the resource in the old intermediate UPF **110-2**.

(111) In an example, if the SMF **160** may selects a new intermediate UPF **110** for the PDU session or may remove the old I-UPF **110-2**, the SMF **160** may send N4 session modification request message **1035** to PDU session anchor, PSA UPF **110-3**, providing the data forwarding indication and DL tunnel information from new intermediate UPF **110**.

(112) In an example, if the new intermediate UPF **110** may be added for the PDU session, the (PSA) UPF **110-3** may begin to send the DL data to the new I-UPF **110** as indicated in the DL tunnel information.

(113) In an example, if the service request may be triggered by the network, and the SMF **160** may

remove the old I-UPF **110-2** and may not replace the old I-UPF **110-2** with the new I-UPF **110**, the SMF **160** may include the data forwarding indication in the request. The data forwarding indication may indicate to the (PSA) UPF **110-3** that a second tunnel endpoint may be reserved for buffered DL data from the old I-UPF **110-2**. In this case, the PSA UPF **110-3** may begin to buffer the DL data it may receive at the same time from the N6 interface.

(114) In an example, the PSA UPF **110-3** (PSA) may send to the SMF **160** an N4 session modification response **1035**. In an example, if the data forwarding indication may be received, the PSA UPF **110-3** may become as N3 terminating point and may send CN DL tunnel info for the old (intermediate) UPF **110-2** to the SMF **160**. The SMF **160** may start a timer, to release the resource in old intermediate UPF **110-2** if there is one.

(115) In an example, the SMF **160** may send to the old UPF **110-2** an N4 session modification request **1045** (e.g., may comprise new UPF **110** address, new UPF **110** DL tunnel ID, and/or the like). In an example, if the service request may be triggered by the network, and/or the SMF **160** may remove the old (intermediate) UPF **110-2**, the SMF **160** may send the N4 session modification request message to the old (intermediate) UPF **110-2**, and may provide the DL tunnel information for the buffered DL data. If the SMF **160** may allocate new I-UPF **110**, the DL tunnel information is from the new (intermediate) UPF **110** may act as N3 terminating point. If the SMF **160** may not allocate a new I-UPF **110**, the DL tunnel information may be from the new UPF **110** (PSA) **110-3** acting as N3 terminating point. The SMF **160** may start a timer to monitor the forwarding tunnel. In an example, the old (intermediate) UPF **110-2** may send N4 session modification response message to the SMF **160**.

(116) In an example, if the I-UPF **110-2** may be relocated and forwarding tunnel was established to the new I-UPF **110**, the old (intermediate) UPF **110-2** may forward its buffered data to the new (intermediate) UPF **110** acting as N3 terminating point. In an example, if the old I-UPF **110-2** may be removed and the new I-UPF **110** may not be assigned for the PDU session and forwarding tunnel may be established to the UPF **110** (PSA) **110-3**, the old (intermediate) UPF **110-2** may forward its buffered data to the UPF **110** (PSA) **110-3** acting as N3 terminating point.

(117) In an example, the SMF **160** may send to the AMF **155** an N11 message **1060** e.g., a Nsmf_PDUSession_UpdateSMContext response (comprising: N1 SM container (PDU session ID, PDU session re-establishment indication), N2 SM information (PDU session ID, QoS profile, CN N3 tunnel info, S-NSSAI), Cause), upon reception of the Nsmf_PDUSession_UpdateSMContext request with a cause including e.g., establishment of user plane resources. The SMF **160** may determine whether UPF **110** reallocation may be performed, based on the UE **100** location information, UPF **110** service area and operator policies. In an example, for a PDU session that the SMF **160** may determine to be served by the current UPF **110**, e.g., PDU session anchor or intermediate UPF, the SMF **160** may generate N2 SM information and may send an Nsmf_PDUSession_UpdateSMContext response **1060** to the AMF **155** to establish the user plane(s). The N2 SM information may contain information that the AMF **155** may provide to the RAN **105**. In an example, for a PDU session that the SMF **160** may determine as requiring a UPF **110** relocation for PDU session anchor UPF, the SMF **160** may reject the activation of UP of the PDU session by sending Nsmf_PDUSession_UpdateSMContext response that may contain N1 SM container to the UE **100** via the AMF **155**. The N1 SM container may include the corresponding PDU session ID and PDU session re-establishment indication.

(118) Upon reception of the Namf_EventExposure_Notify from the AMF **155** to the SMF **160**, with an indication that the UE **100** is reachable, if the SMF **160** may have pending DL data, the SMF **160** may invoke the Namf_Communication_N1N2MessageTransfer service operation to the AMF **155** to establish the user plane(s) for the PDU sessions. In an example, the SMF **160** may resume sending DL data notifications to the AMF **155** in case of DL data.

(119) In an example, the SMF **160** may send a message to the AMF **155** to reject the activation of UP of the PDU session by including a cause in the Nsmf_PDUSession_UpdateSMContext response

if the PDU session may correspond to a LADN and the UE **100** may be outside the area of availability of the LADN, or if the AMF **155** may notify the SMF **160** that the UE **100** may be reachable for regulatory prioritized service, and the PDU session to be activated may not for a regulatory prioritized service; or if the SMF **160** may decide to perform PSA UPF **110-3** relocation for the requested PDU session.

(120) In an example, the AMF **155** may send to the (R)AN **105** an N2 request message **1065** (e.g., N2 SM information received from SMF **160**, security context, AMF **155** signaling connection ID, handover restriction list, MM NAS service accept, list of recommended cells/TAs/NG-RAN node identifiers). In an example, the RAN **105** may store the security context, AMF **155** signaling connection Id, QoS information for the QoS flows of the PDU sessions that may be activated and N3 tunnel IDs in the UE **100** RAN **105** context. In an example, the MM NAS service accept may include PDU session status in the AMF **155**. If the activation of UP of a PDU session may be rejected by the SMF **160**, the MM NAS service accept may include the PDU session ID and the reason why the user plane resources may not be activated (e.g. LADN not available). Local PDU session release during the session request procedure may be indicated to the UE **100** via the session Status.

(121) In an example, if there are multiple PDU sessions that may involve multiple SMF **160**s, the AMF **155** may not wait for responses from all SMF **160**s before it may send N2 SM information to the UE **100**. The AMF **155** may wait for all responses from the SMF **160**s before it may send MM NAS service accept message to the UE **100**.

(122) In an example, the AMF **155** may include at least one N2 SM information from the SMF **160** if the procedure may be triggered for PDU session user plane activation. AMF **155** may send additional N2 SM information from SMF **160**s in separate N2 message(s) (e.g. N2 tunnel setup request), if there is any. Alternatively, if multiple SMF **160**s may be involved, the AMF **155** may send one N2 request message to (R)AN **105** after all the Nsmf_PDUSession_UpdateSMContext response service operations from all the SMF **160**s associated with the UE **100** may be received. In such case, the N2 request message may include the N2 SM information received in one or more of the Nsmf_PDUSession_UpdateSMContext response and PDU session ID to enable AMF **155** to associate responses to relevant SMF **160**.

(123) In an example, if the RAN **105** (e.g., NG RAN) node may provide the list of recommended cells/TAs/NG-RAN node identifiers during the AN release procedure, the AMF **155** may include the information from the list in the N2 request. The RAN **105** may use this information to allocate the RAN **105** notification area when the RAN **105** may decide to enable RRC inactive state for the UE **100**.

(124) If the AMF **155** may receive an indication, from the SMF **160** during a PDU session establishment procedure that the UE **100** may be using a PDU session related to latency sensitive services, for any of the PDU sessions established for the UE **100** and the AMF **155** has received an indication from the UE **100** that may support the CM-CONNECTED with RRC inactive state, then the AMF **155** may include the UE's RRC inactive assistance information. In an example, the AMF **155** based on network configuration, may include the UE's RRC inactive assistance information.

(125) In an example, the (R)AN **105** may send to the UE **100** a message to perform RRC connection reconfiguration **1070** with the UE **100** depending on the QoS information for all the QoS flows of the PDU sessions whose UP connections may be activated and data radio bearers. In an example, the user plane security may be established.

(126) In an example, if the N2 request may include a MM NAS service accept message, the RAN **105** may forward the MM NAS service accept to the UE **100**. The UE **100** may locally delete context of PDU sessions that may not be available in 5GC.

(127) In an example, if the N1 SM information may be transmitted to the UE **100** and may indicate that some PDU session(s) may be re-established, the UE **100** may initiate PDU session re-establishment for the PDU session(s) that may be re-established after the service request procedure

may be complete.

(128) In an example, after the user plane radio resources may be setup, the uplink data from the UE **100** may be forwarded to the RAN **105**. The RAN **105** (e.g., NG-RAN) may send the uplink data to the UPF **110** address and tunnel ID provided.

(129) In an example, the (R)AN **105** may send to the AMF **155** an N2 request Ack **1105** (e.g., N2 SM information (comprising: AN tunnel info, list of accepted QoS flows for the PDU sessions whose UP connections are activated, list of rejected QoS flows for the PDU sessions whose UP connections are activated)). In an example, the N2 request message may include N2 SM information(s), e.g. AN tunnel info. RAN **105** may respond N2 SM information with separate N2 message (e.g. N2 tunnel setup response). In an example, if multiple N2 SM information are included in the N2 request message, the N2 request Ack may include multiple N2 SM information and information to enable the AMF **155** to associate the responses to relevant SMF **160**.

(130) In an example, the AMF **155** may send to the SMF **160** a Nsmf_PDUSession_UpdateSMContext request **1110** (N2 SM information (AN tunnel info), RAT type) per PDU session. If the AMF **155** may receive N2 SM information (one or multiple) from the RAN **105**, then the AMF **155** may forward the N2 SM information to the relevant SMF **160**. If the UE **100** time zone may change compared to the last reported UE **100** Time Zone then the AMF **155** may include the UE **100** time zone IE in the Nsmf_PDUSession_UpdateSMContext request message.

(131) In an example, if dynamic PCC is deployed, the SMF **160** may initiate notification about new location information to the PCF **135** (if subscribed) by invoking an event exposure notification operation (e.g., a Nsmf_EventExposure_Notify service operation). The PCF **135** may provide updated policies by invoking a policy control update notification message **1115** (e.g., a Npcf_SMPolicyControl_UpdateNotify operation).

(132) In an example, if the SMF **160** may select a new UPF **110** to act as intermediate UPF **110** for the PDU session, the SMF **160** may initiate an N4 session modification procedure **1120** to the new I-UPF **110** and may provide AN tunnel info. The downlink data from the new I-UPF **110** may be forwarded to RAN **105** and UE **100**. In an example, the UPF **110** may send to the SMF **160**, an N4 session modification response **1120**. In an example, the SMF **160** may send to the AMF **155**, an Nsmf_PDUSession_UpdateSMContext response **1140**.

(133) In an example, if forwarding tunnel may be established to the new I-UPF **110** and if the timer SMF **160** set for forwarding tunnel may be expired, the SMF **160** may send N4 session modification request **1145** to new (intermediate) UPF **110** acting as N3 terminating point to release the forwarding tunnel. In an example, the new (intermediate) UPF **110** may send to the SMF **160** an N4 session modification response **1145**. In an example, the SMF **160** may send to the PSA UPF **110-3** an N4 session modification request **1150**, or N4 session release request. In an example, if the SMF **160** may continue using the old UPF **110-2**, the SMF **160** may send an N4 session modification request **1155**, providing AN tunnel info. In an example, if the SMF **160** may select a new UPF **110** to act as intermediate UPF **110**, and the old UPF **110-2** may not be PSA UPF **110-3**, the SMF **160** may initiate resource release, after timer expires, by sending an N4 session release request (release cause) to the old intermediate UPF **110-2**.

(134) In an example, the old intermediate UPF **110-2** may send to the SMF **160** an N4 session modification response or N4 session release response **1155**. The old UPF **110-2** may acknowledge with the N4 session modification response or N4 session release response message to confirm the modification or release of resources. The AMF **155** may invoke the Namf_EventExposure_Notify service operation to notify the mobility related events, after this procedure may complete, towards the NFs that may have subscribed for the events. In an example, the AMF **155** may invoke the Namf_EventExposure_Notify towards the SMF **160** if the SMF **160** had subscribed for UE **100** moving into or out of area of interest and if the UE's current location may indicate that it may be moving into or moving outside of the area of interest subscribed, or if the SMF **160** had subscribed

for LADN DNN and if the UE **100** may be moving into or outside of an area where the LADN is available, or if the UE **100** may be in MICO mode and the AMF **155** had notified an SMF **160** of the UE **100** being unreachable and that SMF **160** may not send DL data notifications to the AMF **155**, and the AMF **155** may inform the SMF **160** that the UE **100** is reachable, or if the SMF **160** had subscribed for UE **100** reachability status, then the AMF **155** may notify the UE **100** reachability.

(135) An example PDU session establishment procedure depicted in FIG. **12** and FIG. **13**. In an example embodiment, when the PDU session establishment procedure may be employed, the UE **100** may send to the AMF **155** a NAS Message **1205** (or a SM NAS message) comprising NSSAI, S-NSSAI (e.g., requested S-NSSAI, allowed S-NSSAI, subscribed S-NSSAI, and/or the like), DNN, PDU session ID, request type, old PDU session ID, N1 SM container (PDU session establishment request), and/or the like. In an example, the UE **100**, in order to establish a new PDU session, may generate a new PDU session ID. In an example, when emergency service may be required and an emergency PDU session may not already be established, the UE **100** may initiate the UE **100** requested PDU session establishment procedure with a request type indicating emergency request. In an example, the UE **100** may initiate the UE **100** requested PDU session establishment procedure by the transmission of the NAS message containing a PDU session establishment request within the N1 SM container. The PDU session establishment request may include a PDU type, SSC mode, protocol configuration options, and/or the like. In an example, the request type may indicate initial request if the PDU session establishment is a request to establish the new PDU session and may indicate existing PDU session if the request refers to an existing PDU session between 3GPP access and non-3GPP access or to an existing PDN connection in EPC. In an example, the request type may indicate emergency request if the PDU session establishment may be a request to establish a PDU session for emergency services. The request type may indicate existing emergency PDU session if the request refers to an existing PDU session for emergency services between 3GPP access and non-3GPP access. In an example, the NAS message sent by the UE **100** may be encapsulated by the AN in a N2 message towards the AMF **155** that may include user location information and access technology type information. In an example, the PDU session establishment request message may contain SM PDU DN request container containing information for the PDU session authorization by the external DN. In an example, if the procedure may be triggered for SSC mode **3** operation, the UE **100** may include the old PDU session ID which may indicate the PDU session ID of the on-going PDU session to be released, in the NAS message. The old PDU session ID may be an optional parameter which may be included in this case. In an example, the AMF **155** may receive from the AN the NAS message (e.g., NAS SM message) together with user location information (e.g. cell ID in case of the RAN **105**). In an example, the UE **100** may not trigger a PDU session establishment for a PDU session corresponding to a LADN when the UE **100** is outside the area of availability of the LADN.

(136) In an example, the AMF **155** may determine that the NAS message or the SM NAS message may correspond to the request for the new PDU session based on that request type indicates initial request and that the PDU session ID may not be used for any existing PDU session(s) of the UE **100**. If the NAS message does not contain an S-NSSAI, the AMF **155** may determine a default S-NSSAI for the requested PDU session either according to the UE **100** subscription, if it may contain only one default S-NSSAI, or based on operator policy. In an example, the AMF **155** may perform SMF **160** selection **1210** and select an SMF **160**. If the request type may indicate initial request or the request may be due to handover from EPS, the AMF **155** may store an association of the S-NSSAI, the PDU session ID and a SMF **160** ID. In an example, if the request type is initial request and if the old PDU session ID indicating the existing PDU session may be contained in the message, the AMF **155** may select the SMF **160** and may store an association of the new PDU session ID and the selected SMF **160** ID.

(137) In an example, the AMF **155** may send to the SMF **160**, an N11 message **1215**, e.g.,

Nsmf_PDUSession_CreateSMContext request (comprising: SUPI or PEI, DNN, S-NSSAI, PDU session ID, AMF **155** ID, request type, N1 SM container (PDU session establishment request), user location information, access type, PEI, GPSI), or Nsmf_PDUSession_UpdateSMContext request (SUPI, DNN, S-NSSAI, PDU session ID, AMF **155** ID, request type, N1 SM container (PDU session establishment request), user location information, access type, RAT type, PEI). In an example, if the AMF **155** may not have an association with the SMF **160** for the PDU session ID provided by the UE **100** (e.g. when request type indicates initial request), the AMF **155** may invoke the Nsmf_PDUSession_CreateSMContext request, but if the AMF **155** already has an association with an SMF **160** for the PDU session ID provided by the UE **100** (e.g. when request type indicates existing PDU session), the AMF **155** may invoke the Nsmf_PDUSession_UpdateSMContext request. In an example, the AMF **155** ID may be the UE's GUAMI which uniquely identifies the AMF **155** serving the UE **100**. The AMF **155** may forward the PDU session ID together with the N1 SM container containing the PDU session establishment request received from the UE **100**. The AMF **155** may provide the PEI instead of the SUPI when the UE **100** has registered for emergency services without providing the SUPI. In case the UE **100** has registered for emergency services but has not been authenticated, the AMF **155** may indicate that the SUPI has not been authenticated.

(138) In an example, if the request type may indicate neither emergency request nor existing emergency PDU session and, if the SMF **160** has not yet registered and subscription data may not be available, the SMF **160** may register with the UDM **140**, and may retrieve subscription data **1225** and subscribes to be notified when subscription data may be modified. In an example, if the request type may indicate existing PDU session or existing emergency PDU session, the SMF **160** may determine that the request may be due to handover between 3GPP access and non-3GPP access or due to handover from EPS. The SMF **160** may identify the existing PDU session based on the PDU session ID. The SMF **160** may not create a new SM context but instead may update the existing SM context and may provide the representation of the updated SM context to the AMF **155** in the response. if the request type may be initial request and if the old PDU session ID may be included in Nsmf_PDUSession_CreateSMContext request, the SMF **160** may identify the existing PDU session to be released based on the old PDU session ID.

(139) In an example, the SMF **160** may send to the AMF **155**, the N11 message response **1220**, e.g., either a PDU session create/update response, Nsmf_PDUSession_CreateSMContext response **1220** (cause, SM context ID or N1 SM container (PDU session reject(cause))) or an Nsmf_PDUSession_UpdateSMContext response.

(140) In an example, if the SMF **160** may perform secondary authorization/authentication **1230** during the establishment of the PDU session by a DN-AAA server, the SMF **160** may select a UPF **110** and may trigger a PDU session establishment authentication/authorization.

(141) In an example, if the request type may indicate initial request, the SMF **160** may select an SSC mode for the PDU session. The SMF **160** may select one or more UPFs as needed. In case of PDU type IPv4 or IPv6, the SMF **160** may allocate an IP address/prefix for the PDU session. In case of PDU type IPv6, the SMF **160** may allocate an interface identifier to the UE **100** for the UE **100** to build its link-local address. For Unstructured PDU type the SMF **160** may allocate an IPv6 prefix for the PDU session and N6 point-to-point tunneling (based on UDP/IPv6).

(142) In an example, if dynamic PCC is deployed, the may SMF **160** performs PCF **135** selection **1235**. If the request type indicates existing PDU session or existing emergency PDU session, the SMF **160** may use the PCF **135** already selected for the PDU session. If dynamic PCC is not deployed, the SMF **160** may apply local policy.

(143) In an example, the SMF **160** may perform a session management policy establishment procedure **1240** to establish a PDU session with the PCF **135** and may get the default PCC Rules for the PDU session. The GPSI may be included if available at the SMF **160**. If the request type in **1215** indicates existing PDU session, the SMF **160** may notify an event previously subscribed by the PCF **135** by a session management policy modification procedure and the PCF **135** may update

policy information in the SMF **160**. The PCF **135** may provide authorized session-AMBR and the authorized 5QI and ARP to SMF **160**. The PCF **135** may subscribe to the IP allocation/release event in the SMF **160** (and may subscribe other events).

(144) In an example, the PCF **135**, based on the emergency DNN, may set the ARP of the PCC rules to a value that may be reserved for emergency services.

(145) In an example, if the request type in **1215** indicates initial request, the SMF **160** may select an SSC mode for the PDU session. The SMF **160** may select **1245** one or more UPFs as needed. In case of PDU type IPv4 or IPv6, the SMF **160** may allocate an IP address/prefix for the PDU session. In case of PDU type IPv6, the SMF **160** may allocate an interface identifier to the UE **100** for the UE **100** to build its link-local address. For unstructured PDU type the SMF **160** may allocate an IPv6 prefix for the PDU session and N6 point-to-point tunneling (e.g., based on UDP/IPv6). In an example, for Ethernet PDU type PDU session, neither a MAC nor an IP address may be allocated by the SMF **160** to the UE **100** for this PDU session.

(146) In an example, if the request type in **1215** is existing PDU session, the SMF **160** may maintain the same IP address/prefix that may be allocated to the UE **100** in the source network.

(147) In an example, if the request type in **1215** indicates existing PDU session referring to an existing PDU session moved between 3GPP access and non-3GPP access, the SMF **160** may maintain the SSC mode of the PDU session, e.g., the current PDU session Anchor and IP address. In an example, the SMF **160** may trigger e.g. new intermediate UPF **110** insertion or allocation of a new UPF **110**. In an example, if the request type indicates emergency request, the SMF **160** may select **1245** the UPF **110** and may select SSC mode **1**.

(148) In an example, the SMF **160** may perform a session management policy modification **1250** procedure to report some event to the PCF **135** that has previously subscribed. If request type is initial request and dynamic PCC is deployed and PDU type is IPv4 or IPv6, the SMF **160** may notify the PCF **135** (that has previously subscribed) with the allocated UE **100** IP address/prefix.

(149) In an example, the PCF **135** may provide updated policies to the SMF **160**. The PCF **135** may provide authorized session-AMBR and the authorized 5QI and ARP to the SMF **160**.

(150) In an example, if request type indicates initial request, the SMF **160** may initiate an N4 session establishment procedure **1255** with the selected UPF **110**. The SMF **160** may initiate an N4 session modification procedure with the selected UPF **110**. In an example, the SMF **160** may send an N4 session establishment/modification request **1255** to the UPF **110** and may provide packet detection, enforcement, reporting rules, and/or the like to be installed on the UPF **110** for this PDU session. If CN tunnel info is allocated by the SMF **160**, the CN tunnel info may be provided to the UPF **110**. If the selective user plane deactivation is required for this PDU session, the SMF **160** may determine the Inactivity Timer and may provide it to the UPF **110**. In an example, the UPF **110** may acknowledge by sending an N4 session establishment/modification response **1255**. If CN tunnel info is allocated by the UPF, the CN tunnel info may be provided to SMF **160**. In an example, if multiple UPFs are selected for the PDU session, the SMF **160** may initiate N4 session establishment/modification procedure **1255** with one or more UPF **110** of the PDU session.

(151) In an example, the SMF **160** may send to the AMF **155** an `Namf_Communication_N1N2MessageTransfer` **1305** message (comprising PDU session ID, access type, N2 SM information (PDU session ID, QFI(s), QoS profile(s), CN tunnel info, S-NSSAI, session-AMBR, PDU session type, and/or the like), N1 SM container (PDU session establishment accept (QoS Rule(s), selected SSC mode, S-NSSAI, allocated IPv4 address, interface identifier, session-AMBR, selected PDU session type, and/or the like))). In case of multiple UPFs are used for the PDU session, the CN tunnel info may comprise tunnel information related with the UPF **110** that terminates N3. In an example, the N2 SM information may carry information that the AMF **155** may forward to the (R)AN **105** (e.g., the CN tunnel info corresponding to the core network address of the N3 tunnel corresponding to the PDU session, one or multiple QoS profiles and the corresponding QFIs may be provided to the (R)AN **105**, the PDU session ID may be used by AN

signaling with the UE **100** to indicate to the UE **100** the association between AN resources and a PDU session for the UE **100**, and/or the like). In an example, a PDU session may be associated to an S-NSSAI and a DNN. In an example, the N1 SM container may contain the PDU session establishment accept that the AMF **155** may provide to the UE **100**. In an example, multiple QoS rules and QoS profiles may be included in the PDU session establishment accept within the N1 SM and in the N2 SM information. In an example, the Namf_Communication_N1N2MessageTransfer **1305** may further comprise the PDU session ID and information allowing the AMF **155** to know which access towards the UE **100** to use.

(152) In an example, the AMF **155** may send to the (R)AN **105** an N2 PDU session request **1310** (comprising N2 SM information, NAS message (PDU session ID, N1 SM container (PDU session establishment accept, and/or the like))). In an example, the AMF **155** may send the NAS message **1310** that may comprise PDU session ID and PDU session establishment accept targeted to the UE **100** and the N2 SM information received from the SMF **160** within the N2 PDU session request **1310** to the (R)AN **105**.

(153) In an example, the (R)AN **105** may issue AN specific signaling exchange **1315** with the UE **100** that may be related with the information received from SMF **160**. In an example, in case of a 3GPP RAN **105**, an RRC connection reconfiguration procedure may take place with the UE **100** to establish the necessary RAN **105** resources related to the QoS Rules for the PDU session request **1310**. In an example, (R)AN **105** may allocate (R)AN **105** N3 tunnel information for the PDU session. In case of dual connectivity, the master RAN **105** node may assign some (zero or more) QFIs to be setup to a master RAN **105** node and others to the secondary RAN **105** node. The AN tunnel info may comprise a tunnel endpoint for one or more involved RAN **105** nodes, and the QFIs assigned to one or more tunnel endpoints. A QFI may be assigned to either the master RAN **105** node or the secondary RAN **105** node. In an example, (R)AN **105** may forward the NAS message **1310** (PDU session ID, N1 SM container (PDU session establishment accept)) to the UE **100**. The (R)AN **105** may provide the NAS message to the UE **100** if the necessary RAN **105** resources are established and the allocation of (R)AN **105** tunnel information are successful.

(154) In an example, the N2 PDU session response **1320** may comprise a PDU session ID, cause, N2 SM information (PDU session ID, AN tunnel info, list of accepted/rejected QFI(s)), and/or the like. In an example, the AN tunnel info may correspond to the access network address of the N3 tunnel corresponding to the PDU session.

(155) In an example, the AMF **155** may forward the N2 SM information received from (R)AN **105** to the SMF **160** via a Nsmf_PDUSession_UpdateSMContext request **1330** (comprising: N2 SM information, request type, and/or the like). In an example, if the list of rejected QFI(s) is included in N2 SM information, the SMF **160** may release the rejected QFI(s) associated QoS profiles.

(156) In an example, the SMF **160** may initiate an N4 session modification procedure **1335** with the UPF **110**. The SMF **160** may provide AN tunnel info to the UPF **110** as well as the corresponding forwarding rules. In an example, the UPF **110** may provide an N4 session modification response **1335** to the SMF **160**.

(157) In an example, the SMF **160** may send to the AMF **155** an Nsmf_PDUSession_UpdateSMContext response **1340** (Cause). In an example, the SMF **160** may subscribe to the UE **100** mobility event notification from the AMF **155** (e.g. location reporting, UE **100** moving into or out of area of interest), after this step by invoking Namf_EventExposure_Subscribe service operation. For LADN, the SMF **160** may subscribe to the UE **100** moving into or out of LADN service area event notification by providing the LADN DNN as an indicator for the area of interest. The AMF **155** may forward relevant events subscribed by the SMF **160**.

(158) In an example, the SMF **160** may send to the AMF **155**, a Nsmf_PDUSession_SMContextStatusNotify (release) **1345**. In an example, if during the procedure, any time the PDU session establishment is not successful, the SMF **160** may inform the

AMF **155** by invoking Nsmf_PDUSession_SMCContextStatusNotify(release) **1345**. The SMF **160** may releases any N4 session(s) created, any PDU session address if allocated (e.g. IP address) and may release the association with the PCF **135**.

(159) In an example, in case of PDU type IPv6, the SMF **160** may generate an IPv6 Router Advertisement **1350** and may send it to the UE **100** via N4 and the UPF **110**.

(160) In an example, if the PDU session may not be established, the SMF **160** may unsubscribe **1360** to the modifications of session management subscription data for the corresponding (SUPI, DNN, S-NSSAI), using Nudm_SDM_Unsubscribe (SUPI, DNN, S-NSSAI), if the SMF **160** is no more handling a PDU session of the UE **100** for this (DNN, S-NSSAI). In an example, if the PDU session may not be established, the SMF **160** may deregister **1360** for the given PDU session using Nudm_UECM_Deregistration (SUPI, DNN, PDU session ID).

(161) In an example, a wireless communication system (e.g., 5GS, 3GPP system, 3GPP communication system, 4G, LTE, and/or the like) may support 5G LAN communication. A 5GLAN group communication session may be identified by a tuple of S-NSSAI and/or DNN. In an example, the 5GLAN group may be identified by a group identifier, VLAN ID, DNN, S-NSSAI, and/or the like. In case of supporting VLAN tags for 5G LAN communications, the 5G LAN group communication session may be identified by a tuple of S-NSSAI, DNN and VLAN Tag. In an example, the 5G LAN group, 5G LAN group communication session, and/or the like may be identified by an identifier of a group (e.g., a group id, internal group id, external group id, a group index, group information, and/or the like). In an example, a PDU session, a PDU session establishment, and/or the like may be employed for the 5G LAN group communication session. The PDU session establishment may employ the tuple of S-NSSAI, DNN, a group id, and/or the like. In an example, area restriction of the 5G LAN service may be done by configuring a DNN as the LADN DNN with LADN service area (e.g., a list of tracking areas, and/or the like). In an example, a UE may connect to a virtual network that may connect one or more UEs within the group as depicted in example FIG. **14**. As depicted in Example FIG. **14**, same SMF (one common SMF) may be employed for the group communication session. In an example, a data network may be employed for group communication. In an example, a PDU session anchor UPF (PSA-UPF) may be employed to transmission/sending/receiving/forwarding of 5G LAN communication packets. The PSA-UPF may enforce group AMBR, group quota, individual UE's AMBR or QoS enforcement, and/or the like. The PSA-UPF may be functionally/logically/physically collocated with an intermediate UPF (I-UPF). The SMF may manage/check/determine one or more established and/or activated PDU sessions.

(162) In an example as depicted in FIG. **15**, an admin user (e.g., administrator, a UE which belongs to a 5GLAN admin group, and/or the like) may request addition/deletion of a 5GLAN user group and add (or delete) a member to the 5GLAN user group. A UE may belong to one or more groups and the subscription data for the UE in a UDR may associate the subscriber with groups. In an example, an internal group identifier in the UDR may identify a group. A group management may be a management functionality on manipulating the UDR records. For example, creating a group with list of group members may be implemented as creating a record of group subscription data. In an example, addition, adding or deleting a member in the group may be defined as adding or deleting a SUPI in the group subscription data. A domain may be a logical administrative area within which a member of the admin group may manage the user groups and their membership. A domain may be employed to refer a tenant (e.g., a customer of 5G LAN service provided by an operator). A domain may comprise a domain identifier, an admin group identifier, one or more group identifiers, and/or the like.

(163) An example FIG. **15**, depicts the relationship of domain, admin group and user group for 5G LAN group. A domain may comprise an admin group and one or more user groups. A user in the admin group may manage the user group and membership of the admin/user group in the domain and manage (e.g., provision, activate, deactivate, and/or the like) the 5GLAN communication

session. A user may belong to one or more groups (e.g., a user 2 may be a member of admin group, a member of user group A.1 and a member of user group A.2 as depicted in example FIG. 15.

(164) In an example embodiment as depicted in FIG. 16, an AF (e.g., an admin subscriber, and/or the like) may request an NEF to activate a group communication session. The request may comprise a UE identifier of the requestor, a requestor id, and/or the like with an authorization information. The NEF may check if the requestor is authorized to activate the group communication session. The NEF may retrieve a list of the UE identifiers of the group and may update the UE policy for one or more UE(s) in the group. A UDR may notify a PCF for updating the policy data since the PCF subscribed the UDR on the change of the policy data. The PCF may initiate a UE policy delivery procedure e.g., delivery of a UE route selection policy (URSP). In order for the UE to establish the PDU session after the UE policy is delivered, the URSP may comprise a policy enforcement parameter that may indicate a request for establishment of the PDU session. The UE may receive the UE policy and if the UE policy includes the establishment request of the PDU session, the UE may perform a PDU session establishment procedure with the configured parameters as encoded as route selection components in the URSP rules.

(165) In an example, for one to many communication in a virtual network group, during the UE policy delivery procedure, the SMF may allocate a multicast information, multicast address, and/or the like for the group. The URSP may comprise the multicast address and the UE may be configured to send data to the multicast address when determining to send data for the group communication. The multicast information may further comprise a set of wireless device identifiers in a group, an identifier of the group, and/or the like.

(166) In an example embodiment as depicted in FIG. 17, the AF (e.g., admin user) may request the NEF to activate a group communication. The procedure may be based on a PDU session modification procedure. The request may comprise the UE identifier of the requestor with the authorization information. The NEF may check if the requestor is authorized to activate the group communication session. The NEF may retrieve the list of the UE identifiers of the group and may update the UE policy for one or more UE(s) in the group. The UDR may notify the PCF for updating the policy data since the PCF subscribed the UDR on the change of the policy data. The PCF may perform the SM policy control update notification procedure to deliver the update policy information for the established session for example, the addition of a VLAG TAG, and/or the like. The SMF may initiate the PDU session modification procedure to send the VLAN TAG, and/or the like to the UE.

(167) In an example embodiment as depicted in FIG. 19, a group may be created, and group member UE-T and UE-R1 may be added into the group, and UE-T is authorized to send one to many data to the members in the group. UE-T may initiate group specific PDU Session establishment request, including the requested S-NSSAI, group information, and/or the like. In an example, the group information may be a group index, a group specific DNN information or group specific application server information, and/or the like. After receiving the request from UE-T, the SMF may select the UPF1 as the serving UPF for the specific group and may assign addresses (e.g., multicast address) for one to many data communication based on the S-NSSAI information and the group information. The SMF may send session establishment request to UPF1, including the allocated CN tunnel information on N3 interface. UPF1 may acknowledge by sending Session establishment response message. The SMF may send a PDU Session Accept message to the UE-T with the addresses, multicast address, and/or the like for one to many data communication. In case of PDU Session Type IPv4 or IPv6 or IPv4v6, the SMF may allocate an IP address/prefix for the PDU Session. When UE-R2 is added into the group, UE-R2 may initiate PDU Session establishment request to the SMF, that may comprise S-NSSAI information and group information. The SMF may select UPF2 as the serving UPF for UE-R2 and may assign same addresses for one to many data communication based on the S-NSSAI information and group information, and may determine to establish the forwarding tunnel between UPF1 serving UE-T and the UPF2. The

SMF may send session establishment request to UPF2, including the allocated CN tunnel information and the allocated addresses for one to many data communication. The CN tunnel information may comprise the UPF2 address of the tunnel between UPF1 and UPF2 and the UPF2 address of N3 tunnel. UPF2 may acknowledge by sending Session establishment response message. The SMF may establish a group forwarding tunnel between UPF1 and UPF2, and may provide the UPF2 address of the tunnel between UPF1 and UPF2, as well as addresses for one to many data communication to UPF1. The SMF may associate the forwarding tunnel, addresses for one to many data communication and PDU Session for UE-T to group path and may provide the group forwarding path to UPF1. The SMF may send a PDU Session Accept to UE-R2 with the addresses for one to many data communication. In case of PDU Session Type IPv4 or IPv6 or IPv4v6, the SMF may allocate an IP address/prefix for the PDU Session, and the address/prefix is the group specific for UE-R2. If there is existing PDU Session for another group for UE-R2, the existing PDU Session may be re-used for the newly joined group, e.g., multiple groups may share one PDU Session for the receiving member in the group. The UE-T may send the group data to the UPF1, UPF 1 may determine the receiving UE-R1, UE-R2 according to the destination addresses, the group paths, and/or the like and may route the data to the tunnel corresponding to UE-R1 and UE-R2 respectively.

(168) In an example FIG. 18, a UE may establish a PDU session to join a group. After establishment of the PDU session, the UE may transition to idle (e.g., CM-IDLE). The UE may perform a service request procedure to transmit signaling, data, and/or the like. Upon successful completion of the service request procedure, the UE may transmit data packets for one or more UEs of a group. The UPF may forward the data packets via N6 interface, Nx interface or directly to the receiving UEs (e.g., local switch).

(169) In an example, as depicted in FIG. 23, a policy delivery procedure may be employed. The policy delivery procedure may be employed to transmit the URSP to the UE. In an example the PCF may determine to update UE policy procedures based on triggering conditions such as an initial registration, need for updating UE policy, and/or the like. In an example, for initial registration case, the PCF may compare the list of PSIs included in the UE access selection and PDU session selection related policy information in Npcf_UEPolicyControl_Create request and may determine whether UE access selection and PDU session selection related policy information have to be updated and be included in the response to the AMF. In an example, for the network triggered UE policy update case (e.g. the change of UE location, the change of Subscribed S-NSSAIs, activation of a group, and/or the like), the PCF may check the latest list of PSIs to decide which UE access selection and/or PDU Session selection related policies have to be sent to the UE. The PCF may check if the size of the resulting UE access selection and PDU Session selection related policy information exceeds a predefined limit. If the size is under the limit, then UE access selection and PDU Session selection related policy information may be included in a single Namf_Communication_N1N2MessageTransfer service operation. If the size exceeds the predefined limit, the PCF may split the UE access selection and PDU Session selection related policy information in smaller, logically independent UE access selection and PDU Session selection related policy information ensuring the size of each is under the predefined limit. One or more UE access selection and PDU Session selection related policy information may be sent in one or more Namf_Communication_N1N2MessageTransfer service operations.

(170) In an example, the PCF may invoke Namf_Communication_N1N2MessageTransfer service operation provided by the AMF. The message may comprise a SUPI, UE Policy Container, and/or the like. If the UE is registered and reachable by AMF in either 3GPP access or non-3GPP access, the AMF may transfer transparently the UE policy container to the UE via the registered and reachable access. If the UE is registered in both 3GPP and non-3GPP accesses and reachable on both access and served by the same AMF, the AMF may transfer transparently the UE Policy container to the UE via one of the accesses based on the AMF local policy. If the UE is not

reachable by AMF over both 3GPP access and non-3GPP access, the AMF may report to the PCF that the UE Policy container may not be delivered to the UE using Namf_Communication_N1N2TransferFailureNotification. If AMF determines/decides to transfer transparently the UE Policy container to the UE via 3GPP access, e.g. the UE is registered and reachable by AMF in 3GPP access only, or if the UE is registered and reachable by AMF in both 3GPP and non-3GPP accesses served by the same AMF and the AMF decides/determines to transfer transparently the UE Policy container to the UE via 3GPP access based on local policy, and the UE is in CM-IDLE and reachable by AMF in 3GPP access, the AMF may start a paging procedure by sending a paging message to the UE. Upon reception of paging request, the UE may initiate the UE triggered service request procedure. If the UE is in CM-CONNECTED over 3GPP access or non-3GPP access, the AMF may send/transfer transparently the UE Policy container (e.g., UE access selection and PDU Session selection related policy information) received from the PCF to the UE. The UE Policy container may comprise URSP, and/or the like. The UE may update the UE policy provided by the PCF and may send the result to the AMF. If the AMF received the UE Policy container and the PCF subscribed to be notified of the reception of the UE Policy container, the AMF may forward the response of the UE to the PCF employing a Namf N1MessageNotify, and/or the like. The PCF may maintain the list of PSIs delivered to the UE and may update the latest list of PSIs in the UDR by invoking Nudr_DM_Update (e.g., comprising SUPI, Policy Data, Policy Set Entry, updated PSI data) service operation, and/or the like.

(171) A 5GLAN Group may be managed (e.g., created, modified, and removed) based on AF request or UE request. A UE that belongs to the 5GLAN Group may access the 5G LAN-type service corresponding to the 5GLAN Group.

(172) The UE may access the 5G LAN-type service by establishing a PDU session. During establishment of the PDU Session, the UE may be authenticated/authorized for accessing the 5G LAN-type service. The 5G LAN-type service may support 5GLAN communication within the 5GLAN group by coordinating PDU sessions of the UEs, e.g., traffic routing between PDU sessions may take place within the 5GS.

(173) The 5GS may support the 5G LAN-type service by establishing a user plane composed of one UPF or multiple interconnected UPFs. When the UEs within the 5GLAN group communicate with a physical LAN in the DN for one or more data services, an Ethernet transport service may be associated with the DN and may support connecting the UEs to the physical LAN in the DN.

(174) The user plane of a 5G LAN-type service may comprise an access UP and a backbone UP. The access UP may comprise the UP path of a PDU Session, of which UP paths terminates at an anchor UPF (e.g., not to a DN). The backbone UP may comprise one anchor UPF or multiple anchor UPFs with one or multiple connections (e.g., Nx connections, tunnels, and/or the like) which may bridge the UP paths in the access UP with each other. The Nx connections in the backbone UP may be managed by the 5GC. Traffic routing over Nx in the backbone UP may be configured at the 5G LAN-type service level. The UPF(s) in the backbone UP may function as a router or a switch (Ethernet switch) and may treat the user plane path of the PDU session as the cable connecting the UE to one port/interface on the router or switch.

(175) In an example, depending on implementation and operator's configuration, the backbone UP (e.g., comprising UPFs and Nx connections in between) may be pre-established before the UE requests PDU session for access to the 5G LAN-type service and updated/modified afterward. The Nx connections in the backbone UP may support IP traffic and/or Ethernet traffic and may be managed by the 5GC. An Nx connection may belong to a PDU session. The connection may be a per 5GLAN Group connection, shared by multiple PDU Sessions for support of traffic routing between those Sessions. Private communication (of 5G LAN-type service) is achieved by shared anchor UPF or by interconnecting two anchor UPFs via an Nx interface. The combination of two anchor UPFs and the Nx interface in between may be an Nx connection. One or more Nx connections may be further interconnected for the private communication in the same 5GLAN

group (e.g., depending how many group member UEs are involved).

(176) An example FIG. 21 depicts an example of user plane topology for one to many data communication. As depicted in FIG. 21, the group specific PDU Session may be terminated at the group member and the serving UPF. When a group is established by one AF or one UE, a group specific PDU Session may be established for each group member who are added into the group with the group creation. After the group creation, when a group member is added into the group, the group specific PDU Session may be established for the new joined member. The SMF may be responsible for establishing the forwarding tunnel between the UPF serving the new joined member and the UPFs serving the authorized transmitting members. The PDU Session for UE-T, PDU Session for UE-R1, forwarding tunnel on N9 interface for this group, PDU Session for UE-R2 compose the group data forwarding path. UPF1 may forward the data received from UE-T to UE-R1 and UPF2 according to group data forwarding path. If there are multiple UPFs (i.e. more than two UPFs) on the group data forwarding path, group forwarding tunnel may be established on each N9 interface on the group data forwarding path. UPF(s) detect one to many communication based on the destination address in the received data, e.g., if the destination address in the received data is broadcast/multicast address, then the UPF(s) may forward the data to the related group members.

(177) The access UP and the backbone UP may intersect at UPFs, which may be PSA UPFs from the access part point of view and BUAP (Backbone UP Access Point) UPFs from the backbone part point of view. Example FIG. 22 depicts the user plane architecture of 5GLAN communication framework.

(178) In an example, an authorized entity, e.g., a UE or an AF, may interact with a GMF, UDM, UDR, NRF, and/or the like to manage a 5GLAN group. This may include to create, modify or remove a 5GLAN group, or to query information related to a 5GLAN group, for example, information such as IP address of a member UE in the 5GLAN group. In an example, when a UE interacts with the GMF, UDM, UDR, NRF, and/or the like, the UE may send a request for 5GLAN group management to the GMF, UDM, UDR, NRF, and/or the like, via the AMF, and the UE request may be authorized by the GMF according to subscription information, e.g. whether the UE is authorized to create a 5GLAN group. In an example, when an AF interacts with the GMF, the AF may send a request for 5GLAN group management to the GMF directly or via the NEF, depending on whether operator allows the AF to access the network directly. When the NEF is involved, the NEF may authorize the AF request if the AF request is not yet authorized. The request may comprise GPSI if the requesting entity is a UE, or AF-service-ID if the requesting entity is an AF, and 5G LAN-VN DNN. Depending on the management purpose, the request may further comprise type of traffic (e.g. IP type or Ethernet type) to be supported during 5GLAN communication, metadata of the 5GLAN group (e.g. describing the purpose of the 5GLAN group), identity information (e.g. GPSIs of the UEs to be added in or removed from the 5GLAN group), service restrictions (e.g., allowed area), information identifying the 5GLAN group (e.g., in the form of Internal group ID or External group ID), the types of information (e.g., information of member UEs) being queried, and/or the like. The GMF may validate the information provided by the entity, e.g., whether a member UE identified in the information is allowed to access the 5G LAN-type service, and manages the 5GLAN group according to the information. As a result of the 5GLAN group management operations, the context of the 5GLAN group is created, modified, or removed in the GMF, UDM, UDR, and/or the like or information being queried by the entity is identified from local storage of the GMF, UDM, UDR, and/or the like and sent back to the requesting entity. The GMF may update the 5GLAN group membership information to the UDM. The GMF may provide policy requirements (e.g., service restrictions) to the PCF. When creating a 5GLAN group, the GMF may allocate an ID to the 5GLAN group and may include the 5GLAN group ID in the response sent to the requesting entity. When a UE is added into the 5GLAN group, the GMF may allocate group credential for the UE, which is to be provided by the UE to the network as authentication and authorization information for accessing 5G LAN-type service for the 5GLAN

group.

(179) In an example, the wireless communication system, e.g., the 3GPP system, 5GS, 4G, LTE, and/or the like may be employed for group communication, UE to UE communication session, one UE to/from one or more UE(s) communication session(s), one to many communication, and/or the like.

(180) An example FIG. 24 depicts one or more UEs that may perform a PDU session establishment to join a group. The SMF allocates or retrieves the multicast information associated with the group and provide the multicast information to the UE members of the group.

(181) An example FIG. 25 depicts a transmitting wireless device (UE-T) performing a service request procedure to initiate transmission of data packets to the receiving wireless devices of the VN group. The AMF and/or the SMF determine to proactively initiate service request procedure and activation of receiving wireless devices.

(182) A transmitting wireless device may attempt to transmit data packets to a large group of receiving wireless devices. The transmitting wireless device may perform a service request procedure to activate a user plane connection. Upon successful activation of the transmitting wireless device user plane connection, the transmitting wireless device may send data packets targeted to the group. A UPF may receive the data packets and determine that the data packet destination is a multicast address or that the data packets are targeted to one or more wireless devices. The UPF may determine that the user plane connection for one or more of the targeted wireless devices is inactive, and may send data notifications to activate the inactive user plane connections. The receiving wireless devices may be notified by the network to perform a service request procedure. Upon successful activation of the receiving wireless device user plane connection, the UPF may transmit the data packets. The data packets may not be distributed by the UPF until the user plane activation is complete which can result in significant delay. The present application proposes new techniques to reduce the delay associated with user plane activation for the group.

(183) For example, when the transmitting wireless device sends a service request with an indication that the service request is for activation of user plane connection for a virtual network group communication, the transmitting wireless device may include multicast information in the service request message. The AMF may employ the indication and the multicast information to proactively activate the user plane connection for the receiving wireless devices of the group prior to the completion of the transmitting wireless device user plane connection activation. The proactive activation may reduce the amount of time between the initiation of service request by the transmitting wireless device and user plane connection activation for the group. As a result, the UPF may distribute the data packets to the group as soon the data packets are received from the transmitting wireless device. The AMF can facilitate this reduction of delay by acting on the service request received from the transmitting wireless device instead of waiting for data notifications from the SMF for the receiving wireless devices. An example FIG. 26 depicts service request procedure delay.

(184) In an example embodiment as described in the present application, the transmitting wireless device (UE-T) may send a service request procedure to (re)activate user plane resources or connection for the transmitting wireless device. The UE-T may receive information about a group for VN group communication, one to many communication, one to one communication and/or the like, via a PDU session establishment procedure, policy delivery, URSP, configuration update, local configuration and/or the like. The VN group may be a VLAN group. The UE-T may act as a VLAN switch with one or more ports supporting one or more VLAN groups. The UE-T may transmit and receive packets for the VLAN group behind the UE-T. The UE-T may forward the data packets to the appropriate port based on VLAN ID, port ID, VLAN TAG, V-TAG, C-TAG, MAC address, ethernet address, and/or the like. The UE-T, UPF, and/or the like, may support framed routing. Framed Routing may allow to support an IP network behind a UE, such that a range of IP addresses

or IPv6 prefixes is reachable over a single PDU session, e.g., for enterprise connectivity. Frame Routes may be IP routes behind the UE. In an example, the UE may send a service request message to the network. The message may comprise an indication for the cause of the service request procedure such as transmit data to a group, a multicast address, multicast information, and/or the like. The network may receive the indication and the multicast information. The network based on the indication and the information may determine a group associated with the multicast information/address and may proactively activate user plane resources and user plane connections for the receiving wireless devices. The activation of user plane may comprise activating by the AMF and the RAN node the receiving UEs (UE-Rs) associated with the group. The AMF may determine the IDLE UE-Rs and page the UE-Rs. The activation of user plane may comprise a proactive action by the SMF to activate and/or modify the N4 sessions associated with the group members (UE-Rs and the UE-T). When the UE-T receives a service accept message, the service accept message may indicate that activation of user plane for the group has been initiated or completed. The UE-T may send data packets to the UPF with the multicast information targeting the UEs of the group. Upon reception of the data packets by the UPF, the CN tunnel, N3 tunnel, user plane, and/or the like of the receiving wireless devices may be activated and data notifications may not be required.

(185) In an example embodiment, multicast information may comprise one or more multicast addresses, a set of one or more UE members of the group, an identifier of a UE member of the group (UE ID, SUPI, and/or the like), an identifier/address of a UE acting as a VLAN switch/router and a port number that connects a VLAN group associated with the group to the network via the UE-T, a VLAN ID, V-TAG, C-TAG, S-TAG, VLAN TAG, and/or the like.

(186) In an example embodiment the PDU session establishment procedure as depicted in FIG. 12 and FIG. 13, and FIG. 20 may be employed by a wireless device to join a virtual network VN group communication. In an example, when the UE sends to the AMF the NAS Message (or the SM NAS message), if the UE is establishing the PDU session for sending one to many communication data of a 5GLAN group, VN group, and/or the like it may indicate that it requests a multicast address, multicast information, and/or the like. The UE may indicate the group information within the N1 SM container. If the UE is establishing the PDU session for receiving one to many communication data of a 5GLAN group, it may indicate the group information and may indicate that it is a receiver of the group within the N1 SM container.

(187) In an example embodiment, when the AMF receives the NAS message, if the request type indicates initial request and the UE subscription indicates the support for 5G LAN-type (e.g., VN group, and/or the like) service for the requested DNN, the AMF may select the SMF associated with the requested DNN in UE subscription data received from a UDM. The case where the request type indicating initial request and the UE subscription indicating the support for 5G LAN-type service for the requested DNN, and UE subscription received from the UDM during the registration or subscription profile update notification procedure does not contain SMF information corresponding to the requested DNN may constitute an error case, the AMF may reject the NAS message containing PDU Session Establishment Request from the UE with a cause indicating that the requested 5G LAN-type service is not supported.

(188) In an example, when the SMF receives the PDU session establishment request if the request indicates the one to many communication, VN group, group communication, and/or the like establishment request for an indicated group, the SMF may allocate a 5GLAN group (VN group) unique multicast address (e.g., IP address for IP type PDU session, MAC address for Ethernet type, and/or the like). In an example, the SMF may obtain the address information for the one to many communication from 5GLAN group provision information (e.g., from a UDR, UDM, PCF, a repository function, a group management function, locally configured information, and/or the like).

(189) In an example, during the PDU session establishment procedure, the SMF may perform the N4 session establishment or N4 session modification procedure. The SMF may send the N4

session establishment/modification request to the UPF and may provide packet detection (e.g., PDR), forwarding (e.g., FAR), enforcement and reporting rules to be installed on the UPF for the PDU session. If CN tunnel info is allocated by the SMF, the CN Tunnel Info may be provided to the UPF. If selective user plane deactivation is required for the PDU Session, the SMF may determine the inactivity timer and may provide it to the UPF. The SMF may provide trace requirements to the UPF if it has received trace requirements. If the PDU Session is targeting to the DNN associated with a 5GLAN group, the SMF may create the packet detection and forwarding rules in order to bind the session or service data flow to the related 5G LAN-VN. The packets detection includes session tunnel information, UE address, and/or the like and the packets forwarding rules may include the related VLAN ID, 5G LAN-VN ID, and/or the like. In an example, when the PDU session is for sending and/or receiving one to many communication data of a 5GLAN group, the SMF may provide the multicast address, multicast information, and/or the like to the UPF for detecting packets, and receiving packets from the PDU session or sending packets to the PDU session.

(190) In an example, when the PDU session establishment is in progress, the SMF may send to the AMF the Namf_Communication_N1N2MessageTransfer message that may comprise the PDU Session ID, N2 SM information (PDU Session ID, QFI(s), QoS Profile(s), CN Tunnel Info, S-NSSAI from the Allowed NSSAI, Session-AMBR, PDU Session Type, User Plane Security Enforcement information, UE Integrity Protection Maximum Data Rate), N1 SM container (PDU Session Establishment Accept (QoS Rule(s) and QoS Flow level QoS parameters if needed for the QoS Flow(s) associated with the QoS rule(s), selected SSC mode, S-NSSAI(s), DNN, allocated IPv4 address, interface identifier, Session-AMBR, selected PDU Session Type, Reflective QoS Timer (if available), P-CSCF address(es), [Always-on PDU Session], allocated multicast address, the multicast address for one to many communication, the multicast information, and/or the like))). If multiple UPFs are employed for the PDU Session, the CN Tunnel Info may contain tunnel information related with the UPF that terminates N3.

(191) In an example, during the PDU session establishment procedure, the UPF may provide the N4 session modification response to the SMF. If multiple UPFs are employed in the PDU Session, the UPF may be the UPF terminating N3. If the PDU Session is targeting to the DNN associated with the 5GLAN group, the SMF may create new packet handling rules (PHRs) including the UE address and the association to the downlink packet forwarding rules of the PDU Session. The SMF may initiate N4 PHRs management procedure to update the PHRs for the corresponding 5G LAN-VN group in the UPF.

(192) In an example, during the PDU session establishment procedure, the AMF may send to the (R)AN the N2 PDU Session Request (N2 SM information, NAS message (PDU Session ID, N1 SM container (PDU Session Establishment Accept))). In an example, the N2 PDU Session Request, the N2 SM information, the NAS message, and/or the like may comprise the multicast address, multicast information, and/or the like of the 5GLAN group (VN group). The AMF may send the NAS message containing PDU Session ID and PDU Session Establishment Accept targeted to the UE and the N2 SM information received from the SMF within the N2 PDU Session Request to the (R)AN. The (R)AN may issue to the UE the AN specific signalling exchange with the UE that is related with the information received from SMF. For example, in case of a NG-RAN, an RRC Connection Reconfiguration may take place with the UE establishing the necessary NG-RAN resources related to the QoS Rules for the PDU Session request. The AN specific signalling exchange procedure may be employed to transmit the multicast information, multicast address and/or the like to the UE. The (R)AN may allocate (R)AN N3 tunnel Info for the PDU Session. The (R)AN may forwards the NAS message (multicast address, multicast information, the PDU Session ID, N1 SM container (PDU Session Establishment Accept)) to the UE.

(193) In an example embodiment, upon successful establishment of the PDU session, the UPF may transmit the multicast information, multicast address, and/or the like associated with the 5GLAN,

VN group, to the UE via a user plane connection. An advertising mechanism may be employed to transmit/deliver/send the multicast information of the group to the UE.

(194) In an example, VN group, 5GLAN group communication, and/or the like may comprise communication among one or more wireless devices. The group communication may comprise and/or employ unicast, multicast, anycast, geocast, broadcast, and/or the like methods of communication/routing/switching. The multicast information may refer to address, identity, and/or the like that determines/identifies the group communication. In an example, the multicast information may be a multicast address, multicast IP address, multicast MAC address, and/or the like. The multicast information may comprise an identifier of a receiving wireless device, identifier/identifiers/addresses of one or more wireless devices, a subset of wireless devices of a group, and/or the like. In an example, the group may comprise one or more wireless devices. In an example, the group may comprise a group of wireless devices reachable via a domain, IP domain, multicast address (e.g., IP, MAC, and/or the like), a network instance, VLAN, VLAN ID, S-TAG, C-TAG, VLAN TAG, a group GTP tunnel identifier, a group GTP tunnel end point identifier, and/or the like. In an example, the network instance may be employed to separate IP domains, e.g., when a UPF is connected to 5G-ANs in different IP domains, overlapping UE IP addresses assigned by multiple Data Networks, and for transport network isolation in the same PLMN, and/or the like.

(195) In an example embodiment as depicted in FIG. 18, after the PDU session establishment, the UE may transition to idle state. When the UE determines to send signaling or data, the UE may perform a service request procedure.

(196) As depicted in example FIG. 10, FIG. 11, and FIG. 27, a transmitting wireless device (e.g., a UE, UE-T) may perform a service request procedure. The UE in CM IDLE state may initiate the service request procedure in order to send uplink signalling messages, user data, or as a response to a network paging request. After receiving the service request message, the AMF may perform authentication. After the establishment of the signalling connection to an AMF, the UE or network may send signalling messages, e.g., PDU Session establishment from UE to the SMF, via the AMF. The Service Request procedure may be employed by a UE in CM-CONNECTED to request activation of a user plane connection for PDU Sessions and to respond to a NAS Notification message from the AMF. When a user plane connection for a PDU Session is activated, the AS layer in the UE may indicate it to the NAS layer. For any service request, the AMF may respond with a service accept message to synchronize PDU session status between UE and network. The AMF may respond with a service reject message to UE, if the service request cannot be accepted by network. The service reject message may include an indication or cause code requesting the UE to perform registration procedure. In an example, the UE may initiate service request procedures via non-3GPP Access via an N3-IWF.

(197) In an example embodiment, a transmitting wireless device (the UE, the UE-T) may receive a PDU session establishment accept message indicating successful establishment of the PDU session to join the VN group, the group, and/or the like. The UE may receive from a session management function in response to requesting establishment of a PDU session for joining the group (comprising one or more other wireless devices), a message comprising the multicast information, the multicast address, and/or the like.

(198) In an example, the wireless device (UE-T) may send to an AMF, a service request message requesting activation of a user plane connection of the PDU session for transmission of data packets to one or more wireless devices of the group. In an example, the service request message may comprise a service request. The service request may comprise the (VN) group multicast information, the multicast information, the multicast address, the indication that the service request is for transmission of data packets for the VN group, activation of user plane connection for the VN group, and/or the like, one or more wireless device identifiers, and/or the like. In an example, the one or more wireless device identifiers may correspond to a subset of the group. In an example, the

multicast information may comprise the multicast address, the one or more wireless device identifiers, and/or the like. In an example, the service request message may further comprise an indication that the service request is for transmission of data packets for a VN group, activation of user plane connection for the VN group, and/or the like.

(199) In an example embodiment, the service request message may comprise an AN message. The UE-T (the UE) may send to the (R)AN the AN message comprising AN parameters, Service Request (the multicast information, the indication that the service request is for transmission of data packets for the VN group, activation of user plane connection for the VN group, and/or the like, List Of PDU Sessions To Be Activated, List Of Allowed PDU Sessions, security parameters, PDU Session status, 5G-S-TMSI, [NAS message container], and/or the like). The NAS message container may be included if the UE is sending a Service Request message as an Initial NAS message and the UE needs to send non-clear-text IEs. The List Of PDU Sessions To Be Activated may be provided by the UE when the UE wants to re-activate the PDU Session(s). The List Of Allowed PDU Sessions may be provided by the UE when the Service Request is a response of a Paging or a NAS Notification for a PDU Session associated with non-3GPP access, and identifies the PDU Sessions that can be transferred to 3GPP access. In an example when NG-RAN is employed the AN parameters may comprise the multicast information, the indication that the service request is for transmission of data packets for the VN group, activation of user plane connection for the VN group, and/or the like, 5G-S-TMSI, Selected PLMN ID, PLMN ID (or PLMN ID and NID, and/or the like) and Establishment cause. The Establishment cause may provide the reason for requesting the establishment of an RRC connection. The AN parameters may further comprise a CAG Identifier if the UE is accessing the NG-RAN using a CAG cell. The UE may send Service Request message towards the AMF encapsulated in an RRC message to the NG-RAN. The RRC message(s) may be employed to carry the 5G-S-TMSI and the NAS message. In an example, if the Service Request is triggered by the UE for user data, the UE identifies, using the List Of PDU Sessions To Be Activated, the PDU Session(s) for which the UP connections are to be activated may be further included in the service request message. When the UE includes the List Of PDU Sessions To Be Activated, the UE may indicate PDU Sessions associated with the access the service request is related to. If the service request is triggered by the UE for signalling only, the UE doesn't identify any List Of PDU Sessions To Be Activated. If this procedure is triggered for paging response, and the UE has at the same time data packets to be transferred, the UE may identify the PDU Session(s) whose UP connections are to be activated in service request message, by the List Of PDU Sessions To Be Activated. Otherwise the UE does not identify any PDU Session(s) in the Service Request message for paging response. The UE may include always-on PDU Sessions which are accepted by the network in the List Of PDU Sessions To Be Activated even if there are no pending uplink data for those PDU Sessions or when the Service Request is triggered for signalling only or when the Service Request is triggered for paging response. If the Service Request over 3GPP access is triggered in response to the paging or NAS Notification indicating non-3GPP access, the Service Request message may identify the list of PDU Sessions associated with the non-3GPP access that can be re-activated over 3GPP in the List Of Allowed PDU Sessions. The PDU Session status may indicate the PDU Sessions available in the UE.

(200) In an example, the (R)AN node may send to the AMF the N2 Message comprising N2 parameters, the service request, and/or the like. In an example, the N2 parameters and/or the service request may comprise the multicast information, the indication that the service request is for transmission of data packets for the VN group, activation of user plane connection for the VN group, and/or the like.

(201) In an example, when the NG-RAN is employed, the N2 parameters may include the multicast information, the indication that the service request is for transmission of data packets for the VN group, activation of user plane connection for the VN group, and/or the like, the 5G-S-TMSI, Selected PLMN ID (or PLMN ID and NID, and/or the like), Location information and

Establishment cause, UE Context Request. If the UE is in CM-IDLE state, the NG-RAN may obtain the 5G-S-TMSI in RRC procedure. The NG-RAN may select the AMF according to 5G-S-TMSI. The location information relates to the cell in which the UE is camping.

(202) In an example embodiment, in response to receiving the multicast information, the indication that the service request is for transmission of data packets for the VN group, activation of user plane connection for the VN group, and/or the like, by the AMF, the AMF may determine that the transmitting UE may send data to a group of UEs (receiving wireless devices, UE-Rs). The AMF may determine the members of the group associated with the multicast information, or obtain the group information associated with the multicast information from a repository. The AMF may determine from a list/set of UEs associated with the group, one or more UEs that are in idle state and send one or more paging messages to the one or more UEs in idle state. In an example, the AMF may determine to activate the user plane connection of the UEs that are associated with the group.

(203) If there is a Service Gap timer running in the UE Context in AMF for the UE and the AMF is not waiting for a MT paging response from the UE, the AMF may reject the Service Request with an appropriate cause. In an example, the AMF may provide a UE with a Mobility Management Back-off timer set to the remaining value of the Service Gap timer. In an example, the AMF may determine that the transmitting wireless device is not allowed to perform a service request procedure that triggers the AMF to proactively activate the user plane connection/resources of the receiving wireless devices. The determining by the AMF may be based on a query to a repository (UDR, UDM, and/or the like), a query to a policy function such as PCF, and/or the like. The AMF in response to the determining, may reject the service request with an appropriate cause (indicating an error, a restriction, and/or the like).

(204) In an example, when the UE (UE-R) is in CM-CONNECTED state, the UE-R may perform the UE triggered service request procedure to establish the radio resources and, in the case that the User Plane is to be activated, to establish the N3 tunnel without sending a Paging message to the (R)AN node and the UE. If the UE is in CM-IDLE state in 3GPP access the AMF may determine/decide to notify the UE through 3GPP access. The AMF may send a Paging message to NG-RAN node(s) via 3GPP access. In an example, different paging strategies may be configured in the AMF for different combinations of DNN, Paging Policy Indicator (if supported), ARP and 5QI. The paging strategy may further correspond to the VN group activation, priority associated with related procedures of VN group, and/or the like. The (R)AN node may prioritize the paging of UEs according to a Paging Priority associated with VN group, one to many communication, and/or the like.

(205) In an example, the AMF may determine a group information associated with the multicast information. In an example, the AMF may send to the SMF an Nsmf_PDUSession_UpdateSMContext Request (the multicast information, the group information, the indication that the service request is for transmission of data packets for the VN group, activation of user plane connection for the VN group, and/or the like the PDU Session ID(s), Operation Type, UE location information, Access Type, RAT Type, UE presence in LADN service area, Indication of Access Type can be changed). In an example, the operation type may indicate that the operation is related to activation of user plane connection/resources for the group. The operation type may be VN group user plane activation, VN group PDU session activation, and/or the like. The Nsmf_PDUSession_UpdateSMContext Request may be invoked when the UE identifies List Of PDU Sessions To Be Activated in the Service Request message, the UE provides the multicast information, the AMF provides the group information/multicast information, and/or the like. In an example, the AMF may determine the PDU Session(s) for which the UP connection(s) may be activated and may send an Nsmf_PDUSession_UpdateSMContext Request to SMF(s) associated with the PDU Session(s) with Operation Type set to UP activate, VN group user plane activation, VN group PDU session activation, and/or the like to indicate establishment of

User Plane resources for the PDU Session(s). The AMF may determine access type and RAT type.

(206) In an example embodiment, the SMF may send to the UPF (PSA) the N4 session modification request for the N4 session associated to the transmitting wireless device, UE-T. Depending on the network deployment, the CN Tunnel Info of UPF (PSA) allocated for N3 or N9 interface may be changed during the Service Request procedure, e.g., UPF connected to different IP domains. If the different CN Tunnel Info need be used, and the CN tunnel info is allocated by the UPF, the SMF may send N4 session modification request message to UPF (PSA). If the CN Tunnel Info is allocated by the SMF, the SMF may provide updated CN tunnel info and UL Packet detection rules. In an example, when the SMF receives the operation type that is VN group user plane activation, VN group PDU session activation, and/or the like, the SMF may determine one or more PDU sessions associated with the group (e.g., receiving wireless devices) and perform the N4 session modification for one or more N4 sessions associated with the one or more PDU sessions. In an example, the N4 session modification request may comprise an N4 session modification request comprising the multicast information of the group. The UPF upon receiving the multicast information, may activate the CN tunnel, N3 tunnel, and/or the like for the one or more sessions (N4 sessions, PDU sessions, and/or the like) of the group. The UPF (PSA) may send to the SMF the N4 session modification response. The UPF (PSA) may send an N4 Session Establishment Response message to the SMF. If the UPF (PSA) allocates CN Tunnel Info of UPF (PSA), it may provide CN Tunnel Info to the SMF. The UPF (PSA) may associate the CN Tunnel Info associated with the UEs, the multicast information, the multicast address, and/or the like with UL Packet detection rules provided by the SMF.

(207) In an example embodiment, the SMF may send to the AMF, an Nsmf_PDUSession_UpdateSMContext Response (e.g., comprising N2 SM information (PDU Session ID, QFI(s), QoS profile(s), CN N3 Tunnel Info, S-NSSAI, User Plane Security Enforcement, UE Integrity Protection Maximum Data Rate, RSN), N1 SM Container, Cause) to the AMF. If the UPF that connects to RAN is the UPF (PSA), the CN N3 Tunnel Info is the UL Tunnel Info of the UPF (PSA). If the UPF that connects to RAN may be the new intermediate UPF, the CN N3 Tunnel Info is the UL Tunnel Info of the intermediate UPF. In an example, for a PDU session that the SMF has determined to accept the activation of UP connection, the SMF may generate only N2 SM information and may send Nsmf_PDUSession_UpdateSMContext Response to the AMF to establish the User Plane(s). The N2 SM information may comprise information that the AMF may provide to the NG-RAN.

(208) In an example embodiment, in response to receiving the Nsmf_PDUSession_UpdateSMContext Response from the SMF, the AMF may determine that the transmitting UE-T may send data to a group of UEs (receiving wireless devices, UE-Rs). The AMF may determine the members of the group associated with the multicast information, PDU session IDs (associated with the VN group—receiving wireless devices) received from the SMF, or obtain the group information associated with the multicast information from a repository. The AMF may determine from a list/set of UEs associated with the group or associated with the PDU session IDs received from the SMF, one or more UEs (transmitting wireless devices, receiving wireless devices, and/or the like) that are in idle state and may send one or more paging messages to the one or more UEs in idle state. In an example, the AMF may determine to activate the user plane connection of the UEs that are associated with the group.

(209) In an example embodiment, the AMF may send to the (R)AN node, an N2 request (comprising N2 SM information received from the SMF, security context, Mobility Restriction List, Subscribed UE-AMBR, MM NAS Service Accept, list of recommended cells/TAs/NG-RAN node identifiers, UE Radio Capability, Core Network Assistance Information, Tracing Requirements). The Allowed NSSAI for the Access Type for the UE is included in the N2 message. If the subscription information includes Tracing Requirements, the AMF may include Tracing Requirements in the N2 Request.

(210) In an example embodiment, the (R)AN node may send to the UE (UE-T) an RRC reconfiguration message. The NG-RAN may perform RRC Connection Reconfiguration with the UE depending on the QoS Information for all the QoS Flows of the PDU Sessions whose UP connections are activated and Data Radio Bearers. For a UE-T that was in CM-IDLE state, if the Service Request is not triggered by UE for a signalling connection only, the User Plane security may be established. For a UE that was in CM-IDLE state, if the Service Request is triggered by UE for a signaling connection only, AS security context may be established.

(211) In an example embodiment when a service accept message is received by the UE-T, it may indicate that the service request procedure for the receiving wireless devices may be in progress, completed and/or successful. The service request accept message may indicate that upon completion of N4 related procedures between the SMF and the UPF for the UE-T, the UE-T may transmit data to targeted to the group, by employing the multicast information, multicast address, and/or the like.

(212) In an example embodiment as depicted in FIG. 28, the AMF upon reception of the N2 message that comprises the multicast information, the group information, the indication that the service request is for transmission of data packets for the VN group, activation of user plane connection for the VN group, and/or the like, may perform activation of user plane resources for the receiving wireless devices of the group.

(213) In an example embodiment as depicted in FIG. 29 and FIG. 30, the AMF upon reception of the N2 message that comprises the multicast information, the group information, the indication that the service request is for transmission of data packets for the VN group, activation of user plane connection for the VN group, and/or the like, may perform paging procedure to page the receiving wireless devices of the group. The receiving wireless devices in response to the paging message may perform the UE triggered service procedure as depicted in FIG. 10 and FIG. 11.

(214) In an example embodiment as depicted in FIG. 31, the AMF upon reception of the N11 message comprising the group information, may determine to activate one or more receiving wireless devices of the group. The AMF may perform paging procedure to page the receiving wireless devices of the group. The receiving wireless devices in response to the paging message may perform the UE triggered service procedure as depicted in FIG. 10 and FIG. 11. Upon completion of the service request procedure for the transmitting UE and the receiving UEs, the UE-T may transmit data packets to the group.

(215) In an example embodiment, a wireless device may receive from a session management function via an AMF and a base station, after requesting establishment of a PDU session for joining a group comprising one or more other wireless devices, a message comprising a multicast information, and/or the like. The wireless device may send to an access and mobility management function AMF, a service request message requesting activation of a user plane connection of the PDU session for transmission of data packets to the group, the service request message comprising a service request. The service request may comprise the multicast information, an indication that the service request is for transmission of data packets to the group, and/or the like. The wireless device may receive from the AMF, a service accept message indicating a result of the service request. The wireless device may send to the group, based on the service accept message, the data packets via the user plane connection. The multicast information may comprise a multicast address for transmission of data packets to the group. The multicast information may comprise one or more wireless device identifiers. The one or more wireless device identifiers may correspond to a subset of the group. The sending of the service request message may be in response to receiving a paging message by the wireless device. The sending of the service request message may be in response to determining by the wireless device to send data packets to the group. The result of the service request may indicate that user plane connections are activated for at least one of the one or more other wireless devices. The AMF may determine a group information associated with the multicast information. The AMF may send to the SMF a session management request comprising the group

information. The AMF may receive from the SMF a list PDU sessions associated with the group. The AMF may determine to activate the wireless devices associated with the list of PDU sessions. The AMF may determine the one or more wireless devices of the group based on the multicast information. The AMF may determine that an inactive wireless device of the group requires a user plane connection activation. The service request message may further comprise an indication that the service request is for transmission of data packets to the group.

(216) In an example embodiment, an AMF may receive from a wireless device, a service request message requesting activation of a user plane connection of a PDU session for transmission of data packets to a group. The group may comprise one or more other wireless devices. The service request message may comprise a service request comprising a multicast information. The AMF may determine the one or more other wireless devices of the group based on the multicast information. The AMF may determine that an inactive wireless device of the group requires a user plane connection activation. The AMF may activate a user plane connection of the inactive wireless device. The multicast information may comprise a multicast address for transmission of data packets to a group of wireless devices. The multicast information may comprise identifiers of one or more wireless devices. The one or more wireless devices may be a subset member of the group. The AMF may receive from a SMF a message indicating that the user plane connection for the one or more devices may be activated. The AMF may determine whether the wireless device is allowed to send the service request for the group. The AMF may reject the service request based on the determining. The AMF may send to a SMF a request for activation of user plane connections for the one or more wireless devices. The AMF may send to the one more wireless devices, a paging message. The service request message may further comprise an indication that the service request is for transmission of data packets to the group.

(217) In an example embodiment, a SMF may receive from a wireless device, a service request message requesting activation of a user plane connection for a PDU session for transmission of data packets to a group comprising one or more other wireless devices. The service request message may comprise a service request comprising a group information, multicast information, and/or the like. The SMF may determine one or more PDU session of the group based on the multicast information. The SMF may determine that an inactive PDU session of the group may require a user plane connection activation. The SMF may activate a user plane connection of the inactive PDU session. The service request message may further comprise an indication that the service request is for transmission of data packets to the group. The SMF may send to the AMF a message comprising a list of PDU sessions associated with the group. The AMF may activate an inactive wireless device based on the message.

(218) According to various embodiments, a device such as, for example, a wireless device, off-network wireless device, a base station, a core network device, a core network function, and/or the like, may comprise one or more processors and memory. The memory may store instructions that, when executed by the one or more processors, cause the device to perform a series of actions. Embodiments of example actions are illustrated in the accompanying figures and specification. Features from various embodiments may be combined to create yet further embodiments.

(219) FIG. 36 is an flow diagram as per an aspect of an example embodiment of the present disclosure. At 3610, an access and mobility management function (AMF) may receive a service request message from a first wireless device. The service request message may request activation of a user plane connection of a PDU session for transmission of data packets to a wireless device group comprising one or more second wireless devices. The service request message may comprise multicast information associated with the wireless device group. At 3620, a determination may be made, based on the service request message, to activate a user plane connection of the wireless device group. At 3630, the AMF may send, to a Session Management Function (SMF), a message requesting activation of the user plane connection of the wireless device group.

(220) According to an example embodiment, the multicast information may comprise a multicast

address for transmission of data packets to the wireless device group. the multicast information may comprise identifiers of one or more second wireless devices. The one or more second wireless devices may be a subset of the wireless device group.

(221) According to an example embodiment, the AMF may receive from a SMF, a message indicating that the user plane connection for the one or more second wireless devices is activated. According to an example embodiment, the AMF may determine a group information associated with the multicast information. According to an example embodiment, the AMF may send, to the SMF, a session management request message comprising the group information. According to an example embodiment, the AMF may receive, from the SMF, a list of PDU sessions associated with the wireless device group. The AMF may determine to activate a wireless devices associated with the list of PDU sessions. According to an example embodiment, the service request message may comprise an indication that a service request is for transmission of data packets to the wireless device group.

(222) According to an example embodiment, the AMF may receive, from the first wireless device, a PDU session establishment request message comprising an indication that the PDU session is for a group communication session. The AMF may send, to the first wireless device after requesting establishment of a PDU session, a session configuration message comprising the multicast information associated with the wireless device group.

(223) According to an example embodiment, the AMF may send, to the one or more second wireless devices, a paging message. According to an example embodiment, the service request message may comprise an indication that the service request message is for transmission of data packets to the wireless device group. The wireless device group may comprise the first wireless device.

(224) In this specification, a and an and similar phrases are to be interpreted as at least one and one or more. In this specification, the term may is to be interpreted as may, for example. In other words, the term may is indicative that the phrase following the term may is an example of one of a multitude of suitable possibilities that may, or may not, be employed to one or more of the various embodiments. If A and B are sets and every element of A is also an element of B, A is called a subset of B. In this specification, only non-empty sets and subsets are considered. For example, possible subsets of $B = \{\text{cell1}, \text{cell2}\}$ are: $\{\text{cell1}\}$, $\{\text{cell2}\}$, and $\{\text{cell1}, \text{cell2}\}$.

(225) In this specification, parameters (Information elements: IEs) may comprise one or more objects, and each of those objects may comprise one or more other objects. For example, if parameter (IE) N comprises parameter (IE) M, and parameter (IE) M comprises parameter (IE) K, and parameter (IE) K comprises parameter (information element) J, then, for example, N comprises K, and N comprises J. In an example embodiment, when one or more messages comprise a plurality of parameters, it implies that a parameter in the plurality of parameters is in at least one of the one or more messages, but does not have to be in each of the one or more messages.

(226) Many of the elements described in the disclosed embodiments may be implemented as modules. A module is defined here as an isolatable element that performs a defined function and has a defined interface to other elements. The modules described in this disclosure may be implemented in hardware, software in combination with hardware, firmware, wetware (i.e. hardware with a biological element) or a combination thereof, which may be behaviorally equivalent. For example, modules may be implemented as a software routine written in a computer language configured to be executed by a hardware machine (such as C, C++, Fortran, Java, Basic, Matlab or the like) or a modeling/simulation program such as Simulink, Stateflow, GNU Octave, or LabVIEWMathScript. Additionally, it may be possible to implement modules using physical hardware that incorporates discrete or programmable analog, digital and/or quantum hardware. Examples of programmable hardware comprise: computers, microcontrollers, microprocessors, application-specific integrated circuits (ASICs); field programmable gate arrays (FPGAs); and complex programmable logic devices (CPLDs). Computers, microcontrollers and microprocessors

are programmed using languages such as assembly, C, C++ or the like. FPGAs, ASICs and CPLDs are often programmed using hardware description languages (HDL) such as VHSIC hardware description language (VHDL) or Verilog that configure connections between internal hardware modules with lesser functionality on a programmable device. Finally, it needs to be emphasized that the above mentioned technologies are often employed in combination to achieve the result of a functional module.

(227) Example embodiments of the invention may be implemented using various physical and/or virtual network elements, software defined networking, virtual network functions.

(228) The disclosure of this patent document incorporates material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, for the limited purposes required by law, but otherwise reserves all copyright rights whatsoever.

(229) While various embodiments have been described above, it should be understood that they have been presented by way of example, and not limitation. It will be apparent to persons skilled in the relevant art(s) that various changes in form and detail can be made therein without departing from the spirit and scope. In fact, after reading the above description, it will be apparent to one skilled in the relevant art(s) how to implement alternative embodiments. Thus, the present embodiments should not be limited by any of the above described exemplary embodiments. In particular, it should be noted that, for example purposes, the above explanation has focused on the example(s) using 5G AN. However, one skilled in the art will recognize that embodiments of the invention may also be implemented in a system comprising one or more legacy systems or LTE. The disclosed methods and systems may be implemented in wireless or wireline systems. The features of various embodiments presented in this invention may be combined. One or many features (method or system) of one embodiment may be implemented in other embodiments. A limited number of example combinations are shown to indicate to one skilled in the art the possibility of features that may be combined in various embodiments to create enhanced transmission and reception systems and methods.

(230) In addition, it should be understood that any figures which highlight the functionality and advantages, are presented for example purposes. The disclosed architecture is sufficiently flexible and configurable, such that it may be utilized in ways other than that shown. For example, the actions listed in any flowchart may be re-ordered or optionally used in some embodiments.

(231) Further, the purpose of the Abstract of the Disclosure is to enable the U.S. Patent and Trademark Office and the public generally, and especially the scientists, engineers and practitioners in the art who are not familiar with patent or legal terms or phraseology, to determine quickly from a cursory inspection the nature and essence of the technical disclosure of the application. The Abstract of the Disclosure is not intended to be limiting as to the scope in any way.

(232) Finally, it is the applicant's intent that only claims that include the express language means for or step for be interpreted under 35 U.S.C. 112. Claims that do not expressly include the phrase means for or step for are not to be interpreted under 35 U.S.C. 112.

Claims

1. A method comprising: receiving, by an access and mobility management function (AMF) from a first wireless device, a non-access stratum (NAS) message comprising an identifier (ID) of a group communication session for at least one of: multicasting; or broadcasting; receiving, by the AMF from a session management function (SMF) a message comprising: a list of one or more second wireless devices associated with the group communication session; and a list of one or more packet data unit (PDU) sessions; determining, by the AMF and based on a state of the one or more second wireless devices, to page the one or more second wireless devices; and receiving, by the AMF from

the one or more second wireless devices, one or more service request messages.

2. The method of claim 1, wherein the list of one or more PDU sessions is received via a list of associated PDU sessions IDs.

3. The method of claim 1, wherein the message, from the SMF, further comprises the ID of the group communication session.

4. The method of claim 1, wherein the message, from the SMF, further comprises reachability information.

5. The method of claim 1, wherein the message, from the SMF, further comprises an allocation and retention priority (ARP) and a 5G quality of service identifier (5QI).

6. The method of claim 1, further comprising based on the determining to page the one or more second wireless devices, sending, by the AMF to the one or more second wireless devices, a group paging message.

7. The method of claim 6, wherein the paging message comprises an indication indicating the group communication session.

8. An access and mobility management function (AMF) comprising: one or more processors; and memory storing instructions that, when executed by the one or more processors, cause the AMF to: receive, from a first wireless device, a non-access stratum (NAS) message comprising an identifier (ID) of a group communication session for at least one of: multicasting; or broadcasting; receive, from a session management function (SMF), a message comprising: a list of one or more second wireless devices associated with the group communication session; and a list of one or more packet data unit (PDU) sessions; determine, based on a state of the one or more second wireless devices, to page the one or more second wireless devices; and receive, from the one or more second wireless devices, one or more service request messages in response to the paging.

9. The AMF of claim 8, wherein the list of one or more PDU sessions is received via a list of associated PDU sessions IDs.

10. The AMF of claim 8, wherein the message, from the SMF, further comprises the ID of the group communication session.

11. The AMF of claim 8, wherein the message, from the SMF, further comprises reachability information.

12. The AMF of claim 8, wherein the message, from the SMF, further comprises an allocation and retention priority (ARP) and a 5G quality of service identifier (5QI).

13. The AMF of claim 8, wherein, based on the determining to page the one or more second wireless devices, the instructions further cause the AMF to send, to the one or more second wireless devices, a group paging message.

14. The AMF of claim 13, wherein the paging message comprises an indication indicating the group communication session.

15. A non-transitory computer-readable medium comprising instructions that, when executed by one or more processors of an access and mobility management function (AMF), cause the AMF to: receive, from a first wireless device, a non-access stratum (NAS) message comprising an identifier (ID) of a group communication session for at least one of: multicasting; or broadcasting; receive, from a session management function (SMF), a message comprising: a list of one or more second wireless devices associated with the group communication session; and a list of one or more packet data unit (PDU) sessions; determine, based on a state of the one or more second wireless devices, to page the one or more second wireless devices; and receive, from the one or more second wireless devices, one or more service request messages in response to the paging.

16. The non-transitory computer-readable medium of claim 15, wherein the list of one or more PDU sessions is received via a list of associated PDU sessions IDs.

17. The non-transitory computer-readable medium of claim 15, wherein the message, from the SMF, further comprises the ID of the group communication session.

18. The non-transitory computer-readable medium of claim 15, wherein the message, from the

SMF, further comprises reachability information.

19. The non-transitory computer-readable medium of claim 15, wherein the message, from the SMF, further comprises an allocation and retention priority (ARP) and a 5G quality of service identifier (5QI).

20. The non-transitory computer-readable medium of claim 15, wherein, based on the determining to page the one or more second wireless devices, the instructions further cause the AMF to send, to the one or more second wireless devices, a group paging message.
