

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409691
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Danielson; Devin Joseph et al.

Off-road utility vehicle

Abstract

An off-highway recreational vehicle having a longitudinal centerline includes a frame and a rear suspension. The rear suspension includes a left A-arm, wherein the left A-arm has a pivot axis, the pivot axis being on a right-hand side of the longitudinal centerline.

Inventors: Danielson; Devin Joseph (Saint Cloud, MN), Krone; Adam Christian (Becker, MN), Wiater; Nathan Len (Richmond, MN), Swanson; Aaron Lee (Kandiyohi, MN), Halvorson; Erick John (Albany, MN), Grangroth; Douglas Robert (Big Lake, MN), Miller; Kevin James (Big Lake, MN), Spindler; Jared Richard (Albany, MN), Collyer; Leigh Raymond (Sauk Rapids, MN), Hansen; Donald Scott (Big Lake, MN), Wood; Joseph Patrick (Becker, MN), MacDonald; Todd (Balderson, CA)

Applicant: Arctic Cat Inc. (Thief River Falls, MN)

Family ID: 63916417

Assignee: Arctic Cat Inc. (Thief River Falls, MN)

Appl. No.: 18/593394

Filed: March 01, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240253409 A1	Aug. 01, 2024

Related U.S. Application Data

continuation parent-doc US 17325522 20210520 ABANDONED child-doc US 18593394
continuation parent-doc US 15927524 20180321 US 11014419 20210525 child-doc US 17325522
us-provisional-application US 62474562 20170321

Publication Classification

Int. Cl.: **B60G3/20** (20060101); **B60G7/00** (20060101); **B60G15/06** (20060101); **B60G21/055** (20060101); **B60J5/04** (20060101); **B60K11/04** (20060101); **B60K11/08** (20060101); **B60K13/02** (20060101); **B60K13/04** (20060101); **B60K15/03** (20060101); **B60K17/344** (20060101); **B60K20/06** (20060101); **B60N2/015** (20060101); **B60N2/02** (20060101); **B60N2/24** (20060101); **B60N3/04** (20060101); **B60T1/08** (20060101); **B60T7/04** (20060101); **B60T7/06** (20060101); F16H57/02 (20120101); F16H57/029 (20120101); F16H57/035 (20120101); F16H59/02 (20060101); F16H59/10 (20060101)

U.S. Cl.:

CPC **B60G3/20** (20130101); **B60G7/001** (20130101); **B60G15/062** (20130101); **B60G21/055** (20130101); **B60J5/048** (20130101); **B60K11/04** (20130101); **B60K11/08** (20130101); **B60K13/02** (20130101); **B60K13/04** (20130101); **B60K15/03** (20130101); **B60K17/344** (20130101); **B60K20/06** (20130101); **B60N2/015** (20130101); **B60N2/02** (20130101); **B60N2/24** (20130101); **B60N3/04** (20130101); **B60T1/08** (20130101); **B60T7/04** (20130101); **B60T7/06** (20130101); B60G2200/144 (20130101); B60G2200/156 (20130101); B60G2202/135 (20130101); B60G2204/129 (20130101); B60G2204/416 (20130101); B60G2206/124 (20130101); B60G2300/07 (20130101); F16H2057/02065 (20130101); F16H57/029 (20130101); F16H57/035 (20130101); F16H59/0278 (20130101); F16H59/10 (20130101)

Field of Classification Search

CPC: B60G (3/20); B60G (7/001); B60G (2200/156); B60G (2206/124); B60G (2300/07)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1687590	12/1927	Randol	N/A	N/A
2085738	12/1936	Coleman	N/A	N/A
2138438	12/1937	Max	N/A	N/A
2150456	12/1938	Perrine	N/A	N/A
RE21348	12/1939	Haltenberger	280/124.136	B62D 7/00
2263107	12/1940	Smirl	280/124.164	B60G 11/00
2344072	12/1943	Otto	N/A	N/A
RE22955	12/1946	Penney	N/A	N/A
2481943	12/1948	Murphy et al.	N/A	N/A
RE23623	12/1952	Randol	N/A	N/A
2643897	12/1952	Chowning	N/A	N/A
2669315	12/1953	Butterfield	267/67	B60G 9/00
RE24108	12/1955	Felt	N/A	N/A
RE24122	12/1955	Randol	N/A	N/A
2805550	12/1956	Ayers	N/A	N/A
2942893	12/1959	Nallinger	N/A	N/A
3107762	12/1962	Snyder et al.	N/A	N/A
3189118	12/1964	Arning	267/221	B60G 3/20

3254734	12/1965	Georg	N/A	N/A
3583160	12/1970	Nakamura	N/A	N/A
3598385	12/1970	Parsons	N/A	N/A
3627379	12/1970	Faust	N/A	N/A
3630303	12/1970	Froumajou	280/124.136	B60G 15/062
3691522	12/1971	Hocking et al.	N/A	N/A
3743047	12/1972	Dapolito	N/A	N/A
3881741	12/1974	Muller	280/86.757	B60G 3/20
3922030	12/1974	Stedman	N/A	N/A
3939720	12/1975	Aaen et al.	N/A	N/A
4046403	12/1976	Yoshida	280/124.145	B60G 3/02
4138155	12/1978	Chrysler	N/A	N/A
4217970	12/1979	Chika	N/A	N/A
4344718	12/1981	Taylor	N/A	N/A
4373743	12/1982	Parsons	N/A	N/A
4431234	12/1983	Lacey	N/A	N/A
4433594	12/1983	Smirl	N/A	N/A
4441520	12/1983	Bruso et al.	N/A	N/A
4458318	12/1983	Smit et al.	N/A	N/A
4502352	12/1984	Svab	N/A	N/A
4511160	12/1984	Inoue	280/124.148	B60G 15/07
4537446	12/1984	Roney et al.	N/A	N/A
4541654	12/1984	Jonasson	N/A	N/A
4585427	12/1985	Lamarche	N/A	N/A
4589678	12/1985	Lund	N/A	N/A
4590765	12/1985	Leigh-Monstevens	N/A	N/A
4623196	12/1985	Roney	N/A	N/A
4650211	12/1986	Tanahashi	280/124.135	B60G 3/20
4664412	12/1986	Matschinsky	280/771	B60G 3/26
4671532	12/1986	Matschinsky	280/124.135	B60G 99/00
4679847	12/1986	Dirck	N/A	N/A
4679854	12/1986	Putsch et al.	N/A	N/A
4681342	12/1986	Goerich	280/124.15	B60G 3/26
4798400	12/1988	Kosuge	N/A	N/A
4799708	12/1988	Handa et al.	N/A	N/A
4810035	12/1988	Takahashi	N/A	N/A
4840396	12/1988	Kubo	280/124.151	B60G 3/202
4842296	12/1988	Kubo	280/124.136	B60G 3/26
4883287	12/1988	Murakami et al.	N/A	N/A
4887488	12/1988	Miyazaki	N/A	N/A
4908008	12/1989	Gorski	N/A	N/A
4910962	12/1989	Keane	N/A	N/A
4930804	12/1989	Tattermusch	280/124.138	B60G 3/20
4941677	12/1989	Matsumoto	280/124.138	B62D 17/00
4947700	12/1989	Kern et al.	N/A	N/A
4949590	12/1989	Barker et al.	N/A	N/A
4957308	12/1989	Takizawa	280/124.144	B60G 3/20
4966385	12/1989	Iwasaki	280/124.141	B60G 3/265
4968056	12/1989	Haraguchi	280/124.135	B60G 3/20
5048860	12/1990	Kanai	280/124.148	B60G 3/205

5058694	12/1990	Iwanaga	N/A	N/A
5071391	12/1990	Kita	N/A	N/A
5082078	12/1991	Umeda et al.	N/A	N/A
5083433	12/1991	Leigh-Monstevens	N/A	N/A
5086858	12/1991	Mizuta et al.	N/A	N/A
5114175	12/1991	Sakai	280/124.137	B60G 3/20
5125677	12/1991	Ogilvie et al.	N/A	N/A
5152361	12/1991	Hasegawa et al.	N/A	N/A
5161275	12/1991	Simpson et al.	N/A	N/A
5183444	12/1992	Robbins	N/A	N/A
5197755	12/1992	Quick	280/124.141	B60G 11/16
5246084	12/1992	Ferraiuolo et al.	N/A	N/A
5282499	12/1993	Shaw et al.	N/A	N/A
5327989	12/1993	Furuhashi et al.	N/A	N/A
5348334	12/1993	Giltinan	280/124.153	B60G 7/001
5348337	12/1993	Ando	280/124.135	B60G 15/062
5362118	12/1993	Houriez	N/A	N/A
5380035	12/1994	Lee	280/124.145	B60G 3/265
5493863	12/1995	Yanagi et al.	N/A	N/A
5496055	12/1995	Shibahata	280/124.141	B62D 7/18
5498018	12/1995	Wahl et al.	N/A	N/A
5507510	12/1995	Kami	280/124.136	B60G 3/26
5538274	12/1995	Schmitz et al.	N/A	N/A
5560638	12/1995	Lee	280/124.148	B60G 3/202
5560651	12/1995	Kami	180/311	B60K 13/04
5568959	12/1995	Weber et al.	N/A	N/A
5647212	12/1996	Coleman	N/A	N/A
5655372	12/1996	Branum et al.	N/A	N/A
5722724	12/1997	Takei et al.	N/A	N/A
5725273	12/1997	Vernon et al.	N/A	N/A
5743093	12/1997	Nakayoku et al.	N/A	N/A
5782484	12/1997	Kuhn, Jr.	267/248	B60G 3/265
5820150	12/1997	Archer et al.	N/A	N/A
5836659	12/1997	Feigel et al.	N/A	N/A
5860888	12/1998	Lee	N/A	N/A
5868410	12/1998	Kawabe	280/124.134	B60G 3/265
5921341	12/1998	Atkins	N/A	N/A
5921578	12/1998	Sekita	296/203.02	B60K 1/04
5938219	12/1998	Hayami	280/124.135	B60G 3/20
5950748	12/1998	Matsumoto et al.	N/A	N/A
5975541	12/1998	Harara	280/124.135	B60G 7/006
5988757	12/1998	Vishey et al.	N/A	N/A
5992868	12/1998	Orimoto	280/124.138	B60G 3/26
6000706	12/1998	Boberg	280/124.135	B60G 3/20
6076624	12/1999	Izumi et al.	N/A	N/A
6099005	12/1999	Wakatsuki	280/124.135	B60G 7/02
6102481	12/1999	Tateyama	N/A	N/A
6123351	12/1999	Bruehl	280/124.135	B60G 3/20
6142253	12/1999	Mueller et al.	N/A	N/A
6155371	12/1999	Izumi	N/A	N/A

6170597	12/2000	Fukuda	N/A	N/A
6186109	12/2000	Matsuno	N/A	N/A
6212888	12/2000	Nix et al.	N/A	N/A
6223865	12/2000	Lang et al.	N/A	N/A
6238166	12/2000	Collier	N/A	N/A
6257081	12/2000	Gagnon et al.	N/A	N/A
6269895	12/2000	Tanuguchi et al.	N/A	N/A
6290620	12/2000	Tsai et al.	N/A	N/A
6302420	12/2000	Sano	280/124.135	B60G 3/26
6305700	12/2000	Bruehl	280/124.135	B60G 3/26
6306043	12/2000	Annic et al.	N/A	N/A
6338495	12/2001	Lee	280/124.148	B60G 7/003
6343666	12/2001	Olson et al.	N/A	N/A
6354974	12/2001	Kozarekar	N/A	N/A
6378881	12/2001	Stenvall	280/124.171	B60G 3/06
6390486	12/2001	Boes	280/124.171	B60G 11/08
6394555	12/2001	Mizuta et al.	N/A	N/A
6419270	12/2001	Boyle et al.	N/A	N/A
6419608	12/2001	Miller	N/A	N/A
6431569	12/2001	Handa	280/124.138	B60G 3/20
6457729	12/2001	Stenvall	280/124.171	B60G 11/08
6467783	12/2001	Blondelet et al.	N/A	N/A
6471304	12/2001	Deml et al.	N/A	N/A
6488137	12/2001	Katou et al.	N/A	N/A
6508348	12/2002	Sugano	N/A	N/A
6550591	12/2002	Honda	N/A	N/A
6550796	12/2002	Behr	280/124.179	B60G 15/06
6551210	12/2002	Miller	N/A	N/A
6557516	12/2002	Tsutsumikoshi	N/A	N/A
6609436	12/2002	Laws	N/A	N/A
6623067	12/2002	Gabbianelli et al.	N/A	N/A
6688331	12/2003	Demersseman et al.	N/A	N/A
6688616	12/2003	Ziech	N/A	N/A
6695329	12/2003	Handa	280/124.152	B60G 3/18
6719314	12/2003	Schote	280/124.135	B60G 7/001
6727962	12/2003	Adams	N/A	N/A
6752409	12/2003	Kunert	280/124.135	B60G 3/26
6764084	12/2003	Nakamura	280/124.135	B60G 7/02
6767022	12/2003	Chevalier	N/A	N/A
6799781	12/2003	Rasidescu et al.	N/A	N/A
6808238	12/2003	Drott et al.	N/A	N/A
D498435	12/2003	Saito et al.	N/A	N/A
6817647	12/2003	Green	N/A	N/A
6840044	12/2004	Leboisne	N/A	N/A
6863288	12/2004	Van Den Brink et al.	N/A	N/A
6866110	12/2004	Mallette et al.	N/A	N/A
6866322	12/2004	Willard	N/A	N/A
6868932	12/2004	Davis et al.	N/A	N/A
6896087	12/2004	Korenjak et al.	N/A	N/A
6905159	12/2004	Saito et al.	N/A	N/A

6916142	12/2004	Hansen et al.	N/A	N/A
6935672	12/2004	Dehart	N/A	N/A
6938908	12/2004	Oda	280/124.109	B60G 3/26
6942075	12/2004	Buckley et al.	N/A	N/A
D513223	12/2004	Saito et al.	N/A	N/A
6984000	12/2005	Fraisse et al.	N/A	N/A
6996985	12/2005	Bornkessel et al.	N/A	N/A
7000931	12/2005	Chevalier	N/A	N/A
7004484	12/2005	Chevalier	N/A	N/A
7029194	12/2005	Ishikawa et al.	N/A	N/A
7040708	12/2005	Black	N/A	N/A
7048286	12/2005	Eppelein	280/124.106	B60G 3/26
7052051	12/2005	Gaffe et al.	N/A	N/A
7070239	12/2005	Ugrekheldze et al.	N/A	N/A
7083016	12/2005	Chernoff	454/69	B60L 50/16
7083176	12/2005	Soles et al.	N/A	N/A
7114585	12/2005	Man et al.	N/A	N/A
7121623	12/2005	Fujihara et al.	N/A	N/A
7147075	12/2005	Tanaka et al.	N/A	N/A
7147076	12/2005	Izumi	N/A	N/A
7249798	12/2006	Saito et al.	N/A	N/A
7258355	12/2006	Amano	280/124.135	B60G 3/20
7281603	12/2006	Fukuda	N/A	N/A
7281753	12/2006	Curtis, Jr. et al.	N/A	N/A
7311167	12/2006	Takayanagi et al.	N/A	N/A
7331270	12/2007	Booher	N/A	N/A
7347490	12/2007	Kobayashi et al.	N/A	N/A
7359785	12/2007	Yoshida et al.	N/A	N/A
7377295	12/2007	Byers	446/471	B60G 7/00
7445075	12/2007	Ozawa et al.	N/A	N/A
7487985	12/2008	Mighell	N/A	N/A
7506712	12/2008	Kato et al.	N/A	N/A
7506882	12/2008	Gerrard	280/124.145	B60G 7/001
7510199	12/2008	Nash et al.	N/A	N/A
7530420	12/2008	Davis et al.	N/A	N/A
7533754	12/2008	Burrows et al.	N/A	N/A
7537071	12/2008	Kamiya	180/57	B60K 17/043
7571788	12/2008	Barnard	N/A	N/A
7578523	12/2008	Kosuge et al.	N/A	N/A
7578544	12/2008	Shimamura et al.	N/A	N/A
7581464	12/2008	Munz	N/A	N/A
7600769	12/2008	Bessho et al.	N/A	N/A
7607671	12/2008	McConville	280/124.135	B60G 3/20
7640823	12/2009	Bowman et al.	N/A	N/A
7661688	12/2009	Koumura	280/124.135	B60G 7/008
7661689	12/2009	Kinugasa	N/A	N/A
7686379	12/2009	Lemieux	N/A	N/A
7690661	12/2009	Tsuruta et al.	N/A	N/A
7694983	12/2009	Griffiths	280/124.135	B60G 3/20
7717495	12/2009	Leonard et al.	N/A	N/A

7722063	12/2009	Dieziger	N/A	N/A
7753427	12/2009	Yamamura et al.	N/A	N/A
7766344	12/2009	Buma	280/124.152	B60G 3/202
7784807	12/2009	Brandl	280/124.135	B60G 7/008
7798507	12/2009	Hirai	280/124.135	B60G 3/20
7819220	12/2009	Sunsdahl et al.	N/A	N/A
7819428	12/2009	Tsuruta et al.	N/A	N/A
7828364	12/2009	Causey	N/A	N/A
7887116	12/2010	Feng	N/A	N/A
7891684	12/2010	Luttinen	280/124.136	B60G 3/20
7905307	12/2010	Kubota et al.	N/A	N/A
7905803	12/2010	Mochizuki et al.	N/A	N/A
7926862	12/2010	Smith et al.	N/A	N/A
7938410	12/2010	Buma et al.	N/A	N/A
7938481	12/2010	Kobayashi et al.	N/A	N/A
7950486	12/2010	Van et al.	N/A	N/A
7963538	12/2010	Roland	280/124.138	B60G 7/008
8002653	12/2010	Shiozaki et al.	N/A	N/A
8028788	12/2010	Stilwell et al.	N/A	N/A
8052160	12/2010	Hirai	280/124.135	B60G 3/265
8079602	12/2010	Kinsman et al.	N/A	N/A
8100104	12/2011	Widdall et al.	N/A	N/A
8156841	12/2011	Yasuda et al.	N/A	N/A
8157039	12/2011	Melvin et al.	N/A	N/A
8251170	12/2011	Miura	N/A	N/A
8260497	12/2011	Satake et al.	N/A	N/A
8267830	12/2011	Brown	N/A	N/A
8272685	12/2011	Lucas et al.	N/A	N/A
8292352	12/2011	Furman et al.	N/A	N/A
8313136	12/2011	Arnold et al.	N/A	N/A
8328235	12/2011	Schneider et al.	N/A	N/A
8328261	12/2011	Kanazawa et al.	N/A	N/A
8381855	12/2012	Suzuki et al.	N/A	N/A
8382125	12/2012	Sunsdahl et al.	N/A	N/A
8408088	12/2012	Park et al.	N/A	N/A
8418580	12/2012	Ruhlander et al.	N/A	N/A
8439141	12/2012	Bessho et al.	N/A	N/A
8444160	12/2012	Okamoto	280/124.135	B60G 3/20
8459397	12/2012	Bessho et al.	N/A	N/A
8465050	12/2012	Spindler et al.	N/A	N/A
8485541	12/2012	Pozio	N/A	N/A
8556324	12/2012	Takegami et al.	N/A	N/A
8567543	12/2012	Kubota et al.	N/A	N/A
8579310	12/2012	Tanaka et al.	N/A	N/A
8583328	12/2012	Mori	280/5.522	B62D 17/00
8585088	12/2012	Kaku et al.	N/A	N/A
8596405	12/2012	Sunsdahl et al.	N/A	N/A
8607563	12/2012	Takahashi	N/A	N/A
8613335	12/2012	Deckard et al.	N/A	N/A
8613336	12/2012	Deckard et al.	N/A	N/A

8640814	12/2013	Deckard et al.	N/A	N/A
8678409	12/2013	Koide	280/124.135	B60G 7/008
RE44854	12/2013	Henderson	N/A	N/A
8696006	12/2013	Sanschagrin et al.	N/A	N/A
8708359	12/2013	Murray	280/124.148	B60G 7/001
8714618	12/2013	Heit et al.	N/A	N/A
8746394	12/2013	Kuramoto et al.	N/A	N/A
8746719	12/2013	Safranski	280/124.152	B60G 7/008
8752878	12/2013	Yamamoto et al.	N/A	N/A
8752879	12/2013	Heit et al.	N/A	N/A
8827028	12/2013	Sunsdahl et al.	N/A	N/A
8870206	12/2013	Bandy	N/A	N/A
8888163	12/2013	Johnson	N/A	N/A
8893571	12/2013	Rouleau	N/A	N/A
8899039	12/2013	Mouri	N/A	N/A
8899364	12/2013	Al Qanaei	180/89.1	B62D 21/183
8911312	12/2013	Ito et al.	N/A	N/A
8944449	12/2014	Hurd et al.	N/A	N/A
8960348	12/2014	Shomura et al.	N/A	N/A
8973701	12/2014	Holihan et al.	N/A	N/A
8997908	12/2014	Kinsman et al.	N/A	N/A
8998216	12/2014	Maeda	280/5.511	B62D 21/183
9039060	12/2014	Yamamoto et al.	N/A	N/A
9079602	12/2014	Konomi et al.	N/A	N/A
9096273	12/2014	Mohrlock	N/A	B60G 7/02
9102205	12/2014	Kvien et al.	N/A	N/A
9114682	12/2014	Bandy	N/A	N/A
9126581	12/2014	Swales et al.	N/A	N/A
9180773	12/2014	Honda et al.	N/A	N/A
9180801	12/2014	Kennedy et al.	N/A	N/A
9182012	12/2014	Greiss et al.	N/A	N/A
9187023	12/2014	Takahashi et al.	N/A	N/A
9217501	12/2014	Deckard et al.	N/A	N/A
9238395	12/2015	Roland	N/A	B60G 21/007
9254725	12/2015	Okuyama	N/A	B60G 3/20
9279443	12/2015	Kulkarni et al.	N/A	N/A
9308896	12/2015	Schmidt	N/A	N/A
9327587	12/2015	Spindler et al.	N/A	N/A
9341255	12/2015	Ito et al.	N/A	N/A
9381940	12/2015	Gale	N/A	N/A
9393894	12/2015	Steinmetz et al.	N/A	N/A
9394014	12/2015	Girouard et al.	N/A	N/A
9410512	12/2015	Takahashi et al.	N/A	N/A
9440671	12/2015	Schlangen et al.	N/A	N/A
9453573	12/2015	Renner et al.	N/A	N/A
9469173	12/2015	Murray	N/A	B60G 3/202
9512809	12/2015	Tsumiyama et al.	N/A	N/A
9518623	12/2015	Mastie et al.	N/A	N/A
9522664	12/2015	Ohnishi et al.	N/A	N/A
9541179	12/2016	Cooper et al.	N/A	N/A

9545827	12/2016	Goldberg	N/A	B60G 7/02
9545846	12/2016	Sasaki et al.	N/A	N/A
9555702	12/2016	Olli	N/A	N/A
9587689	12/2016	Pongo et al.	N/A	N/A
9623741	12/2016	Honda et al.	N/A	N/A
9669869	12/2016	Kageyama	N/A	B62D 5/00
9694676	12/2016	Bandy	N/A	B60G 3/202
9713976	12/2016	Miller et al.	N/A	N/A
9718351	12/2016	Ripley et al.	N/A	N/A
9719591	12/2016	Wade et al.	N/A	N/A
9764639	12/2016	Park et al.	N/A	N/A
9764767	12/2016	Proulx et al.	N/A	N/A
9771112	12/2016	Spindler et al.	N/A	N/A
9776481	12/2016	Deckard et al.	N/A	N/A
9821784	12/2016	Oosawa	N/A	N/A
9840243	12/2016	Saito	N/A	N/A
9844991	12/2016	Dusini	N/A	B62D 17/00
9845004	12/2016	Hedlund et al.	N/A	N/A
9863523	12/2017	Stocks et al.	N/A	N/A
9873316	12/2017	Lovold et al.	N/A	N/A
9889777	12/2017	Proulx et al.	N/A	N/A
9909659	12/2017	Bessho et al.	N/A	N/A
9987896	12/2017	Schmidt	N/A	B60G 7/001
10030751	12/2017	Taskiran et al.	N/A	N/A
10047846	12/2017	Watanabe	N/A	N/A
10066728	12/2017	Yolitz	N/A	N/A
10077823	12/2017	Ai et al.	N/A	N/A
10207554	12/2018	Schroeder et al.	N/A	N/A
10207555	12/2018	Mailhot et al.	N/A	N/A
10226977	12/2018	Coppuck	N/A	B60G 3/202
10266052	12/2018	Vermeersch et al.	N/A	N/A
10281039	12/2018	Dearden et al.	N/A	N/A
10300877	12/2018	Gordon	N/A	N/A
10350955	12/2018	Langhoff	N/A	B60G 3/20
10363816	12/2018	Takata	N/A	N/A
10399401	12/2018	Schlangen	N/A	B60G 3/20
10442264	12/2018	Mailhot et al.	N/A	N/A
10451181	12/2018	Saarela	N/A	N/A
10479422	12/2018	Hollman et al.	N/A	N/A
10639976	12/2019	Pepe et al.	N/A	N/A
10648554	12/2019	Kuhl et al.	N/A	N/A
10663053	12/2019	Quinn	N/A	N/A
10697532	12/2019	Schleif et al.	N/A	N/A
10738875	12/2019	Stocks et al.	N/A	N/A
10747257	12/2019	Frazier	N/A	N/A
10807426	12/2019	Girelli Consolaro	N/A	B60G 3/20
10807430	12/2019	Babu	N/A	F16F 1/3842
10814855	12/2019	Ganzel et al.	N/A	N/A
10864813	12/2019	Lahr et al.	N/A	N/A
10906518	12/2020	Kim	N/A	N/A

10995843	12/2020	Bessho et al.	N/A	N/A
11014419	12/2020	Danielson	N/A	B60N 3/04
11014420	12/2020	Sawai	N/A	B60G 7/001
11046176	12/2020	Danielson et al.	N/A	N/A
11072216	12/2020	Yang	N/A	B60G 7/005
11167744	12/2020	Wang et al.	N/A	N/A
11173808	12/2020	Swain et al.	N/A	N/A
11242920	12/2021	Li et al.	N/A	N/A
11279217	12/2021	Kraft	N/A	B60G 11/181
11293540	12/2021	Leclair et al.	N/A	N/A
11305619	12/2021	Vanover	N/A	N/A
11318830	12/2021	Iwata et al.	N/A	N/A
11326686	12/2021	Allicock	N/A	N/A
11376910	12/2021	Yamamoto	N/A	B62D 21/11
11691471	12/2022	Okuyama	280/124.156	B60G 7/001
11820194	12/2022	Okuyama	N/A	B60G 7/005
11912097	12/2023	Dong	N/A	B60G 3/202
2001/0024046	12/2000	Mizuta	N/A	N/A
2001/0048207	12/2000	Handa	280/124.135	B60G 15/062
2004/0002405	12/2003	Laukkanen	N/A	N/A
2004/0021286	12/2003	Bombardier et al.	N/A	N/A
2004/0026146	12/2003	Mallette et al.	N/A	N/A
2004/0178600	12/2003	Wagner	N/A	N/A
2004/0206567	12/2003	Kato et al.	N/A	N/A
2004/0207250	12/2003	Porchet et al.	N/A	N/A
2004/0227321	12/2003	Kuroki et al.	N/A	N/A
2005/0046136	12/2004	Sutton	280/124.135	B60G 3/20
2005/0072613	12/2004	Maltais et al.	N/A	N/A
2005/0077098	12/2004	Takayanagi et al.	N/A	N/A
2005/0140176	12/2004	Hampel	N/A	N/A
2005/0186024	12/2004	Ruhlander	N/A	N/A
2006/0038441	12/2005	Justaman et al.	N/A	N/A
2006/0169549	12/2005	Lang et al.	N/A	N/A
2006/0270503	12/2005	Suzuki et al.	N/A	N/A
2007/0021222	12/2006	Voigt	N/A	N/A
2007/0090621	12/2006	Vigen	N/A	N/A
2007/0108712	12/2006	Ryan	N/A	N/A
2007/0219030	12/2006	Ho	N/A	N/A
2007/0228684	12/2006	Bowers	280/124.134	B60G 3/20
2008/0023240	12/2007	Sunsdahl et al.	N/A	N/A
2008/0023249	12/2007	Sunsdahl et al.	N/A	N/A
2008/0100018	12/2007	Dieziger	N/A	N/A
2008/0179116	12/2007	Ikenoya	180/63	B60K 17/356
2008/0265609	12/2007	Orrell et al.	N/A	N/A
2009/0008887	12/2008	Buma	280/5.511	B60G 17/0164
2009/0008890	12/2008	Woodford	N/A	N/A
2009/0120231	12/2008	Choby et al.	N/A	N/A
2009/0184534	12/2008	Smith et al.	N/A	N/A
2009/0194961	12/2008	Dieziger	N/A	N/A

2009/0243339	12/2008	Orr et al.	N/A	N/A
2009/0301830	12/2008	Kinsman et al.	N/A	N/A
2009/0302590	12/2008	Van et al.	N/A	N/A
2010/0155170	12/2009	Melvin et al.	N/A	N/A
2011/0079454	12/2010	Maguire et al.	N/A	N/A
2011/0241325	12/2010	King et al.	N/A	N/A
2012/0043736	12/2011	Okamoto	280/124.135	B60G 3/20
2012/0193163	12/2011	Wimpfheimer et al.	N/A	N/A
2012/0217715	12/2011	Ehrlich et al.	N/A	N/A
2013/0033070	12/2012	Kinsman et al.	N/A	N/A
2013/0038082	12/2012	Bertocchi	N/A	N/A
2013/0087396	12/2012	Ito et al.	N/A	N/A
2013/0113244	12/2012	Kaku et al.	N/A	N/A
2013/0187407	12/2012	Hufnagl	N/A	N/A
2013/0241228	12/2012	Fujiwara et al.	N/A	N/A
2014/0225357	12/2013	Shinbori	280/771	B60R 21/13
2014/0262584	12/2013	Lovold et al.	N/A	N/A
2014/0332298	12/2013	Girouard et al.	N/A	N/A
2015/0015021	12/2014	Breen	N/A	N/A
2015/0259011	12/2014	Deckard et al.	N/A	N/A
2015/0268010	12/2014	Strauss	N/A	N/A
2015/0344005	12/2014	Shand	N/A	N/A
2016/0159180	12/2015	Palatov	280/5.507	B60G 13/003
2016/0238081	12/2015	Knuth	N/A	N/A
2016/0258474	12/2015	Jeong	N/A	N/A
2016/0348731	12/2015	Knuth	N/A	N/A
2017/0002920	12/2016	Bessho et al.	N/A	N/A
2017/0045131	12/2016	Yolitz	N/A	N/A
2017/0152928	12/2016	Byltiauw	N/A	N/A
2017/0174027	12/2016	Mailhot et al.	N/A	N/A
2017/0327049	12/2016	Tsumiyama et al.	N/A	N/A
2017/0341590	12/2016	McLauchlan	N/A	N/A
2018/0031097	12/2017	Matsuura et al.	N/A	N/A
2018/0038401	12/2017	Cloutier et al.	N/A	N/A
2018/0186329	12/2017	Tsumiyama et al.	N/A	N/A
2018/0257467	12/2017	Rodriguez	N/A	N/A
2018/0326843	12/2017	Danielson et al.	N/A	N/A
2019/0120421	12/2018	Ohnishi et al.	N/A	N/A
2019/0170193	12/2018	Rodriguez	N/A	N/A
2019/0193501	12/2018	Brady	N/A	B60G 3/202
2019/0291521	12/2018	Sawai	N/A	B60G 3/202
2019/0367086	12/2018	De Grammont	N/A	B62D 7/18
2020/0262292	12/2019	Younggren et al.	N/A	N/A
2021/0354549	12/2020	Zhao et al.	N/A	N/A
2021/0402875	12/2020	Pham	N/A	B62D 7/14
2022/0219659	12/2021	Wagner et al.	N/A	N/A
2022/0410859	12/2021	Freund	N/A	N/A

OTHER PUBLICATIONS

“Office Action Mailed for CA Application No. 3,003,854 mailed Jun. 25, 2024”, 4 Pages. cited by applicant

“Office Action Received for Application No. 2,998,648 mailed on Aug. 23, 2024”, 3 Pages. cited by applicant

QA1 Bearing Kits, <http://www.qa1.net/suspension/street-performance-racing-shock-accessories/bearing-kits>. cited by applicant

“Kubota RTV1100 brochure”. cited by applicant

“Non-Final Office Action Mailed on Oct. 13, 2023”, 3 Pages. cited by applicant

“Non-Final Office Action Mailed on Oct. 25, 2023”, 7 Pages. cited by applicant

Arctic Cat , “2009 Prowler 1000 Xtz 4X4 Baja Metallic Cat Green”, 82 pages. cited by applicant

Ford , “Electric Power-Assisted Steering (EPAS) | Ford How-To Video”. cited by applicant

Stocksdale, Joel , “John Deere and BMW designed a hybrid backhoe”, Fox News, published Mar. 9, 2017, 2 pages, available at: <http://www.foxnews.com/auto/2017/03I00/john-deere-and-bmw-designed-hybrid-backhoe.html>. cited by applicant

Primary Examiner: Wilhelm; Timothy

Attorney, Agent or Firm: Billion & Armitage

Background/Summary

CROSS-REFERENCE (1) This application claims priority to U.S. Provisional Application No. 62/474,562, filed Mar. 21, 2017, and titled “OFF-ROAD UTILITY VEHICLE”, which is incorporated by reference herein. This application also incorporates by reference the subject matter of co-filed application titled, “Cab and Fasteners for Vehicle Cab”; having inventors Leigh Raymond Collyer, Aaron Lee Swanson, and Matt Eastwood; and Application No. 62/474,556 filed on Mar. 21, 2017, the contents of which are herein incorporated by reference.

BACKGROUND

(1) Side-by-side recreational off-highway vehicles (“ROVs”) are quite capable in a wide variety of riding environments and situations, whether for sport or utility purposes. The ability of the vehicles to carry multiple occupants in a side-by-side seating arrangement makes them socially enjoyable to ride as well. The vehicles can be easy to enter and exit and easy to operate with controls and ergonomics somewhat similar to automobiles. However, unlike most automobiles, ROVs can be driven on harsh off-road terrain. The extent to which such terrain can be accessed depends on multiple factors, including the vehicle width, suspension, turning radius, under-carriage clearance, wheelbase, center of gravity, and power. The arrangement of these aspects and their interrelations can be important in determining the occupant ride characteristics, reliability, ease of maintenance, and terrain and cargo capabilities of the ROV.

SUMMARY

(2) According to some embodiments, an off-highway recreational vehicle is disclosed having a longitudinal centerline and including a frame and a rear suspension. The rear suspension includes a left A-arm, wherein the left A-arm has a pivot axis, the pivot axis being on a right-hand side of the longitudinal centerline.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of the off-road utility vehicle according to some embodiments.
- (2) FIG. 2 is a side view of the off-road utility vehicle according to some embodiments.
- (3) FIG. 3 is a front view of the off-road utility vehicle according to some embodiments.
- (4) FIG. 4 is a rear view of the off-road utility vehicle according to some embodiments.
- (5) FIG. 5 is a front perspective view of the off-road utility vehicle, with body components removed to illustrate the frame, drivetrain, and front/rear suspension components of the utility vehicle according to some embodiments.
- (6) FIG. 6 is a rear perspective view of the off-road utility vehicle, with body components removed to illustrate the
- (7) frame, drivetrain, and front/rear suspension components of the utility vehicle according to some embodiments.
- (8) FIG. 7 is a side view of the off-road utility vehicle, with body components removed to illustrate the frame, drivetrain, and front/rear suspension components of the utility vehicle according to some embodiments.
- (9) FIG. 8 is a front view of the off-road utility vehicle, with body components removed to illustrate the frame, drivetrain, and front/rear suspension components of the utility vehicle according to some embodiments.
- (10) FIG. 9 is a back view of the off-road utility vehicle, with body components removed to illustrate the frame, drivetrain, and front/rear suspension components of the utility vehicle according to some embodiments.
- (11) FIG. 10 is a top view of the off-road utility vehicle, with body components removed to illustrate the frame, drivetrain, and front/rear suspension components of the utility vehicle according to some embodiments.
- (12) FIG. 11 is a perspective view of the off-road utility vehicle, with body components, drivetrain and front/rear suspension components removed to illustrate frame components of the off-road vehicle according to some embodiments.
- (13) FIG. 12 is a side view of the off-road utility vehicle, with body components, drivetrain and front/rear suspension components removed to illustrate frame components of the off-road vehicle according to some embodiments.
- (14) FIG. 13 is a top view of the off-road utility vehicle, with body components, drivetrain and front/rear suspension components removed to illustrate frame components of the off-road vehicle according to some embodiments.
- (15) FIG. 14 is a perspective view of a roll over protection system (ROPS) according to some embodiments.
- (16) FIG. 15 is an exploded view illustrating the connection of a first ROPS connection member to a second ROPS connection member according to some embodiments.
- (17) FIG. 16 is a perspective view of a ROPS including a forward overhead member overlapping with a mating surface according to some embodiments.
- (18) FIG. 17 is a cross-sectional view of ROPS members according to some embodiments.
- (19) FIG. 18 is a side view of second ROPS connection member; and FIGS. 18a-18c are cross-sectional views of the second ROPS connection member according to some embodiments.
- (20) FIG. 19 is a perspective view illustrating an accessory attachment connected to the second ROPS connection member according to some embodiments.
- (21) FIG. 20 is a perspective view of second ROPS connection member having first, second and third connection portions according to some embodiments.
- (22) FIG. 21 is a side view of a brake pedal assembly according to some embodiments.
- (23) FIG. 22 is a top view of a brake pedal assembly according to some embodiments.
- (24) FIG. 23 is a front view of a brake pedal assembly according to some embodiments.

- (25) FIG. **24** is a bottom view of a brake pedal assembly according to some embodiments.
- (26) FIG. **25** is a front view of a brake pedal assembly formed from a single piece of metal according to some embodiments.
- (27) FIG. **26** is a side view of a brake pedal assembly formed from a single piece of metal according to some embodiments.
- (28) FIG. **27** is an exploded view of brake pedal assembly according to some embodiments.
- (29) FIG. **28** is an assembled view of brake pedal assembly according to some embodiments.
- (30) FIG. **29** is a side view of a front suspension system according to some embodiments.
- (31) FIG. **30** is a top view of a front suspension system according to some embodiments.
- (32) FIG. **31** is a front view of a front suspension system according to some embodiments.
- (33) FIG. **32** is a bottom view of a front suspension system according to some embodiments.
- (34) FIG. **33** is a side view of a front spring and front anti-roll bar (ARB) connected to front upper A-arm according to some embodiments.
- (35) FIG. **34** is a top view illustrating the connection of front ARB to front upper A-arm according to some embodiments.
- (36) FIG. **35** is a front view illustrating the connection of front ARB to front upper A-arm according to some embodiments.
- (37) FIG. **36** is a bottom view illustrating the connection of front ARB to front upper A-arm according to some embodiments.
- (38) FIG. **37** is an exploded view of the upper A-arm according to some embodiments.
- (39) FIG. **38** is an assembled view of the upper A-arm according to some embodiments.
- (40) FIG. **39** is a side view of a rear suspension system according to some embodiments.
- (41) FIG. **40** is a top view of a rear suspension system according to some embodiments.
- (42) FIG. **41** is a front view of a rear suspension system according to some embodiments.
- (43) FIG. **42** is a bottom view of a rear suspension system according to some embodiments.
- (44) FIG. **43** is a side view illustrating connection of a rear anti-roll bar (ARB) to rear upper A-arm according to some embodiments.
- (45) FIG. **44** is a top view illustrating connection of a rear anti-roll bar (ARB) to rear upper A-arm according to some embodiments.
- (46) FIG. **45** is a front view illustrating connection of a rear anti-roll bar (ARB) to rear upper A-arm according to some embodiments.
- (47) FIG. **46** is a bottom view illustrating connection of a rear anti-roll bar (ARB) to rear upper A-arm according to some embodiments.
- (48) FIG. **47** is a perspective view illustrating the relationship between upper A-arm and lower A-arm according to some embodiments.
- (49) FIG. **48** is a perspective view illustrating the connection of tie rods to a steering rack according to some embodiments.
- (50) FIG. **49** is a perspective view illustrating the connection of tie rods to a steering rack according to some embodiments.
- (51) FIG. **50** is a perspective view illustrating the connection of tie rods to a steering rack according to some embodiments.
- (52) FIG. **51** is a perspective view illustrating the connection of tie rods to a steering rack according to some embodiments.
- (53) FIG. **52** is a side views illustrating the connection of tie rods to a steering rack according to some embodiments.
- (54) FIG. **53** is a side views illustrating the connection of tie rods to a steering rack according to some embodiments.
- (55) FIG. **54** is a rear view illustrating the connection of tie rods to the steering rack according to some embodiments.
- (56) FIG. **55** is a top view illustrating the connection of tie rods to the steering rack according to

some embodiments.

(57) FIG. 55A is a perspective view of the front upper cross bracket according to some embodiments.

(58) FIG. 55B is a perspective view of the front upper cross bracket according to some embodiments.

(59) FIG. 56 is a perspective view illustrating the driveline according to some embodiments.

(60) FIG. 57 is a top view of the engine and transmission according to some embodiments.

(61) FIG. 58 is an exploded view of the continuously variable transmission (CVT) and transmission relative to the engine according to some embodiments.

(62) FIG. 59 is an exploded view of front drive shaft and front drive assembly according to some embodiments, and FIG. 59A is a cross-sectional view taken along line 59A-59A according to some embodiments.

(63) FIG. 60 is a perspective view of front drive assembly and CVT cover according to some embodiments.

(64) FIG. 61 is a side view illustrating the connection of front drive shaft to the transmission according to some embodiments.

(65) FIG. 62 is a side view illustrating the connection of front drive shaft to the transmission according to some embodiments.

(66) FIG. 63 is a perspective view illustrating standoff members and flywheel attached to a prime mover according to some embodiments.

(67) FIG. 64 is a perspective view of the continuously variable transmission (CVT) and associated CVT intake according to some embodiments.

(68) FIG. 64A is a perspective view of the continuously variable transmission (CVT) and associated CVT intake according to some embodiments.

(69) FIG. 64B is a perspective view of the flywheel located within the continuously variable transmission (CVT) according to some embodiments.

(70) FIG. 65 is a perspective view of the CVT cover according to some embodiments.

(71) FIG. 66 is an exploded view of the CVT cover assembly according to some embodiments.

(72) FIG. 67 is a side view of CVT cover assembly according to some embodiments.

(73) FIG. 68 is a rear view of CVT cover assembly according to some embodiments.

(74) FIG. 69 is a magnified view of a portion of the CVT over and intermediate CVT cover highlighted in FIG. 68 according to some embodiments.

(75) FIG. 70 is a perspective view illustrating the mounting of inner CVT cover to a mount plate adjacent to the engine according to some embodiments.

(76) FIG. 71 is a side view of the steering column assembly and the gear selector assembly according to some embodiments.

(77) FIG. 72 is a top view of the steering column assembly and the gear selector assembly according to some embodiments.

(78) FIG. 73 is a perspective view of gear selector assembly according to some embodiments.

(79) FIG. 74 is a perspective view of gear selector assembly according to some embodiments.

(80) FIG. 75 is an exploded view of the steering column assembly according to some embodiments.

(81) FIG. 76 is an assembled view of the steering column assembly according to some embodiments.

(82) FIG. 77 is a front view of the seating area according to some embodiments.

(83) FIG. 78 is a rear perspective view of the seating area according to some embodiments.

(84) FIG. 79 is a rear perspective view of the seating area according to some embodiments.

(85) FIG. 80 is a front perspective view of the seating area according to some embodiments.

(86) FIG. 81 is a top view of the floorboards included in the seating area.

(87) FIG. 82 is a cross-sectional view of the floorboards taken along line 82-82 according to some embodiments.

(88) FIG. **83** is a cross-sectional view of the floorboards taken along line **83-83** according to some embodiments.

(89) FIG. **84** is a perspective view of the seating area that includes the seatback body panel and upwardly extending floorboard portion according to some embodiments.

(90) FIG. **85** is an isometric view illustrating the coupling of the seatback body panel with the ROPS cross member according to some embodiments.

(91) FIG. **86** is a rear view of seat backs according to some embodiments.

(92) FIG. **87** is a front view of seat backs according to some embodiments.

(93) FIG. **88** is a front view of seat bases and seat backs according to some embodiments.

(94) FIG. **89** is a back view of seat bases and seat backs according to some embodiments.

(95) FIG. **90** is a top view of a first seat base according to some embodiments.

(96) FIG. **91** is a bottom view of a first seat base according to some embodiments.

(97) FIG. **92** is a top view of a second seat base according to some embodiments.

(98) FIG. **93** is a bottom view of a second seat base according to some embodiments.

(99) FIG. **94** is a perspective view that illustrates rotation of the seat bases relative to the seat backs and removal of the seat bases from the seat support frame according to some embodiments.

(100) FIG. **95** is a perspective view that illustrates rotation of the seat bases relative to the seat backs and removal of the seat bases from the seat support frame according to some embodiments.

(101) FIG. **96** is a perspective view illustrating the connection of seat backs and seat bases to the seat support frame according to some embodiments.

(102) FIG. **97** is a perspective view illustrating the connection of seat backs and seat bases to the seat support frame according to some embodiments.

(103) FIG. **98** is a perspective view of the bumper assembly according to some embodiments.

(104) FIG. **99** is a perspective view illustrating the cooling system in relation to various other components of the off-road utility vehicle according to some embodiments.

(105) FIG. **100** is a perspective view illustrating the cooling system in relation to various other components of the off-road utility vehicle according to some embodiments.

(106) FIG. **101** is a perspective view illustrating the cooling system in relation to various other components of the off-road utility vehicle according to some embodiments.

(107) FIG. **102** is a perspective view illustrating the cooling system in relation to various other components of the off-road utility vehicle according to some embodiments.

(108) FIG. **103** is a perspective view of the exhaust and intake systems in relation to a diesel engine according to some embodiments.

(109) FIG. **104** is a perspective view of the intake system according to some embodiments.

(110) FIG. **105** is a perspective view of the exhaust system according to some embodiments.

(111) FIG. **106** is a perspective view of the of the exhaust and intake systems in relation to a gasoline engine according to some embodiments.

(112) FIG. **107** is a perspective view of the intake system according to some embodiments.

(113) FIG. **108** is a perspective view of the exhaust system in relation to the engine according to some embodiments.

(114) FIG. **109** is a perspective/exploded view of the exhaust system according to some embodiments.

(115) FIG. **110** is a top view of the off-road utility vehicle according to some embodiments.

(116) FIG. **111** is a cross-sectional view of the off-road utility vehicle shown in FIG. **110** taken along line **111-111** according to some embodiments.

(117) FIG. **112** is a rear perspective view of frame components of the off-road utility vehicle according to some embodiments.

(118) FIG. **113** is a side view illustrating tilting of the cargo box according to some embodiments.

(119) FIG. **114** is a top perspective view of the cargo box according to some embodiments.

(120) FIG. **115** is a bottom perspective view of the cargo box according to some embodiments.

(121) FIG. **116** is an exploded view of panels associated with the cargo box according to some embodiments.

(122) FIG. **117** is a top view of the cargo box according to some embodiments.

(123) FIG. **118** is a sectional view of the cargo box taken along line **118-118** according to some embodiments.

(124) FIG. **119** is a sectional view of the cargo box taken along line **119-119** according to some embodiments.

(125) FIG. **120** is a perspective view of fuel system and fuel tank according to some embodiments.

(126) FIG. **121** is a top view of the fuel tank according to some embodiments.

(127) FIG. **122** is a cross-sectional view of the fuel tank taken along line **122-122** according to some embodiments.

(128) FIG. **123** is a perspective view illustrating the attachment of the bumper to the main frame according to some embodiments.

(129) FIG. **124** is an exploded view illustrating attachment of dash panels and hood panels to the main frame according to some embodiments.

(130) FIG. **125** is a perspective view of dash panels and hood panels affixed to the main frame according to some embodiments.

(131) FIG. **126** is an exploded view of the front fascia members attached to the main frame according to some embodiments.

(132) FIG. **127** is a front perspective view of the front fascia members according to some embodiments.

(133) FIG. **128** is an exploded view of the fender panels attached to the main frame according to some embodiments.

(134) FIG. **129** is a rear perspective view of the fender panels according to some embodiments.

(135) FIG. **130** is an exploded view of the cargo box panels affixed to the cargo box according to some embodiments.

(136) FIG. **131** is a perspective view of the cargo box including affixed cargo box panels according to some embodiments.

(137) FIG. **132** is an outer view of the cab door according to some embodiments.

(138) FIG. **133** is a front view of the cab door according to some embodiments.

(139) FIG. **134** is an inner side view of the cab door according to some embodiments.

(140) FIG. **135** is a rear view of the cab door according to some embodiments.

(141) FIG. **136** is a top view of the cab door according to some embodiments.

(142) FIG. **137** is a bottom view of the cab door according to some embodiments.

(143) FIG. **138** is a perspective view of roof assembly, brush guard and windows according to some embodiments.

(144) FIG. **139** is a perspective view of the roof assembly affixed to the ROPS system according to some embodiments.

(145) FIG. **140** is a top view of the roof assembly according to some embodiments.

(146) FIG. **141** is a cross-sectional view of the roof assembly and ROPS system taken along line **141-141** as shown in FIG. **140** according to some embodiments.

(147) FIG. **142** is a cross-sectional view of the roof assembly and ROPS system taken along line **142-142** as shown in FIG. **141** according to some embodiments.

(148) FIG. **143** is a perspective view of the seat support frame according to some embodiments.

(149) In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in difference views. The drawings illustrate generally, by way of example, but not by way of limitation, various embodiments discussed in the present document.

DETAILED DESCRIPTION

(150) As shown in FIG. **1**, a utility vehicle **10** has a body **12**, a frame **14**, and a plurality of ground engaging members **16** (e.g., tires, tracks). In at least some embodiments, the utility vehicle **10**

includes a cargo carrying portion such as a cargo box **18**. As shown in FIG. **1**, the cargo box **18** is rearward of a seating area **20**. The frame **14** includes structural members **22** which are coupled together (e.g., welded, bolted, glued). Further, the structural members **22** can be tubular steel or aluminum, stamped sheet metal (e.g., steel, aluminum), hydroformed, cast, forged, or formed in any other suitable manner. The utility vehicle **10** can be 2-wheel or 4-wheel drive. Further, it can have any suitable style of drive system. In some embodiments, the utility vehicle **10** is 4-wheel drive and includes a differential in both the front end and rear end of the vehicle **10**. The differentials can include optional locking differentials or they can be open differentials, which can be manually selectable by an operator or engaged automatically in response to terrain conditions (e.g., wheel slip). In some embodiments, the vehicle has a limited slip differential (e.g., clutch pack, Quaife, Torsen) or any other suitable configuration (e.g., spool). In other embodiments, the utility vehicle is a 2-wheel drive system. The 2-wheel drive system may be a rear-wheel drive system or a front-wheel drive system.

(151) As further illustrated in FIGS. **1** and **5**, the seating area **20** includes one or more seats **24**. The seats **24** can be arranged in a side-by-side configuration and can include bench seating or bucket seating. As shown in FIG. **1**, for example, the seats **24** are arranged in a three-abreast configuration. The seats **24** can further be arranged in a **60/40** arrangement. Further, in some embodiments, one or more of the seat bottoms and/or seat backs is adjustable. In some embodiments, the driver's seat **24a** is adjustable (e.g., forward and back) and one or more of the passenger seats (**24b**, **24c**) are not adjustable. In some embodiments, both the driver's seat **24a** and one or more of the passenger seats **24b**, **24c** are adjustable. In some embodiments, one or more of the seat base(s) **26a-26c** (FIG. **10**) are adjustable, for example vertically, horizontally, pivotally (e.g., tilt/recline), and/or laterally. In some embodiments one or more of the seat backs **28a-c** are adjustable, for example vertically, horizontally, and/or laterally. The seat bases **26a-c** can be adjustable and the seat backs **28a, b** can be fixed or vice-versa. In some embodiments, at least some of the seats have adjustable backs and adjustable bases. In some embodiments, the seat backs have a lumbar support adjustment, for example via an air filled bladder in a portion of the seat back **28**. In some embodiments, the seat back **28b** extends across two seat bases, for example **26a**, **26b**.

(152) With further regard to FIG. **1**, the utility vehicle **10** has a fuel filling port **30**. In some examples, the fuel filling port **30** is located on the left-hand side of the utility vehicle **10**, however it can be located on any appropriate side or location of the vehicle, for example rear, front, side, etc. In some embodiments, a rear cab-side body panel **32** (e.g., **32a**, left-hand rear cab-side body panel) has a cutout to provide access to the filling port **30**. As shown in FIG. **2**, in some embodiments, a concavity **34** can be formed into the rear cab-side body panel **32** in order to provide access to the fuel cap **36** (FIG. **79**). In some embodiments, fuel cap **36** is located inside the outermost surface of rear cab-side body panel **32**, such that rear cab-side body panel **32** provides protection to fuel cap **36**. The concavity **34** can further be formed provided in a body panel that is independent of the rear cab-side body panel **32**. As illustrated in FIG. **120**, the fuel cap **36**, in turn, is fastened to a filler neck **38**, as discussed in greater detail below.

(153) With further regard to FIG. **6**, the utility vehicle **10** includes a receiver hitch assembly **40**. The receiver hitch assembly **40** can be sized for any suitably sized ball mount (not shown), for example using as a 2" receiver or 1¼" receiver. The receiver hitch assembly **40** further includes a hitch plate **42** which can include one or more rear suspension attachments **44**, as illustrated in FIGS. **11** and **41**.

(154) Returning to FIGS. **1** and **2**, the utility vehicle **10** further can include headlights **46** and taillights **48**. In some embodiments, the utility vehicle **10** can further include brake lights **50** (FIG. **4**) and turn signals **52**. Any of the headlights **46**, taillights **48**, brake lights **50**, and turn signals **52** can be located in any suitable location, for example on the front, rear, or sides of the vehicle, as appropriate. Moreover, the utility vehicle can also include fog lamps, hazard lights, high and low beam lights, light bars, integrated reflectors, etc., as desired. Any lights and reflectors can be placed

in any suitable location, including on the front and rear of the cab **54** (FIG. **2**).

(155) As further shown in FIGS. **1-4**, in some embodiments, the utility vehicle **10** includes one or more headrests **58**. As shown, each of the headrests **58** is coupled to an angled cab member **60**, for example with one or more fasteners (FIG. **4**).

(156) In some embodiments, the vehicle **10** has one or more (e.g., one on each side) doors **62**. The doors **62** can be of any desirable configuration. In some embodiments, one or more of the doors **62** is positioned upwardly of a portion of the lower cab panel **64**. As further shown in FIG. **2**, in some embodiments, one or more of the doors **62** extends upwardly above the top of the seat base **26a**. In some embodiments, one or more of the doors **62** extends upwardly to a height that is level with the top of the seat base **26a** and, in some embodiments, one or more of the doors extends upwardly (e.g., vertically) to a height that is below the top of the seat base **26a**. In some embodiments, one or more of the doors **62** include one or more hinges **766** (FIG. **133-137**). As shown in FIGS. **5** and **133-137**, in some embodiments, the hinges **766** are coupled to a door support member **68** which, in some embodiments, is also referred to as a first seating support member **142** (FIG. **12**) and which extends vertically from an outer lower frame member **70**. As discussed in greater detail below, in some embodiments, the lower cab panel **64** is integrally formed with the rear cab-side body panel **34**, as shown for example in FIG. **128**.

(157) In some embodiments, the door support member **68** is a tubular member which is welded to the outer lower frame member **70**. In some embodiments, the door support member **68** has a rectangular cross-section, however, the door support member can have any suitable cross-section; it can be manufactured from any suitable material (e.g., steel, plastic, carbon-fiber). Further, it can be stamped, extruded, molded, cast, etc. As further shown in FIG. **5**, in some embodiments, the door **62** is hinged at its rear. Alternatively, the door **62** can be hinged at its front, so as to swing forwardly upon opening.

(158) In some embodiments, the vehicle **10** further includes a ROPS (roll-over protection structure) **72**. In some embodiments, the ROPS **72** is attached to the main frame **74**. As used herein, the term "frame" **14** includes both the ROPS **72** and the main frame **74**.

(159) With regard to FIGS. **2**, **5**, **11**, and **12**, in some embodiments, the vehicle **10** further includes at least one side restraint **76**. In some embodiments, the side restraint **76** is coupled to main frame **74** (e.g., rear outer frame member **78**), for example via one or more fasteners or welding. In some embodiments, the side restraint **76** is further coupled to a portion of the ROPS **72**, for example via one or more fasteners. In some embodiments, an upper end of the side restraint **76** is coupled to a portion of the ROPS **72** via a stub **80** that extends from an interior portion of the rear ROPS member **82**. In some embodiments, the stub **80** is welded to an interior portion of the rear ROPS member **82** and the side restraint **76** is attached to the stub via one or more fasteners. In some embodiments, the upper end of the side restraint **76** is attached to the ROPS **72** inwardly of the channel in the ROPS tubing, as shown in FIGS. **139** and **142**. In some embodiments, both ends of the side restraint **76** are coupled to the main frame **74**; in some embodiments, both ends of the side restraint **76** are coupled to the ROPS **72**.

(160) In some embodiments, the vehicle **10** includes a steering wheel **84** which is coupled, for example via a steering linkage, to at least two of the ground engaging members **16**, for example the front ground engaging members **16a**. The steering wheel **84** is coupled to the front ground engaging members **16a** in any suitable way, for example by mechanical steering linkage, electric power steering (EPS), hydraulically assisted power steering, electric power steering without mechanical linkage (e.g., drive-by-wire), electric assisted power steering ((EPAS), e.g., including pull-drift compensation, active nibble control, etc.) or in any other suitable way. Further, in some embodiments, the steering can include variable ratio steering and it can be programmable such that the user can set the steering ratio (and rate-of-change of steering ratio, if it is variable) to illicit a steering response in accordance with the user's or manufacturer's desires (e.g., exhibiting understeer characteristics). In some embodiments, the steering wheel **84** is coupled to the rear ground

engaging members **16b**, for example, via a steering linkage mechanical steering linkage, electric power steering (EPS), hydraulically assisted power steering, electric power steering without mechanical linkage (e.g., drive-by-wire), electric assisted power steering ((EPAS), e.g., including pull-drift compensation, active nibble control, etc.) or in any other suitable way. As illustrated in FIG. 7, an electric power steering unit **102** is positioned between the steering wheel **84** and the steering rack **104**. In some embodiments, the electric power steering unit **102** includes a motor **106** (e.g., direct current or alternating current motor), at least a portion of which is positioned in a vertical plane **110** passing through the motor **106** and brake pedal **108**, the vertical plane extending laterally orthogonal to the longitudinal axis of the vehicle **10**.

(161) With further regard to FIG. 2, in some embodiments, the steering wheel **84** tilts, shown via arrow **86**. A tilt assembly **88** includes a shock **90** to adjust the tilt configuration of the steering wheel **84**.

(162) Turning to FIG. 3, in some embodiments, the utility vehicle **10** has a front bumper **92** which, in some embodiments, is positioned in front of the front ground engaging members **16a**. Further, in some embodiments, the vehicle **10** has at least one hand-hold **94**. The hand-hold **94** can be coupled to a portion of the vehicle **10** in any suitable way and in any suitable location(s). By way of example, in some embodiments, the hand-hold **94** is coupled to a portion of the ROPS **72**, for example an A-frame member **96**. In some embodiments, the hand-hold **94** is coupled to a forward overhead member **98**. In some embodiments, the hand-hold **94** is coupled to a portion of the frame **14**, for example via welding or via one or more fasteners (e.g., bolts).

(163) With regard to FIGS. 6 and 7, in some embodiments, the front bumper **92** is coupled to the main frame **74**, for example via one or more bumper brackets **100**.

(164) As shown in FIGS. 11 and 12, in some embodiments, the frame **14** comprises a rear upper frame member **124**, a rear lower frame member **126**, a front outer frame member **128**, and an upper dash frame member **130**. In some embodiments, the rear upper frame member **124**, rear lower frame member, and an upper dash frame member **130** are horizontal frame members. As shown in FIG. 112, in some embodiments, the frame **14** comprises a left-hand inner frame member **132** and a right-hand inner frame member **134**. In some embodiments, one or both of the left-hand inner frame member **132** and a right-hand inner frame member **134** includes one or more bends **136**. In some embodiments, the frame **14** comprises angled connecting member **138**; in some embodiments, the angled connecting member **138** is coupled to the outer lower frame member **70**. In some embodiments, the frame **14** includes a ROPS support member **140**, which, in some embodiments is rearward of the rear outer frame member **78**. In some embodiments, the frame includes a first seating support member **142** and a second seating support member **144**; in some embodiments, the first seating support member **142** is coupled to the outer lower frame member **70** and the second seating support member **144** is coupled to the rear outer frame member **78** (e.g., by welding or via one or more fasteners). As shown for example in FIGS. 11 and 12, the first seating support member **142** extends vertically and slightly rearwardly, however the first seating support member **142** can have any suitable configuration. Further, as shown in FIGS. 11 and 12, the second seating support member **144** extends horizontally. In some embodiments, the first seating support member **142** is coupled to the second seating support member **144**.

(165) In some embodiments, a seat support frame **146** is coupled to the frame **14**, e.g., main frame **74**. In at least some embodiments, the seat support frame **146** includes a plurality of structural members. In some embodiments, the seat support frame **146** includes one or more lateral seat support frame members **148** and one or more longitudinal seat support frame members **150**. As shown in FIG. 143, in some embodiments, the lateral seat support frame members **148** include first and second lateral support frame members **148a** and **148b**, respectively.

(166) As shown in FIG. 143, in some embodiments, the longitudinal seat support frame members **150** include a bent portion **152**. In some embodiments, the seat support frame **146** is coupled to the main frame **74** via one or more fasteners or weldments. In some embodiments, the seat support

frame **146** is coupled to the second seating support member **144** via a plurality of fasteners. Further, in some embodiments, the seat support frame **146** is coupled to the lateral rear cab frame member **154** via a plurality of fasteners.

(167) Returning to FIGS. **11** and **12**, in some embodiments, the frame **14** includes rear joining frame member **156**, which couples the rear upper cross member **178** and rear lower frame member **126**. In some embodiments, the frame **14** has an intermediate joining frame member **158**, which couples the box support member **160** and rear lower frame member **126** at a location forward of the rear joining frame member **156**. The box support member **160**, in turn, is coupled to left and right rear upper frame members **124a**, **124b** (FIG. **13**).

(168) With further regard to FIGS. **12** and **13**, the frame **14** includes longitudinal intermediate rear frame member **162**, which couples the rear joining frame member **156** and intermediate joining frame member **158**. In some embodiments, the frame **14** additionally include a front upper rear-suspension support member **164**, a rear upper rear-suspension support member **166**, a front lower rear-suspension support member **168**, and a rear lower rear-suspension support member **170**. In some embodiments, the front upper rear-suspension support member **164** and rear upper rear-suspension support member **166** extend between opposing longitudinal intermediate rear frame members **162a** and **162b** (FIG. **13**). In some embodiments, the front lower rear-suspension support member **168** and rear lower rear-suspension support member **170** extend between opposing rear lower frame members **126a** and **126b** (FIG. **112**). In some embodiments, the frame **14** further includes an intermediate lower rear-suspension support member **172** which extends between the rear lower frame members **126a** and **126b**. As will be appreciated from certain of the drawings, frame members, body panels, etc., may be, where appropriate, referred to via a suffix 'a' or 'b'.

(169) As further shown in FIG. **112**, in some embodiments, the frame **14** includes a third panel **174**. In some embodiments, one or more of the first panel **114**, second panel **122**, and third panel **174** includes one or more stiffening ribs **176**. The stiffening ribs can be formed via a stamping operation, for example. In some embodiments, the third panel **174** is welded (or otherwise coupled) to the main frame **74**. In some embodiments, one, two, or all of the first panel **114**, second panel **122**, and third panel **174** are formed from a metallic material such as steel or aluminum. Where the frame **14** is made of steel, for example, and one or more of the panels (**114**, **122**, **174**) are welded thereto, the panels (**114**, **122**, **174**) may also be formed of steel.

(170) With additional reference to FIGS. **11** and **112**, in some embodiments, the frame **14** includes lower front frame member **180**, longitudinal intermediate front frame member **182**, front joining frame member **184**, front intermediate joining frame member **186**, intermediate dash support member **188**, front angled connecting member **190**, and front upper cross member **192**. In some embodiments, the lower front frame member **180** includes rear lower front-suspension support member **194**. In some embodiments, the lower front frame member **180** is coupled to a front frame bracket **196**. In some embodiments, the frame **14** includes a fourth panel **198**. In some embodiments, the fourth panel **198** extends laterally between the opposing lower front frame members **180a** and **180b**, forwardly to the front frame bracket **196**, and rearwardly to a portion of the lateral lower frame member **200**. In some embodiments, the fourth panel **198** is formed from a metallic material, such as steel.

(171) As shown in FIGS. **11** and **12**, an outer fender support member **202** is coupled (e.g., by one or more fasteners) to the front outer frame member **128** and front joining frame member **184**. In some embodiments, the front joining frame member **184** includes a bend such a portion of the front joining frame member **184** includes a vertical portion and a generally longitudinal portion.

(172) In some embodiments, the utility vehicle **10** includes a fuel tank **112**. As shown for example in FIGS. **13** and **78**, in some embodiments, a first panel **114** (e.g., steel panel) supports the fuel tank **112**. In some embodiments, the first panel **114** is coupled (e.g., welded) to one or more adjacent frame members. In some embodiments, the first panel **114** includes one or more depressions **116**. The one or more depressions **116** can be formed, for example, via a sheet metal press. In some

embodiments, one or more of the depressions **116** can be used to locate the fuel tank **112** relative to the first panel **114**. In some embodiments, the fuel tank **112** includes a protruding portion **716** (FIG. **122**) that matches one or more depressions **116**. In some embodiments, one of the depressions **116** corresponds to a low point of the fuel tank **112** where a fuel pick is located within the fuel tank **112**. In some embodiments, the one or more depressions **116** extend downwardly from the first panel **114**. The one or more depressions **116** can extend below the bottom of the adjacent outer lower frame member **70**. In some embodiments, however, for example as shown in FIG. **112**, the bottom of the outer lower frame member **70** is lower than the bottom of one or more of the depressions **116**. In this way, one or more skid plates (not shown) are coupled to the frame **14** below the one or more depressions **116**. Further, as shown in FIG. **12**, in some embodiments, a horizontal plane **120**, defined by the bottom of the frame **14**, is lower than the depressions **116**. Although shown on the left side of the vehicle **10** (e.g., driver's side), the fuel tank **112** can be located in any appropriate location and with any appropriate arrangement. By way of example, the fuel tank **112** can also be located on the passenger side of the vehicle **10**; further, in some embodiments, the vehicle **10** can have two or more fuel tanks **112**, which can be located in any appropriate location and with any appropriate arrangement.

(173) With further regard to FIG. **13**, in some embodiments, the vehicle **10** has a second panel **122**. In some embodiments, the second panel **122** is welded to one or more of the adjacent frame members. In some embodiments, the second panel **122** is located on the right side of the vehicle **10**. The second panel **122** can support, for example, a battery or fuel tank; in at least some embodiments, the second panel **122** provides structural rigidity for the frame **14**. In some embodiments, the first panel **114** provides structural rigidity for the frame **14**. The first panel **114** and second panel **122** can include one or more cut-outs **124**, which can serve to lighten the respective panel.

(174) Turning to FIG. **14**, in some embodiments, the ROPS **72** includes a rear lateral ROPS member **204**, longitudinal ROPS members **206** (**206a**, **206b**), forward overhead member **98**, A-frame members **96** (**96a**, **96b**), rear ROPS members **82** (**82a**, **82b**), and ROPS cross member **208**. In some embodiments, one or more of the ROPS members have a channel, as shown in FIG. **17**, in order to provide mating surfaces **210** for doors, a windshield, rear window, and roof. In some embodiments, forward overhead member **98** is formed from sheet steel and is stamped to provide a portion generally matching the contoured channel of the adjacent ROPS members (e.g., **206a**, **206b**, **96a**, **96b**). In some embodiments, an end edge **212** of the forward overhead member **98** overlaps a portion of the mating surface **210** of longitudinal ROPS member **206**, as shown in FIG. **16**, for example. Further, as shown in FIG. **1**, in some embodiments, an edge **212** of the forward overhead member **98** overlaps a portion of the mating surface **210** of the A-frame members **96**.

(175) With regard to FIG. **15**, in some embodiments, the ROPS **72** includes a first ROPS connection member **214** and a second ROPS connection member **216**. In some embodiments, the first and second ROPS connection members **214**, **216** are formed from castings. In some embodiments, first ROPS connection member(s) is/are welded to an adjacent section of ROPS tubing. As shown in FIG. **15**, for example, in some embodiments, the first ROPS connection member **214** would be welded to the longitudinal ROPS member **206**. Further, in some embodiments, a portion of the first ROPS connection member **214** is inserted into the interior space of the adjacent ROPS tube such that an end of the ROPS tube abuts a ledge of the first ROPS connection member **214**, permitting the first ROPS connection member **214** to be easily located relative to the ROPS tube for welding.

(176) As further illustrated in FIG. **15**, the first ROPS connection member **214** can be fastened to the second ROPS connection member **216**, for example via fasteners (e.g., nuts and bolts).

(177) As shown in FIGS. **18-20**, the second ROPS connection member **216** includes a first connection portion **218**, a second connection portion **220**, and a third connection portion **222**. In some embodiments, the first connection portion **218** is fastened to a mating portion **234** of the first

ROPS connection member **214**. In turn, in some embodiments, the second connection portion **220** is coupled to the rear ROPS member **82**. In some embodiments, the second connection portion **220** is welded to the rear ROPS member **82**, for example by fitting a portion of the second connection portion **220** into a portion of the ROPS member **82**, in a fashion similar to that discussed previously with respect to the first ROPS connection member **214** and longitudinal ROPS member **206**. In some embodiments, the third connection portion **222** is coupled to the rear lateral ROPS member **204**, for example by welding in a fashion similar to that discussed above with respect to the first ROPS connection member **214** and longitudinal ROPS member **206**. Of course, the second ROPS connection member **216** can be coupled to adjacent tubes/connection members in any suitable way, for example with fasteners, by welding, gluing, etc.

(178) As shown in FIG. **19**, in some embodiments, the second ROPS connection member **216** includes an accessory attachment portion **224**. In some embodiments, an accessory can be attached thereto, for example, via fasteners (e.g., bolts) that are inserted into the one or more aperture(s) **226**. Further, nuts can be inserted into opening(s) **228** to mate with bolts inserted through aperture(s) **226**. The walls of the opening(s) **228** can capture sides of a nut such that a tool or wrench is not required to keep the nut from turning as the fastener (e.g., bolt) is tightened against the nut. In some embodiments, a door hinge is attached to the attachment portion **224**, as discussed in greater detail below. In some embodiments, a headache rack or other accessory can be attached to the accessory attachment portion **224**. Further still, in some embodiments, more than one accessory can be attached to the accessory attachment portion **224** at any given time.

(179) Regarding FIGS. **18A-18C** show cross-sectional profiles of the second ROPS connection member **216** along portions thereof. With regard to FIG. **18C**, in some embodiments, one or more nuts (not shown) can be captured by channel **230** such that upon insertion of fasteners (e.g., bolts) through apertures **232** of the first connection portion **218**. In this way, a tool or wrench is not required to keep the nut from turning as the fastener (e.g., bolt) is tightened against the nut.

(180) With regard to FIGS. **21-28**, an embodiment of a brake pedal assembly **236** is shown. The brake pedal assembly **236** is coupled to brake calipers, via brake lines, to stop or slow the vehicle **10** when the brake pedal **240** is depressed. In some embodiments, a portion of the brake pedal assembly **236** is coupled to pedal assembly mount **238**. As shown in FIGS. **25-27**, in some embodiments, the pedal assembly mount **238** is formed from a single piece of sheet steel which has bends **242**. The pedal assembly mount **238** can also be formed from multiple pieces of material and of any suitable material (e.g., plastic, composite, aluminum, alloy, etc.). As further shown, the pedal assembly mount **238** is coupled to the frame **14** and, in some embodiments, it is welded to the upper dash frame member **130** and the intermediate dash support member **188**, though it can be coupled to the frame **14** in any suitable way.

(181) As shown in FIG. **27**, in some embodiments, the brake pedal assembly **236** has a brake pedal arm **244**, to which the brake pedal **240** is coupled (e.g., via one or more fasteners, welding, etc.), a collar member **246**, to which the brake pedal arm **244** is coupled (e.g., via one or more fasteners, welding, etc.), a shoulder bolt **248** around which the brake pedal arm **244** pivots, one or more bushings **250**, through which a portion of the shoulder bolt **248** extends, and a nut **252** (FIG. **25**), which is mated to shoulder bolt **248**. In some embodiments, the brake pedal assembly **236** further includes a master cylinder **254**, having therein a piston (not shown) which is coupled to rod **256**. The rod **256**, in turn, is coupled to fork **258**. The fork **258** is rotatably coupled to the brake pedal arm **244**. As shown in FIGS. **27-28**, the fork **258** is rotatably coupled to the brake pedal arm **244** via coaxial apertures in the fork **258** and brake pedal arm **244**, through which pivot pin **260** extends. Pivot pin **260** is held in place with a retaining clip (e.g., snap ring, c-clip, c-clip), nut, or other appropriate fastener.

(182) In some embodiments, the brake pedal assembly **236** includes at least one pressure switch **262**. The at least one pressure switch **262** has an electrical output to activate the brake light(s) **50** (FIG. **4**) and/or provide a signal to the vehicle's CAN (controlled area network) bus (not shown),

ECU (engine control unit), or other electrical component, when the brake pedal **240** is depressed. (183) In some embodiments, the brake pedal assembly **236** includes a first fluid reservoir **264**. In some embodiments, the first reservoir **264** is positioned vertically above the master cylinder **254** and rearwardly of the front splash panel **268** (FIG. **124**). In some embodiments, the brake pedal assembly **236** includes a second fluid reservoir **266**. In some embodiments, the second fluid reservoir **266** is positioned forwardly of the front splash panel **268** (FIG. **124**) and forwardly of the first fluid reservoir **264** and master cylinder **254**. In some embodiments, the second fluid reservoir **266** is in fluid communication with the first fluid reservoir **264** via fill tube **270**. In some embodiments, the fill tube **270** slopes downwardly and to the rear such that a user can fill the first fluid reservoir **264** via the second fluid reservoir **266**. The second fluid reservoir **266**, being remotely located relative to the first fluid reservoir **264**, allows the user to conveniently fill the brake fluid while the master cylinder **254** and first fluid reservoir **264** are positioned rearwardly of the front splash panel **268**.

(184) In some embodiments, the master cylinder **254** has at least one piston (not shown) which is between 0.5 and 1.25 inches in diameter, though other sizes can also be utilized. In some embodiments, the master cylinder is 0.5-1.0 inches in diameter, and in some embodiments, the piston is 0.75 inches in diameter. Further, in some embodiments, each of the front calipers (not shown) can be single piston calipers or dual piston calipers, though other arrangements can also be used. In some embodiments, the front calipers are dual piston calipers, the pistons having a diameter of between 0.75 inches and 2.0 inches. In some embodiments, the front calipers are dual piston, each piston having a diameter of 1.375 inches. In some embodiments, each rear caliper is a single piston caliper, the pistons having a diameter of between 0.75 inches and 2.0 inches. In some embodiments, the rear calipers are single piston, each piston having a diameter of 1.375 inches. In some embodiments, the rear calipers are dual piston, though other arrangements can also be used.

(185) The brake pedal assembly **236** can also include more than one master cylinder (e.g., two master cylinders), for example one master cylinder in fluid communication with front calipers and one master cylinder in fluid communication with the rear calipers. In some embodiments, the brake pedal assembly **236** includes an adjustable brake balancer, which can be adjusted when the vehicle is stopped or it can be adjusted dynamically from within the seating area during usage of the vehicle **10**.

(186) In some embodiments, the brake pedal assembly **236** has a pedal ratio, which is ratio of distance moved by the center of the face of the brake pedal **240** relative to the distance moved by the pivot pin **260**. In some embodiments, the pedal ratio is between 4:1 and 7:1; in some embodiments, between 4.5:1 and 6.5:1; in some embodiments, between 5.5:1 and 6.5:1; in some embodiments, between 5.5:1 and 6:1. By way of example, in some embodiments, the pedal ratio is 5.8:1. In such an example, the pivot pin **260** moves 1 inch for every 5.8 inches moved by the center of the face of the brake pedal **240**. Other ratios can also be used, as appropriate, depending upon the size of the master cylinder(s), size of the brake caliper pistons, number of brake caliper pistons, brake bias, etc. In some embodiments, the brake pedal assembly **236** further includes power brakes, for example, via a brake booster.

(187) Turning to FIGS. **29-38**, the utility vehicle **10** includes a front suspension **272**. In some embodiments, the front suspension **272** includes a front upper A-arm **274**, front lower A-arm **276**, front knuckle **278**, front damping member **280**, front anti-roll bar (ARB) **282**, front hanger **284**, and front ARB link **286**. In some embodiments, the front ARB link **286** is coupled to the front upper A-arm **274**, for example via a fastener such as a nut. Further, as shown at least in FIGS. **29** and **33**, in some embodiments, a portion of the front ARB link **286** extends through an aperture in the front anti-roll bar **282** and a portion of the front ARB link **286** extends through front link aperture **288** (FIG. **37**) in the front upper A-arm **274**. Although the front ARB link **286** is shown as extending through an aperture in the front upper A-arm **274** (e.g., front link aperture **288**), the front ARB link **286** can, instead, be linked with the front lower A-arm **276**, for example via an aperture or in any appropriate

way. Further, the front ARB link **286** can be linked with the front upper A-arm **274** in any appropriate way. In some embodiments, one or more portions of the front ARB link **286** extends through one or more elastomeric members **290**. In some embodiments, there are four elastomeric members **290**—one on each side of the aperture in the front anti-roll bar **282** (above and below the aperture) and one on each side of the front link aperture **288** in the front lower A-arm (above and below the front link aperture **288**). Thus, in some embodiments, the front suspension **272** includes eight total elastomeric members **290**. In some embodiments, the elastomeric members **290** an annular-cross sectional shape. In some embodiments, the front anti-roll bar **282** connects the left side of the front suspension with the right side of the front suspension in order to reduce roll.

(188) By way of example, in a turn, the outside suspension compresses and the vehicle **10** tends to lean to the outside. The front anti-roll bar **282** connects the left side front suspension with the right side front suspension, thereby reducing roll and increasing the effective spring rate (as compared to the same suspension without the anti-roll bar) and roll stiffness. In some embodiments, however, the vehicle **10** does not includes a front anti-roll bar **282**.

(189) In some embodiments, the front anti-roll bar **282** includes a central portion **291** (FIG. **34**) and arm portions **292** (**292a**, **292b**). As shown, the arm portions **292** extend from the central portion **291**. In some embodiments, the central portion **291** undergoes torsional strain when one of the sides (left or right) of the front suspension is compressed or extended relative to the other side of the front suspension (left or right). The arm portions **292** can be rearwardly extending (as shown in FIG. **34**) or forwardly extending. Further, the central portion **291** can be located inside the frame **14**, outside the frame **14**, above an appropriate frame member, below an appropriate frame member, or otherwise packaged in any appropriate way. As will be appreciated, the material, length of the arm portions **292**, length of the central portion **291**, cross-section of the central portion **291**, cross-section of the arm portions **292**, wall thickness (if not formed from a solid piece of material), diameter, etc., of the anti-roll bar **282** can all be selected to achieve desired suspension characteristics.

(190) In some embodiments, the front damping member **280** include a shock **294** and a spring **296**. In some embodiments, the damping member **280** comprises a coil-over shock, as shown in FIGS. **29-36**, however, other arrangements are also contemplated. By way of example, leaf springs, coils springs, torsion springs can also be used. Further, the shock **294** can be located remotely from the spring.

(191) In some embodiments, the shock **294** is remotely adjustable, for example to adjust shock characteristics. In some embodiments, the shock **294** is adjustable via a mechanical adjuster (e.g., dial) or graphical user interface (GUI), which may employ a controller to adjust shock valving, etc.

(192) In some embodiments, the damping member **280** includes a magnetorheological fluid, such that the shock characteristics can be dynamically adjusted by a microprocessor. Further still, in some embodiments, the utility vehicle **10** may not include a front anti-roll bar **282** (or rear anti-roll bar), as the microprocessor can react to changing conditions encountered by the vehicle, and vary the shock characteristics.

(193) In some embodiments, for example as shown in FIG. **36**, the front lower A-arm **276a** (left hand side of the vehicle) is the same as the front lower A-arm **276b** (right hand side of the vehicle), such that these front lower A-arms are interchangeable. In some embodiments, the front lower A-arm **276** is stamped from a piece of sheet metal (e.g., sheet steel). In some embodiments, the front lower A-arm is welded together from tubular steel, however, the A-arms can be formed in any suitable way and from any suitable material or materials, alloys, etc. Further, in some embodiments, the front lower A-arm **276** is formed from two or more stamped components which are welded together.

(194) With regard to FIG. **37**, in some embodiments, the front upper A-arm **274** has bearings **298** which are pressed into respective receptacles **300**. In some embodiments, the bearings **298** are spherical bearings, however other types of bearings or bushings can also be used. In some

embodiments, the bearings **298** have an inner bearing member **302** and an outer bearing member **304**. In some embodiments, the inner bearing member **302** includes a center portion having a convex spherical portion which is encircled by the outer bearing member **304**. In some embodiments, the inner bearing member **302** has end portions **306**, extending from the center portion. The end portions **306** are encircled by respective seals **309**, which are also inserted into receptacles **300**, to protect the bearing **298**.

(195) With further reference to FIG. **37**, in some embodiments, the front upper A-arm **274** has a ball joint **308** which is retained in the front upper A-arm **274** via a retaining clip (e.g. snap ring **310**), or in any other suitable way (e.g., press fit).

(196) In some embodiments, the front lower A-arm **274** includes a mount **310**, to which the front damping member **280** is coupled.

(197) Although the bearing **298**, receptacles **300**, ball joint **308**, etc., are discussed with respect to the front upper A-arm, these components are, in some embodiments, employed with the front lower A-arm **276**, as well.

(198) Turning now to FIGS. **39-47**, the utility vehicle **10** includes a rear suspension **312**. In some embodiments, the rear suspension **312** includes a rear upper A-arm **314**, rear lower A-arm **316**, rear knuckle **318**, rear damping member **320**, rear anti-roll bar (ARB) **322**, rear hanger **324**, and rear ARB link **326**. In some embodiments, the rear ARB link **326** is coupled to the rear upper A-arm **314**, for example via a fastener such as a nut. As further shown, in some embodiments, a portion of the rear ARB link **326** extends through an aperture in the rear anti-roll bar **322** and a portion of the rear ARB link **326** extends through rear link aperture **328** (FIG. **47**) in the rear upper A-arm **314**. Although the rear ARB link **326** is shown as extending through an aperture in the rear upper A-arm **314**, the rear ARB link **326** can, instead, be linked with the rear lower A-arm **316**, for example via an aperture or in any appropriate way. Further, the rear ARB link **326** can be linked with the rear upper A-arm **314** in any appropriate way. In some embodiments, one or more portions of the rear ARB link **326** extend(s) through one or more elastomeric members **290**, in a fashion similar to that discussed above with respect to the front anti-roll bar.

(199) By way of example, in a turn, the outside suspension compresses and the vehicle **10** tends to lean to the outside. The rear anti-roll bar **322** connects the left side front suspension with the right side front suspension, thereby reducing roll and increasing the effective spring rate (as compared to the same suspension without the anti-roll bar) and roll stiffness. In some embodiments, however, the vehicle **10** does not include a rear anti-roll bar **322**.

(200) In some embodiments, the rear anti-roll bar **322** includes a central portion **330** (FIG. **44**) and arm portions **332** (**332a**, **332b**). As shown, the arm portions **332** extend from the central portion **330**. In some embodiments, the central portion **330** undergoes torsional strain when one of the sides (left or right) of the rear suspension is compressed or extended relative to the other side of the rear suspension (left or right). The arm portions **332** can be rearwardly extending (as shown in FIG. **39**) or forwardly extending. Further, the central portion **330** can be located inside the frame **14**, outside the frame **14**, above an appropriate frame member, below an appropriate frame member, or otherwise packaged in any appropriate way. As will be appreciated, the material, length of the arm portions **332**, length of the central portion **330**, cross-section of the central portion **330**, cross-section of the arm portions **332**, wall thickness (if not formed from a solid piece of material), diameter, etc., of the rear anti-roll bar **322** can all be selected to achieve desired suspension characteristics.

(201) In some embodiments, the rear damping member **320** includes a shock **294** and a spring **296**. In some embodiments, the rear damping member **320** comprises a coil-over shock, as shown in FIGS. **39-43**, **45**, and **46**, however, other arrangements are also contemplated. By way of example, leaf springs, coils springs, torsion springs can also be used. Further, the shock **294** can be located remotely from the spring.

(202) In some embodiments, the shock **294** is remotely adjustable, for example to adjust shock

characteristics. In some embodiments, the shock **294** is adjustable via a mechanical adjuster (e.g., dial) or graphical user interface (GUI), which may employ a controller to adjust shock valving, etc. (203) In some embodiments, the rear damping member **320** includes a magnetorheological fluid, such that the shock characteristics can be dynamically adjusted by a microprocessor. Further still, in some embodiments, the utility vehicle **10** may not include a front anti-roll bar **282** (or rear anti-roll bar), as the microprocessor can react to changing conditions encountered by the vehicle, and vary the shock characteristics.

(204) In some embodiments, the rear lower A-arm **316a** (left hand side of the vehicle) is the same as the rear lower A-arm **316b** (right hand side of the vehicle), such that these rear lower A-arms are interchangeable. In some embodiments, the rear lower A-arms **316** is stamped from a piece of sheet metal (e.g., sheet steel). In some embodiments, the rear lower A-arm is welded together from tubular steel, however, the A-arms can be formed in any suitable way and from any suitable material or materials, alloys, etc. Further, in some embodiments, the rear lower A-arm **316** is formed from two or more stamped components which are welded together. In some embodiments, the rear lower A-arms **316a**, **316b** are not the same.

(205) In some embodiments, one or more of the rear upper A-arm **314**, rear lower A-arm **316**, front lower A-arm **276**, utilize bearings **298** and seals **309**, as discussed above with respect to FIG. 37.

(206) With regard to FIG. 47, in some embodiments, the rear upper A-arm **314** includes a mount **334** to which the rear damping member **320** is coupled. The rear damping member **320** can also be coupled to the lower A-arm.

(207) In some embodiments, at least a portion of the rear lower A-arm **316** extends through a vertically extending longitudinal plane **336**. The vertically extending longitudinal plane **336** includes the centerline (shown in FIG. 42) of the vehicle **10**. Plane **336** is shown illustratively in FIGS. 40 and 41. In some embodiments, at least a portion of the lower A-arm **316** is positioned above the lower rear frame member **126**, as shown in FIG. 42. In some embodiments, the left lower A-arm **316a** has a left lower A-arm pivot axis **338**, around which the left lower A-arm pivots as it moves through its range of travel. As shown in FIG. 42, the left lower A-arm pivot axis **338** extends longitudinally and is positioned (in bottom view looking upwardly) between the centerline of the vehicle **10** and the right rear lower frame member **126b**. Similarly, in some embodiments, the right lower A-arm pivot axis **340**, around which the right lower A-arm **316b** pivots, is positioned, in bottom view, between the centerline of the vehicle **10** and the left rear lower frame member **126a**.

(208) In some embodiments, respective upper and lower A-arms of left rear suspension, right rear suspension, left front suspension, right front suspension are parallel A-arms. In some embodiments, the respective arms are non-parallel A-arms. In some embodiments, the respective upper and lower A-arms are unequal in length. In some embodiments, the lower A-arm is longer than the upper A-arm, as shown in FIGS. 44-47.

(209) Turning to FIGS. 48-55, in some embodiments, the steering rack **104** has tie rods **342** (**342a**, **342b**) coupled thereto. In turn, in some embodiments, the tie rods **342** have tie rod ends **344** (**344a**, **344b**) respectively coupled to the tie rods **342**, for example by threading the tie rods to threads on the tie rods **342**. The tie rod ends **344** include steering ball joints **346** which, in some embodiments, are coupled to front knuckle **278** (FIG. 29) in order to facilitate steering of the vehicle **10**. In some embodiments, the steering ball joints **346** are coupled to respective front knuckles **278** via a castle nut **348** and cotter pin **350**.

(210) In some embodiments, the steering rack **104** is positioned above at least a portion of a front drive assembly **352**. In some embodiments, the front drive assembly **352** includes a differential (not shown) which transmits power from the front drive shaft **354** to the front half-shafts **356**. In some embodiments, the steering rack **104** is coupled to rack bracket **358** (FIG. 54). In turn, in some embodiments, the rack bracket **358** is coupled to rack mount **360**. The rack mount **360** is coupled to a portion of the front upper cross-bracket **372**, as shown for example in FIG. 55. In some embodiments, the rack bracket **358** is coupled to the rack mount **360** via one or more fasteners;

further, in some embodiments, the rack mount **360** is coupled to the front upper cross-bracket **372** via one or more fasteners.

(211) Turning to FIGS. **52-56** and **59**, in some embodiments, the front drive assembly **352** is coupled to an upper front drive assembly bracket **362** and a lower front drive assembly bracket **364**. In some embodiments, the housing of the front drive assembly **352** is coupled to the upper front drive assembly bracket **362** and lower front drive assembly bracket **364** via one or more fasteners (e.g., bolts). In turn, in some embodiments, one or both of the upper front drive assembly bracket **362** and lower front drive assembly bracket **364** are coupled to the frame **14**. In some embodiments, the upper front drive assembly bracket **362** is coupled, for example via one or more fasteners, to front upper cross-bracket **372** (FIG. **50**). In some embodiments, the front upper cross-bracket **372** is formed front a piece of bent sheet metal (e.g., steel). In some embodiments, the front upper cross-bracket **372** includes one or more mounting locations for the front upper A-arm **274** and, in some embodiments, the front upper front-suspension support member **370** is integrally formed with the front upper cross bracket **372** (FIG. **52**). As shown in FIG. **52**, in some embodiments, the front upper cross-bracket **372** includes tabs to which a front fork portion and rear fork portion, respectively, of the front upper A-arm **274** are rotatably mounted, to permit movement of the suspension. In some embodiments, a horizontal portion of the upper front drive assembly bracket **362** is positioned above a horizontal portion of the front upper cross-bracket **372**.

(212) Returning to FIG. **32**, in some embodiments, the front fork portion **414** of the front lower A-arm **276** is rotatably mounted to the front lower front-suspension support member **366** and the rear fork portion of the front lower A-arm **276** is rotatably mounted to a backer **418**. In some embodiments, the backer **418** is piece of sheet steel that is welded to a portion of the front joining frame member **184** (FIG. **11**). In some embodiments, a portion of the front upper A-arm **274**, can be rotatably mounted in a similar fashion, for example, to an appropriate backer. Portions of the rear suspension **312** can be rotatably mounted via an appropriate backer, as well.

(213) With further regard to FIG. **52**, in some embodiments, the frame **14** includes a rear upper front-suspension support member **368** and a front lower front-suspension support member **366**. In some embodiments, the rear upper front-suspension support member **368** and front lower front-suspension support member **366** are welded to the lower front frame member **180**. In some embodiments, the front upper cross bracket **372** and rear upper front-suspension support member **368** are formed from a single piece of bent sheet metal (e.g., steel), as shown for example in FIGS. **55A** and **55B**. In some embodiments, the front upper cross-bracket **372** is welded to one or more adjacent portions of the frame **14** (e.g., longitudinal intermediate front frame member **182**). In some embodiments, one or more portions of the front upper cross-bracket **372** are welded to one or more other portions of the front upper cross-bracket **372**. As shown in FIG. **55B**, for example, angled portion **390** of the front upper cross-bracket **372** is welded at **392**.

(214) In some embodiments, the lower front drive assembly bracket **364** is coupled to the fourth panel **198**, for example via one or more fasteners (e.g., bolts), as shown in FIG. **54**.

(215) Turning to FIGS. **56-63**, one or more portions of the driveline **374** are shown. In some embodiments, the driveline **372** includes a prime mover **376** (e.g., engine, electric motor, etc.), transmission **378** (e.g., transaxle, which includes a rear differential), front drive shaft **354**, front drive assembly **352**, front half shaft(s) **356**, rear half shafts **380**, drive clutch **382** (FIG. **58**), and driven clutch **384** (FIG. **58**). In some embodiments, the prime mover **376** and transmission **378** are rigidly coupled to one another, for example via one or more coupling members **386** (FIG. **56**). In turn, in some embodiments, the prime mover **376** and transmission **378**, as a unit, is isolated from the frame **14** (FIG. **11**) via vibration isolators **388** (FIG. **56**). As shown in FIGS. **58**, **63**, and **70**, in some embodiments, the prime mover **376** is coupled to a lateral mount member **394**, for example via one or more brackets. In turn, the lateral mount member **394** is isolated, via vibration isolators **388**, from standoff members **396**. The standoff members **396** are coupled to portions of the frame **14**, for example, via one or more fasteners. In some embodiments, the vibration isolators include an

elastomeric portion (e.g., rubber isolator), to isolate vibration caused by one or more of the driveline components (e.g., engine, transmission, etc.).

(216) In some embodiments, the transmission **378** is coupled to vibration isolators **388** via one or more transmission isolator brackets **398**, as shown in FIGS. **56**, **57**, and **70**.

(217) With regard to FIGS. **58** and **61-63**, in some embodiments, a portion of the front drive shaft **354** extends under the lateral mount member **394** and under a portion of the prime mover **376**. As shown in FIG. **63**, in some embodiments, a portion of the front drive shaft **354** extends between an oil pan **400** and an inner CVT (continuously variable transmission) cover **402**.

(218) With further regard to FIG. **58**, in some embodiments, the CVT cover assembly **404** includes an inner CVT cover **402**, an intermediate CVT cover **406**, and an outer CVT cover **408**. In some embodiments, the drive clutch **382** and driven clutch **384** are housed within a space between the intermediate CVT cover **406** and outer CVT cover **408**. In some embodiments, the flywheel **410** (FIGS. **63** and **70**) is housed within a space between the inner CVT cover **402** and mount plate **412**. In some embodiments, the mount plate **412** also serves as a coupler member **386** to couple the prime mover **376** with the transmission **378**.

(219) In some embodiments the front drive assembly **352** is coupled to one or more of the lower front drive assembly bracket **364**, upper front drive assembly bracket **362**, and frame **14** via one or more vibration isolators. Alternatively, in some embodiments, the front drive assembly **352** is rigidly coupled to one or more of the lower front drive assembly bracket **364**, upper front drive assembly bracket **362**, and frame **14**.

(220) With regard to FIGS. **64**, an embodiment of a CVT cover assembly **404** is shown. Also shown in FIG. **64** is a CVT intake duct member **420**, CVT exhaust duct member **422**, and CVT air box **424**. In some embodiments, the outer CVT cover **408** is removable from the intermediate CVT cover **406** without the use of tools (i.e. with hands only). In some embodiments, the outer CVT cover **408** is removed from the intermediate CVT cover **406** by releasing CVT cover fasteners **426**. In some embodiments, CVT cover fasteners **426** are spring-type retainers.

(221) Shown in FIG. **64A** is another embodiment of a CVT cover assembly **404** and CVT air box **424**. In some embodiments, the CVT air box **424** has one or more mounting tabs **428**. The mounting tabs **428** can support (or help support) the CVT air box **424** such that the CVT air box **424** can be coupled to an adjacent frame member or piece of material (e.g., sheet metal) which is welded or otherwise coupled to the frame. An example of the CVT air box **424** being coupled to an adjacent frame member is shown in FIG. **5**. In some embodiments, the CVT air box **424** is coupled to a frame member, mounting bracket, etc., via an air box fastener **430** (e.g., sheet metal screw, nut, etc.).

(222) Turning to FIG. **64B**, the flywheel **410** is shown in position within the inner CVT cover **402**. In some embodiments, the flywheel **410** includes a plurality of projections **432** extending radially from the flywheel **410**. In some embodiments, the projections **432** are formed of the same piece of material as the flywheel **410**; in some embodiments, however, the projections **432** are individual members which are attached to the flywheel **410**; in still other embodiments, the projections **432** extend from an annular portion of a member that is coupled to the flywheel **410** via one or more fasteners.

(223) With further regard to FIG. **64B**, in some embodiments, a sensor **434** (e.g., magnetic pickup) is positioned adjacent to the flywheel **410** such that upon rotation of the flywheel **410** the sensor **434** detects passage of the projections **432**. In this way, the engine speed is known and can be displayed on the dash of the vehicle. In this way, an operator will know how fast the engine is rotating. Such information can be displayed in revolutions per minute (RPM). In addition, the projections **432** can be arranged in a configuration that the sensor **434** can detect the position of the crankshaft of the engine. In some embodiments, an electrical lead **436** extends from the sensor **434**. The electrical lead **436** can transmit a signal to the CAN bus, ECU, etc. In some embodiments, however, the signal is transmitted wirelessly to the CAN bus, ECU, etc. such that the inner CVT

cover **402** does not have a CVT cover cutout **438** for the electrical lead **436**. Stated differently, in some embodiments, the electrical lead **436** extends from an interior of the inner CVT cover **402** to the exterior of the inner CVT cover **402**. Thus, where a signal is transmitted wirelessly from within the inner CVT cover **402**, the CVT cover cutout **438** may not be necessary.

(224) In some embodiments, the inner CVT cover **402** is coupled to the mount plate **412** (FIG. **70**) via one or more fasteners. Further, in some embodiments, an inner CVT gasket **442**. In some embodiments, the CVT gasket **442** resides in an inner CVT cover gasket channel **444** (FIG. **68**). In some embodiments, the CVT gasket **442** is pressed against the mount plate **412** to provide seal therebetween.

(225) With regard to FIGS. **65**, **66**, **68**, and **69**, in some embodiments, one or more of the CVT covers (e.g., inner CVT cover **402** and intermediate CVT cover **406**) are coupled together via a CVT cover retainer **440**. In some embodiments, the CVT cover retainer **440** comprises a snap ring. In some embodiments, the inner CVT cover **402** comprises one or more retaining tabs **446**. As illustrated in FIGS. **65** and **69**, the CVT cover retainer **440** is positioned between a portion of the intermediate CVT cover **406** and retaining tabs **446**. In this way, the intermediate CVT cover **406** is secured to the inner CVT cover **402**. In order to disassemble the intermediate CVT cover **406** from the inner CVT cover **402**, in some embodiments, the CVT cover retainer **440** is expanded (in diameter) and removed from the first groove **448** (FIG. **65**). Thereafter, the intermediate CVT cover **406** can be removed from the inner CVT cover **402**.

(226) With further reference to FIG. **69**, in some embodiments, the inner CVT cover **402** and intermediate CVT cover **406** include ridges **450**. The ridges **450** of the inner CVT cover **402** and the ridges **450** of the intermediate CVT cover **406** mate with each other in order to provide a positive interaction between the inner CVT cover **402** and the intermediate CVT cover **406**, and to facilitate locating the inner CVT cover **402** and the intermediate CVT cover **406** relative to one another during assembly. Further, the ridges **450** can provide a water-tight seal between the respective CVT covers. Although the ridges **450** are shown between the inner CVT cover **402** and intermediate CVT cover **406**, they can be utilized at an interface with any of the CVT covers.

(227) Returning to FIG. **66**, in some embodiments, an outer CVT gasket **452** is positioned in a second groove **454** (FIG. **68**). The outer CVT gasket **452** provides a watertight seal between the outer CVT cover **408** and the intermediate CVT cover **406**. In some embodiments, the outer CVT gasket **452** is formed from an elastomeric material. In some embodiments, the outer CVT gasket **452** is formed from an extruded foam material or molded rubber material. In some embodiments, the outer CVT gasket **452** has a circular cross-section.

(228) With additional reference to FIG. **66**, in some embodiments, the inner CVT gasket **442** is formed from an elastomeric material. In some embodiments, the inner CVT gasket **442** is formed from an extruded foam material or molded rubber material. In some embodiments, the inner CVT gasket **442** includes a plug portion **456**. As shown in FIG. **64B**, the plug portion **456** fits in the CVT cover cutout **438**. In some embodiments, the plug portion **456** includes a slit **458** and/or plug portion aperture **460**. During assembly or disassembly of the inner CT cover **402**, the slit **458** can facilitate passage of the electrical lead **436**. As is shown in FIG. **70**, in this way, the sensor **434** can remain coupled to the mount plate **412** (for example via an appropriate mounting bracket) upon removal of the inner CVT cover **402**. Further, in some embodiments, the electrical lead **436** extends through plug portion aperture **460** when the inner CVT cover **402** is assembled to the mount plate **412**. In some embodiments, the plug portion **456** is integrally formed with the inner CVT gasket **442**, for example in a molding process.

(229) As also shown in FIG. **66**, in some embodiments, a CVT filter **462** (e.g., foam) is positioned within a cavity of the CVT air box **424**. The CVT filter **462** can be of any suitable type, such as paper filter, foam filter, centrifugal filter, etc.

(230) In some embodiments, air enters the CVT cover assembly **404** via CVT air box **424** and is then routed into the inner CVT cover **402**. The air then flows from the inner CVT cover **402**, past

the inner CVT cover opening **466** and into a space between the intermediate CVT cover **406** and outer CVT cover **408** (a portion of which space is, in some embodiments, also occupied by the drive clutch **382** (FIG. **58**)). Thereafter, the air flows into a narrowing region in the space between the intermediate CVT cover **406** and outer CVT cover **408** and exists through the exit port **464** (FIG. **64B**) which leads into CVT exhaust duct member **422**. The air is then exhausted out into the atmosphere or is used to cool an oxygen sensor or other sensor, for example as disclosed in U.S. Pub. No. 2016/0061088, titled, "Oxygen Sensor Cooling Duct," the contents of which are herein incorporated by reference.

(231) Turning to FIGS. **71-76**, in some embodiments the vehicle **10** includes a steering column assembly **468**. In some embodiments, the steering column assembly **468** includes a gear selector assembly **470** and a tilt assembly **88** (also shown in FIG. **2**). In some embodiments, the gear selector assembly **470** includes a cable **472** (e.g., a push-pull cable); the cable **472** extends to the transmission **378**, thereby permitting the operator to select a desired gear (e.g., park, high, low, neutral, reverse). In some embodiments, the cable **472** is surrounded by a sheath **526** (FIG. **73**) to protect the cable **472**.

(232) In some embodiments, the steering column assembly **468** further includes an upper steering shaft **474**, first steering shaft bushing **476**, and a second steering shaft bushing **478**. In some embodiments, the steering column assembly **468** includes a first steering shaft washer **480** (e.g., a wave washer), a second steering shaft washer **482**, and a steering shaft retaining clip **484** (e.g., c-clip, e-clip, snap ring, etc.). Although shown with a steering shaft retaining clip **484** in FIG. **75**, other fasteners can also be used, such as a nut. In some embodiments, the upper steering shaft **474** has a splined portion **486** and a threaded portion **488**. In some embodiments, the threaded portion **488** has a hole extending therethrough such that a castle nut (not shown) and cotter pin (not shown) can be used to fasten the steering wheel **84** (FIG. **2**) to the upper steering shaft **474**. In some embodiments, the upper steering shaft **474** includes a U-joint **490** at a lower end thereof.

(233) In some embodiments, the tilt assembly **88** (shown without shock **90** in FIGS. **71-76**) includes a barrel member **492**, through which a portion of the upper steering shaft **474** extends. Further, in some embodiments, the first steering shaft bushing **476** and second steering shaft bushing **478** are positioned within a portion of the barrel member **492**. In some embodiments, the tilt assembly **88** further includes a horseshoe member **494**, which may be coupled to barrel member **492**, for example by welding or via one or more fasteners. In some embodiments, the horseshoe member **494** and barrel member **492** are formed from a single piece of material (e.g., by casting). In some embodiments, the tilt assembly **88** further includes an inner tilt bushing **496**, an outer tilt bushing **498**, a tilt pivot member **500** (e.g., bolt), and tilt fastener **502** (e.g., nut). In some embodiments, for example as shown in FIG. **75**, the tilt assembly **88** includes two of each of the inner tilt bushing **496**, outer tilt bushing **498**, tilt pivot member **500**, and tilt fastener **502**. In some embodiments, the tilt assembly **88** includes an upper shock mount **504**. In some embodiments, the upper shock mount **504** is coupled to the barrel member **492**, for example with one or more fasteners.

(234) With regard to FIGS. **73-76**, in some embodiments, the gear selector assembly **486** includes a shift tube **510**, shift handle **506**, shift arm **508**, jam nut **514**, torque arm **512**, first gear selector bushing **516**, and second gear selector bushing **518**. The first and second gear selector bushings **516**, **518** are positioned over first and second collar portions **520**, **522**, respectively, of the barrel member **492**, as shown in FIG. **75**. In some embodiments, at least one of the first and second gear selector bushings **516**, **518** is formed from a polyacetyl resin. In some embodiments, at least one of the first and second gear selector bushings **516**, **518** has a hardness of at least 80 shore D. In some embodiments, the jam nut **514** is utilized to adjust the position length and position of the shift handle **506**.

(235) In some embodiments, the shift arm **508** is coupled to the shift tube **510**, for example by welding, however the shift arm **508** can be coupled to the shift tube **510** in any other suitable

manner (e.g., one or more fasteners, adhesive, etc.). In some embodiments, the shift arm **508** has a threaded end onto which the shift handle **506** and jam nut **514** are threaded. In some embodiments, the jam nut **514** is tightened against the shift handle **506** to prevent the shift handle **506** from loosening.

(236) In some embodiments, the gear selector assembly **486** further includes a cable bracket **524**. In some embodiments, an end of the cable sheath **526** (FIG. **73**) includes a threaded member that extends through a slot or aperture **530** in the cable bracket **524**. In this way, the cable **472** can move within the cable sheath **526**, thereby permitting the operator to select the desired gear by rotating the shift handle **506**. As further shown in FIG. **73**, in some embodiments, a cable boot **528** extends over a portion of the cable **472**.

(237) In some embodiments, the shift tube **510** includes a shift tube opening **532** (FIG. **74**). The shift tube opening **532** permits rotation of the shift tube **510** over the upper shock mount **504**.

(238) Although components of the steering column assembly **468** may be described within the context of the gear selector assembly **470** or tilt assembly **88**, it will be appreciated that some components can be grouped into more than one of these assemblies. Further, it will be appreciated that the steering/tilt/gear select components discussed in the preceding paragraphs can be aptly included in the context of any one of the steering column assembly **468**, gear selector assembly **470**, and/or tilt assembly **88**.

(239) Turning to FIGS. **77-84**, in some embodiments, the vehicle **10** includes a floorboard **534**. In some embodiments, the floorboard **534** extends the width of the seating area **20**; in some embodiments, it extends forwardly to the front splash panel **268** (FIG. **124**); and, in some embodiments, it extends rearwardly to a forward end of the rear outer frame member **78** (FIG. **11**). In some embodiments, one or more portions of the floorboard **534** include one or more gutters **536**. The one or more gutters **536** direct water (or other liquid or debris) to the one or more drains **538**. In some embodiments, the gutters **536** are connected such that water (or other liquid or debris) can flow downhill when the vehicle **10** is situated on level ground. In some embodiments, the floorboard **534** is sloped to permit flow via the gutters **536** for exit via the drain(s) **538**. With regard to FIGS. **82** and **83**, in some embodiments, some of the gutters **536** have a greater depth, x.sub.1, than other gutters **536**, x.sub.2. In this way, fluid (or other debris) will flow via the gutters **536**, in combination, even where the floorboard **534** is not otherwise sloped. In some embodiments, the depth of gutters **536** can change along the length of the gutter to facilitate flow. In some embodiments, certain of the gutters **536** are wider (or narrower) than others.

(240) As shown for example in FIG. **82**, in some embodiments, the floorboard **534** includes one or more traction-enhancing features, for example projections **540** (which can also be indentations, texturing, etc.) which, in some embodiments, are arranged in a pattern. With regard to FIGS. **77**, **78**, and **81**, in some embodiments, the floorboard **534** includes a footrest **542** (e.g., dead-pedal) which in some embodiments comprises a sloped portion of the floorboard **534** on which the operator can rest a foot (e.g., left foot). In some embodiments, the floorboard **534** includes a raised tunnel portion **544**. The raised tunnel portion **544** can provide a space for a portion of the driveline **374**, such as the front drive shaft **354** (FIG. **56**).

(241) As shown in FIG. **80**, in some examples, the floorboard **534** includes one or more removable covers **546**. In some embodiments, the removable cover **546**, as shown in FIG. **80**, snaps into place. As further shown in FIG. **80**, the removable cover **546** can be removed to provide access to one or more components (not shown in FIG. **80**) behind the removable cover **546**. By way of example, the removable cover **546** can be removed to access a dipstick, oil filter, or other engine component. In some embodiments, the removable cover **546** includes a cover handle **548**, which can be gripped by an operator to facilitate removal or replacement of the removable cover **546**.

(242) With regard to FIGS. **81**, **83**, and **84**, in some embodiments, the floorboard **534** includes one or more upwardly extending portions **550**. As shown in FIGS. **83** and **84**, the upwardly extending portion **550** is integrally formed with the floorboard **534**, for example during a molding process. In

some embodiments, the floorboard **534** includes a plateau portion **552**. The plateau portion **552** extends longitudinally and laterally, for example above at least a portion of the fuel tank **112** (FIG. 7).

(243) In FIGS. **88** and **89**, an embodiment of a driver's seat **24a** is shown. In some embodiments, the driver's seat **24a** includes one or more seat structural portions **554a** (e.g., frame members). The seat structural portions **554a** can comprise any suitable material, for example metal (e.g., steel), composite, plastic, glass-filled nylon, etc. In some embodiments, the seat base **26a** includes a cushion **556a**. In some embodiments, the seat back **28a** includes a cushion.

(244) In FIGS. **90** and **91**, an embodiment of a passenger seat base **26b** is shown. In some embodiments, the passenger seat base **26b** is removably coupled to one or more portions of the seat support frame **146** (FIGS. **94-97**). In some embodiments, the passenger seat base **26b** includes one or more structural portions **554b** (e.g., frame members) and a cushion **556b**. The seat structural portions **554b** can comprise any suitable material, for example metal (e.g., steel), composite, plastic, glass-filled nylon, etc. In some embodiments, the passenger seat base **26b** includes one or more seat attachment members **558b**. The seat attachment members **558b** can facilitate attachment of the seat base **26b** to one or more portions of the seat support frame **146** (FIGS. **94-97**). In some embodiments, the seat attachment members **558b** comprise one or more hooks. The one or more hooks, in turn, are matingly coupled to seat support pins **560b** (FIGS. **95-97**). Although shown with the seat base **26b** having hooks and the seat support frame **146** having seat support pins **560b**, the seat base **26b** can alternatively comprise supports pins and the seat support frame **146** can have hooks. Further, the seat support frame **146** and seat base **26b** can comprise any suitable mating, interlocking, coupling structure(s). In some embodiments, the seat base **26b** (e.g., seat structural portion **554b**) includes one or more seat alignment members **562b**. The seat alignment members **562b** mate with seat receiver members **564b** (FIGS. **94-97**). In some embodiments, the seat receiver members **564b** facilitate alignment of the seat base **26b** with respect to the seat support frame **146** when the seat base **26b** is placed on the seat support frame **146** (e.g., upon returning the seat base **26b** to a seating configuration, as discussed in greater detail below). In some embodiments, the seat receiver members **564b** also support the seat base **26b**. Although shown in FIGS. **94-97** with the seat alignment members **562b** having a male portion and the seat receiver members **564b** having a female portion, these roles can be reversed such that a male portion is positioned on the seat support frame **146** (or is an integral part thereof) and a female portion is positioned on the seat structural portion **554b** (or is an integral part thereof). Other arrangements and structures can also be employed.

(245) With regard to FIGS. **92** and **93**, an embodiment of a passenger seat base **26c** is shown. In some embodiments, the passenger seat base **26c** is removably coupled to one or more portions of the seat support frame **146** (FIGS. **94-97**). In some embodiments, the passenger seat base **26c** includes one or more structural portions **554c** (e.g., frame members) and a cushion **556c**. The seat structural portions **554c** can comprise any suitable material, for example metal (e.g., steel), composite, plastic, glass-filled nylon, etc. In some embodiments, the passenger seat base **26c** includes one or more seat attachment members **558c**. The seat attachment members **558c** can facilitate attachment of the seat base **26c** to one or more portions of the seat support frame **146** (FIGS. **94-97**). In some embodiments, the seat attachment members **558c** comprise one or more hooks. The one or more hooks, in turn, are matingly coupled to seat support pins **560c** (FIGS. **95-97**). Although shown with the seat base **26c** having hooks and the seat support frame **146** having seat support pins **560c**, the seat base **26c** can alternatively comprise supports pins and the seat support frame **146** can have hooks. Further, the seat support frame **146** and seat base **26c** can comprise any suitable mating, interlocking, coupling structure(s). In some embodiments, the seat base **26c** (e.g., seat structural portion **554c**) includes one or more seat alignment members **562c**. The seat alignment members **562c** mate with seat receiver members **564c** (FIGS. **94-97**). In some embodiments, the seat receiver members **564c** facilitate alignment of the seat base **26c** with respect

to the seat support frame **146** when the seat base **26c** is placed on the seat support frame **146** (e.g., upon returning the seat base **26c** to a seating configuration, as discussed in greater detail below). In some embodiments, the seat receiver members **564c** also support the seat base **26c**. Although shown in FIGS. **94-97** with the seat alignment members **562c** having a male portion and the seat receiver members **564c** having a female portion, these roles can be reversed such that a male portion is positioned on the seat support frame **146** (or is an integral part thereof) and a female portion is positioned on the seat structural portion **554c** (or is an integral part thereof). Other arrangements and structures can also be employed.

(246) FIGS. **94-97** show progressive views for removing and storing the seat bases **26b** and **26c**. Reference is further made to FIGS. **86** and **87**. As illustrated in FIG. **94**, front portions of the seat bases **26b** and **26c** are rotated upwardly about an axis of the seat support pins **560** such that the seat alignment members **562** are free and clear of the seat receiver members **564**. With regard to FIG. **95**, the seat bases **26b**, **26c** are removed from the seat support frame **146**. As further shown in FIGS. **95-97**, in some embodiments, the seat backs **28b**, **28c** are supported by one or more lower seatback supports **566**. In some embodiments, the lower seatback supports **556** are coupled to the lateral rear cab frame member **154** (FIG. **111**), for example via one or more fasteners. In some embodiments, the lower seatback supports **566** comprise hook members into which a portion of the seat backs **28b**, **28c** extends. In some embodiments, the lower seatback supports **566** have an axis which is collinear with a seatback axis **568** (FIG. **95**), discussed below.

(247) Referring to FIG. **96**, in some embodiments, the seat backs **28b**, **28c** are rotated forward. In some embodiments, the seat backs **28b**, **28c** are rotated about seatback axis **568** (FIG. **95**). Referring to FIGS. **86** and **87**, in some embodiments, the seat backs **28b**, **28c** are coupled together via one or more seatback bridging members **570**, for example an upper seatback bridging member **572** and a lower seatback bridging member **574**. In some embodiments, the lower seatback bridging member **572** comprises a metallic member (e.g., tubular member) that is bent or formed into an appropriate shape. The lower seatback bridging member **574** can be formed from any suitable material (e.g., metal, plastic, composite, etc.) and in any suitable way. In some embodiments, the lower seatback bridging member **574** is coupled to one or more structural portions of the seat backs **28b**, **28c**. In some embodiments, the lower seatback bridging member **574** is coupled to structural portions of each of the seat backs **28b**, **28c** in three locations, as illustrated in FIG. **86**, for example via fasteners (e.g., screws, bolts, etc.) (not shown).

(248) In some embodiments, the upper seatback bridging member **572** comprises a metallic member that is bent or formed into an appropriate shape. In some embodiments, the upper seatback bridging member **572** is formed from a piece of sheet metal (e.g., sheet steel) which is bent. In some embodiments, the upper seatback bridging member **572** has one or more holes which receive fasteners (e.g., to couple the upper seatback bridging member **572** to one or more structural portions of each of the seat backs **28b**, **28c**) (e.g., screws, bolts, etc.) (not shown). In some embodiments, the upper seatback bridging member **572** includes one or more upper seatback receiver members **576**, which mate with the seatback alignment members **578** (FIG. **85**). Although shown with the female member (e.g., upper seatback receiver member(s) **576**) being a portion of (or coupled to) upper seatback bridging member **572** and the male member (e.g., seatback alignment member(s) **578**) being a portion of (or coupled to) the seatback body panel **580**, the male member can be a portion of (or coupled to) the upper seatback bridging member **572** and the female member (e.g., seatback alignment member(s) **578**) can be a portion of (or coupled to) the seatback body panel **580**. Other configurations, fasteners, etc. are also suitable. In some embodiments, the seatback body panel **580** is coupled (e.g., fastened via one or more fasteners (e.g., screws, bolts, etc.)) to the ROPS cross member **208**, as shown in FIG. **85**.

(249) Returning to FIG. **86**, in some embodiments, the upper seatback bridging member **572** includes one or more seatback retainer apertures **582**. Further, as shown in FIG. **85**, one or more seatback fastening members **584** are coupled to the seatback body panel **580** such that the

seatback fastening member(s) **584** matingly engages with the one or more seatback retainer apertures **582**. In some embodiments, the seatback fastening member **584** is a quarter-turn fastener, as shown.

(250) Returning now to FIG. **96**, the seat bases **26b**, **26c** are stowed forward of the rear portion of the seatback body panel **580** (see also FIG. **111**). Thereafter, as illustrated in FIG. **97**, the seat backs **28b**, **28c** are rotated rearwardly into an upright configuration and the seatback fastening member **584** is oriented (e.g., turned $\frac{1}{4}$ turn) to retain the upper seatback bridging member **572**. As shown in the cross-section of FIG. **111**, the seat base **26b** is shown in both configurations: (1) in a stowed configuration, wherein the seat base **26b** is positioned forward of the rear portion of the seatback body panel **580** and rearward of the seat back **28b**, and (2) in an seating configuration, wherein the seat base **26b** is situated such that an operator can sit on it.

(251) In order to orient the seat bases **26b**, **26c** from a stowed configuration to a seating configuration, the process is reversed. Specifically, after orienting the seatback fastening member **584** in an appropriate fashion, the seat back **28b**, **28c** is rotated forwardly about seatback axis **568** (FIG. **95**). Thereafter, the seat bases **26b**, **26c** are removed from their stowed location, positioned relative to the seat support pins **560**, and then rotated about an axis defined by the seat support pins **560** until the seat alignment members **562** are received within the seat receiver members **564**, as shown in FIGS. **93-96**.

(252) In some embodiments, the seat back **28b**, **28c** can be removed by orienting the seatback fastening member **584** (e.g., rotating $\frac{1}{4}$ turn to unlock), rotating a top portion of the seat back **28b**, **28c** forwardly about seatback axis **568** (FIG. **95**), and lifting the seatback **28b**, **28c** such that the lower seatback bridging member **574** (FIG. **86**) is free of the lower seatback supports **566** (FIG. **95**).

(253) Returning to FIGS. **78** and **79**, in some embodiments, the vehicle **10** includes a rear splash panel **586**. In some embodiments, the vehicle includes left (**586a**) and right (**586b**) rear splash panels. In some embodiments, one or both of the rear splash panels **586a**, **586b** include rear splash panel attachment tabs **588**. In some embodiments, the rear splash panel attachment tabs **588** couple the rear splash panels **586a**, **586b** to the adjacent body panel or frame member, as discussed in greater detail below. In some embodiments, the splash panel attachment tabs **588** include barbs to facilitate a positive connection to maintain hold between the panels.

(254) Turning now to FIGS. **98** and **123**, in some embodiments, the bumper **92** is coupled to the main frame **74**, for example via one or more bumper brackets **100**. In some embodiments, the bumper brackets **100** are coupled to portions of the main frame **74** for example via one or more fasteners (e.g., bolts). In some embodiments, the bumper brackets **100** are coupled, via fasteners, to frame bumper mounts **590**. In some embodiments, the frame bumper mounts **590** are welded to front joining frame members **184**, respectively. In some embodiments, the bumper **90** is formed from more than components that are fastened together, for example via fasteners. In some embodiments, the bumper **92** is coupled to the bumper brackets **100** via one or more fasteners.

(255) Referring specifically to FIG. **98**, in some embodiments, the bumper **92** has a winch guide **592** coupled thereto, for example via one or more fasteners. In some embodiments, a winch **594** is positioned rearwardly of at least a portion of the bumper **92**. In some embodiments, at least a portion of the bumper **92** is positioned longitudinally between the winch guide **592** and the winch **594**.

(256) With regard to FIGS. **99** and **100**, in some embodiments, a cooling system **596** is shown, for example, in relation to a diesel engine. As illustrated, in some embodiments, the cooling system **596** includes a radiator **598**, fill tank **600**, coolant feed conduit **602**, and coolant return conduit **604**. In some embodiments, the fill tank **600** also serves as an overflow tank. With regard to FIG. **99**, in some embodiments, the fill tank **600** is positioned rearwardly of the core support member **606**.

(257) With regard to FIGS. **101** and **102**, in some embodiments, the cooling system **596** is shown, for example, in relation to a gasoline engine. As illustrated, in some embodiments, the cooling

system **596** includes a radiator **598**, fill tank **600**, coolant feed conduit **602**, and coolant return conduit **604**. In some embodiments, the fill tank **600** also serves as an overflow tank. With regard to FIG. **101**, in some embodiments, the fill tank **600** is positioned rearwardly of the core support member **606**.

(258) Turning now to FIGS. **103-105**, an embodiment of one or more portions of exhaust and intake systems are illustrated in respective figures. In FIG. **103**, portions of illustrative intake and exhaust systems are shown in relation to a diesel engine. In some embodiments, an intake system **608** includes (FIG. **104**) an air filter assembly **610**, an engine intake duct member **612** (e.g., rubber hose), filter support member **614**, first engine intake conduit **616** (e.g., angled rubber hose), second engine intake conduit **618** (e.g., plastic tube, aluminum tube), and third engine intake conduit **620** (e.g., angled rubber hose). In some embodiments, the third engine intake conduit **620** is coupled to an intake manifold or throttle body, for example via a hose clamp.

(259) With regard to FIG. **105**, in some embodiments, an exhaust system **622** includes a first exhaust gasket **624**, a first exhaust pipe **626**, an exhaust donut **628**, one or more exhaust retaining members **630** (e.g., springs), a second exhaust pipe **632**, a second exhaust gasket **634**, a muffler **636**, and one or more exhaust support members **638**. In some embodiments, the first exhaust pipe **626** is coupled (e.g., via fasteners such as nuts) to an exhaust manifold. In some embodiments, the exhaust retaining members **630** couple the first and second exhaust pipe **626**, **632** together. In some embodiments, the exhaust support members **638** are welded to portions of the muffler **636** and, as shown in FIG. **103**, support the muffler **636** (or other component of the exhaust system **622**) via one or more exhaust isolators **640** (e.g., rubberized inserts).

(260) In FIGS. **106-109**, an embodiment of one or more portions of exhaust and intake systems are illustrated in respective figures. In FIG. **106**, portions of illustrative intake and exhaust systems are shown in relation to a gasoline engine, however, the type of engine is only illustrative. Further, the engine can be an HCCI (homogeneous charge compression ignition), HCSI (homogeneous charge spark ignition), SCCI (stratified charge compression ignition), RCCI (reactively controlled compression ignition), etc., with any appropriate fuel type (gas, propane, diesel, etc.).

(261) With regard to FIG. **107**, in some embodiments, an intake system **608** includes an air filter assembly **610**, an engine intake duct member **612** (e.g., rubber hose), filter support member **614**, first engine intake conduit **616** (e.g., angled rubber hose), second engine intake conduit **618** (e.g., plastic tube, aluminum tube), and third engine intake conduit **620** (e.g., angled rubber hose). In some embodiments, the third engine intake conduit **620** is coupled to an intake manifold or throttle body, for example via a hose clamp. As further shown in FIG. **107**, in some embodiments, the intake system **608** includes a breather tube **642**. As shown FIG. **106**, in some embodiments, the breather tube **642** is in fluid communication with a portion of the prime mover **376** (e.g., engine), such as valve cover **644**. The breather tube **642** can provide ventilation for the engine.

(262) With regard to FIGS. **108** and **109**, in some embodiments, an exhaust system **622** includes a first exhaust gasket **624**, a first exhaust pipe **626**, an exhaust donut **628**, one or more exhaust retaining members **630** (e.g., springs), a second exhaust pipe **632**, a second exhaust gasket **634**, a muffler **636**, and one or more exhaust support members **638**. In some embodiments, the first exhaust pipe **626** is coupled (e.g., via fasteners such as nuts) to an exhaust manifold **646** (FIG. **108**). In some embodiments, the exhaust retaining members **630** couple the first and second exhaust pipe **626**, **632** together. In some embodiments, the exhaust support members **638** are welded to portions of the muffler **636** and, as shown in FIG. **103**, support the muffler **636** (or other component of the exhaust system **622**) via one or more exhaust isolators **640** (e.g., rubberized inserts). In some embodiments, the exhaust system **622** further includes a bung **648** for an oxygen sensor **650** (O.sub.2 sensor).

(263) FIG. **110** shows a top view of an embodiment of a vehicle **10**, while FIG. **111** shows the vehicle of FIG. **110** in cross-section. As illustrated in FIG. **111**, in some embodiments, the cargo box **18** tilts with respect to the frame **14**, for example to dump cargo out of the cargo box **18**. In

some embodiments, the cargo box tilts about tilt axis **652** (also shown in FIG. **118**). In some embodiments, the rear joining frame member **156** includes a sloped portion **654**, which provides clearance for the cargo box **18** when it is tilted, as shown in FIG. **113**. In some embodiments, a portion of the cargo box **18** extends forwardly of a portion of the seatback body panel **580**, as illustrated in FIG. **111**. Moreover, in some embodiments, when the seat base **26b** (or **26c**) is in the stowed configuration, a portion of the cargo box **18** is forward of at least a portion of the seat base **26b** (or **26c**).

(264) With regard to FIG. **113**, in some embodiments, the vehicle **10** includes a hip restraint **656**. Although the vehicle **10** is shown in FIG. **113** with both a side restraint **76** and a hip restraint **656**, the vehicle **10** will have, in some embodiments, either a side restraint **76** or a hip restraint **656**, but not both. As illustrated in FIG. **112**, in some embodiments, the hip restraint **656** is coupled to the rear outer frame member **78** and the first seating support member **142**.

(265) Referring to FIGS. **114-119**, in some embodiments, the cargo box **18** has a first lateral side **658**, a second lateral side **660**, a front side **662**, and a rear side **664**. In some embodiments, the rear side **664** comprises a tailgate **666**. In some embodiments, the front side **662** includes a portion that extends upward away from cargo box **18**. This upward extending portion is located adjacent to ROPS cross member **208** (shown in FIG. **14**) to act as a noise barrier between cargo box **18** and passengers. In some embodiments, the upward extending portion directly abuts ROPS cross member **208**. In other embodiments, the upward extending portion is situated to allow cargo box **18** to tilt as shown in FIG. **113**.

(266) In some embodiments, the vehicle **10** includes a cargo box assembly **682**. In some embodiments, the cargo box assembly **682** includes the cargo box **18**, a tilt release member **668** (FIG. **115**), and one or more tilt release catches **670**. In some embodiments, the tilt release member **668** is formed from piece of metallic (e.g., steel) rod or tubing that is formed into the appropriate shape. In some embodiments, the one or more tilt release catches **670** have a latch portion that releasably catches on latch pin **672** (FIG. **78**). In some embodiments, the tilt release member **668** further tilt handle **674**. The tilt handle **674** is pulled upwardly to release the catch from the latch pin **672** (FIG. **78**) such that the cargo box **18** can be tilted. Although shown as having a circular cross section, the latch pin **672** can have any desirable shape. For example, it can be formed from square tubing, round tubing, a bracket, etc. In some embodiments, the tilt release member **668** interfaces with one or more biasing members **676** (e.g., springs, torsion springs), such that tilt release member **668** is biased into a latched configuration.

(267) With regard to FIG. **115**, in some embodiments, the cargo box assembly **682** has a tilt shock **678**. In some embodiments, the tilt shock **678** resists quick raising or lowering of the cargo box **18**. In some embodiments, the tilt shock **678** is coupled, for example via a fastener, to one or more box supporting ribs **680** or channel members.

(268) Referring to FIG. **116**, in some embodiments, the cargo box assembly **682** further includes at least one protective cover **684**, one or more tailgate handles **686**, one or more handle latches **688** (for example, over center latches), one or more latch receivers **690**, one or more tailgate hinge members **692**, one or more tailgate hinge bushings **694**, one or more tailgate support members **696** (e.g., cables), one or more bumper members **698**, and one or more tilt release mounts **700**. In some embodiments, the protective cover **684** protects a portion of the wiring harness (not shown), for example a portion of the wiring harness that connects to a brake light. In some embodiments, a portion of the wiring harness (not shown) is routed between opposing lateral sides of the protective cover **684**. In addition, hardware (e.g., fasteners such as nuts, bolts, screws, etc.) can be utilized to assemble various components, as illustratively shown in FIG. **116**. In some embodiments, the bumper members **698** are formed from an elastomeric material (e.g., rubber). In some embodiments, a bottom surface of the bumper members **698** rests on a portion of the frame **14**, as shown in FIG. **111**, for example when the cargo box **18** is in a lowered configuration. In some embodiments, the bumpers **698** rest on the rear upper frame members **124** (FIG. **111**).

(269) In some embodiments, the cargo box **18** is formed from a metallic material, such as steel or aluminum. In some embodiments, the cargo box **18** is formed from one or more sheets of steel that are bent into an appropriate shape, as illustratively shown in FIGS. **117-119**, to form the floor of the cargo box **18**, one or more portions of the first lateral side **658**, second lateral side **660**, front side **662**, rear side **664**, and tailgate **666**. In some embodiments, one or more plastic body panels are attached to exterior portions of the bent metallic sheets which form structural portions of the cargo box **18**.

(270) Turning to FIGS. **120-122**, in some embodiments, a fuel tank **112** and portions of a fuel system **702** are shown. The fuel system **702** includes the fuel tank **112**, filler neck **38**, fuel cap **36**, fuel supply line **704**, fuel return line **706**, fuel level sender **708**, fuel filter **710**, pressure release valve **712**, and vent tube **714**. In some embodiments, the fuel level sender **708** communicates with a fuel gauge on the dash to display the level of fuel in the fuel tank **112** operator. In some embodiments the pressure release valve **712** can vent pressure inside or outside the tank in order to equalize pressure inside the tank with respect to the atmosphere. In some embodiments, the pressure release valve **712** is a rollover valve, such that, in the event the fuel tank **112** is tipped, liquid fuel does not leak out of the fuel tank **112**.

(271) With regard to FIG. **122**, in some embodiments, the fuel tank **112** includes a protruding portion **716** (discussed previously). In some embodiments, the fuel tank **112** also includes a recessed portion **718**, which can facilitate locating the fuel tank **112** relative to a frame member, panel (e.g., first panel **114**), body panel, etc.

(272) With regard to FIGS. **124-131**, one or more panels (e.g., plastic body panels) are shown. In FIGS. **124** and **125**, in some embodiments, the vehicle **10** has a hood **720**, bridging dash member **722**, upper dash member **724**, and lower dash member **726**, and glovebox door **728**. In some embodiments, the hood **720** is removable, hingeable, etc. to facilitate access to a compartment, accessory, electrical, radiator, etc. which may be located under the hood **720**.

(273) With regard to FIGS. **126** and **127**, in some embodiments, the vehicle **10** includes an upper fascia member **730**, intermediate fascia member **732**, and lower fascia member **734**. In some embodiments, the upper fascia member **730** includes a grille **736**, which can be integrally formed with the remainder of the upper fascia member **730** or it can be formed separately and coupled (e.g., with tabs, fasteners, etc.) to the remainder of the upper fascia member **730**. In some embodiments, the radiator is located rearwardly of the grille **736**.

(274) As shown in FIGS. **128** and **129**, in some embodiments, the vehicle **10** includes a fender panel member **738** and a fender trim member **740**. In some embodiments, the fender trim member **740** is coupled to the fender panel member **738** via one or more trim member attachment tabs **742**, which fit into tab apertures in the fender panel member **738**.

(275) Turning to FIGS. **130** and **131**, in some embodiments, one or more portions of the cargo box assembly **682** are formed from one or more plastic or composite materials. In some embodiments, the cargo box **18** is formed in a single molding process, for example from a high-density polyethylene (HDPE) with a foaming agent. In some embodiments, the cargo box assembly **682** further includes a box sub-frame **744**, upper cargo box body panel **56**, and lower cargo box body panel **746**. In some embodiments, the tailgate **666** includes an inner tailgate member **748**, and an outer tailgate member **750**. In some embodiments, the inner tailgate member **784** is formed from a sheet of stamped metal (e.g., stamped sheet metal). In some embodiments, the outer tailgate member **750** is formed from an HDPE material. In some embodiments, the upper cargo box body panel **56** is formed from a thermoplastic olefin (TPO) or an ionomer resin such as DuPont's Surlyn. In some embodiments, the lower tailgate member **748** is formed from HDPE. These materials are only illustrative, and other materials such as thermoplastics, thermosets, metals, metal alloys, composites, etc. can also be used. In some embodiments, the box sub-frame **744** is formed from one or more steel components, which may be welded or otherwise fastened together (e.g., using fasteners).

(276) In some embodiments, the cargo box assembly **682** further comprises one or more tie-down members **752**. The tie-down members **752** are coupled, for example via one or more fasteners, to the cargo box **18**, as illustratively shown in FIG. **131**. In some embodiments, the cargo box assembly **682** includes one or more box retainers **754**. In some embodiments, the box retainers **754** secure the floor of the cargo box **18** to one or more portions of the box sub-frame **744**, for example via fasteners such as bolts (e.g., carriage bolts), nuts, and/or screws, etc.

(277) Turning to FIGS. **133-137**, in some embodiments, the one or more doors **62** comprises a door which vertically spans only a portion of the cab opening. For example, in some embodiments, an upper edge of the door **62** extends upwardly to a position that is $\frac{1}{2}$ -4" above the top of the seat base **26a**, as illustratively shown in FIG. **2**. The upper edge of the door **62** can also be below the top of the seat base **26a**, level with the seat base **26a**, or any other suitable height. In some embodiments, the doors **62** include an outer door panel **756** and an inner door panel **758**. In at least some embodiments, the door **62** is part of a door assembly **760**. In some embodiments, the door assembly **760** further includes an outer door handle **762**, a door hinge **766**, and a door latch assembly **768**. One or more portions of the door latch assembly **768** are coupled to the frame **14** (FIG. **5**), for example via one or more fasteners (e.g., nuts, bolts, screws, etc.). Further, one or more portions of the door hinge **766** may be coupled to the frame **14**, seat support frame **146**, etc., for example via one or more fasteners (e.g., nuts, bolts, screws, etc.). In some embodiments, a portion of the door hinge **766** is coupled to the first seating support member **142** (FIG. **12**).

(278) In some embodiments, actuation of the outer door handle **766** unlatches the door latch assembly **768**, permitting the door **62** to open. Although not shown in FIGS. **133-137**, in some embodiments, the door assembly **760** also includes an inner door handle, by which an operator can unlatch the door assembly **768** to open the door **62**.

(279) Referring to FIGS. **134-135**, in some embodiments, the inner door panel **758** includes a door pocket **770**. In some embodiments, the door pocket **770** is at least partly defined by a space between the inner door panel **758** and outer door panel **756**.

(280) Turning now to FIGS. **138-142**, in some embodiments, the vehicle **10** includes a roof assembly **772**, a brush guard **774** (FIG. **138**), and one or more side windows **776**. In some embodiments, the vehicle **10** further includes front and rear windshields, which may have one or more transparent portions that pivot outwardly, slide (e.g., rear sliding windows), include one or more accessories (e.g., wiper and washer assemblies), etc. As shown in FIG. **141**, in some embodiments, the roof assembly **772** includes an inner front panel **778**, an outer front panel **780**, and an outer main panel **782**. In some embodiments, for example as shown in FIG. **141**, the inner front panel **778** and outer front panel **780** are coupled to one another, for example via one or more fasteners (e.g., clips, screws, bolts, nuts, etc.). In some embodiments, the roof assembly **772** include a headliner (not shown), roof console, and/or one or more roof mounted controls (e.g., light switch), roof mounted storage areas, etc.

(281) In some embodiments, one or more of the body panels can be formed from a composite material, HDPE material, TPO material, or other suitable material. In some embodiments, one or more of the panels (e.g., rear cab-side panel **32**, upper cargo box body panel **56**, lower cab panel **64**, front splash panel **268**, seatback body panel **580**, rear splash panel **586**, hood **720**, bridging dash member **724**, lower dash member **726**, glovebox door **728**, upper fascia member **730**, intermediate fascia member **732**, lower fascia member **734**, fender panel member **738**, fender trim member **740**, lower cargo box body panel **746**, inner tailgate member **748**, outer tailgate member **750**, outer door panel **756**, inner door panel **758**, inner front panel **778**, outer front panel **780**, outer main panel **782**) can be formed from a composite material having a resin and fibers. In some embodiments, the fibers have an average fiber length of 0.2-2 inches. In some embodiments, the fibers have an average fiber length of 0.5-1.5 inches, and in some embodiments, the fibers have an average fiber length of 0.75-1.25 inches. In some embodiments, the fibers have an average fiber length of 1 inch. In some embodiments, one or more of the panels (e.g., rear cab-side panel **32**, upper cargo box

body panel **56**, lower cab panel **64**, front splash panel **268**, seatback body panel **580**, rear splash panel **586**, hood **720**, bridging dash member **724**, lower dash member **726**, glovebox door **728**, upper fascia member **730**, intermediate fascia member **732**, lower fascia member **734**, fender panel member **738**, fender trim member **740**, lower cargo box body panel **746**, inner tailgate member **748**, outer tailgate member **750**, outer door panel **756**, inner door panel **758**, inner front panel **778**, outer front panel **780**, outer main panel **782**) is formed via a Reaction Injection Molding process (RIM), which can utilize IMP (In-mold-paint). In some embodiments, the composite utilizes a polyurethane. In some embodiments, polyurethane based composites include chopped glass reinforcement fibers, structural foam, and elastomers. In some embodiments, the composite is a dicyclopentadiene (DCPD) composite or a fiberglass/polyester composite.

(282) In some embodiments, the composite uses a 2-part thermoset polyurethane [Iso/poly] material. In some embodiments, one or more of the panels (e.g., rear cab-side panel **32**, upper cargo box body panel **56**, lower cab panel **64**, front splash panel **268**, seatback body panel **580**, rear splash panel **586**, hood **720**, bridging dash member **724**, lower dash member **726**, glovebox door **728**, upper fascia member **730**, intermediate fascia member **732**, lower fascia member **734**, fender panel member **738**, fender trim member **740**, lower cargo box body panel **746**, inner tailgate member **748**, outer tailgate member **750**, outer door panel **756**, inner door panel **758**, inner front panel **778**, outer front panel **780**, outer main panel **782**) has a high gloss (class “A”) on one or more of the surfaces (e.g., exterior surface). In some embodiments, one or more of the panels (e.g., rear cab-side panel **32**, upper cargo box body panel **56**, lower cab panel **64**, front splash panel **268**, seatback body panel **580**, rear splash panel **586**, hood **720**, bridging dash member **724**, lower dash member **726**, glovebox door **728**, upper fascia member **730**, intermediate fascia member **732**, lower fascia member **734**, fender panel member **738**, fender trim member **740**, lower cargo box body panel **746**, inner tailgate member **748**, outer tailgate member **750**, outer door panel **756**, inner door panel **758**, inner front panel **778**, outer front panel **780**, outer main panel **782**) has color on only one side of the panel. In some embodiments, one or more of the panels (e.g., rear cab-side panel **32**, upper cargo box body panel **56**, lower cab panel **64**, front splash panel **268**, seatback body panel **580**, rear splash panel **586**, hood **720**, bridging dash member **724**, lower dash member **726**, glovebox door **728**, upper fascia member **730**, intermediate fascia member **732**, lower fascia member **734**, fender panel member **738**, fender trim member **740**, lower cargo box body panel **746**, inner tailgate member **748**, outer tailgate member **750**, outer door panel **756**, inner door panel **758**, inner front panel **778**, outer front panel **780**, outer main panel **782**) is formed via compression molding, using fiberglass reinforced plastics, and/or resin transfer molding.

(283) In some embodiments, one or more of the roof panels (e.g., inner front panel **778**, outer front panel **780**, outer main panel **782**) provides falling object protection, for example when is formed using fibers having an average fiber length of 0.5-1.5 inches.

(284) In some embodiments, one or more of the panels (e.g., rear cab-side panel **32**, upper cargo box body panel **56**, lower cab panel **64**, front splash panel **268**, seatback body panel **580**, rear splash panel **586**, hood **720**, bridging dash member **724**, lower dash member **726**, glovebox door **728**, upper fascia member **730**, intermediate fascia member **732**, lower fascia member **734**, fender panel member **738**, fender trim member **740**, lower cargo box body panel **746**, inner tailgate member **748**, outer tailgate member **750**, outer door panel **756**, inner door panel **758**, inner front panel **778**, outer front panel **780**, outer main panel **782**) includes one or more composite materials, which can include carbon fiber, fiberglass, and Kevlar. In some embodiments, one or more of these materials can be utilized to provide light armament for the vehicle **10**, for example small-arms fire ballistic protection. Additionally, nomex, titanium, steel, epoxy, or polyester resins can be utilized. Further still, additional panels can be added, for example, between inner and outer door panels, which are formed form a material which provides ballistic protection (e.g., Kevlar composites, as previously discussed).

(285) In some embodiments, driveline can also include a differential between the front and rear

differentials. Thus, the utility vehicle **10** can have one, two, three, or more differentials. The differentials can be oriented laterally or longitudinally. For example, a differential coupling the front and rear differentials can be oriented longitudinally, while front and rear differentials can be oriented laterally.

Claims

1. An off-road utility vehicle comprising: a frame; an engine; a transmission; first and second rear half-shafts connected between the transmission and first and second rear wheels; and a rear suspension that includes first and second upper arms, wherein the first and second upper arms are connected to the frame at a forwardmost upper arm connection point and a rearwardmost upper arm connection point, respectively, wherein the forwardmost upper arm connection point and the rearwardmost upper arm connection point are rearward of a connection of the first and second half-shafts to the transmission, and wherein the rear suspension includes a damping member attached to the frame at a point rearward of the forwardmost upper arm connection point.
2. The off-road utility vehicle of claim 1, wherein the rear suspension further includes first and second upper suspension support members that connect the first and second upper arms, respectively, to the frame.
3. The off-road utility vehicle of claim 2, wherein the first and second upper arms form an upper A-arm assembly.
4. The off-road utility vehicle of claim 1, wherein the first and second upper arms are connected to the frame in a horizontal plane that is vertically above the connection of the first and second half-shafts to the transmission.
5. The off-road utility vehicle of claim 1, wherein the rear suspension further includes first and second lower arms are connected to the frame rearward of the connection of the first and second half-shafts to the transmission.
6. The off-road utility vehicle of claim 5, wherein the rear suspension further includes first and second lower suspension support members that connect the first and second lower arms, respectively, to the frame.
7. The off-road utility vehicle of claim 5, wherein the first and second lower arms form a lower A-arm assembly.
8. The off-road utility vehicle of claim 5, wherein the first upper arm is located forward of the second upper arm and the first lower arm is located forward of the second lower arm.
9. The off-road utility vehicle of claim 8, wherein the first upper arm is located forward of the first lower arm.
10. The off-road utility vehicle of claim 8, wherein the second upper arm is located rearward of the second lower arm.
11. An off-road utility vehicle comprising: a frame; an engine; a transmission; first and second rear half-shafts connected between the transmission and first and second rear wheels; and a rear suspension comprising: an upper A-arm having first and second upper arms connected to the frame via first and second upper suspension support members; and a lower A-arm having first and second lower arms connected to the frame via first and second lower suspension support members, wherein the first and second upper suspension support members and first and second lower suspension support members are located rearward of a connection of the first and second rear half-shafts to the transmission.
12. The off-road utility vehicle of claim 11, wherein the first upper arm is located forward of the second upper arm and the first lower arm is located forward of the second lower arm.
13. The off-road utility vehicle of claim 12, wherein the first upper arm is located forward of the first rear arm.
14. The off-road utility vehicle of claim 13, wherein the second upper arm is located rearward of

the second lower arm.

15. An off-road utility vehicle, comprising: a frame; an engine; a transmission; a first rear half-shaft connected to a second rear-half shaft between the transmission and first and second rear wheels; and a rear suspension including first and second upper arms, and first and second lower arms, wherein the first and second upper arms are connected to the frame rearward of a connection of the first and second half-shafts to the transmission, wherein a first connection of the first upper arm to the frame is forward of a second connection of the second lower arm to the frame.

16. The off-road utility vehicle of claim 15, wherein the first upper arm is forward of the second upper arm and wherein the first lower arm is forward of the second lower arm.
