

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410035
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Suzuki; Naohiko

Elevator system controlling elevators in response to call information from a mobile terminal

Abstract

A mobile terminal (7) has an acceleration sensor (8) and a direction sensor (9). The mobile terminal (7) includes a route specifying unit (11), a calculating unit (13), a determining unit (14), and a communicating unit (16). The calculating unit (13) calculates a feature quantity of a route specified by the route specifying unit (11) on the basis of the route specified by the route specifying unit (11). The communicating unit (16) transmits call information to the communicating device (6) when the determining unit (14) determines that the route specified by the route specifying unit (11) is a boarding route.

Inventors:	Suzuki; Naohiko (Tokyo, JP)
Applicant:	Mitsubishi Electric Corporation (Tokyo, JP)
Family ID:	64273490
Assignee:	MITSUBISHI ELECTRIC CORPORATION (Tokyo, JP)
Appl. No.:	16/490078
Filed (or PCT Filed):	May 16, 2017
PCT No.:	PCT/JP2017/018384
PCT Pub. No.:	WO2018/211593
PCT Pub. Date:	November 22, 2018

Prior Publication Data

Document Identifier	Publication Date
US 20200062537 A1	Feb. 27, 2020

Publication Classification

Int. Cl.: B66B1/34 (20060101); B66B1/14 (20060101)

U.S. Cl.:

CPC B66B1/3476 (20130101); B66B1/3446 (20130101); B66B1/3461 (20130101); B66B1/14 (20130101); B66B2201/232 (20130101); B66B2201/4607 (20130101); B66B2201/4684 (20130101)

Field of Classification Search

CPC: B66B (1/468); B66B (2201/4653); B66B (1/2408); B66B (1/3461); B66B (2201/4615); B66B (5/0012); B66B (1/2458); B66B (2201/103); B66B (2201/4638); B66B (1/3446); B66B (1/3492); B66B (3/02); B66B (2201/232); B66B (2201/405); B66B (9/16)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8020672	12/2010	Lin	187/316	B66B 1/34
2018/0327214	12/2017	Armistead	N/A	G01C 21/206
2020/0062537	12/2019	Suzuki	N/A	B66B 1/14

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
104276462	12/2014	CN	N/A
2578524	12/2015	ES	B66B 1/20
2003-226473	12/2002	JP	N/A
2014-118263	12/2013	JP	N/A
2015-16917	12/2014	JP	N/A
2015-132629	12/2014	JP	N/A
2017178474	12/2016	JP	B66B 1/2458
WO-2009122002	12/2008	WO	B66B 1/2458
WO-2009132696	12/2008	WO	B66B 1/468
WO-2016100293	12/2015	WO	B66B 1/3461

OTHER PUBLICATIONS

Japanese Notice of Reasons for Refusal issued May 19, 2020 in Japanese Application No. 2019-518638. cited by applicant

Office Action issued on Apr. 26, 2021, in corresponding Chinese patent Application No. 201780090033.1, 16 pages. cited by applicant

International Search Report and Written Opinion mailed on Aug. 1, 2017 for PCT/JP2017/018384

filed on May 16, 2017, 7 pages including English Translation of the International Search Report.
cited by applicant
Office Action issued on Mar. 30, 2021, in corresponding Korean patent Application No. 10-2019-7033028, 10 pages. cited by applicant

Primary Examiner: Uhler; Christopher

Attorney, Agent or Firm: XSENSUS LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) The present application is based on PCT filing PCT/JP2017/018384, filed May 16, 2017, the entire contents of which are incorporated herein by reference.

FIELD

(2) The present invention relates to an elevator system and a mobile terminal.

BACKGROUND

(3) PTL 1 discloses an elevator system. The system disclosed in PTL 1 includes a receiving device configured to receive information from a mobile terminal. The receiving device receives information with different reception intensities from a plurality of communication areas. A call for a user is registered on the basis of the information received by the receiving device.

CITATION LIST

Patent Literature

(4) [PTL 1] Japanese Patent Application Publication No. 2003-226473

SUMMARY

Technical Problem

(5) In the system disclosed in PTL 1, as the communication area is expanded, the receiving device may receive information transmitted from a mobile terminal carried by a person who does not use the elevator. This causes call registration to be wasted.

(6) The present invention is made in order to solve the above problem. An object of the present invention is to provide an elevator system which enables automatic call registration for a user while preventing useless call registration. Another object of the present invention is to provide a mobile terminal for use in the system.

Solution to Problem

(7) An elevator system of the present invention comprises a mobile terminal having an acceleration sensor and a direction sensor, a communicating device configured to wirelessly communicate with the mobile terminal, and registering means configured to register a call on the basis of call information from the mobile terminal, the call information received by the communicating device. The acceleration sensor detects an acceleration of the mobile terminal. The direction sensor detects a particular direction on a horizontal plane. The mobile terminal comprises route specifying means configured to specify a route on which the mobile terminal has moved on the horizontal plane on the basis of at least one of the acceleration detected by the acceleration sensor and the direction detected by the direction sensor, first calculating means configured to calculate a feature quantity of the route specified by the route specifying means on the basis of the route specified by the route specifying means, first determining means configured to determine whether the route specified by the route specifying means is a boarding route for boarding a car on the basis of the feature quantity calculated by the first calculating means, and communicating means configured to transmit the call information to the communicating device when the first determining means determines that the

route specified by the route specifying means is the boarding route.

(8) A mobile terminal of the present invention comprises an acceleration sensor configured to detect an acceleration, a direction sensor configured to detect a particular direction on a horizontal plane, route specifying means configured to specify a route on which the mobile terminal has moved on the horizontal plane on the basis of at least one of the acceleration detected by the acceleration sensor and the direction detected by the direction sensor, first calculating means configured to calculate a feature quantity of the route specified by the route specifying means on the basis of the route specified by the route specifying means, first determining means configured to determine whether the route specified by the route specifying means is a boarding route for boarding a car on the basis of the feature quantity calculated by the first calculating means, and communicating means configured to wirelessly transmit call information for requesting for registration of a call when the first determining means determines that the route specified by the route specifying means is the boarding route.

Advantageous Effects of Invention

(9) The elevator system of the present invention includes a mobile terminal, a communicating device, and registering means. The mobile terminal includes route specifying means, first calculating means, first determining means, and communicating means. The first calculating means calculates a feature quantity of a route specified by the route specifying means on the basis of the route specified by the route specifying means. The first determining means determines whether the route specified by the route specifying means is a boarding route for boarding a car on the basis of the feature quantity calculated by the first calculating means. The elevator system of the present invention allows a call for a user to be automatically registered while preventing useless call registration.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a diagram illustrating an example of an elevator system according to a first embodiment of the present invention.

(2) FIG. 2 is a flowchart for illustrating an operation example of a mobile terminal.

(3) FIG. 3 is a plan view showing an example of a building in which the elevator system shown in FIG. 1 is applied.

(4) FIG. 4 is an example of a route specified by a route specifying unit.

(5) FIG. 5 is a diagram for illustrating functions of a calculating unit.

(6) FIG. 6 is a diagram for illustrating functions of the calculating unit.

(7) FIG. 7 is a diagram for illustrating functions of the calculating unit.

(8) FIG. 8 is a diagram for illustrating functions of the calculating unit.

(9) FIG. 9 is a diagram for illustrating functions of a determining unit.

(10) FIG. 10 is a diagram for illustrating functions of the determining unit.

(11) FIG. 11 is a flowchart for illustrating an operation example of a group controller.

(12) FIG. 12 is a view showing a display example of a display.

(13) FIG. 13 is a plan view showing another example of a building in which the elevator system shown in FIG. 1 is applied.

(14) FIG. 14 is a view showing another display example of the display.

(15) FIG. 15 is a diagram illustrating an example of an elevator system according to a second embodiment of the present invention.

(16) FIG. 16 is a flowchart for illustrating an operation example of the mobile terminal.

(17) FIG. 17 is a diagrams for illustrating functions of a condition creating unit.

(18) FIG. 18 is a diagrams for illustrating functions of the condition creating unit.

(19) FIG. 19 is a diagram showing an example of a hardware configuration of the group controller.
(20) FIG. 20 is a diagram showing an example of a hardware configuration of the mobile terminal.
DESCRIPTION OF EMBODIMENTS

(21) The present invention will be described with reference to the accompanying drawings. Redundant descriptions will be simplified or omitted as appropriate. In the respective drawings, the same reference numerals indicate the same or corresponding portions.

First Embodiment

(22) FIG. 1 is a diagram illustrating an example of an elevator system according to a first embodiment of the present invention. A group controller 1 controls, as a group, a plurality of elevator devices provided in a building or the like. FIG. 1 shows an example in which the group controller 1 controls three elevator devices. Two elevator devices or four or more elevator devices may be controlled by the group controller 1. In the following description, a particular elevator device will be designated with one of A to C as a suffix to be distinguished from the other elevator devices.

(23) Each of the elevator devices controlled by the group controller 1 includes a car 2, a traction machine 3, and a controller 4. For example, an elevator device A includes a car 2A, a traction machine 3A, and a controller 4A. The car 2 moves up and down in a shaft. The car 2 includes a door motor 5 configured to drive doors. The door motor 5 is controlled by the controller 4. The car 2 is driven by the traction machine 3. The traction machine 3 is controlled by the controller 4. The controller 4 controls various devices on the basis of a response instruction received from the group controller 1.

(24) The group controller 1 communicates with an external device through a communicating device 6. For example, the communication device 6 wirelessly communicates with a mobile terminal 7. The communicating device 6 is electrically connected to the group controller 1.

(25) The mobile terminal 7 is a terminal carried by a user. The mobile terminal 7 may be a smart phone. The mobile terminal 7 may be a terminal dedicated to this system. The mobile terminal 7 includes, for example, an acceleration sensor 8, a direction sensor 9, a storage unit 10, a route specifying unit 11, a receiving unit 12, a calculating unit 13, a determining unit 14, a call creating unit 15, and a communicating unit 16.

(26) The acceleration sensor 8 detects an acceleration of the mobile terminal 7. The acceleration sensor 8 detects, for example, a horizontal acceleration and a vertical acceleration. The acceleration sensor 8 detects, for example, an acceleration in an x-axis direction and an acceleration in a y-axis direction as horizontal accelerations. The acceleration sensor 8 detects, for example, an acceleration in a z-axis direction as a vertical acceleration. The directions of the x-axis, the y-axis, and the z-axis are orthogonal to one another.

(27) The direction sensor 9 detects a particular direction on a horizontal plane. The direction sensor 9 detects, for example, a direction of north. An electronic compass using magnetism may be used as the direction sensor 9.

(28) The route specifying unit 11 specifies a route on which the mobile terminal 7 has moved on the horizontal plane. The route specifying unit 11 specifies a movement route on the basis of the acceleration detected by the acceleration sensor 8 and the direction detected by the direction sensor 9. For example, the route specifying unit 11 calculates a movement amount of the mobile terminal 7 in the horizontal direction by integrating accelerations in the x- and y-axis directions detected by the acceleration sensor 8. The route specifying unit 11 specifies the movement route on the basis of the movement amount obtained by the calculation and the direction detected by the direction sensor 9. The route specifying unit 11 specifies the movement route on the basis of at least one of the acceleration detected by the acceleration sensor 8 and the direction detected by the direction sensor 9.

(29) FIG. 1 shows an example in which the system includes a transmitting device 27. The transmitting device 27 wirelessly transmits starting information to a predetermined transmission

area. The transmitting device **27** may use a wireless method such as Bluetooth® Low Energy (BLE). The receiving unit **12** receives the starting information transmitted from the transmitting device **27**. When the mobile terminal **7** exists in the transmission area of the transmitting device **27**, the starting information from the transmitting device **27** is received by the receiving unit **12**.

(30) The calculating unit **13** calculates a feature quantity of the route specified by the route specifying unit **11**. The calculating unit **13** divides the route specified by the route specifying unit **11** into a plurality of elements. The calculating unit **13** calculates the feature quantity on the basis of each of the elements obtained by the division.

(31) The determining unit **14** determines whether the route specified by the route specifying unit **11** is a boarding route. The boarding route is a route for a user to move on and board into the car **2**. A first determination condition for determining that the route specified by the route specifying unit **11** is a boarding route is previously stored in the storage unit **10**. The determining unit **14** determines on the basis of the feature quantity calculated by the calculating unit **13**.

(32) The call creating unit **15** creates call information used for requesting registering a hall destination call. The call information includes information on a boarding floor and information on a destination floor. The boarding floor is a floor at which a user boards the car **2**. The destination floor is a floor at which the user gets off the car **2**. The call creating unit **15** creates the call information when the determining unit **14** determines that the route specified by the route specifying unit **11** is a boarding route.

(33) The communicating unit **16** communicates with the communicating device **6**. The communicating unit **16** wirelessly transmits the call information created by the call creating unit **15** to the communicating device **6** when the determining unit **14** determines that the route specified by the route specifying unit **11** is a boarding route. The communication between the communicating unit **16** and the communicating device **6** may be carried out by wireless LAN. A public mobile phone network such as 3G and 4G and an Internet network may be used as a communication between the communicating unit **16** and the communicating device **6**.

(34) Upon receiving the call information from the mobile terminal **7**, the communicating device **6** transmits the received call information to the group controller **1**.

(35) With reference to FIGS. **2** to **12**, functions and operations of the elevator system will be described in detail. FIG. **2** is a flowchart for illustrating an operation example of the mobile terminal **7**. FIG. **3** is a plan view showing an example of a building in which the elevator system shown in FIG. **1** is applied.

(36) In the example shown in FIG. **3**, the elevator devices **A** to **C** face a passage **T1**. A passage **T2** meets up with the passage **T1**. The passages **T1** and **T2** form a T-junction. The transmitting device **27** is provided at a wall of the passage **T2**. FIG. **3** shows an example in which the transmitting device **27** is provided in a position apart from a hall. The transmitting device **27** may be provided at a wall of the hall. The transmission area of the transmitting device **27** is set so that the mobile terminal **7** receives the starting information when a user carrying the mobile terminal **7** passes in front of the transmitting device **27**.

(37) In the mobile terminal **7**, it is determined whether starting information from the transmitting device **27** has been received by the receiving unit **12** (**S101**). The transmitting device **27** transmits starting information at prescribed intervals. When a user carrying the mobile terminal **7** passes in front of the transmitting device **27**, the receiving unit **12** receives starting information transmitted from the transmitting device **27**.

(38) When the receiving unit **12** receives the starting information, the route specifying unit **11** starts processing for specifying a route on which the mobile terminal **7** has moved on the horizontal plane (**S102**). For example, when the receiving unit **12** receives the starting information, the acceleration sensor **8** starts to detect an acceleration and the direction sensor **9** starts to detect a direction. The route specifying unit **11** obtains information about the acceleration from the acceleration sensor **8** when the receiving unit **12** receives the starting information. The route specifying unit **11** obtains

information about the direction from the direction sensor **9** when the receiving unit **12** receives the starting information. The route specifying unit **11** specifies a movement route of the mobile terminal **7** on the basis of the acceleration detected by the acceleration sensor **8** and the direction detected by the direction sensor **9**. FIG. **4** shows an example of the route specified by the route specifying unit **11**. In FIG. **4**, the route specified by the route specifying unit **11** is designated by K. (39) The calculating unit **13** calculates a feature quantity of the route specified by the route specifying unit **11** (S103). FIGS. **5** to **8** are diagrams for illustrating functions of the calculating unit **13**. As illustrated in FIGS. **5** and **6**, the calculating unit **13** divides the route K specified by the route specifying unit **11** into a plurality of elements. In the example shown in FIGS. **5** and **6**, the route K is divided into elements k1, k2, and k3. In the example in FIG. **6**, the elements k1, k2, and k3 are each represented by a straight line vector. The element k1 is the closest to a boarding position J. The element k2 is the second closest to the boarding position J after the element k1. The element k3 is the furthest from the boarding position J. The boarding position J is previously set. This embodiment shows an example in which the boarding position J is set in the center position of the hall doors of the elevator device C. The boarding position J is not limited to the examples shown in FIG. **5** and other figures.

(40) The calculating unit **13** calculates a first index related to a distance and a second index related to an angle as feature quantities of the route specified by the route specifying unit **11**. In the following description, the first index is also referred to as a distance R. The second index is also referred to as an angle θ . For example, the distance R is calculated by the following expression 1. The angle θ is calculated by the following expression 2.

(41) [Math. 1]

$$R = \sum_{i=1}^N l_i R_i \quad (1)$$

$$\theta = \sum_{i=1}^N m_i \theta_i \quad (2)$$

(42) In expressions 1 and 2, N is the number of elements. In the example shown in FIG. **5**, N=3. R_i is a distance from an element. θ_i is an angle of an element. For example, as shown in FIG. **6**, the distance R1 from the element k1 is a distance between an end of the element k1 and the boarding position J. The angle θ_1 of the element k1 is an angle formed by the vector of the element k1 and a vector connecting the end of the element k1 and the boarding position J. As shown in FIG. **7**, the distance R2 from the element k2 is a distance between an end of the element k2 and the boarding position J. The angle θ_2 of the element k2 is an angle formed by the vector of the element k2 and a vector connecting the end of the element k2 and the boarding position J. As shown in FIG. **8**, the distance R3 from the element k3 is a distance between an end of the element k3 and the boarding position J. The angle θ_3 of the element k3 is an angle formed by the vector of the element k3 and a vector connecting the end of the element k3 and the boarding position J. The characters l_i and m_i represent coefficients. For example, the coefficient l_i is set to a greater value as the value of i is smaller so that an element closer to the boarding position J is given priority. Similarly, the coefficient m_i is set to a greater value as the value of i is smaller.

(43) When the calculating unit **13** calculates the feature quantities, the determining unit **14** determines whether the route specified by the route specifying unit **11** is a boarding route (S104). The determining unit **14** may use the determining method, for example, disclosed in the following non-patent literature.

(44) "The Development of Recognition System of Person Movement Based on RFID and Stereo Camera, Naohiko Suzuki, Kentaro Hayashi, Masafumi Iwata, Takuya Ishioka, and Koichi Sasakawa, Ubiquitous Computing System Study Group, Information Processing Society of Japan, September 2004, 2004-UBI-6"

(45) FIGS. **9** and **10** are diagrams for illustrating functions of the determining unit **14**. A route KA in FIG. **3** advances straightforward through the passage T2 toward the passage T1 and then curves to the left at the passage T1. FIG. **9** shows change with time in the indexes (R, θ) when the mobile terminal **7** moves on the route KA. In the example shown in FIG. **9**, the distance R and the angle θ

approach zero with time. For example, the determining unit **14** determines that the route specified by the route specifying unit **11** is a boarding route when the following expression 3 or 4 is satisfied for the indexes (R, θ).

[Math. 2]

$$(46) \quad \left\{ \begin{array}{l} R \leq R_a \\ \leq a \end{array} \right. \quad (3)$$

$$\left\{ \begin{array}{l} \leq \frac{a}{R_a - R_b} (R - R_b) \\ R_a < R \leq R_b \end{array} \right. \quad (4)$$

(47) A route KB shown in FIG. 3 advances straightforward through the passage T2 toward the passage T1, and then curves to the right at the passage T1. FIG. 10 shows change with time in the indexes (R, θ) when the mobile terminal 7 moves on the route KB. In the example in FIG. 10, the values of distance R and the angle θ increase before expression 3 or 4 is satisfied. In the example in FIG. 10, the determining unit **14** does not determine that the route specified by the route specifying unit **11** is a boarding route.

(48) If it is not determined in S104 that the route specified by the route specifying unit **11** is a boarding route, the determining unit **14** determines whether a prescribed period of time has elapsed after the start of processing for specifying the route in S102 (S105). The processing in steps S102 to S105 is repeatedly carried out until the result of determination in S104 or S105 is YES. If the prescribed period elapses and it is not determined by the determining unit **14** that the route specified by the route specifying unit **11** is a boarding route after the start of the processing for specifying the route in S102, the processing ends.

(49) If the result of determination is YES in S104 before the prescribed period elapses after the start of the processing for specifying the route in S102, the call creating unit **15** creates call information (S106). As described above, the call information includes information on a boarding floor and information on a destination floor. The boarding floor is set to a floor provided with the transmitting device 27. When the transmitting device 27 is provided at each of a plurality of floors at which the car 2 stops, each of the transmitting devices 27 transmits starting information including a signal used for specifying the installation floor thereof. For example, the transmitting device 27 provided at the first floor transmits starting information including a floor code of the first floor. In this case, the call creating unit **15** sets a boarding floor on the basis of the starting information received from the transmitting device 27.

(50) The information on the destination floor is previously stored, for example, in the storage unit **10**. The call creating unit **15** may set a destination floor from usage data in the past. For example, the call creating unit **15** sets the most frequently used floor as the destination floor. The frequency may be learned in consideration of combinations with boarding floors. In this case, the call creating unit **15** sets the floor used most frequently from the present boarding floor as the destination floor.

(51) The communicating unit **16** wirelessly transmits the call information created by the call creating unit **15** (S107).

(52) FIG. 11 is a flowchart for illustrating an operation example of the group controller 1. As illustrated in FIG. 1, the group controller 1 includes a registering unit **28**, an assigning unit **29**, and an instructing unit **30**. The group controller 1 determines whether call information from the communicating device 6 has been received (S201). Upon receiving call information from the mobile terminal 7, the communicating device 6 transmits the received call information to the group controller 1. The registering unit **28** registers a hall destination call on the basis of the call information received by the communicating device 6 (S202). The assigning unit **29** determines an assigned car 2 to the hall destination call registered in S202 (S203).

(53) When the assigning unit **29** determines the assigned car, the instructing unit **30** transmits, to the controller 4, a response instruction which causes the assigned car to respond to the hall

destination call (S204). For example, when the assigned car is a car 2A, the instructing unit 30 transmits the response instruction to the controller 4A. The controller 4 controls the traction machine 3, the door motor 5, and other devices on the basis of the response instruction received from the instructing unit 30.

(54) FIG. 1 shows an example in which the mobile terminal 7 further includes a display control unit 17 and a display 25. The display control unit 17 controls the display 25. When the mobile terminal 7 includes the display 25, the assigning unit 29 determines an assigned car, and then has the communicating device 6 transmit information on the assigned car to the mobile terminal 7 (S205).

(55) When the mobile terminal 7 transmits the call information to the communicating device 6 in S107, it is determined whether information on the assigned car has been received from the communicating device 6 as a response (S108). The information on the assigned car transmitted from the communicating device 6 in S205 is received by the communicating unit 16. The display control unit 17 controls the display 25 to display the information on the assigned car received by the communicating unit 16 (S109). Users can easily understand which car 2 to board by looking at the display 25.

(56) FIG. 12 is a view showing a display example of the display 25. The display control unit 17 controls the display 25 to display "A" which refers to the car 2A as the assigned car when, for example, the assigned car is the car 2A. The display control unit 17 may control the display 25 to display information on a hall destination call registered by the group controller 1. For example, when the boarding floor is the first floor and the destination floor is the eighth floor, the display control unit 17 controls the display 25 to display a message such as "1F.fwdarw.8F registered."

(57) In the example according to this embodiment, the determining unit 14 determines whether the route specified by the route specifying unit 11 is a boarding route. When the determining unit 14 determines that the route specified by the route specifying unit 11 is a boarding route, call information created by the call creating unit 15 is transmitted to the communicating device 6. Therefore, a call for a user can be registered automatically. Also in the example according to this embodiment, the movement route of the mobile terminal 7 on the horizontal plane is specified by the route specifying unit 11. The feature quantity of the route specified by the route specifying unit 11 is calculated by the calculating unit 13. The determining unit 14 determines on the basis of the feature quantity calculated by the calculating unit 13. Therefore, a user boarding the car 2 can be determined with high accuracy, so that useless call registration can be prevented.

(58) Hereinbelow, other functions which may be used in this system will be described.

(59) As shown in FIG. 1, the mobile terminal 7 may further include a selecting unit 18. When the mobile terminal 7 includes the selecting unit 18, a plurality of setting values necessary for calculating a feature quantity are previously stored in the storage unit 10. For example, a plurality of coordinates are stored in the storage unit 10 as the boarding position J. The selecting unit 18 selects one of the plurality of setting values stored in the storage unit 10. The calculating unit 13 calculates a feature quantity using the setting value selected by the selecting unit 18.

(60) When the mobile terminal 7 includes the selecting unit 18, a plurality of first determination conditions necessary for determining a boarding route are previously stored in the storage unit 10. The selecting unit 18 selects one of the plurality of the first determination conditions stored in the storage unit 10. The determining unit 14 determines whether the route specified by the route specifying unit 11 is a boarding route on the basis of the feature quantity calculated by the calculating unit 13 and the first determination condition selected by the selecting unit 18.

(61) For example, depending on the building, the way to get to a hall in some floors may be different from that in the other floors. In the case, a feature quantity must be calculated using an appropriate boarding position J. The first determination condition may desirably be changed depending on the way to get to the hall. For example, when the transmitting device 27 is provided at each of a plurality of floors at which the car 2 stops, the transmitting device 27 wirelessly

transmits starting information including a signal used for specifying the installation floor thereof. The selecting unit **18** selects a setting value corresponding to the installation floor of the transmitting device **27** and the first determination condition on the basis of the starting information received by the receiving unit **12**.

(62) FIG. **13** is a plan view showing another example of a building in which the elevator system shown in FIG. **1** is applied. FIG. **13** shows an example of the way to get to a hall not only through the passage **T2** but also through the passage **T3**. The passage **T3** meets up with the passage **T1**. The passages **T1** and **T3** form a T-junction. In the example shown in FIG. **13**, the transmitting device **27a** is provided at the wall of the passage **T2**. The transmission area of the transmitting device **27a** is set so that the mobile terminal **7** receives starting information when a user carrying the mobile terminal **7** passes in front of the transmitting device **27a**. Similarly, a transmitting device **27b** is provided at a wall of the passage **T3**. The transmission area of the transmitting device **27b** is set so that the mobile terminal **7** receives starting information when a user carrying the mobile terminal **7** passes in front of the transmitting device **27b**.

(63) A route **KA1** shown in FIG. **13** is the same as the route **KA** shown in FIG. **3**. A route **KB1** shown in FIG. **13** is the same as the route **KB** shown in FIG. **3**. A route **KA2** shown in FIG. **13** advances straightforward through the passage **T3** toward the passage **T1** and then curves to the right at the passage **T1**. A route **KB2** shown in FIG. **13** advances straightforward through the passage **T3** toward the passage **T1** and then curved to the left at the passage **T1**. In the example shown in FIG. **13**, the determining unit **14** must determine that the route specified by the route specifying unit **11** is a boarding route when the mobile terminal **7** moves on the route **KA1**. Similarly, the determining unit **14** must determine that the route specified by the route specifying unit **11** is a boarding route when the mobile terminal **7** moves on the route **KA2**.

(64) The mobile terminal **7** may include the selecting unit **18** when a plurality of transmitting devices **27** are provided on the same floor. In this case, the transmitting devices **27** each wirelessly transmit starting information including a signal used for specifying the installation position thereof. For example, each of the transmitting devices **27** transmits starting information including a code used for specifying itself. The selecting unit **18** selects a setting value corresponding to the installation position of the transmitting device **27** and a first determination condition on the basis of the starting information received by the receiving unit **12**.

(65) As shown in FIG. **1**, the mobile terminal **7** may further include a determining unit **19**. The determining unit **19** determines whether the mobile terminal **7** has moved in the vertical direction in a particular movement pattern. The determining unit **19** determines on the basis of the vertical acceleration detected by the acceleration sensor **8**. For example, when the car **2** moves from one floor to another floor, the car **2** is accelerated, then moved at a constant speed, and then decelerated. The car **2** increases its speed with a constant acceleration, the value of which often ranges from 0.3 m/s.² to 1.0 m/s.². Upon reaching a certain value, the acceleration value as the car **2** increases its speed does not change for a prescribed period of time. Such behavior is the same when the car **2** decelerates. For example, the determining unit **19** determines that the mobile terminal **7** has moved in the vertical direction in the particular movement pattern when the vertical acceleration detected by the acceleration sensor **8** reaches a certain range and then the state continues for a prescribed period of time. More specifically, the determining unit **19** determines that the mobile terminal **7** is in the moving car **2**.

(66) Users rarely follow a route to be determined as a boarding route by the determining unit **14** immediately after leaving the car **2**. Therefore, when the determining unit **19** determines that the mobile terminal **7** is in the moving car **2**, the determining unit **14** does not determine for a prescribed period thereafter that the route specified by the route specifying unit **11** is a boarding route. In this way, a hall destination call can be prevented from being erroneously registered in the group controller **1**.

(67) Note that when the acceleration sensor **8** detects change in both the horizontal and vertical

accelerations, the route on which the mobile terminal **7** has moved on the horizontal plane may not be specified accurately. In this case, the route specifying unit **11** does not have to specify a route. Alternatively, the determining unit **14** does not have to determine whether the route specified by the route specifying unit **11** is a boarding route.

(68) As shown in FIG. **1**, the group controller **1** may further include a time setting unit **31**. The time setting unit **31** sets time at which an assigned car is made to stand by in an open-door state.

(69) As described above, the distance **R1** is the distance between the end of the element **k** and the boarding position **J**. Therefore, when a walking speed of a user is previously set, the time until a user carrying the mobile terminal **7** arrives at the boarding position **J** can be calculated. The walking speed is set to a value, for example, in the range from 1.0 m/s to 1.2 m/s. The walking speed is previously stored in the storage unit **10**. The calculating unit **13** calculates a first arrival time period until a user arrives at the boarding position **J** using the walking speed stored in the storage unit **10**. The call creating unit **15** creates call information including information on the first arrival time period calculated by the calculating unit **13** in addition to the information on the boarding floor and the destination floor when the route specified by the route specifying unit **11** is determined as a boarding route by the determining unit **14**. The communicating unit **16** wirelessly transmits the call information created by the call creating unit **15**.

(70) In the group controller **1**, the assigning unit **29** determines an assigned car in response to a hall destination call. The time setting unit **31** calculates a second arrival time period until the assigned car arrives at the boarding floor when the assigning unit **29** determines the assigned car. The time setting unit **31** sets time resulting from adding the first arrival time period to the present time as expected boarding time when the first arrival time period is longer than the second arrival time period. The instructing unit **30** transmits, to the controller **4**, a response instruction for keeping the assigned car in an open-door standby state at the boarding floor until the expected boarding time when the expected boarding time is set by the time setting unit **31**. In this way, the assigned car stands by in an open-door state until the expected boarding time after arriving at the boarding floor. When the group controller **1** includes the time setting unit **31**, users can be prevented from being late for boarding. Note that when there are a plurality of hall destination calls for the same boarding floor and in the same moving direction for the same assigned car, the time setting unit **31** may set the time resulting from adding the longest first arrival time period to the present time as the expected boarding time.

(71) In the described example according to the embodiment, when the receiving unit **12** receives starting information from the transmitting device **27**, the route specifying unit **11** starts processing for specifying a route. In this example, the start of the route can be clear, and the route can be specified accurately. Meanwhile, this is only an example. The route specifying unit **11** may start processing for specifying a route on the basis of any of other conditions.

(72) In the example shown in FIG. **1**, the mobile terminal **7** further includes an input device **26**. A user inputs information from the input device **26**. For example, the user inputs starting information from the input device **26**. The input device **26** is, for example, a mechanical button having a contact. The input device **26** may be a touch panel button. These examples are not intended to limit the method for inputting information from the input device **26**. The route specifying unit **11** may start processing for specifying a route in **S102** when the starting information is input from the input device **26**.

(73) The route specifying unit **11** may start processing for specifying a route in **S102** when the acceleration sensor **8** detects a particular acceleration pattern. For example, the route specifying unit **11** starts the processing described above when the acceleration sensor **8** consecutively detects accelerations greater than or equal to a prescribed value. In this example, a user may vibrate the mobile terminal **7** to transmit call information to the group controller **1** when the user desires to use the elevator device.

(74) The route specifying unit **11** may start processing for specifying a route in **S102** when wireless

IC card authentication is carried out. The function of the wireless IC card may be provided in the mobile terminal 7. A user may carry the wireless IC card separately from the mobile terminal 7. When the mobile terminal 7 is provided with the wireless IC card function, the user places the mobile terminal 7 over a card reader, a security gate or the like. When the mobile terminal 7 is provided with the wireless IC card function, the communicating method may be NFC (Near Field Communication) which is a short-distance wireless communication system.

(75) In the described example according to the embodiment, when the receiving unit 12 receives starting information from the transmitting device 27, the route specifying unit 11 always starts processing for specifying a route. Meanwhile, this is only an example. The function of automatically registering a call may be valid only for a particular period of time. The function of automatically registering a call may be valid only at a particular floor or a particular hall. When the automatic registration function is not valid, users may manually input a destination floor from the mobile terminal 7.

(76) In the described example according to the embodiment, the display control unit 17 controls the display 25 to display information on an assigned car. The display control unit 17 may control the display 25 to display other kinds of information. FIG. 14 is a view showing another display example of the display 25. The display control unit 17 controls the display 25 to display a method for acknowledging and cancelling call registration when the communicating unit 16 receives the information on an assigned car from the communicating device 6. When an operation for acknowledging the call registration is carried out, the communicating unit 16 transmits information for confirming the call registration, in other words, confirmation information to the communicating device 6. In this case, the instructing unit 30 in the group controller 1 transmits a response instruction to the controller 4 after the communicating device 6 receives the confirmation information. Meanwhile, when an operation of cancelling the call registration is carried out, the communicating unit 16 transmits information for canceling the call registration, in other words, cancel information to the communicating device 6. When the communicating device 6 receives the cancel information from the mobile terminal 7, the group controller 1 cancels the hall destination call registered in S202.

(77) For example, the display control unit 17 controls the display 25 to display an OK button 25a and a cancel button 25b when the communicating unit 16 receives information on an assigned car from the communicating device 6. When the OK button 25a is pressed, the communicating unit 16 transmits confirmation information to the communicating device 6. When the cancel button 25b is pressed, the communicating unit 16 transmits cancel information to the communicating device 6. When the cancel button 25b is pressed, the display control unit 17 may control the display 25 to display guidance or the like for manually transmitting call information. In this example, the car 2 can be prevented from responding to an irrelevant call. Also, an erroneously registered call if any can quickly be canceled.

(78) In the described example according to the embodiment, the calculating unit 13 calculates the distance R and the angle θ as feature quantities of a route. More specifically, the calculating unit 13 calculates the distance R using the position of a point on each element and a boarding position. The calculating unit 13 calculates the angle θ using the vector representing each element and a vector connecting the position of the point on the element and the boarding position. In this example, the determination accuracy by the determining unit 14 can be improved. Meanwhile, this is merely an example. The calculating unit 13 may calculate only the distance R as a feature quantity of a route. The calculating unit 13 may calculate only the angle θ as a feature quantity of a route.

Alternatively, the calculating unit 13 may calculate a change ratio in the angle θ as a feature quantity of a route. The calculating unit 13 may calculate a horizontal speed as a feature quantity of a route. Note that when the calculating unit 13 calculates only the distance R , the end point of the route needs only be determined, and the entire route does not have to be specified.

(79) In the described example according to the embodiment, the calculating unit 13 calculates a

feature quantity on the basis of a plurality of elements. Meanwhile, this is merely an example. The calculating unit **13** may calculate a feature quantity only on the basis of the newest element. The calculating unit **13** may calculate a feature quantity using the route specified by the route specifying unit **11** as is without dividing the route.

Second Embodiment

(80) In the following example according to this embodiment, a system includes functions of creating a first determination condition. FIG. **15** is a diagram illustrating an example of an elevator system according to a second embodiment of the present invention. FIG. **15** shows only functions necessary for creating the first determination condition. The mobile terminal **7** further includes, for example, a route recording unit **20**, a boarding route specifying unit **21**, a calculating unit **22**, and a condition creating unit **23**. Note that the elevator system according to this embodiment includes all the devices and functions disclosed in the first embodiment. In the example shown in FIG. **15**, some of the devices and functions necessary for automatically registering a hall destination call are not shown.

(81) As described above, the acceleration sensor **8** detects the acceleration of the mobile terminal **7**. The direction sensor **9** detects a particular direction on a horizontal plane. The receiving unit **12** receives starting information transmitted from the transmitting device **27**. The determining unit **19** determines whether the mobile terminal **7** has moved in the vertical direction in a particular movement pattern.

(82) The route recording unit **20** records a route on which the mobile terminal **7** has moved on a horizontal plane. The route recording unit **20** records a movement route on the basis of the acceleration detected by the acceleration sensor **8** and the direction detected by the direction sensor **9**. For example, the route recording unit **20** integrates accelerations in the x-axis direction and accelerations in the y-axis direction detected by the acceleration sensor **8** and calculates a horizontal movement amount of the mobile terminal **7**. The route recording unit **20** records a movement route on the basis of the movement amount obtained by the calculation and the direction detected by the direction sensor **9**. The route recording unit **20** records a movement route on the basis of at least one of the acceleration detected by the acceleration sensor **8** and the direction detected by the direction sensor **9**.

(83) FIG. **15** shows an example in which the system includes the transmitting device **27**. As described above, the transmitting device **27** wirelessly transmits starting information to a predetermined transmission area. When the mobile terminal **7** exists in the transmission area of the transmitting device **27**, the starting information from the transmitting device **27** is received by the receiving unit **12**.

(84) When the determining unit **19** determines that the mobile terminal **7** has moved in the vertical direction in the particular movement pattern, the boarding route specifying unit **21** specifies a route recorded immediately before by the route recording unit **20** as a boarding route. The route specified as a boarding route by the boarding route specifying unit **21** is recorded in the storage unit **10**.

(85) The calculating unit **22** calculates a feature quantity of the route specified as a boarding route by the boarding route specifying unit **21**. The calculating unit **22** divides the route specified as a boarding route by the boarding route specifying unit **21** into a plurality of elements. The calculating unit **22** calculates the feature quantity on the basis of each of the elements obtained by the division.

(86) The condition creating unit **23** creates a first determination condition to be used by the determining unit **14** to determine a route as a boarding route. The condition creating unit **23** creates the first determination condition on the basis of the feature quantity calculated by the calculating unit **22**. The condition creating unit **23** has the storage unit **10** store the created first determination condition. The determining unit **14** carries out determination shown in **S104** in FIG. **2** on the basis of the first determination condition created by the condition creating unit **23**.

(87) With reference also to FIGS. **16** to **18**, functions and operations of the elevator system will be described in detail. FIG. **16** is a flowchart for illustrating an operation example of the mobile

terminal 7.

(88) The mobile terminal 7 determines whether starting information from the transmitting device 27 has been received by the receiving unit 12 (S301). When a user carrying the mobile terminal 7 passes in front of the transmitting device 27, the starting information transmitted from the transmitting device 27 is received by the receiving unit 12.

(89) The route recording unit 20 starts processing for recording a route on which the mobile terminal 7 has moved on a horizontal plane when the receiving unit 12 receives the starting information (S302). For example, when the receiving unit 12 receives the starting information, the acceleration sensor 8 starts to detect an acceleration and the direction sensor 9 starts to detect a direction. When the receiving unit 12 receives the starting information, the route recording unit 20 obtains information on the acceleration from the acceleration sensor 8. The route recording unit 20 obtains information on the direction from the direction sensor 9 when the receiving unit 12 receives the starting information. The route recording unit 20 specifies a movement route of the mobile terminal 7 on the basis of the acceleration detected by the acceleration sensor 8 and the direction detected by the direction sensor 9 and records the specified route.

(90) The determining unit 19 determines whether the mobile terminal 7 has moved in the vertical direction in a particular movement pattern when the receiving unit 12 receives starting information (S303). The determining unit 19 carries out determination on the basis of the vertical acceleration detected by the acceleration sensor 8. As described above, when the car 2 moves from one floor to another floor, the car 2 is accelerated, then moved at a constant speed, and then decelerated. The car 2 is accelerated with a constant acceleration, the value of which is often in the range from 0.3 m/s.² to 1.0 m/s.². Furthermore, the value of the acceleration of the accelerated car 2 becomes unchanged for a prescribed period of time after reaching a certain value. Such behavior is the same for the car 2 during deceleration. For example, the determining unit 19 determines that the mobile terminal 7 has moved in the vertical direction in the particular movement pattern when an acceleration in the vertical direction detected by the acceleration sensor 8 is within a certain range and then the state continues for a prescribed period of time. In other words, the determining unit 19 determines that the mobile terminal 7 is in the moving car 2.

(91) When the determining unit 19 determines that the mobile terminal 7 has moved in the vertical direction in the particular movement pattern, the boarding route specifying unit 21 specifies the route recorded immediately before by the route recording unit 20 as a boarding route (S304). The boarding route specifying unit 21 has the route specified as a boarding route stored in the storage unit 10 (S305).

(92) The boarding route specifying unit 21 determines whether a prescribed period of time has elapsed after the start of the processing for recording a route in S302 when the determining unit 19 does not determine that the mobile terminal 7 has moved in the vertical direction in the particular movement pattern (S306). The processing shown in S302, S303, and S306 is repeatedly carried out until the result of the processing shown in S303 or S306 is YES. When the result of the determination in S303 is not YES after the elapse of the prescribed period of time from the start of recording of the route by the route recording unit 20 in S302, the boarding route specifying unit 21 specifies the route recorded immediately before by the route recording unit 20 as a non-boarding route (S307). The non-boarding route is a route on which a user who does not board the car 2 moves. The boarding route specifying unit 21 has the storage unit 10 store the route specified as a non-boarding route (S308).

(93) The calculating unit 22 calculates a feature quantity of the route stored as a boarding route in the storage unit 10. Similarly, the calculating unit 22 calculates a feature quantity of the route stored as a non-boarding route in the storage unit 10 (S309). The calculating unit 22 may calculate the feature quantity in the same manner as the calculating unit 13 calculates a feature quantity. For example, the calculating unit 22 divides the route stored as a boarding route in the storage unit 10 into a plurality of elements. The calculating unit 22 calculates a feature quantity of the route on the

basis of the elements obtained by the division. For example, the calculating unit **22** calculates a first index related to a distance and a second index related to an angle as feature quantities of the boarding route. Similarly, the calculating unit **22** divides the route stored as a non-boarding route in the storage unit **10** into a plurality of elements. The calculating unit **22** calculates a feature quantity of the route on the basis of the elements obtained by the division. For example, the calculating unit **22** calculates a first index related to a distance and a second index related to an angle as feature quantities of the non-boarding route.

(94) The condition creating unit **23** creates a first determination condition on the basis of the feature quantities calculated by the calculating unit **22** (S310). For example, the condition creating unit **23** creates a first determination condition as represented by expressions 3 and 4. In this case, the condition creating unit **23** determines values for R_a , R_b , and θ_a on the basis of the feature quantities calculated by the calculating unit **22**.

(95) FIGS. **17** and **18** are diagrams for illustrating functions of the condition creating unit **23**. FIG. **17** shows change with time in the feature quantities of boarding routes. The condition creating unit **23** sets the first determination condition so that each of lines representing change with time in the feature quantities of the boarding routes enters the range for the determining unit **14** to determine the boarding route from the outside. FIG. **18** shows change with time in the feature quantities of non-boarding routes. The condition creating unit **23** sets the first determination condition so that each of lines representing change with time in the feature quantities of the non-boarding routes does not enter the range for the determining unit **14** to determine a boarding route.

(96) Note that the condition creating unit **23** may create the first determination condition so that the area of the range for the determining unit **14** to determine a boarding route is maximized. The condition creating unit **23** may create the first determination condition so that the distance R is given priority over the angle θ . The condition creating unit **23** may create the first determination condition so that the angle θ is given priority over the distance R . The condition creating unit **23** may create the first determination condition so that the determination error by the determining unit **14** is not more than a prescribed value. For example, the condition creating unit **23** creates the first determination condition so that the determination error by the determining unit **14** is not more than 5%. The condition creating unit **23** has the created first determination condition stored in the storage unit **10** (S311).

(97) In the example according to the embodiment, the calculating unit **22** calculates the feature quantities of the route specified as a boarding route by the boarding route specifying unit **21**. The condition creating unit **23** creates the first determination condition on the basis of the feature quantities calculated by the calculating unit **22**. Therefore, it is not necessary to previously set map information on each floor, positional information on the transmitting device **27** and the like. The first determination condition can be created only by using the relative positional relation between the transmitting device **27** and the mobile terminal **7**. In the example according to the embodiment, when the determining unit **19** determines that the mobile terminal **7** has moved in the vertical direction in the particular movement pattern, the route recorded immediately before by the route recording unit **20** is specified as a boarding route. Therefore, the boarding route can be specified accurately.

(98) Other functions which can be used in this system will be described.

(99) As shown in FIG. **15**, the mobile terminal **7** may further include a moving time learning unit **24**. The moving time learning unit **24** learns a first arrival time period for a user to arrive at the boarding position J from a position in which the first determination condition created by the condition creating unit **23** is satisfied. The moving time learning unit **24** has a learning result, for example, stored in the storage unit **10**. In this case, the call creating unit **15** creates call information including information on the first arrival time period stored in the storage unit **10** when the determining unit **14** determines that the route specified by the route specifying unit **11** is a boarding route. The communicating unit **16** wirelessly transmits the call information created by the call

creating unit **15**.

(100) When the transmitting device **27** is provided at each of a plurality of floors of a building, the condition creating unit **23** may create a first determination condition for each of the floors provided with the transmitting device **27**. For example, when the transmitting device **27** is provided at each of the floors at which the car **2** stops, each of the transmitting devices **27** wirelessly transmits starting information including a signal used for specifying the installation floor thereof. For example, the transmitting device **27** provided at the first floor transmits starting information including a floor code of the first floor.

(101) When the transmitting devices **27** are provided in a plurality of positions on a horizontal plane, the condition creating unit **23** may create a first determination condition for each of the installation positions of the transmitting devices **27**. For example, when a plurality of transmitting devices **27** are provided at the same floor of a building, the condition creating unit **23** creates a first determination condition for each of the installation positions of the transmitting devices **27**. In this case, each of the transmitting devices **27** wirelessly transmits starting information including a signal used for specifying the installation position thereof. For example, each of the transmitting devices **27** transmits starting information including a code used for specifying itself.

(102) In the described example according to the embodiment, the mobile terminal **7** is provided with functions necessary for creating the first determination condition. This is merely an example. Some or all of the route recording unit **20**, the boarding route specifying unit **21**, the calculating unit **22**, and the condition creating unit **23** may be included in a server as a discrete device from the mobile terminal **7**. The server may include a function corresponding to the storage unit **10** and a function corresponding to the determining unit **19**. The server may include the moving time learning unit **24**.

(103) For example, the mobile terminal **7** includes the boarding route specifying unit **21**. The server may include the calculating unit **22** and the condition creating unit **23**. The boarding route specifying unit **21** has a route specified as a boarding route stored in a storage unit included in the server. The boarding route specifying unit **21** has a route specified as a non-boarding route stored in the storage unit included in the server. The condition creating unit **23** transmits information on the created first determination condition to the mobile terminal **7**. In this way, the first determination condition created by the condition creating unit **23** is stored in the storage unit **10** of the mobile terminal **7**.

(104) In this example, the server may obtain route information from a plurality of mobile terminals **7**. The condition creating unit **23** may create a first determination condition for each of the mobile terminals **7**. The condition creating unit **23** may create a first determination condition which is common among the plurality of mobile terminals **7**.

(105) In the described example according to the embodiment, the determining unit **19** determines that the mobile terminal **7** has moved in the vertical direction in a particular movement pattern when a certain movement condition is satisfied. The determining unit **19** may determine that the mobile terminal **7** has moved in the vertical direction in the particular movement pattern when another movement condition is satisfied. For example, the determining unit **19** may determine that the mobile terminal **7** has moved in the vertical direction in the particular movement pattern when the mobile terminal **7** has moved in the vertical direction for a prescribed distance. The determining unit **19** may determine that the mobile terminal **7** has moved in the vertical direction in the particular movement pattern when the vertical speed of the mobile terminal **7** changes at least by a prescribed value. The determining unit **19** may determine that the mobile terminal **7** has moved in the vertical direction in the particular movement pattern when two of the above three movement conditions are satisfied. The determining unit **19** may determine that the mobile terminal **7** has moved in the vertical direction in the particular movement pattern when all the three conditions are satisfied. The determining method by the determining unit **19** may be applied to the example according to the first embodiment. According to the illustrated examples, the user's movement in

the car **2** can be determined more accurately.

(106) Users rarely moves on a route which is valid as a sample for specifying a boarding or non-boarding route immediately after getting off from the car **2**. Therefore, the route recording unit **20** does not have to record a route for a prescribed period of time after the determining unit **19** determines that the mobile terminal **7** has moved in the vertical direction in the particular movement pattern. The route recording unit **20** does not have to record a route until the mobile terminal **7** is without a particular range when the determining unit **19** determines that the mobile terminal **7** has moved in the vertical direction in the particular movement pattern. The particular range is set, for example, on the basis of the distance from the boarding position J. In this way, the route immediately after the user gets off from the car **2** may be excluded from a boarding route and a non-boarding route, so that a highly accurate first determination condition can be produced.

(107) In the described example according to the embodiment, the boarding route specifying unit **21** specifies a route as a non-boarding route in **S306** when a particular condition is satisfied. When another particular condition is satisfied, the boarding route specifying unit **21** may specify a route recorded immediately before by the route recording unit **20** as a non-boarding route. For example, when the route recording unit **20** records a route for a prescribed distance but the determining unit **19** does not determine that the mobile terminal **7** has moved in the vertical direction in a particular movement pattern, the boarding route specifying unit **21** may specify the route as a non-boarding route. When the movement of the mobile terminal **7** away from the boarding position J is detected before the determining unit **19** determines that the mobile terminal has moved in the vertical direction in the particular movement pattern, the boarding route specifying unit **21** may specify a non-boarding route. The boarding route specifying unit **21** may specify a non-boarding route when two of the above three particular conditions are satisfied. The boarding route specifying unit **21** may specify a non-boarding route when all the three movement conditions are satisfied. Note that the boarding route specifying unit **21** may specify only a boarding route. Meanwhile, when the boarding route specifying unit **21** specifies both boarding and non-boarding routes, a highly accurate first determination condition can be produced.

(108) In the described examples according to the first and second embodiments, the elevator system includes the group controller **1**. The system may include only one elevator device. In this case, the controller **4** of the elevator device is provided with the registering unit **28**, the instructing unit **30**, and the time setting unit **31**.

(109) The units designated by reference numerals **28** to **31** are the functions of the group controller **1**. FIG. **19** is a diagram showing an example of a hardware configuration of the group controller **1**. The group controller **1** includes processing circuitry including, for example, a processor **32** and a memory **33** as hardware resources. The group controller **1** implements the function of each of the units designated by **28** to **31** as the processor **32** executes a program stored in the memory **33**.

(110) The units designated by reference numerals **10** to **24** are the functions of the mobile terminal **7**. FIG. **20** is a diagram showing an example of a hardware configuration of the mobile terminal **7**. The mobile terminal **7** includes processing circuitry including, for example, a processor **34** and a memory **35** as hardware resources. The function of the storage unit **10** is implement by the memory **35**. The mobile terminal **7** implements the function of each of the units designated by reference numerals **11** to **24** as the processor **34** executes a program stored in the memory **35**.

(111) The processors **32** and **34** are each also referred to as a CPU (Central Processing Unit), a central processor, a processing device, an arithmetic device, a microprocessor, a microcomputer or a DSP. As each of the memory **33** and the memory **35**, a semiconductor memory, a magnetic disk, a flexible disk, an optical disk, a compact disk, a minidisk or a DVD may be adopted. The available semiconductor memory may include a RAM, a ROM, a flash memory, an EPROM and an EEPROM.

(112) A part of or all of each of the functions included in the group controller **1** may be implemented by hardware. A part of or all of each of the functions included in the mobile terminal

7 may be implemented by hardware. As the hardware for implementing the functions included in the group controller 1 and the functions included in the mobile terminal 7, a single circuit, a composite circuit, a programmed processor, a parallel-programmed processor, an ASIC, an FPGA or a combination of thereof may be adopted.

INDUSTRIAL APPLICABILITY

(113) The present invention is applicable to an elevator system which automatically registers a call.

(114) TABLE-US-00001 Reference Signs List 1 group controller, 2 car, 3 traction machine, 4 controller, 5 door motor, 6 communicating device, 7 mobile terminal, 8 acceleration sensor, 9 direction sensor, 10 storage unit, 11 route specifying unit, 12 receiving unit, 13 calculating unit, 14 determining unit, 15 call creating unit, 16 communicating unit, 17 display control unit, 18 selecting unit, 19 determining unit, 20 route recording unit, 21 boarding route specifying unit, 22 calculating unit, 23 condition creating unit, 24 moving time learning unit, 25 display, 25a OK button, 25b cancel button, 26 input device, 27 transmitting device, 28 registering unit, 29 assigning unit, 30 instructing unit, 31 time setting unit, 32 processor, 33 memory, 34 processor, 35 memory

Claims

1. An elevator system, including a group controller which controls a plurality of elevator devices as a group in response to call information from a mobile terminal, the mobile terminal having an acceleration sensor and a direction sensor which detects a particular direction on a horizontal plane, the elevator system comprising: first processing circuitry configured to specify a route on which the mobile terminal has moved on the horizontal plane on the basis of at least one of the acceleration detected by the acceleration sensor and the direction detected by the direction sensor; the first processing circuitry is configured to calculate an angle-related index as a part of a feature quantity of the specified route, the angle-related index being calculated using a vector representing an element or elements of the route and a vector connecting a position of a point on the element or elements of the route and a boarding position; the first processing circuitry is configured to determine whether the specified route is a boarding route for boarding a car on the basis of the feature quantity; and the first processing circuitry is configured to transmit the call information in response to determining that the specified route is the boarding route; and second processing circuitry configured to register a call on the basis of the call information.
2. The elevator system according to claim 1, wherein the first processing circuitry is configured to calculate a distance-related index as a further part of the feature quantity of the specified route, the distance-related index is calculated using a position of the point on the element or elements of the route and the boarding position.
3. The elevator system according to claim 1, further comprising a transmitter configured to wirelessly transmit starting information, wherein the first processing circuitry is configured to receive the starting information from the transmitter, and the first processing circuitry is configured to start processing for specifying a route in response to receiving the starting information from the transmitter.
4. The elevator system according to claim 1, further comprising an input device used by a user to input starting information, wherein the first processing circuitry is configured to start processing for specifying a route when the starting information is input from the input device.
5. The elevator system according to claim 1, the first processing circuitry is configured to start processing for specifying a route when a particular acceleration pattern is detected by the acceleration sensor.
6. The elevator system according to claim 1, wherein the second processing circuitry is configured to determine an assigned car to the registered call, and the first processing circuitry is configured to cause information on the assigned car to be displayed on a display of the mobile terminal.
7. The elevator system according to claim 6, wherein the first processing circuitry is configured to

- cause a method for cancelling call registration to be displayed on the display when the information on the assigned car is received.
8. The elevator system according to claim 1, the second processing circuitry is configured to determine an assigned car to the registered call, and the second processing circuitry is configured to set time for keeping the assigned car in an open-door standby state at a boarding floor.
9. The elevator system according to claim 1, wherein the first processing circuitry is further configured to divide the specified route into a plurality of straight line segments, and to calculate the feature quantity based on an angle and a distance to the car of each of the plurality of straight line segments.
10. An elevator system, including a group controller which controls a plurality of elevator devices as a group in response to call information from a mobile terminal, the mobile terminal having an acceleration sensor and a direction sensor which detects a particular direction on a horizontal plane, the elevator system comprising: a first processor and first memory configured to specify a route on which the mobile terminal has moved on the horizontal plane on the basis of at least one of the acceleration detected by the acceleration sensor and the direction detected by the direction sensor; the first processor and first memory are configured to calculate an angle-related index as a part of a feature quantity of the specified route, the angle-related index being calculated using a vector representing an element or elements of the route and a vector connecting a position of a point on the element or elements of the route and a boarding position; the first processor and first memory are configured to determine whether the specified route is a boarding route for boarding a car on the basis of the feature quantity; the first processor and first memory are configured to transmit the call information in response to determining that the specified route is the boarding route; and a second processor and second memory configured to register a call on the basis of the call information.
-