

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412192
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Hardham; Lee et al.

System for providing information

Abstract

A messaging system comprising: a user device to: receive a beacon ID from a local beacon device when within a communication distance of the local beacon device; communicate information enabling a merchant database to identify a merchant profile associated with the local beacon device in response to receiving the beacon ID; and receive product message(s) for presentation via a user interface of the user device, the merchant database comprising merchant profile(s), each merchant profile comprising data entries associated with product(s), a user database comprising user profile(s), and a comparison server to: receive from the merchant database a merchant profile associated with a beacon ID obtained by the user device and a user profile associated with the user device from the user database; identify, based on the received merchant profile and user profile, product message(s) for communication to the user device; and communicate the product message(s) to the user device.

Inventors:	Hardham; Lee (Brunswick, AU), Yeluri; Rajesh (Brunswick, AU)
Applicant:	Honeycomb Media Pty Ltd (Brunswick, AU)
Family ID:	63583870
Assignee:	Honeycomb Media Pty Ltd (Brunswick, AU)
Appl. No.:	18/665427
Filed:	May 15, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240370901 A1	Nov. 07, 2024

Foreign Application Priority Data

AU	2017901317	Mar. 24, 2017
----	------------	---------------

Related U.S. Application Data

continuation parent-doc US 16580563 20190924 US 11995683 child-doc US 18665427
continuation parent-doc WO PCT/AU2018/050249 20180319 PENDING child-doc US 16580563

Publication Classification

Int. Cl.: G06Q30/02 (20230101); G06Q30/0251 (20230101)

U.S. Cl.:

CPC G06Q30/0261 (20130101); G06Q30/0267 (20130101); G06Q30/0269 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8781502	12/2013	Middleton et al.	N/A	N/A
8990287	12/2014	Stewart	N/A	N/A
10242384	12/2018	Otis et al.	N/A	N/A
10552868	12/2019	Kim	N/A	N/A
11995683	12/2023	Hardham et al.	N/A	N/A
2004/0034723	12/2003	Giroti	N/A	N/A
2004/0162059	12/2003	Hiltunen et al.	N/A	N/A
2004/0254834	12/2003	Wohlers et al.	N/A	N/A
2005/0234771	12/2004	Register et al.	N/A	N/A
2006/0085049	12/2005	Cory et al.	N/A	N/A
2007/0038614	12/2006	Guha	N/A	N/A
2007/0073799	12/2006	Adjali et al.	N/A	N/A
2008/0215436	12/2007	Roberts	N/A	N/A
2009/0106099	12/2008	Chow et al.	N/A	N/A
2010/0057639	12/2009	Schwarz et al.	N/A	N/A
2011/0026697	12/2010	Vanier et al.	N/A	N/A
2011/0029370	12/2010	Roeding et al.	N/A	N/A
2011/0143779	12/2010	Rowe et al.	N/A	N/A
2011/0202881	12/2010	Singh et al.	N/A	N/A
2011/0295692	12/2010	Zivkovic et al.	N/A	N/A
2012/0022776	12/2011	Razavilar	N/A	N/A
2012/0311328	12/2011	Wang et al.	N/A	N/A
2014/0006141	12/2013	Vassilvitskii et al.	N/A	N/A
2014/0006161	12/2013	Jabara et al.	N/A	N/A
2014/0214547	12/2013	Signorelli et al.	N/A	N/A
2014/0358666	12/2013	Baghaie et al.	N/A	N/A
2015/0019326	12/2014	Russell et al.	N/A	N/A

2015/0063472	12/2014	Chatterton	N/A	N/A
2015/0066742	12/2014	Chatterton et al.	N/A	N/A
2015/0170256	12/2014	Pettyjohn	705/26.9	G06Q 30/0603
2015/0242899	12/2014	Farhi	N/A	N/A
2015/0248702	12/2014	Chatterton	N/A	N/A
2015/0262117	12/2014	Li	N/A	N/A
2015/0362315	12/2014	Abdi et al.	N/A	N/A
2015/0363861	12/2014	Capel	705/26.7	G06Q 30/0631
2016/0019522	12/2015	Granbery et al.	N/A	N/A
2016/0027073	12/2015	Eramian	N/A	N/A
2016/0057184	12/2015	O'Brien	N/A	N/A
2016/0105515	12/2015	Murdock et al.	N/A	N/A
2016/0125467	12/2015	Scott et al.	N/A	N/A
2016/0162938	12/2015	LeBeau et al.	N/A	N/A
2016/0165056	12/2015	Bargetzi et al.	N/A	N/A
2016/0189276	12/2015	Batra	N/A	N/A
2016/0267569	12/2015	Hampson	N/A	G06F 16/248
2016/0300216	12/2015	Godsey	N/A	G06Q 20/4016
2016/0307181	12/2015	Syed	N/A	N/A
2017/0061490	12/2016	Ghahremani et al.	N/A	N/A
2017/0091823	12/2016	Adinarayan et al.	N/A	N/A
2017/0093991	12/2016	Douglas et al.	N/A	N/A
2017/0099575	12/2016	Schulz et al.	N/A	N/A
2017/0164159	12/2016	Mycek et al.	N/A	N/A
2017/0255915	12/2016	Chandrasekaran et al.	N/A	N/A
2017/0300972	12/2016	Moon	N/A	N/A
2018/0063684	12/2017	Cheng et al.	N/A	N/A
2018/0077572	12/2017	Trappitt	N/A	G06Q 30/0271
2020/0387948	12/2019	Kurani	N/A	G06Q 30/0639

OTHER PUBLICATIONS

Stan et al. Intelligent Store—An Innovative Technological Solution for Retail Activities with Mobile Access, The Third International Multi-Conference on Computing in the Global Information Technology, 2008. cited by examiner

Trademark Electronic Search System (TESS), Bluetooth, United States Patent and Trademark Office, Retrieved from the Internet:, retrieved on Feb. 3, 2022, 3 pages. cited by applicant

U.S. Appl. No. 16/580,563 , “Final Office Action”, Oct. 18, 2022, 46 pages. cited by applicant

U.S. Appl. No. 16/580,563 , “Non-Final Office Action”, Jun. 26, 2023, 36 pages. cited by applicant

U.S. Appl. No. 16/580,563 , “Non-Final Office Action”, Feb. 8, 2022, 44 pages. cited by applicant

U.S. Appl. No. 16/580,563 , “Notice of Allowance”, Jan. 25, 2024, 12 pages. cited by applicant

Lopes et al., “ShopAssist—A Unified Location-Aware System for Shopping”, IEEE, Global Information Infrastructure and Networking Symposium (GIIS), 2016, 6 pages. cited by applicant

PCT/AU2018/050249 , “International Search Report and Written Opinion”, Jun. 19, 2018, 16 pages. cited by applicant

Primary Examiner: Stoltenberg; David J

Attorney, Agent or Firm: Kilpatrick Townsend & Stockton LLP

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS (1) This application is a continuation application of U.S. patent application Ser. No. 16/580,563 entitled “SYSTEM AND METHOD FOR PROVIDING INFORMATION,” filed on Sep. 24, 2019, which is a continuation application of International Patent Application No. PCT/AU2018/050249 entitled “SYSTEM AND METHOD FOR PROVIDING INFORMATION,” filed on Mar. 19, 2018, which claims priority to Australian Patent Application No. 2017901317, filed on Mar. 24, 2017, each of which are herein incorporated by reference in their entirety for all purposes.

FIELD OF THE INVENTION

(1) The invention generally relates to presenting location relevant messages to a user, for example, personalised advertisements etc.

BACKGROUND OF THE INVENTION

(2) It is known to provide online targeted advertisements to users, for example when the user searches for a product using a web browser and a search engine. However, such online advertising can be at the expense of so-called “brick and mortar” shops—i.e. where a customer is required to be physically present to peruse products and make purchases.

(3) There is a need to provide engagement and interest between merchants and potential customers. Such engagement can assist in increasing sales and providing an overall better experience to customers.

SUMMARY OF THE INVENTION

(4) According to an aspect of the present invention, there is provided messaging system comprising: a user device configured to: receive, via a local wireless channel, a beacon ID from a local beacon device when within a communication distance of the local beacon device; communicate, via a network, information enabling a merchant database to identify a merchant profile associated with the local beacon device in response to receiving the beacon ID; and receive, via the network, one or more product messages for presentation via a user interface of the user device, the merchant database comprising one or more merchant profiles, each merchant profile comprising data entries associated with one or more products, a user database comprising one or more user profiles, a comparison server configured to: receive from the merchant database a merchant profile associated with a beacon ID obtained by the user device and a user profile associated with the user device from the user database; identify, based on the received merchant profile and user profile, at least one product message for communication to the user device; and communicate the at least one product message to the user device via the network.

(5) Typically, the user device is a smartphone. Preferably, the local wireless channel comprises Bluetooth Low Energy.

(6) The system preferably further comprises one or more local beacon devices. The beacon ID is stored in a memory of the, or each, local beacon device.

(7) Optionally, each merchant profile includes one or more products provided by a merchant associated with the merchant profile. Also optionally, each user profile includes products determined to be of interest to a user associated with the user profile. The at least one product message may be associated with a product present in both the received user profile and the received merchant profile. Optionally, the comparison server is configured to select the at least one product message randomly. Each user profile may include a plurality of hierarchical categories, each associated with at least one item, and the comparison server may be configured to select the at least one product message in accordance with items determined to be of relevance to the user. Preferably, the comparison server is configured to select the at least one product message in accordance with a bidding procedure.

(8) The user device may be configured to present a notification that a product message has been received, and may be configured to present the product message via a user interface.

(9) The system preferably further comprises a user tracker configured to update a user profile of a user in response to online searching activities of the user. The online searching activities may comprise using a smartphone application or web application, and the user may tracker receive information from the relevant application on the user's searching behaviour.

(10) According to another aspect of the present invention, there is provided a method for providing a message to a user, comprising: a user device: receiving, via a local wireless channel, a beacon ID from a local beacon device when within a communication distance of the local beacon device; communicating, via a network, information enabling a merchant database to identify a merchant profile associated with the local beacon device in response to receiving the beacon ID; and receiving, via the network, one or more product messages for presentation via a user interface of the user device.

(11) Optionally, the method further comprises: maintaining the merchant database comprising one or more merchant profiles, each merchant profile comprising data entries associated with one or more products; maintaining a user database comprising one or more user profiles; and a comparison server: receiving from the merchant database a merchant profile associated with a beacon ID obtained by the user device and a user profile associated with the user device from the user database; identifying, based on the received merchant profile and user profile, at least one product message for communication to the user device; and communicating the at least one product message to the user device via the network.

(12) According to another aspect of the present invention, there is provided a virtual marketplace system comprising: a virtual marketplace module configured to: generate a virtual store rendering including one or more product set images, wherein each product set image is associated with one or more products, and generate a virtual product list in response to a user selection of a product set image, wherein the virtual product list comprises information of the, or each, product associated with the selected product set image; a virtual interactive device configured to: display the virtual store rendering to a user of the virtual interactive device, provide selection mechanism by which the user can select a product set image included within the virtual store rendering, and display the virtual product list generated in response to selection of an associated product set image by the user.

(13) In an embodiment, the selection mechanism includes a visual selection mechanism configured to: identify a viewing direction of the user; determine that the user is viewing one of the one or more product set images based on the identified viewing direction; and, in response, to determine that the user has selected said identified product set image. Optionally, the user viewing determiner utilises orientation data obtained from an orientation sensor of the virtual interactive device. A product set image may be required to be viewed for a predetermined dwell time in order to indicate selection. The virtual interactive device may be configured to display an animation indicating a remaining time before a product set image is determined to be selected.

(14) Optionally, each product set image is associated with a category, and the product list associated with a product set image is generated at least in part in accordance with the category associated with the product set image.

(15) Optionally, the messaging system further comprises a user database comprising one or more user profiles, wherein the virtual marketplace module is in communication with the user database and is configured to: identify a user profile within the user database associated with the user of the virtual interactive device; obtain one or more products determined to be of interest to the user from the identified user profile; and generate the product list at least in part in accordance with the obtained one or more products.

(16) Optionally, the messaging system further comprises a merchant database comprising one or more merchant profiles, wherein the virtual marketplace module is in communication with the

merchant database and is configured to: identify a merchant profile within the merchant database associated with the selected product set image; obtain one or more products associated with the merchant profile; and generate the product list at least in part in accordance with the obtained one or more products.

(17) The virtual interactive device may be a smartphone. In this case, the virtual marketplace module may be implemented as a program executed by the smartphone. Alternatively, the virtual marketplace module may be implemented as a program executed by a marketplace server in communication with the smartphone.

(18) Optionally, the virtual marketplace module is further configured to generate a virtual store-selection rendering including a plurality of store images, each store image associated with a virtual store rendering, the virtual interactive device is further configured to display a rendering of the virtual store-selection rendering to a user of the virtual interactive device and provide a selection mechanism by which the user can select a store image included within the virtual market rendering, and in response, generate the virtual store rendering in accordance with the selected store image.

(19) According to yet another aspect of the present invention, there is provided a method for providing a virtual marketplace comprising: generating a virtual store rendering including one or more product set images, wherein each product set image is associated with one or more products, and generating a virtual product list in response to a user selection of a product set image, wherein the virtual product list comprises information of the, or each, product associated with the selected product set image; displaying on a virtual interactive device the virtual store rendering, providing a selection mechanism by which the user can select a product set image included within the virtual store rendering, and displaying the virtual product list generated in response to selection of an associated product set image by the user.

(20) According to still yet another aspect of the present invention, there is provided a system comprising the messaging system and the virtual marketplace system of the previous aspects.

(21) As used herein, the word “comprise” or variations such as “comprises” or “comprising” is used in an inclusive sense, i.e. to specify the presence of the stated features but not to preclude the presence or addition of further features in various embodiments of the invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order that the invention may be more clearly understood, embodiments will now be described, by way of example, with reference to the accompanying drawing, in which:

(2) FIG. 1 shows a messaging system according to an embodiment;

(3) FIG. 2 shows a user device within a communication distance of a local beacon device;

(4) FIG. 3 shows a user database and a merchant database;

(5) FIG. 4 shows a comparison server receiving a user profile and a merchant profile;

(6) FIG. 5 shows a method for selecting a product message;

(7) FIG. 6 shows a hierarchical structure of categories and items;

(8) FIG. 7 shows a system comprising a virtual interactive device;

(9) FIG. 8 shows a virtual store rendering displayed to a user;

(10) FIGS. 9A and 9B show a visual indicator both non-overlapping, and overlapping, a product image set; and

(11) FIG. 10 shows an embodiment including a merchant device.

DESCRIPTION OF EMBODIMENTS

(12) FIG. 1 shows a messaging system 10 according to an embodiment, comprising an identification server 11 in communication with a plurality of user devices 12a-12c. In the present embodiment, the identification server 11 communicates with the user devices 12a-12c via a

network **15**, which typically includes the Internet. Although three user devices **12a-12c** are shown, generally the system **10** can comprise one or more user devices **12**. The system **10** further comprises one or more local beacon devices **13** (two local beacon devices **13a**, **13b** are shown). The local beacon devices **13** are configured to communicate via a local channel **81** with user devices **12** which are present within a communication range. The communication range (for communication via the local channel **81**) is typically less than 50 metres, for example less than 25 metres and preferably approximately 10 metres or less. The local channel **81** is a wireless communication channel, for example employing the Bluetooth Low Energy standard. Also shown is a comparison server **16**, in communication with the network **15**. The comparison server **16** is also interfaced with the identification server **11** (either directly or via network **15**).

(13) The user devices **12**, according to an embodiment, implement programmable computing functionality and are portable (in the sense that, the user device **12** may be carried by a person with case). For example, a user device **12** may be a smartphone or other portable computing device implementing computer software (such as a downloaded application, sometimes referred to as an “app”) enabling the functionality described herein. The user devices **12** include a local wireless module for enabling communication via the local channel **81** with the local beacon devices **13** and a network communication module for enabling communication with the network **15**, for example via one or both of a WiFi connection (e.g. IEEE 802.11) and a mobile data connection (e.g. 3G or 4G, such as LTE).

(14) FIG. 2 shows an illustration of a user device **12** being within communication range via the local channel **81** (the communication range is represented by dotted line **80**) with a local beacon device **13**. The user device **12** receives, via the local channel **81**, a beacon ID of the local beacon device **13**. Generally, each local beacon device **13** is associated with a beacon ID which is configured to allow identification of the local beacon device **13** and is preferably uniquely associated with the local beacon device **13**. The beacon ID may be a unique number recorded into a memory of the local beacon device **13** at manufacture. For example, the beacon ID may be a MAC address.

(15) In response to receiving a beacon ID from a local beacon device **13**, each user device **12** is configured to communicate information to the identification server **11** via the network **15** enabling the identification server **11** to identify the local beacon device **13**. Typically, this information will comprise or is generated from the beacon ID. For the purposes of this disclosure, it is assumed that the beacon ID is communicated to the identification server **11**. It may be preferred that the user devices **12** are configured to communicate the information without requiring an additional user input (i.e. “automatically”), however, an embodiment may require that a user interacts with their user device **12** to authorise the communication.

(16) Referring to FIG. 3, the identification server **11** is configured to maintain a user database **20** comprising database entries corresponding to a user profile **21** for each of one or more users (i.e. each database entry corresponds to a user profile **21**). Each user device **12** is associated with a user, and therefore, a user profile **21**. Generally, there may be more than one user device **12** associated with a user profile **21** (e.g. a user having more than one user device **12**). The identification server **11** is configured to identify a user profile **21** associated with a user device **12** when a beacon ID is communicated to the identification server **11** from the user device, within the user database **20**.

(17) Referring still to FIG. 3, the identification server **11** is also configured to maintain a merchant database **30** comprising database entries corresponding to a merchant profile **31** for each of one or more merchants (i.e. each database entry corresponds to a merchant profile **31**). Each local beacon device **13** is associated with a merchant. The identification server **11** is configured to identify a merchant profile **31** associated with a received beacon ID within the merchant database **30**.

(18) Generally, the functionality of each of the identification server **11** and the comparison server **16** may be implemented in a standalone computing device, a multi-processor computing device, and interlinked plurality of computing devices such as provided by a cloud service provider, or any

other suitable configuration for implementing the functionality herein described. Furthermore, although the identification server **11** is described as maintaining a number of databases, in an alternative embodiment the user database **20** is maintained by a physically and/or logically distinct server to the merchant database **30**.

(19) Referring to FIG. **4**, the comparison server **16** is configured to receive the identified merchant profile **31** and the identified user profile **21** from the merchant database **30** and user database **20**, respectively. The comparison server **16** is further configured to, in response, identify one or more product messages to communicate to the respective user device **12** based on the identified merchant profile **31** and user profile **21**. The comparison server **16** can be implemented within the same hardware as the identification server **11** (but may optionally be logically distinct), or can be implemented in different hardware with a data connection (optionally via network **15**) allowing communication between the two servers **11**, **16**.

(20) A product message is typically associated with a product offered by the merchant associated with the beacon ID (and therefore, the identified merchant profile **31**). In one example, the product message is an advertisement for the product. In another example, the product message is an advertisement for a collection of items which include the product.

(21) The one or more identified product messages are communicated to the user device **12** via the network **13**. The user device **12** is typically configured to provide a notification to the user of the user device **12** in response to receiving the media content. The user may then interact with the user device **12** in a known manner (such as via a touch screen user interface) in order to acknowledge the notification and cause the media content to be displayed on a display of the user device **12**. The product messages generally can comprise one or more of: text, images, sound, etc. In an alternative embodiment, the product messages are displayed without presenting a notification.

(22) In this way, the user device **12** is configured to cause product messages to be presented to the user in response to communication with the local beacon device **13**. The user therefore receives one or more product messages when in proximity with the physical location of the merchant. It is preferred that the product messages are delivered in “real-time”; that is, without a noticeable delay to the user.

(23) The user tracker is configured to identify, based on actions of a user, products that may be of interest to the user. In an embodiment, the user tracker is implemented as a searching application through which the user directly interacts, for example as one or both of a smartphone “app” or as a web application. In both cases, the user is enabled to login to the searching application, such that the user tracker is able to associate activities undertaken by the user through the searching application with the user profile **21** of the user. In another embodiment, the user tracker is interfaced to third party applications (such as web applications and smartphone apps). The third party applications provide for the user to search for products of interest. The user tracker is configured to receive information on such searching of the user from the third party application. In another embodiment, the user may install a separate monitoring application onto a device (such as a personal computer or smartphone), which monitors searching of the user. Generally, any one or more of these embodiments may be employed, and further embodiments in which searching by a user is monitored.

(24) Generally, a user is enabled to search for products of interest to the user, and the user tracker is configured to record products that may be of interest into the user profile **21** associated with the user. The user may be enabled to provide an explicit indication of products of interest, for example, by marking a product as a “favourite”. This action is then identified by the user tracker, which then associates the product with the user profile **21** (i.e. the product is recorded as a “linked product” in the user profile **21** associated with the user). Alternatively, or in addition, the user tracker is configured to infer products that may be of interest to the user through searching actions of the user. For example, if a user undertakes an action to obtain further detail of a product, this action may be recorded into the user profile **21**. In another example, the purchase of a product by a user

may be recorded into the user profile **21**.

(25) According to an implementation, one or more of the following user trackers may be utilised: online via website & app provided by a system operator; in-store interactions which may be recorded through interaction between the user device **12** and the local beacon device **13**, for example, the user device may be configured to communicate with the user tracker information such as time in the vicinity of the local beacon device **13**; online analytics, for example, utilising Google Analytics; and interactions by a user with product messages received at a user device **12**.

(26) Each merchant profile **31** comprises one or more products identifiers. The merchant associated with the merchant profile **31** provides products which may be purchased. Each product identifier is associated with a product available at the merchant. The merchants may each be associated with physical locations; for example, the physical location is a “bricks and mortar” store or the like where a customer is able to be physically present.

(27) In an embodiment, a merchant or an agent of the merchant (herein, both are referred to interchangeably as the “merchant”) is enabled to record into the merchant database products available for purchase at their premises. For example, the merchant may use a computer to access, via the network **15**, the identification server **11** (for example, by accessing a web application via a web browser, or by utilising a smartphone app). The merchant can then record database entries corresponding to one or more of the products available for purchase within the merchant profile **31** associated with the merchant.

(28) In an embodiment, the merchant database **30** is in communication with an image database (not shown). The image database comprises one or more entries corresponding to product profiles. Each product profile comprises information relating to a product, typically including image and/or virtual rendering information for generating a visual representation of the product. The product profile may also comprise information on the product (e.g. manufacturer). In an implementation, when a merchant profile is updated to include a new product, the information on that product is obtained by the merchant database **30** from the product database. In another implementation, when information on a product is required for presentation to a user of a user device **12**, the information is obtained from the product database. The product database may be obtained by a separate product manager, for example a user with authorisation to manage the product database. The information may at least in part be automatically obtained via the network **15** (e.g. via scraping of relevant Internet website(s)).

(29) Referring to FIG. 5, a method is shown whereby a message comprising one or more product messages is communicated to a user device **12** in response to the user device **12** communicating with a local beacon device **13**. The user device **12** is initiated at initiation step **100**. The user may cause the user device **12** to initiate by, for example, instructing the user device **12** to begin running software providing the functionality described herein. The user device **12** may also be initialised simply by having thereon software implementing the functionality described herein (i.e. the user device **12** is initialised whenever powered on).

(30) When within a communication distance of a local beacon device **13**, the user device **12** is configured to determine that communication with the local beacon device **13** is possible via the local channel **81**, and beacon detection step **101**. For example, the local beacon device **13** may periodically (for example, every one second, although any suitable period may be employed) broadcast a broadcast message indicating its presence. When within range, the user device **12** is able to detect the broadcast message, and may then communicate with the local beacon device. In an embodiment, the broadcast message comprises the beacon ID of the local beacon device **13** and the user device **12** is not required to transmit data to the local beacon device **13**. In another embodiment, the user device **12** is required to communicate data corresponding to an enquiry to the local beacon device **13**, to which the local beacon device **13** is configured to respond with its beacon ID. Generally, the beacon detection step **101** results in the user device **12** obtaining the beacon ID of the local beacon device **13**.

(31) The user device **12** then communicates the beacon ID (or at least, information from which the beacon ID can be derived) to the identification server **11**, such that the merchant profile **31** associated with the beacon ID can be identified within the merchant database **30**, at merchant profile identification step **102**. The user device **12** typically also communicates a user identifier enabling identification of the user profile **21** associated with the user device **12** to the identification server **11**, thereby enabling identification of the relevant user profile **21** within the user database **20**, at user profile identification step **103**.

(32) The comparison server **16** obtains the identified merchant profile **31** and the identified user profile **21**, and undertakes a comparison in order to identify one or more product messages to communicate to the user device **12** associated with the merchant profile **31** and user profile **21**, at comparison step **104**.

(33) In an embodiment, the comparison server **16** attempts to identify one or more products that have been associated with the identified user profile **21** which are also present in the identified merchant profile **31**. If it is successful, then the method proceeds to product message selection step **105** (described below). If it is unsuccessful, then according to this embodiment no product message is selected and the method proceeds to end step **110**.

(34) In another embodiment, the comparison server **16** utilises user categories associated with the user profile **21** and/or product categories associated with merchant profile **31** in order to identify one or more product messages for selection at product message selection step **105**.

(35) Referring to FIG. **6**, a user profile **21** can be associated with a plurality of user categories **40**, **41**, **42**, each category associated with one or more items. Each user category **40**, **41**, **42** provides information on the user associated with the user profile **21**. The user categories **40**, **41**, **42** are arranged in a hierarchical manner, the example shown including a first user category **40**, being a “top-level” or “major” category, optionally one or more second user categories **41**, being “sub” categories related to the major category, and a product user category **42**. In the example shown, there are two second categories **41a**, **41b**, with second category **41a** located under the first category **40** and second category **41b** located under second category **41a**. Generally, there can be as many second categories as required. The product category **42** is effectively located under the lowest of the second categories **42** (in the example, second category **41b**).

(36) The purpose of the user categories **40**, **41**, **42** is to enable a product message (or product messages) to be identified that are likely to be of interest to the user. For a user profile **21**, the user categories **40**, **41**, **42** are populated in accordance with the user behaviour as recorded by the user tracker.

(37) In the example shown, the first user category **40** comprises three items, namely “home”, “sport”, and “food”. In the example, the second user category **41a** associated with the home item is shown. As can be seen, there are several items in this category **41a**, including “bedroom”, “kitchen”, and “living”. In the example, the second user category **41b** associated with the bedroom item is shown. Here, as can be seen, are several items, including “bedding”, “storage”, and “lighting”. Finally, under the item bedding in second category **41b** is shown a number of products within the associated product category **42**.

(38) For each category **40**, **41**, **42** there are a collection of associated items, with each item having a sub-category associated with it (except in the case of product category **42**). Based on the information obtained by the user tracker, information is recorded in the user profile **21** of a user indicating which items within each user category **40**, **41**, **42** may be of interest to the user. For example, if the user has searched online for “pillow”, and this has been identified by the user tracker, then the item “home” in the first user category **40** is updated to include an indication that the user has an interest in “home” products. Further, the item “bedroom” in the second category **41a** is also updated to include an indication that the user has an interest in “bedroom” products. Additionally, the item “bedding” in the second category **41b** is also updated to include an indication that the user has an interest in “bedding” products. Finally, the actual item of “pillow” is updated in

the corresponding product category **42**.

(39) The example shown is illustrative. Generally, the user categories **40, 41, 42** can be configured as desired, for example, by an operator of the identification server **11** and comparison server **16**. Furthermore, the items present in each user category **40, 41, 42** can be configured as desired. An operator may be enabled to utilise a computing device (for example, one in communication with the Internet) to configured to user categories **40, 41, 42** and the items present in each user category **40, 41, 42**. The number of user categories **40, 41, 42** may be configured by the operator.

(40) A product message according to an embodiment is selected in dependence of an identified user profile **21** and an identified merchant profile **31**. Each product associated with the identified merchant profile **31** is compared to the user profile **21**, in order to identify items associated with the user profile **21** associated with the product. For example, if the product is a “pillow”, then considering the example of FIG. 7, item “home” from the first user category **40**, item “bedroom” from second user category **41a**, item “bedding” from second user category **41b**, and item “pillow” from product user category **42** are identified. In another example, if the product were a “valance” (which it is assumed has not directly been associated with an item in the product user category **42** of the user profile **21**), then only items “home” from the first user category **40**, “bedroom” from second user category **41a**, “bedding” from second user category **41b** are identified.

(41) In order for the comparison to be effective, each product should be identifiable with a user category **40, 41, 42**. This can be achieved, for example, by the operation of an operator responsible for managing information on products (which may be the merchant when configured their associated merchant profile **31** or another entity). In an embodiment, the operator is enabled to add products to a merchant profile **31**, and when doing so, associate each product with various user categories **40, 41, 42** and items. The operator may be enabled to define new items and/or user categories **40, 41, 42**.

(42) A product message is then selected. Generally, there can exist one, or one or more, product messages associated with each product of the merchant profile **31**. Each product message is effectively scored based on the matching items from the user profile **21**. Generally, a “higher” score will be assigned to product messages associated with a product that matches an item in a “lower” category **40, 41, 42**. In the previously described examples, product messages associated with “pillows” would score higher (as “pillow” is an item in the lowest category, namely product user category **42**) than product messages associated with “valances” (as the lowest category matching “valance” is second user category **41b**). In an embodiment, each product can be associated with multiple items in a category **40, 41, 42**. For example, “pillow” may also be associated with the “living” item in second user category **41a**. The score associated with each product message may also depend on the number of matching items in each category **40, 41, 42**. The term “higher” in respect of a score is not intended to be limiting—scoring can be undertaken as desired.

(43) In an embodiment, a product message is selected based on having a highest score. In the event of two or more product messages associated with the same highest score, a tie-breaker may be employed such as a random selection from the highest scoring product messages.

(44) In another embodiment, a product message is selected in a semi-random manner, wherein the likelihood of a product message being selected is proportional to its score. That is, a product message associated with a product matching an item in a lower category **40, 41, 42** of the user profile is more likely to be selected than a product message associated with a product not matching an item in the same category **40, 41, 42**.

(45) In an embodiment, a product message is selected utilising a bidding technique. Here, each product message is associated with a provider (who may be the merchant or another entity), and the provider selects bidding parameters which act to potentially modify the probability of a particular product message being selected. In effect, a bidding technique is undertaken, with the highest bidder obtaining an increased chance of the associated product message being selected. The provider may be enabled to place a budget to limit the amount of successful highest bids that they

can make. In effect, the probability of a product message being selected is proportional to the bid value selected by the provider.

(46) In an embodiment, the product message is selected both in accordance with its score and in accordance with a bidding technique. In this embodiment, the probability of a product message being selected increases with a higher score (e.g. the product message is associated with a product of higher interest to the user) and with a higher bid value being selected by the provider.

(47) In an embodiment, additional user information is utilised when selecting a product message. The additional user information may be in the form of user data associated with the user's user profile **21**. Depending on the implementation, each product is either mandatorily or optionally associated with such additional user information. The additional user information is typically provided by the user (although additional information may be inferred). For example, additional user information can include one or more of: user's age; user's gender; user's occupation; user's income; etc. Each product or product message is associated can optionally (or mandatorily) comprise information indicating compatible additional user information. The product message can then be selected, generally in part, based on the product or product message matching the additional user information of the user.

(48) The selected product message is communicated to the user device **12** which originally communicated the beacon ID to the identification server **11**, at communicate product message step **106**. The user device **12** is then typically configured to display a notification to the user of the user device **12**, who is then enabled to view the product message (for example, by making a selection to “open” the product message).

(49) The method then proceeds to end step **110**.

(50) Generally, the above embodiments may be modified to allow for one or more product messages to be selected and communicated to the user device **12**.

(51) Referring to FIG. **10**, in an embodiment, a representative of a merchant (“salesperson”) is provided with a merchant device **19** (and therefore, the merchant device **19** is associated with a particular merchant and in turn, with a particular beacon ID). A merchant device **19**, according to an embodiment, implements programmable computing functionality and is portable (in the sense that, the merchant device **19** may be carried by a person, such as the salesperson, with ease). For example, a merchant device **19** may be a smartphone or other portable computing device implementing software (such as a downloaded “app”) enabling the functionality described herein. The merchant device **19** includes a network communication module for communication with the network **15**, for example via one or both of a WiFi connection (e.g. IEEE 802.11) and a mobile data connection (e.g. 3G or 4G, such as LTE).

(52) The identification server **11** is configured to communicate to the merchant device **19** associated with a received beacon ID. In this way, the merchant device **19** receives information indicating that a user is present at the merchant, the salesperson can then retrieve information on the user using the merchant device **19**, via communication between the merchant device **19** and the user database **20**. The merchant device **19** is configured to obtain information of products present at the merchant which may be of interest to the user. This typically involves interaction between the merchant device **19**, user database **20**, and merchant database **30**. Typically, the merchant profile **31** of the merchant is compared with the user profile **21** of the user, and one or more relevant products identified and presented to the salesperson on the merchant device **19**. In this way, the salesperson is provided with information enabling them to better serve the user, who may be a customer interested in purchasing one or more products located at the merchant's premises.

(53) In an embodiment, as shown in FIG. **7**, a virtual interactive device **18** is provided. The virtual interactive device **18** implements programmable computing functionality and is typically portable. For example, the virtual interactive device **18** can comprise a smartphone implementing software (such as a downloaded “app”) enabling the functionality described herein. The virtual interactive device **18** typically includes a network communication module for communication with the

network **15** (not shown in FIG. 7), for example via one or both of a WiFi connection (e.g. IEEE 802.11) and a mobile data connection (e.g. 3G or 4G, such as LTE). The virtual interactive device **18** may be implemented within the same hardware as a user device **12** (for example, a smartphone having software for implementing the functionality of a user device **12** and software for implementing the functionality of a virtual interactive device **18**).

(54) A virtual marketplace module **50** is interfaced with the virtual interactive device **18**. In an implementation, the virtual marketplace module **50** is implemented as a feature of the virtual interactive device **18** (e.g. as a software module of the virtual interactive device **18**). In another implementation, the virtual marketplace module **50** is implemented within separate computing hardware to the virtual interactive device **18**, and is in data communication (for example, via the network **15**).

(55) The virtual marketplace module **50** is configured to receive data from the user database **20** and the merchant database **30**, and may be in network communication with each. In an implementation, a product database is provided comprising entries corresponding to the entries of either or both of the user database **20** and the merchant database **30**, and the virtual marketplace module **50** is in data communication (for example, network communication) with the product database (and thereby, receive data originating from, or equivalent to, the entries of either or both of the user database **20** and the merchant database **30**).

(56) The virtual interactive device **18** is configured to provide an interactive user experience to a user via a display, and is typically utilisable away from the physical merchant locations—for example, at the user's home or workplace. The virtual interactive device **18** can communicate with the user database **20** and merchant database **30** via network **15**. A physical mounting device (such as a headset) may be provided for enabling viewing of virtual images presented on the display—for example, the physical mounting device may be “Google Cardboard”. The physical mounting device is typically configured to ensure separate images are presented to each eye of the user, thereby creating a 3-dimensional “virtual image”.

(57) With reference to FIG. 8, the virtual marketplace module **50** is configured to generate a virtual store rendering **51** for presentation on a display of the virtual interactive device **18**. The virtual store rendering **51** corresponds to a virtual image, and provides an apparent 3-dimensional viewing effect. Additionally, the virtual image is configured to change due to motion of the user, typically motion of the user's head when the virtual interactive device **18** is worn on said head. The virtual store rendering **51** can provide a visual impression of a store, however, other impressions may be provided. The virtual store rendering **51** may be a 360 degree rendering.

(58) The virtual store rendering **51** includes rendering of one or more product set images **52** (in FIG. 8, three product set images **52a**, **52b**, **52c** are shown). Each product set image **52** takes up a “position” within the virtual store rendering **51**, and is configured to be identifiable by a user. Each product set image **52** can be associated with a product type (e.g. a category)—the product set image **52** may be selected to be representative of the associated product type. Each product set image **52** is associated with a product set comprising one or more products.

(59) In an embodiment, the product(s) for the product set are selected from products stored within a product database. The product database can be interfaced with the merchant database **30** such that each product present within the merchant database **30** is represented as a database entry in the product database **52**. For example, the product database is maintained such that it is updated when products are added to, removed from, or modified within the merchant database **30**. In this way, the products are indirectly obtained from the merchant database **30**. In an alternative embodiment, the virtual marketplace module **50** obtains information for the product(s) directly from the merchant database **30**. The virtual interactive device **18** comprises a selection mechanism configured to enable the user of the virtual interactive device **18** to select a feature, such as a product set image **52**, displayed within a virtual rendering.

(60) Referring to FIGS. 9A and 9B, in an embodiment, the virtual interactive device **18** comprises a

visual selection mechanism. A visual indicator **55** is presented on the display of the virtual interactive device **18** (for example, as a “cross-hair” or “dot”). In an implementation, the visual indicator **55** is perceived as “fixed” in place, such that it does not appear to move relative to the user (as opposed to the virtual store rendering **51**, which will change in appearance as the virtual interactive device **18** is moved). The visual indicator **55** may be presented in the middle of the virtual store rendering **51**. In a variation, a visual indicator **55** is not displayed, however, a fixed point (relative to the user) is still associated with the user's viewing direction, and may be the centre of the virtual store rendering **51**.

(61) A feature (such as a product set image **52**) is selected when the user manoeuvres the virtual interactive device **18** such that the visual indicator **55** overlaps the feature (as shown in FIG. **9B**—here, the visual indicator **55** is shown overlapping product set image **52a**). Optionally, a dwell time is implemented, such that the visual indicator **55** is required to overlap the feature for a predefined time period (for example, approximately one second) in order for the feature to be selected. An animation may be provided to indicate the amount of time remaining before selection is effected. In FIG. **9A**, the visual indicator **55** is shown not overlapping any one of the product image sets **52**. In FIG. **9B**, the user has moved the visual interactive device **18** such as to cause the second product image set **52b** to be overlapped by the visual indicator **55**.

(62) In an embodiment, the selection mechanism comprises voice-activated functionality. The user is able to speak commands that are detected by a microphone of the virtual interactive device **18**, and a corresponding action taken. For example, a viewing direction (as described above) may be determined to be overlapping a feature, and the user is able to select the feature by speaking a command.

(63) In an embodiment, the selection mechanism comprises a physical interface provided on a body of the virtual interactive device **18**, for example comprising one or more buttons and/or a track pad. One or more peripherals may also be provided, such as a keyboard and/or mouse, enabling the user to cause interact with the virtual interactive device **18**. For example, a viewing direction (as described above) may be determined to be overlapping a feature, and the user is able to select the feature by pressing a button.

(64) In response to a determination that a product set image **52** has been selected, the virtual marketplace module **50** is configured to present, via the virtual interactive device **18**, information on product(s) associated with the product set image **52**. In an embodiment, as shown in FIG. **9A**, a product list **53** is presented as an overlay within the virtual store rendering **51**. The product list **53** can comprise all the products associated with the selected product set image **52**, or a selection of said products. The user can then obtain more detailed information on a product by selecting the product from the product list **53** (e.g. by using the selection mechanism described herein). Alternatively, or in addition, the user can be presented with additional options related to the product (such as an option to purchase the product). The information may be presented as a “floating” window containing said information, where the floating window appears to float within the virtual store rendering **51**.

(65) In an embodiment, the virtual marketplace module **50** is configured to generate a virtual store-selection rendering. One or more (typically a plurality) of store images are presented within the virtual store-selection rendering, and the user is enabled to select one (e.g. using a selection mechanism described herein). In response, the virtual marketplace module **50** is configured to generate a virtual store rendering **51** associated with the selected store image. In this way, the virtual marketplace module **50** can be configured to provide a user with means for selecting a particular desired virtual store rendering **51** (which may be associated with particular products of interest).

(66) In an embodiment, the virtual interactive device **18** is interfaced with the user tracker. For example, the virtual marketplace module **50** can be configured to implement functionality of the user tracker, or to provide information to a separate user tracker. The user tracker can be configured

to receive information such as: products which the user has viewed in the virtual marketplace (e.g. the user may manoeuvre their head in order to view a particular representation of a product and obtain information about that product); products that have been searched for by the user; etc.

(67) In an embodiment, a product list is generated at least in part in accordance with information stored in the user profile **21** of the user. For example, the user profile **21** can comprise information on previous searching activity of the user. This information is utilised in order to determine which product(s) to include within a product list and/or the ordering of product(s) to include in a product list. For example, a product determined to be of higher interest to a user based on information within the user profile **21** may be placed higher on the product list (higher may be interpreted as located at a more prominent position) than other product(s).

(68) Also in an embodiment, each virtual store rendering **51** is associated with a merchant profile **31**. Therefore, a product list can be generated, at least in part, in accordance with products identified as being available at the merchant associated with the same merchant profile **31**. Each product set image **52** can be associated with a particular category stored within the merchant profile **31** associated with the virtual store rendering **51**. For example, categories may include “shirts”, “trousers”, “other clothing”. In another example, categories include “clothing”; “whiteware”, “electronics”. The product(s) included within a product list associated with a product set image **52** are selected from products labelled as being associated with the category.

(69) In an embodiment, user device **12** is configured to receive a link from another device (for example, another user device **12**). The link is selectable by a user of the user device **12**. Upon selection of a link, the user device **12** identifies a virtual store rendering **51** to present to the user based on the content of the link.

(70) In an embodiment, two user devices **12** (or more) are in communication with one another—this may include text or voice communication—while the associated users are presented with virtual store renderings **51** and/or virtual store-selection rendering. The users are thereby enabled to communicate with one another, and may use the opportunity to discuss products (in particular, those being rendered). In an implementation, a first user may cause a second user to become aware of a particular product, for example, by undertaking a highlight action whereby the user device **12** of the first user is utilised to identify a product for highlighting to the second user (for example, the first user **12** may utilise a voice command or other input). The user device **12** of the first user communicates to the user device **12** of the second user information indicating that the user device **12** of the second user is to present the highlighted product. This presentation may require authorisation by the second user. The presentation may include additional graphical components to indicate that the product has been highlighted by the first user.

(71) Further modifications can be made without departing from the scope of the invention.

Claims

1. A messaging system comprising: a server arrangement including a comparison server and an identification server which are in use in communication with each other; the identification server being configured to: maintain a merchant database, the merchant database comprising two or more merchant profiles, each merchant profile comprising data entries associated with one or more products, the merchant database being adapted to be queried to identify a merchant profile of a corresponding merchant, in response to receiving a beacon ID assigned to a beacon device which is associated with the corresponding merchant; and maintain a user database, the user database comprising database entries of user profiles associated with one or more user devices of registered users; the comparison server being configured to: receive from the merchant database an identified merchant profile associated with a received beacon ID and a user profile associated with a user device from which the beacon ID is received, via a communication network; identify, based on the received merchant profile and user profile, at least one product message for communication to the

user device; and communicate the at least one product message to the user device via the communication network; the server arrangement being configured to support instances of a user interface on the user devices, the user interface being configured to operate a local communication arrangement on the user device on which the user interface is running, to detect a local beacon device within range of the local communication arrangement, obtain a beacon ID associated with the detected local beacon device; communicate the local beacon device to the identification server; acknowledge a communication from the server arrangement of at least one product message; and in response to acknowledging the communication, display content associated with the communicated at least one product message.

2. The messaging system as claimed in claim 1, further comprising entries of merchant devices, each merchant device being associated with a merchant profile.

3. The messaging system as claimed in claim 2, wherein the identification server is further configured to: in response to identifying the merchant profile associated with the local beacon device upon receipt of the beacon ID from the user device, determine and communicate user information derived from the user profile associated with said user device to at least one merchant device associated with the identified merchant profile, wherein said user information is suitable for enabling a representative of the corresponding merchant to identify a user associated with said user device; and each merchant device is configured to: in response to receiving the user information from the identification server, present said user information on a merchant device user interface to thereby enable the representative of the corresponding merchant to identify the user associated with the received user information, such that the user information presented on the merchant device is associated with the user of the user device currently located in proximity to the local beacon device and therefore in proximity to a physical location of the corresponding merchant.

4. The messaging system as claimed in claim 1, wherein the user device is a smartphone.

5. The messaging system as claimed in claim 1, wherein the local communication arrangement comprises a wireless channel comprises Bluetooth Low Energy.

6. The messaging system as claimed in claim 1, further comprising one or more local beacon devices.

7. The messaging system as claimed in claim 6, wherein the beacon ID is stored in a memory of the, or each, local beacon device.

8. The messaging system as claimed in claim 1, wherein each merchant profile includes one or more products provided by the corresponding merchant associated with the merchant profile.

9. The messaging system as claimed in claim 1, wherein each user profile includes products determined to be of interest to a user associated with the user profile.

10. The messaging system as claimed in claim 8, wherein each merchant profile includes the one or more products provided by the corresponding merchant associated with the merchant profile, each user profile includes products determined to be of interest to a user associated with the user profile, and the at least one product message is associated with a product present in both the received user profile and the received merchant profile.

11. The messaging system as claimed in claim 8, wherein the comparison server is configured to select the at least one product message randomly.

12. The messaging system as claimed in claim 8, wherein each user profile includes a plurality of hierarchical categories, each associated with at least one item, and wherein the comparison server is configured to select the at least one product message in accordance with items determined to be of relevance to a user.

13. The messaging system as claimed in claim 8, wherein the comparison server is configured to select the at least one product message in accordance with a bidding procedure.

14. The messaging system as claimed claim 1, wherein the user interface is configured to, in response to acknowledging the communication from the server arrangement of the at least one product message, present a notification that a product message has been received.

15. The messaging system as claimed in claim 1, further comprising a user tracker configured to update the user profile of a user in response to online searching activities of the user.

16. The messaging system as claimed in claim 1, further comprising: a virtual marketplace module configured to: generate a virtual store rendering including one or more product set images, wherein each product set image is associated with one or more products, and generate a virtual product list in response to a user selection of a product set image, wherein the virtual product list comprises information of the, or each, product associated with a selected product set image; a virtual interactive device configured to: display the virtual store rendering to a user of the virtual interactive device; provide selection mechanism by which the user can select a product set image included within the virtual store rendering; and display the virtual product list generated in response to selection of the product set image by the user.
