

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412463
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Sellathamby; Chris et al.

Systems and methods for early warning of seismic events

Abstract

A seismic warning system comprises: a plurality of sensors, each sensor sensitive to a physical phenomenon associated with seismic events and operative to output an electronic signal representative of the sensed physical phenomenon; a data acquisition unit communicatively coupled to receive the electronic signal from each of the plurality of sensors, the data acquisition unit comprising a processor configured to estimate characteristics of a seismic event based on the electronic signal associated with a P-wave from each of the plurality of sensors; and a local device communicatively coupled to the data acquisition unit.

Inventors: Sellathamby; Chris (Victoria, CA), Weir-Jones; Iain (Vancouver, CA), Zaicenco; Anton (North Vancouver, CA), Weir-Jones; Toby Evan George (Warrenton, VA), Weir-Jones; Andrew James (Vancouver, CA)

Applicant: Weir-Jones Engineering Consultants Ltd. (Vancouver, CA)

Family ID: 62018072

Assignee: Weir-Jones Engineering Consultants Ltd. (Vancouver, CA)

Appl. No.: 17/736596

Filed: May 04, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220335804 A1	Oct. 20, 2022

Related U.S. Application Data

continuation parent-doc US 16929928 20200715 US 11354998 child-doc US 17736596
continuation parent-doc US 16388787 20190418 US 10755548 20200825 child-doc US 16929928

Publication Classification

Int. Cl.: **G08B21/10** (20060101); **G01V1/28** (20060101); **G08B27/00** (20060101)

U.S. Cl.:

CPC **G08B21/10** (20130101); **G01V1/288** (20130101); **G08B27/005** (20130101);
G01V2210/41 (20130101)

Field of Classification Search

CPC: **G08B** (21/10); **G08B** (27/005); **G08B** (29/188); **G01V** (1/288); **G01V** (2210/41); **G01V** (1/01); **G01V** (2210/1232); **G01V** (2210/65); **G01V** (2210/72)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5381136	12/1994	Powers et al.	N/A	N/A
5910763	12/1998	Flanagan	N/A	N/A
6356204	12/2001	Guindi et al.	N/A	N/A
7005993	12/2005	Webb et al.	N/A	N/A
8452540	12/2012	Sugawara et al.	N/A	N/A
8720470	12/2013	Hosseini et al.	N/A	N/A
8787871	12/2013	Givens et al.	N/A	N/A
9372272	12/2015	Price et al.	N/A	N/A
10755548	12/2019	Sellathamby et al.	N/A	N/A
11354998	12/2021	Sellathamby	N/A	G01V 1/288
2001/0023614	12/2000	Tubel	73/152.39	G01V 1/40
2003/0002942	12/2002	Gass	408/241R	B23Q 5/58
2004/0034476	12/2003	Lee	702/15	G01V 1/01
2004/0135698	12/2003	Webb	324/323	G01V 1/01
2006/0062084	12/2005	Drew	367/68	G01V 1/01
2007/0279239	12/2006	Lachenit	340/522	G01V 1/01
2008/0018472	12/2007	Dasilva	340/572.4	G08B 25/016
2011/0037588	12/2010	Zeng	340/669	G01V 1/01
2011/0255371	12/2010	Jing	367/73	G01V 1/288
2013/0328622	12/2012	Chiu	N/A	N/A
2013/0328688	12/2012	Price et al.	N/A	N/A
2014/0087780	12/2013	Abhyanker	455/521	G06Q 30/02
2014/0187142	12/2013	Liu et al.	N/A	N/A
2014/0266762	12/2013	Warren et al.	N/A	N/A
2015/0195693	12/2014	Hooriani et al.	N/A	N/A
2016/0054460	12/2015	Jackson et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

OTHER PUBLICATIONS

- Allen, R.M. (1978). Automatic earthquake recognition and timing from single traces. Bull. Seism. Soc. Am. 68:5, 1521-1532. cited by applicant
- Atwater, T. (1970). Implications of plate tectonics for the Cenozoic tectonic evolution of western North America, Geological Society of America Bulletin. 81, 3513-3536. cited by applicant
- Balfour, N. (2011). Sources of Seismic Hazard in British Columbia: What Controls Earthquakes in the Crust? PhD dissertation, the School of Earth and Ocean Sciences, University of Victoria. cited by applicant
- Cassidy, J., Rogers, G. (1999). Seismic site response in the greater Vancouver, British Columbia, area: spectral ratios from moderate earthquakes, Can Jeotech. J., 36: 195-209. cited by applicant
- Cassidy, J., Rogers, G. and Waldhauser, F. (2000). Characterization of active faulting beneath the Strait of Georgia, British Columbia, Bulletin of the Seismological Society of America, 90(5): 1188-1199. cited by applicant
- Cramer, H. and Leadbetter, M.R. (1967). Stationary and related stochastic processes, Wiley, New York. cited by applicant
- Goldfinger, C., Grijalva, K., Burgmann, R., Morey, A. E., Johnson, J. E., Nelson, C. H., Gutierrez-Pastor, J., Ericsson, A., Karabanov, E., Chaytor, J. D., Patton, J. and Gracia, E. (2008). Late Holocene Rupture of the Northern San Andreas Fault and Possible Stress Linkage to the Cascadia Subduction Zone, Bulletin of the Seismological Society of America, 98(2): 861-889. cited by applicant
- Hyndman, R., Yorath, C., Clowes, R. and Davis, E. E. (1990). The northern Cascadia subduction zone at Vancouver Island: seismic structure and tectonic history, Canadian Journal of Earth Science. 27, 313-329. cited by applicant
- Jun Saita, Tsutomu Sato, Yutaka Nakamura. (2008). What is the Useful Application of the Earthquake Early Warning System?, 14th WCEE, Beijing, China, Oct. 12-17. cited by applicant
- Kanamori, H., (2005). Real time seismology and earthquake damage mitigation, Ann. Rev. Earth Planet Sci., 33(1), 195-214. cited by applicant
- Weir-Jones, I., Shaking Things Up. Canadian Mining Journal Editor, Feb. 1, 2012. cited by applicant
- Riddihough, R. (1984). Recent movements of the Juan de Fuca plate system, Journal of Geophysical Research, 89 (B8): 6980-6994. cited by applicant
- Rogers, G.C. (1998). Earthquakes and earthquake hazard in the Vancouver area. Clague JJ, Lutemauer JL, Mosher DC, Editors. Geology and natural hazards of the Fraser River delta, British Columbia. GSC Bulletin, 525: 17-25. cited by applicant
- Seed, H.B., Lysmer, J., and Schnabel, P.B. (1992). SHAKE-91: Equivalent Linear Seismic Response Analysis of Horizontally Layered Soil Deposits, Department of Civil Engineering, University of California, Berkeley. cited by applicant
- Wu, Y.M., and Kanamori, H. (2008). Development of an Earthquake Early Warning System Using Real-Time Strong Motion Signals. Sensors, 8:1-9. cited by applicant
- Zaicenco A., Alkaz V. (2008). Numerical solution of an elastic wave equation using the spectral method, In: Harmonization of Seismic Hazard in Vrancea Zone, Editors: Zaicenco A., Craifaleanu I., Paskaleva I., Springer, NATO Science for Peace and Security Series C: Environmental Security, pp. 319-327. cited by applicant
- Zaicenco, A., Huffman, S., Weir-Jones, I. (2010). Seismic P-wave polarization in the context of on-site early warning system. 5th Intl. Conf on Recent Advances in Geotech. Eq. Eng. And Soil Dyn., San Diego, CA, paper #3.12a. cited by applicant
- Zaicenco, A., Weir-Jones, I. (2011). Elastic wave polarization using EMD vs. Fourier and wavelet

basis. SEG Expanded abstracts, San Antonio, Sep. 18-23, 30:4388-4392. cited by applicant
Zollo, A., Amoroso, O., Lancieri, M., Wu, Y.-M. and Kanamori, H. (2010). A threshold-based earthquake early warning using dense accelerometer networks, Geophys. J. Int., 183: 963-974. cited by applicant

Zaicenco, A., Weir-Jones, I., (2012). Lessons Learned from Operating an On-site Earthquake Early Warning System. 15 WCEE LISBOA 2012. cited by applicant

Onur, T., Ventura, C., Tao, S. (2001). Strong Motion Records from the Feb. 28, 2001 Nisqually Earthquake Recorded by Three Structural Arrays in BC, Report EQ 01-02, UBC Earthquake Engineering Research Lab. cited by applicant

Primary Examiner: Sherwin; Ryan W

Attorney, Agent or Firm: Oyen Wiggs Green & Mutala LLP

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 16/929,928 filed 15 Jul. 2020, which is in turn a continuation of U.S. application Ser. No. 16/388,787 filed 18 Apr. 2019, which is itself a continuation of Patent Cooperation Treaty (PCT) application No. PCT/CA2017/051251 having an international filing date of 19 Oct. 2017, which in turn claims the benefit of the priority of U.S. application No. 62/410,358 filed 19 Oct. 2017 and which, for the purposes of the United States, claims the benefit under 35 USC 119 in relation to U.S. application No. 62/410,358 filed 19 Oct. 2017. All of the applications referenced in this paragraph are hereby incorporated herein by reference.

TECHNICAL FIELD

(1) Systems and methods provide early detection of seismic events (e.g. earthquakes), determine characteristics of detected seismic events, take actions to minimize damage in view of detected seismic events, take actions to minimize injury in view of detected seismic events and/or provide situational alarms and/or recommendations to user(s) in view of detected seismic events.

BACKGROUND

(2) Sensors may be used to detect earthquakes. Some such sensors may also be used in earthquake early warning systems (EEWS) to determine (or estimate) characteristics of earthquakes, such as the epicenter or hypocenter of the earthquake, the magnitude of the surface wave associated with the earthquake and the time of arrival of the surface wave associated with the earthquake. The sensors of prior art earthquake detection systems are generally placed several tens of kilometers or several hundreds of kilometers apart, with the earthquake detection systems comprising data acquisition equipment at each spaced-apart sensor location. This large separation between sensors is typically required in most prior art systems, since most prior art systems have a timing accuracy on the order of seconds or hundreds of milliseconds. The placement of such sensors in close proximity is not possible, where it is desired to know the epicenter of the seismic event, since the epicenter would not be detectable.

(3) Data acquisition equipment (typically located at the same location as the sensors) may be used to log detected data. U.S. Pat. No. 5,381,136 (Powers et al.) describes a remote logger unit for monitoring a variety of operating parameters along a fluid distribution or transmission system. An RF link is activated by which a logger unit alerts a central controller when predetermined operating limits are exceeded. Relatively more distal logger units transmit data to a central controller via relatively more proximate logger units in daisy chain fashion.

(4) U.S. Pat. No. 8,452,540 (Sugawara et al.) describes an earthquake damage spread reducing

method and an earthquake damage spread reducing system, for use in a semiconductor manufacturing apparatus, which can predict occurrence of an earthquake and prevent fall down of a boat, thus minimizing damage by the earthquake. An earthquake damage spread reducing system includes a receiving unit for receiving urgent earthquake information, based on preliminary tremors, distributed via a communication network, or alternatively, includes a preliminary tremors detection unit for directly detecting the preliminary tremors. A control unit performs a first step of stopping operation of a semiconductor manufacturing apparatus, based on the urgent earthquake information received or on the preliminary tremors detected, as well as performs a second step of holding a boat to prevent fall of the boat, in which objects to be processed are loaded in a multistage fashion.

(5) US Patent Application No. 2014/0187142 (Liu et al.) describes a seismic alarm system designed to alarm users of an upcoming seismic event and other natural disasters, and aid victims' survival after an earthquake. The seismic alarm system includes an accelerometer, a controller, an acoustic-to-electric transducer for acoustic pattern detection, and RF module to receive emergency radio signals. The alarm system has central controlling unit that sets off an alarm after processing signals from several modules and components. The accelerometer detects seismic P wave acceleration changes for early earthquake detection. The acoustic-to-electric transducer detects human acoustics or predetermined acoustic patterns, then initiates an alarm that brings rescue attention to survivors. The RF module is tuned to receive emergency radio signals.

(6) U.S. Pat. No. 5,910,763 (Flanagan et al.) describes a system that provides an area warning to a specific general population of an earthquake prior to the arrival of the hazardous ground motion typically associated with earthquakes, and of approaching natural disasters that could impact an area. This area advanced warning thereby provides time for users to seek shelter and through automated means to reduce property damage as well as injuries and lives lost. A preferred embodiment utilizes a plurality of "Local Station Detector Sites", equipped with earthquake seismic motion detectors and microprocessors designed to provide a profile of existing ground motion to a "Central Processing Site" in conjunction with further analysis of similar signals from multiple sites. A warning instruction is then transmitted back to all appropriate Local Station Detector Sites to initiate transmission of local area warnings to a general population of all users in an appropriate and specific geographic area with minimal possibility of false alarms. Additionally all Local Station Detector Sites are equipped to receive notification transmissions from the Central Processing Site, which have been initiated by "Public Safety Offices" for other natural disasters, and transmit appropriate warning signals to the general population of users in specific geographic areas.

(7) US Patent Application No. US2015/0195693 (Hoorianin et al.) describes a mobile phone and tablet-based earthquake early warning system that utilizes the on board accelerometer, gyroscope, GPS and other location and movement sensing technologies built into today's mobile smart phones and tablet devices to detect an earthquake event and send an alarm to those in nearby locations that could be adversely affected by the event.

(8) Existing EEWS systems use various data acquisition techniques to obtain seismic activity measurements. Seismic activity measurements reveal risks of potential damage from earthquakes and provide early warning of the arrival of the S-wave (secondary wave) associated with an earthquake, making such measurements useful for preventing and/or minimizing human injury/death and damage to property. When an earthquake occurs, casualties and damage are typically positively correlated with preparedness and amount of warning time.

(9) The US Geological Survey states that early warning of earthquakes "can give enough time to slow and stop trains and taxiing planes, to prevent cars from entering bridges and tunnels, to move away from dangerous machines or chemicals in work environments and to take cover under a desk, or to automatically shut down and isolate industrial systems. Taking such actions before shaking starts can reduce damage and casualties during an earthquake. It can also prevent cascading failures

in the aftermath of an event. For example, isolating utilities before shaking starts can reduce the number of fire initiations.”

(10) The Federal Emergency Management Agency (FEMA) has estimated the average annualized loss from earthquakes, nationwide, to be \$5.3 billion. The Seismological Society of America states that “Earthquake Early Warning Systems (EEWS) could also reduce the number of injuries in earthquakes by more than 50%.”

(11) Many countries, including the US, Canada and Japan, are investing in the deployment of EEWS, as are government authorities at other levels.

(12) The Seismological Society of America states that EEWS, “like warnings for other natural disasters, such as tornadoes, hurricanes, and tsunamis, is a forecast of activity that is imminent. However, unlike hurricane warnings, which can come days in advance of severe weather, or tsunami warnings, which build over the course of a few minutes to a few hours before the tsunami makes landfall, earthquakes have a much shorter lead time, shorter even than a funnel cloud that starts spiraling toward the earth. A warning could be just seconds. This short warning time is a product of the physical process of an earthquake rupture. EEWS typically use seismometers to detect the first signature of an earthquake (P-wave), to process the waveform information, and to forecast the intensity of shaking that will arrive after the S-wave. For local EEWS installations, the P-wave is detected onsite (i.e., at the user location), and the difference between the P- and S-wave arrival times defines the maximum alert time. For regional networks, the P-waves are detected by sensors closest to the epicenter, and estimates are immediately relayed to earthquake alerting applications (TV, smart phones, radio, etc.) to provide businesses, citizens, and emergency responders more advance knowledge of the expected arrival and intensity of shaking at their location.”

(13) Prior art EEWS systems make use of electronic sensors measure physical quantities (such as velocity, acceleration strain, temperature, crack, pressure, etc.) and convert these physical quantities into signals using suitable reading instruments (e.g. transducers). The particular reading instrument varies depending on the type of sensor. For example, geophones typically incorporate a wire coil with a magnet in the middle that is free to move. As the sensor shakes or vibrates (as is the case during an earthquake), the magnet moves through the coil producing a current, which can be measured to record the variations. To determine the epicenter and the magnitude of an earthquake in accordance with prior art EEWS systems, three to four sensor locations (typically spaced apart by tens of kilometers or hundreds of kilometers) detect the earthquake and communicate with each other to exchange data. The accuracy of epicenter and magnitude predictions depends on the time synchronization between sensor locations and network communication speed between sensor locations.

(14) While existing EEWS systems provide some early warning and damage reduction capabilities, they have at least the following deficiencies: To accurately detect the epicenter and magnitude of the earthquake, the sensors must typically be located relatively far apart (typically 10's or 100's of km) from one another, since the timing accuracy of the systems is on the order of seconds or hundreds of milliseconds. Data from all sensors of interest must typically be gathered and correlated, and the data must then be processed before determining if a warning is to be issued. When sensor locations are hundreds of kilometers apart, gathering, correlating and processing data are time consuming, thereby reducing potential warning time. Some EEWS systems, for example, the system described in U.S. Pat. No. 9,372,272 (Price et al.) comprise sensors that can be placed less than 500 m apart from each other; however, such sensors must be hard wired to a central controller. This is undesirable. First, installation is difficult and complicated since long cables must be installed, which may require digging channels in the earth or through concrete. Second, the long length of the cables could lead to signal degradation and unwanted noise, resulting in unreliable detection of the P-wave signal. Existing EEWS system employ centralized processing of data, which typically involves transmittal of large amounts of data, resulting in a corresponding need for

high bandwidth, highly reliable and costly network infrastructure. Existing EEWS systems also have a need to transfer high volumes of data via network communications. These data transfer requirements dictate a corresponding need for high bandwidth network capability. Establishing and/or maintaining high bandwidth networks over large areas and/or remote locations can be very difficult and costly. Generating a warning with time to arrival of the damaging S-wave requires sensors at multiple locations with time synchronization between locations and high quality network communication between locations. The network communication must be able to transmit signals between the various components of the system with minimal latency in order to be an effective EEWS. There is thus a high need for low latency network communications which may not be readily available at all times. When sensors are far apart, the geology from the epicenter to each sensor can differ significantly. Such geological differences may result in inaccurate prediction of the time and magnitude of the oncoming S-wave. Alternatively, such geological differences require the use of accurate geological models which are costly and time consuming to generate. When existing EEWS systems issue warnings, these warnings are blanket warnings to all within the warning area. It is up to the individuals or organizations within the warning area to interpret the warning, assess the danger and take any desired actions. Some choose to do nothing simply because they do not know what to do or do not think they are in danger. Prior art EEWS systems have no knowledge an individual's or organization's situation or location or least do not incorporate any such knowledge into any applicable recommended courses of action. For instance, if an individual is driving on the freeway, the recommendation should be to pull over safely and stop. However, if the individual is driving in a tunnel, pulling over and stopping inside the tunnel is not the correct action. The preferred action would be to drive through the tunnel and then pull over and stop. As another example, because the generic warnings issued by prior art EEWS systems lack situational awareness within the warning area, such generic warnings can result in an organization unnecessarily shutting down equipment or processes, which can cause unnecessary losses and create more harm than good. Still further, generic warnings (without situational awareness) issued by prior art EEWS systems can cause unnecessary panic. In many existing EEWS systems, the decision-making and actions are left for individual manual execution, which is unreliable and inefficient. In many cases, manual execution is not possible due to the short time available prior to arrival of the damage-causing S-wave. Manual execution is prone to errors. Shutdown of critical equipment typically requires concentration and thought, which may be lacking in panic-driven conditions. Some existing EEWS systems do incorporate autonomous decision-making, but these EEWS systems have been historically unreliable, are expensive or non-viable, and/or have a false-positive ratio which is too high. In addition, these autonomous EEWS systems must typically be placed over a wide area with complicated networking schemes that make them impractical for use by smaller scale businesses and individuals. These autonomous EEWS systems are typically limited to large-scale deployment by government institutions or the like. Some existing autonomous EEWS systems have not operated reliably when earthquakes actually occur. These systems may work well in the laboratory under simulated or mechanically generated vibration conditions, but can tend to fail during actual earthquakes. Also, earthquakes do not occur regularly, making it difficult to perform thorough field testing. Existing EEWS systems only allow for one-way communication from the EEWS system to individuals (affected individuals and emergency response teams) in the warning zone over communication channels which typically require high priority and reliability. Emergency response teams typically use their own communication methods which are only accessible to the public through single points of entry, such as dedicated (call-in) phone numbers. The mere volume of calls during a disaster makes these call-in numbers congested resulting in long wait times. Other than such call-in numbers, there is no provision in existing EEWS systems for affected individuals to communicate back to emergency response teams, family and friends. As a result, affected individuals and emergency response teams may tend to rely on other available communication services, such as social media, to communicate their condition,

location and emergency needs. This individual use of distributed communication channels such as social media is highly inefficient and unreliable, especially when data networks become congested in the affected area (as is typical). Also, not all people affected are connected via social media and not all emergency response teams monitor social media. Further, general data communications over communication networks during a disaster can get highly congested due to the high volume of messages and messages typically do not receive high priority. Some existing EEWS systems, such as the one depicted in US Patent Application No. 2015/0195693 (Hooriani et al.), use sensors in mobile phones and tablets to detect earthquakes and provide warnings. However, such sensors cannot detect the P-wave and can only detect large movements of the S-wave, so they cannot provide a warning of a pending S-wave. Existing EEWS systems do not monitor the surrounding structures and equipment, so any damage resulting from a seismic event cannot be qualified and quantified. Existing EEWS systems report on the seismic event parameters only and have no knowledges of parameters (other than those of the seismic event) in the region in which the warning is issued. It is up to the use of the existing EEWS system to determine the safety risks and/or potential damage that is likely to result from a seismic event. It would be useful to know if the damage from a seismic event results in (or would be likely to result in) safety risks to the personnel using the equipment or utilizing the structure. Alarms and warning can then be issued as necessary to prevent further injuries or damage.

(15) Accordingly, there is a general desire for systems and methods for early warning of seismic events that make use of autonomous actions, which autonomous actions may be executed quickly and efficiently, without the need for manual intervention. There is a general desire for such systems and methods to overcome or at least ameliorate some the drawbacks with prior art EEWS systems.

(16) There is also a general desire for systems and methods for early warning of seismic events which incorporate situational awareness into any warnings that are issued in the event of a seismic event.

(17) There is also a general desire for systems and methods for early warning of seismic events which can monitor and/or control communications (e.g. multi-way communications) through a suitable communication network.

(18) There is also a general desire for systems and methods for early warning of seismic events which provide and maintain reliable, secure and rapid communications.

(19) The foregoing examples of the related art and limitations related thereto are intended to be illustrative and not exclusive. Other limitations of the related art will become apparent to those of skill in the art upon a reading of the specification and a study of the drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIGS. 1*a* and 1*b* (collectively, “FIG. 1”) are schematic diagrams illustrating the operability of sensors of prior art EEWS.

(2) FIGS. 2*a* and 2*b* (collectively, “FIG. 2”) are schematic diagrams illustrating the operability of sensors used in EEWS according to particular embodiments of the invention.

(3) FIG. 3 is a schematic diagram of a system for early warning of seismic events according to an exemplary embodiment of the invention.

(4) FIG. 4 is a schematic diagram of the components within a data acquisition unit (DAU) according to an exemplary embodiment of the invention.

(5) FIG. 5 is a diagram of the hardware of an exemplary DAU according to an exemplary embodiment of the invention.

(6) FIG. 6 is a block diagram illustrating the different software modules of the software application installed on a DAU and their interconnectivity according to an exemplary embodiment of the

invention.

(7) FIG. 7 is a flow chart illustrating the process of triggering local and, optionally, remote situational emergency measures upon sensing a seismic event according to an exemplary embodiment of the invention.

(8) FIG. 8 is a flow chart illustrating the process of authenticating a DAU according to an exemplary embodiment of the invention.

(9) FIG. 9 is a flow chart illustrating the steps of operation at each software application installed on a Personal Internet Device (PID) and the communication between the application and the DAU when a seismic event occurs according to an exemplary embodiment of the invention.

DETAILED DESCRIPTION

(10) Throughout the following description specific details are set forth in order to provide a more thorough understanding to persons skilled in the art. However, well known elements may not have been shown or described in detail to avoid unnecessarily obscuring the disclosure. Accordingly, the description and drawings are to be regarded in an illustrative, rather than a restrictive, sense.

(11) Aspects of the invention provide systems and methods for early warning of seismic events. Such systems and methods may comprise a plurality (e.g. three) separate technologies combined to operate as a flexible condition monitoring and event prediction system—data acquisition technology, sensor technology and event prediction software technology.

(12) The sensors of prior art EEWS are generally placed tens to hundreds of kilometers apart, with the EEWS comprising data acquisition equipment at each sensor location. This large separation between sensors is typically required in most prior art systems, since most prior art systems have a timing accuracy on the order of seconds or hundreds of milliseconds. The need for sensors to be spaced apart by such distances is illustrated schematically by FIG. 1. FIG. 1A illustrates three prior art sensors that are relatively widely spaced apart. The thickness of the lines that surround the FIG. 1A sensors are representative of the timing accuracy of the prior art sensors. When the sensors are spaced apart from one another (as shown in FIG. 1A), the epicenter of an earthquake event (which is represented by the intersection of the three sensor circles) can be detected, despite relatively coarse timing accuracy of the sensors. In contrast, when the sensors are located relatively close to one another, as is the case in FIG. 1B, the timing inaccuracy of the sensors obscures the location of the epicenter—i.e. it is not possible to determine the location of the intersection of the three circles surrounding the sensors.

(13) EEWS systems according to particular embodiments of the invention comprise sensors which take advantage of recent sensor developments which provide sensors with noticeably improved timing accuracy. This is shown schematically in FIG. 2, where the timing accuracy of the sensors is much better (corresponding to circular lines having less thickness). FIG. 2A illustrates three relatively widely spaced apart sensors of the type used in EEWS according to particular embodiments of the invention. Like FIG. 1A described above, when the sensors are spaced apart from one another (as shown in FIG. 2A), the epicenter of an earthquake event can be detected to be the intersection of the three sensor circles. However, unlike the prior art circumstance, with accurate sensors, the intersection of the sensor circles can still be determined, even when the sensors are located relatively close to one another, as is the case in FIG. 2B.

(14) In particular embodiments, the ability to locate sensors relatively close to one another is exploited to provide new EEWS functionality and performance as described further herein.

(15) FIG. 3 is a schematic diagram of a system 10 for early warning of seismic events according to a particular exemplary embodiment of the invention. System 10 of the FIG. 3 embodiment comprises one or more DAUs 16. FIG. 4 is a schematic block diagram representation of an exemplary DAU 16. Referring to FIG. 4, DAU 16 may comprise, without limitation, any or all of the illustrated features to help ensure reliable operation in harsh environments. FIG. 5 is a diagram of the hardware of a DAU 16 according to an exemplary embodiment. FIG. 6 is a block diagram illustrating the different software modules executed by processor 100 of DAU 16 according to an

exemplary embodiment of the invention.

(16) System **10** of the FIG. **3** embodiment comprises a number of sensors **12**. Sensors **12** may comprise a wide range of proven sensor options to measure or sense a correspondingly wide range of phenomena. Sensors may be used to detect P-waves and S-waves, which signal the presence or absence of a seismic event. For example, the sensor options used for detecting P-wave and S-wave may comprise, without limitation, any or all of: single or multi-axial velocity sensors (or geophones); single or multi-axial acceleration sensors; piezometric patch sensors; MEMS velocity and acceleration sensors; combinations of the above; and/or the like.

(17) System **10** may also comprise or be operatively connected to additional sensors **13** which may be used for controlling and/or monitoring external equipment, building structures and/or other infrastructure (not shown). Such sensors **13** may, for example, be used to provide information to help control the proper shutdown of equipment, to verify the shutdown of equipment when a seismic event has been detected, to monitor the effect of an earthquake on building structures and/or equipment and quantify the damage that could have been or could possibly be done to such structures and/or equipment and/or the like. The sensor options used for such sensors **13** may comprise, without limitation, any or all of: strain sensors; temperatures sensors; hall effect sensors for controlling and verifying the shutdown of equipment; visual sensors; acoustic sensors; pressure sensors; flow sensors; humidity sensors; sensors for detecting fluid levels; combinations of the above; and/or the like.

(18) System **10** (and the corresponding method of operating system **10**) provides for early warning of seismic events. System **10** may comprise one or more of its own sensors **12** for detecting seismic events such as those listed above. System **10** may additionally or alternatively be retrofitted to interface with the sensors **12** of a previously installed system. System **10** may incorporate software and/or apps (not expressly shown in the drawing) which may operate on any combination of DAUs **16** (specifically, microprocessor **100** of DAU **16**—see FIG. **4**), servers **51**, **52**, local devices **17** and/or user computing devices **14**. System **10** (through sensors **12** and DAUs **16**) may provide any or all of detection of seismic events (detection of P-waves and/or S-waves), data analysis, determination of event characteristics (e.g. epicenter estimation, magnitude estimation, and/or the like), predictive damage assessment, predictive time to event arrival, damage prevention, early warning, situational alarming, and reliable emergency communication as further explained below.

(19) Referring to FIG. **3**, system **10** comprises one or more DAUs **16** and one or more sensors **12** corresponding to each DAU **16**. In the illustrated embodiment of FIG. **3**, system **10** comprises a first DAU **16**, with one or more corresponding sensors **12A** and a second DAU **16B** with one or more corresponding sensors **12B**. DAUs **16A**, **16B** and their corresponding sensors **12A**, **12B** may be collectively referred to herein as DAUs **16** and sensors **12**. Components of system **10** (e.g. DAUs **16**, sensors **12**, devices **17** and sensors **13**) can operate locally (i.e. in relatively small environments) and can implement local situational emergency measures (recommendations) **18A**, **18B** [collectively, local situational emergency measures (recommendations) **18**], which are specific to particular locations in which such local situational emergency measures **18** are implemented and/or to specific conditions in existence at the locations where, and/or times when, such local situational emergency measures **18** are implemented. Such specific conditions may be based on output from additional sensors **13**. Local situational emergency measures **18** may be communicated to and implemented on or via any suitable local device **17A**, **17B** (collectively devices **17**) capable of local communication with DAU **16**. For example, local situational emergency measures **18** may be communicated to the embedded controller/processor associated with a piece of industrial equipment, building structure or other infrastructure (device **17**) and may be implemented by causing the controller/processor to assume emergency control of the operation and/or shut down of the equipment, building structure or other infrastructure or by causing the controller/processor to display a suitable warning message to the operator of the equipment, building structure or other infrastructure. As another example, local situational emergency measures **18** may be communicated

to a more general purpose computing device **17** which may be programmed or otherwise configured to take any suitable emergency measures. Where local devices **17** have sufficient capability, suitable software operating on local devices **17** may be used to interrogate specific local conditions and may be used in whole or in part to implement local situational emergency measures **18**. Device **17** may comprise other types of devices (e.g. audible alarms, optical warning indicators, PA systems and/or the like).

(20) In particular embodiments, the concept of locality means that each DAU **16**, its corresponding sensors **12**, any device **17** to which corresponding local situational emergency measures **18** are communicated and/or by which corresponding local situational emergency measures **18** are implemented and any local sensors **13** do not depend on network connectivity to other systems or components of system **10** that are installed at relatively large distances (e.g. **10s** and **100s** of km) away. Components of system **10** that are hardwired to one another or which can communicate through a local area network LAN, may be considered to be local, but components requiring larger communication networks, such as the internet **15** or a cellular communication network are not considered to be local. For example, in some embodiments, the separation of the closest pairs of sensors **12A** or sensors **12B** of system **10** may be less than 100 m. In some embodiments, this separation is less than 50 m, making system **10** suitable for deployment in residential properties or in small industrial operations.

(21) System **10** may also operate remotely. For example, DAUs **16** which detect a seismic event may communicate to remote computing devices **14** over the internet **15** or other wide area network and may implement remote situational emergency measures **19**. Remote computing devices **14** may comprise any computing device **14** capable of operating operational software. FIG. **3** shows a number of exemplary and non-limiting types of such computing devices **14**—e.g. desktop computers, laptop computers, tablets, phones, other forms of personal internet devices (PIDs) and/or the like, Remote computing devices **14** may additionally or alternatively comprise suitable embedded processors which may provide part of larger systems, equipment, building structures and/or other infrastructure. By way of non-limiting example, remote computing devices **14** may comprise a processor embedded in a vehicle (e.g. in an automobile or plane), a processor embedded in other equipment (e.g. industrial equipment), a processor associated with the monitoring of a bridge or tunnel and/or the like.

(22) Other than being remote (e.g. separated from DAUs **16** by the internet **15** or other wide area network), remote situational emergency measures **19** may be similar to local situational emergency measures **18**. That is, remote situational emergency measures **19** may be specific to the locations where they are implemented and may depend on specific conditions in existence at the locations where and/or times when they are implemented. Such specific conditions may be based on output from additional sensors **13**. In the illustrated embodiment of FIG. **3**, remote situational emergency measures **19** are schematically depicted as being communicated to various types of computing devices **14** which may implement remote situational emergency measures **19**. This is not necessary, however, and, like local situational emergency measures **18**, remote situational emergency measures **19** may be communicated to and/or implemented by any suitable devices capable of communicating with DAUs **16** over the internet **15** or other wide area network. Where remote devices **14** have sufficient capability, suitable software operating on remote devices **14** may be used to interrogate specific local conditions and may be used in whole or in part to implement, effect or otherwise provide remote situational emergency measures **19**. For example, a remote device, such as a mobile phone **14**, may have the ability to detect its current location (e.g. via a GPS receiver). Accordingly, in some embodiments, DAU **16** and/or alerting server **51** (described further below) may issue an alert comprising some information about a seismic event and software resident on the phone **14** may consider the current location of the phone **14** relative to the seismic event and/or other information specific to the location of the phone **14** before issuing a situational emergency measure **19** that depends on the location of the phone **14**.

(23) FIGS. 4 and 5 show different schematic views of the hardware components of a DAU 16 according to a particular embodiment. DAU 16 comprises a suitable processor 100 which may be programmed or otherwise configured to provide the functionality and perform the methods described herein. FIG. 6 shows a block diagram illustrating the different software modules which may be executed by processor 100 of DAU 16 according to an exemplary embodiment of the invention. Some of the software executed by processor 100 may be resident on a memory 104 accessible to processor 100. Memory 104 may also be used to record data received from sensors 12. The FIG. 6 software modules are explained in more detail below.

(24) Referring to FIG. 4, processor 100 of DAU 16 is connected to receive outputs from sensors 12 and optionally from additional sensors 13 directly or through corresponding devices 17. DAU 16 and/or sensors 12, 13 may comprise signal conditioning circuitry (e.g. amplifiers, DACs, buffers, filters and/or the like not shown) which is well known to those skilled in the art. DAU 16 of the illustrated embodiment comprises a GPS receiver 102 that is connected to receive signal from GPS satellites 20. Such signals received by GPS receiver 102 may provide location information and timing information. DAU 16 of the illustrated embodiment comprises a local communication interface 106, via which DAU 16 can communicate local situational emergency measures 18 to local devices 17 (or to sensors 13 associated with local devices 17). In some embodiments, local communication interface 16 may comprise a hard-wired interface between devices 17, sensors 13 and DAU 16, although this is not necessary. In some embodiments, local communication interface 16 comprises a wireless communication interface. DAU 16 of the illustrated embodiment comprises a remote communication interface 108 (e.g. an internet communication interface) which may be used to communicate remote situational emergency measures 19 to devices 14 via the internet 15 or other wide area network. Remote communications interface 108 may comprise a wired and/or wireless communications interface.

(25) In some embodiments, each sensor 12 is connected to a corresponding single DAU 16 via hard-wired communications (or also referred to as local connections or local communications). In some embodiments, each sensor 12 is connected to its own dedicated DAU 16 via hard-wired communications. In such embodiments, the need for using long running cables to connect the sensors 12 to a single DAU 16 may be avoided. This avoids the need to dig ditches in the earth, bore holes through concrete or other structures and the like to fish hard-wired cables and reduces the risk of signal degradation in a long cable; resulting in a system which is more reliable and easier to install. Hard-wired connection may be more desirable than wireless connection because hard-wired communications permit data from sensors 12 to be processed by DAU 16 relatively quickly (as compared to prior art systems relying on communication of sensor information over communication networks), enabling correspondingly fast response times and damage prevention actions and/or recommendations for local situational emergency measures 18, and additional warning time for individuals and organizations that may be impacted by a seismic event.

(26) The ability to synchronize time with high precision between different DAUs 16 enables installation of multiple DAUs 16 in close proximity and eliminates the need to connect all sensors 12 with long wired cables to a central controller. High precision time synchronization may be achieved in DAUs 16 by using a combination of GPS signal output from GPS receiver 102 and an optional temperature compensated crystal oscillator (TCXO) 110. In particular embodiments, DAUs 16 may comprise a GPS receiver 102 (see FIG. 4), which may be operatively connected to GPS satellites 20 to obtain precise time information. In situations where satellite communication is not available, DAUs 16 may be provided with an optional TCXO 110 which may be used to maintain the time accurately until satellite communication is re-established.

(27) In particular embodiments, parameters and/or characteristics of seismic events (such as, by way of non-limiting example, epicenter of the earthquake, the magnitude of the surface wave (S-wave) associated with the earthquake and the time of arrival of the S-wave) can be determined locally by processor 100 based on input from sensors 12 in relation to a detected P-wave or S-

wave. DAU **16** may provide multi-kilohertz sampling capability of the outputs of sensors **12** and sub-millisecond accuracy of the arrival times of the P-waves and S-waves associated with seismic events. In embodiments where components of system **10** (e.g. DAU **16**, sensors **12** and devices **17**) are locally connected with each other (e.g., via hard-wired connections or via a LAN), failures of wide(r) area networks (e.g. the internet or cellular communications networks) do not affect the operation of DAUs **16** and sensors **12** to provide local damage prevention actions and/or recommendations for local situational emergency measures **18** to devices **17**, because each DAU **16** comprises its own local processing capabilities (processor **100**—see FIG. **4**).

(28) Local situational emergency measures **18** may include, without limitation, local sirens, visual warnings/instructions/recommendations displayed on specialized displays, equipment displays, local computing devices and/or the like (together devices **17**) locally connected via hardwiring or via LAN, automatic assumption of control or shutdown of devices **17**, instructions issued over a local public address system and/or the like.

(29) The local-wired communications between DAU **16**, sensors **12** and devices **17** which receive local situational emergency measures **18** also reduce or eliminate the need for high data bandwidth, high reliability and high cost network infrastructure used to interconnect multiple systems or sensors located over large geographic areas. Since each DAU **16** can act autonomously, data from sensors **12** can be processed locally. The results of this processed data may be transmitted to other DAUs **16** (other local DAUs **16** or distributed DAUs **16**, via the internet **15** or some other suitable wide area network) to provide additional early warning time if deemed necessary. This transmission of results between DAUs **16** may involve the use of minimal bandwidth (since results, rather than raw data can be transmitted) and can be implemented over low cost data communication infrastructure. Transmission of results between DAUs **16** is not required but may provide additional early warning to locations further away from the epicenter. Local-wired communications also means that sensors **12** or system **10** may be placed in remote areas where reliable network connectivity is unavailable or difficult to achieve.

(30) In some embodiments, components within system **10** (e.g., DAU **16**, sensors **12**, additional sensors **13** and/or devices **17**) may be connected wirelessly. In such cases, sensors **12**, **13** and any wireless transceivers (not shown) may be powered using batteries, solar, wind, geothermal, or energy harvesting from the surrounding environment. If network communications are available, then DAU(s) **16** can transmit earthquake parameters to user computing devices **14** and/or other systems (not shown) via the internet **15** or other suitable wide area network. Such user computing devices **14** and/or other systems can decide to remotely implement damage prevention actions and/or recommendations for their own local situational emergency measures **18**, based on the earthquake parameters determined and communicated by DAU **16**.

(31) In some embodiments, DAUs **16** may transmit and users may receive alarms, warnings and other forms of remote situational emergency measures **19** through the internet (or other wide area networks) **15** via remote devices **14**; however, these remote situational emergency measures **19** would be subject to network delays and failures. In some embodiments, DAUs **16** may transmit determined event parameters or characteristics to user computing devices **14** and/or other systems (not shown) via the internet **15** or other suitable wide area network. Such user computing devices **14** and/or other systems can then decide on their own accord implement damage prevention actions, recommendations and/or other forms of remote situational emergency measures **19**, based on the earthquake parameters/characteristics determined and communicated by DAU **16**.

(32) System **10** may also include a Controller Area Network (CAN) interface **21** which enables DAU(s) **16** to connect to vehicles and industrial controllers to obtain situational parameters and execute local situational emergency measures **18** that may be specific to the location or operating condition of the vehicle or industrial controller.

(33) System **10** may further include a main server (not shown in FIG. **3**) which may be interconnected with DAUs **16** and/or other prior art EEWs systems to form a large network

covering a vast geographic area, although this is not a necessity. In some embodiments, such a main server may be implemented by one of DAUs **16**. This interconnectivity between multiple DAUs **16** and/or with prior art EEWS systems, if available, may improve the accuracy of epicenter estimation and/or magnitude prediction. The improved accuracy may be due to data transmitted from a large number of sensors spread throughout a large geographic area. As discussed above in relation to FIGS. **1** and **2**, if the sensors are further separated from each other, the accuracy of the epicenter estimation would be less dependent on timing accuracies and geological anomalies related to P-wave and S-wave propagation. Although this interconnectivity is not necessary for implementing the features of early warning, damage prevention actions and/or recommendations for local situational emergency measures **18**, it may be used for remotely implementing local situational emergency measures **18**.

(34) System **10** can be connected to output damage prevention actions (which may be part of local situational emergency measures **18**) to most types of electrical and/or mechanical devices **17** and such damage prevention actions may be used to automate shutdown of, or otherwise control the operation of, equipment, building structures, other infrastructure and systems that could be damaged during a disaster and cause more damage to the surrounding infrastructure and/or environment. By way of non-limiting example, tunnels can be closed to prevent additional vehicles from entering, trains can be stopped to prevent derailments, water systems can be shut off to prevent flooding, electricity can be shut off to prevent short circuits and fires, and pipelines can be shut down to prevent environmental damage.

(35) FIG. **7** illustrates an exemplary method **50** for initiating local situational emergency measures **18** and, optionally, remote situational emergency measures **19** upon sensing a seismic event. Method **50** may be performed by processor **100** of one or more (e.g. each of) DAUs **16** (see FIG. **4**) in system **10**. Method **50** begins in block **52**, where DAU **16** monitors the outputs of its associated sensors **12**. As discussed elsewhere herein, the outputs of sensors **12** are sensitive to P-waves and S-waves associated with seismic events. Sensors **12** may be located relatively close to one another—e.g. in a building, in an industrial site and/or the like. Sensors **12** need not be spaced by tens or hundreds of kilometers. In block **53**, DAU **16** analyzes the output signals from its corresponding sensors **12** to determine if a detected P-wave comprises characteristics indicative of an earthquake. This block **53** determination may be based on comparing the amplitudes and/or frequencies of one or more sensor signals to corresponding threshold levels. Such threshold levels may be configurable (e.g. user configurable) depending on desired sensitivity. Such threshold levels may be dependent on the particular types of sensors **12** and signal conditioning circuitry (not shown) which are used in system **10**. The block **53** determination is not limited to being based on amplitude and/or frequency thresholds alone and may be made on other characteristics of a detected P-wave which may be indicative of an earthquake.

(36) DAU **16** continues to monitor sensors **12** (block **52** and block **53** NO branch) until it determines in block **53** that a detected P-wave is indicative of a seismic event. If DAU **16** determines that the incoming P-wave comprises characteristics indicative of an earthquake (block **53** YES branch), alerts (e.g., in the form of an audible, visual and/or electronic alarms, recommendations and/or the like) may be triggered (block **54**) and local situational emergency measures **18** may be initiated (block **56**) and, optionally, remote situational emergency measures **19** may be initiated in block **57**. In particular embodiments, high priority and reliable data channels are used to communicate the block **54** alerts to users and to implement local situational emergency measures **18** in block **56**. Remote situational emergency measures **19** implemented in block **57** may be similar to local situational emergency measures **18**, except that DAU **16** may communicate such remote situational emergency measures **19** over the internet **15** or some other wide area network (see FIG. **3**). High priority and reliable communications channels may be secured a priori with network communications service providers. The block **54** alerts may be effected and the block **56**, **57** situational emergency measures **18** may be initiated as soon as P-waves having characteristics of

earthquakes are detected in block **52** (i.e. before the arrival of the more damaging S-waves).

(37) Local situational emergency measures **18** that may be initiated in block **56** may depend on the specific location at which the local situational emergency measures **18** are implemented. For example, local situational emergency measures **18** at the collar of an oil well may be different than local situational emergency measures **18** at the office located some distance away from the collar of the oil well. Local situational emergency measures **18** that may be initiated in block **56** may additionally or alternatively depend on specific situations that may be present at a particular time in the location where local situational emergency measures **18** are implemented. For example, local situational emergency measures **18** at the collar of an oil well may be different depending on whether or not drilling is active at the time that local situational emergency measures **18** are implemented. Local situational emergency measures **18** that may be initiated in block **56** may additionally or alternatively depend on specific situations determinable from the output of additional sensors **13** associated with devices **17**. For example, additional sensors **13** associated with a drilling rig may detect the presence or absence of workers at some distance up the derrick oil well (e.g. at the racking (monkey) board or at the crown block of the derrick) and local situational emergency measures **18** may be different depending on whether workers are detected at such above-ground locations. Where local devices **17** (FIG. **3**) have sufficient capability, suitable software operating on local devices **17** may be used to interrogate specific local conditions (e.g. data from additional sensors **13** or other available databases) and may be used in whole or in part to implement local situational emergency measures **18**. Remote situational emergency measures **19** that may be initiated in block **57** may be similar to local situational emergency measures **18** initiated in block **56** (e.g. they may depend on specific locations, situations, times and/or sensor outputs where they are implemented), except that remote situational emergency measures **19** may be initiated over the internet **15** or other wide area network as opposed to locally. Where remote devices **14** (FIG. **3**) have sufficient capability, suitable software operating on remote devices **14** may be used to interrogate specific local conditions and may be used in whole or in part to implement remote situational emergency measures **19**.

(38) In addition to effecting the block **54** alerts and initiating the block **56**, **57** situational emergency measures **18**, **19**, DAU **16** is also configured, in block **58**, to use the detected P-wave to determine or estimate a number of event characteristics (step **58**). Exemplary event characteristics include earthquake epicenter, earthquake magnitude, predicted earthquake S-wave characteristics and earthquake time of arrival estimations (e.g. at the DAU location or at some other location(s) of interest). For example, an earthquake epicenter location may be determined or estimated by calculating the difference between the arrival times of the P-wave from different sensor locations along with geological P-wave characteristic data and geological data. The magnitude of the earthquake may be determined or estimated based on the epicenter location and the magnitude of the P-wave output signal. Based on the calculated epicenter location and the magnitude of the earthquake, S-wave characteristics and time of arrival at one or more locations of interest may be estimated.

(39) The information determined in block **58** (which is ascertained prior to the arrival of the damaging S-wave) may be used in providing or updating alerts (block **54**) and/or situational emergency measures **18**, **19** (blocks **56**, **57**). For example, the degree of a block **54** alert may be based on information determined in block **58**. Similarly, the specific local situational emergency measures **18** in block **56** and/or remote situational emergency measures **19** in block **57** may be based on event characteristics determined in block **58**. Block **54** alerts and block **56**, **57** situational emergency measures **18**, **19** provided prior to the arrival of the damage causing S-waves may help to mitigate human injury and damage to industrial equipment and/or building structures, loss due to unnecessary shut-down of industrial equipment and/or the like. Block **54** alerts and block **56**, **57** situational emergency measures **18**, **19** which are tailored based on block **58** event characteristics may further mitigate such injury, damage and/or loss.

(40) The illustrative example shown in FIG. 7 assumes that an actual seismic event **60** occurs. In block **62**, outputs from sensors **12** associated with DAU **16** are monitored to detect measured S-wave data and this measured S-wave data may be compared to the block **58** predicted S-wave characteristics. This optional block **62** comparison may be used to improve performance of system **10**, for example, to validate S-wave prediction algorithm(s) or portion(s) thereof that may be used by system **10**; to further tune S-wave detection algorithm(s) or portion(s) thereof that may be used by system **10**; and/or the like.

(41) After a seismic event **60**, method **50** also comprises performing a post-event check in block **62** to ascertain the condition of buildings and or equipment of interest. The building and/or equipment of interest evaluated in block **62** may comprise local equipment comprising or otherwise associated with devices **17**. The block **62** evaluation may be based on measured S-wave characteristics and data from additional sensors **13A**, **13B** (collectively, sensors **13**) associated with devices **17** (e.g. equipment, building structures and/or other infrastructure of interest). Sensors **13** may, for example, comprise strain sensors, pressure sensors and or the like, which may be associated with the equipment, building structures and/or other infrastructure of interest (e.g. devices **17**). If seismic event **60** causes excessive strain or stress on the buildings and/or equipment of interest (block **62** NO branch), then method proceeds to block **64** which involves updating alerts (block **54**) and/or situational emergency measures **18**, **19** (blocks **56**, **57**) based on the updated information associated with the actual seismic event **60**. For example, in block **56**, it may be determined (based on the P-wave and/or based on sensors local to a piece of equipment) that the piece of equipment is suitable for operation, but after the actual earthquake **60**, it may be determined in block **64** that the equipment should be shut down to prevent future damage to the equipment, further damage to other equipment or buildings, further risk to individuals and/or the like. Block **64** may also involve recommending future maintenance decisions for the equipment, building structures and/or other infrastructure of interest and/or future design considerations for the equipment, building structures and/or other infrastructure of interest based on the output of sensors **13** and/or the measured S-wave characteristics.

(42) After the conclusion of block **64** and/or on a block **62** YES branch, method **50** may return to block **52**.

(43) In some embodiments, system **10** comprises one or more alerting server(s) **51**. Alerting server(s) **51** may comprise a virtual cloud of one or more server(s). In some embodiments, the functionality of alerting server(s) **51** is performed by DAU **16** (specifically, by alerting module **151** (FIG. 6), which may be performed by processor **100**). In some embodiments, alerting server **51** is separate and distinct from DAU **16**.

(44) Security measures may be implemented to protect alerting server **51** from unwanted attacks or other malicious use (such as rogue insertion of false positives, or the manipulation of the server **51** to suppress alerts and/or generate false positives). In particular embodiments, security protections are in place to prevent inbound connections at the network layer from all senders other than those with explicit permission. In some embodiments, DAU **16** and alerting server **51** may be communicatively connected via a wired and/or wireless connection. In some embodiments, DAU **16** and alerting server **51** may be local to one another. In some embodiments, DAU and alerting server **51** may be remote from one another. In some embodiments, each DAU **16** must first be authenticated before any connections between DAU **16** and alerting server **51** can be enabled. In some embodiments, each DAU **16** can be identified by alerting server **51** via each DAU's current IP address and assigned time-limited authentication key.

(45) FIG. 8 schematically depicts an exemplary authentication process **200** between a DAU **16** and an alerting server **51** according to a particular embodiment. Authentication process **200** may be performed in part by DAU **200** and in part by alerting server **51**. Authentication process **200** of the illustrated embodiment starts in block **202** where a DAU **16** that wants to communicate with alerting server **51** transmits its current IP address to the alerting server **51**. Upon receipt of the IP

address of DAU **16**, method **200** proceeds to block **204** where alerting server **51** transmits to DAU **16** an authentication key (hereinafter referred to as a “token”). The block **204** token may be used as an identifier by each DAU **16** to identify itself to the alerting server **51** to thereby authenticate future communications (e.g. in block **208**) between DAU **16** and the alerting server **51**. In block **206**, alerting server **51** associates the current IP address and token of the respective DAU **16** and stores such information in a whitelist database to facilitate such future communications (e.g. in block **208**). In block **208**, the whitelisted DAU **16** and alerting server **51** communicate with one another as may be suitable in any particular circumstance. As part of block **204** and/or block **208**, alerting server **51** may transmit a number of operational parameters to DAU **16**. Such parameters may include, without limitation, a Distinguished Name (DN) for the node, any policy configuration parameters for alert transmission, and destination IP addresses to be used when DAU **16** communicates updates to the alerting server **51**.

(46) The block **204** token may include a validity period and expiration date. The token may, for example, be valid for a duration of 15 to 30 days; however, any suitable validity periods may be used. If, the expiry of a token is approaching (e.g. when a threshold amount (e.g. 85%) of the authentication period has expired) and continued communication is desired, then it may be desirable to renew the token (block **212** YES branch). It may additionally or alternatively be desirable to renew a token (block **212** YES branch) if the IP address of DAU **16** has changed (e.g. unexpectedly by the local internet connection service provider and/or the like).

(47) If method **200** proceeds along the block **212** YES branch, then method **200** arrives at block **214**, where DAU **16** submits its old token together with its (potentially new) IP address and requests a new token. In block **216**, alerting server **51** verifies the old token and the (potentially new) IP address of the requesting DAU **16**. Block **216** may involve matching the block **214** information with the whitelist database. Once the old token and IP address of the requesting DAU **16** has been verified, alerting server **51** sends a new token to DAU **16** as a part of block **216**. Block **216** may optionally involve alerting server **51** sending operational parameters (such as those discussed above for blocks **204/208**). Block **214** may optionally involve sending one or more confirmatory communications between the DAU **16** and alerting server **51**. Method **200** then returns to block **206**, where alerting server **51** updates the whitelist with information regarding the new token and IP address of DAU **16**.

(48) In particular embodiments, as part of the block **208** communications or otherwise, alerting server **51** transmits to DAU **16** operational updates (e.g. software updates, situational updates and/or the like) when such updates become available. Updates may be transmitted to DAU **16** via real-time or queued/batched mechanisms. Different communication links may be used for such update communications, depending on the bandwidth and connectivity of the available network connection. For example, if the available network connection has adequate bandwidth and reliable connectivity, DAU **16** may have a full-duplex persistent connection to alerting server **51**. In such case, updates, if available, may be communicated immediately to DAU **16** as part of block **208** or otherwise. By contrast, if the available network connection has low bandwidth and poor connectivity, DAU **16** may not establish persistent connection with alerting server **51**. In such case, updates may be transmitted to DAU **16** via a queued/batched mechanism as part of block **208** or otherwise. Any transmission of updates between alerting server **51** and DAU **16** will be interrupted when a seismic event occurs. In some embodiments, DAU **16** comprises protocols (e.g. software routines) to test any new update to ensure proper and successful installation prior to usage.

(49) Referring to FIG. **3**, alerting server(s) **51** are configured to deliver alerts to any registered users (i.e., individuals who have installed the system **10** software application on their devices **14**) and unregistered users (i.e., individuals who do not have the system **10** application installed on their devices **14**, but who have third-party application software that is programmatically linked to the system **10** infrastructure). In some embodiments, such alerts may comprise situational emergency measures **19**. As discussed above, situational emergency measures **19** may depend on or otherwise

be specific to the locations of devices **14** where they are implemented and may depend on specific conditions in existence at the locations of devices **14** where and/or times when they are implemented. Such specific location conditions may be determined based on output from additional sensors **13**. Where remote devices **14** have sufficient capability, suitable software operating on remote devices **14** may be used to interrogate specific local conditions (e.g. from sensors **13** and/or other accessible databases) and may be used in whole or in part to implement, effect or otherwise provide situational emergency measures **19**.

(50) The decision as to whether alerting server(s) **51** may send such alerts to any particular user computing device **14** may depend on a number of criteria, which may include, without limitation, the current location of the particular device **14**, the type/size/location or other characteristics of a detected seismic event, and the risk of assessment for immediate danger at the particular location of device **14**. Alerting servers **14** may send alerts to particular third parties, who request alerts event in circumstances where their particular device **14** does not otherwise meet the alert criteria, but another device **14** and/or location of interest meets the alert criteria. For example, a parent may receive notifications about a seismic event which is a material risk to his/her child's school building. Similarly, a business operator may receive an alert if the building in which his/her business is located is at risk of major damage, even if the business operator isn't present at the location at the time of the event. In some embodiments, the software application may be configured to prioritize the display of situational emergency measures **19** on such third parties' devices **14**. Specifically, each software application may be configured to first display guidance in respect of situational emergency measures **19** relevant to the current location of a device **14** if a seismic event is relevant at that current location. Alerts (including, possibly, situational emergency measures **19**) in respect of other locations may be displayed subsequently or upon user request.

(51) In particular embodiments, alerting server **51** is configured to apply one or more customized alerting policies to different users or groups of users depending on various parameters (e.g. user-configurable parameters). Such parameters may include, without limitation, the user's location (e.g. location of device **14**), the type/size/location or other characteristics of a detected seismic event, and the risk of assessment for immediate danger at the location of the device **14**. Such parameters may be configured by operators such as government or private entities. The one or more customized alerting policies (which may include situational emergency measures **19**) may be preset by different operators, and may operate concurrently. Exemplary customized alerting policies include, without limitation, the following: a government emergency alerting policy where alerts (which may include situational emergency measures **19**) are provided to anyone within a given geographical region of any seismic event at or above a threshold magnitude; and an alerting policy unique to a particular facility such as a large office building where alerts (which may include situational emergency measures **19**) are provided to all the workers (or specifically, those who are known to be in the building at the time of the report as reported by the location services on their devices **14**) if any seismic event is detected to be at or above a threshold magnitude during business hours and/or if the type of seismic event is likely to cause structural damage to the particular building itself.

(52) In particular embodiments, system **10** further comprises one or more notification servers **52**. Notification server(s) **52** may comprise a virtual cloud of one or more server(s). In some embodiments, the functionality of notification server(s) **52** is performed by DAU **16** (specifically, by notification module **152** (FIG. 6), which may be performed by processor **100**). In some embodiments, notification server **52** is separate and distinct from DAU **16**. Alerting server(s) **51** may be configured to transmit alert(s) (which may include situational emergency measures **19**) to the one or more notification server(s) **52**. Notification servers **52** may be connected to one or more notification channels. Exemplary notification channels include, without limitation, "push notification" for smartphones **14** or similar PIDs **14**, live connections to a government-run Emergency Alerting System (EAS) and/or the like. Alerting server(s) **51** may be configured to

transmit alert(s) to the notification server(s) **52** via an Application Programming Interface (API) which comprises a number of parameters. Such parameters may include, without limitation, the time/date of the seismic event, the calculated magnitude of the seismic event, any uncertainty factors in respect of the accuracy in calculating the magnitude of the seismic event, and the location of the particular sensor **12** that first detected the event. Notification server(s) **52** may be configured to receive such alert(s) (which may include situational emergency measures **19**) and transmit such alert(s) rapidly and directly to the one or more notification channels without applying further analysis or decision logic. In other respects, notification server(s) **52** and the alert(s) communication by notification server(s) **52** may be similar to notification servers **51** and the alert(s) communicated by alerting server **51** described herein.

(53) As discussed above, alerting server **51** may be configured to deliver alerts to the devices **14** of any registered users and unregistered users meeting particular criteria. Alerting server **51** may also be configured to apply one or more customized alerting policies to different users or groups of users depending on various user-configurable parameters. One of such configurable parameters may be the current location of the user device **14**. In particular embodiments, alerting server(s) **51** is configured to respond to requests from the user's device **14** about specific information related to the user's customized alerting policies prior to a seismic event. For example, if location signal(s) received via the GPS receiver of the user's device **14** has associated with it a customized alerting policy, the software application installed on the user's device **14** may download and cache alert data specific to that location of the user's device **14**.

(54) Downloadable alert data may include for example, infrastructure information and geological data about the area, optimized travel routes to and from the area, and information on the presence of any of the user's family members in the area. In some embodiments, alerting server **51** may request a particular user's device **14** to send location signal(s) via the GPS of the user's device **14** for emergency response or emergency notification purposes. In the event a seismic event occurs, situational emergency measures **19** (such as, for example, the locations of emergency exits or the recommended locations to find safety inside a building) may be displayed on the user's device **14**. In some embodiments, any alert situational emergency measures **19** downloaded onto a user device **14** is not removed from such device **14** when the user leaves the particular location. In such case, the cached situational emergency measures **19** may be retained so that when the alerting server(s) **51** receives the same location signal from that particular device **14** in the future, situational emergency measures **19** may be rapidly made available to the user. The software application executed on device **14** may compare the cached copies of the situational emergency measures **19** against the current copies, and replaces the cached copies only if updates have been created.

(55) In some embodiments, the software application installed on the user's device **14** may additionally include a database of customized alerting policies which may be available to system **10**. The database may include information such as the geographic boundaries in which particular alert policies apply. The software application running on device **14** may be configured to compare the device's current location (obtained via the GPS of each device **14**) with the database to determine whether the user has entered a geographic boundary in which a particular alerting policy applies. In some embodiments, the software application on each device **14** requests for updates to the database from alerting servers **51** at configurable time periods. In some embodiments, alerting servers **51** transmit to the software application on each device **14** any updates as they become available.

(56) In some embodiments, the software application on each device **14** does not permit users to perform any administrative changes to the system. In such cases, the software application on each device **14** is intended to only comprise a display-only capability. In cases which operators wish to configure their own customized alerting policies, a separate software application may be used to allow operators to configure and test their customized alerting policies without delivering actual notifications to end users.

(57) FIG. 9 is a flow chart illustrating a method 300 of implementing situational emergency measures 18, 19 according to a particular embodiment. Method 300 may be performed by any combination of DAUs 16 (specifically, microprocessor 100 of DAU 16—see FIG. 4), servers 51, 52, local devices 17 and/or user computing devices 14. Method 300 may be used to perform block 56 (local situational emergency measures 18) and/or block 57 (remote situational emergency measures 19) of method 50 (FIG. 7). Method 300 may additionally or alternatively be used when situational emergency measures 18, 19 are updated in block 64 (FIG. 7). For the purpose of explaining method 300, it is assumed that the P-wave associated with a seismic event has been detected (see block 53 YES branch of method 50 (FIG. 7)) and that the expected characteristics of the S-wave associated with the seismic event have been predicted (see block 58 of method 50 (FIG. 7)). These estimated seismic event characteristics are represented in FIG. 9 by estimated earthquake data 302.

(58) Method 300 involves using estimated earthquake data 302 to determine and implement local situational emergency measures 18 (in block 304) and, optionally, remote situational emergency measures 19 (in block 306). As discussed above, situational emergency measures 18, 19 are specific to particular locations in which such situational emergency measures 18, 19 are implemented and/or to specific conditions in existence at the locations where, and/or times when, such situational emergency measures 18, 19 are implemented. Local situational emergency measures 18 implemented in block 304 may be locally implemented—e.g. using a hardwired configuration or a local area network configuration and without having to use the internet 15 or any other external wide area network. In some embodiments, situational information (e.g. the locations of devices 17 and/or the specific conditions in existence at the locations where, and/or times when, and/or as measured by associated additional sensors 13 where, location situational emergency measures are implemented) may be known to device(s) 17 (at which the situational emergency measures 18 are implemented), to DAUs 16 and/or to other local devices 17. In such circumstances, some of the procedures of blocks 318, 320, 322 and/or 324 need not be performed for the local situational emergency measures 18 implemented in block 304. In some circumstances or embodiments, this a priori knowledge may not be known and implementing local emergency measures 18 in block 304 may involve procedures similar to any of those of blocks 318, 320, 322 and/or 324 described in more detail below.

(59) This a priori knowledge may not (and typically does not) exist in the case of the remote situational emergency measures 19 implemented in block 306 of method 300. Block 306 may comprise transmitting the estimated earthquake data 302 to connected devices 14 (block 308). The block 308 procedure may involve communicating with remote devices 14 which are programmed to operate with application software specific to system 10 (FIG. 3). In addition, in block 310, the estimated earthquake data 302 may optionally be transmitted to remote DAUs 16, which may in turn transmit the estimated earthquake data 302 to their connected devices 14 (in block 312). The block 312 procedure may be similar to the block 308 procedure, except for block 312 may involve different DAUs 16 and different devices 14. Still further, in block 314, estimated earthquake data 52 may optionally be transmitted to one or more other external earthquake early warning system (EEWS) networks, which may then transmit this estimated earthquake information to additional connected devices 14 (block 316). The devices 14 to which the estimated earthquake data 52 is sent in block 316 may comprise devices 14 that are not running application software specific to system 10 (although this is not necessary).

(60) At the conclusion of blocks 308, 312, 316, any device 14 receiving the estimated earthquake data 302 may become involved in implementing situational emergency measures 19 that are specific to the location of the particular device and/or to specific conditions in existence at the locations where, and/or times when, and/or as measured by associated additional sensors 13 where, such situational emergency measures 19 are implemented. This portion of block 306 may start in block 318, where each device 14 checks for its location (if available, for example, via GPS receiver

that forms part of the device) and, in some circumstances, checks for situational information. Such situational information may include any information related to specific conditions in existence at the locations where, and/or times when, and/or as measured by associated additional sensors **13** where, block **318** is performed. Situational information may comprise, for example, information accessible in databases of infrastructure information, customized alerting policies, alert data for various locations, such as infrastructure construction type, construction materials, building foundation type, building design parameters, building age, remote gas and/or electricity shut off locations, commuting patterns, locations where people accumulate (e.g. schools, arenas, etc.), optimized routes to nearby hospitals, information from associated sensors **13** and/or the like. By way of specific example, device **14** may comprise a computer associated with a piece of equipment, and the situational information ascertained in block **318** may comprise an operational state of the equipment, as measured by an associated sensor **13**. As another example, the location information associated with a device **14** may determine that the device is inside a particular building and situational information may include a seismic upgrade database that advises that this particular building has undergone recent seismic upgrades. As still another example, the situational information may ascertain that there is no parking on a particular roadway at a particular time and, consequently, it would be unwise to stop a vehicle. It will be appreciated that there are many examples of situational information that could be determined in association with a particular device **14**.

(61) Method **300** then proceeds to block **320** which involves estimating local earthquake information at the location of device **14**. The block **320** local earthquake information may be based on device location information determined in block **318** (if available) and estimated earthquake information **52** that is transmitted to device **14**, via one of blocks **308**, **312**, **316**. If the specific location of a particular device is not known in block **320** (e.g. because a device **14** does not know or cannot ascertain its location), then block **320** may assume that device **14** is relatively close to the epicenter of the seismic event. Method **300** may then proceed to block **322** which may involve checking the block **320** local earthquake characteristic estimates against the block **318** location and situational information. Then, based on this block **322** comparison, specific situational emergency measures may be implemented in block **324**. For example, in some circumstances, the block **318** situational information may ascertain that a device **14** is located in a building with a seismic rating up to a particular threshold. The block **320** local information may determine that the estimated earthquake parameters at the location of device **14** may be above or below this threshold and the block **324** situational emergency measures **19** may depend on the block **322** comparison of the block **320** local earthquake estimates to the block **318** seismic thresholds.

(62) Eventually, the seismic event **60** occurs. After the occurrence of seismic event **60**, system **10** generates actual (i.e. measured) earthquake data **326** in relation to the actual seismic event **60**. Method **300** may then proceed to block **328** which may implement block **64** of method **50** (FIG. 7) and may involve updating alerts and/or situational emergency measures **18**, **19** implemented in blocks **304**, **306** based on the updated earthquake data **326** associated with actual seismic event **60**. Block **328** may comprise block **330** which may update local situational emergency measures **18** and block **332** which may update remote situational emergency measures **19**. Blocks **330**, **332** may be respectively similar to blocks **304**, **306** described herein, except that blocks **330**, **332** may use actual earthquake data **326** in the place of estimated earthquake data **302**.

(63) System **10** may be provided with a user-friendly graphical interface (e.g. operating on user computing devices **14** and/or on devices **17** and/or on DAUs **16**) which can be accessed via standard web-browsers from Internet-connected devices **14**, **17** and/or DAUs **16** or via applications on user computing devices **14**, devices **17** and/or DAUs **16**. Applications performed on user computing devices **14** may also allow for pre-programming emergency contacts that can be reached via device **14** and/or an associated communication device. Pre-programming of emergency contacts may permit high priority communication with relatives and friends, and emergency response teams

through highly reliable data channels, which may be secured through prior agreements with cellular service providers, for example. In some embodiments, an administrator user interface (e.g. operating on one or more user computing devices **14**) may be provided to adjust various parameters or features of DAU **16** and/or other aspects of system **10**.

(64) When operating on a personal internet device (PID) **14**, such as a mobile telephone or the like, the application software operating on device **14** may have access to the PID's sensors (which may embody additional sensors **13**) and/or network information, including, for example, GPS information, IP address and/or the like, which may in turn enable the application software to know the geographical location of PID **14**. Knowing the geographical location of PID **14** enables system **10** to remotely provide the individual associated with PID **14** with recommendations for remote situational emergency measures **19**. In addition, the application operating on device **14** may be able to access databases of infrastructure structural information, infrastructure type, geological information and/or the like to tailor the remote situational emergency measures **19** to the individual's location.

(65) For example, system **10** may determine that an individual (and his/her PID **14**) are located at a particular geographic location and an infrastructure information database may indicate that the particular geographic location is associated with a multi-story brick building. The infrastructure information database may provide an indication that the corresponding building has been upgraded with earthquake proofing technology capable of withstanding earthquakes up to a particular magnitude. In such circumstances, system **10** may remotely provide user computing device **14** with remote situational emergency measures **19** which may depend on the level of the expected earthquake at the particular geographic location. For example, if the expected earthquake at the particular geographic location is less than the building's earthquake-proofness level, then a first remote situational emergency measure **19** may be recommended, but if the expected earthquake at the particular geographic location is greater than the building's earthquake-proofness level, then a second remote situational emergency measure **19** (different from the first remote situational emergency measure **19**) may be recommended. In addition, if the app associated with a particular PID **14** determines that the sensor data does not warrant an alarm, an all-clear message may be displayed on the device **14**.

(66) System **10** can be set up with double or triple redundancy, minimizing the risk of false alarms. This redundancy may be provided by having a redundant number of DAUs **16** and/or a redundant number of sensors **12**. As a non-limiting example, if two identical systems of DAUs **16** and sensors **12** are installed at a given location, the DAUs **16** can be interconnected such that the block **53** YES branch (FIG. 7) is only reached when both sensor/DAU systems detect a P-wave. If only one sensor/DAU system detects a P-wave, the event may be treated as a false positive and method **50** (FIG. 7) may exit block **53** via the NO branch. This redundancy may significantly improve the reliability of system **10**. DAU **16** may use the P-wave detection algorithm and S-wave prediction techniques associated with the ShakeAlarm® seismic detection products manufactured and sold by Weir-Jones Engineering of Vancouver, British Columbia, Canada.

(67) In some embodiments, system **10**, which is already connected to the internet **15** and/or other communication networks, may act as a monitor and/or message relay (e.g. through a mobile application on user computing devices **14**). This creates a very efficient mesh network with multiple channels of communications between parties. Messages can easily be monitored by emergency response teams and services can be prioritized based on real information from the affected zone. The application may be configured to prioritize data based on readings from the local sensors on the device **14**. Local device **14** sensors include, for example, GPS sensor and accelerometers. Local device **14** sensors may be configured to measure the device's proximity to the epicenter. The priority level given to the particular data may depend on the proximity of the device **14** used to transmit that particular data. For example, if the device's GPS sensor indicates that the device **14** is very close to the epicenter, the message transmitted from that particular device

14 may be given a high priority. Another example is that if the signal from the device's accelerometer reads high levels of shaking and motion and that the device's GPS sensor indicates that the device is very close to the epicenter, the message transmitted from that particular device **14** may be given an even higher priority. To reduce the risk of false alarms, messages may be sent with accompanying information generated by the DAUs **16** and/or device **14** sensors. For example, if a user transmits a message which indicates that he/she is trapped under earthquake rubble, but his/her device **14** sensors indicate that the user is far away from the epicenter, then the message may be tagged as a low priority since it is likely a false alarm.

(68) The application operating on devices **14** can be pre-programmed with an individual's emergency contact numbers. The device **14** can then inform the emergency contacts of the individual's condition and/or whereabouts through voice messaging, text messaging, email messaging, internet based instant messaging and/or the like. High priority and reliable data channels can be secured through prior agreements with network communication service providers, resulting in timely and efficient delivery of messages over highly congested networks.

(69) As discussed above, FIG. 6 schematically illustrates a non-limiting set of the software modules which are implemented processor **100** of DAU **16** according to an exemplary embodiment of the invention. The software modules illustrated in FIG. 6 include: data input module **154** which receives data from sensors **12**, formats the received data and passes the data to the circular memory buffer **156**; circular memory buffer **156** which stores received data and when the buffer becomes full, the oldest data is overwritten; real-time network feed **158** which transfers the data from circular memory buffer **156** to other network servers (not shown in FIG. 6) for further analysis if a network connection exists. Real-time network feed **158** may also receive alerts and events (e.g. remote situational emergency measures **19** or alerts which may be used to generate such situational emergency measured) from other servers and DAUs **16** if a network connection exists and may forward this information to other software modules; file writer **160** which takes data from circular memory buffer **156**, reformats the data and passes the data to the file format writer **162**; file format writer **162** which writes the data received from file writer **160** to a file on a memory (e.g. memory **104** (FIG. 4)) that is part of or otherwise accessible to DAU **16**; analysis module **164** which analyzes data from circular memory buffer **156** to determine if an event (P-wave or S-wave event) has occurred and the characteristics of any such event. If an event has occurred, event characteristics generated by analysis module **164** may be sent to alerting module **151**, notification module **152**, local emergency measures module **166** and reporting module **168**; reporting module **168** which handles any reporting and logging functions which may be configured for DAU **16**; local emergency measures module **166** which may determine local situational emergency measures **18** (e.g. on the basis of characteristics of events determined by analysis module **164** and any local situational which may be programmed into, or otherwise available to local emergency measures module **166**) and/or execute any local emergency measures **18** that local emergency measures module **166** may be programmed to implement. As discussed above, such local emergency measures **18** may comprise a wide variety of actions, such, such as turning on alarms, sending out specific messages to specific staff, turning off certain utilities, and/or the like; notification module **152** which may communicate event and status notifications through various notification channels, such as "push notifications" for smartphones **14** or similar PIDs **14**, live connections to a government-run Emergency Alerting System (EAS) and/or the like; alerting module **151** which may communicate alerts to other notification servers **51**, as discussed above; remote access module **170** which enables secure login of a network computer or server into DAU **16** for diagnostic and maintenance purposes; configuration module **172** which performs validation of the system configuration on boot-up; local access module **174** which receives inputs from local input devices, such as keypads, switches and tap sensors, and makes these inputs known to the other modules; logger **176** which may comprise a text file logging module that can be invoked by any module to store operational parameters, such as process parameters, times and OS events, in the

system log; and health monitor **178** which performs regular diagnostics on the system and reports back on the overall system health.

(70) Although the present system **10** is described for use in EEWS applications, system **10** is not limited to EEWS applications. System **10** can additionally or alternatively be used for any disaster warning applications by using appropriate sensor(s) **12** and suitable modification of the sensor data analysis algorithms. Such disasters may include, without limitation, tsunamis, tornados, cyclones, hurricanes, and floods. In addition to disaster warning applications, system **10** can also be used in any application where damage prevention actions and/or recommendations for local and remote situational emergency measures **18, 19** may be of benefit. Such applications include, but are not limited to remote security, pipeline monitoring, marine vehicle monitoring, bridge monitoring, rail monitoring, and mine geology monitoring.

(71) Embodiments of the invention may be implemented using specifically designed hardware, configurable hardware, programmable data processors (e.g. processor **100** and/or any other processors described herein) configured by the provision of software (which may optionally comprise “firmware”) capable of executing on the data processors, special purpose computers or data processors that are specifically programmed, configured, or constructed to perform one or more steps in a method and/or to provide the functionality as explained in detail herein and/or combinations of two or more of these. Examples of specifically designed hardware are: logic circuits, application-specific integrated circuits (“ASICs”), large scale integrated circuits (“LSIs”), very large scale integrated circuits (“VLSIs”), and the like. Examples of configurable hardware are: one or more programmable logic devices such as programmable array logic (“PALs”), programmable logic arrays (“PLAs”), and field programmable gate arrays (“FPGAs”). Examples of programmable data processors are: microprocessors, digital signal processors (“DSPs”), embedded processors, graphics processors, math co-processors, general purpose computers, server computers, cloud computers, mainframe computers, computer workstations, and the like. For example, one or more data processors in a control circuit for a device may implement methods and/or provide functionality as described herein by executing software instructions in a program memory accessible to the processors.

(72) While processes or blocks of some methods are presented herein in a given order, alternative examples may perform routines having steps, or employ systems having blocks, in a different order, and some processes or blocks may be deleted, moved, added, subdivided, combined, and/or modified to provide alternative or sub-combinations. Each of these processes or blocks may be implemented in a variety of different ways. Also, while processes or blocks are at times shown as being performed in series, these processes or blocks may instead be performed in parallel, or may be performed at different times. In addition, while elements are at times shown as being performed sequentially, they may instead be performed simultaneously or in different sequences. It is therefore intended that the following claims are interpreted to include all such variations as are within their intended scope.

(73) Software and other modules may reside on servers, workstations, personal computers, tablet computers, image data encoders, image data decoders, PDAs, media players, PIDs and other devices suitable for the purposes described herein. Those skilled in the relevant art will appreciate that aspects of the system can be practiced with other communications, data processing, or computer system configurations, including: internet appliances, hand-held devices (including personal digital assistants (PDAs)), wearable computers, all manner of cellular or mobile phones, multi-processor systems, microprocessor-based or programmable consumer electronics, network PCs, mini-computers, mainframe computers, and the like.

(74) Where a component (e.g. a software module, processor, assembly, device, circuit, etc.) is referred to above, unless otherwise indicated, reference to that component (including a reference to a “means”) should be interpreted as including as equivalents of that component any component which performs the function of the described component (i.e., that is functionally equivalent),

including components which are not structurally equivalent to the disclosed structure which performs the function in the illustrated exemplary embodiments of the invention.

(75) Specific examples of systems, methods and apparatus have been described herein for purposes of illustration. These are only examples. The technology provided herein can be applied to systems other than the example systems described above. While a number of exemplary aspects and embodiments have been discussed above, those of skill in the art will recognize certain modifications, permutations, additions and sub-combinations thereof. It is therefore intended that the following appended claims and claims hereafter introduced are interpreted to include all such modifications, permutations, additions and sub-combinations as are consistent with the broadest interpretation of the specification as a whole.

Claims

1. A seismic warning system comprising: a plurality of sensors, each sensor sensitive to a physical phenomenon associated with seismic events and operative to output an electronic signal representative of the sensed physical phenomenon; a data acquisition unit communicatively coupled to receive the electronic signal from each of the plurality of sensors, the data acquisition unit comprising a processor configured to determine that the received electronic signals are indicative of a P-wave associated with a seismic event and to estimate characteristics of the seismic event based on the received electronic signals; and a local device embodied separately from the data acquisition unit and communicatively coupled to the data acquisition unit; wherein the local device is configured to determine a situational state of industrial equipment at a specific location of the local device; wherein, after determining the situational state of industrial equipment, at least one of the processor and the local device are configured to determine local situational seismic emergency measures to be implemented by the local device based on the estimated characteristics of the seismic event and the situational state of the industrial equipment; and wherein the local device comprises an additional sensor for measuring one or more phenomena upon which the situational state of the industrial equipment is determined, the one or more phenomena independent of the physical phenomenon associated with seismic events.
2. The seismic warning system according to claim 1 wherein the additional sensor is located at the specific location of the local device.
3. The seismic warning system according to claim 1 wherein the additional sensor is part of the local device.
4. The seismic warning system according to claim 1 wherein the additional sensor is part of the industrial equipment.
5. The seismic warning system according to claim 1 wherein the additional sensor measures one or more phenomena associated with the industrial equipment.
6. The seismic warning system according to claim 1 wherein the additional sensor measures one or more phenomena associated with secondary industrial equipment which relies on the industrial equipment.
7. The seismic warning system according to claim 1 wherein the one or more phenomena comprise the presence or absence of workers within a threshold distance from the specific location of the local device.
8. The seismic warning system according to claim 1 wherein the one or more phenomena comprise the presence or absence of workers within a threshold distance from the industrial equipment.
9. The seismic warning system according to claim 1 wherein the local device comprises an embedded controller of the industrial equipment.
10. The seismic warning system according to claim 9 wherein the situational state of the industrial equipment is known to the embedded controller.
11. The seismic warning system according to claim 9 wherein the local situational seismic

emergency measures implemented by the local device comprise causing the embedded controller to assume emergency operational control of the industrial equipment.

12. The seismic warning system according to claim 9 wherein the local situational seismic emergency measures implemented by the local device comprise causing the embedded controller to implement an emergency operational shut-down of the industrial equipment.

13. The seismic warning system according to claim 1 wherein the local situational seismic emergency measures implemented by the local device comprise implementing an emergency shut-down of secondary industrial equipment.

14. The seismic warning system according to claim 1 wherein at least one of the processor and the local device are configured to determine the local situational seismic emergency measures to be implemented by the local device based on output from an additional sensor which measures one or more phenomena representative of damage caused by an S-wave of a seismic event.

15. The seismic warning system according to claim 1 wherein the estimated characteristics of the seismic event include an estimated epicenter of the seismic event and wherein the local situational seismic emergency measures implemented by the local device are based at least in part on a proximity of the local device to the estimated epicenter.

16. The seismic warning system according to claim 1 wherein the local device is part of the industrial equipment.

17. The seismic warning system according to claim 1 wherein at least one of the processor and the local device are configured to determine the local situational seismic emergency measures to be implemented by the local device based at least in part on a time when the local situational seismic emergency measures are determined.

18. A method for effecting situational emergency measures in response to detected seismic events, the method comprising: at each of a plurality of seismic sensors, detecting a physical phenomenon associated with seismic events and generating a corresponding electronic signal representative of the detected physical phenomenon; receiving, from each seismic sensor, the corresponding electronic signal at a data acquisition unit; determining, at the data acquisition unit, that the received electronic signals are indicative of a P-wave associated with a seismic event and computing, at the data acquisition unit, one or more estimated seismic event characteristics based on the received electronic signals; communicating the one or more estimated seismic event characteristics from the data processing unit to a local device embodied separately from the data acquisition unit; measuring, with an additional sensor, one or more phenomena independent of the physical phenomenon associated with the seismic event; determining, by the local device, a situational state of industrial equipment at a specific location of the local device based on at least the one or more measured phenomena independent of the physical phenomenon associated with the seismic event; and after determining the situational state, determining, by at least one of the data acquisition unit and the local device, local situational seismic emergency measures to be implemented by the local device based on the estimated characteristics of the seismic event and the situational state of the industrial equipment at the specific location of the local device.
