

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413646
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Tapse; Sandeep et al.

Methods and apparatus to facilitate meter to meter matching for media identification

Abstract

Example methods, apparatus, systems and articles of manufacture are disclosed to facilitate meter to meter matching for media identification. Example apparatus disclosed herein include an unknown signature comparer, a stack counter, and a reference database updater. The unknown signature comparer is to select a candidate unknown signature segment meeting a threshold length from a set of unknown signature segments collected at a first audience measurement location, and compare individual signatures of the candidate unknown signature segment with a collection of unknown signature segments collected at a second audience measurement location. The stack counter is to count a number of times that the candidate unknown signature segment matches unknown signature segments in the collection, and identify the candidate unknown signature segment as a matched signature segment when the number of times meets a counter threshold. The reference database updater is to store the matched signature segment in a signature reference database.

Inventors:	Tapse; Sandeep (Oldsmar, FL), Nelson; Daniel (Tampa, FL)
Applicant:	The Nielsen Company (US), LLC (New York, NY)
Family ID:	62712160
Assignee:	The Nielsen Company (US), LLC (New York, NY)
Appl. No.:	18/333524
Filed:	June 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240106909 A1	Mar. 28, 2024

Related U.S. Application Data

continuation parent-doc US 17723081 20220418 US 11785105 child-doc US 18333524
continuation parent-doc US 17027265 20200921 US 11310326 20220419 child-doc US 17723081
continuation parent-doc US 15399342 20170105 US 10785329 20200922 child-doc US 17027265

Publication Classification

Int. Cl.: H04L67/50 (20220101)

U.S. Cl.:

CPC H04L67/535 (20220501);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4739398	12/1987	Thomas	725/19	H04H 60/37
5481294	12/1995	Thomas et al.	N/A	N/A
5999689	12/1998	Iggulden	N/A	N/A
6574594	12/2002	Pitman et al.	N/A	N/A
6633651	12/2002	Hirzalla et al.	N/A	N/A
8094872	12/2011	Yagnik et al.	N/A	N/A
9256675	12/2015	Wiegering et al.	N/A	N/A
9277255	12/2015	Rowe	N/A	N/A
9294815	12/2015	McMillan	N/A	N/A
9497505	12/2015	Heffernan et al.	N/A	N/A
10009635	12/2017	Lee	N/A	N/A
10911824	12/2020	Tapse et al.	N/A	N/A
11356773	12/2021	Brunet et al.	N/A	N/A
2006/0153296	12/2005	Deng	N/A	N/A
2007/0106405	12/2006	Cook et al.	N/A	N/A
2007/0124756	12/2006	Covell	348/E7.071	G06F 16/635
2009/0089586	12/2008	Brunk	713/176	G06V 20/46
2010/0131970	12/2009	Falcon	725/19	H04H 60/56
2010/0263020	12/2009	Harrison	726/1	G06F 16/40
2011/0088053	12/2010	Lee	N/A	N/A
2012/0076310	12/2011	DeBusk	381/56	G10L 25/48
2012/0257116	12/2011	Hendrickson et al.	N/A	N/A
2013/0208942	12/2012	Davis	N/A	N/A
2014/0115626	12/2013	Sarda et al.	N/A	N/A
2014/0325555	12/2013	Khader et al.	N/A	N/A
2015/0254344	12/2014	Kulkarni et al.	N/A	N/A
2015/0289013	12/2014	Nelson	725/19	H04N 21/25891
2015/0319489	12/2014	McMillan	725/19	G06F 16/48

2016/0119672	12/2015	Alonso et al.	N/A	N/A
2016/0212495	12/2015	Chang et al.	N/A	N/A
2016/0232538	12/2015	Papakostas et al.	N/A	N/A
2016/0286266	12/2015	Moshitch	N/A	N/A
2016/0286285	12/2015	Geyzel et al.	N/A	N/A
2016/0366478	12/2015	Muller et al.	N/A	N/A
2016/0366492	12/2015	Muller et al.	N/A	N/A
2018/0191850	12/2017	Tapse et al.	N/A	N/A
2018/0278991	12/2017	Tapse et al.	N/A	N/A

OTHER PUBLICATIONS

Bachman, NielsenConnect to Measure ESPN's Multiple Platforms, Mediaweek, vol. 17, Issue 38, pp. 4 and 6, Oct. 22, 2007, 2 pages. cited by applicant

Gibbons, Nielsen's Numbers: Behind the Ratings Giant's Plans to Stay Ahead of Competitors, Viewing Shifts, Cover Story, Multichannel News, Sep. 2, 2013, pp. 10-11, 3 pages. cited by applicant

United States Patent and Trademark Office, Advisory Action, issued in connection with U.S. Appl. No. 16/180,992, dated Aug. 10, 2020, 5 pages. cited by applicant

United States Patent and Trademark Office, Final Office Action, issued in connection with U.S. Appl. No. 16/180,992, dated May 22, 2020, 21 pages. cited by applicant

United States Patent and Trademark Office, Non-Final Office Action, issued in connection with U.S. Appl. No. 16/180,992, dated Jan. 6, 2020, 20 pages. cited by applicant

United States Patent and Trademark Office, Non-Final Office Action, issued in connection with U.S. Appl. No. 17/164,828, dated Sep. 13, 2021, 31 pages. cited by applicant

United States Patent and Trademark Office, Non-Final Office Action, issued in connection with U.S. Appl. No. 17/833,565, dated Nov. 8, 2022, 35 pages. cited by applicant

Primary Examiner: Dollinger; Tonia L

Assistant Examiner: Rashid; Ishrat

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This patent is a continuation of U.S. patent application Ser. No. 17/723,081 (now U.S. Pat. No. 11,785,105), which was filed on Apr. 18, 2022, which is a continuation of U.S. patent application Ser. No. 17/027,265 (now U.S. Pat. No. 11,310,326), which was filed on Sep. 21, 2020, which is a continuation of U.S. patent application Ser. No. 15/399,342 (now U.S. Pat. No. 10,785,329), which was filed on Jan. 5, 2017. U.S. patent application Ser. No. 17/723,081; U.S. patent application Ser. No. 17/027,265; and U.S. patent application Ser. No. 15/399,342 are hereby incorporated herein by reference in their respective entireties. Priority to U.S. patent application Ser. No. 17/723,081; U.S. patent application Ser. No. 17/027,265; and U.S. patent application Ser. No. 15/399,342 is hereby claimed.

FIELD OF THE DISCLOSURE

(1) This disclosure relates generally to monitoring media presentation and/or consumption, and, more particularly, to methods and apparatus to facilitate meter to meter matching for media identification.

BACKGROUND

(2) In recent years, presentation of media to users has been monitored and measured through the

use of, for example, digital signatures for media identification. Media monitoring companies make reference signatures of identified media (e.g., television programs, music, audio broadcasts, internet videos, audio and/or visual advertisements, etc.), typically to develop a reference database. As unidentified media is presented to a user, a series of signatures of the unidentified media is made. The signatures of the unidentified media are then compared to the reference signatures. When the signatures of the unidentified media match one or more of the reference signatures, the unidentified media is identified.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of an example environment in which a measurement system implemented with a matcher constructed in accordance with the teachings of this disclosure operates to monitor media presentation.
- (2) FIG. 2 is a block diagram of an example implementation of the matcher of the example measurement system of FIG. 1.
- (3) FIG. 3 illustrates an example signature string that may be processed by the example matcher of FIGS. 1 and/or 2.
- (4) FIG. 4 illustrates an example set of signature segments that are matched by the example matcher of FIGS. 1 and/or 2.
- (5) FIG. 5 illustrates example signature segments matched by the example matcher of FIGS. 1 and/or 2.
- (6) FIG. 6 illustrates an example uniform resource locator (URL) matched to one of the matching example signature segments of FIG. 5 by the example matcher of FIGS. 1 and/or 2.
- (7) FIG. 7 is a flowchart representative of example machine-readable instructions that may be executed to implement the example matcher of FIGS. 1 and/or 2.
- (8) FIG. 8 is a flowchart representative of example machine-readable instructions that may be executed to implement block 715 of the example machine-readable instructions of FIG. 7.
- (9) FIG. 9 is a flowchart representative of example machine-readable instructions that may be executed to implement block 745 of the example machine-readable instructions of FIG. 7.
- (10) FIG. 10 is a flowchart representative of example machine-readable instructions that may be executed to implement block 755 of the example machine-readable instructions of FIG. 7.
- (11) FIG. 11 is a block diagram of an example processor platform capable of executing the instructions of FIGS. 7, 8, 9, and/or 10 to implement the example matcher of FIGS. 1 and/or 2.
- (12) The figures are not to scale. Instead, to clarify multiple layers and regions, the thickness of the layers may be enlarged in the drawings. Wherever possible, the same reference numbers will be used throughout the drawing(s) and accompanying written description to refer to the same or like parts. As used in this patent, stating that any part (e.g., a layer, film, area, or plate) is in any way positioned on (e.g., positioned on, located on, disposed on, or formed on, etc.) another part, means that the referenced part is either in contact with the other part, or that the referenced part is above the other part with one or more intermediate part(s) located therebetween. Stating that any part is in contact with another part means that there is no intermediate part between the two parts.

DETAILED DESCRIPTION

(13) Audience measurement companies desire to gain knowledge regarding how users interact with client devices (e.g., televisions, handheld mobile devices, smartphones, laptop computers, tablets, etc.). For example, monitoring companies want to monitor media (e.g., television programs, music, Internet videos, etc.) that is presented on the client devices to, among other things, monitor exposure to advertisements, determine advertisement effectiveness, determine user behavior, identify purchasing behavior associated with various demographics, credit media consumption

rates, etc. Some known systems have utilized meters coupled to client devices to generate digital signatures of the media that is presented on the client device. In some examples, the generated signatures are associated with respective timestamps of when the signatures were generated. The meter-generated signatures are then compared to a database of reference signatures to identify and thus monitor media being viewed and/or heard with the client device.

(14) Signature or fingerprint-based media monitoring techniques generally use one or more inherent characteristics of the monitored media during a monitoring time interval to generate a substantially unique proxy for the media. Such a proxy is referred to as a signature or fingerprint, and can take any form (e.g., a series of digital values, a waveform, etc.) representative of any aspect(s) of the media signal(s) (e.g., the audio and/or video signals forming the media presentation being monitored). A signature may be a series of signatures collected in series over a timer interval. A good signature is repeatable when processing the same media presentation, but is unique relative to other (e.g., different) presentations of other (e.g., different) media. Accordingly, the term “fingerprint” and “signature” are used interchangeably herein and are defined herein to mean a proxy for identifying media that is generated from one or more inherent characteristics of the media.

(15) Signature-based media monitoring generally involves determining (e.g., generating and/or collecting) signature(s) representative of a media signal (e.g., an audio signal and/or a video signal) output by a monitored media device and comparing the monitored signature(s) to one or more reference signatures corresponding to known (e.g., reference) media sources. Various comparison criteria, such as a cross-correlation value, a Hamming distance, etc., can be evaluated to determine whether a monitored signature matches a particular reference signature. When a match between the monitored signature and one of the reference signatures is found, the monitored media can be identified as corresponding to the particular reference media represented by the reference signature that with matched the monitored signature. Because attributes, such as an identifier of the media, a presentation time, a broadcast channel, etc., are collected for the reference signature, these attributes may then be associated with the monitored media whose monitored signature matched the reference signature. Example systems for identifying media based on codes and/or signatures are long known and were first disclosed in Thomas, U.S. Pat. No. 5,481,294, which is hereby incorporated by reference in its entirety.

(16) In some examples, a piece of media may not yet be represented by a reference signature in the reference database (e.g., a newly released song, a rare and/or old recording, a regional broadcast, user generated media, etc.). In some such examples, the media not yet represented by a reference signature in the reference database is referred to as unreferenced media. In some such examples, meter-generated signatures of the media presented on client devices will not match the reference signatures in the reference database (e.g., no corresponding reference signature will be present in the reference database to match the meter-generated signature). Further, in some examples, multiple meters respectively coupled to different client devices may generate signatures associated with the same unreferenced media that are separated in time with respect to the unreferenced media (e.g., a signature from the beginning of an unreferenced song made by a first meter and a signature from the end of the same unreferenced song made by a second meter). Thus, meter-generated signatures of unreferenced media may, in fact, correspond to the same piece of unreferenced media.

(17) Example systems, methods, and apparatus disclosed herein collect, analyze, collate, and associate signatures representative of unknown (e.g., unreferenced) media. In some examples, segments of unknown signatures are analyzed (e.g., compared, sorted, etc.) to locate matching individual signatures. In some such examples, the segments of unknown signatures having matching individual signatures are counted. In some such examples, the segments of unknown signatures having matching individual signatures are associated with a uniform resource locator (URL). In some such examples, the segments of unknown signatures are associated with a piece of media via information provided by the URL. Thus, in some examples, the media associated with

the segments of unknown signatures is identified and the segments of unknown signatures become known. In some examples, the collected signatures for unknown media and/or now-known signatures are added to the reference database.

(18) FIG. 1 is a block diagram of an example environment **110** in which a measurement system **112** implemented with a matcher **114** constructed in accordance with the teachings of this disclosure operates to monitor media presentation. The example environment **110** includes the measurement system **112**, a client device **116**, a network meter **118**, a signature generating meter **120**, a central facility **122**, and a network **124**. In the illustrated example of FIG. 1, the client device **116** is shown as a television, although further client devices are possible (e.g., smartphones, radios, computers, laptops, music players, disc readers, streaming media receivers, etc.) In some examples, the environment **110** includes a plurality of client devices **116**, network meters **118**, and signature generating meters **120**. According to the illustrated example, the measurement system **112**, the client device **116**, the network meter **118**, the signature generating meter **120**, and the central facility **122** are interconnected via the example network **124**. The example client device **116** is transmissibly coupled to the network meter **118** (e.g., wired, over Wi-Fi, over Bluetooth®, etc.). The example client device **116** is transmissibly coupled to the signature generating meter **120** (e.g., wired, over Wi-Fi, over Bluetooth®, etc.). The example client device **116** receives network distributed media detectable by the network meter **118** via the network **124**. The example measurement system **112** is housed at the central facility **122**. Alternatively, the example measurement system **112** may be housed at a remote location.

(19) The example signature generating meter **120** generates signatures of the media presented on the client device **116**. Based on the sampling rate of the example signature generating meter **120** and the length of time for which the media was presented, the signatures are generated as strings of individual signatures. For example, where the signature generating meter **120** has a sampling rate of three signatures per second and a piece of media is presented for one minute, a string of 180 individual signatures associated with the piece of media are produced in series. Further, the example signature generating meter **120** each generate the same signature strings for the same piece of presented media. For example, a first signature generating meter coupled to a first client device presenting a movie in Montana at 11:00 AM on a Saturday will generate the same (or substantially the same) signature string as a second signature generating meter coupled to a second client device presenting the same movie in Illinois at 8:00 PM on a Wednesday. Signature strings are to be explained in greater detail below in conjunction with FIGS. 3-6. The example signature generating meter **120** relays the signature strings to the example measurement system **112** via the example network **124**.

(20) The example measurement system **112** includes the example matcher **114**, an example incoming signature database **126**, an example reference database **128**, an example unknown signature database **130**, an example URL database **132**, and an example creditor **134**. The example client device **116**, the example network meter **118**, the example signature generating meter **120**, the example central facility **122**, the example incoming signature database **126**, the example reference database **128**, the example URL database **132**, and the example creditor **134** are communicatively interconnected via the example network **124**. The example matcher **114** is communicatively coupled to the example incoming signature database **126**, the example reference database **128**, the example unknown signature database **130**, the example URL database **132**, and to the example creditor **134**.

(21) In operation, when media is presented to users by the example client devices **116**, the example signature generating meters **120** generate signature strings of the media and relay the signature strings to the example incoming signature database **126** via the example network **124**. The example matcher **114** retrieves the signature strings from the incoming signature database **126** and attempts to match segments of the signature strings to a reference signature from the reference database **128**. Where a signature segment of a signature string matches a reference signature, the example

matcher **114** extracts the matching signature segment from the signature string. The example matcher **114** sends the matching signature segment to the example creditor **134** for crediting. (22) However, where a signature segment does not match a reference signature (e.g., because the media underpinning the signature string is not yet represented with a reference signature in the reference database **128**), the example matcher **114** deposits the unknown (e.g., unmatched) signature segment in the example unknown signature database **130**. As additional unknown signature segments are collected in the example unknown signature database **130**, the example matcher **114** retrieves unknown signature segments from the example unknown signature database **130** and attempts to stack (e.g., associate, connect, attach, etc.) matching unknown signature segments together and redeposits the stacked-together unknown signature segments in the example unknown signature database **130**. Thus, unknown signature segments originating from a single example signature generating meter **120** at different times and/or unknown signature segments originating from a plurality of example signature generating meters **120** are matched and associated together. Further features of the example matcher **114** related to stacking are described below with the aid of FIGS. 2-6.

(23) The example network meter **118** deposits URLs of media presented on the example client device **116** in the URL database **132**. The URLs provide identifying information of the presented media. When the number of stacked-together unknown signature segments reaches a threshold count (e.g., 5, 10, 15, etc.), the example matcher **114** attempts to match the stacked-together unknown signature segments to the URLs from the example URL database **132**. Thus, the media represented by the unknown signature segments is identified, as will be described in greater detail with the aid of FIGS. 2-6.

(24) The example matcher **114** sends the URL-matched stacked-together signature segments to the example creditor **134**. The example creditor **134** counts (e.g., credits) instances of matched signatures per piece of identified media within a specified time period (e.g., weekly, monthly, quarterly, etc.) and relays the count to the example central facility **122** via the example network **124**. The example matcher **114** sends the URL-matched signature segment to the example reference database **128** for storage as a reference signature, as will be described in greater detail with the aid of FIGS. 2-6.

(25) FIG. 2 is a block diagram of an example implementation of the matcher **114** of the example measurement system **112** of FIG. 1. The example matcher **114** includes an example reference comparer **212**, an example duration filter **214**, an example unknown signature comparer **216**, an example stack counter **218**, and an example reference database updater **220**.

(26) The example reference comparer **212** compares signature strings from the example incoming signature database **126** to reference signatures from the example reference database **128**. Where the example reference comparer **212** matches a segment of a signature string from the example incoming signature database **126** with a reference signature, the reference comparer **212** extracts the matched signature segment from the signature string. The example reference comparer **212** sends the matched signature segment to the example creditor **134**. Thus, unknown signature segments (e.g., segments of signature strings unmatched to a reference signature) are leftover. The example reference comparer **212** sends the unknown signature segments to the example duration filter **214**.

(27) The example duration filter **214** analyzes the unknown signature segments based on a threshold length (e.g., a number of individual signatures, a time duration, etc.). The example duration filter **214** discards unknown signature segments that do not meet the threshold length. The example duration filter **214** sends unknown signature segments meeting the threshold length to the example unknown signature database **130**, as will be described in FIGS. 3-5. Thus, the example duration filter **214** acts as a high-pass filter for the unknown signature segments.

(28) The example unknown signature comparer **216** retrieves and analyzes the individual signatures of the unknown signature segments from the example unknown signature database **130** to search

for matching individual unknown signatures common to the unknown signature segments. When unknown signature segments having matching individual unknown signatures are found, the example unknown signature comparer **216** stacks (e.g., associates, connects, attaches, etc.) the unknown signature segments together at the matching individual unknown signatures and sends the unknown signature segments to the example stack counter **218**, as will be described in further detail below in conjunction with FIGS. 3-5.

(29) The example stack counter **218** counts the number of matched stacked unknown signature segments from the example unknown signature comparer **216**. When the example stack counter **218** determines that the stacked-together unknown signature segments do not meet the threshold count described above, the stack counter **218** redeposits the stacked-together unknown signature segments in the example unknown signature database **130**. When the example stack counter **218** determines that the stacked-together unknown signature segments meet the threshold count, the stack counter **218** sends the stacked-together unknown signature segments to the example reference database updater **220**. The example reference database updater **220** retrieves URLs from the example URL database **132**. The example reference database updater **220** compares timestamps of the individual signatures of the stacked-together unknown signature segments to timestamps of the retrieved URLs, as will be explained in greater detail in conjunction with FIG. 6.

(30) Where the example reference database updater **220** finds matching timestamps (e.g., timestamps that indicate the same, or substantially the same, time of day and/or date) between a URL and an individual signature, the reference database updater **220** associates the unknown signature segment of the timestamp-matched individual signature with media-identifying information of the URL. The example reference database updater **220** further associates the remaining stacked-together unknown signature segments with the media identifying information. The example reference database updater **220** sends the media-identified stacked-together signature segments to the example creditor **134**. The example reference database updater **220** sends one of the media-identified signature segments to the example reference database **128** for storage as a reference signature (e.g., the reference database **128** holds singular examples of signature segments as reference signatures).

(31) Where the example reference database updater **220** does not find matching timestamps between a URL and an individual signature, the reference database updater **220** returns the stacked-together unknown signature segments to the example stack counter **218**. In some such examples, the example stack counter **218** returns the stacked-together unknown signature segments to the example unknown signature database **130** as a stacked-together unknown signature segment bundle. The example stack counter **218** periodically (e.g., daily, weekly, monthly, quarterly, etc.) retrieves and sends the stacked-together unknown signature segment bundles from the example unknown signature database **130** to the example reference database updater **220** for a URL-matching reattempt.

(32) FIG. 3 illustrates an example signature string that may be processed by the example matcher **114** of FIGS. 1 and/or 2. In the illustrated example of FIG. 3, signature string **312** is generated by the signature generating meter **120** of FIG. 1. In the illustrated example of FIG. 3, the signature string **312** is composed of a series of individual signatures **314**. The example individual signatures each include a value (e.g., a hexadecimal number, a binary number, an integer, an identifier, a letter, etc.) associated with a signature timestamp. For example, the individual signature **314** with value **316** “2F0” is associated with the signature timestamp **318** “07/15/2016-14:16:16” (e.g., the example signature generating meter **120** of FIG. 1 generated value **316** “2F0” at 2:16:16 PM on Jul. 15, 2016). In the illustrated example of FIG. 3, reference signatures **320a**, **320b** are generated at the example central facility **122** of FIG. 1 and stored in the example reference database **128** of FIG. 1. Reference signatures are composed of a series of the values (e.g., “2E1,” “2F1,” “2F2,” “2F3”). As the example reference signatures are used as a reference, they do not include signature timestamps. Alternatively, the reference signatures may be associated with a timestamp (e.g., reference

signatures associated with live television, broadcast media, etc. may be associated with timestamps).

(33) In operation, the example reference comparer **212** of FIG. 2 searches for known signature segments by comparing the signature string **312** to the reference signatures. The example reference comparer **212** of FIG. 2 searches for matching ordered values between the reference signature and the signature string. In the illustrated example of FIG. 3, reference signature **320a** and the signature string **312** both include values “2E1,” “2F1,” “2F2,” and “2F3” in the same order “2E1, 2F1, 2F2, 2F3.” In the illustrated example of FIG. 3, reference signature **320b** and the signature string **312** both include values “2EE,” “2EF,” and “2FO” in the same order “2EE, 2EF, 2FO.” In operation, the example reference comparer **212** of FIG. 2 removes (e.g., cuts away, extracts, snips, excises, discards, etc.) the known signature segments from the signature string (e.g., removes known signature segments for the signature string to leave unknown signature segments). For example, the example reference comparer **212** of FIG. 2 removes known signature segments **322a**, **322b** from the signature string **312**. The example reference comparer **212** of FIG. 2 sends the removed known signature segments to the creditor **134** of FIG. 1 to credit presentation, exposure, etc. of the known media.

(34) After the known signature segments are removed from the signature string, an unknown signature segment remains (e.g., is leftover, persists, etc.). In the illustrated example of FIG. 3, after known signature segments **322a**, **322b** are removed from the signature string **312**, the unknown signature segment **324** remains. The example reference comparer **212** of FIG. 2 sends the unknown signature segment **324** to the example duration filter **214** of FIG. 2.

(35) The example duration filter **214** of FIG. 2 filters unknown signature segments based on a threshold length (e.g., 7 individual signatures, 30 seconds, etc.). In operation, the example duration filter **214** of FIG. 2 discards unknown signature segments shorter than the threshold length and sends unknown signature segments meeting the threshold length to the example unknown signature database **130** of FIG. 1. In the illustrated example of FIG. 3, given an example threshold length of 7 individual signatures, the example unknown signature segment **324** exceeds the threshold length and would thus be sent by the example duration filter **214** of FIG. 2 to the unknown signature database **130** of FIG. 1.

(36) FIG. 4 illustrates an example set of signature segments that are matched by the example matcher **114** of FIGS. 1 and/or 2. In operation, the example unknown signature comparer **216** of FIG. 2 retrieves a candidate unknown signature segment (e.g., the example unknown signature segment **324** of FIG. 3) and a comparison unknown signature segment from the example unknown signature database **130** of FIG. 1. The comparison unknown signature segment is composed of a series of individual signatures, each having a value and an associated signature timestamp. In the illustrated example of FIG. 4, the example unknown signature retriever **216** of FIG. 2 has retrieved unknown signature segment **324** of FIG. 3 as candidate unknown signature segment **412** and comparison unknown signature segment **414** from the example unknown signature database **130** of FIG. 1.

(37) The example unknown signature comparer **216** aligns a match portion **416** of the candidate unknown signature segment **412** meeting a match threshold (e.g., 7 individual signatures, etc.) with the earliest individual signatures of the comparison unknown signature segment **414** meeting the match threshold. In some examples, the threshold length and the match threshold are equal in length. In operation, the example unknown signature comparer **216** of FIG. 2 then determines whether the values of the aligned individual signatures match. In operation, when the values of the aligned individual signatures do not match, as denoted by crossed lines **418** in FIG. 4, the example unknown signature comparer **216** of FIG. 2 advances the candidate unknown signature segment **412** along the comparison unknown signature segment **414** by one individual signature, as denoted by advancement arrow **420**, and repeats the aligned individual signature value matching determination. In operation, the unknown signature comparer **216** of FIG. 2 repeats this advancing

and determining process, as denoted by transition arrow **422** in FIG. 4, until matching values between aligned individual signatures meeting the match threshold are found, as denoted by double-arrowed lines **424**. In operation, the example unknown signature comparer **216** of FIG. 2 then stacks the candidate and comparison unknown signature segments **412**, **414** together at the matching values, as will be explained greater detail in conjunction with FIG. 5.

(38) In operation, when matching values between the candidate unknown signature segment and the comparison unknown signature segment meeting the match threshold are not found, the example unknown signature comparer **216** of FIG. 2 returns the comparison unknown signature segment to the example unknown signature database **130** of FIG. 1 and selects a further comparison unknown signature segment to continue the comparison process. In operation, when the example unknown signature database **130** of FIG. 1 has been exhausted of comparison unknown signature segments, the example unknown signature comparer **216** of FIG. 2 returns the candidate unknown signature segment to the example unknown signature database **130** of FIG. 1 and selects a further candidate unknown signature segment to continue the comparison process.

(39) FIG. 5 illustrates example signature segments matched by the example matcher **114** of FIGS. 1 and/or 2. In operation, as the example unknown signature comparer **216** of FIG. 2 matches and stacks unknown signature segments, the example stack counter **218** of FIG. 2 counts the number of matched stacked unknown signature segments. In the illustrated example of FIG. 5, because five unknown signature segments **512a**, **512b**, **512c**, **512d**, **512e** include values “2CB,” “45D,” “26F,” “4CA,” “4C5,” “910,” and “1BF” in the order “2CB, 45D, 26F, 4CA, 4C5, 910, 1BF,” the example stack counter **218** of FIG. 2 counts five matched stacked unknown signature segments. In operation, when the number of matched stacked unknown signature segments meets a count threshold (e.g., five matched stacked unknown signature segments), the example stack counter **218** of FIG. 2 extracts a match core. The match core includes the individual signatures across which the unknown signature segments are stacked (e.g., the match core is composed of the portions of the unknown signature segments that have matching ordered values). In the illustrated example of FIG. 5, the match core **514** includes the individual signatures of unknown signature segments **512a**, **512b**, **512c**, **512d**, **512e** that have ordered values “2CB, 45D, 26F, 4CA, 4C5, 910, 1BF,” as denoted by the double-arrowed lines **424** of FIG. 4. The example stack counter **218** of FIG. 2 sends the match core to the example reference database updater **220** of FIG. 2.

(40) FIG. 6 illustrates an example uniform resource locator (URL) matched to an unknown signature segment by the example matcher **114** of FIGS. 1 and/or 2. The URL is generated by the example network meter **118** of FIG. 1 based on online activity by a user and stored in the example URL database **132**. The URL is associated with a network timestamp, a media title, and a media provider. In the illustrated example of FIG. 6, the URL **612**

“www.wechute.com/video=895783939” is associated with the network timestamp **614** “07/08/2016-18:43:23,” the media title **616** “Super Silly Catz!,” and the media provider **618** “Kittyfan5000.” In operation, the example reference database updater **220** of FIG. 2 retrieves the associated URL, network timestamp, media title, and media provider from the example URL database **132** of FIG. 1. In operation, to correlate the match core to the URL, the example reference database updater **220** then compares the network timestamp with the signature timestamps of the match core. In operation, when the example reference database updater **220** of FIG. 2 matches the network timestamp with one of the signature timestamps, the reference database updater **220** associates the unknown signature segment of the network timestamp-matching signature timestamp with the URL, the media title and the media provider, as denoted in FIG. 6 by association arrow **620**. In operation, the example reference database updater **220** of FIG. 2 associates the remaining unknown signature segments of the match core with the URL, the media title, and the media provider via the unknown signature segment that has the network timestamp-matching signature timestamp as denoted by double-arrowed lines **424**. In the illustrated example of FIG. 6, the unknown signature segment **512c** of FIG. 5 including signature timestamp **622** “07/08/2016-

18:43:23" is associated with URL **612** "www.wechute.com/video=895783939," media title **616** "Super Silly Catz!," and media provider **618** "Kittyfan5000" via the network timestamp **614** "07/08/2016-18:43:23." In the illustrated example of FIG. **6**, the example reference database updater **220** of FIG. **2** associates the remaining unknown signature segments **512a**, **512b**, **512d**, **512e** of the match core **514** with the URL **612** "www.wechute.com/video=895783939," the media title **616** "Super Silly Catz!," and the media provider **618** "Kittyfan5000" via the unknown signature segment **512c** that has signature timestamp **622** "07/08/2016-18:43:23." Thus, unknown signature segments of the match core are identified as representative of the media of the media title. (41) In operation, the example reference database updater **220** of FIG. **2** sends the match core to the example creditor **134** of FIG. **1** which credits presentation views to the media of media title according to the number of now-known signature segments in the match core. In operation, the example reference database updater **220** of FIG. **2** updates the example reference database **128** of FIG. **1** with the ordered values of the now-known signature segments and the associated media title and media provider. In the illustrated example of FIG. **6**, the ordered values "2CB, 45D, 26F, 4CA, 4C5, 910, 1BF" shared by the unknown signature segments **512a**, **512b**, **512c**, **512d**, **512e** and the associated media title **616** and media provider **618** are added to the reference database **128** by the reference updater **220**. Thus, in some examples, unknown signature segments are transformed into reference signatures.

(42) While an example manner of implementing the example matcher **114** of FIG. **1** is illustrated in FIG. **2**, one or more of the elements, processes and/or devices illustrated in FIG. **2** may be combined, divided, re-arranged, omitted, eliminated and/or implemented in any other way. Further, the example reference comparer **212**, the example duration filter **214**, the example unknown signature comparer **216**, the example stack counter **218**, the example reference database updater **220** and/or, more generally, the example matcher **114** of FIGS. **1-2** may be implemented by hardware, software, firmware and/or any combination of hardware, software and/or firmware. Thus, for example, any of the example reference comparer **212**, the example duration filter **214**, the example unknown signature comparer **216**, the example stack counter **218**, the example reference database updater **220** and/or, more generally, the example matcher **114** could be implemented by one or more analog or digital circuit(s), logic circuits, programmable processor(s), application specific integrated circuit(s) (ASIC(s)), programmable logic device(s) (PLD(s)) and/or field programmable logic device(s) (FPLD(s)). When reading any of the apparatus or system claims of this patent to cover a purely software and/or firmware implementation, at least one of the example matcher **114**, the example reference comparer **212**, the example duration filter **214**, the example unknown signature comparer **216**, the example stack counter **218** and/or the example reference database updater **220** is/are hereby expressly defined to include a tangible computer readable storage device or storage disk such as a memory, a digital versatile disk (DVD), a compact disk (CD), a Blu-ray disk, etc. storing the software and/or firmware. Further still, the example matcher **114** of FIGS. **1** and/or **2** may include one or more elements, processes and/or devices in addition to, or instead of, those illustrated in FIG. **2**, and/or may include more than one of any or all of the illustrated elements, processes and devices.

(43) Flowcharts representative of example machine readable instructions for implementing the example matcher **114** of FIGS. **1** and/or **2** are shown in FIGS. **7-10**. In this example, the machine readable instructions comprise a program(s) for execution by a processor such as the processor **1112** shown in the example processor platform **1100** discussed below in connection with FIG. **11**. The program may be embodied in software stored on a tangible computer readable storage medium such as a CD-ROM, a floppy disk, a hard drive, a digital versatile disk (DVD), a Blu-ray disk, or a memory associated with the processor **1112**, but the entire program(s) and/or parts thereof could alternatively be executed by a device other than the processor **1112** and/or embodied in firmware or dedicated hardware. Further, although the example program(s) is described with reference to the flowcharts illustrated in FIGS. **7-10**, many other methods of implementing the example matcher

114 may alternatively be used. For example, the order of execution of the blocks may be changed, and/or some of the blocks described may be changed, eliminated, or combined.

(44) As mentioned above, the example processes of FIGS. **7-10** may be implemented using coded instructions (e.g., computer and/or machine readable instructions) stored on a tangible computer readable storage medium such as a hard disk drive, a flash memory, a read-only memory (ROM), a compact disk (CD), a digital versatile disk (DVD), a cache, a random-access memory (RAM) and/or any other storage device or storage disk in which information is stored for any duration (e.g., for extended time periods, permanently, for brief instances, for temporarily buffering, and/or for caching of the information). As used herein, the term tangible computer readable storage medium is expressly defined to include any type of computer readable storage device and/or storage disk and to exclude propagating signals and to exclude transmission media. As used herein, “tangible computer readable storage medium” and “tangible machine readable storage medium” are used interchangeably. Additionally or alternatively, the example processes of FIGS. **7-10** may be implemented using coded instructions (e.g., computer and/or machine readable instructions) stored on a non-transitory computer and/or machine readable medium such as a hard disk drive, a flash memory, a read-only memory, a compact disk, a digital versatile disk, a cache, a random-access memory and/or any other storage device or storage disk in which information is stored for any duration (e.g., for extended time periods, permanently, for brief instances, for temporarily buffering, and/or for caching of the information). As used herein, the term non-transitory computer readable medium is expressly defined to include any type of computer readable storage device and/or storage disk and to exclude propagating signals and to exclude transmission media. As used herein, when the phrase “at least” is used as the transition term in a preamble of a claim, it is open-ended in the same manner as the term “comprising” is open ended.

(45) FIG. **7** is a flowchart representative of example machine-readable instructions **710** that may be executed to implement the example matcher **114** of FIGS. **1** and/or **2**. The example instructions **710** may be performed, for example, to match unknown signature segments together to identify unknown presented media.

(46) To start, the example matcher **114** determines eligible unknown signature segments (e.g., signatures that are not identified in a reference database and meet a threshold length) for analysis, as will be described in greater detail in connection with FIG. **8** (block **715**). Next, the example unknown signature comparer **216** of the example matcher **114** selects a candidate unknown signature segment from the unknown signature database **130** of the example measurement system **112** (block **720**). The example unknown signature comparer **216** further selects a match portion of the candidate unknown signature segment (block **725**). The example unknown signature comparer **216** further selects a comparison unknown signature segment from the unknown signature database **130** (block **730**). The example unknown signature comparer **216** then aligns the match portion with the comparison unknown signature segment (block **735**). The example unknown signature comparer **216** then compares the match portion and the comparison unknown signature segment to determine whether the individual signatures of the match portion match the individual signatures of the comparison unknown signature segment aligned with the match portion (block **740**).

(47) If the individual signatures of the match portion match the individual signatures of the comparison unknown signature segment aligned with the match portion, the example unknown signature comparer **216** stacks the matching signature segments at the matching individual signatures, as will be described in greater detail in connection with FIG. **9** (block **745**). Next, the example stack counter **218** of the example matcher **114** determines whether the number of matching unknown signature segments meets the count threshold (block **750**). If the number of matching unknown signature segments does not meet the count threshold, the instructions **710** return to block **730**.

(48) If the number of matching unknown signature segments meets the count threshold, the example reference database updater **220** of the example matcher **114** builds a reference signature

from the matching unknown signature segments, as will be described in greater detail in connection with FIG. 10, (block 755) and the instructions 710 end.

(49) Referring back to block 740, if the individual signatures of the match portion do not match the individual signatures of the comparison unknown signature segment aligned with the match portion, the example unknown signature comparer 216 determines whether the match portion is at the latest-in-time end of the comparison unknown signature segment (block 760). If the match portion is not at the latest-in-time end of the comparison unknown signature segment, the example unknown signature comparer 216 advances the candidate unknown signature segment along the comparison unknown signature segment (block 765) and the instructions 710 return to block 740. If the match portion is at the latest-in-time end of the comparison unknown signature segment, the example unknown signature comparer 216 determines whether additional unanalyzed unknown signature segments are available for comparison (block 770).

(50) If additional unanalyzed unknown signature segments are available for comparison, the instructions 710 return to block 730. If additional unanalyzed unknown signature segments are not available for comparison, the example unknown signature comparer 216 determines whether the match portion is at the earliest-in-time end of the candidate unknown signature segment (block 775).

(51) If the match portion is not at the earliest-in-time end of the candidate unknown signature segment, the instructions 710 return to block 725. If the match portion is at the earliest-in-time end of the candidate unknown signature segment, the example unknown signature comparer 216 determines whether further unanalyzed unknown signature segments are available for examination as candidate unknown signature segments (block 780).

(52) If further unanalyzed unknown signature segments are available for examination as candidate unknown signature segments, the instructions 710 return to block 720. If further unanalyzed unknown signature segments are not available for examination as candidate unknown signature segments, the instructions 710 return to block 715

(53) FIG. 8 is a flowchart representative of example machine-readable instructions that may be executed to implement block 715 of the example machine-readable instructions of FIG. 7.

(54) To determine eligible unknown signature segments, the example reference comparer 212 of FIG. 2 of the example matcher 114 of FIGS. 1 and 2 retrieves incoming signature strings from the example incoming signature database 126 of the example measurement system 112 of FIG. 1 collected from the example signature generating meters 120 of FIG. 1 (block 815). Next, the example reference comparer 212 removes signature segments from the signature strings that match reference signatures stored in the example reference database 128 of the example measurement system 112 from unknown signature segments (block 820). Then, the example creditor 134 of FIG. 2 of the example measurement system 112 of FIG. 1 credits media according to the reference matched signature segments (block 825). Further, the example duration filter 214 of FIG. 2 of the example matcher 114 discards unknown signature segments that do not meet a threshold length and stores unknown signature segments meeting the length threshold in the example unknown signature database 130 (block 830). The instructions 715 of FIG. 8 end and control returns to block 720 of FIG. 7.

(55) FIG. 9 is a flowchart representative of example machine-readable instructions that may be executed to implement block 745 of the example machine-readable instructions of FIG. 7.

(56) To stack matching unknown signature segments, the example unknown signature comparer 216 determines whether additional individual signatures of the candidate unknown signature segment and the comparison unknown signature segment match (block 915).

(57) If additional individual signatures of the candidate unknown signature segment and the comparison unknown signature segment match, the example unknown signature comparer 216 logs the additional matches (block 920). Next, the example unknown signature comparer 216 associates the candidate unknown signature segment and the comparison unknown segment at the matching

individual signatures (block **925**). The instructions **745** of FIG. **9** end and control returns to block **750** of FIG. **7**.

(58) If additional individual signatures of the candidate unknown signature segment and the comparison unknown signature segment do not match, the instructions **710** progress to block **925**.

(59) FIG. **10** is a flowchart representative of example machine-readable instructions that may be executed to implement block **755** of the example machine-readable instructions of FIG. **7**.

(60) To build a reference signature from the stacked unknown signature segments, the example reference database updater **220** correlates the stacked unknown signature segments to a URL from the URL database **132** via a signature timestamp of the stacked unknown signature segments and a network timestamp associated with the URL (block **1015**). Then, the example reference database updater **220** identifies the media represented by the unknown signature segment is from the URL (block **1020**). Further, the example reference database updater **220** updates the example reference database **128** with the now-known signature segment as a reference signature (block **1025**). The instructions **755** of FIG. **10** then end.

(61) FIG. **11** is a block diagram of an example processor platform **1100** capable of executing the instructions of FIGS. **7-10** to implement the matcher **114** of FIG. **1** and/or FIG. **2**. The processor platform **1100** can be, for example, a server, a personal computer, a mobile device (e.g., a cell phone, a smart phone, a tablet such as an iPad®), a personal digital assistant (PDA), an Internet appliance, a DVD player, a CD player, a digital video recorder, a Blu-ray player, a gaming console, a personal video recorder, a set top box, or any other type of computing device.

(62) The processor platform **1100** of the illustrated example includes a processor **1112**. The processor **1112** of the illustrated example is hardware. For example, the processor **1112** can be implemented by one or more integrated circuits, logic circuits, microprocessors or controllers from any desired family or manufacturer.

(63) The processor **1112** of the illustrated example includes a local memory **1113** (e.g., a cache) and the matcher **114** including the reference comparer **212**, the duration filter **214**, the unknown signature comparer **216**, the stack counter **218**, and the reference database updater **220**. The processor **1112** of the illustrated example is in communication with a main memory including a volatile memory **1114** and a non-volatile memory **1116** via a bus **1118**. The volatile memory **1114** may be implemented by Synchronous Dynamic Random Access Memory (SDRAM), Dynamic Random Access Memory (DRAM), RAMBUS Dynamic Random Access Memory (RDRAM) and/or any other type of random access memory device. The non-volatile memory **1116** may be implemented by flash memory and/or any other desired type of memory device. Access to the main memory **1114**, **1116** is controlled by a memory controller.

(64) The processor platform **1100** of the illustrated example also includes an interface circuit **1120**. The interface circuit **1120** may be implemented by any type of interface standard, such as an Ethernet interface, a universal serial bus (USB), and/or a PCI express interface.

(65) In the illustrated example, one or more input devices **1122** are connected to the interface circuit **1120**. The input device(s) **1122** permit(s) a user to enter data and commands into the processor **1112**. The input device(s) **1122** can be implemented by, for example, an audio sensor, a microphone, a camera (still or video), a keyboard, a button, a mouse, a touchscreen, a track-pad, a trackball, isopoint and/or a voice recognition system.

(66) One or more output devices **1124** are also connected to the interface circuit **1120** of the illustrated example. The output devices **1124** can be implemented, for example, by display devices (e.g., a light emitting diode (LED), an organic light emitting diode (OLED), a liquid crystal display, a cathode ray tube display (CRT), a touchscreen, a tactile output device, a light emitting diode (LED), a printer and/or speakers). The interface circuit **1120** of the illustrated example, thus, typically includes a graphics driver card, a graphics driver chip or a graphics driver processor.

(67) The interface circuit **1120** of the illustrated example also includes a communication device such as a transmitter, a receiver, a transceiver, a modem and/or network interface card to facilitate

exchange of data with external machines (e.g., computing devices of any kind) via a network **1126** (e.g., an Ethernet connection, a digital subscriber line (DSL), a telephone line, coaxial cable, a cellular telephone system, etc.).

(68) The processor platform **1100** of the illustrated example also includes one or more mass storage devices **1128** for storing software and/or data. Examples of such mass storage devices **1128** include floppy disk drives, hard drive disks, compact disk drives, Blu-ray disk drives, RAID systems, and digital versatile disk (DVD) drives.

(69) The coded instructions **1132** of FIGS. 7-10 may be stored in the mass storage device **1128**, in the volatile memory **1114**, in the non-volatile memory **1116**, and/or on a removable tangible computer readable storage medium such as a CD or DVD.

(70) From the foregoing, it will be appreciated that the above disclosed methods, apparatus and articles of manufacture may aid in identifying, analyzing, comparing, and understanding media and when that media is presented. By associating signatures representative of a piece of unknown (e.g., unreferenced) media from multiple signature generating meters together to form a match core, the unknown media may be more quickly identified, which in turn may provide insights into the preferences and habits of media consumers. Further, comparing signature timestamps of a match core to a network timestamp associated with a URL may be accomplished in fewer operations by a processor, thus reducing processor demand in a computer, as compared to comparing the signature timestamps of each individual unknown signature to the network timestamp piecemeal. Moreover, identifying an unknown signature segment via a URL may make reference signature generation more efficient. Learning about audio media consumers' preferences and habits may help media broadcasters to provide media (e.g., music, movies, television programs, etc.) that media consumers want to hear and to additionally deliver targeted advertisements for products that may interest media consumers.

(71) Although certain example methods, apparatus and articles of manufacture have been disclosed herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all methods, apparatus and articles of manufacture fairly falling within the scope of the claims of this patent.

Claims

1. An audience measurement system comprising: at least one processor; and a non-transitory computer-readable storage medium having stored therein instructions that, upon execution by the at least one processor, cause the audience measurement system to perform a set of operations comprising: obtaining, from a first meter at a first audience measurement location, a first set of unknown signature segments; obtaining, from one or more second meters at one or more respective second audience measurement locations, a second set of unknown signature segments; selecting a candidate unknown signature segment from the first set of unknown signature segments, wherein the candidate unknown signature segment meets a threshold length; comparing individual signatures of the candidate unknown signature segment with individual signatures of one or more unknown signature segments from the second set of unknown signature segments; counting a number of times that the individual signatures of the candidate unknown signature segment matches the individual signatures of the unknown signature segments in the second set of unknown signature segments; determining that the candidate unknown signature segment is a matched signature segment when the number of times meets a counter threshold; and in response to a determination that the candidate unknown signature segment is a matched signature segment: identifying, based on online activity associated with the first audience measurement location, media identifying information associated with the matched signature segment; and storing the matched signature segment in association with the media identifying information in a signature reference database as a reference signature.

2. The audience measurement system of claim 1, wherein the set of operations further comprise discarding unknown signature segments collected at the first audience measurement location that do not meet the threshold length.
3. The audience measurement system of claim 1, wherein the media identifying information corresponds to media accessed at the first audience measurement location.
4. The audience measurement system of claim 3, wherein the identifying, based on the online activity associated with the first audience measurement location, the media identifying information comprises: comparing: (i) timestamps of online activity indicative of accessing the media at the first audience measurement location and (ii) timestamps associated with the candidate unknown signature segment; and based on the comparing, correlating the online activity indicative of accessing the media with the candidate unknown signature segment.
5. The audience measurement system of claim 1, wherein the identifying, based on the online activity associated with the first audience measurement location, the media identifying information further comprises identifying the media identifying information based on a uniform resource locator indicative of accessing media associated with the media identifying information at the first audience measurement location.
6. The audience measurement system of claim 5, wherein the storing the matched signature segment in the signature reference database further comprises: updating the signature reference database to associate the matched signature segment with the media identifying information based on the uniform resource locator.
7. The audience measurement system of claim 1, wherein the set of operations further comprise crediting media exposure to media corresponding to the matched signature segment based on an additional unknown signature matching at least a portion of the matched signature segment.
8. A non-transitory computer-readable storage medium comprising instructions that, when executed by at least one processor, cause performance of a set of operations comprising: obtaining, from a first meter at a first audience measurement location, a first set of unknown signature segments; obtaining, from one or more second meters at one or more respective second audience measurement locations, a second set of unknown signature segments; selecting a candidate unknown signature segment from the first set of unknown signature segments, wherein the candidate unknown signature segment meets a threshold length; comparing individual signatures of the candidate unknown signature segment with individual signatures of one or more unknown signature segments from the second set of unknown signature segments; counting a number of times that the individual signatures of the candidate unknown signature segment matches the individual signatures of the unknown signature segments in the second set of unknown signature segments; determining that the candidate unknown signature segment is a matched signature segment when the number of times meets a counter threshold; and in response to a determination that the candidate unknown signature segment is a matched signature segment: identifying, based on online activity associated with the first audience measurement location, media identifying information associated with the matched signature segment; and storing the matched signature segment in association with the media identifying information in a signature reference database as a reference signature.
9. The non-transitory computer-readable storage medium of claim 8, wherein the set of operations further comprise discarding unknown signature segments collected at the first audience measurement location that do not meet the threshold length.
10. The non-transitory computer-readable storage medium of claim 8, wherein the media identifying information corresponds to media accessed at the first audience measurement location.
11. The non-transitory computer-readable storage medium of claim 10, wherein the identifying, based on the online activity associated with the first audience measurement location, the media identifying information further comprises: comparing: (i) timestamps of online activity indicative of accessing the media at the first audience measurement location and (ii) timestamps associated

with the candidate unknown signature segment; and based on the comparing, correlating the online activity indicative of accessing the media with the candidate unknown signature segment.

12. The non-transitory computer-readable storage medium of claim 8, wherein the identifying, based on the online activity associated with the first audience measurement location, the media identifying information further comprises identifying the media identifying information based on a uniform resource locator indicative of accessing media associated with the media identifying information at the first audience measurement location.

13. The non-transitory computer-readable storage medium of claim 8, wherein the set of operations further comprise crediting media exposure to media corresponding to the matched signature segment based on an additional unknown signature matching at least a portion of the matched signature segment.

14. A method comprising: obtaining, from a first meter at a first audience measurement location, a first set of unknown signature segments; obtaining, from one or more second meters at one or more respective second audience measurement locations, a second set of unknown signature segments; selecting a candidate unknown signature segment from the first set of unknown signature segments, wherein the candidate unknown signature segment meets a threshold length; comparing individual signatures of the candidate unknown signature segment with individual signatures of one or more unknown signature segments from the second set of unknown signature segments; counting a number of times that the individual signatures of the candidate unknown signature segment matches the individual signatures of the unknown signature segments in the second set of unknown signatures segments; determining that the candidate unknown signature segment is a matched signature segment when the number of times meets a counter threshold; and in response to a determination that the candidate unknown signature segment is a matched signature segment: identifying, based on online activity associated with the first audience measurement location, media identifying information associated with the matched signature segment; and storing the matched signature segment in association with the media identifying information in a signature reference database as a reference signature.

15. The method of claim 14, further comprising: discarding unknown signature segments collected at the first audience measurement location that do not meet the threshold length.

16. The method of claim 14, wherein the media identifying information corresponds to media accessed at the first audience measurement location.

17. The method of claim 16, wherein the identifying, based on the online activity associated with the first audience measurement location, the media identifying information associated with the matched signature segment further comprises: comparing: (i) timestamps of online activity indicative of accessing the media at the first audience measurement location and (ii) timestamps associated with the candidate unknown signature segment; and based on the comparing, correlating the online activity indicative of accessing the media with the candidate unknown signature segment.

18. The method of claim 14, wherein the identifying, based on the online activity associated with the first audience measurement location, the media identifying information associated with the matched signature segment further comprises identifying the media identification information based on a uniform resource locator indicative of accessing media associated with the media identifying information at the first audience measurement location.

19. The method of claim 18, further comprising: updating the signature reference database to associate the matched signature segment with the media identification information based on the uniform resource locator.

20. The method of claim 14, further comprising: crediting media exposure to media corresponding to the matched signature segment based on an additional unknown signature matching at least a portion of the matched signature segment.
