

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12410727

Kind Code

B2

Date of Patent

September 09, 2025

Inventor(s)

Goyette; Scott et al.

Propulsor blade imaging assembly method for an aircraft propulsion system

Abstract

An assembly for an aircraft propulsion system includes a propulsor and an imaging assembly. The propulsor includes a propulsor disk, a plurality of propulsor blades, and a nose cone. The plurality of propulsor blades are circumferentially distributed about the propulsor disk. Each propulsor blade of the plurality of propulsor blades extends radially between and to a root end and a tip end. The root end is disposed at the propulsor disk. The propulsor disk and the plurality of propulsor blades are configured to rotate about the rotational axis. The nose cone is disposed axially adjacent the propulsor disk. The imaging assembly includes an imaging device disposed on the nose cone. The imaging device includes a camera. The camera is configured to capture image data of each propulsor blade of the plurality of propulsor blades as the plurality of propulsor blades rotate about the rotational axis.

Inventors: Goyette; Scott (Moosup, CT), Hagen; Gregory S. (Glastonbury, CT), Chaudhry; Zaffir A. (South Glastonbury, CT), Attridge; Paul (Colchester, CT), Shaw; Janet (Tolland, CT), Lincoln; David L. (Cromwell, CT), King; Jeffrey P. (Coventry, CT)

Applicant: RTX Corporation (Farmington, CT)

Family ID: 90789469

Assignee: RTX Corporation (Farmington, CT)

Appl. No.: 18/951129

Filed: November 18, 2024

Prior Publication Data

Document Identifier

US 20250075631 A1

Publication Date

Mar. 06, 2025

Related U.S. Application Data

division parent-doc US 18136115 20230418 US 12146416 child-doc US 18951129

Publication Classification

Int. Cl.: F01D25/00 (20060101); B08B5/02 (20060101); F01D21/00 (20060101); H04N7/18 (20060101); H04N23/90 (20230101)

U.S. Cl.:

CPC F01D21/003 (20130101); H04N7/188 (20130101); H04N23/90 (20230101); F05D2260/83 (20130101)

Field of Classification Search

CPC: F01D (21/003); H04N (7/188); H04N (23/90); F05D (2260/83)

USPC: 415/118

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7656445	12/2009	Heyworth	N/A	N/A
10605165	12/2019	Abe	N/A	N/A
12055055	12/2023	Goyette	N/A	F01D 25/002
2007/0085904	12/2006	Heyworth	N/A	N/A
2015/0138342	12/2014	Brdar	348/128	G01N 21/8851
2017/0318220	12/2016	Miller	N/A	N/A
2019/0338666	12/2018	Finn	N/A	G06T 3/4038
2020/0056501	12/2019	Eastment	N/A	N/A
2021/0180466	12/2020	Gavrilovski	N/A	N/A

Primary Examiner: Newton; J. Todd

Attorney, Agent or Firm: Getz Balich LLC

Background/Summary

(1) This application is a divisional of U.S. patent application Ser. No. 18/136,115 filed Apr. 18, 2023, which is hereby incorporated herein by reference in its entirety.

BACKGROUND

1. Technical Field

(1) The present disclosure relates to aircraft propulsion systems and, more particularly, to imaging assemblies for in situ inspection of propulsor blades for aircraft propulsion systems.

2. Background Information

(2) Propulsion systems for aircraft may include rotational equipment, such as propulsors or other rotational equipment components, which may be susceptible to foreign object damage (FOD). Various systems and methods for inspecting rotational equipment components for FOD are known in the art. While these known systems and methods have various advantages, there is still room in the art for improvement. There is a need in the art, therefore, for improved systems and methods for identifying damage to propulsors and other rotational equipment for aircraft propulsion systems.

SUMMARY

(3) It should be understood that any or all of the features or embodiments described herein can be used or combined in any combination with each and every other feature or embodiment described herein unless expressly noted otherwise.

(4) According to an aspect of the present disclosure, an assembly for an aircraft propulsion system includes a propulsor and an imaging assembly. The propulsor includes a propulsor disk, a plurality of propulsor blades, and a nose cone. The propulsor disk extends circumferentially about a rotational axis. The plurality of propulsor blades are circumferentially distributed about the propulsor disk. Each propulsor blade of the plurality of propulsor blades extends radially between and to a root end and a tip end. The root end is disposed at the propulsor disk. The propulsor disk and the plurality of propulsor blades are configured to rotate about the rotational axis. The nose cone is disposed axially adjacent the propulsor disk. The imaging assembly includes an imaging device disposed on the nose cone. The imaging device includes a camera. The camera is configured to capture image data of each propulsor blade of the plurality of propulsor blades as the plurality of propulsor blades rotate about the rotational axis.

(5) In any of the aspects or embodiments described above and herein, the nose cone may be rotationally fixed relative to the rotational axis.

(6) In any of the aspects or embodiments described above and herein, the nose cone may extend axially between and to a leading end and a trailing end. The trailing end may be positioned at the propulsor disk. The nose cone may form an exterior surface extending between and to the leading end and the trailing end. The camera may be positioned at the exterior surface.

(7) In any of the aspects or embodiments described above and herein, the nose cone may be positioned axially between and spaced from the leading end and the trailing end.

(8) In any of the aspects or embodiments described above and herein, the exterior surface may diverge in a radial direction from the leading end to the trailing end, and divergence of the exterior surface axially between the imaging device and the trailing end may be linear.

(9) In any of the aspects or embodiments described above and herein, the camera may be configured to capture the image data for a portion of a radial span of each propulsor blade of the plurality of propulsor blades.

(10) In any of the aspects or embodiments described above and herein, the portion may be at the root end.

(11) In any of the aspects or embodiments described above and herein, the imaging device may include a plurality of cameras. The plurality of cameras may include the camera. Each camera of the plurality of cameras may be configured to capture the image data for a different portion of the radial span relative to each other camera of the plurality of cameras.

(12) In any of the aspects or embodiments described above and herein, the imaging assembly may further include a controller connected in signal communication with the imaging device. The controller may include a processor in communication with a non-transitory memory storing instructions, which instructions when executed by the processor, may cause the processor to: initiate the capture of the image data by controlling the camera to capture the image data based on a measured rotation speed of the propulsor about the rotational axis.

(13) In any of the aspects or embodiments described above and herein, the instructions, when executed by the processor, may further cause the processor to initiate the capture of the image data by controlling the camera to capture the image data based on the measured rotation speed when the

measured rotation speed is less than or equal to a predetermined rotation speed threshold value.

(14) In any of the aspects or embodiments described above and herein, the predetermined rotation speed threshold value may be greater than zero (0) RPM.

(15) In any of the aspects or embodiments described above and herein, the instructions, when executed by the processor, may further cause the processor to identify a presence or an absence of damage for each propulsor blade of the plurality of propulsor blades using the image data.

(16) In any of the aspects or embodiments described above and herein, the instructions, when executed by the processor, may further cause the processor to transmit to an offboard system an indication of identification of the presence of damage to at least one propulsor blade of the plurality of propulsor blades.

(17) According to another aspect of the present disclosure, a method for inspection of a plurality of propulsor blades for an aircraft propulsion system is provided. The method includes rotating the plurality of propulsor blades about a rotational axis at a first rotation speed, shutting down the aircraft propulsion system, capturing image data for each propulsor blade of the plurality of propulsor blades for the shutdown aircraft propulsion system subsequent to rotation speed of the plurality of propulsor blades decreasing to or below a second rotation speed which is less than the first rotation speed and greater than zero (0) RPM, and identifying a presence or an absence of damage for each propulsor blade of the plurality of propulsor blades using the captured image data.

(18) In any of the aspects or embodiments described above and herein, capturing the image data for each propulsor blade of the plurality of propulsor blades may include capturing the image data for each propulsor blade of the plurality of propulsor blades with a camera disposed at a propulsor nose cone axially adjacent the plurality of propulsor blades. The propulsor nose cone may be rotationally fixed relative to the rotational axis.

(19) In any of the aspects or embodiments described above and herein, shutting down the aircraft propulsion system may be performed with the aircraft propulsion system in a grounded condition.

(20) According to an aspect of the present disclosure, a propulsion system for an aircraft includes a gas turbine engine and an imaging assembly. The gas turbine engine includes a rotational assembly and a propulsor. The rotational assembly includes a shaft rotatable about a rotational axis. The propulsor includes a plurality of propulsor blades and a nose cone. The plurality of propulsor blades is configured to be driven by the shaft for rotation about the rotational axis. The nose cone is rotationally fixed relative to the rotational axis. The imaging assembly includes an imaging device disposed on the nose cone. The imaging device includes a camera. The camera is configured to capture image data of each propulsor blade of the plurality of propulsor blades as the propulsor blades rotate about the rotational axis.

(21) In any of the aspects or embodiments described above and herein, the imaging assembly may further include a controller connected in signal communication with the imaging device. The controller may include a processor in communication with a non-transitory memory storing instructions, which instructions when executed by the processor, may cause the processor to: initiate the capture of the image data by controlling the camera to capture the image data based on a rotation speed of the shaft about the rotational axis.

(22) In any of the aspects or embodiments described above and herein, the imaging assembly may further include a shaft speed sensor configured to measure the rotation speed of the shaft, generate an output signal proportional to the measured rotation speed, and transmit the output signal to the controller.

(23) In any of the aspects or embodiments described above and herein, the gas turbine engine may further include a generator. The generator may be configured to generate and direct electrical power to the imaging assembly.

(24) The present disclosure, and all its aspects, embodiments and advantages associated therewith will become more readily apparent in view of the detailed description provided below, including the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 illustrates a schematic side, cutaway view of an aircraft propulsion system, in accordance with one or more embodiments of the present disclosure.
- (2) FIG. 2 illustrates a block diagram of a propulsor blade imaging assembly for an aircraft propulsion system, in accordance with one or more embodiments of the present disclosure.
- (3) FIG. 3 illustrates a perspective view of a portion of a propulsor blade imaging assembly installed on a propulsor for an aircraft propulsion system, in accordance with one or more embodiments of the present disclosure.
- (4) FIG. 4 illustrates a perspective view of a portion of another propulsor blade imaging assembly installed on a propulsor for an aircraft propulsion system, in accordance with one or more embodiments of the present disclosure.
- (5) FIG. 5 illustrates an exemplary graph of an aircraft propulsion system propulsor rotation speed during an engine shutdown, in accordance with one or more embodiments of the present disclosure.

DETAILED DESCRIPTION

- (6) FIG. 1 schematically illustrates a side, cutaway view of a propulsion system **20** configured for an aircraft. The aircraft propulsion system **20** of FIG. 1 includes a gas turbine engine **22**, a nacelle **24**, and an imaging assembly **26**.
- (7) The gas turbine engine **22** of FIG. 1 is configured as a multi-spool turbfan gas turbine engine. The gas turbine engine **22** of FIG. 1 includes a propulsor section **28**, a compressor section **30**, a combustor section **32**, a turbine section **34**, and an engine static structure **36**. The present disclosure, however, is not limited to the particular gas turbine engine **22** configuration of FIG. 1. For example, aspects of the present disclosure may also be applicable to propulsion system gas turbine engines having single-spool and three-spool configurations.
- (8) The gas turbine engine **22** sections **28**, **30**, **32**, and **34**, of FIG. 1 are arranged sequentially along an axial centerline **38** (e.g., a rotational axis) of the gas turbine engine **22**. The engine static structure **36** may include, for example, one or more engine cases for the gas turbine engine **22**. The engine static structure **36** may additionally include cowlings, bearing assemblies, or other structural components of the gas turbine engine **22**. The engine static structure **36** and its components house, structurally support, and/or rotationally support components of the engine sections **28**, **30**, **32**, and **34**.
- (9) The propulsor section **28** includes a propulsor **40** (e.g., a fan, an open rotor propulsor, etc.) The propulsor section **28** may additionally include a propulsor case **42** (e.g., a fan case). The propulsor **40** includes a propulsor disk **44**, a plurality of propulsor blades **46**, and a nose cone **48**. The propulsor disk **44** is configured as an annular body. For example, the propulsor disk **44** extends circumferentially about (e.g., completely around) the axial centerline **38**. Each of the plurality of propulsor blades **46** includes a root end **50** and a tip end **52**. The root end **50** is mounted to the propulsor disk **44**. Each of the plurality of propulsor blades **46** extends radially outward from the root end **50** to the tip end **52**. The plurality of propulsor blades **46** are circumferentially distributed about the propulsor disk **44**. The nose cone **48** forms an aerodynamic structure of the propulsor **40** axially adjacent the propulsor disk **44**. For example, the nose cone **48** may be disposed upstream of (e.g., axially forward of) the propulsor disk **44**. The nose cone **48** extends (e.g., axially extends) between and to a leading end **54** of the nose cone **48** and a trailing end **56** of the nose cone **48**. The leading end **54** is disposed upstream of (e.g., axially forward of) the trailing end **56**. The trailing end **56** is disposed at (e.g., on, adjacent, or proximate) the propulsor disk **44**. The nose cone **48** forms an exterior surface **58** extending between and to the leading end **54** and the trailing end **56**. The exterior surface **58** is configured with a conical shape which radially diverges in a direction from the leading end **54** to the trailing end **56**. The nose cone **48** of FIG. 1 is rotationally fixed

relative to the propulsor disk **44**. In other words, the propulsor disk **44** and the plurality of propulsor blades **46** may rotate about the axial centerline **38** while the nose cone **48** remains rotationally fixed relative to the axial centerline **38**. The propulsor **40** may include one or more struts **59**, vanes, or other structural components for supporting the nose cone **48** (e.g., for mounting the nose cone **48** to the propulsor case **42**); however, the present disclosure is not limited to any particular mounting configuration for the nose cone **48**. The propulsor case **42** extends circumferentially about (e.g., completely around) the axial centerline **38**. The propulsor case **42** radially circumscribes the plurality of propulsor blades **46**. The propulsor case **42** may be formed by or otherwise disposed at the nacelle **24**.

(10) The compressor section **30** may include a low-pressure compressor (LPC) **60** and a high-pressure compressor (HPC) **62**. The combustor section **32** includes a combustor **64** (e.g., an annular combustor) forming a combustion chamber. The turbine section **34** may include a high-pressure turbine (HPT) **66** a low-pressure turbine (LPT) **68**.

(11) The gas turbine engine **22** sections **28**, **30**, **32**, **34** form a first rotational assembly **70** (e.g., a high-pressure spool) and a second rotational assembly **72** (e.g., a low-pressure spool) of the gas turbine engine **22**. The first rotational assembly **70** and the second rotational assembly **72** of FIG. **1** are mounted for rotation about the axial centerline **38** relative to the engine static structure **36**. Alternatively, the first rotational assembly **70** and the second rotational assembly **72** may each be mounted for rotation about different respective rotational axes.

(12) The first rotational assembly **70** includes a first shaft **74**, a bladed first compressor rotor **76** for the high-pressure compressor **62**, and a bladed first turbine rotor **78** for the high-pressure turbine **66**. The first shaft **74** interconnects the bladed first compressor rotor **76** and the bladed first turbine rotor **78**. The first rotational assembly **70** may further include one or more engine accessories connected in rotational communication with the first shaft **74**. For example, the first rotational assembly **70** of FIG. **1** includes a generator **80** connected in rotational communication with the first shaft **74**. The generator **80** may be directly mechanically coupled to the first shaft **74**. Alternatively, the generator **80** may be indirectly mechanically coupled to the first shaft **74**, for example, by an accessory gear assembly (not shown) configured to rotationally drive the generator **80** at a reduced rotational speed relative to the first shaft **74**. Rotation of the first shaft **74** drives rotation of the generator **80** causing the generator **80** to generate electrical power for electrical loads (e.g., electronic control systems, electric motors, lighting systems, etc.) of the propulsion system **20** and/or an aircraft on which the propulsion system **20** is installed. For example, the generator **80** may direct electrical power **82** to all or a portion of the imaging assembly **26**. While engine accessories, such as the generator **80**, are described above as components of the first rotational assembly **70**, the engine accessories (e.g., the generator **80**) may alternatively be components of the second rotational assembly **72** and may be mechanically coupled to and driven by the second rotational assembly **72** in a similar manner.

(13) The second rotational assembly **72** includes a second shaft **84**, a bladed second compressor rotor **86** for the low-pressure compressor **60**, and a bladed second turbine rotor **88** for the low-pressure turbine **68**. The second shaft **84** interconnects the bladed second compressor rotor **86** and the bladed second turbine rotor **88**. The second shaft **84** may be directly or indirectly connected to the propulsor **40** (e.g., the propulsor disk **44**) to drive rotation of the propulsor **40**. For example, the second shaft **84** may be connected to the propulsor **40** by one or more speed-reducing gear assemblies (not shown) to drive the propulsor **40** at a reduced rotational speed relative to the second shaft **84**.

(14) The nacelle **24** forms an exterior aerodynamic housing for the propulsion system **20**. The nacelle **24** of FIG. **1** extends circumferentially about (e.g., completely around) the axial centerline **38** and surrounds the gas turbine engine **22**. The nacelle **24** surrounds and forms an annular bypass duct **90** between (e.g., radially between) the nacelle **24** and the engine static structure **36** (e.g., a core cowling).

(15) During operation of the gas turbine engine 22 of FIG. 1, ambient air enters the gas turbine engine 22 through the propulsor section 28 and is directed into a core flow path 92 and a bypass flow path 94 by rotation of the propulsor 40. The core flow path 92 extends generally axially along the axial centerline 38 in the gas turbine engine 22. For example, the core flow path 92 extends axially through the gas turbine engine 22 sections 30, 32, and 34 of FIG. 1. The air in the core flow path 92 may be referred to as “core air.” The core air is compressed by the bladed second compressor rotor 86 and the bladed first compressor rotor 76 and directed into the combustion chamber of the combustor 64. Fuel is injected into the combustion chamber and mixed with the compressed core air to form a fuel-air mixture. This fuel-air mixture is ignited and combustion products thereof, which may be referred to as “core combustion gas,” flow through and sequentially cause the bladed first turbine rotor 78 and the bladed second turbine rotor 88 to rotate. The rotation of the bladed first turbine rotor 78 and the bladed second turbine rotor 88 respectively drive rotation of the first rotational assembly 70 and the second rotational assembly 72. Rotation of the second rotational assembly 72 further drives rotation of the propulsor 40, as discussed above. The air in the bypass flow path 90 is directed through the bypass duct 90. The air in the bypass flow path 90 may be referred to as “bypass air.”

(16) The imaging assembly 26 of FIG. 1 includes a controller 96 and one or more imaging devices 98. The imaging assembly 26 may additionally include a shaft speed sensor 100.

(17) The controller 96 is connected in signal communication with the imaging device(s) 98 to perform the functions described herein. The controller 96 includes a processor 102 and memory 104. The memory 104 is connected in signal communication with the processor 102.

(18) The processor 102 may include any type of computing device, computational circuit, processor(s), CPU, computer, or the like capable of executing a series of instructions that are stored in the memory 104. Instructions can be directly executable or can be used to develop executable instructions. For example, instructions can be realized as executable or non-executable machine code or as instructions in a high-level language that can be compiled to produce executable or non-executable machine code. Further, instructions also can be realized as or can include data. Computer-executable instructions also can be organized in any format, including routines, subroutines, programs, data structures, objects, modules, applications, applets, functions, etc. The instructions may include an operating system, and/or executable software modules such as program files, system data, buffers, drivers, utilities, and the like. The executable instructions may apply to any functionality described herein to enable the imaging assembly 26 to accomplish the same algorithmically and/or by coordination of imaging assembly 26 components. The memory 104 may include a single memory device or a plurality of memory devices, for example, a computer-readable storage device that can be read, written, or otherwise accessed by a general purpose or special purpose computing device, including any processing electronics, and/or processing circuitry capable of executing instructions. The present disclosure is not limited to any particular type of configuration for the memory 104, which may be non-transitory, and may include read-only memory, random access memory, volatile memory, non-volatile memory, static memory, dynamic memory, flash memory, cache memory, volatile or non-volatile semiconductor memory, optical disk storage, magnetic disk storage, magnetic tape, other magnetic storage devices, or any other medium capable of storing one or more instructions, and/or any device that stores digital information. The memory 104 may be directly or indirectly electronically integrated with the controller 96. The controller 96 may include, or may be in communication with, an input device that enables a user to enter data and/or instructions, and may include, or be in communication with, an output device configured, for example to display information (e.g., a visual display or a printer), or to transfer data, etc. Communications between the controller 96 and other components, such as other components of the imaging assembly 26, may be via a hardwire connection or via a wireless connection. A person of skill in the art will recognize that portions of the controller 96 may assume various forms (e.g., digital signal processor, analog device, etc.) capable of performing the

functions described herein.

(19) The controller **96** may form or otherwise be part of an electronic engine controller (EEC) for the gas turbine engine **22**. The EEC may control operating parameters of the gas turbine engine **22** including, but not limited to, fuel flow to the combustor **64**, stator vane position (e.g., variable compressor inlet guide vane (IGV) position), compressor air bleed valve position, etc. so as to control an engine power and/or thrust of the gas turbine engine **22**. In some embodiments, the EEC may be part of a full authority digital engine control (FADEC) system for the gas turbine engine **22**.

(20) The shaft speed sensor **100** may be connected in signal communication with the controller **96**, as shown in FIG. **1**. The shaft speed sensor **100** of FIG. **1** is positioned at (e.g., on, adjacent, or proximate) the second shaft **84**. The shaft speed sensor **100** is configured to measure a rotation speed of the second rotational assembly **72** (e.g., the second shaft **84**) and generate an output signal proportional to the measured rotation speed.

(21) The controller **96** may be configured for wireless communication with one or more offboard systems **106** (e.g., an electronic system which is external to both the propulsion system **20** and an aircraft on which the propulsion system **20** is installed). As will be discussed in further detail, the controller **96** may transmit image data and/or other operational data collected from the propulsion system **20** (e.g., from the imaging device **98**) to the offboard system(s) **106** for remote monitoring and/or analysis of propulsion system **20** health. For example, the offboard system(s) **106** may allow maintenance personnel to remotely monitor and/or analyze the health of the propulsion system **20** (e.g., the plurality of propulsor blades **46**). The offboard system(s) **106** may include, for example, a ground station, a near-wing maintenance computer, and/or any other device with which the controller **96** may establish one-way or two-way wireless communication. Wireless communication may be implemented by a variety of technologies such as, but not limited to, Wi-Fi (e.g., radio wireless local area networking based on IEEE 802.11 or other applicable standards), cellular networks, satellite communication, and/or other wireless communication technologies known in the art. Wireless communication between the controller **96** and the offboard system(s) **106** may be direct or indirect. For example, the controller **96** may directly wirelessly communicate with the offboard system(s) **106**. Alternatively, for example, the controller **96** may indirectly wirelessly communicate with the offboard system(s) **106** using one or more intermediate systems or components (e.g., communication systems) of the propulsion system **20** and/or an aircraft on which the propulsion system **20** is installed. It should be understood, of course, that wired communication systems may be used in addition to or as an alternative to wireless communication systems.

(22) Referring to FIGS. **1** and **2**, the imaging device **98** will be described in further detail. The imaging device **98** of FIG. **1** is installed on the nose cone **48**. FIG. **2** illustrates a block diagram including the imaging device **98**, the controller **96**, and the propulsor **40**. The imaging device **98** includes at least one camera **108**, as shown in FIG. **2**. The imaging device **98** may further include a light source **110**.

(23) The camera **108** is configured to capture image data of the plurality of propulsor blades **46** as the plurality of propulsor blades **46** rotate with the propulsor disk **44** about the axial centerline **38**, and subsequently transmit the capture image data to the controller **96**. The camera **108** is configured to capture image data for at least a portion of each of the plurality of propulsor blades **46**. For example, the camera **108** of FIG. **2** is configured to capture image data of a radial portion of the plurality of propulsor blades **46** as the plurality of propulsor blades **46** pass through a focused field-of-view of the camera **108**. The camera **108** of FIG. **3** is configured with a focused field-of-view (schematically illustrated in FIG. **3** as field-of-view **114** having a field-of-view angle α) directed toward an axially forward side of the plurality of propulsor blades **46** (e.g., toward a leading edge of each of the plurality of propulsor blades **46**). For example, the camera **108** of FIG. **2** is configured to capture image data associated with a radial portion of the illustrated propulsor blade **46** at (e.g., on, adjacent, or proximate) the root end **50**. The camera **108** may alternatively be configured to capture an entire radial span of the passing plurality of propulsor blades **46** from the

root end **50** to the tip end **52**. As will be discussed in further detail, the camera **108** has a shutter speed, which shutter speed is representative of a length of time in which a digital image sensor of the camera **108** is exposed to light (e.g., while capturing the image data). The particular shutter speed for the camera **108** may correspond to a rotation speed range of the propulsor **40** at which the camera **108** may be used to capture image data of the plurality of propulsor blades **46**. For example, a faster shutter speed of the camera **108** may facilitate the capture of suitable image data of the plurality of propulsor blades **46** for greater rotation speeds of the propulsor **40**. The present disclosure, however, is not limited to any particular shutter speed for the camera **108**. The imaging device **98** may include a plurality of cameras **108**. Each of the plurality of cameras may be positioned with a focused field-of-view of a different portion (e.g., a different radial portion) of the plurality of propulsor blades **46**. Accordingly, the plurality of cameras **108** may cooperatively capture image data associated with all or at least a substantial portion of a radial span of the passing plurality of propulsor blades **46**.

(24) The light source **110** is configured to direct light (schematically illustrated in FIG. 2 as light vector **112**) toward the plurality of propulsor blades **46** to facilitate the capture of image data of the plurality of propulsor blades **46** by the camera **108**. The light source **110** may have any suitable lighting configuration conventionally known in the art. The light source **110** may be positioned at (e.g., on, adjacent, or proximate) the camera **108**. Alternatively, the light source **110** may be positioned in a discrete location of the propulsor section **28** separated from the camera **108** (e.g., on the propulsor case **42**).

(25) FIG. 3 illustrates a perspective view of the propulsor **40** and a portion of an exemplary configuration of the imaging assembly **26**. Structural portions of the propulsor section **28** including the propulsor case **42** and the struts **59** have been omitted from FIG. 3 for clarity. As previously discussed, the nose cone **48** is rotationally fixed about the axial centerline **38** (e.g., relative to the propulsor disk **44**). The imaging device **98** is disposed on the nose cone **48**. For example, the imaging device **98** is disposed at (e.g., on, adjacent, or proximate) the exterior surface **58**. The imaging device **98** may be disposed at an intermediate axial position of the nose cone **48** (e.g., axially between and spaced from the leading end **54** and the trailing end **56**). The camera **108** of FIG. 3 is configured with the field-of-view **114** directed toward an axially forward side of the plurality of propulsor blades **46** (e.g., toward a leading edge of each of the plurality of propulsor blades **46**). The field-of-view **114** of FIG. 3 is directed toward a radial portion of the plurality of propulsor blades **46** at (e.g., on, adjacent, or proximate) the root end **50**; however, the present disclosure is not limited to this particular field-of-view. As previously discussed, the exterior surface **58** may radially diverge in a direction from the leading end **54** to the trailing end **56**. The divergence of the exterior surface **58** between the imaging device **98** and the trailing end **56** may be linear or substantially linear to facilitate an uninterrupted field-of-view **114** of the camera **108** to the root end **50**.

(26) FIG. 4 illustrates a perspective view of the propulsor **40** and a portion of another exemplary configuration of the imaging assembly **26**. Structural portions of the propulsor section **28** including the propulsor case **42** and the struts **59** have been omitted from FIG. 4 for clarity. As previously discussed, the nose cone **48** is rotationally fixed about the axial centerline **38** (e.g., relative to the propulsor disk **44**). The imaging device **98** includes a plurality of cameras **108** with each camera **108** having a different respective focused field-of-view **114A**, **114B**, **114C** directed toward an axially forward side of the plurality of propulsor blades **46**. In other words, each of the cameras **108** is configured to capture image data of a different radial portion of each of the plurality of propulsor blades **46**.

(27) During operation of the propulsion system **20** and its gas turbine engine **22** (e.g., during flight), the plurality of propulsor blades **46** may be exposed to foreign objects (e.g., birds, dirt, rocks, loose mechanical fasteners, etc.) which may enter the propulsor section **28** and collide with one or more of the plurality of propulsor blades **46**. As a result, one or more of the plurality of

propulsor blades **46** may be damaged (e.g., foreign object damage or “FOD”). For example, one or more of the plurality of propulsor blades **46** may include nicks, dents, scratches, tears, and the like caused by a foreign object. Propulsor blades, such as the plurality of propulsor blades **46**, which experience foreign object damage may exhibit an increased likelihood of material failure. Inner radial portions of propulsor blades (e.g., at the root end **50**) may experience greater steady stress and vibratory stress relative to other portions of the propulsor blades and these inner radial portions may, therefore, be more susceptible to material failure resulting from foreign object damage.

(28) To identify the presence of foreign object damage on propulsor blades, the propulsor blades may be periodically inspected. This inspection process may conventionally be performed manually by an inspector directly visually observing the propulsor blades and feeling the propulsor blades to identify foreign object damage. While this may be a reliable method for identifying foreign object damage, it can require a considerable amount of time, during which time the propulsion system **20** and its gas turbine engine **22** may not be operated. Moreover, this manual inspection process may present an increased likelihood of inspection tools and/or maintenance materials being left inside the gas turbine engine, where they may subsequently be ingested by the gas turbine engine contributing to the risk of foreign object damage.

(29) In operation of the imaging assembly **26**, the imaging device **98** (e.g., the camera(s) **108**) captures image data of the plurality of propulsor blades **46** and transmits the image data to the controller **96**. The memory **104** includes instructions which, when executed by the controller **96** and/or its processor **102**, cause the controller **96** and/or its processor **102** to identify the presence or absence of damage (e.g., foreign object damage) for the plurality of propulsor blades **46**. Using the image data, the controller **96** may identify a probability that the plurality of propulsor blades **46** or one or more of the plurality of propulsor blades **46** includes damage. The controller **96** may identify damage to the plurality of propulsor blades **46** or one or more of the plurality of propulsor blades **46** if the determined probability exceeds a damage probability threshold. The damage probability threshold may be a predetermined value (e.g., a user input). The instructions may include, for example, a machine learning algorithm to identify the presence of damage or otherwise determine a probability of damage using the image data from the cameras **108**. The machine learning algorithm may be trained using historical image data of propulsor blades, which historical image data may include flagged (e.g., manually identified) propulsor blade damage. Alternatively, the instructions may cause the controller **96** to compare the image data from the cameras **108** to reference image data which is representative of the plurality of propulsor blades **46**. The controller **96** may compare the image data from the cameras **108** to the reference image data to identify differences which may be indicative of the presence of damage for the plurality of propulsor blades **46**. The present disclosure, however, is not limited to any particular algorithm or process for identifying damage using the image data from the cameras **108**. The location of the imaging device **98** on the nose cone **48**, as previously discussed, positions the camera(s) **108** in closer proximity to the root end **50** of each of the plurality of propulsor blades **46**, relative to other portions of the propulsor section **28**. Accordingly, the camera(s) **108** may capture clearer and/or higher quality image data for portions (e.g., radial portions) of the plurality of propulsor blades **46** at (e.g., on, adjacent, or proximate) the root end **50** which portions, as previously discussed, may be more susceptible to material failure resulting from foreign object damage.

(30) The controller **96** may control the imaging device **98** (e.g., the camera(s) **108** and/or the light source **110**) to capture the image data for the plurality of propulsor blades **46**. For example, the memory **104** may include instructions which, when executed by the controller **96** and/or its processor **102**, cause the controller **96** to control the imaging device **98** (e.g., the camera(s) **108** and/or the light source **110**) to capture the image data for the plurality of propulsor blades **46**. The controller **96** may control the imaging device **98** based on a measured or otherwise determined rotation speed of the propulsor **40**. For example, the controller **96** may control the imaging device **98** based on the output signal of the shaft speed sensor **100**, which output signal may be

representative of the rotation speed of the propulsor **40**. For embodiments of the gas turbine engine **22** in which the propulsor **40** may be driven by the second shaft **84** via a speed-reducing gear assembly, the rotation speed of the propulsor **40** may be determined by the controller **96** based on a known speed-reduction ratio of the speed-reducing gear assembly.

(31) The controller **96** may control the imaging device **98** to capture the image data for the plurality of propulsor blades **46** when the rotation speed of the propulsor **40** is less than or equal to a rotation speed threshold value (e.g., a predetermined rotation speed value). The rotation speed threshold value may be representative of a rotation speed of the propulsor **40** at or below which the camera(s) **108** may capture image data of the plurality of propulsor blades **46** which is suitable for the controller **96** to identify the presence or absence of damage (e.g., foreign object damage) for the plurality of propulsor blades **46**, for example, based on the shutter speed for each camera **108**.

(32) The controller **96** may control the imaging device **98** to capture the image data for the plurality of propulsor blades **46** subsequent to shutdown of the propulsion system **20** and/or its gas turbine engine **22** (e.g., when fuel is no longer being supplied to the combustor **64** to drive rotation of the rotational assemblies **70**, **72**). In other words, the propulsion system **20** may be understood to be in a shutdown condition when the propulsion system **20** is no longer expending energy (e.g., fuel, stored battery energy, etc.) to drive rotation of the propulsor **40** (e.g., using the rotational assemblies **70**, **72**). FIG. 5 illustrates a graph of propulsor **40** rotation speed vs. time following shutdown of the gas turbine engine **22**. A shutdown **116** of the gas turbine engine **22** may occur at Time **0**, as shown in FIG. 5. A rotation speed **118** of the propulsor **40** (e.g., based on measurement of the second shaft **84** rotation speed) will gradually decrease toward zero (0) revolutions per minute (RPM) subsequent to the shutdown **116**. For ease of understanding, the slope of the rotation speed **118** in FIG. 5 is illustrated as being substantially linear, however, the present disclosure should not be understood to be limited in this regard. The controller **96** may control the imaging device **98** to capture the image data for the plurality of propulsor blades **46** when the rotation speed **118** of the propulsor **40** is less than or equal to a rotation speed threshold value **120**. As shown in FIG. 5, the rotation speed threshold value **120** is a rotation speed value greater than zero (0) RPM. The rotation speed threshold value **120** may be less than an initial rotation speed **118** of the propulsor **40** at the shutdown **116**. The rotation speed threshold value **120** may be selected such that the captured image data of the plurality of propulsor blades **46** is suitable for analysis by the controller **96**, as described above, but provides sufficient time for the capture of the image data of each of the plurality of propulsor blades **46** prior to the propulsor **40** reaching a rotationally stationary condition (e.g., the rotation speed **118** at or approximately at zero (0) RPM). In some embodiments of the propulsion system **20**, the imaging assembly **26** or components (e.g., the imaging device **98**) of the imaging assembly **26** may receive electrical power from the generator **80** (see FIG. 1). Following the shutdown **116**, rotation of the first rotational assembly **70** and the second rotational assembly **72** may gradually decrease to a point at which the generator **80** may no longer be capable of suitably generating electrical power for the imaging assembly **26** or components (e.g., the imaging device **98**) of the imaging assembly **26**. Accordingly, the rotation speed threshold value **120** may be selected to provide sufficient time for the capture of the image data of each of the plurality of propulsor blades **46** prior to a loss of electrical power by the imaging assembly **26** or components (e.g., the imaging device **98**) of the imaging assembly **26**. Routine experimentation, simulation, and/or analysis may be performed by a person of ordinary skill in the art to determine suitable a rotation speed threshold value(s) in accordance with and as informed by one or more aspects of the present disclosure. The process for capturing the image data for the plurality of propulsor blades **46** following the shutdown **116**, as described above, may generally be performed with the propulsion system **20** in a grounded condition (e.g., with the aircraft on which the propulsion system **20** is installed being on the ground). For example, the controller **96** may initiate the capture of the image data following an aircraft landing procedure, where the gas turbine engine **22** is shutdown during or following aircraft transit on the ground (e.g.,

taxiing).

(33) The controller **96** may transmit the image data and/or an indication of the identified presence or absence of damage for the plurality of propulsor blades **46** to the offboard system(s) **106**. For example, the controller **96** may transmit data to the offboard system(s) **106** indicating that one or more of the plurality of propulsor blades **46** has been identified as being damaged. Receipt of the damage-indicative data by the offboard system(s) **106** may facilitate the scheduling and/or performing of inspections and/or repair for the plurality of propulsor blades **46** (e.g., the damaged one or more propulsor blades of the plurality of propulsor blades **46**). Accordingly, aspects of the present disclosure may facilitate a reduction or elimination of periodic manual inspections of the plurality of propulsor blades **46**, and inspections and repairs may instead be performed based on in situ identification of damage to the plurality of propulsor blades **46** as identified by the imaging assembly **26**.

(34) While the principles of the disclosure have been described above in connection with specific apparatuses and methods, it is to be clearly understood that this description is made only by way of example and not as limitation on the scope of the disclosure. Specific details are given in the above description to provide a thorough understanding of the embodiments. However, it is understood that the embodiments may be practiced without these specific details.

(35) It is noted that the embodiments may be described as a process which is depicted as a flowchart, a flow diagram, a block diagram, etc. Although any one of these structures may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be rearranged. A process may correspond to a method, a function, a procedure, a subroutine, a subprogram, etc.

(36) The singular forms “a,” “an,” and “the” refer to one or more than one, unless the context clearly dictates otherwise. For example, the term “comprising a specimen” includes single or plural specimens and is considered equivalent to the phrase “comprising at least one specimen.” The term “or” refers to a single element of stated alternative elements or a combination of two or more elements unless the context clearly indicates otherwise. As used herein, “comprises” means “includes.” Thus, “comprising A or B,” means “including A or B, or A and B,” without excluding additional elements.

(37) It is noted that various connections are set forth between elements in the present description and drawings (the contents of which are included in this disclosure by way of reference). It is noted that these connections are general and, unless specified otherwise, may be direct or indirect and that this specification is not intended to be limiting in this respect. Any reference to attached, fixed, connected or the like may include permanent, removable, temporary, partial, full and/or any other possible attachment option.

(38) No element, component, or method step in the present disclosure is intended to be dedicated to the public regardless of whether the element, component, or method step is explicitly recited in the claims. No claim element herein is to be construed under the provisions of 35 U.S.C. 112 (f) unless the element is expressly recited using the phrase “means for.” As used herein, the terms “comprise”, “comprising”, or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus.

(39) While various inventive aspects, concepts and features of the disclosures may be described and illustrated herein as embodied in combination in the exemplary embodiments, these various aspects, concepts, and features may be used in many alternative embodiments, either individually or in various combinations and sub-combinations thereof. Unless expressly excluded herein all such combinations and sub-combinations are intended to be in the scope of the present application. Still further, while various alternative embodiments as to the various aspects, concepts, and features of the disclosures--such as alternative materials, structures, configurations, methods, devices, and

components, and so on--may be described herein, such descriptions are not intended to be a complete or exhaustive list of available alternative embodiments, whether presently known or later developed. Those skilled in the art may readily adopt one or more of the inventive aspects, concepts, or features into additional embodiments and uses in the scope of the present application even if such embodiments are not expressly disclosed herein. For example, in the exemplary embodiments described above in the Detailed Description portion of the present specification, elements may be described as individual units and shown as independent of one another to facilitate the description. In alternative embodiments, such elements may be configured as combined elements.

Claims

1. A method for inspection of a plurality of propulsor blades for an aircraft propulsion system, the method comprising: rotating the plurality of propulsor blades about a rotational axis at a first rotation speed; shutting down the aircraft propulsion system; capturing image data for each propulsor blade of the plurality of propulsor blades for the shutdown aircraft propulsion system subsequent to a rotation speed of the plurality of propulsor blades decreasing to or below a second rotation speed which is less than the first rotation speed and greater than zero (0) RPM; identifying a presence or an absence of damage for each propulsor blade of the plurality of propulsor blades using the captured image data; and wherein capturing the image data for each propulsor blade of the plurality of propulsor blades includes capturing the image data for each propulsor blade of the plurality of propulsor blades with a camera disposed at a propulsor nose cone axially adjacent the plurality of propulsor blades, the propulsor nose cone rotationally fixed relative to the rotational axis.
2. The method of claim 1, wherein shutting down the aircraft propulsion system is performed with the aircraft propulsion system in a grounded condition.
3. The method of claim 1, wherein capturing the image data for each propulsor blade of the plurality of propulsor blades includes capturing the image data for a portion of a radial span of each propulsor blade of the plurality of propulsor blades.
4. The method of claim 3, wherein each propulsor blade extends radially between and to a root end and a tip end, and the portion is at the root end.
5. The method of claim 1, wherein each propulsor blade extends radially between and to a root end and a tip end, and capturing the image data for each propulsor blade of the plurality of propulsor blades includes capturing the image data for each propulsor blade of the plurality of propulsor blades with a plurality of cameras by capturing the image data with each cameras of the plurality of cameras for a different portion of a radial span of each propulsor blade of the plurality of propulsor blades relative to each other camera of the plurality of cameras.
6. The method of claim 1, wherein capturing the image data for each propulsor blade of the plurality of propulsor blades includes capturing the image data for each propulsor blade of the plurality of propulsor blades as the rotation speed decreases and while the rotation speed is greater than zero (0) RPM.
7. A method for inspection of a plurality of propulsor blades for an aircraft propulsion system, the method comprising: rotating the plurality of propulsor blades about a rotational axis at a rotation speed; identifying the rotation speed decreasing below a rotation speed threshold, the rotation speed threshold greater than zero (0) RPM; capturing image data for each propulsor blade of the plurality of propulsor blades in response to identification of the rotation speed decreasing below the rotation speed threshold; identifying a presence or an absence of damage for each propulsor blade of the plurality of propulsor blades using the captured image data; wherein capturing the image data for each propulsor blade of the plurality of propulsor blades includes capturing the image data for each propulsor blade of the plurality of propulsor blades with a camera disposed at a propulsor nose

cone axially adjacent the plurality of propulsor blades; and wherein the propulsor nose cone is rotationally fixed relative to the rotational axis.

8. The method of claim 7, wherein capturing the image data for each propulsor blade of the plurality of propulsor blades includes capturing the image data for a portion of a radial span of each propulsor blade of the plurality of propulsor blades.

9. The method of claim 8, wherein each propulsor blade extends radially between and to a root end and a tip end, and the portion is at the root end.

10. A method for inspection of a plurality of propulsor blades for an aircraft propulsion system, the method comprising: rotating the plurality of propulsor blades about a rotational axis at a rotation speed; shutting down the aircraft propulsion system; identifying, at a controller subsequent to shutting down the aircraft propulsion system, the rotation speed decreasing below a rotation speed threshold; controlling at least one camera, at the controller in response to identifying the rotation speed decreasing below the rotation speed threshold, to capture image data for each propulsor blade of the plurality of propulsor blades wherein the at least one camera is disposed at a propulsor nose cone axially adjacent the plurality of propulsor blades; and wherein the propulsor nose cone is rotationally fixed relative to the rotational axis.

11. The method of claim 10, further comprising identifying, at the controller, a presence or an absence of damage for each propulsor blade of the plurality of propulsor blades using the captured image data.

12. The method of claim 10, wherein identifying the presence or the absence of damage for each propulsor blade of the plurality of propulsor blades includes identifying, at the controller, a damage probability that each propulsor blade of the plurality of propulsor blades includes damage using the captured image data, the presence of damage for each propulsor blade of the plurality of propulsor blades identified where the probability is greater than a damage probability threshold.

13. The method of claim 10, further comprising transmitting the image data from the controller to an offboard system.

14. The method of claim 10, further comprising transmitting an indication of the presence or the absence of damage for each propulsor blade of the plurality of propulsor blades to an offboard system.

15. The method of claim 10, wherein shutting down the aircraft propulsion system is performed with the aircraft propulsion system in a grounded condition.
