

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411528
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Wen; Chun-Hung et al.

Portable electronic device

Abstract

A portable electronic device including a casing, a heat source, a fan, a heat dissipation fin, a heat pipe and a dust collecting member is provided. The heat source, the fan, the heat dissipation fin, and the heat pipe are located inside the casing, and the heat pipe is thermally coupled between the heat source and the heat dissipation fin. The dust collecting member is detachably assembled to the casing and is inserted into the casing. The heat dissipation fin is disposed as corresponding to the fan, and the dust collecting member is located between the fan and the heat dissipation fin.

Inventors: Wen; Chun-Hung (New Taipei, TW), Chen; Chun-Hsien (New Taipei, TW)

Applicant: Acer Incorporated (New Taipei, TW)

Family ID: 90834803

Assignee: Acer Incorporated (New Taipei, TW)

Appl. No.: 18/492791

Filed: October 24, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240143038 A1	May. 02, 2024

Foreign Application Priority Data

TW	111141740	Nov. 02, 2022
----	-----------	---------------

Publication Classification

Int. Cl.: G06F1/16 (20060101); G06F1/20 (20060101); H05K7/20 (20060101)

U.S. Cl.:

CPC **G06F1/1656** (20130101); **G06F1/203** (20130101); **H05K7/20172** (20130101);
H05K7/20409 (20130101);

Field of Classification Search

CPC: G06F (1/203); G06F (1/20); H05K (7/20145); H05K (7/20181); H05K (7/20136); H05K (7/20154); H05K (7/20172); H05K (7/20209); F28F (19/008); F28F (3/02); F28F (19/01)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7345874	12/2007	Cheng	165/104.33	G06F 1/20
8055392	12/2010	Kitamura	123/41.1	G05B 23/0235
8256495	12/2011	Hattori	165/200	G06F 1/203
8717756	12/2013	Ito	361/679.48	G06F 1/203
2009/0223649	12/2008	Lee	165/95	F28G 1/08
2010/0073867	12/2009	Tachikawa	361/679.48	G06F 1/203
2010/0079947	12/2009	Aoki	361/695	G06F 1/203
2010/0097764	12/2009	Likubo	361/697	G06F 1/20
2013/0027881	12/2012	Goto	361/697	G06F 1/203

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
207475767	12/2017	CN	N/A
207965748	12/2017	CN	N/A
200704353	12/2006	TW	N/A
201443624	12/2013	TW	N/A

Primary Examiner: Rathod; Abhishek M

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims the priority benefit of Taiwan application serial no. 111141740, filed on Nov. 2, 2022. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

Technical Field

(2) The disclosure relates to a portable electronic device, and in particular to a portable electronic device with dust collection design.

DESCRIPTION OF RELATED ART

(3) The host of a common notebook computer is provided with an air-cooled forced heat dissipation mechanism to quickly dissipate the heat inside the host to the outside. The air-cooled forced heat dissipation mechanism includes a fan, a heat dissipation fin, and a heat pipe. A condensation end of the heat pipe is thermally coupled to the heat dissipation fin, and the heat dissipation fin

corresponds to the air outlet configuration of the fan. In detail, the heat generated by the heat source inside the host can be transferred to the condensation end through the evaporation end of the heat pipe, and then transferred to the heat dissipation fin from the condensation end. The cold air blown from the air outlet of the fan to the heat dissipation fin exchanges heat with the heat dissipation fin to form hot air, which is then forced out to the outside. In this way, heat accumulation inside the host is avoided, so as to maintain the computing performance of the notebook computer.

(4) However, the fan introduces cold air into the host from the outside, and it is difficult to avoid dust from the outside being also introduced into the host and blown to the heat dissipation fin. Over a long period of time, dust will accumulate on the heat dissipation fin, resulting in a decline in heat dissipation efficiency.

SUMMARY

(5) The invention provides a portable electronic device, which not only has good heat dissipation efficiency, but also is convenient for users to operate.

(6) A portable electronic device including a casing, a heat source, a fan, a heat dissipation fin, a heat pipe and a dust collecting member is provided. The heat source, the fan, the heat dissipation fin, and the heat pipe are located inside the casing, and the heat pipe is thermally coupled between the heat source and the heat dissipation fin. The dust collecting member is detachably assembled to the casing and is inserted into the casing. The heat dissipation fin is disposed as corresponding to the fan, and the dust collecting member is located between the fan and the heat dissipation fin.

(7) A portable electronic device including a first body, a second body pivoted to the first body and a dust collecting member is provided. The first body includes a casing, a heat source, a fan, a heat dissipation fin, a heat pipe and a dust collecting member. The heat source, the fan, the heat dissipation fin, and the heat pipe are located inside the casing, and the heat pipe is thermally coupled between the heat source and the heat dissipation fin. The dust collecting member is detachably assembled to the casing and is inserted into the casing. The heat dissipation fin is disposed as corresponding to the fan, and the dust collecting member is located between the fan and the heat dissipation fin.

(8) Based on the above, the portable electronic device of the invention is provided with a dust collecting member between the fan and the heat dissipation fin to collect the dust blown from the fan to the heat dissipation fin, so as to prevent dust from accumulating on the heat dissipation fin and improve heat dissipation efficiency. On the other hand, the dust collecting member is detachably installed on the casing, and the user can periodically remove the dust collecting member from the casing. After removing the dust adsorbed or attached to the dust collecting member, install the dust collecting member back into the casing. Therefore, it is not only easy and intuitive to operate, but also conducive to maintaining the dust collection effect.

(9) In order to make the above-mentioned features and advantages of the present application more obvious and easier to understand, the following specific examples are given, and are described in detail as follows in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a partially enlarged schematic diagram of a portable electronic device according to an embodiment of the invention.

(2) FIG. 2 is a partial cross-sectional schematic diagram of the portable electronic device in FIG. 1.

(3) FIG. 3 is a partially enlarged schematic diagram of the detached casing of a dust collecting member of FIG. 1.

(4) FIG. 4 is a schematic diagram of a dust collecting member of another embodiment of the

invention.

(5) FIG. 5 is a schematic cross-sectional view of a dust collecting member of another embodiment of the invention.

DESCRIPTION OF THE EMBODIMENTS

(6) FIG. 1 is a partially enlarged schematic diagram of a portable electronic device according to an embodiment of the invention. FIG. 2 is a partial cross-sectional schematic diagram of the portable electronic device in FIG. 1. FIG. 3 is a partially enlarged schematic diagram of the detached casing of the dust collecting member of FIG. 1. Referring to FIG. 1, in the embodiment, the portable electronic device **100** can be a notebook computer, and includes a first body **110**, a second body **120** pivoted to the first body **110** and a dust collecting member **130** detachably installed on the first body **110**. The first body **110** has logic operation and data access capabilities, and the second body **120** has display capabilities.

(7) As shown in FIG. 1 to FIG. 3, first body **110** comprises a casing **111**, heat source **112**, a fan **113**, a heat dissipation fin **114** and a heat pipe **115**. And the heat source **112**, the fan **113**, the heat dissipation fin **114** and the heat pipe **115** are located in the casing **111**. The heat dissipation fin **114** is set corresponding to the fan **113**, and an evaporation end **115a** and a condensation end **115b** of the heat pipe **115** are thermally coupled to the heat source **112** and the heat dissipation fin **114** respectively. The casing **111** has a bottom surface **111a**, a rear side **111b** connected to the bottom surface **111a**, an air inlet hole **111c** located on the bottom surface **111a**, a mounting opening **111d** located on the bottom surface **111a** and a heat dissipation hole **111e** located on the rear side **111b**. The dust collecting member **130** is detachably mounted on the bottom surface **111a** of the casing **111**, and inserted into the inside of the casing **111** through the mounting opening **111d**.

(8) The fan **113** can be a centrifugal fan, wherein the heat dissipation fin **114** is set corresponding to the fan **113**, and the dust collecting member **130** is located between the fan **113** and the heat dissipation fin **114**. In detail, the fan **113** has an air inlet **113a** corresponding to the air inlet hole **111c** and an air outlet **113b** corresponding to the heat dissipation fin **114**. The heat dissipation fin **114** is set corresponding to the heat dissipation hole **111e**, and is located between the air outlet **113b** of the fan **113** and the heat dissipation hole **111e** of the casing **111**. On the other hand, the mounting opening **111d** is located between the air inlet hole **111c** and the heat dissipation hole **111e**. The dust collecting member **130** inserted into the casing **111** through the mounting opening **111d** is located between the air inlet hole **111c** and the heat dissipation hole **111e**, and is located between the air outlet **113b** of the fan **113** and the heat dissipation fin **114**.

(9) When the cold air is blown from the air outlet **113b** of the fan **113** to the heat dissipation fin **114**, the cold air and the dust flowing with the cold air will first flow through the dust collecting member **130**, and the dust will be adsorbed or attached to the dust collecting member **130**. In this way, dust is prevented from being blown to the heat dissipation fin **114** and accumulated in the heat dissipation fin **114**, so as to improve heat dissipation efficiency. On the other hand, the user can regularly disassemble the dust collecting member **130** from the casing **111**, and install the dust collecting member **130** back to the casing **111** after removing the dust adsorbed or attached to the dust collecting member **130**. Therefore, it is not only easy and intuitive to operate, but also conducive to maintaining the dust collection effect.

(10) As shown in FIG. 2 and FIG. 3, in the embodiment, the dust collecting member **130** includes a foot pad part **131** and a dust collecting part **132** connected to the foot pad part **131**. The foot pad part **131** can be made of rubber, silicone or other suitable materials, and protrudes from the bottom surface **111a** of the casing **111**. Since the foot pad part **131** protrudes from the bottom surface **111a** of the casing **111**, the foot pad part **131** can support the casing **111**. Therefore, there is a gap between the bottom surface **111a** of the casing **111** and the working plane, so as to increase the flow rate of the fan **113** to introduce the cold air from outside to the inside of the casing **111** through the air inlet hole **111c**.

(11) On the other hand, the dust collecting part **132** is inserted into the casing **111**, and is located

between the air outlet **113b** of the fan **113** and the heat dissipation fin **114**. The dust collecting part **132** can be a metal grille, and has a plurality of grooves **133**, which is not only beneficial for collecting dust, but also beneficial for blowing cold air to the heat dissipation fin **114**.

(12) As shown in FIG. 2 and FIG. 3, in the embodiment, the foot pad part **131** has a first mounting end **134** and a second mounting end **135** relative to the first mounting end **134**, and the casing **111** also has a first positioning portion **111f** and a second positioning portion **111g** relative to the first positioning portion **111f**. The first positioning portion **111f** and the second positioning portion **111g** are located in the mounting opening **111d**, wherein the first mounting end **134** is installed in the first positioning portion **111f**, and the second mounting end **135** is installed in the second positioning portion **111g**. The first mounting end **134** and first positioning portion **111f** can be a combination of two lock holes, and the first mounting end **134** and first positioning portion **111f** are fixed by a screw **111h** locking. In addition, the second mounting end **135** and the second positioning portion **111g** can be a combination of card protrusions and card slots engaged with each other.

(13) In another embodiment, the first mounting end and the first positioning portion can be a combination of a card protrusion and a card slot that engage with each other. In addition, the second mounting end and the second positioning portion can be a combination of two lock holes, and the second mounting end and the second positioning portion can be fixed by the screw locking.

(14) In another embodiment, the first mounting end and the first positioning portion can be a combination of two lock holes, and the first mounting end and the first positioning portion are fixed by the screw locking. Similarly, the second mounting end and the second positioning portion can be a combination of two lock holes, and the second mounting end and the second positioning portion are fixed by the screw locking.

(15) In another embodiment, the first mounting end and the first positioning portion may be a combination of card protrusions and card slots engaged with each other. Similarly, the second mounting end and the second positioning portion may be a combination of card protrusions and card slots engaged with each other.

(16) FIG. 4 is a schematic diagram of a dust collecting member of another embodiment of the invention. The design principle of the dust collecting member **130a** of the embodiment is substantially the same as that of the dust collecting member **130** of the previous embodiment. The difference is that in this embodiment, the dust collecting part **132a** of the dust collecting member **130a** can be a metal mesh plate connected to the foot pad part **131a**, and has a plurality of openings **133a** to facilitate dust collection and airflow.

(17) FIG. 5 is a schematic cross-sectional view of a dust collecting member of another embodiment of the invention. The design principle of the dust collecting member **130b** of the embodiment is substantially the same as that of the dust collecting member **130** of the previous embodiment. The difference is that in this embodiment, the dust collecting part **132b** of the dust collecting member **130b** includes a metal mesh plate **1301**, a first positioning frame **1302** and a second positioning frame **1303** relative to the first positioning frame **1302**. The first positioning frame **1302** and the second positioning frame **1303** are connected to the foot pad part **131b**, and the metal mesh plate **1301** is clamped and positioned between the first positioning frame **1302** and the second positioning frame **1303**. The metal mesh plate **1301** has a plurality of openings **133b** to facilitate dust collection and airflow. Further, the first positioning frame **1302** has ventilation openings **1304** connected to the plurality of openings **133b**, and the second positioning frame **1303** has ventilation openings **1305** connected to the plurality of openings **133b** to facilitate airflow.

(18) In summary, the portable electronic device of the invention is provided with a dust collecting member between the fan and the heat dissipation fin to collect the dust blown from the fan to the heat dissipation fin, so as to prevent dust from accumulating on the heat dissipation fin and improve heat dissipation efficiency. On the other hand, the dust collecting member is detachably installed on the casing, and the user can periodically remove the dust collecting member from the

casing. After removing the dust adsorbed or attached to the dust collecting member, install the dust collecting member back into the casing. Therefore, it is not only easy and intuitive to operate, but also conducive to maintaining the dust collection effect. In addition, the dust collecting member includes a protruding foot pad part facing the bottom surface of the casing, and is used to support the casing. Therefore, there is a gap between the bottom surface of the casing and the working plane to improve the flow of cold air from the outside into the inside of the casing by the fan. (19) Although the present application has been disclosed as above with embodiments, it is not intended to limit the present application, any person with ordinary knowledge in the technical field, without departing from the spirit and scope of the present application, can make some changes. Therefore, the protection scope of the present application shall be determined by the scope of the claims.

Claims

1. A portable electronic device, comprising: a casing; heat source; a fan; a heat dissipation fin; a heat pipe, wherein the heat source, the fan, the heat dissipation fin, and the heat pipe are located inside the casing, and the heat pipe is thermally coupled between the heat source and the heat dissipation fin; and a dust collecting member, detachably assembled to the casing and is inserted into the casing, wherein the heat dissipation fin is disposed as corresponding to the fan, and the dust collecting member is located between the fan and the heat dissipation fin; wherein the casing has a bottom surface and a mounting opening located on the bottom surface, and the dust collecting member is detachably mounted on the bottom surface, and the dust collecting member is inserted inside the casing through the mounting opening; wherein the dust collecting member comprises a foot pad part and a dust collecting part connected to the foot pad part, and the foot pad part protrudes from the bottom surface, the dust collecting part is inserted inside the casing, and is located between the fan and the heat dissipation fin; wherein the dust collecting part comprises a metal mesh plate, a first positioning frame and a second positioning frame opposite the first positioning frame, the first positioning frame and the second positioning frame are connected to the foot pad part, and the metal mesh plate is clamped and positioned between the first positioning frame and the second positioning frame.
2. The portable electronic device according to claim 1, wherein the casing also has a rear side connected to the bottom surface, an air inlet hole located on the bottom surface and a heat dissipation hole located on the rear side, and the mounting opening is located between the air inlet hole and the heat dissipation hole.
3. The portable electronic device according to claim 2, wherein the fan has an air inlet corresponding to the air inlet hole and an air outlet corresponding to the heat dissipation fin, and the heat dissipation fin is located between the air outlet and the heat dissipation hole.
4. The portable electronic device according to claim 2, wherein the fan has an air outlet corresponding to the heat dissipation fin, and the dust collecting member is located between the air outlet and the heat dissipation fin.
5. The portable electronic device according to claim 1, wherein the dust collecting part comprises a metal grille or a metal mesh plate.
6. The portable electronic device according to claim 1, wherein the foot pad part has a first mounting end and a second mounting end opposite to the first mounting end, and the casing further has a first positioning portion and a second positioning portion relative to the first positioning portion, and the first positioning portion and the second positioning portion are located within the mounting opening, wherein the first mounting end is mounted on the first positioning portion, and the second mounting end is mounted on the second positioning portion.
7. The portable electronic device according to claim 6, wherein the first mounting end and the first positioning portion are a combination of two locking holes, and the second mounting end and the

second positioning portion are a combination of a card protrusion and a card slot, the first mounting end and the first positioning portion are secured to each other by screw locking.

8. A portable electronic device, comprising: a first body, comprises: a casing; heat source; a fan; a heat dissipation fin; and a heat pipe, wherein the heat source, the fan, the heat dissipation fin, and the heat pipe are located inside the casing, and the heat pipe is thermally coupled between the heat source and the heat dissipation fin; a second body, pivoted to the first body; and a dust collecting member, detachably assembled to the casing and is inserted into the casing, wherein the heat dissipation fin is disposed as corresponding to the fan, and the dust collecting member is located between the fan and the heat dissipation fin; wherein the casing has a bottom surface and a mounting opening located on the bottom surface, and the dust collecting member is detachably mounted on the bottom surface, and the dust collecting member is inserted inside the casing through the mounting opening; wherein the dust collecting member comprises a foot pad part and a dust collecting part connected to the foot pad part, and the foot pad part protrudes from the bottom surface, the dust collecting part is inserted inside the casing, and is located between the fan and the heat dissipation fin; wherein the dust collecting part comprises a metal mesh plate, a first positioning frame and a second positioning frame opposite the first positioning frame, the first positioning frame and the second positioning frame are connected to the foot pad part, and the metal mesh plate is clamped and positioned between the first positioning frame and the second positioning frame.
