

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411918
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Dravneek; Victoria Lynn et al.

Performing secure data interactions in a virtual environment

Abstract

A system includes a memory and a processor coupled to the memory. The processor receives a user credential associated with a user and authorizes an avatar of the user to enter a virtual environment. The processor monitors a plurality of data interactions associated with the first user that are performed in the virtual environment, records information relating to a set of parameters that correspond to a first user profile associated with the first user and determines a first confidence indicator for the first user relating to the first user profile. The processor receives a request from a second user for the first confidence indicator, obtains the first confidence indicator and transmits the obtained first confidence indicator to a user device of the second user.

Inventors: Dravneek; Victoria Lynn (Charlotte, NC), Kurian; Manu Jacob (Dallas, TX), Maxim; Ana (Arlington, VA)

Applicant: Bank of America Corporation (Charlotte, NC)

Family ID: 91079896

Assignee: Bank of America Corporation (Charlotte, NC)

Appl. No.: 18/057984

Filed: November 22, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240169037 A1	May. 23, 2024

Publication Classification

Int. Cl.: G06F21/31 (20130101); G06F3/04815 (20220101); G06T13/40 (20110101); H04L67/306 (20220101)

U.S. Cl.:

CPC **G06F21/31** (20130101); **G06F3/04815** (20130101); **G06T13/40** (20130101);
H04L67/306 (20130101);

Field of Classification Search

CPC: G06F (21/31); G06F (3/04815); G06T (13/40); H04L (67/306)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6347993	12/2001	Kondo	434/167	A63F 13/95
8082297	12/2010	Syvain et al.	N/A	N/A
8631417	12/2013	Mendes Da Costa et al.	N/A	N/A
8676659	12/2013	Shnowske	705/26.1	G06Q 30/00
9165426	12/2014	Jones et al.	N/A	N/A
9203860	12/2014	Casillas	N/A	H04L 63/1441
9342211	12/2015	Deluca et al.	N/A	N/A
9355110	12/2015	Chi	N/A	G02B 27/0172
10326667	12/2018	Jones et al.	N/A	N/A
10587584	12/2019	Vikramaratne et al.	N/A	N/A
10610787	12/2019	Hamilton et al.	N/A	N/A
10931650	12/2020	Mccown et al.	N/A	N/A
10981069	12/2020	Kawachiya et al.	N/A	N/A
11170003	12/2020	Wu et al.	N/A	N/A
11212362	12/2020	Dhara	N/A	H04L 67/306
11468446	12/2021	Li	N/A	G06F 17/16
2007/0254631	12/2006	Spooner	N/A	N/A
2008/0270292	12/2007	Ghosh	705/38	G06Q 40/02
2008/0279416	12/2007	Lo	382/100	G06V 40/1365
2010/0250383	12/2009	Frazier et al.	N/A	N/A
2011/0072367	12/2010	Bauer	N/A	N/A
2011/0126272	12/2010	Betzler	726/6	G06F 21/41
2012/0185916	12/2011	Chae	726/2	G06F 21/316
2013/0041713	12/2012	Henrich	705/7.28	G06Q 10/0635
2014/0026078	12/2013	Dawson et al.	N/A	N/A
2015/0052453	12/2014	Yu	715/753	H04L 67/535
2015/0088717	12/2014	Votaw	705/35	G06Q 50/01
2015/0199645	12/2014	Sulur	705/342	G06Q 10/10
2015/0310204	12/2014	Pruthi	726/25	G06F 21/41
2015/0339494	12/2014	Young	726/28	G06F 21/6263
2016/0350859	12/2015	Dintenfass	N/A	G06Q 40/06
2016/0358170	12/2015	Kurian	N/A	G06Q 20/385
2016/0358258	12/2015	Dintenfass	N/A	G06Q 40/06
2017/0235848	12/2016	Van Dusen	705/12	G06Q 10/101
2018/0104595	12/2017	Kawachiya et al.	N/A	N/A
2018/0123816	12/2017	Tandon et al.	N/A	N/A

2018/0307303	12/2017	Powderly	N/A	G06F 3/017
2018/0337908	12/2017	Rappaport	N/A	G06F 21/30
2018/0342070	12/2017	Chen	N/A	G06V 20/52
2019/0027141	12/2018	Strong	N/A	G10L 15/1815
2019/0289025	12/2018	Kursun	N/A	G06F 16/285
2019/0327237	12/2018	Bar	N/A	G06F 21/316
2019/0370551	12/2018	Mao	N/A	G06V 20/52
2020/0068031	12/2019	Kursun	N/A	H04W 24/02
2020/0098155	12/2019	Chou	N/A	G06T 13/40
2020/0169483	12/2019	Kursun	N/A	G06Q 20/3678
2020/0338458	12/2019	Huang et al.	N/A	N/A
2021/0012112	12/2020	Ulbricht	N/A	G06V 20/10
2021/0042748	12/2020	Sepulveda et al.	N/A	N/A
2021/0406541	12/2020	Ulbricht	N/A	G06V 30/274
2022/0335221	12/2021	Baumgartner	N/A	G06F 40/279
2023/0092487	12/2022	Kalbasi	455/411	H04W 4/027
2023/0410129	12/2022	Varghese	N/A	H04L 63/1425

OTHER PUBLICATIONS

NPL Search History (Year: 2024). cited by examiner

Primary Examiner: King; John B

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates generally to network communication, and more specifically to performing secure data interactions in a virtual environment.

BACKGROUND

(2) In a network environment, user devices are in data communication with other user devices that may be distributed anywhere in the world. These network environments allow data and information to be shared among these devices. Some of the technical challenges that occur when data is exchanged between devices are controlling data leakage, unauthorized access to data, and preventing malicious activities. Data storing user devices, such as computers, laptops, augmented reality devices, virtual reality devices, and smartphones, are vulnerable to attacks. This vulnerability poses several network security challenges. Existing systems are typically unable to detect a malicious attack until after the attack has occurred. For example, a bad actor may pretend to be another user in a virtual environment which then allows the bad actor to gain access to other users' information.

SUMMARY

(3) The system and methods implemented by the system as disclosed in the present disclosure provide technical solutions to the technical problems discussed above by allowing a user to securely access a virtual environment and perform secure data interactions in the virtual environment. The disclosed system and methods provide several practical applications and technical advantages.

(4) For example, the disclosed system and methods provide the practical application of improving interoperability of real-world systems and virtual world systems (e.g., metaverse systems) so that information may be seamlessly shared between these systems to implement data security,

authorization of data interactions, and other data interactions performed in real-world and virtual environments. For example, user information collected from the user and/or assigned to the user in a real-world environment may be used in a virtual environment (e.g., metaverse environment) to authenticate the user before allowing the user to access the virtual environment and perform any kind of action or interaction within the virtual environment. This process provides improved information security because it authenticates that an avatar is associated with the user and not an unauthorized party and that the user is authorized to access the virtual environment.

(5) The disclosed system and methods provide an additional practical application of improving information security in the virtual environment and/or real-world environment based on data interactions performed by the users in the virtual environment. As described in embodiments of the present disclosure, a first user of the virtual environment is assigned one or more confidence indicators based on data interactions performed by the first user and/or related to the first user in the virtual environment. A confidence indicator associated with the first user may be indicative of a credibility/reputation of the first user in the virtual environment, wherein a higher confidence indicator indicates a higher credibility/reputation. Data interactions with the first user or relating to the first user in the virtual environment and/or real-world environment may be performed based on one or more confidence indicators of the first user. For example, a data interaction relating to the first user that is to be performed in the virtual environment or the real-world environment may be authorized when a confidence indicator of the first user equals or exceeds a threshold value. Thus, the disclosed system and methods help ensure that only those data interactions that involve users having high credibility/reputation are authorized to occur in the virtual environment.

(6) The disclosed system and methods provide an additional practical application of improving information security in the virtual environment and/or real-world environment by limiting user data that can be accessed by users in the virtual environment. As described in accordance with embodiments of the disclosure, virtual-world server may be configured to provide upon request from a second user or entity one or more confidence indicators associated with one or more respective user profiles of the first user. In one embodiment, virtual-world server may provide to the second user or entity only those confidence indicators the second user or entity is authorized to obtain. For example, virtual-world server may register the second user to obtain confidence indicators of other users (e.g., first user) associated with certain user profiles. In this case, virtual-world server may provide to the second user confidence indicators associated with only those user profiles the second user is registered to receive. The virtual-world server may not provide the second user confidence indicators associated with those user profiles the second user is not registered to receive. This limits users and entities in the virtual environment to obtain only that information about other users which is relevant to their needs. By controlling dissemination of user information, virtual-world server improves data security in the virtual environment.

(7) Thus, the disclosed system and methods improve data security in the virtual environment. By improving data security in virtual environment, the disclosed system and methods generally improve technology related to performing secure data interactions in a virtual environment.

(8) The disclosed system and methods provide the additional practical application of saving memory resources. The seamless data flow between the real-world systems and virtual-world systems as a result of interoperability of these systems allows each system to store less data by avoiding the need to store the same data (e.g., authentication data, login credentials, etc.) in both systems, as data stored in one system can be accessed, or otherwise leveraged, by the other system. This saves memory resources by avoiding duplication of data. The saving of memory resources may leave more system memory for storing other data used in other technical operations. This provides the additional technical advantage of improving processing efficiency of computing systems that manage the real-world and virtual word environments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) For a more complete understanding of this disclosure, reference is now made to the following brief description, taken in connection with the accompanying drawings and detailed description, wherein like reference numerals represent like parts.
- (2) FIG. 1 is a schematic diagram of a system, in accordance with certain aspects of the present disclosure;
- (3) FIG. 2 is a block diagram of an embodiment of the first user device used by the system of FIG. 1; and
- (4) FIG. 3 illustrates a flowchart of an example method 300 for performing secure data interactions in a virtual environment 102, in accordance with one or more embodiments of the present disclosure.

DETAILED DESCRIPTION

Example System

- (5) FIG. 1 is a schematic diagram of a system 100, in accordance with certain aspects of the present disclosure. System 100 may include a first user device 104, a second user device 106, real-world server 130, and virtual-world server 150, each connected to a network 180. A first user 110 is associated with the first user device 104 and a second user 112 is associated with the second user device 106. The system 100 may be communicatively coupled to the communication network 180 and may be operable to transmit data between each one of the first user device 104, second user device 106, real-world server 130, and virtual-world server 150 through the communication network 180.
- (6) In general, the system 100 may improve interoperability of real-world systems and virtual world systems (e.g., metaverse systems) so that information may be seamlessly shared between these systems to implement data security, authorization of data interactions, and other data interactions performed in real-world and virtual environments. For example, user information collected from the user and/or assigned to the user in a real-world environment may be used in a virtual environment 102 (e.g., metaverse environment) to authenticate the first user 110 before allowing the first user 110 to access the virtual environment 102 and perform any kind of action or interaction within the virtual environment 102. This process provides improved information security because it authenticates that a first avatar 114 is associated with the first user 110, not an unauthorized party, and that the first user 110 is authorized to access the virtual environment 102. Additionally or alternatively, system 100 may improve data and network security in the virtual environment 102. As described in embodiments of the present disclosure, a first user 110 of the virtual environment 102 is assigned one or more confidence indicators 158 based on data interactions performed by the first user 110 and/or related to the first user 110 in the virtual environment 102. A confidence indicator 158 associated with the first user 110 may be indicative of a credibility/reputation of the first user 110 in the virtual environment 102, wherein a higher confidence indicator 158 indicates a higher credibility/reputation. Data interactions with the first user 110 or relating to the first user 110 in the virtual environment 102 may be performed based on one or more confidence indicators 158 of the first user 110. For example, a data interaction relating to the first user 110 may be authorized when a confidence indicator 158 of the first user 110 equals or exceeds a threshold value. Thus, system 100 helps ensure that only those data interactions that involve users having high credibility/reputation are authorized to occur in the virtual environment 102.
- (7) It may be noted that the terms “real-world” and “real-world environment” in this disclosure refer to any non-virtual environment where users (e.g., users 110 and 112) can physically interact with real persons and objects. A real-world data interaction may refer to any data interaction

performed outside the virtual environment **102** (e.g., a metaverse environment). Further, it may be noted that while certain embodiments of the present disclosure may be described in the context of a metaverse environment which is an example of a virtual environment **102**, the methods discussed in this disclosure apply to any other virtual environment **102**. The terms “virtual environment” and “metaverse environment” are used interchangeably throughout this disclosure. Furthermore, it may be noted that while certain embodiments of this disclosure describe one or more operations in relation to the first user **110**, these embodiments apply to any other user (e.g., second user **112**) connected to network **180**.

(8) The first user **110** may access the virtual environment **102** (e.g., a metaverse environment) through the first user device **104**. The first user device **104** is configured to display a two-dimensional (2D) or three-dimensional (3D) representation of the virtual environment **102** to the first user **110**. Examples of a virtual environment **102** may include, but are not limited to, a graphical or virtual representation of a metaverse, a map, a building interior, a landscape, a fictional location, an alternate reality, or any other suitable type of location or environment. The virtual environment **102** may be configured to use realistic or non-realistic physics for the motion of objects within the virtual environment **102**. For example, some virtual environments **102** may be configured to use gravity whereas other virtual environments **102** be configured not to use gravity. Within the virtual environment **102**, each user may be associated with an avatar (such as the first avatar **114** for the first user **110**). An avatar is a graphical representation of a user at a virtual location within the virtual environment **102**. In embodiments, the virtual location of the avatar may be correlated to the physical location of a user in the real-world environment. Examples of an avatar may include, but are not limited to, a person, an animal, or an object. In some embodiments, the features and characteristics of the avatar may be customizable and user-defined. For example, the size, shape, color, attire, accessories, or any other suitable type of appearance features may be specified by a user. By using an avatar, a user is able to move within the virtual environment **102** to interact with one or more avatars and objects within the virtual environment **102** while independently remaining at a physical location in the real-world environment or being in transit in the real-world environment.

(9) While engaging in the virtual environment **102** via the first avatar **114**, the first user **110** may interact with a plurality of other users, objects and/or entities through a respective avatar. For example, the second user **112** may attempt to engage in an interaction session with the first avatar **114** through a second avatar **116** associated with the second user **112**. In the real-world environment, the second user **112** may be physically located at a distance away from the first user **110**. The second user **112** may access the virtual environment **102** through the second user device **106** to control the second avatar **116** and attempt to engage in an interaction session with the first user **110** through the first avatar **114**.

(10) Before the interaction between the first avatar **114** and the second avatar **116** occurs, the virtual-world server **150** may authenticate that the first avatar **114** is associated with the first user **110** and not an unauthorized third-party. For example, the first user **110** may be required to sign into a secure portal that provides access to a data file (e.g., real-world data file **134** and/or virtual data file **160**) associated with the first user **110**. As shown in FIG. 1, the real-world data file **134** of the first user **110** is stored and managed by the real-world server **130** and the virtual data file **160** of the first user **110** is stored and managed by the virtual-world server **150**. In one or more embodiments, the virtual-world server **150** may employ single sign-on (SSO), multifactor authentication, or any other suitable authentication scheme in order to allow the first user **110** access to the virtual data file **160** and/or the real-world data file **134**. The virtual data file **160** and the real-world data file **134** may include virtual data objects **162** and real-world data objects **136** respectively owned by the first user **110**. The real-world server **130** and the virtual-world server **150** may store other information related to the first user **110** including, but not limited to, user profile information, account information (e.g., including identity and other details relating to the

respective data files **134** and **160**), avatar information, digital assets (e.g., respective real-world data objects **136** and virtual data objects **162**) information, or any other suitable type of information that is associated with a user within the virtual environment **102** and/or the real-world environment.

(11) As shown in FIG. 1, virtual-world server **150** comprises a processor **170**, a memory **174**, and a network interface **172**. The processor **170** comprises one or more processors operably coupled to the memory **174**. The processor **170** is any electronic circuitry including, but not limited to, state machines, one or more central processing unit (CPU) chips, logic units, cores (e.g. a multi-core processor), field-programmable gate array (FPGAs), application specific integrated circuits (ASICs), or digital signal processors (DSPs). The processor **170** may be a programmable logic device, a microcontroller, a microprocessor, or any suitable combination of the preceding. The processor **170** is communicatively coupled to and in signal communication with the memory **174**. The one or more processors are configured to process data and may be implemented in hardware or software. For example, the processor **170** may be 8-bit, 16-bit, 32-bit, 64-bit or of any other suitable architecture. The processor **170** may include an arithmetic logic unit (ALU) for performing arithmetic and logic operations, processor registers that supply operands to the ALU and store the results of ALU operations, and a control unit that fetches instructions from memory and executes them by directing the coordinated operations of the ALU, registers and other components.

(12) The one or more processors are configured to implement various instructions. For example, the one or more processors are configured to execute instructions (e.g., virtual-world server instructions **176**) to implement the virtual-world server **150**. In this way, processor **170** may be a special-purpose computer designed to implement the functions disclosed herein. In one or more embodiments, the virtual-world server **150** is implemented using logic units, FPGAs, ASICs, DSPs, or any other suitable hardware. The virtual-world server **150** is configured to operate as described with reference to FIGS. 1 and 3. For example, the processor **170** may be configured to perform at least a portion of the method **300** as described in FIG. 3.

(13) The memory **174** comprises one or more disks, tape drives, or solid-state drives, and may be used as an over-flow data storage device, to store programs when such programs are selected for execution, and to store instructions and data that are read during program execution. The memory **174** may be volatile or non-volatile and may comprise a read-only memory (ROM), random-access memory (RAM), ternary content-addressable memory (TCAM), dynamic random-access memory (DRAM), and static random-access memory (SRAM).

(14) The memory **174** is operable to store the user credential **152**, user profiles **154**, profile parameters **156**, confidence indicators **158**, virtual data file **160**, virtual data objects **162**, and the virtual-world server instructions **176**. The virtual-world server instructions **176** may include any suitable set of instructions, logic, rules, or code operable to execute the virtual-world server **150**.

(15) The network interface **172** is configured to enable wired and/or wireless communications. The network interface **172** is configured to communicate data between the virtual-world server **150** and other devices, systems, or domains (e.g. user devices **104** and **106** and the real-world server **130**). For example, the network interface **172** may comprise a Wi-Fi interface, a LAN interface, a WAN interface, a modem, a switch, or a router. The processor **170** is configured to send and receive data using the network interface **172**. The network interface **172** may be configured to use any suitable type of communication protocol as would be appreciated by one of ordinary skill in the art.

(16) The real-world server **130** comprises a processor **140**, a memory **144**, and a network interface **142**. The processor **140** comprises one or more processors operably coupled to the memory **144**. The processor **140** is any electronic circuitry including, but not limited to, state machines, one or more central processing unit (CPU) chips, logic units, cores (e.g. a multi-core processor), field-programmable gate array (FPGAs), application specific integrated circuits (ASICs), or digital signal processors (DSPs). The processor **140** may be a programmable logic device, a microcontroller, a microprocessor, or any suitable combination of the preceding. The processor **140** is communicatively coupled to and in signal communication with the memory **144**. The one or

more processors are configured to process data and may be implemented in hardware or software. For example, the processor **140** may be 8-bit, 16-bit, 32-bit, 64-bit or of any other suitable architecture. The processor **140** may include an arithmetic logic unit (ALU) for performing arithmetic and logic operations, processor registers that supply operands to the ALU and store the results of ALU operations, and a control unit that fetches instructions from memory and executes them by directing the coordinated operations of the ALU, registers and other components.

(17) The one or more processors are configured to implement various instructions. For example, the one or more processors are configured to execute instructions (e.g., real-world server instructions **146**) to implement the real-world server **130**. In this way, processor **140** may be a special-purpose computer designed to implement the functions disclosed herein. In one or more embodiments, the real-world server **130** is implemented using logic units, FPGAs, ASICs, DSPs, or any other suitable hardware. The real-world server **130** is configured to operate as described with reference to FIGS. **1** and **3**. For example, the processor **140** may be configured to perform at least a portion of the method **300** as described in FIG. **3**.

(18) The memory **144** comprises one or more disks, tape drives, or solid-state drives, and may be used as an over-flow data storage device, to store programs when such programs are selected for execution, and to store instructions and data that are read during program execution. The memory **144** may be volatile or non-volatile and may comprise a read-only memory (ROM), random-access memory (RAM), ternary content-addressable memory (TCAM), dynamic random-access memory (DRAM), and static random-access memory (SRAM).

(19) The memory **144** is operable to store information relating to user data **132**, real-world data file **134**, real-world data objects **136**, user credential **152**, and the real-world server instructions **146**. The real-world server instructions **146** may include any suitable set of instructions, logic, rules, or code operable to execute the real-world server **130**.

(20) The network interface **142** is configured to enable wired and/or wireless communications. The network interface **142** is configured to communicate data between the real-world server **130** and other devices, systems, or domains (e.g. user devices **104** and **106** and the virtual-world server **150**). For example, the network interface **142** may comprise a Wi-Fi interface, a LAN interface, a WAN interface, a modem, a switch, or a router. The processor **140** is configured to send and receive data using the network interface **142**. The network interface **142** may be configured to use any suitable type of communication protocol as would be appreciated by one of ordinary skill in the art.

(21) Each of the real-world server **130** and the virtual-world server **150** is generally a suitable server (e.g., including a physical server and/or virtual server) operable to store data in a memory (e.g., respective memories **144** and **174**) and/or provide access to application(s) or other services. One or both of the real-world server **130** and the virtual-world server **150** may be a backend server associated with a particular entity (e.g., organization) that facilitates conducting interactions between entities and one or more users. In other embodiments, one or both of the real-world server **130** and the virtual-world server **150** may be organized in a distributed manner, or by leveraging cloud computing technologies. Real-world server **130** may store information which is primarily used to support data interactions performed in the real-world environment. Virtual-world server **150** may store information which is primarily used to support data interactions performed in the virtual environment **102** (e.g., a metaverse environment). It may be noted that the operations performed by the real-world server **130** and the virtual-world server **150** described in embodiments of the present disclosure may be implemented by a single server.

(22) The communication network **180** may facilitate communication within the system **100**. This disclosure contemplates the communication network **180** being any suitable network operable to facilitate communication between the first user device **104**, second user device **106**, real-world server **130** and the virtual-world server **150**. Communication network **180** may include any interconnecting system capable of transmitting audio, video, signals, data, messages, or any

combination of the preceding. Communication network **180** may include all or a portion of a local area network (LAN), a wide area network (WAN), an overlay network, a software-defined network (SDN), a virtual private network (VPN), a packet data network (e.g., the Internet), a mobile telephone network (e.g., cellular networks, such as 4G or 5G), a Plain Old Telephone (POT) network, a wireless data network (e.g., WiFi, WiGig, WiMax, etc.), a Long Term Evolution (LTE) network, a Universal Mobile Telecommunications System (UMTS) network, a peer-to-peer (P2P) network, a Bluetooth network, a Near Field Communication network, a Zigbee network, and/or any other suitable network, operable to facilitate communication between the components of system **100**. In other embodiments, system **100** may not have all of these components and/or may have other elements instead of, or in addition to, those above.

(23) Each of the user devices (i.e., first user device **104** and second user device **106**) may be any computing device configured to communicate with other devices, such as a server (e.g., real-world server **130** and/or virtual-world server **150**), databases, etc. through the communication network **180**. Each of the user devices may be configured to perform specific functions described herein and interact with one or both of real-world server **130** and the virtual-world server **150**, e.g., via respective user interfaces. Each of the user devices is a hardware device that is generally configured to provide hardware and software resources to a user. Examples of a user device include, but are not limited to, a virtual reality device, an augmented reality device, a laptop, a computer, a smartphone, a tablet, a smart device, an Internet-of-Things (IoT) device, or any other suitable type of device. The user devices may comprise a graphical user interface (e.g., a display), a touchscreen, a touchpad, keys, buttons, a mouse, or any other suitable type of hardware that allows a user to view data and/or to provide inputs into the user device. Each user device may be configured to allow a user to send requests to one or both of real-world server **130** and the virtual-world server **150**, or to another user device.

(24) Example User Device

(25) FIG. 2 is a block diagram of an embodiment of the first user device **104** used by the system of FIG. 1. First user device **104** may be configured to display the virtual environment **102** (referring to FIG. 1) within a field of view of the first user **110** (referring to FIG. 1), capture biometric, sensory, and/or physical information of the first user **110** wearing the first user device **104**, and to facilitate an electronic interaction between the first user **110** and the second user **112** (referring to FIG. 1) or between the first user **110** and an entity (e.g., represented by a virtual entity in the virtual environment **102**).

(26) First user device **104** comprises a processor **202**, a memory **204**, and a display **206**. Further embodiments may include a camera **208**, a wireless communication interface **210**, a network interface **212**, a microphone **214**, a global position system (GPS) sensor **216**, and/or one or more biometric devices **218**. First user device **104** may be configured as shown or in any other suitable configuration. For example, first user device **104** may comprise one or more additional components and/or one or more shown components may be omitted.

(27) The processor **202** comprises one or more processors operably coupled to and in signal communication with memory **204**, display **206**, camera **208**, wireless communication interface **210**, network interface **212**, microphone **214**, GPS sensor **216**, and biometric devices **218**. Processor **202** is configured to receive and transmit electrical signals among one or more of memory **204**, display **206**, camera **208**, wireless communication interface **210**, network interface **212**, microphone **214**, GPS sensor **216**, and biometric devices **218**. The electrical signals are used to send and receive data (e.g., images captured from camera **208**, virtual objects to display on display **206**, etc.) and/or to control or communicate with other devices. Processor **202** may be operably coupled to one or more other devices (for example, the real-world server **130** and/or virtual-world server **150** shown in FIG. 1).

(28) The processor **202** is any electronic circuitry including, but not limited to, state machines, one or more central processing unit (CPU) chips, logic units, cores (e.g., a multi-core processor), field-

programmable gate array (FPGAs), application specific integrated circuits (ASICs), or digital signal processors (DSPs). The processor **202** may be a programmable logic device, a microcontroller, a microprocessor, or any suitable combination of the preceding. The one or more processors are configured to process data and may be implemented in hardware or software. For example, the processor **202** may be 8-bit, 16-bit, 32-bit, 64-bit or of any other suitable architecture. The processor **202** may include an arithmetic logic unit (ALU) for performing arithmetic and logic operations, processor registers that supply operands to the ALU and store the results of ALU operations, and a control unit that fetches instructions from memory and executes them by directing the coordinated operations of the ALU, registers and other components.

(29) The one or more processors are configured to implement various instructions. For example, the one or more processors are configured to execute instructions to implement the function disclosed herein, such as some or all of those described with respect to FIGS. **1** and **3**. For example, processor **202** may be configured to display virtual objects on display **206**, detect hand gestures, identify virtual objects selected by a detected hand gesture, capture biometric information of a user, such as first user **110**, via one or more of camera **208**, microphone **214**, and/or biometric devices **218**, and communicate via wireless communication interface **210** with the real-world server **130**, virtual-world server **150** and/or second user device **106**. In some embodiments, the function described herein is implemented using logic units, FPGAs, ASICs, DSPs, or any other suitable hardware or electronic circuitry.

(30) The memory **204** is operable to store any of the information described with respect to FIGS. **1** and **3** along with any other data, instructions, logic, rules, or code operable to implement the function(s) described herein when executed by processor **202**. For example, the memory **204** may store the instructions **220**. The memory **204** comprises one or more disks, tape drives, or solid-state drives, and may be used as an over-flow data storage device, to store programs when such programs are selected for execution, and to store instructions and data that are read during program execution. Memory **204** is operable to store, for example, information relating to the identity of the user (e.g., at least a portion of user data **132**), instructions for performing the functions of first user device **104** described herein, and any other data or instructions. The memory **204** may be volatile or non-volatile and may comprise read-only memory (ROM), random-access memory (RAM), ternary content-addressable memory (TCAM), dynamic random-access memory (DRAM), and static random-access memory (SRAM).

(31) Display **206** is configured to present visual information to a user (for example, first user **110** in FIG. **1**) in a virtual reality environment, an augmented reality environment or mixed reality environment. In other embodiments, the display **206** is configured to present visual information to the user as the virtual environment **102** (referring to FIG. **1**) in real-time. In an embodiment, display **206** is a wearable optical display (e.g., glasses or a headset) configured to reflect projected images and enables a user to see through the display. For example, display **206** may comprise display units, lens, semi-transparent mirrors embedded in an eye glass structure, a visor structure, or a helmet structure. Examples of display units include, but are not limited to, a cathode ray tube (CRT) display, a liquid crystal display (LCD), a liquid crystal on silicon (LCOS) display, a light emitting diode (LED) display, an active-matrix OLED (AMOLED), an organic LED (OLED) display, a projector display, or any other suitable type of display as would be appreciated by one of ordinary skill in the art upon viewing this disclosure. In another embodiment, display **206** is a graphical display on a user device. For example, the graphical display may be the display of a tablet or smart phone configured to display virtual environment **102**.

(32) Examples of camera **208** include, but are not limited to, charge-coupled device (CCD) cameras and complementary metal-oxide semiconductor (CMOS) cameras. Camera **208** is configured to capture images of a wearer of first user device **104**, such as first user **110**. Camera **208** may be configured to capture images continuously, at predetermined intervals, or on-demand. For example, camera **208** may be configured to receive a command from first user **110** to capture an image. In

another example, camera **208** is configured to continuously capture images to form a video stream. Camera **208** is communicably coupled to processor **202**.

(33) Examples of wireless communication interface **210** include, but are not limited to, a Bluetooth interface, an RFID interface, a near field communication interface, a local area network (LAN) interface, a personal area network interface, a wide area network (WAN) interface, a Wi-Fi interface, a ZigBee interface, or any other suitable wireless communication interface as would be appreciated by one of ordinary skill in the art upon viewing this disclosure. Wireless communication interface **210** is configured to facilitate processor **202** in communicating with other devices. For example, wireless communication interface **210** is configured to enable processor **202** to send and receive signals with other devices, such as second user device **106**, the real-world server **130** and/or virtual-world server **150** (referring to FIG. 1). Wireless communication interface **210** is configured to employ any suitable communication protocol.

(34) The network interface **212** is configured to enable wired and/or wireless communications. The network interface **212** is configured to communicate data between the first user device **104** and other network devices, systems, or domain(s). For example, the network interface **212** may comprise a WIFI interface, a local area network (LAN) interface, a wide area network (WAN) interface, a modem, a switch, or a router. The processor **202** is configured to send and receive data using the network interface **212**. The network interface **212** may be configured to use any suitable type of communication protocol as would be appreciated by one of ordinary skill in the art.

(35) Microphone **214** is configured to capture audio signals (e.g., voice signals or commands) from a user, such as first user **110**. Microphone **214** is configured to capture audio signals continuously, at predetermined intervals, or on-demand. Microphone **214** is communicably coupled to processor **202**.

(36) GPS sensor **216** is configured to capture and to provide geographical location information. For example, GPS sensor **216** is configured to provide a geographic location of a user, such as first user **110**, employing first user device **104**. GPS sensor **216** may be configured to provide the geographic location information as a relative geographic location or an absolute geographic location. GPS sensor **216** may provide the geographic location information using geographic coordinates (i.e., longitude and latitude) or any other suitable coordinate system. GPS sensor **216** is communicably coupled to processor **202**.

(37) Examples of biometric devices **218** may include, but are not limited to, retina scanners, fingerprint scanners and facial scanners. Biometric devices **218** are configured to capture information about a person's physical characteristics and to output a biometric signal based on captured information. A biometric signal is a signal that is uniquely linked to a person based on their physical characteristics. For example, biometric device **218** may be configured to perform a retinal scan of the user's eye and to generate a biometric signal for the user based on the retinal scan. As another example, a biometric device **218** is configured to perform a fingerprint scan of the user's finger and to generate a biometric signal for the user based on the fingerprint scan. Biometric device **218** is communicably coupled to processor **202**.

(38) Referring back to FIG. 1, in one or more embodiments, one or both of the real-world server **130** and the virtual-world server **150**, and one or more user devices (e.g., first user device **104** and/or second user device **106**) may be part of an Information Technology (IT) infrastructure of an entity or organization. For example, second user **112** may be a representative of the organization who may use the second user device **106** to enter the virtual environment **102** and virtually interact with one or more users (e.g., first user **110**) via the second avatar **116** to provide services to the first user **110**.

(39) The real-world server **130** may be configured to allow users (e.g., first user **110**) registered with the real-world server **130** to perform one or more data interactions in the real-world environment. Data interactions performed in the real-world environment may be referred to as real-world data interactions. Similarly, virtual-world server **150** may be configured to allow users (e.g.,

first user **110**) registered with the virtual-world server **150** to perform one or more data interactions in the virtual environment **102** (e.g., a metaverse environment). Data interactions performed in the virtual environment **102** may be referred to as virtual-world data interactions or virtual data interactions. In one embodiment, the real-world server **130** and the virtual-world server **150** are owned and/or operated by the same entity/organization. In this context, virtual-world server **150** may be configured to allow users (e.g., first user **110**) registered with the real-world server **130** to perform one or more data interactions in the virtual environment **102** (e.g., a metaverse environment). In alternative embodiments, the real-world server **130** and the virtual-world server **150** may be owned and/or operated by different entities/organizations.

(40) In one or more embodiments, as the first user **110** initially registers with the real-world server **130** in the real-world environment, the real-world server **130** may collect several pieces of information from the user including information relating to the identity of the user such as legal name, biometrics (e.g., fingerprints, retina scans, face ID etc.), residence address, phone numbers, assets owned by the user, and copies of government issued documents (e.g., driver permit, state identity card etc.). This information is stored by real-world server **130** as part of user data **132** of the first user **110**. In one embodiment, at least a portion of the user data **132** relating to the first user **110** collected in the real-world environment may be stored in the virtual-world server **150**. Once the identity of the first user **110** is confirmed and all other information provided by the first user **110** is verified to be correct, the real-world server **130** may generate a real-world data file **134** for the first user **110** in which the first user **110** may store real-world data objects **136** owned by the first user **110**. In one example, the first user **110** may engage in a real-world data interaction with a service representative managing the real-world server **130** (e.g., physical interaction at an office location, over phone, voice chat etc.) to provide such information that can be used to register the first user **110** at the real-world server **130** and generate the real-world data file **134** of the first user **110**. In another example, the first user **110** may engage in a real-world data interaction by accessing a webpage provided and managed by the real-world server **130**. Once the first user **110** initiates a registration process via the webpage, the real-world server **130** may walk the first user **110** through several steps in which the first user **110** may be asked to provide information necessary to verify the identity of the first user **110** and register the first user **110** with the real-world server **130**.

(41) Information relating to the real-world data file **134** of the first user **110** may be stored as part of the user data **132** of the first user **110**. This information may include, but is not limited to, an identity of the real-world data file **134**, amount of real-world data objects **136** stored in the real-world data file **134**, a log of data interactions conducted in relation to the real-world data file **134** and any other information relating to the real-world data file **134**.

(42) Once registered with the real-world server **130**, the real-world server **130** may allow the first user **110** to perform one or more data interactions in the real-world environment. For example, a real-world data interaction may include transferring one or more real-world data objects **136** from the real-world data file **134** of the first user **110** to a second real-world data file (not shown) of the second user **112**. Another example data interaction may include receiving one or more real-world data objects **136** in the real-world data file **134** of the first user **110** from the second real-world data file of the second user **112**. Another example data interaction may include requesting by the first user **110** transfer of real-world data objects from a data file of a second user to a user data file of a third user as part of satisfying an agreement between the first user **110** and the third user. Another example data interaction may include modifying at least a portion of the user data **132** (e.g., user credentials to access the real-world server, phone numbers, residential address, email address, information relating to user assets etc.) stored at the real-world server **130**. It may be noted that a data interaction in accordance with embodiments of the present disclosure refers to any interaction in the real-world environment and/or virtual environment **102** that includes transfer of data between computing nodes (e.g., first user device **104**, second user device **106**, real-world server **130** and virtual-world server **150**).

(43) The first user **110** may additionally register with the virtual-world server **150**. In one embodiment, when initially registering with the virtual-world server **150**, the first user **110** may provide to the virtual-world server **150** a credential (e.g., username and password) that provides the first user **110** access to the real-world server **130**. In one embodiment, a single web page or web portal may allow the first user **110** to register with the real-world server **130** as well as the virtual-world server **150**. The first user **110** may first register with the real-world server **130** as described above and generate credentials that allow the first user **110** access to the real-world server **130** and services provided by the real-world server **130**. Once registered with the real-world server **130**, the web portal may offer the first user **110** an option to additionally register with the virtual-world server **150** which may allow the first user **110** to perform data interactions in the virtual environment **102**. Registration with the virtual-world server **150** may include generating a user credential **152** that allows the first user **110** to sign on to the virtual-world server **150** and enter the virtual environment **102** via first avatar **114** of the first user **110**. Other users may register with the real-world server **130** and the virtual-world server **150** in a similar manner as the first user **110**. For example, second user **112** may register with the virtual-world server **150** which may include generating a second user credential (not shown) that allows the second user **112** to sign on to the virtual-world server **150** and enter the virtual environment **102** via second avatar **116** of the second user **112**.

(44) Once registered with the virtual-world server **150**, the first user **110** may generate a virtual data file **160** in which the first user **110** may store virtual data objects **162** owned by the first user **110**. In one or more embodiments, the virtual data file **160** of the first user **110** is associated with the real-world data file **134** of the first user **110**. For example, the virtual data file **160** is a virtual image of the real-world data file **134**, wherein the virtual data objects **162** correspond to the real-world data objects **136**. In other words, the virtual data file **160** is a virtual representation of the real-world data file **134**. In another example, the virtual data file **160** stores a portion of the real-world data objects **136** in the form of virtual data objects **162**. In another example, real-world data objects **136** may be converted to virtual data objects **162**, and vice versa. In this case, there may not be a one-to-one conversion between the real-world data objects **136** and virtual data objects **162**. For example, one real-world data object **136** may be converted to a plurality of virtual data objects **162**, wherein the conversion ratio may dynamically change from time to time.

(45) Information relating to the virtual data file **160** of the first user **110** may be stored by the virtual-world server **150**. This information may include, but is not limited to, an identity of the virtual data file **160**, amount of virtual data objects **162** stored in the virtual data file **160**, a log of virtual data interactions conducted in the virtual environment **102** in relation to the virtual data file **160** and any other information relating to the virtual data file **160**.

(46) Once registered with the virtual-world server **150**, the virtual-world server **150** may allow the first user **110** to perform one or more virtual data interactions. For example, a virtual data interaction may include transferring one or more virtual data objects **162** from the virtual data file **160** of the first user **110** to a second virtual data file (not shown) of the second user **112**. Another example data interaction may include receiving one or more virtual data objects **162** in the virtual data file **160** of the first user **110** from the second virtual data file of the second user **112**. Another example data interaction may include requesting by the first user **110** transfer of virtual data objects from a data file of a second user to a data file of a third user as part of satisfying an agreement between the first user **110** and the third user.

(47) In one or more embodiments, the virtual data file (e.g. virtual data file **160**) is a software application running on a computing node owned and/or operated by the respective user (e.g., first user **110**). For example, when the first user **110** desires to receive virtual data objects **162** from a virtual data file of the second user **112**, first user **110** may direct the second user **112** to a unique cryptographic address (e.g., public key) issued by the virtual data file **160**. In one embodiment, the virtual data file **160** may not itself store the virtual data objects **162** but may store information that

points to a location of the virtual data objects **162**, for example, on a server (e.g., virtual-world server **150**). Virtual data file **160** may be web-based or hardware-based. For example, virtual data file **160** may be stored in a mobile device or a desktop computer connected to the internet. Additionally or alternatively, virtual data file **160** may be stored in a device (e.g., USB drive) that is not connected to the network **180**.

(48) With the advent of virtual-world technology such as metaverse technology that allows users to enter mixed reality environments and perform data interactions, data security has become a challenge as the development of metaverse related technologies is still at a nascent stage and standardized systems that provide robust data security are not yet in place. For example, a bad actor may pretend to be another user in a virtual environment which then allows the bad actor to interact with other users, gain access to other users' information, and avail services reserved only for authorized users. Present virtual-world technologies (e.g., metaverse technologies) do not provide robust systems and processes that can reliably verify the credibility of a user operating in the virtual environment **102**. Thus, data interactions conducted in the virtual environment **102** are prone to deception, data theft and other security threats.

(49) Embodiments of the present disclosure discuss techniques that intelligently and reliably verify credibility of a user in a virtual environment and help improve security of data interactions conducted in the virtual environment as well as the real-world environment.

(50) Virtual-world server **150** may be configured to generate one or more confidence indicators **158** for the first user **110** that are indicative of a credibility of the first user **110** in the virtual environment **102** as well as the real-world environment. Several user profiles **154** may be defined and associated with the first user **110**, wherein each user profile **154** of the first user **110** represents a specific set of skills and/or characteristics related to the first user **110**. Virtual-world server **150** may be configured to generate and maintain several confidence indicators **158** for the first user **110**, wherein each confidence indicator **158** of the first user **110** is associated with a different user profile **154** related to the first user **110**. Thus, the confidence indicator **158** associated with each user profile **154** is indicative of a credibility and/or reputation of the first user **110** with regard to the specific set of skills and/or characteristics of the first user **110** represented by the user profile **154**.

(51) Examples of user profiles **154** may include, but are not limited to, engineering, financial, legal, medicine, fitness, and nutrition. For example, an engineering user profile of the first user **110** may represent specific engineering skills that the first user **110** may possess. A confidence indicator **158** of the first user **110** associated with the engineering profile of the first user **110** is indicative of a proficiency of the first user **110** relating to the specific engineering skills represented by the engineering profile. In another example, a fitness user profile of the first user **110** may represent fitness related skills (e.g., formal fitness education, experience as fitness instructor etc.) that the first user **110** may possess. A confidence indicator **158** of the first user **110** associated with the fitness profile of the first user **110** is indicative of a proficiency of the first user **110** in fitness related skills represented by the fitness profile. In another example, a security profile of the first user **110** may represent a security level associated with the first user **110**. A confidence indicator **158** of the first user **110** associated with the security profile of the first user **110** is indicative of a security credibility of the first user **110**. For example, the confidence indicator **158** of the first user **110** associated with the security profile indicates to other users a level of security associated with engaging in virtual data interactions with the first user **110**.

(52) Virtual-world server **150** may be configured to generate and/or update the confidence indicators **158** related to the first user **110** based on monitoring data interactions related to the first user **110** that are performed in the virtual environment **102** and/or the real-world environment. Virtual-world server **150** may be configured to monitor several data interactions related to the first user **110** that are performed in the virtual environment **102** and/or the real-world environment. Data interactions related to the first user **110** may include, but are not limited to, data interactions

performed by the first user **110** (e.g., with a second user **112** or entity) in the virtual environment **102** and data interactions performed by other users (e.g., second user **112**) or entities in the virtual environment **102** that relate to the first user **110**. Examples of data interactions performed by the first user **110** in the virtual environment **102** may include, but are not limited to, transferring virtual data objects **162** to a second user **112** or entity, receiving virtual data objects **162** from the second user **112** or entity, and attending a virtual event (e.g., virtual class, virtual conference, virtual seminar, virtual meeting etc.) in the virtual environment **102**. Examples of data interactions performed by other users (e.g., second user **112**) or entities in the virtual environment **102** and/or real-world environment that relate to the first user **110** may include, but are not limited to, an entity issuing a virtual award to the first user **110**, an educational entity issuing an educational degree/diploma to the first user **110**, the second user **112** publishing a recommendation related to a specific skill of the first user **110** on a virtual platform in the virtual environment, and an entity registering and admitting the first user **110** in a virtual group.

(53) Based on monitoring the data interactions related to the first user **110**, virtual-world server **150** may be configured to record information relating to a plurality of profile parameters **156**. Each profile parameter **156** represents a specific skill, behavior and/or characteristic associated with the first user **110**. Examples of profile parameters **156** may include, but are not limited to, confidence indicators **158** of other users (e.g., second user **112**) the first user **110** interacts with in the virtual environment **102**, amount of virtual data object **162** sent or received by the first user **110**, confirmation of virtual events attended by the first user **110**, virtual awards received by the first user **110**, educational degrees/diplomas received by the first user **110**, recommendations received by the first user **110**, confirmation of admission of the first user **110** to virtual groups, and confirmation of registration of the first user **110** to an entity/organization. For example, when the first user **110** conducts a virtual fitness class in the virtual environment **102**, virtual-world server **150** records this event as a profile parameter **156** related to the first user **110**. In another example, when the first user **110** is issued an award by a virtual entity in the virtual environment **102**, virtual-world server **150** records this event as a profile parameter **156** related to the first user **110**.

(54) A confidence indicator **158** associated with a user profile **154** related to the first user **110** may be based on a specific set of profile parameters **156** from the plurality of profile parameters **156** recorded for the first user **110** by the virtual-world server **150**. In one embodiment, each user profile **154** may be based on a different set of profile parameters **156**. For example, a confidence indicator **158** associated with an engineering profile of the first user **110** may be generated/updated based on a set of profile parameters **156** including, but not limited to, engineering degrees/diplomas received by the first user **110**, engineering awards received by the first user **110**, work experience of the first user **110** as an engineer (e.g., number of years worked in an engineering role), memberships to virtual engineering groups, virtual interaction with other engineers in the virtual environment **102**, and engineering conferences attended by the first user **110**. In another example, a confidence indicator **158** associated with a fitness profile of the first user **110** may be generated/updated based on a set of profile parameters **156** including, but not limited to, fitness related degrees/diplomas received by the first user **110**, fitness related awards received by the first user **110**, experience as a fitness instructor (e.g., a number of fitness classes conducted by the first user **110**), a length of time the first user is registered as a fitness instructor with a fitness related entity, memberships to fitness groups, and virtual interaction with other fitness related entities or users.

(55) Virtual-world server **150** may be configured to build one or more confidence indicators **158** (e.g., associated with respective user profiles **154**) for the first user **110** over time as information regarding more and more data interactions related to the first user **110** is recorded. For example, a confidence indicator **158** of the first user **110** associated with a respective user profile **154** may be initialized with a default numerical value (e.g., 1, 10, 100 etc.). The confidence indicator **158** may be updated with each recorded data interaction related to the first user **110** that occurs in the virtual

environment **102**. For example, a confidence indicator **158** associated with a fitness profile of the first user **110** may first be initialized and assigned a default value of 100. With each piece of user data **132** related to the first user **110** that is collected and each virtual data interaction related to the first user **110** that is recorded, virtual-world server **150** updates the confidence indicator. For example, when a data interaction related to the first user **110** receiving a fitness related diploma is detected, virtual-world server **150** records the diploma as a profile parameter **156** related to the first user **110** and increments the confidence indicator **158** associated with the fitness profile by a selected amount. Subsequently, when a data interaction related to the first user **110** conducting a virtual fitness class is detected, virtual-world server **150** records this event as a profile parameter **156** related to the first user **110** and further increments the confidence indicator **158** by another selected amount. Thus, the confidence indicator **158** associated with a user profile **154** increases in value as more profile parameters **156** related to the user profile **154** are recorded. A higher numerical value of the confidence indicator is indicative of a higher credibility and/or reputation. Thus, the credibility/reputation of the first user **110** associated with a user profile **154** may increase over time as more profile parameters **156** associated with the user profile **154** are recorded. It may be noted that each profile parameter **156** may be associated with a same or different pre-selected increment value. When a profile parameter **156** is recorded based on a data interaction related to the first user **110**, a confidence indicator **158** associated with the profile parameter **156** is incremented by the respective pre-selected increment value of the profile parameter **156**.

(56) In some cases, virtual-world server **150** may lower (e.g., decrease) the confidence indicator **158** associated with a user profile **154** of the first user **110** in response to recording profile parameters **156** that negatively affect the credibility and/or reputation of the first user **110**. For example, when the first user **110** receives a negative recommendation from a reputed user/entity (e.g., another user having a high confidence indicator), virtual-world server **150** may decrement the confidence indicator **158** by a pre-selected amount. In another example, in response to detecting that a membership of the first user **110** to a virtual group was cancelled by an entity managing the virtual group, virtual-world server **150** may decrement the confidence indicator **158** by a pre-selected amount.

(57) In one or more embodiments, virtual-world server **150** may be configured to adjust a confidence indicator **158** associated with the first user **110** based on virtual data interactions of the first user **110** with other users in the virtual environment **102**. For example, in response to detecting that the first user **110** performed a data interaction with the second user **112** in the virtual environment **102**, virtual-world server **150** may be configured to adjust a confidence indicator **158** of the first user **110** based on a confidence indicator **158** of the second user **112**. For example, virtual-world server **150** may decrement the confidence indicator **158** of the first user **110** by a pre-selected amount when the corresponding confidence indicator **158** of the second user **112** is equal to or below a threshold value. On the other hand, virtual-world server **150** may increment the confidence indicator **158** of the first user **110** by a pre-selected amount when the corresponding confidence indicator **158** of the second user **112** exceeds a threshold value. In one example, a confidence indicator **158** associated with a security profile of the first user **110** may be adjusted based on a corresponding confidence indicator **158** associated with the security profile of the second user **112**. The assumption here is that users who interact with less credible users (e.g., having lower confidence indicators) are more prone to security risks as compared to users who interact with highly credible users (e.g., having high confidence indicators). Thus, when the first user **110** interacts with users with low confidence indicators **158**, virtual-world server **150** lowers the corresponding confidence indicator of the first user **110**. On the other hand, when the first user **110** interacts with users with high confidence indicators, virtual-world server **150** raises the corresponding confidence indicator of the first user **110**.

(58) Virtual-world server **150** may be configured to generate and maintain (e.g., update based on newly recorded profile parameters) custom confidence indicators **158** for the first user **110** based on

a set of profile parameters **156** selected by the first user **110**. For example, virtual-world server **150** may allow the first user **110** to select a set of profile parameters **156** based on which a custom confidence indicator **158** is to be generated and maintained for the first user **110**. First user **110** may also define a custom user profile that is to be associated with the selected set of profile parameters **156**. In response to receiving a request from the first user **110** for generating the custom confidence indicator **158** associated with the custom user profile of the first user **110** based on a selected set of profile parameters **156**, virtual-world server **150** may start recording information relating to the selected set of profile parameters **156**. Virtual-world server generates and continually updates the custom confidence indicator **158** based on the recorded set of profile parameters **156**. This mechanism allows the first user **110** to generate custom confidence indicators for use by other users and entities in the virtual environment **102**. For example, first user **110** may select a set of profile parameters **156** that relate to a specific engineering skill set needed by an engineering entity to admit users to an elite virtual engineering group in the virtual environment **102**. The customized confidence indicator may allow the engineering entity to verify proficiency of the first user **110** relating to the specific skill set and may help the first user **110** to secure an admission to the elite engineering group. In alternative or additional embodiments, virtual-world server **150** may be configured to generate and maintain (e.g., update based on newly recorded profile parameters) for the first user **110** one or more default confidence indicators **158** associated with one or more respective default user profiles **154** that are based on one or more respective default sets of profile parameters **156**. For example, virtual-world server **150** may generate and maintain for the first user **110** a default confidence indicator **158** associated with a default user profile **154** that is based on a default set of profile parameters **156**. For instance, by default the virtual-world server **150** may generate and maintain for the first user **110** a confidence indicator **158** associated with a security profile of the user based on a default set of profile parameters **156** indicative of security characteristics of the first user **110**.

(59) In certain embodiments, a second user **112** may request the virtual-world server **150** for one or more confidence indicators **158** associated with one or more respective user profiles **154** of the first user **110**. The second user **112** may perform one or more data interactions related to the first user **110** in the virtual environment **102** based on one or more confidence indicators **158** of the first user **110**. For example, the second user **112** may request a confidence indicator **158** associated with the security profile of the first user **110** and then decide to transfer virtual data objects **162** to the first user **110** or receive virtual data objects **162** from the first user **110** based on the confidence indicator **158** of the first user **110**. For instance, if the confidence indicator **158** associated with the security profile of the first user **110** is low (e.g., lower than a threshold value) indicating a high security risk associated with the first user **110**, the second user **112** may decide to not engage in data interactions with the first user **110** to avoid a data breach. Thus, the confidence indicators **158** may improve data security in the virtual environment **102**. In certain embodiments, the second user **112** or entity may use confidence indicators **158** associated with certain user profiles **154** of the first user **110** to make certain decisions relating to the first user **110**. For example, an engineering firm wanting to add engineers having certain skills to their team may request for a confidence indicator **158** associated with an engineering profile of the first user **110**. The engineering firm may decide to add the first user **110** to their team only when the confidence indicator **158** of the first user equals or exceeds a threshold value. In another example, a virtual fitness school wanting to add fitness instructors to their team may request for a confidence indicator **158** associated with a fitness profile of the first user **110**. The fitness school may decide to add the first user **110** to their team only when the confidence indicator **158** of the first user **110** equals or exceeds a threshold value.

(60) Virtual-world server **150** may be configured to provide upon request from a second user **112** or entity one or more confidence indicators **158** associated with one or more respective user profiles **154** of the first user **110**. In one embodiment, virtual-world server **150** may provide to the second

user **112** or entity only those confidence indicators **158** the second user **112** or entity is authorized to obtain. For example, virtual-world server **150** may register the second user **112** to obtain confidence indicators **158** of other users (e.g., first user **110**) associated with certain user profiles **154**. In this case, virtual-world server **150** may provide to the second user **112** confidence indicators **158** associated with only those user profiles **154** the second user **112** is registered to receive. The virtual-world server **150** may not provide the second user **112** confidence indicators **158** associated with those user profiles **154** the second user **112** is not registered to receive. For example, an engineering firm may be registered to receive confidence indicators **158** of other users associated with engineering profiles only. This limits users and entities in the virtual environment **102** to obtain only that information about other users which is relevant to their needs. By controlling dissemination of user information, virtual-world server **150** improves data security in the virtual environment **102**. In one embodiment, virtual-world server **150** may be configured to indicate the requested one or more confidence indicators **158** to the second user **112** in the virtual environment **102**. For example, virtual-world server **150** may transmit a requested confidence indicator **158** to the second user device **106** which may display the confidence indicator **158** to the second user on a display of the second user device **106**.

(61) In additional or alternative embodiments, the virtual-world server **150** may be configured to generate a confidence indicator **158** associated with the first user **110** based on a requested set of profile parameters **156**. For example, virtual-world server **150** may receive a request from the second user **112** for a confidence indicator **158** related to the first user **110** based on a set of profile parameters **156** selected by the second user **112**. The set of profile parameters **156** selected by the second user **112** may or may not relate to a user profile **154** defined for the first user **110**. In response to receiving the request from the second user **112**, virtual-world server **150** checks whether information was recorded for the first user **110** relating to one or more profile parameters **156** of the set of profile parameters **156** included in the request. Upon determining that information was recorded for one or more of the requested profile parameters **156**, virtual-world server **150** generates a confidence indicator **158** for the first user **110** based on the one or more profile parameters **156** requested by the second user **112**. Virtual-world server **150** may be configured to indicate the generated confidence indicator **158** to the second user **112** in the virtual environment **102**. For example, virtual-world server **150** may transmit the generated confidence indicator **158** to the second user device **106** which may display the confidence indicator **158** to the second user on a display of the second user device **106**.

(62) Virtual-world server **150** may be configured to authorize and/or perform certain data interactions related to the first user **110** based on one or more confidence indicators **158** associated with the first user **110**. For example, when a second user **112** requests to transfer virtual data objects **162** to the first user **110** or receive virtual data objects **162** from the first user **110**, virtual-world server **150** authorizes the requested data interaction only when the confidence indicator **158** associated with the security profile of the first user **110** equals or exceeds a threshold value. In another example, virtual-world server **150** may be configured by the second user **112** or an entity to add users to a designated virtual engineering group based on confidence indicators **158** associated with those users. When the first user **110** requests to be added to the virtual engineering group, virtual-world server **150** adds the first user **110** to the virtual engineering group when the confidence indicator **158** associated with the engineering profile of the first user **110** equals or exceeds a threshold value.

(63) FIG. 3 illustrates a flowchart of an example method **300** for performing secure data interactions in a virtual environment **102**, in accordance with one or more embodiments of the present disclosure. Method **300** may be performed by the virtual-world server **150** shown in FIG. 1.

(64) At operation **302**, virtual-world server **150** receives a user credential **152** associated with a first user **110**, wherein the user credential **152** provides the first user **110** access to a virtual environment **102**.

(65) At operation **304**, virtual-world server **150** verifies the user credential **152**. If the verification is unsuccessful, method **300** proceeds to operation **306** where virtual-world server **150** denies the first user **110** access to the virtual environment. On the other hand, if the user credential **152** is successfully verified, method **300** proceeds to operation **308** where virtual-world server **150** authorizes, based on the user credential **152**, an avatar (e.g., first avatar **114**) of the first user **110** to enter the virtual environment **102**.

(66) As described above, virtual-world server **150** may be configured to use a user credential **152** collected from the first user **110**, generated by the first user **110** or assigned to the first user **110** during real-world data interactions with the first user **110**, to verify identity of the first user **110** in the virtual environment **102**. Thus, the user credential **152** provides the first user **110** access to the virtual environment **102**. For example, the user credential **152** may be used by the virtual-world server **150** to verify that the first avatar **114** belongs to and is controlled by the first user **110**.

(67) In one example, user credential **152** may include a username and password generated by the first user **110** as part of registering with the real-world server **130**. The virtual-world server **150** may allow the first user **110** to use the same username and password to enter the virtual environment **102** via first avatar **114**. In an alternative embodiment, the first user **110** may generate a separate user credential (different from the user credential **152**) as part of registering with the real-world server **130** and use the separate user credential to log into the real-world server **130** and perform real-world data interaction. The first user **110** may separately generate user credential **152** as part of registering with the virtual-world server **150** (e.g., during a real-world data interaction with the real-world server **130**). Once the first user **110** has registered with the virtual-world server **150** and generated the user credential **152**, the first user **110** may use the user credential **152** to log into the virtual-world server **150** and perform virtual-world data interactions.

(68) At operation **310**, virtual-world server **150** monitors a plurality of data interactions associated with the first user **110** that are performed in the virtual environment **102**.

(69) As described above, virtual-world server **150** may be configured to generate one or more confidence indicators **158** for the first user **110** that are indicative of a credibility of the first user **110** in the virtual environment **102** as well as the real-world environment. Several user profiles **154** may be defined and associated with the first user **110**, wherein each user profile **154** of the first user **110** represents a specific set of skills and/or characteristics related to the first user **110**. Virtual-world server **150** may be configured to generate and maintain several confidence indicators **158** for the first user **110**, wherein each confidence indicator **158** of the first user **110** is associated with a different user profile **154** related to the first user **110**. Thus, the confidence indicator **158** associated with each user profile **154** is indicative of a credibility and/or reputation of the first user **110** with regard to the specific set of skills and/or characteristics of the first user **110** represented by the user profile **154**.

(70) Virtual-world server **150** may be configured to generate and/or update the confidence indicators **158** related to the first user **110** based on monitoring data interactions related to the first user **110** that are performed in the virtual environment **102** and/or the real-world environment. Virtual-world server **150** may be configured to monitor several data interactions related to the first user **110** that are performed in the virtual environment **102** and/or the real-world environment. Data interactions related to the first user **110** may include, but are not limited to, data interactions performed by the first user **110** (e.g., with a second user **112** or entity) in the virtual environment **102** and data interactions performed by other users (e.g., second user **112**) or entities in the virtual environment **102** that relate to the first user **110**. Examples of data interactions performed by the first user **110** in the virtual environment **102** may include, but are not limited to, transferring virtual data objects **162** to a second user **112** or entity, receiving virtual data objects **162** from the second user **112** or entity, and attending a virtual event (e.g., virtual class, virtual conference, virtual seminar, virtual meeting etc.) in the virtual environment **102**. Examples of data interactions performed by other users (e.g., second user **112**) or entities in the virtual environment **102** and/or

real-world environment that relate to the first user **110** may include, but are not limited to, an entity issuing a virtual award to the first user **110**, an educational entity issuing an educational degree/diploma to the first user **110**, the second user **112** publishing a recommendation related to a specific skill of the first user **110** on a virtual platform in the virtual environment, and an entity registering and admitting the first user **110** in a virtual group.

(71) At operation **312**, virtual-world server **150** records, based on the plurality of data interactions associated with the first user **110**, information relating to a set of parameters (e.g., a set of profile parameters **156**), wherein the set of parameters corresponds to a first user profile **154** of a plurality of user profiles **154** associated with the first user **110**. Each parameter of the set of parameters defines a characteristic associated with the first user **110** related to the user profile **154**.

(72) As described above, based on monitoring the data interactions related to the first user **110**, virtual-world server **150** may be configured to record information relating to a plurality of profile parameters **156**. Each profile parameter **156** represents a specific skill, behavior and/or characteristic associated with the first user **110**. Examples of profile parameters **156** may include, but are not limited to, confidence indicators **158** of other users (e.g., second user **112**) the first user **110** interacts with in the virtual environment **102**, amount of virtual data object **162** sent or received by the first user **110**, confirmation of virtual events attended by the first user **110**, virtual awards received by the first user **110**, educational degrees/diplomas received by the first user **110**, recommendations received by the first user **110**, confirmation of admission of the first user **110** to virtual groups, and confirmation of registration of the first user **110** to an entity/organization. For example, when the first user **110** conducts a virtual fitness class in the virtual environment **102**, virtual-world server **150** records this event as a profile parameter **156** related to the first user **110**. In another example, when the first user **110** is issued an award by a virtual entity in the virtual environment **102**, virtual-world server **150** records this event as a profile parameter **156** related to the first user **110**.

(73) A confidence indicator **158** associated with a user profile **154** related to the first user **110** may be based on a specific set of profile parameters **156** from the plurality of profile parameters **156** recorded for the first user **110** by the virtual-world server **150**. In one embodiment, each user profile **154** may be based on a different set of profile parameters **156**. For example, a confidence indicator **158** associated with an engineering profile of the first user **110** may be generated/updated based on a set of profile parameters **156** including, but not limited to, engineering degrees/diplomas received by the first user **110**, engineering awards received by the first user **110**, work experience of the first user **110** as an engineer (e.g., number of years worked in an engineering role), memberships to virtual engineering groups, virtual interaction with other engineers in the virtual environment **102**, and engineering conferences attended by the first user **110**. In another example, a confidence indicator **158** associated with a fitness profile of the first user **110** may be generated/updated based on a set of profile parameters **156** including, but not limited to, fitness related degrees/diplomas received by the first user **110**, fitness related awards received by the first user **110**, experience as a fitness instructor (e.g., a number of fitness classes conducted by the first user **110**), a length of time the first user is registered as a fitness instructor with a fitness related entity, memberships to fitness groups, and virtual interaction with other fitness related entities or users.

(74) At operation **314**, virtual-world server **150** determines, based on the recorded information relating to the set of profile parameters **156**, a first confidence indicator **158** for the first user **110** relating to the first user profile **154** associated with the first user **110**.

(75) As described above, virtual-world server **150** may be configured to build one or more confidence indicators **158** (e.g., associated with respective user profiles **154**) for the first user **110** over time as information regarding more and more data interactions related to the first user **110** is recorded. For example, a confidence indicator **158** of the first user **110** associated with a respective user profile **154** may be initialized with a default numerical value (e.g., 1, 10, 100 etc.). The

confidence indicator **158** may be updated with each recorded data interaction related to the first user **110** that occurs in the virtual environment **102**. For example, a confidence indicator **158** associated with a fitness profile of the first user **110** may first be initialized and assigned a default value of 100. With each piece of user data **132** related to the first user **110** that is collected and each virtual data interaction related to the first user **110** that is recorded, virtual-world server **150** updates the confidence indicator. For example, when a data interaction related to the first user **110** receiving a fitness related diploma is detected, virtual-world server **150** records the diploma as a profile parameter **156** related to the first user **110** and increments the confidence indicator **158** associated with the fitness profile by a selected amount. Subsequently, when a data interaction related to the first user **110** conducting a virtual fitness class is detected, virtual-world server **150** records this event as a profile parameter **156** related to the first user **110** and further increments the confidence indicator **158** by another selected amount. Thus, the confidence indicator **158** associated with a user profile **154** increases in value as more profile parameters **156** related to the user profile **154** are recorded. A higher numerical value of the confidence indicator is indicative of a higher credibility and/or reputation. Thus, the credibility/reputation of the first user **110** associated with a user profile **154** may increase over time as more profile parameters **156** associated with the user profile **154** are recorded. It may be noted that each profile parameter **156** may be associated with a same or different pre-selected increment value. When a profile parameter **156** is recorded based on a data interaction related to the first user **110**, a confidence indicator **158** associated with the profile parameter **156** is incremented by the respective pre-selected increment value of the profile parameter **156**.

(76) In some cases, virtual-world server **150** may lower (e.g., decrease) the confidence indicator **158** associated with a user profile **154** of the first user **110** in response to recording profile parameters **156** that negatively affect the credibility and/or reputation of the first user **110**. For example, when the first user **110** receives a negative recommendation from a reputed user/entity (e.g., another user having a high confidence indicator), virtual-world server **150** may decrement the confidence indicator **158** by a pre-selected amount. In another example, in response to detecting that a membership of the first user **110** to a virtual group was cancelled by an entity managing the virtual group, virtual-world server **150** may decrement the confidence indicator **158** by a pre-selected amount.

(77) In one or more embodiments, virtual-world server **150** may be configured to adjust a confidence indicator **158** associated with the first user **110** based on virtual data interactions of the first user **110** with other users in the virtual environment **102**. For example, in response to detecting that the first user **110** performed a data interaction with the second user **112** in the virtual environment **102**, virtual-world server **150** may be configured to adjust a confidence indicator **158** of the first user **110** based on a confidence indicator **158** of the second user **112**. For example, virtual-world server **150** may decrement the confidence indicator **158** of the first user **110** by a pre-selected amount when the corresponding confidence indicator **158** of the second user **112** is equal to or below a threshold value. On the other hand, virtual-world server **150** may increment the confidence indicator **158** of the first user **110** by a pre-selected amount when the corresponding confidence indicator **158** of the second user **112** exceeds a threshold value. In one example, a confidence indicator **158** associated with a security profile of the first user **110** may be adjusted based on a corresponding confidence indicator **158** associated with the security profile of the second user **112**. The assumption here is that users who interact with less credible users (e.g., having lower confidence indicators) are more prone to security risks as compared to users who interact with highly credible users (e.g., having high confidence indicators). Thus, when the first user **110** interacts with users with low confidence indicators **158**, virtual-world server **150** lowers the corresponding confidence indicator of the first user **110**. On the other hand, when the first user **110** interacts with users with high confidence indicators, virtual-world server **150** raises the corresponding confidence indicator of the first user **110**.

(78) At operation **316**, virtual-world server **150** receives a request from a second user **112** for the first confidence indicator **158** of the first user **110** that relates to the first user profile **154** associated with the first user **110**.

(79) As described above, a second user **112** may request the virtual-world server **150** for one or more confidence indicators **158** associated with one or more respective user profiles **154** of the first user **110**. The second user **112** may perform one or more data interactions related to the first user **110** in the virtual environment **102** based on one or more confidence indicators **158** of the first user **110**. For example, the second user **112** may request a confidence indicator **158** associated with the security profile of the first user **110** and then decide to transfer virtual data objects **162** to the first user **110** or receive virtual data objects **162** from the first user **110** based on the confidence indicator **158** of the first user **110**. For instance, if the confidence indicator **158** associated with the security profile of the first user **110** is low (e.g., lower than a threshold value) indicating a high security risk associated with the first user **110**, the second user **112** may decide to not engage in data interactions with the first user **110** to avoid a data breach. Thus, the confidence indicators **158** may improve data security in the virtual environment **102**. In certain embodiments, the second user **112** or entity may use confidence indicators **158** associated with certain user profiles **154** of the first user **110** to make certain decisions relating to the first user **110**. For example, an engineering firm wanting to add engineers having certain skills to their team may request for a confidence indicator **158** associated with an engineering profile of the first user **110**. The engineering firm may decide to add the first user **110** to their team only when the confidence indicator **158** of the first user equals or exceeds a threshold value. In another example, a virtual fitness school wanting to add fitness instructors to their team may request for a confidence indicator **158** associated with a fitness profile of the first user **110**. The fitness school may decide to add the first user **110** to their team only when the confidence indicator **158** of the first user **110** equals or exceeds a threshold value.

(80) At operation **318**, virtual-world server **150** obtains the first confidence indicator **158** of the first user **110** that is associated with the first user profile **154**.

(81) As described above, virtual-world server **150** may be configured to provide upon request from a second user **112** or entity one or more confidence indicators **158** associated with one or more respective user profiles **154** of the first user **110**. In one embodiment, virtual-world server **150** may provide to the second user **112** or entity only those confidence indicators **158** the second user **112** or entity is authorized to obtain. For example, virtual-world server **150** may register the second user **112** to obtain confidence indicators **158** of other users (e.g., first user **110**) associated with certain user profiles **154**. In this case, virtual-world server **150** may provide to the second user **112** confidence indicators **158** associated with only those user profiles **154** the second user **112** is registered to receive. The virtual-world server **150** may not provide the second user **112** confidence indicators **158** associated with those user profiles **154** the second user **112** is not registered to receive. For example, an engineering firm may be registered to receive confidence indicators **158** of other users associated with engineering profiles only. This limits users and entities in the virtual environment **102** to obtain only that information about other users which is relevant to their needs. By controlling dissemination of user information, virtual-world server **150** improves data security in the virtual environment **102**.

(82) At operation **320**, virtual-world server **150** transmits the obtained first confidence indicator **158** of the first user **110** to a user device (e.g., second user device **106**) of the second user **112** for presenting to the second user **112** in the virtual environment **102**.

(83) As described above, virtual-world server **150** may be configured to indicate the requested one or more confidence indicators **158** to the second user **112** in the virtual environment **102**. For example, virtual-world server **150** may transmit a requested confidence indicator **158** to the second user device **106** which may display the confidence indicator **158** to the second user on a display of the second user device **106**.

(84) While several embodiments have been provided in the present disclosure, it should be understood that the disclosed systems and methods might be embodied in many other specific forms without departing from the spirit or scope of the present disclosure. The present examples are to be considered as illustrative and not restrictive, and the intention is not to be limited to the details given herein. For example, the various elements or components may be combined or integrated in another system or certain features may be omitted, or not implemented.

(85) In addition, techniques, systems, subsystems, and methods described and illustrated in the various embodiments as discrete or separate may be combined or integrated with other systems, modules, techniques, or methods without departing from the scope of the present disclosure. Other items shown or discussed as coupled or directly coupled or communicating with each other may be indirectly coupled or communicating through some interface, device, or intermediate component whether electrically, mechanically, or otherwise. Other examples of changes, substitutions, and alterations are ascertainable by one skilled in the art and could be made without departing from the spirit and scope disclosed herein.

(86) To aid the Patent Office, and any readers of any patent issued on this application in interpreting the claims appended hereto, applicants note that they do not intend any of the appended claims to invoke 35 U.S.C. § 112(f) as it exists on the date of filing hereof unless the words “means for” or “step for” are explicitly used in the particular claim.

Claims

1. A system comprising: a memory that stores a user credential associated with a first user; and at least one processor coupled to the memory, and configured to: receive the user credential associated with the first user, wherein the user credential provides the first user access to a virtual environment; authorize, based on the user credential, an avatar of the first user to enter the virtual environment; monitor a plurality of data interactions associated with the first user that are performed in the virtual environment; record, based on the plurality of data interactions, information relating to a set of parameters, wherein the set of parameters corresponds to a first user profile of a plurality of user profiles associated with the first user, wherein each parameter of the set of parameters defines a characteristic of the first user related to the first user profile; determine, based on the recorded information relating to the set of parameters, a first confidence indicator for the first user relating to the first user profile associated with the first user; receive a request from a second user for the first confidence indicator of the first user that relates to the first user profile associated with the first user, wherein the second user is registered to receive confidence indicators from a first set of user profiles associated with a virtual organization and the first user profile is part of the first set of user profiles; in response to receiving the request from the second user for the first confidence indicator, determine whether the first user profile associated with the first confidence indicator is included in the first set of user profiles associated with the virtual organization; obtain the first confidence indicator of the first user that is associated with the first user profile in response to determining that the first user profile associated with the first confidence indicator is included in the first set of user profiles; and transmit the obtained first confidence indicator to a user device of the second user for presenting to the second user in the virtual environment.

2. The system of claim 1, wherein: the plurality of data interactions associated with the first user comprises a data interaction performed by the first user with a third user in the virtual environment; the set of parameters comprises a second confidence indicator of the third user; the first confidence indicator and the second confidence indicator are numerical values; the at least one processor is configured to update the first confidence indicator of the first user by: decreasing the first confidence indicator by a first amount when the second confidence indicator of the third user is below a threshold; and increasing the first confidence indicator by a second amount when the second confidence indicator of the third user equals or exceeds the threshold.

3. The system of claim 1, wherein the at least one processor is further configured to: receive a request from the first user to generate a custom user profile based on a selected set of parameters; record, based on the plurality of data interactions, information relating to the selected set of parameters; determine, based on the recorded information relating to the selected set of parameters, a custom confidence indicator for the first user; and assign the custom confidence indicator to the custom user profile.
4. The system of claim 1, wherein the at least one processor is further configured to: record, based on the plurality of data interactions, information relating to a default set of parameters; and determine a second confidence indicator for the first user based on the recorded information relating to the default set of parameters.
5. The system of claim 4, wherein the default set of parameters corresponds to a default user profile of the first user.
6. The system of claim 1, wherein the at least one processor is configured to determine the first confidence indicator for the first user relating to the first user profile by adjusting the first confidence indicator based on the recorded information relating to the first set of parameters.
7. The system of claim 1, wherein the at least one processor is further configured to: receive a second request from a third user for a second confidence indicator of the first user based on a selected set of parameters; determining that information was recorded for one or more parameters of the selected set of parameters; generate the second confidence indicator for the first user based on the one or more parameters of the selected set of parameters; and transmit the second confidence indicator to a user device of the third user for presenting to the third user in the virtual environment.
8. The system of claim 1, wherein the at least one processor is further configured to: receive a request from the second user to perform a data interaction associated with the first user; compare the first confidence indicator of the first user with a threshold confidence indicator; and when the first confidence indicator equals or exceeds the threshold confidence indicator, authorize the requested data interaction associated with the first user.
9. A method for performing data interactions, comprising: receiving a user credential associated with a first user, wherein the user credential provides the first user access to a virtual environment; authorizing, based on the user credential, an avatar of the first user to enter the virtual environment; monitoring a plurality of data interactions associated with the first user that are performed in the virtual environment; recording, based on the plurality of data interactions, information relating to a set of parameters, wherein the set of parameters corresponds to a first user profile of a plurality of user profiles associated with the first user, wherein each parameter of the set of parameters defines a characteristic of the first user related to the first user profile; determining, based on the recorded information relating to the set of parameters, a first confidence indicator for the first user relating to the first user profile associated with the first user; receiving a request from a second user for the first confidence indicator of the first user that relates to the first user profile associated with the first user, wherein the second user is registered to receive confidence indicators from a first set of user profiles associated with a virtual organization and the first user profile is part of the first set of user profiles; in response to receiving the request from the second user for the first confidence indicator, determining whether the first user profile associated with the first confidence indicator is included in the first set of user profiles associated with the virtual organization; obtaining the first confidence indicator of the first user that is associated with the first user profile in response to determining that the first user profile associated with the first confidence indicator is included in the first set of user profiles; and transmitting the obtained first confidence indicator to a user device of the second user for presenting to the second user in the virtual environment.
10. The method of claim 9, wherein: the plurality of data interactions associated with the first user comprises a data interaction performed by the first user with a third user in the virtual environment; the set of parameters comprises a second confidence indicator of the third user; the first confidence

indicator and the second confidence indicator are numerical values; updating the first confidence indicator of the first user comprises: decreasing the first confidence indicator by a first amount when the second confidence indicator of the third user is below a threshold; and increasing the first confidence indicator by a second amount when the second confidence indicator of the third user equals or exceeds the threshold.

11. The method of claim 9, further comprising: receiving a request from the first user to generate a custom user profile based on a selected set of parameters; recording, based on the plurality of data interactions, information relating to the selected set of parameters; determining, based on the recorded information relating to the selected set of parameters, a custom confidence indicator for the first user; and assigning the custom confidence indicator to the custom user profile.

12. The method of claim 9, further comprising: recording, based on the plurality of data interactions, information relating to a default set of parameters; and determining a second confidence indicator for the first user based on the recorded information relating to the default set of parameters.

13. The method of claim 12, wherein the default set of parameters corresponds to a default user profile of the first user.

14. The method of claim 9, wherein determining the first confidence indicator for the first user relating to the first user profile comprises adjusting the first confidence indicator based on the recorded information relating to the first set of parameters.

15. A non-transitory computer-readable medium storing instructions that when executed by a processor cause the processor to: receive a user credential associated with a first user, wherein the user credential provides the first user access to a virtual environment; authorize, based on the user credential, an avatar of the first user to enter the virtual environment; monitor a plurality of data interactions associated with the first user that are performed in the virtual environment; record, based on the plurality of data interactions, information relating to a set of parameters, wherein the set of parameters corresponds to a first user profile of a plurality of user profiles associated with the first user, wherein each parameter of the set of parameters defines a characteristic of the first user related to the first user profile; determine, based on the recorded information relating to the set of parameters, a first confidence indicator for the first user relating to the first user profile associated with the first user; receive a request from a second user for the first confidence indicator of the first user that relates to the first user profile associated with the first user, wherein the second user is registered to receive confidence indicators from a first set of user profiles associated with a virtual organization and the first user profile is part of the first set of user profiles; in response to receiving the request from the second user for the first confidence indicator, determine whether the first user profile associated with the first confidence indicator is included in the first set of user profiles associated with the virtual organization; obtain the first confidence indicator of the first user that is associated with the first user profile in response to determining that the first user profile associated with the first confidence indicator is included in the first set of user profiles; and transmit the obtained first confidence indicator to a user device of the second user for presenting to the second user in the virtual environment.

16. The non-transitory computer-readable medium of claim 15, wherein: the plurality of data interactions associated with the first user comprises a data interaction performed by the first user with a third user in the virtual environment; the set of parameters comprises a second confidence indicator of the third user; the first confidence indicator and the second confidence indicator are numerical values; updating the first confidence indicator of the first user comprises: decreasing the first confidence indicator by a first amount when the second confidence indicator of the third user is below a threshold; and increasing the first confidence indicator by a second amount when the second confidence indicator of the third user equals or exceeds the threshold.

17. The non-transitory computer-readable medium of claim 15, wherein the instructions further cause the processor to: receive a request from the first user to generate a custom user profile based

on a selected set of parameters; record, based on the plurality of data interactions, information relating to the selected set of parameters; determine, based on the recorded information relating to the selected set of parameters, a custom confidence indicator for the first user; and assign the custom confidence indicator to the custom user profile.

18. The non-transitory computer-readable medium of claim 15, wherein the instructions further cause the processor to: record, based on the plurality of data interactions, information relating to a default set of parameters; and determine a second confidence indicator for the first user based on the recorded information relating to the default set of parameters.

19. The non-transitory computer-readable medium of claim 18, wherein the default set of parameters corresponds to a default user profile of the first user.

20. The non-transitory computer-readable medium of claim 15, wherein determining the first confidence indicator for the first user relating to the first user profile comprises adjusting the first confidence indicator based on the recorded information relating to the first set of parameters.
