

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411936
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Wang; Wei et al.

On-demand trusted extended reality environments

Abstract

The concepts and technologies disclosed herein are directed to on-demand trusted extended reality (“XR”) environments. According to one aspect disclosed herein, a user device can create a trusted list identifying at least one trusted XR environment. The user device can connect to an untrusted XR server computer and can allow a user avatar associated with a user to enter an untrusted XR environment provided by the untrusted XR server. The user device can detect an event for which a trusted XR environment is desired. The user device can select the trusted XR environment to handle the event. The user device can select the trusted XR environment from the trusted list. The user device can instruct the untrusted XR server computer to teleport the user avatar from the untrusted XR environment to the trusted XR environment.

Inventors: Wang; Wei (Harrison, NJ), Istomin; Mikhail (Brooklyn, NY), Johnson; Lars (Brooklyn, NY), Rosencrantz; Rachel (Seattle, WA)

Applicant: AT&T Intellectual Property I, L.P. (Atlanta, GA)

Family ID: 91079869

Assignee: AT&T Intellectual Property I, L.P. (Atlanta, GA)

Appl. No.: 17/993646

Filed: November 23, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240169052 A1	May. 23, 2024

Publication Classification

Int. Cl.: G06F21/53 (20130101); G06F21/55 (20130101)

U.S. Cl.:

CPC **G06F21/53** (20130101); **G06F21/554** (20130101); G06F2221/034 (20130101)

Field of Classification Search

CPC: G06F (21/53); G06F (21/554); G06F (2221/034)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2017/0181645	12/2016	Mahalingam	N/A	G16H 10/60
2022/0070232	12/2021	Young	N/A	G06T 19/003
2022/0109810	12/2021	Kancharlawar	N/A	H04N 7/157

Primary Examiner: Gadalla; Hany S.

Attorney, Agent or Firm: Hartman & Citrin LLC

Background/Summary

BACKGROUND

(1) The advent of metaverse as a potential successor to the Internet will bring a number of changes. One foreseeable change is the way in which people interact with non-physical environments. Today, interactions with the Internet are limited to text and multimedia consumption (known as web2—read and write). This media is usually static in nature, such as webpages with multimedia (e.g., images, audio, and/or video). More dynamic interactions are either limited (e.g., forums, chat rooms, social media groups, and the like) or handled in a strictly-controlled environment (e.g., voice, video, and/or text chat and multiplayer games). Metaverse (also known as web3—read, write, own) will allow for more interactive environments (e.g., virtual rooms) that incorporate aspects of extended reality (“XR”), such as virtual reality (“VR”), augmented reality (“AR”), and mixed reality (“MR”).

(2) In recent years, the widespread adoption of the work-from-home model has had negative effects on some workers due to less in-person interaction with peers. XR technology provides a safe environment for co-workers to meet in a virtual space and interact as if in-person. This can increase morale and decrease the negative effects of isolation. Moreover, as the cost of XR headsets continues to decrease, XR technology will continue to become more commonplace, allowing friends and families to engage in social events, holidays, and daily social interactions.

(3) Metaverse is an ever-growing arena containing worlds created by various companies. Some spaces hosted by well-known companies in metaverse might be secure, similar to secure uniform resource locators (“URLs”) today, but others might not be secure and may pose security risks. Currently, no authority exists that is responsible for assigning security labels to spaces within metaverse as secure or not secure. Additional challenges are created by the combination of the immersive nature of metaverse experiences and the fact that the objects in XR environment are dynamic and often transient. Additionally, with objects belonging to different owners and avatars that can take any form, ensuring the safety of these spaces is a challenge.

SUMMARY

(4) Concepts and technologies are disclosed that are directed to on-demand trusted XR environments. According to one aspect disclosed herein, a user device can create a trusted list identifying at least one trusted XR environment. The user device can connect to an untrusted XR server computer and can allow a user avatar associated with a user to enter an untrusted XR environment provided by the untrusted XR server computer. The user device can detect an event for which a trusted XR environment is desired. In some embodiments, the user device can detect the event based upon receiving a direct request from the user. The event can include an interaction between the user and at least one additional user through the user avatar and at least one additional user avatar. Alternatively, the event can include an interaction between the user, represented as the user avatar, and a business (e.g., a financial institution). The user device can select the trusted XR environment to handle the event. The user device can select the trusted XR environment from the trusted list. In some embodiments, the trusted list is defined, at least in part, by the user. In other embodiments, the trusted list is defined, at least in part, based upon crowd-sourced data. The user device can instruct the untrusted XR server computer to teleport the user avatar from the untrusted XR environment to the trusted XR environment. After the event is handled, the user device can instruct a trusted XR server computer to teleport the user avatar back to the untrusted XR environment.

(5) It should be appreciated that the above-described subject matter may be implemented as a computer-controlled apparatus, a computer process, a computing system, or as an article of manufacture such as a computer-readable storage medium. These and various other features will be apparent from a reading of the following Detailed Description and a review of the associated drawings.

(6) This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended that this Summary be used to limit the scope of the claimed subject matter. Furthermore, the claimed subject matter is not limited to implementations that solve any or all disadvantages noted in any part of this disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a block diagram illustrating aspects of an illustrative operating environment in which the concepts and technologies disclosed herein can be implemented.

(2) FIG. 2 is a flow diagram illustrating aspects of a method for providing on-demand trusted XR environments, according to an illustrative embodiment.

(3) FIG. 3 is a block diagram illustrating an example computer system capable of implementing aspects of the embodiments presented herein.

(4) FIG. 4 schematically illustrates a network, according to an illustrative embodiment.

(5) FIG. 5 is a block diagram illustrating an example mobile device and components thereof, according to an illustrative embodiment.

(6) FIG. 6 is a diagram illustrating a virtualized cloud architecture capable of implementing aspects of the embodiments presented herein.

DETAILED DESCRIPTION

(7) The concepts and technologies disclosed herein are directed to on-demand trusted XR environments. According to embodiments, a user, at any time, in an untrusted XR environment, regardless of whether the user knows if the XR environment is secure or not, can choose to, on-demand, teleport to a trusted XR environment to perform one or more tasks within the trusted XR environment, and then teleport back into the untrusted XR environment when the trusted XR

environment is no longer needed.

(8) While the subject matter described herein may be presented, at times, in the general context of program modules that execute in conjunction with the execution of an operating system and application programs on a computer system, those skilled in the art will recognize that other implementations may be performed in combination with other types of program modules.

Generally, program modules include routines, programs, components, data structures, computer-executable instructions, and/or other types of structures that perform particular tasks or implement particular abstract data types. Moreover, those skilled in the art will appreciate that the subject matter described herein may be practiced with other computer systems, including hand-held devices, mobile devices, wireless devices, multiprocessor systems, distributed computing systems, microprocessor-based or programmable consumer electronics, minicomputers, mainframe computers, routers, switches, other computing devices described herein, and the like.

(9) Referring now to FIG. 1, aspects of an operating environment **100** in which various embodiments presented herein may be implemented will be described, according to an illustrative embodiment. The illustrated operating environment **100** includes an untrusted XR server computer **102** and a trusted XR server computer **104**. Both the untrusted XR server computer **102** and the trusted XR server computer **104** can provide an XR service to a plurality of user devices **106A-106N** (hereafter referred to collectively as “user devices **106**” or individually as “user device **106**” associated with a plurality of users **108A-108N**, respectively (hereafter referred to collectively as “users **108**” or individually as “user **108**”). The XR service can be a virtual reality (“VR”) service, an augmented reality (“AR”) service, a mixed reality service, or any combination thereof. The XR service can create XR environments in which the users **108** can interact with each other and/or with other entities (not shown) such as businesses.

(10) “Virtual reality” or “VR” is used herein to describe a concept that provides a computer-generated environment (also referred to herein as a “virtual environment”) that the users **108** can explore via the user devices **106**. A virtual environment can include a gathering of many individual objects that represent small parts of the overall environment. A virtual environment may be a single room, a house, a city, a world, or any other virtualization of a real-world environment. The virtual environment may be a completely imaginary environment that does not have a real-world analog. The virtual environment may be a combination of real-world and imaginary environments. A virtual object can represent any real-world object, such as furniture, individual avatars (i.e., representations of real-world users), animals (e.g., virtual pets and wildlife), vehicles, electronics, and the like. Each virtual object may belong to a virtual environment. A virtual object may be something that was created as part of the virtual environment. Alternatively, a virtual object may be something that was added at a later point by either the environment owner or another user.

(11) A VR environment can be generated by any software framework designed for the creation and development of graphics. Some example software frameworks include, but are not limited to, UNREAL ENGINE (available from Epic Games), UNITY (available from Unity Technologies), CRYENGINE (available from Crytek), HAVOK VISION ENGINE (available from Havok), and open source software frameworks. In some embodiments, the software frameworks utilize graphics assets, such as textures, that include or are derived from photographs of the real-world environment that is to be virtualized. Those skilled in the art will appreciate the wide range of graphical fidelity, visual styles, and other attributes a particular VR environment may have, and as such, further details in this regard are not provided herein.

(12) “Augmented reality” or “AR” is used herein to describe a concept in which at least a portion of a physical, real-world environment is augmented to include computer-generated data. The computer-generated data can include virtual objects that are presented over and/or spatially integrated with real-world objects of the physical, real-world environment. The virtual objects can include text, colors, patterns, gradients, graphics, other images, videos, animations, combinations thereof, and the like. Computer-generated data that augments in some manner a view of a physical,

real-world environment and/or elements thereof is referred to herein generally as an “augmentation.”

(13) The AR service can provide a live view of a physical, real-world environment. In these embodiments, the AR service may utilize a camera component (best shown in FIG. 5) of the user device **106** to provide a live view of the physical, real-world environment to be augmented. In other embodiments, the AR service can provide a non-live view of a physical, real-world environment. In these embodiments, the non-live view can present a physical, real-world environment as a static image. Accordingly, a reality that is to be augmented need not be a present reality and can instead be a past reality, encapsulated in a photograph that is augmented at a later time such as the present, for example.

(14) “Mixed reality” is used herein to describe a concept in which elements of VR and elements of AR are used together. The term “XR” is used herein to refer to VR-only, AR-only, or mixed reality.

(15) In the illustrated example, the untrusted XR server computer **102** provides one or more untrusted XR environments **110** (hereafter referred to collectively as “untrusted XR environments **110**” or individually as “untrusted XR environment **110**”) in which one or more user avatars **112** (hereafter referred to collectively as “user avatars **112**” or individually as “user avatar **112**”), which are digital representations of one or more of the users **108**, can interact with each other and/or one or more untrusted objects **114** (hereafter referred to collectively as “untrusted objects **114**” or individually as “untrusted object **114**”). The untrusted objects **114** can include any XR object represented in the untrusted XR environment **110** that has not been verified by one or more trusted authorities **116** (hereafter referred to collectively as “trusted authorities **116**” or individually as “trusted authority **116**”). Generally, the untrusted XR environment **110** may provide a space in which the users **108**, via the user avatars **112**, can interact with each other through chat, interactive games, and/or other activities that do not require a secure, trusted environment.

(16) The trusted XR server computer **104** provides one or more trusted XR environments **118** (hereafter referred to collectively as “trusted XR environments **118**” or individually as “trusted XR environment **118**”) in which one or more teleported user avatars **120** (hereafter referred to collectively as “teleported user avatars **120**” or individually as “teleported user avatar **120**”) can interact with each other and/or one or more trusted objects **122** (hereafter referred to collectively as “trusted objects **122**” or individually as “trusted object **122**”). The trusted objects **122** can include any XR object represented in the trusted XR environment **118** that has been verified by one or more of the trusted authorities **116** (e.g., certificate authority). Generally, the trusted XR environment **118** may provide a space in which the users **108**, via the teleported user avatars **120**, can interact with each other through chat, interactive games, and/or other activities that require a secure, trusted environment.

(17) The untrusted XR server computer **102** can execute an untrusted XR server operating system (“OS”) **124** and one or more application programs such as an untrusted XR server application **126**. Similarly, the trusted XR server computer **104** can execute a trusted XR server OS **128** and one or more application programs such as a trusted XR server application **130**. The untrusted XR server OS **124** and the trusted XR server OS **128** are computer programs for controlling the operation of the untrusted XR server computer **102** and the trusted XR server computer **104**, respectively. The untrusted XR server application **126** and the trusted XR server application **130** are executable programs configured to execute on top of the untrusted XR server OS **124** and the trusted XR server OS **128**, respectively, to provide various functions described herein.

(18) The untrusted XR server computer **102**, the trusted XR server computer **104**, the user devices **106**, and the trusted authorities **116** can communicate via one or more networks **132**. An example network **400** is illustrated and described herein below with reference to FIG. 4.

(19) The illustrated user devices **106** can be or can include one or more mobile telephones, smartphones, tablet computers, slate computers, smart watches, fitness devices, smart glasses (e.g., the GOOGLE GLASS family of products), a dedicated AR device, a dedicated VR device, a

dedicated mixed reality device, a wearable device, mobile media playback devices, laptop computers, notebook computers, ultrabook computers, netbook computers, computers of other form factors, computing devices of other form factors, other computing systems, other computing devices, and/or the like. It should be understood that the functionality of the user devices **106** can be provided by a single device, by two or more similar devices, and/or by two or more dissimilar devices. For purposes of describing the concepts and technologies disclosed herein, the user device **106** is described herein as a smartphone. It should be understood that this embodiment is illustrative, and should not be construed as being limiting in any way.

(20) In the illustrated example, a first user device **106A** includes a device OS **134**, an XR app **136**, and an XR component **138**. The other user devices **106B-106N** can be configured the same as or similar to the first user device **106A**. It should be understood, however, that the user devices **106** can include other components. Illustrative example architectures of the user devices **106** are described in greater detail herein with reference to FIGS. **3** and **5**.

(21) The device OS **134** can control the operation of the user device **106**. In some embodiments, the device OS **134** includes the functionality of the XR app **136**. The device OS **134** can be executed by one or more processors (best shown in FIGS. **3** and **5**) to cause the user device **106** to perform various operations. The device OS **134** can include a member of the IOS family of operating systems from APPLE INC., a member of the ANDROID OS family of operating systems from GOOGLE INC., and/or other operating systems. These operating systems are merely illustrative of some contemplated operating systems that may be used in accordance with various embodiments of the concepts and technologies described herein and therefore should not be construed as being limiting in any way.

(22) The XR app **136** can execute on top of the device OS **134**. The XR app **136** can be executed by one or more processors (best shown in FIGS. **3** and **5**) to cause the user device **106** to perform various operations described herein. The XR app **136** can be a client-side application that communicates, via the network(s) **132**, with the untrusted XR server application **126** executing on the untrusted XR server computer **102** to provide, at least in part, an untrusted XR service to the user **108** of the user device **106**. The XR app **136** can be a client-side application that communicates, via the network(s) **132**, with the trusted XR server application **130** executing on the trusted XR server computer **104** to provide, at least in part, a trusted XR service to the user **108** of the user device **106**. The XR app **136**, in some embodiments, can utilize the XR component **138** to provide, at least in part, an XR service to the user **108** of the user device **106**. The illustrated embodiment of the XR component **138** represents the XR component **138** as an internal component of the user device **106**. It should be understood that the XR component **138** alternatively may be an external component that is in communication with the user device **106** via a wired or wireless connection. The XR component **138**, in some embodiments, is or includes a camera (e.g., a still camera and/or video camera), a sensor (e.g., an accelerometer, a global positioning system sensor, a solid state compass, or the like), a display (e.g., an integrated display, a head-mounted display, an eyeglasses display, a head-up display, an external monitor, a projection system, or a holographic display), an input device, or the like. The XR component **138**, in other embodiments, is or includes a display (e.g., an integrated display, a head-mounted display, an eyeglasses display, a head-up display, an external monitor, a projection system, or a holographic display), an input device, a combination thereof, or the like. In some embodiments, the XR component **138** is META QUEST (available from META), PLAYSTATION VR (available from SONY), HTC VIVE (available from HTC and VALVE), MICROSOFT HOLOLENS (available from MICROSOFT), or the like. The XR app **136** can provide an interface, using the XR component **138**, through which the user **108** can interact with the untrusted XR environment **110** provided, at least in part, by the untrusted XR server computer **102**. The XR app **136** also can provide an interface, using the XR component **138**, through which the user **108** can interact with the trusted XR environment **118** provided, at least in part, by the trusted XR server computer **104**.

(23) In the illustrated example, the first user device **106A** also has a trusted environment list (“trusted list”) **140**. The other user devices **106B-106N** can include similar lists. The trusted list **140** can be defined by the user **108**, by the trusted authority **116**, and/or crowd-sourced from other users (e.g., the users **108B-108N**). In some embodiments, the trusted list **140** can identify the trusted XR environment(s) **118** that the user **108** personally trusts without external verification, such as via the trusted authority **116**. In other embodiments, the trusted list **140** can identify the trusted XR environment(s) **118** that have been separately verified by a trusted entity, such as the trusted authority **116**. In still other embodiments, the trusted list **140** can identify the trusted XR environment(s) **118** determined based upon crowd-sourced data. For example, the crowd-sourced data can include review data, and the determination of whether a given XR environment should be considered a trusted XR environment **118** can be based on review scores (e.g., 1-5 stars) and a specified review score threshold (e.g., above 4.5 stars).

(24) As briefly mentioned above, the user **108** may engage in the untrusted XR environment **110** and then desire to be teleported (as a user avatar **112**) to the trusted XR environment **118** to perform one or more tasks. The tasks can be anything the user **108** wants to do within the trusted XR environment **118** instead of the untrusted XR environment **110**. A couple example tasks are private conversations and financial transactions. Other tasks are contemplated.

(25) The concept of teleportation, as used herein, is the transfer of the user avatar **112** from the untrusted XR environment **110** to the trusted XR environment **118** (shown as the teleported user avatar **120**) or vice versa. Additional details regarding teleportation will be described in greater detail herein below.

(26) In some embodiments, the user **108** may want to understand what occurred in the untrusted XR environment **110** while the user avatar **112** was in the trusted XR environment **118**. In these embodiments, the untrusted XR environment **110** can be recorded so that the user **108** can replay a recording of the untrusted XR environment **110** in the user's **108** absence. In this manner, the user **108** can review what happened in the untrusted XR environment **110** (e.g., interactions among other user avatars **112** and/or untrusted objects **114** while the user **108** was in the trusted XR environment **118**). Moreover, the user **108** may establish one or more alarms that can be triggered upon specific events that occur within the untrusted XR environment **110** during the user's **108** absence. Alternatively or additionally, an alarm can be established based upon a timer, the expiration of which can notify the user **108** that the user **108** has spent too long in the trusted XR environment **118**.

(27) Turning now to FIG. 2, aspects of a method **200** for providing on-demand trusted XR environments **118** will be described, according to an illustrative embodiment. It should be understood that the operations of the methods disclosed herein are not necessarily presented in any particular order and that performance of some or all of the operations in an alternative order(s) is possible and is contemplated. The operations have been presented in the demonstrated order for ease of description and illustration. Operations may be added, omitted, and/or performed simultaneously, without departing from the scope of the concepts and technologies disclosed herein.

(28) It also should be understood that the method disclosed herein can be ended at any time and need not be performed in their respective entireties. Some or all operations of the method, and/or substantially equivalent operations, can be performed by execution of computer-readable instructions included on a computer storage media, as defined herein. The term “computer-readable instructions,” and variants thereof, as used herein, is used expansively to include routines, applications, application modules, program modules, programs, components, data structures, algorithms, and the like. Computer-readable instructions can be implemented on various system configurations including the untrusted XR server computer **102**, the trusted XR server computer **104**, the user device **106**, the trusted authority **116**, single-processor or multiprocessor systems, minicomputers, mainframe computers, personal computers, hand-held computing devices,

microprocessor-based, programmable consumer electronics, combinations thereof, and the like.

(29) Thus, it should be appreciated that the logical operations described herein are implemented (1) as a sequence of computer implemented acts or program modules running on a computing system and/or (2) as interconnected machine logic circuits or circuit modules within the computing system. The implementation is a matter of choice dependent on the performance and other requirements of the computing system. Accordingly, the logical operations described herein are referred to variously as states, operations, structural devices, acts, or modules. These states, operations, structural devices, acts, and modules may be implemented in software, in firmware, in special purpose digital logic, and any combination thereof. As used herein, the phrase “cause a processor to perform operations” and variants thereof refers to causing a processor of a computing system or device, such as the untrusted XR server computer **102**, the trusted XR server computer **104**, the user device **106**, or the trusted authority **116**, to perform one or more operations and/or causing the processor to direct other components of the computing system or device to perform one or more of the operations.

(30) For purposes of illustrating and describing some of the concepts of the present disclosure, the methods disclosed herein are described as being performed, at least in part, by the untrusted XR server computer **102**, the trusted XR server computer **104**, the user device **106**, the trusted authority **116**, or some combination thereof, via execution of one or more software modules and/or software applications. It should be understood that additional and/or alternative devices and/or network nodes can provide the functionality described herein via execution of one or more modules, applications, and/or other software. Thus, the illustrated embodiments are illustrative, and should not be viewed as being limiting in any way.

(31) The method **200** begins and proceeds to operation **202**. At operation **202**, the user device **106** creates the trusted list **140**. The trusted list **140** can be defined by the user **108**, by the trusted authority **116**, and/or crowd-sourced from other users (e.g., the users **108B-108N**). In some embodiments, the trusted list **140** can identify the trusted XR environment(s) **118** that the user **108** personally trusts without external verification, such as via the trusted authority **116**. In other embodiments, the trusted list **140** can identify the trusted XR environment(s) **118** that have been separately verified by a trusted entity, such as the trusted authority **116**. In still other embodiments, the trusted list **140** can identify the trusted XR environment(s) **118** determined based upon crowd-sourced data. For example, the crowd-sourced data can include review data, and the determination of whether a given XR environment should be considered a trusted XR environment **118** can be based on review scores (e.g., 1-5 stars) and a specified review score threshold (e.g., above 4.5 stars).

(32) From operation **202**, the method **200** proceeds to operation **204**. At operation **204**, the user avatar **112** enters the untrusted XR environment **110**. For example, the user **108** can instruct the XR application **136** to connect to the untrusted XR server computer **102** and allow the user avatar **112** to enter the untrusted XR environment **110**. Since the untrusted XR environment **110** is untrusted, entry into the untrusted XR environment **110** does not require any authentication credentials to verify the identity of the user **108** associated with the user avatar **112**.

(33) From operation **204**, the method **200** proceeds to operation **206**. At operation **206**, the user device **106** detects an event for which a trusted XR environment **118** is desired. The event can be a direct request made by the user **108** via the XR app **136**. The event can be an interaction between two or more of the users **108** via respective user avatars **112** within the untrusted XR environment **110**. The interaction may be better-suited in the trusted XR environment **118**, and as such, the XR app **136** of the respective user devices **106** may prompt the users **108** to move the interaction to the trusted XR environment **118**. The event may be an external request made, for example, by another entity such as the trusted authority **116**. The event can be anything for which a trusted XR environment **118** is desired. The example events described above therefore should not be construed as being limiting in any way.

(34) From operation **206**, the method **200** proceeds to operation **208**. At operation **208**, the user device **106** selects, from the trusted list **140**, the trusted XR environment **118** in which to handle the event. In some embodiments, the user device **106** can prompt the user **108** to provide the selection. In other embodiments, the user device **106** can make the selection based upon the nature of the event. Other methods of selection are contemplated.

(35) From operation **208**, the method **200** proceeds to operation **210**. At operation **210**, the trusted XR server computer **104** establishes the trusted XR environment **118**. Alternatively, the trusted XR environment **118** may be pre-established. The trusted XR environment **118** may be temporary or on-going.

(36) From operation **210**, the method **200** proceeds to operation **212**. At operation **212**, the untrusted XR server computer **102** and the trusted XR server computer **104** coordinate to teleport the user avatar **112** from the untrusted XR server computer **102** to the trusted XR server computer **104** via the network(s) **132**. From operation **212**, the method **200** proceeds to operation **214**. At operation **214**, the event is handled within the trusted XR environment **118**. From operation **214**, the method **200** proceeds to operation **216**. At operation **216**, the trusted XR server computer **104** and the untrusted XR server computer **102** coordinate to teleport the user avatar **112** back to the untrusted XR server computer **102** via the network(s) **132**.

(37) From operation **216**, the method **200** proceeds to operation **218**. At operation **218**, the method **200** ends.

(38) FIG. **3** is a block diagram illustrating a computer system **300** configured to provide the functionality in accordance with various embodiments of the concepts and technologies disclosed herein. In some implementations, the untrusted XR server computer **102**, the trusted XR server computer **104**, the user device **106**, and/or the trusted authority **116** utilize an architecture that is the same as or similar to the architecture of the computer system **300**. It should be understood, however, that modification to the architecture may be made to facilitate certain interactions among elements described herein.

(39) The computer system **300** includes a processing unit **302**, a memory **304**, one or more user interface devices **306**, one or more input/output (“I/O”) devices **308**, and one or more network devices **310**, each of which is operatively connected to a system bus **312**. The bus **312** enables bi-directional communication between the processing unit **302**, the memory **304**, the user interface devices **306**, the I/O devices **308**, and the network devices **310**.

(40) The processing unit **302** may be a standard central processor that performs arithmetic and logical operations, a more specific purpose programmable logic controller (“PLC”), a programmable gate array, a system-on-a-chip, or other type of processor known to those skilled in the art and suitable for controlling the operation of the server computer. Processing units are generally known, and therefore are not described in further detail herein.

(41) The memory **304** communicates with the processing unit **302** via the system bus **312**. In some embodiments, the memory **304** is operatively connected to a memory controller (not shown) that enables communication with the processing unit **302** via the system bus **312**. The memory **304** includes an operating system **314** and one or more program modules **316**. The operating system **314** can include, but is not limited to, members of the WINDOWS, WINDOWS CE, and/or WINDOWS MOBILE families of operating systems from MICROSOFT CORPORATION, the LINUX family of operating systems, the MAC OSX and/or iOS families of operating systems from APPLE CORPORATION, other operating systems, and the like. The operating system **314** can be the untrusted XR server OS **124**/trusted XR server OS **128** as illustrated and described with reference to FIG. **1**.

(42) The program modules **316** may include various software and/or program modules to perform the various operations described herein. The program modules **316** for the computer system **300** embodied as the untrusted XR server computer **102** can include the untrusted XR server application **126**. The program modules **316** for the computer system **300** embodied as the trusted XR server

computer **104** can include the trusted XR server application **130**. The program modules **316** for the computer system **300** embodied as the user device **106** can include the XR app **136**. The program modules **316** and/or other programs can be embodied in computer-readable media containing instructions that, when executed by the processing unit **302**, perform one or more operations, such as the operations described herein above with reference to the method **200** illustrated in FIG. 2. According to embodiments, the program modules **316** may be embodied in hardware, software, firmware, or any combination thereof.

(43) By way of example, and not limitation, computer-readable media may include any available computer storage media or communication media that can be accessed by the computer system **300**. Communication media includes computer-readable instructions, data structures, program modules, or other data in a modulated data signal such as a carrier wave or other transport mechanism and includes any delivery media. The term “modulated data signal” means a signal that has one or more of its characteristics changed or set in a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media. Combinations of any of the above should also be included within the scope of computer-readable media.

(44) Computer storage media includes volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage of information such as computer-readable instructions, data structures, program modules, or other data. Computer storage media includes, but is not limited to, RAM, ROM, Erasable Programmable ROM (“EPROM”), Electrically Erasable Programmable ROM (“EEPROM”), flash memory or other solid state memory technology, CD-ROM, digital versatile disks (“DVD”), or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by the computer system **300**. In the claims, the phrase “computer storage medium,” “computer-readable storage medium,” and variations thereof does not include waves or signals per se and/or communication media, and therefore should be construed as being directed to “non-transitory” media only.

(45) The user interface devices **306** may include one or more devices with which a user accesses the computer system **300**. The user interface devices **306** may include, but are not limited to, computers, servers, personal digital assistants, cellular phones, or any suitable computing devices. The I/O devices **308** enable a user to interface with the program modules **316**. In one embodiment, the I/O devices **308** are operatively connected to an I/O controller (not shown) that enables communication with the processing unit **302** via the system bus **312**. The I/O devices **308** may include one or more input devices, such as, but not limited to, a keyboard, a mouse, or an electronic stylus. Further, the I/O devices **308** may include one or more output devices, such as, but not limited to, a display screen or a printer.

(46) The network devices **310** enable the computer system **300** to communicate with other networks or remote systems via a network **318**, such as the network(s) **132/400** (best shown in FIGS. 1 and 4). Examples of the network devices **310** include, but are not limited to, a modem, a radio frequency (“RF”) or infrared (“IR”) transceiver, a telephonic interface, a bridge, a router, or a network card. The network **318** may include a wireless network such as, but not limited to, a wireless local area network (“WLAN”), a wireless wide area network (“WWAN”), a wireless personal area network (“WPAN”) such as provided via BLUETOOTH technology, a wireless metropolitan area network (“WMAN”) such as a WiMAX network or metropolitan cellular network. Alternatively, the network **318** may be a wired network such as, but not limited to, a wide area network (“WAN”), a wired LAN such as provided via Ethernet, a wired personal area network (“PAN”), or a wired metropolitan area network (“MAN”).

(47) Turning now to FIG. 4, additional details of a network **400**, such as the network(s) **132**, are

illustrated, according to an illustrative embodiment. The network **400** includes a cellular network **402**, a packet data network **404**, for example, the Internet, and a circuit switched network **406**, for example, a publicly switched telephone network (“PSTN”). The cellular network **402** includes various components such as, but not limited to, base transceiver stations (“BTSs”), Node-B's or e-Node-B's, base station controllers (“BSCs”), radio network controllers (“RNCs”), mobile switching centers (“MSCs”), mobile management entities (“MMEs”), short message service centers (“SMSCs”), multimedia messaging service centers (“MMSCs”), home location registers (“HLRs”), home subscriber servers (“HSSs”), visitor location registers (“VLRs”), charging platforms, billing platforms, voicemail platforms, GPRS core network components, location service nodes, an IP Multimedia Subsystem (“IMS”), and the like. The cellular network **402** also includes radios and nodes for receiving and transmitting voice, data, and combinations thereof to and from radio transceivers, networks, the packet data network **404**, and the circuit switched network **406**.

(48) A mobile communications device **408**, such as, for example, the user device **106**, a cellular telephone, a user equipment, a mobile terminal, a PDA, a laptop computer, a handheld computer, and combinations thereof, can be operatively connected to the cellular network **402**. The cellular network **402** can be configured as a 2G Global System for Mobile communications (“GSM”) network and can provide data communications via General Packet Radio Service (“GPRS”) and/or Enhanced Data rates for GSM Evolution (“EDGE”). Additionally, or alternatively, the cellular network **402** can be configured as a 3G Universal Mobile Telecommunications System (“UMTS”) network and can provide data communications via the High-Speed Packet Access (“HSPA”) protocol family, for example, High-Speed Downlink Packet Access (“HSDPA”), Enhanced UpLink (“EUL”) (also referred to as High-Speed Uplink Packet Access (“HSUPA”)), and HSPA+. The cellular network **402** also is compatible with 4G mobile communications standards such as Long-Term Evolution (“LTE”), or the like, as well as evolved and future mobile standards.

(49) The packet data network **404** includes various devices, for example, servers, computers, databases, and other devices in communication with another, as is generally known. The packet data network **404** devices are accessible via one or more network links. The servers often store various files that are provided to a requesting device such as, for example, a computer, a terminal, a smartphone, or the like. Typically, the requesting device includes software (a “browser”) for executing a web page in a format readable by the browser or other software. Other files and/or data may be accessible via “links” in the retrieved files, as is generally known. In some embodiments, the packet data network **404** includes or is in communication with the Internet. The circuit switched network **406** includes various hardware and software for providing circuit switched communications. The circuit switched network **406** may include, or may be, what is often referred to as a plain old telephone system (“POTS”). The functionality of a circuit switched network **406** or other circuit-switched network are generally known and will not be described herein in detail.

(50) The illustrated cellular network **402** is shown in communication with the packet data network **404** and a circuit switched network **406**, though it should be appreciated that this is not necessarily the case. One or more Internet-capable devices **410**, for example, the user device **106**, a PC, a laptop, a portable device, or another suitable device, can communicate with one or more cellular networks **402**, and devices connected thereto, through the packet data network **404**. It also should be appreciated that the Internet-capable device **410** can communicate with the packet data network **404** through the circuit switched network **406**, the cellular network **402**, and/or via other networks (not illustrated).

(51) As illustrated, a communications device **412**, for example, a telephone, facsimile machine, modem, computer, or the like, can be in communication with the circuit switched network **406**, and therethrough to the packet data network **404** and/or the cellular network **402**. It should be appreciated that the communications device **412** can be an Internet-capable device, and can be substantially similar to the Internet-capable device **410**. In the specification, the network **400** is used to refer broadly to any combination of the networks **402**, **404**, **406**. It should be appreciated

that substantially all of the functionality described with reference to the network **400** can be performed by the cellular network **402**, the packet data network **404**, and/or the circuit switched network **406**, alone or in combination with other networks, network elements, and the like.

(52) Turning now to FIG. 5, an illustrative mobile device **500** and components thereof will be described. In some embodiments, the user device **106** described above with reference to FIG. 1 can be configured as and/or can have an architecture similar or identical to the mobile device **500** described herein in FIG. 5. It should be understood, however, that the user device **106** may or may not include the functionality described herein with reference to FIG. 5. While connections are not shown between the various components illustrated in FIG. 5, it should be understood that some, none, or all of the components illustrated in FIG. 5 can be configured to interact with one other to carry out various device functions. In some embodiments, the components are arranged so as to communicate via one or more busses (not shown). Thus, it should be understood that FIG. 5 and the following description are intended to provide a general understanding of a suitable environment in which various aspects of embodiments can be implemented, and should not be construed as being limiting in any way.

(53) As illustrated in FIG. 5, the mobile device **500** can include a display **502** for displaying data. According to various embodiments, the display **502** can be configured to display various graphical user interface (“GUI”) elements, text, images, video, advertisements, prompts, virtual keypads and/or keyboards, messaging data, notification messages, metadata, internet content, device status, time, date, calendar data, device preferences, map and location data, combinations thereof, and the like. The mobile device **500** also can include a processor **504** and a memory or other data storage device (“memory”) **506**. The processor **504** can be configured to process data and/or can execute computer-executable instructions stored in the memory **506**. The computer-executable instructions executed by the processor **504** can include, for example, an operating system **508** (e.g., the device OS **134**), one or more applications **510** (e.g., the XR app **136**), other computer-executable instructions stored in a memory **506**, or the like. In some embodiments, the applications **510** also can include a UI application (not illustrated in FIG. 5).

(54) The UI application can interface with the operating system **508** to facilitate user interaction with functionality and/or data stored at the mobile device **500** and/or stored elsewhere. In some embodiments, the operating system **508** can include a member of the IOS family of operating systems from APPLE INC., a member of the ANDROID OS family of operating systems from GOOGLE INC., and/or other operating systems. These operating systems are merely illustrative of some contemplated operating systems that may be used in accordance with various embodiments of the concepts and technologies described herein and therefore should not be construed as being limiting in any way.

(55) The UI application can be executed by the processor **504** to aid a user in entering content, viewing account information, answering/initiating calls, entering/deleting data, entering and setting user IDs and passwords for device access, configuring settings, manipulating address book content and/or settings, multimode interaction, interacting with other applications **510**, and otherwise facilitating user interaction with the operating system **508**, the applications **510**, and/or other types or instances of data **512** that can be stored at the mobile device **500**.

(56) According to various embodiments, the applications **510** can include, for example, presence applications, visual voice mail applications, messaging applications, text-to-speech and speech-to-text applications, add-ons, plug-ins, email applications, music applications, video applications, camera applications, location-based service applications, power conservation applications, game applications, productivity applications, entertainment applications, enterprise applications, combinations thereof, and the like. The applications **510**, the data **512**, and/or portions thereof can be stored in the memory **506** and/or in a firmware **514**, and can be executed by the processor **504**. The firmware **514** also can store code for execution during device power up and power down operations. It can be appreciated that the firmware **514** can be stored in a volatile or non-volatile

data storage device including, but not limited to, the memory **506** and/or a portion thereof.

(57) The mobile device **500** also can include an input/output (“I/O”) interface **516**. The I/O interface **516** can be configured to support the input/output of data such as location information, user information, organization information, presence status information, user IDs, passwords, and application initiation (start-up) requests. In some embodiments, the I/O interface **516** can include a hardwire connection such as USB port, a mini-USB port, a micro-USB port, an audio jack, a PS2 port, an IEEE 1394 (“FIREWIRE”) port, a serial port, a parallel port, an Ethernet (RJ45) port, an RJ11 port, a proprietary port, combinations thereof, or the like. In some embodiments, the mobile device **500** can be configured to synchronize with another device to transfer content to and/or from the mobile device **500**. In some embodiments, the mobile device **500** can be configured to receive updates to one or more of the applications **510** via the I/O interface **516**, though this is not necessarily the case. In some embodiments, the I/O interface **516** accepts I/O devices such as keyboards, keypads, mice, interface tethers, printers, plotters, external storage, touch/multi-touch screens, touch pads, trackballs, joysticks, microphones, remote control devices, displays, projectors, medical equipment (e.g., stethoscopes, heart monitors, and other health metric monitors), modems, routers, external power sources, docking stations, the XR component **138**, combinations thereof, and the like. It should be appreciated that the I/O interface **516** may be used for communications between the mobile device **500** and a network device or local device.

(58) The mobile device **500** also can include a communications component **518**. The communications component **518** can be configured to interface with the processor **504** to facilitate wired and/or wireless communications with one or more networks described above herein. In some embodiments, other networks include networks that utilize non-cellular wireless technologies such as WI-FI or WIMAX. In some embodiments, the communications component **518** includes a multimode communications subsystem for facilitating communications via the cellular network and one or more other networks.

(59) The communications component **518**, in some embodiments, includes one or more transceivers. The one or more transceivers, if included, can be configured to communicate over the same and/or different wireless technology standards with respect to one another. For example, in some embodiments one or more of the transceivers of the communications component **518** may be configured to communicate using GSM, CDMA, CDMAONE, CDMA2000, LTE, and various other 2G, 2.5G, 3G, 4G, 5G, and greater generation technology standards. Moreover, the communications component **518** may facilitate communications over various channel access methods (which may or may not be used by the aforementioned standards) including, but not limited to, TDMA, FDMA, W-CDMA, OFDM, SDMA, and the like.

(60) In addition, the communications component **518** may facilitate data communications using GPRS, EDGE, the HSPA protocol family, including HSDPA, EUL, or otherwise termed HSUPA, HSPA+, and various other current and future wireless data access standards. In the illustrated embodiment, the communications component **518** can include a first transceiver (“TxRx”) **520A** that can operate in a first communications mode (e.g., GSM). The communications component **518** also can include an N.sup.th transceiver (“TxRx”) **520N** that can operate in a second communications mode relative to the first transceiver **520A** (e.g., UMTS). While two transceivers **520A-520N** (hereinafter collectively and/or generically referred to as “transceivers **520**”) are shown in FIG. 5, it should be appreciated that less than two, two, and/or more than two transceivers **520** can be included in the communications component **518**.

(61) The communications component **518** also can include an alternative transceiver (“Alt TxRx”) **522** for supporting other types and/or standards of communications. According to various contemplated embodiments, the alternative transceiver **522** can communicate using various communications technologies such as, for example, WI-FI, WIMAX, BLUETOOTH, infrared, infrared data association (“IRDA”), near-field communications (“NFC”), other radio frequency (“RF”) technologies, combinations thereof, and the like.

(62) In some embodiments, the communications component **518** also can facilitate reception from terrestrial radio networks, digital satellite radio networks, internet-based radio service networks, combinations thereof, and the like. The communications component **518** can process data from a network such as the Internet, an intranet, a broadband network, a WI-FI hotspot, an Internet service provider (“ISP”), a digital subscriber line (“DSL”) provider, a broadband provider, combinations thereof, or the like.

(63) The mobile device **500** also can include one or more sensors **524**. The sensors **524** can include temperature sensors, light sensors, air quality sensors, movement sensors, orientation sensors, noise sensors, proximity sensors, or the like. As such, it should be understood that the sensors **524** can include, but are not limited to, accelerometers, magnetometers, gyroscopes, infrared sensors, noise sensors, microphones, combinations thereof, or the like. Additionally, audio capabilities for the mobile device **500** may be provided by an audio I/O component **526**. The audio I/O component **526** of the mobile device **500** can include one or more speakers for the output of audio signals, one or more microphones for the collection and/or input of audio signals, and/or other audio input and/or output devices.

(64) The illustrated mobile device **500** also can include a subscriber identity module (“SIM”) system **528**. The SIM system **528** can include a universal SIM (“USIM”), a universal integrated circuit card (“UICC”) and/or other identity devices. The SIM system **528** can include and/or can be connected to or inserted into an interface such as a slot interface **530**. In some embodiments, the slot interface **530** can be configured to accept insertion of other identity cards or modules for accessing various types of networks. Additionally, or alternatively, the slot interface **530** can be configured to accept multiple subscriber identity cards. Because other devices and/or modules for identifying users and/or the mobile device **500** are contemplated, it should be understood that these embodiments are illustrative, and should not be construed as being limiting in any way.

(65) The mobile device **500** also can include an image capture and processing system **532** (“image system”). The image system **532** can be configured to capture or otherwise obtain photos, videos, and/or other visual information. As such, the image system **532** can include cameras, lenses, charge-coupled devices (“CCDs”), combinations thereof, or the like. The mobile device **500** may also include a video system **534**. The video system **534** can be configured to capture, process, record, modify, and/or store video content. Photos and videos obtained using the image system **532** and the video system **534**, respectively, may be added as message content to a multimedia message service (“MMS”) message, email message, and sent to another mobile device. The video and/or photo content also can be shared with other devices via various types of data transfers via wired and/or wireless communication devices as described herein.

(66) The mobile device **500** also can include one or more location components **536**. The location components **536** can be configured to send and/or receive signals to determine a geographic location of the mobile device **500**. According to various embodiments, the location components **536** can send and/or receive signals from GPS devices, A-GPS devices, WI-FI/WIMAX and/or cellular network triangulation data, combinations thereof, and the like. The location component **536** also can be configured to communicate with the communications component **518** to retrieve triangulation data for determining a location of the mobile device **500**. In some embodiments, the location component **536** can interface with cellular network nodes, telephone lines, satellites, location transmitters and/or beacons, wireless network transmitters and receivers, combinations thereof, and the like. In some embodiments, the location component **536** can include and/or can communicate with one or more of the sensors **524** such as a compass, an accelerometer, and/or a gyroscope to determine the orientation of the mobile device **500**. Using the location component **536**, the mobile device **500** can generate and/or receive data to identify its geographic location, or to transmit data used by other devices to determine the location of the mobile device **500**. The location component **536** may include multiple components for determining the location and/or orientation of the mobile device **500**.

(67) The illustrated mobile device **500** also can include a power source **538**. The power source **538** can include one or more batteries, power supplies, power cells, and/or other power subsystems including alternating current (“AC”) and/or direct current (“DC”) power devices. The power source **538** also can interface with an external power system or charging equipment via a power I/O component **540**. Because the mobile device **500** can include additional and/or alternative components, the above embodiment should be understood as being illustrative of one possible operating environment for various embodiments of the concepts and technologies described herein. The described embodiment of the mobile device **500** is illustrative, and should not be construed as being limiting in any way.

(68) As used herein, communication media includes computer-executable instructions, data structures, program modules, or other data in a modulated data signal such as a carrier wave or other transport mechanism and includes any delivery media. The term “modulated data signal” means a signal that has one or more of its characteristics changed or set in a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared, UV, and other wireless media. Combinations of any of the above should also be included within the scope of computer-readable media.

(69) By way of example, and not limitation, computer storage media may include volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage of information such as computer-executable instructions, data structures, program modules, or other data. For example, computer media includes, but is not limited to, RAM, ROM, EPROM, EEPROM, flash memory or other solid state memory technology, CD-ROM, digital versatile disks (“DVD”), HD-DVD, BLU-RAY, or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by the mobile device **500** or other devices or computers described herein, such as the computer system **300** described above with reference to FIG. **3**. In the claims, the phrase “computer storage medium,” “computer-readable storage medium,” and variations thereof does not include waves or signals per se and/or communication media, and therefore should be construed as being directed to “non-transitory” media only.

(70) Encoding the software modules presented herein also may transform the physical structure of the computer-readable media presented herein. The specific transformation of physical structure may depend on various factors, in different implementations of this description. Examples of such factors may include, but are not limited to, the technology used to implement the computer-readable media, whether the computer-readable media is characterized as primary or secondary storage, and the like. For example, if the computer-readable media is implemented as semiconductor-based memory, the software disclosed herein may be encoded on the computer-readable media by transforming the physical state of the semiconductor memory. For example, the software may transform the state of transistors, capacitors, or other discrete circuit elements constituting the semiconductor memory. The software also may transform the physical state of such components in order to store data thereupon.

(71) As another example, the computer-readable media disclosed herein may be implemented using magnetic or optical technology. In such implementations, the software presented herein may transform the physical state of magnetic or optical media, when the software is encoded therein. These transformations may include altering the magnetic characteristics of particular locations within given magnetic media. These transformations also may include altering the physical features or characteristics of particular locations within given optical media, to change the optical characteristics of those locations. Other transformations of physical media are possible without departing from the scope and spirit of the present description, with the foregoing examples provided only to facilitate this discussion.

(72) In light of the above, it should be appreciated that many types of physical transformations may

take place in the mobile device **500** in order to store and execute the software components presented herein. It is also contemplated that the mobile device **500** may not include all of the components shown in FIG. 5, may include other components that are not explicitly shown in FIG. 5, or may utilize an architecture completely different than that shown in FIG. 5.

(73) Turning now to FIG. 6, a block diagram illustrating an example virtualized cloud architecture **600** and components thereof will be described, according to an exemplary embodiment. In some embodiments, the virtualized cloud architecture **600** can be utilized to implement, at least in part, the untrusted XR server computer **102**, the trusted XR server computer **104**, aspects of the network(s) **132**, portions thereof, and/or combinations thereof. The virtualized cloud architecture **600** is a shared infrastructure that can support multiple services and network applications. The illustrated virtualized cloud architecture **600** includes a hardware resource layer **602**, a control layer **604**, a virtual resource layer **606**, and an application layer **608** that work together to perform operations as will be described in detail herein.

(74) The hardware resource layer **602** provides hardware resources, which, in the illustrated embodiment, include one or more compute resources **610**, one or more memory resources **612**, and one or more other resources **614**. The compute resource(s) **610** can include one or more hardware components that perform computations to process data, and/or to execute computer-executable instructions of one or more application programs, operating systems, and/or other software. The compute resources **610** can include one or more central processing units (“CPUs”) configured with one or more processing cores. The compute resources **610** can include one or more graphics processing unit (“GPU”) configured to accelerate operations performed by one or more CPUs, and/or to perform computations to process data, and/or to execute computer-executable instructions of one or more application programs, operating systems, and/or other software that may or may not include instructions particular to graphics computations. In some embodiments, the compute resources **610** can include one or more discrete GPUs. In some other embodiments, the compute resources **610** can include CPU and GPU components that are configured in accordance with a co-processing CPU/GPU computing model, wherein the sequential part of an application executes on the CPU and the computationally-intensive part is accelerated by the GPU. The compute resources **610** can include one or more system-on-chip (“SoC”) components along with one or more other components, including, for example, one or more of the memory resources **612**, and/or one or more of the other resources **614**. In some embodiments, the compute resources **610** can be or can include one or more SNAPDRAGON SoCs, available from QUALCOMM; one or more TEGRA SoCs, available from NVIDIA; one or more HUMMINGBIRD SoCs, available from SAMSUNG; one or more Open Multimedia Application Platform (“OMAP”) SoCs, available from TEXAS INSTRUMENTS; one or more customized versions of any of the above SoCs; and/or one or more proprietary SoCs. The compute resources **610** can be or can include one or more hardware components architected in accordance with an advanced reduced instruction set computing (“RISC”) machine (“ARM”) architecture, available for license from ARM HOLDINGS. Alternatively, the compute resources **610** can be or can include one or more hardware components architected in accordance with an x86 architecture, such an architecture available from INTEL CORPORATION of Mountain View, California, and others. Those skilled in the art will appreciate the implementation of the compute resources **610** can utilize various computation architectures, and as such, the compute resources **610** should not be construed as being limited to any particular computation architecture or combination of computation architectures, including those explicitly disclosed herein.

(75) The memory resource(s) **612** can include one or more hardware components that perform storage operations, including temporary or permanent storage operations. In some embodiments, the memory resource(s) **612** include volatile and/or non-volatile memory implemented in any method or technology for storage of information such as computer-readable instructions, data structures, program modules, or other data disclosed herein.

(76) Computer storage media includes, but is not limited to, random access memory (“RAM”), read-only memory (“ROM”), Erasable Programmable ROM (“EPROM”), Electrically Erasable Programmable ROM (“EEPROM”), flash memory or other solid state memory technology, CD-ROM, digital versatile disks (“DVD”), or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store data and which can be accessed by the compute resources **610**.

(77) The other resource(s) **614** can include any other hardware resources that can be utilized by the compute resources(s) **610** and/or the memory resource(s) **612** to perform operations described herein. The other resource(s) **614** can include one or more input and/or output processors (e.g., network interface controller or wireless radio), one or more modems, one or more codec chipset, one or more pipeline processors, one or more fast Fourier transform (“FFT”) processors, one or more digital signal processors (“DSPs”), one or more speech synthesizers, and/or the like.

(78) The hardware resources operating within the hardware resource layer **602** can be virtualized by one or more virtual machine monitors (“VMMs”) **616A-616N** (also known as “hypervisors;” hereinafter “VMMs **616**”) operating within the control layer **604** to manage one or more virtual resources that reside in the virtual resource layer **606**. The VMMs **616** can be or can include software, firmware, and/or hardware that alone or in combination with other software, firmware, and/or hardware, manages one or more virtual resources operating within the virtual resource layer **606**.

(79) The virtual resources operating within the virtual resource layer **606** can include abstractions of at least a portion of the compute resources **610**, the memory resources **612**, the other resources **614**, or any combination thereof. These abstractions are referred to herein as virtual machines (“VMs”). In the illustrated embodiment, the virtual resource layer **606** includes VMs **618A-618N** (hereinafter “VMs **618**”). Each of the VMs **618** can execute one or more applications **620A-620N** in the application layer **608**. The applications **620A-620N** can include the untrusted XR server OS **124**, the untrusted XR server application **126**, the trusted XR server OS **128**, and/or the trusted XR server application **130**.

(80) Based on the foregoing, it should be appreciated that concepts and technologies directed to on-demand trusted XR environments have been disclosed herein. Although the subject matter presented herein has been described in language specific to computer structural features, methodological and transformative acts, specific computing machinery, and computer-readable media, it is to be understood that the concepts and technologies disclosed herein are not necessarily limited to the specific features, acts, or media described herein. Rather, the specific features, acts and mediums are disclosed as example forms of implementing the concepts and technologies disclosed herein.

(81) The subject matter described above is provided by way of illustration only and should not be construed as limiting. Various modifications and changes may be made to the subject matter described herein without following the example embodiments and applications illustrated and described, and without departing from the true spirit and scope of the embodiments of the concepts and technologies disclosed herein.

Claims

1. A user device comprising: a processor; and a memory that stores instructions that, when executed by the processor, cause the processor to perform operations comprising connecting to an untrusted extended reality server computer and allowing a user avatar associated with a user to enter an untrusted extended reality environment provided by the untrusted extended reality server computer, detecting an event for which a trusted extended reality environment is desired, selecting the trusted extended reality environment to handle the event, wherein the trusted extended reality environment is provided by a trusted extended reality server computer, instructing the untrusted extended reality

server computer to teleport the user avatar from the untrusted extended reality environment to the trusted extended reality environment provided by the trusted extended reality server computer, and while the user avatar is within the trusted extended reality environment, recording the untrusted extended reality environment.

2. The user device of claim 1, wherein the operations further comprise creating a trusted list identifying a plurality of trusted extended reality environments including the trusted extended reality environment, and wherein selecting the trusted extended reality environment to handle the event comprises selecting the trusted extended reality environment from the trusted list.
3. The user device of claim 2, wherein the trusted list is defined, at least in part, by the user.
4. The user device of claim 2, wherein the trusted list is defined, at least in part, based upon crowd-sourced data.
5. The user device of claim 1, wherein detecting the event comprises receiving a direct request from the user.
6. The user device of claim 5, wherein the event comprises an interaction between the user and at least one additional user through the user avatar and at least one additional user avatar.
7. The user device of claim 5, wherein the event comprises an interaction between the user, represented as the user avatar, and a business.
8. A method comprising: connecting, by a user device comprising a processor, to an untrusted extended reality server computer and allowing a user avatar associated with a user to enter an untrusted extended reality environment provided by the untrusted extended reality server computer; detecting, by the user device, an event for which a trusted extended reality environment is desired; selecting, by the user device, the trusted extended reality environment to handle the event, wherein the trusted extended reality environment is provided by a trusted extended reality server computer; instructing, by the user device, the untrusted extended reality server computer to teleport the user avatar from the untrusted extended reality environment to the trusted extended reality environment provided by the trusted extended reality server computer; and while the user avatar is within the trusted extended reality environment, recording the untrusted extended reality environment.
9. The method of claim 8, further comprising creating, by the user device, a trusted list identifying a plurality of trusted extended reality environments including the trusted extended reality environment, and wherein selecting the trusted extended reality environment to handle the event comprises selecting the trusted extended reality environment from the trusted list.
10. The method of claim 9, wherein the trusted list is defined, at least in part, by the user.
11. The method of claim 9, wherein the trusted list is defined, at least in part, based upon crowd-sourced data.
12. The method of claim 8, wherein detecting, by the user device, the event comprises receiving, by the user device, a direct request from the user.
13. The method of claim 12, wherein the event comprises an interaction between the user and at least one additional user through the user avatar and at least one additional user avatar.
14. The method of claim 12, wherein the event comprises an interaction between the user, represented as the user avatar, and a business.
15. A computer-readable storage medium comprising computer-executable instructions that, when executed by a processor of a user device, cause the user device to perform operations comprising: connecting to an untrusted extended reality server computer and allowing a user avatar associated with a user to enter an untrusted extended reality environment provided by the untrusted extended reality server computer; detecting an event for which a trusted extended reality environment is desired; selecting the trusted extended reality environment to handle the event, wherein the trusted extended reality environment is provided by a trusted extended reality server computer; instructing the untrusted extended reality server computer to teleport the user avatar from the untrusted extended reality environment to the trusted extended reality environment provided by the trusted extended reality server computer; and while the user avatar is within the trusted extended reality

environment, recording the untrusted extended reality environment.

16. The computer-readable storage medium of claim 15, wherein the operations further comprise creating a trusted list identifying a plurality of trusted extended reality environments including the trusted extended reality environment, and wherein selecting the trusted extended reality environment to handle the event comprises selecting the trusted extended reality environment from the trusted list.

17. The computer-readable storage medium of claim 16, wherein the trusted list is defined, at least in part, by the user.

18. The computer-readable storage medium of claim 16, wherein the trusted list is defined, at least in part, based upon crowd-sourced data.

19. The computer-readable storage medium of claim 15, wherein detecting the event comprises receiving a direct request from the user.

20. The computer-readable storage medium of claim 19, wherein the event comprises an interaction between the user and at least one additional user through the user avatar and at least one additional user avatar, or wherein the event comprises an interaction between the user, represented as the user avatar, and a business.
