

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280961

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Wei; Yahong

SOFA

Abstract

A sofa includes: a base assembly comprising a base that comprises at least one of a first connection member and a second connection member, wherein the first connection member is configured to detachably connect with a base connecting member, two bases are detachably connectable to each other through the first connection member and the base connecting member, the second connection member is configured to detachably connect with a backrest connecting member, thereby allowing a backrest connected to the backrest connecting member to be detachably connected to the base assembly.

Inventors: Wei; Yahong (Shenzhen, CN)

Applicant: AuGroup technology Co., Ltd. (Shenzhen, CN)

Family ID: 93629359

Appl. No.: 18/676430

Filed: May 28, 2024

Foreign Application Priority Data

CN 202420431493.3

Mar. 06, 2024

Publication Classification

Int. Cl.: A47C17/13 (20060101); A47C17/86 (20060101)

U.S. Cl.:

CPC A47C17/132 (20130101); A47C17/86 (20130101);

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to Chinese Patent Application No. CN 202420431493.3, filed Mar. 6, 2024, which is hereby incorporated by reference herein as if set forth in its entirety.

TECHNICAL FIELD

[0002] The present disclosure generally relates to furniture, and in particular relates to a sofa.

BACKGROUND

[0003] Sofas usually include bases, backrest assemblies and armrest assemblies. For some sofas, these components are fixed to one another, and the final appearance of the sofa is fixed. It would therefore be advantageous to be able to assemble these components together in different ways to provide sofas of different configurations.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0004] Many aspects of the present embodiments can be better understood with reference to the following drawings. The components in the drawings are not necessarily drawn to scale, the emphasis instead being placed upon clearly illustrating the principles of the present embodiments. Moreover, in the drawings, all the views are schematic, and like reference numerals designate corresponding parts throughout the several views.

[0005] FIG. 1 is a schematic isometric view of a sofa according to one embodiment, in which some components are omitted.

[0006] FIG. 2 is a schematic isometric view of a sofa (i.e., a two-seater sofa) according to another embodiment, in which some components are omitted and the backrest is in an exploded state.

[0007] FIG. 3 is a schematic diagram showing the connection member of the base and the backrest of the sofa in an unconnected state.

[0008] FIG. 4 is a schematic diagram showing the connection member of the base and the backrest of the sofa in a connected state.

[0009] FIG. 5 is a schematic isometric view of the backrest connection member of the sofa according to one embodiment.

[0010] FIG. 6 is a rear view of a sofa (i.e., a two-seater sofa) according to another embodiment, in which some components are omitted.

[0011] FIG. 7 is a schematic isometric view of the sofa shown in FIG. 6, in which some components are omitted.

[0012] FIG. 8 is a schematic isometric view of a sofa (i.e., a one-seater sofa) according to another embodiment.

DETAILED DESCRIPTION

[0013] The disclosure is illustrated by way of example and not by way of limitation in the figures of the accompanying drawings, in which like reference numerals indicate similar elements. It should be noted that references to “an” or “one” embodiment in this disclosure are not necessarily to the same embodiment, and such references can mean “at least one” embodiment.

[0014] Although the features and elements of the present disclosure are described as embodiments in particular combinations, each feature or element can be used alone or in other various combinations within the principles of the present disclosure to the full extent indicated by the broad general meaning of the terms in which the appended claims are expressed.

[0015] Referring to FIGS. 1 and 2, in one embodiment, a sofa **100** includes at least one base assembly **1** that includes a base **11** including a first connection member **12** and/or a second connecting member **13**. The first connection member **12** is to detachably connect with a base connecting member **20**. Two bases **11** can be detachably connected to each other through the first

connection member **12** and the base connecting member **20**. With such configuration, two bases **11** of two sofas **100** can be assembled to form a new sofa. The second connection member **13** is to detachably connect with a backrest connecting member **30**, thereby allowing the backrest **40** connected to the backrest connecting member **30** to be detachably connected to the base assembly **10**.

[0016] With such configuration, different numbers of base assemblies **10** can be used to construct sofas of different structures. For example, a one-seater sofa can be constructed using a single base assembly **10**; a two-seater sofa can be constructed using two base assemblies **10**; and a three-seater sofa can be constructed using three base assemblies **10** and multiple base assemblies **10** can be assembled in different manners to form sofas with different structures.

[0017] In one embodiment, the base **11** is a flat cuboid, and the first connection member **12** and the second connecting member **13** can be disposed on the top surface of the base **11** and close to the edges. For example, the top surface **111** of the base **11** is provided with a number of receiving holes **112**, and a first group of receiving holes among the receiving holes **112** constitutes the first connection member **12**. As shown in FIG. 1, the two receiving holes **112** near the left side and the two receiving holes **112** near the right side of the base **11** respectively constitute two first connection members **12**. A second group of receiving holes among the receiving holes **112** constitutes the second connecting member **13**. As shown in FIG. 1, the two receiving holes **112** near the rear end of the base **11** constitute the second connecting member **13**.

[0018] Referring to FIGS. 3 and 4, in one embodiment, the base **11** includes a square metal frame **113** and a number of plastic members **114** embedded in the metal frame **113**. The receiving holes **112** are respectively formed in the plastic members **114**. The square metal frame **113** ensures the required support strength for the sofa **100**. By forming the receiving holes **112** in the plastic members **114**, it is advantageous for providing sufficient friction needed to connect the first connection member **12** and the second connection member **13** with the base connecting member **20** and the backrest connecting member **30**. This allows the base connecting member **20** and the backrest connecting member **30** to be stably connected to the receiving holes **112**.

[0019] In one embodiment, each base assembly **10** further includes a seat cushion **50** removably attached to its base **11**. The seat cushion **50** is placed on the top surface of the base **11**. The seat cushion **50** can not only provide comfortable support for the user, but also block the receiving hole **112** formed on the top surface of the base **11**, so that the receiving holes **112** does not affect the aesthetics of the sofa **100**.

[0020] In one embodiment, the seat cushion **50** can be detachably connected to the base **11** through a zipper or hook-and-loop fastener **60**. This ensures that the seat cushion **50** does not easily move relative to the base **11**.

[0021] In one embodiment, each base connecting member **20** includes two posts **21** spaced apart from each other and connected to each other. Two adjacent bases **11** of the bases **11** are detachably connected to each other through at least one base connecting member **20**. The two posts **21** of the at least one base connecting member **20** are inserted into the receiving holes **112** of the two adjacent bases **11**, respectively. In the embodiment shown in FIGS. 1 and 2, two adjacent bases **11** are detachably connected to each other through two base connecting members **20**.

[0022] Referring to FIGS. 5 to 7, in one embodiment, the backrest connecting member **30** includes a support frame **31** and two insertion portions **32** connected to the support frame **31**. The insertion portions **32** can be inserted into the first group of receiving holes **112**. In one embodiment, the insertion portions **32** are located below the support frame **31**.

[0023] In one embodiment, the backrest connecting member **30** includes a number of bars connected to one another. The support frame **31** includes a main body **311** and two support bars **312** located below the main body **311**. The main body **311** includes a horizontal bar **313** and two longitudinal bars **314** connected to opposite ends of the horizontal bar **313**. The ends of the two longitudinal bars **314** away from the horizontal bar **313** have connecting bars **315** extending toward

each other. The two support bars **312** are respectively connected to the ends of the two connecting bars **315**. In this way, the distance between the two support bars **312** is less than the distance between the two longitudinal bars **314**, that is, the distance between the two support bars **312** is less than the width of the bracket body **311**.

[0024] Referring to FIGS. **5** and **6**, in one embodiment, the backrest **40** includes a connection member **41** provided on its back. For example, a square piece of fabric can be sewn to the back of the backrest **40** to form a square connection member **41**, and three sides of the square piece of fabric can be sewn to the back of the backrest **40**. A receiving space is formed between the square piece of fabric and the back of the backrest **40**, and an opening **42** is formed between the last side of the square piece of fabric and the back of the backrest **40**. Through the opening **42**, the backrest connecting member **30** can penetrate deeply into the receiving space, thereby detachably connecting the backrest **40** to the backrest connecting member **30** and further to the base **11**.

[0025] In one embodiment, the main body **311** and the two support bars **312** are substantially on the same plane, or the plane where the main body **311** is located may be inclined relative to the plane where the two support bars **312** are located. The ends of the two support bars **312** away from the main body **311** are provided with connecting bars **316**. The two connecting bars **316** are substantially perpendicular to the support bars **312**. The two insertion portions **32** are respectively connected to the ends of the connecting bars **316**. The two insertion portions **32** are both rod-shaped and substantially parallel to each other. When the two insertion portions **32** are inserted into the two receiving holes **112** of a base **11**, the connecting bars **315** of the backrest connecting member **30** is higher than the seat cushion **50**. When the backrest **40** is connected to the backrest connecting member **30**, the opening **42** of the connection member **41** of the backrest **40** is located below the connecting bars **315**. Referring to FIG. **8**, when a user leans on the backrest **40**, the portion **43** of the connection member **41** of the backrest **40** close to the opening **42** tightly contacts the connecting bars **315**, which can prevent the connection member **41** of the backrest **40** from being separated from the backrest connecting member **30**.

[0026] With such configuration, a single base assembly **10** can be used as a sofa; a single base assembly **10**, backrest connecting member **30** and backrest **40** can be connected to one another to form a one-seater sofa; and two one-seater sofas can be connected together through one or two base connecting members **20** to form a two-seater sofa, as shown in FIG. **2**. A two-seater sofa can be combined with a footstool ottoman. Additionally, a two-seater sofa, a one-seater sofa, and one or two base connecting members **20** can be connected together to form a three-seater sofa. Therefore, it can be seen that the sofa provided according to the above-mentioned embodiments can form different configurations through various installation methods.

[0027] The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications as are suited to the particular use contemplated.

Claims

1. A sofa comprising: a base assembly comprising a base that comprises at least one of a first connection member and a second connection member; wherein the first connection member is configured to detachably connect with a base connecting member, two bases are detachably connectable to each other through the first connection member and the base connecting member; the second connection member is configured to detachably connect with a backrest connecting member, thereby allowing a backrest connected to the backrest connecting member to be

detachably connected to the base assembly.

2. The sofa of claim 1, wherein the base comprises a top surface that defines a plurality of receiving holes, and a first group of receiving holes among the plurality of the receiving holes constitutes the first connection member, and a second group of receiving holes among the plurality of the receiving holes constitutes the second connection member.

3. A sofa comprising: two base assemblies, each of the base assemblies comprising a base that comprises a first connection member and a second connection member; a base connecting member detachably connected to the first connection members of the bases of the two base assemblies, thereby detachably connecting the bases of the two base assemblies to each other; two backrests; two backrest connecting members, the backrest connecting members detachably connected to the second connection members of the bases of the two base assemblies, respectively, and connected to the two backrests, respectively, thereby detachably connecting the two backrests to the bases of the two base assemblies.

4. The sofa of claim 3, wherein each of the bases comprises a top surface that defines a plurality of receiving holes, and a first group of receiving holes among the plurality of the receiving holes constitutes the first connection member, and a second group of receiving holes among the plurality of the receiving holes constitutes the second connection member.

5. The sofa of claim 3, wherein each of the base assemblies comprises a seat cushion removably attached to a corresponding one of the bases.

6. The sofa of claim 5, wherein each of the seat cushion is detachably connected to the corresponding one of the bases through a zipper or hook-and-loop fastener.

7. The sofa of claim 4, wherein each of the backrest connecting members comprises a support frame and two insertion portions connected to the support frame, and the insertion portions are inserted into the first group of receiving holes.

8. The sofa of claim 7, wherein the support frame comprises a main body and two support bars located below the main body, the two support bars are connected to the main body and the insertion portions, and a distance between the two support bars is smaller than a width of the main body.

9. The sofa of claim 4, wherein each of the bases comprises a metal frame and a plurality of plastic members embedded in the metal frame, and the plurality of receiving holes are respectively formed in the plurality of plastic members.

10. A sofa comprising: a plurality of base assemblies, each of the base assemblies comprising a base that defines a plurality of receiving holes; a plurality of base connecting members, each of the base connecting members comprising two posts that are connected to and spaced apart from each other, each two adjacent ones of the bases detachably connected to each other through at least one of the base connecting members, wherein the two posts of each of the at least one of the base connecting members are inserted into the receiving holes of the two adjacent ones of the bases; a backrest; a backrest connecting members comprising a support frame and two insertion portions connected to the support frame, the backrest detachably connected to the support frame, the two insertion portions inserted into two of the receiving holes of the base of one of the base assemblies so as to detachably connect the backrest to the base of the one of the base assemblies.
