

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281779

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

KIM; Jeong Woo et al.

FIRE EXTINGUISHING SYSTEM OF ENERGY STORAGE SYSTEM

Abstract

A fire extinguishing system includes: a plurality of battery racks each configured to receive a plurality of battery modules, the fire extinguishing system including: a sensing unit configured to sense at least one of temperature, voltage, or smoke of the battery modules; and a fire extinguishing unit spraying a fire extinguishing agent to the battery module if at least one of values sensed by the sensing unit is higher than a preset threshold, wherein the fire extinguishing unit comprises a spray pipe connected to a top of the battery module, the spray pipe allowing the fire extinguishing agent to be sprayed therethrough, a plurality of spray holes is formed through the spray pipe so as to correspond to positions of battery cells of the battery module, and the spray pipe is rotationally arranged such that the spray holes are arranged in a direction diagonal to the battery module.

Inventors: KIM; Jeong Woo (Yongin-si, KR), YANG; Jong Woon (Yongin-si, KR)

Applicant: Samsung SDI Co., Ltd. (Yongin-si, KR)

Family ID: 93656142

Appl. No.: 18/791234

Filed: July 31, 2024

Foreign Application Priority Data

KR 10-2024-0033859

Mar. 11, 2024

Publication Classification

Int. Cl.: A62C3/16 (20060101); A62C31/28 (20060101); A62C37/40 (20060101)

U.S. Cl.:

CPC A62C3/16 (20130101); A62C31/28 (20130101); A62C37/40 (20130101);

Background/Summary

CROSS-REFERENCE TO THE RELATED APPLICATION

[0001] The present application claims priority to and the benefit of Korean Patent Application No. 10-2024-0033859, filed on Mar. 11, 2024, in the Korean Intellectual Property Office, the entire disclosure of which is incorporated herein by reference.

BACKGROUND

1. Field

[0002] Aspects of some embodiments of the present disclosure relate to a fire extinguishing system of an energy storage system.

2. Description of the Related Art

[0003] An energy storage system is a system capable of storing surplus electricity or storing electricity generated by utilizing renewable energy. By utilizing an energy storage system, idle electricity may be stored during times of low electricity demand and then supplied during times of high electricity demand to more smoothly control electricity supply and demand.

[0004] The space or facility where the energy storage system is installed and operated may desirably be equipped with facilities to suppress battery fires caused by electric shock, short circuit, external surge, etc. A fire extinguishing system may include a fire sensor and a spring cooler or a fire extinguishing agent sprayer installed in the vicinity of a battery rack or on the ceiling, etc.

[0005] The fire extinguishing system may be an indirect spray type fire extinguishing system configured to spray water or a fire extinguishing agent to a battery or the entire area where the battery is installed in the event of a battery fire. However, as the energy density of the battery continues to increase, the flame volume and ejection pressure at a vent of battery cell are increasing, which may make it difficult to extinguish or suppress fires early with some fire suppression equipment. Therefore, it may be desirable to provide a fire extinguishing system capable of effectively suppressing fires generated from a plurality of batteries in an energy storage system and extinguishing high-pressure fires early.

[0006] The above information disclosed in this Background section is only for enhancement of understanding of the background and therefore the information discussed in this Background section does not necessarily constitute prior art.

SUMMARY

[0007] Aspects of some embodiments of the present disclosure relate to a fire extinguishing system of an energy storage system that may be capable of effectively extinguishing a fire in the event of the fire.

[0008] Aspects of some embodiments of the present disclosure include a fire extinguishing system of an energy storage system capable of effectively suppressing and extinguishing a fire.

[0009] It should be noted that characteristics of embodiments according to the present disclosure are not limited to the characteristics as mentioned above, and other unmentioned characteristics of embodiments according to the present disclosure will be more clearly understood by those skilled in the art from the following description.

[0010] According to some embodiments of the present disclosure, a fire extinguishing system of an energy storage system includes: a plurality of battery racks each configured to receive a plurality of

battery modules, the fire extinguishing system including a sensing unit configured to sense at least one of the temperature, voltage, and smoke of each of the battery modules and a fire extinguishing unit configured to spray a fire extinguishing agent to the battery module if at least one of values sensed by the sensing unit is higher than a preset threshold, wherein the fire extinguishing unit includes a spray pipe connected to the top of the battery module, the spray pipe being configured to allow the fire extinguishing agent to be sprayed therethrough, a plurality of spray holes is formed through the spray pipe so as to correspond to the positions of battery cells of the battery module, and the spray pipe is rotationally arranged such that the spray holes are located in a direction diagonal to the battery module.

[0011] According to some embodiments, the battery module may include a top cover having a plurality of through-openings formed so as to correspond to the positions of vent holes of the battery cells, and the through-openings may be formed through the top cover.

[0012] According to some embodiments, each of the battery racks may include a main frame on which pipes are installed and a subframe configured to support the battery module, the subframe having a seating groove, in which the spray pipe is seated, formed therein, and the subframe may include an extension portion extending from the seating groove inwardly of the battery rack, the extension portion being formed in an insertion direction of the battery module.

[0013] According to some embodiments, the extension portion may be bent in a direction diagonal to a direction toward the top cover.

[0014] According to some embodiments, a through-hole configured to allow the fire extinguishing agent sprayed from the spray hole to pass therethrough may be formed in the seating groove, and the through-hole may be formed at the position corresponding to the direction toward the spray hole.

[0015] According to some embodiments, the fire extinguishing agent sprayed from the spray hole may be sprayed in a straight line toward the through-hole.

[0016] According to some embodiments, the fire extinguishing agent sprayed from the spray hole may be sprayed in a straight line from the through-hole toward the top cover.

[0017] According to some embodiments, the battery rack may be formed such that the extension portion and the top cover come into contact with each other upon insertion of the battery module in the state in which the extension portion and the top cover are spaced apart from each other.

[0018] According to some embodiments, the bent angle of the extension portion may be set to an angle such that the subframe contacts the top cover if the subframe is pressed by the battery module.

[0019] According to some embodiments, the length from the center of the spray pipe to an end of the extension portion may be set to a length such that a bent end of the subframe comes into contact with the top cover if the subframe is pressed by the battery module.

[0020] According to some embodiments, the spray angle of the fire extinguishing agent from the spray hole may be set based on at least one of the bent angle of the extension portion, the distance from the center of the spray pipe to the point where the extension portion and the top cover contact each other, and a range of the through-opening of the top cover.

[0021] According to some embodiments, the maximum angle at which the spray hole is rotationally arranged may be based on a position in front of the through-opening such that the fire extinguishing agent is not sprayed to the through-opening.

[0022] According to some embodiments, the minimum angle at which the spray hole is rotationally arranged may be based on an upper surface of the top cover such that the fire extinguishing agent is not sprayed out of the top cover.

[0023] According to some embodiments, the minimum angle at which the spray hole is rotationally arranged may be based on the point where the top cover and the extension portion contact each other such that the fire extinguishing agent is not sprayed out of the top cover.

[0024] According to some embodiments, the spray hole of the spray pipe may be rotationally

arranged inwardly of the battery rack.

[0025] According to some embodiments, the distance from the spray pipe to the top cover may be 8 mm to 12 mm.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0026] The accompanying drawings, which are incorporated in this specification, illustrate aspects of some embodiments and serve to further illustrate the technical ideas of embodiments according to the present disclosure in conjunction with the detailed description of some embodiments that follows, and the present disclosure is not to be construed as limited to what is shown in such drawings. In the drawings:

[0027] FIG. 1 is a block diagram schematically showing a fire extinguishing system according to some embodiments of the present disclosure;

[0028] FIG. 2 is a schematic view illustratively showing the fire extinguishing system according to some embodiments of the present disclosure;

[0029] FIG. 3 is a perspective view briefly showing major parts of the fire extinguishing system shown in FIG. 1;

[0030] FIG. 4 is a partial perspective view showing a battery rack according to some embodiments of the present disclosure;

[0031] FIG. 5 is a perspective view showing a direction of movement of a fire extinguishing agent in the battery rack of FIG. 4;

[0032] FIG. 6 is a perspective view showing a battery module and a spray pipe shown in FIG. 4;

[0033] FIG. 7 is an enlarged perspective view of a coupling region between the battery module and the spray pipe shown in FIG. 6;

[0034] FIG. 8 is a side view showing a top cover of the battery module and the spray pipe shown in FIG. 6;

[0035] FIG. 9 is an enlarged view showing one side of the top cover of the battery module and the spray pipe shown in FIG. 8;

[0036] FIG. 10 is a perspective view showing a lower surface of the spray pipe shown in FIG. 4;

[0037] FIG. 11 is an enlarged perspective view of part C shown in FIG. 10;

[0038] FIG. 12 is a plan view showing the lower surface of the spray pipe shown in FIG. 11;

[0039] FIG. 13 is an enlarged perspective view showing a part of a lower surface of a spray pipe according to some embodiments of the present disclosure;

[0040] FIG. 14 is a plan view showing a part of the lower surface of the spray pipe shown in FIG. 13;

[0041] FIG. 15 is a schematic view briefly showing a fire extinguishing process according to some embodiments of the present disclosure; and

[0042] FIG. 16 is a schematic view briefly showing a fire extinguishing system according to some embodiments of the present disclosure.

DETAILED DESCRIPTION

[0043] Hereinafter, aspects of some embodiments of the present disclosure will be described in more detail with reference to the accompanying drawings. It should be understood that the terms or words used in the specification and appended claims should not be construed as being limited to general and dictionary meanings, but should be construed based on meanings and concepts according to the technical idea of the present disclosure on the basis of the principle that the inventor is permitted to define appropriate terms for the best explanation. Embodiments described in this specification and constructions shown in the drawings illustrated and describe aspects of some embodiments and do not speak for the entirety of the technical idea of the present disclosure,

and therefore it should be understood that various replaceable equivalents and modifications may be possible at the time of filing the present application.

[0044] As used herein, the terms “comprise” (or “include”) and/or “comprising” (or “including”) are intended to specify the presence of stated figures, numbers, steps, operations, members, elements, and/or groups thereof and do not exclude the presence or addition of one or more other figures, numbers, steps, operations, members, elements, and/or groups.

[0045] The accompanying drawings may not be to scale and some components may be exaggerated in dimensions in order to facilitate understanding of the present disclosure. In different embodiments, the same components may be denoted by the same reference numerals.

[0046] A reference to two comparables being “identical” means that they are “substantially identical.” Thus, substantially the same may include deviations that are considered low in the art, such as deviations of less than 5%. If a parameter is uniform in a given region, this may mean that the parameter is uniform from an average perspective.

[0047] Although first, second, and the like are used to describe various components, the components are not limited by these terms. These terms are used only to distinguish one component from another, and a first component may be a second component unless otherwise noted.

[0048] Throughout the specification, each component may be singular or plural unless otherwise indicated.

[0049] If any configuration is located “above” (or “below”) a component or “on” (or “under”) the component, this may mean not only that the configuration is arranged abutting an upper surface (or a lower surface) of the component, but that another configuration may be interposed between the component and the configuration located on (or under) the component.

[0050] It should also be understood that if a component is described as being “on,” “connected to,” or “coupled to” another component, the components may be directly connected or linked to each other, another component may be “interposed” between other components, or the components may be “connected,” “coupled,” or “linked” to each other via another component.

[0051] As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. The use of “may” in describing embodiments of the present disclosure is directed to “one or more embodiments of the present disclosure.” Expressions such as “one or more” preceding a list of elements modify the list of elements as a whole and do not modify individual elements in the list.

[0052] Throughout the specification, references to “A and/or B” mean A, B, or A and B, unless otherwise indicated, and references to “C to D” mean C or higher and D or lower, unless otherwise indicated.

[0053] If a phrase such as “at least one of A, B, and C,” “at least one of A, B, or C,” “at least one selected from the group consisting of A, B, and C,” or “at least one selected from A, B, and C” is used to specify a list of elements A, B, and C, the phrase may refer to any suitable combination.

[0054] The term “use” may be considered synonymous with the term “utilize.” As used herein, the terms “substantially” and “about” and similar terms are used as terms of approximation, not as terms of degree, and are intended to take into account inherent variations in measured or calculated values that would be recognized by a person of ordinary skill in the art.

[0055] While terms such as first, second, and third may be used herein to describe various elements, components, regions, layers, and/or sections, such elements, components, regions, layers, and/or sections are not to be limited by such terms. The terms are used to distinguish one element, component, region, layer, or section from another element, component, region, layer, or section. Thus, a first element, component, region, layer, or section discussed below may be named a second element, component, region, layer, or section without departing from the teachings of the disclosed embodiments.

[0056] In order to describe the relationship of one element or feature to another element(s) or feature(s) as shown in the drawings, spatially relative terms such as “beneath,” “below,” “lower,”

“above,” “upper,” and the like may be used herein for ease of description. It will be understood that spatially relative positions are intended to encompass different directions of a device in use or operation in addition to the orientations depicted in the figures. For example, if the device in the drawings is inverted, an element or feature described as “beneath” or “below” becomes “above” or “upper.” Thus, “beneath” is a concept that encompasses “above” or “below”.

[0057] The terminology used herein is intended to describe embodiments of the present disclosure and is not intended to limit the present disclosure.

[0058] A controller and/or other related devices or parts according to the present disclosure may be implemented using any suitable hardware, firmware (e.g., semiconductor on demand), software, or any suitable combination of software, firmware, and hardware. For example, various components of the controller and/or the other related devices or parts according to the present disclosure may be formed on a single integrated circuit chip or on separate integrated circuit chips. The various components of the controller may be implemented on a flexible printed circuit film, and may be formed on a tape carrier package, a printed circuit board, or on the same substrate as the controller. The various components of the controller may be processes or threads executed by on one or more processors in one or more computing devices, which may execute computer program instructions and interact with the other components to perform various functions described below. The computer program instructions may be stored in memory be executable in a computing device using a standard memory device, such as random access memory. The computer program instructions may also be stored on other non-transitory computer readable media, such as a CD-ROM or flash drive. Those skilled in the art should recognize that the functions of various computing devices may be combined with each other or integrated into a single computing device, or the function of a specific computing device may be distributed to one or more other computing devices, without departing from the spirit and scope of embodiments of the present disclosure.

[0059] In an example, the controller according to the present disclosure may be operated on a computer including a central processing unit, a mass storage device such as a hard disk or a solid state drive, a volatile memory device, an input device such as a keyboard or a mouse, and an output device such as a monitor or a printer.

[0060] Hereinafter, a fire extinguishing system of an energy storage system according to some embodiments of the present disclosure will be described in detail with reference to the accompanying drawings.

[0061] FIG. 1 is a block diagram schematically showing a fire extinguishing system according to some embodiments of the present disclosure. FIG. 2 is a schematic view illustratively showing the fire extinguishing system according to some embodiments of the present disclosure. FIG. 3 is a perspective view briefly showing aspects of the fire extinguishing system shown in FIG. 1. FIG. 4 is a partial perspective view showing a battery rack according to some embodiments of the present disclosure.

[0062] Referring to FIGS. 1 to 4, the fire extinguishing system of the energy storage system (or energy storage apparatus) according to some embodiments of the present disclosure may mainly include a supply unit **100** configured to supply a fire extinguishing agent to the energy storage system **1**, a fire extinguishing unit **300** configured to transport and spray the fire extinguishing agent to the energy storage system **1**, and a sensing unit **500** configured to monitor a fire.

[0063] Referring to FIGS. 1 and 2, the supply unit **100** may include an agent container **110** configured to store the fire extinguishing agent, a leak detector **120** configured to detect leakage from the agent container **110**, a main valve **130** configured to supply the fire extinguishing agent and stop the supply of the fire extinguishing agent, a regulator **140** configured to regulate the supply pressure and time of the fire extinguishing agent, and a controller **150** configured to perform control.

[0064] Referring to FIGS. 2 to 4, the fire extinguishing unit **300** may include a main pipe **310** through which the fire extinguishing agent is transported, a branch pipe **320** diverging from the

main pipe **310**, and a spray pipe **330** connected to a battery module **30** and through which the fire extinguishing agent is sprayed.

[0065] Referring to FIG. **1**, the sensing unit **500** may include a first sensor **510** configured to sense a fire in the battery module **30**, and a second sensor **520** configured to sense smoke in the event of a fire outside the battery module **30**.

[0066] The energy storage system **1** will be briefly described before describing the fire extinguishing system in detail.

[0067] Referring to FIGS. **1** to **4**, according to some embodiments, the energy storage system **1** may include a plurality of battery modules **30** mounted in each of a plurality of battery racks **10** and a plurality of battery cells **33** received in a case **31** of each battery module **30**. Each battery cell **33** may be a secondary battery capable of being charged and discharged.

[0068] The battery rack **10** may include a main frame **11** on which pipes may be installed and a subframe **13** configured to support the battery modules **30**. The main frame **11** may be roughly hexahedral in shape, and parts thereof corresponding to plate surfaces may be closed or open. The subframe **13** may be arranged in a direction perpendicular to a longitudinal direction of the battery rack **10** (upward-downward direction in FIG. **4**) to support the battery modules **30**. According to some embodiments, if the battery modules **30** are placed on the subframe **13**, the subframe **13** may be pressed by the battery modules **30** and may droop downward.

[0069] For example, the subframe **13** may drop by about 3 mm. According to some embodiments, therefore, the subframe **13** may be designed so as to be spaced apart from the battery modules **30** by about 3 mm.

[0070] According to some embodiments, a seating groove **13a**, in which the spray pipe **330**, a description of which will follow, is seated, may be formed on the subframe **13**. The seating groove **13a** may be formed in an insertion direction of the battery module **30**. The size of the seating groove **13a** may be equal to or greater than the length and diameter of the spray pipe **330**, which will be described in more detail later.

[0071] According to some embodiments, an extension portion **13b** may be formed on the subframe **13** extending from the seating groove **13a** in an inward direction of the battery rack **10**. The extension portion **13b** may be formed in an extension direction of the seating groove **13a**. The extension portion **13b** may be formed in the insertion direction of the battery module **30**. According to some embodiments, the extension portion **13b** may be formed as the result of an end of the subframe **13** being bent downward. The extension portion **13b** may be bent in a direction diagonal to the direction of the battery module **30**. The extension portion **13b** may block the possibility of heat propagation to the back row in the event of a fire in a battery cell in the battery module **30**. The second sensor **520** configured to sense smoke may be installed on the battery rack **10**, which will be described later.

[0072] The battery module **30** may include a plurality of battery cells **33** housed inside the case **31**, which has a roughly hexahedral shape. The battery cells **33** may be spaced apart from each other by a distance (e.g., a set or predetermined distance), and may be arranged in a plurality of rows. The battery module **30** may also include a top cover **32** configured to cover the tops of the plurality of battery cells **33** after the plurality of battery cells **33** is received in the case **31**. The top cover **32** may have a plurality of through-openings **32a** formed so as to correspond to the position of a vent hole of each of the battery cells **33**. However, embodiments according to the present disclosure are not limited thereto. The battery module **30** may not be separately provided with the top cover **32**, and the case **31** may be formed as a single body, or the case **31** may have covers formed on a bottom and a side thereof. The top cover **32** may refer to the top of the case **31**.

[0073] Each battery module **30** may be equipped with a battery management system (BMS), which may transmit a fire signal to the controller **150**, a description of which will follow, in the event of a fire in the battery cell **33**. A plurality of first sensors **510** may be installed in the battery module **30**, and a second sensor **520** may be installed externally on the battery rack **10**, which will be described

later. The first sensor **510** may be a sensor configured to sense ambient temperature in the battery module **30**. According to some embodiments, the first sensor **510** may be a voltage sensor. According to some embodiments, the first sensors **510** may be arranged one for each row of battery cells **33**, as shown in FIG. **3**. In this case, two first sensors **510** may be installed so as to face each other. The number and installation position of the first sensors **510** may vary according to various embodiments.

[0074] If the value measured by the first sensor **510** is higher than a preset threshold, the controller **150** may determine to supply the fire extinguishing agent. According to some embodiments, if the temperature in the battery module **30** measured by the first sensor **510** is equal to or higher than a threshold or the voltage is equal to or higher than a threshold, the BMS may send an abnormality signal to the controller **150**.

[0075] According to some embodiments, the BMS may determine that an abnormal condition exists if a threshold temperature is sensed, and then may determine that an abnormality has occurred in the battery when a temperature higher than the threshold temperature by approximately one degree or more is sensed. According to some embodiments, the BMS may determine that an abnormality has occurred in the battery if a temperature increase of about 5 degrees or more in one second is successively detected twice. For voltage, if voltage equal to or higher than a threshold voltage is successively detected twice, the BMS may determine that an abnormality has occurred in the battery and may drop the voltage.

[0076] The fire extinguishing unit **300** may be installed on the battery rack **10** and battery modules **30**. If a fire is sensed by the sensing unit **500**, the fire extinguishing agent may be supplied through the supply unit **100**, and the fire extinguishing agent may be transported to the battery rack **10** and the battery modules **30** through the fire extinguishing unit **300**. Consequently, a fire occurring in the battery module **30** may be initially quickly extinguished. In the fire extinguishing system of the present disclosure, it is possible to supply the fire extinguishing agent to a battery cell **33** in which a fire has occurred and battery cells **33** adjacent thereto, among the battery cells **33** in the battery module **30**.

[0077] Hereinafter, the fire extinguishing system according to some embodiments of the present disclosure will be described in detail (components not shown in FIGS. **5** to **9** will be described with reference to FIGS. **1** to **4**).

[0078] FIG. **5** is a perspective view showing a direction of movement of the fire extinguishing agent in the battery rack of FIG. **4**. FIG. **6** is a perspective view showing the battery module and the spray pipe shown in FIG. **4**. FIG. **7** is an enlarged perspective view of a coupling region between the battery module and the spray pipe shown in FIG. **6**. FIG. **8** is a side view showing the top cover of the battery module and the spray pipe shown in FIG. **6**. FIG. **9** is an enlarged view showing one side of the top cover of the battery module and the spray pipe shown in FIG. **8**. FIG. **10** is a perspective view showing a lower surface of the spray pipe shown in FIG. **4**. FIG. **11** is an enlarged perspective view of part C shown in FIG. **10**. FIG. **12** is a plan view showing the lower surface of the spray pipe shown in FIG. **11**.

[0079] Referring to FIG. **1**, components of the supply unit **100**, the fire extinguishing unit **300**, and the sensing unit **500** of the fire extinguishing system may be organically connected to each other.

[0080] First, the supply unit **100** will be described in more detail with reference to

[0081] FIGS. **1** and **2**.

[0082] The agent container **110** may be a kind of storage container configured to store the fire extinguishing agent. The agent container **110** may be fixed to an installation site using a package method or a wall mounting method. According to some embodiments, the agent container **110** may be a pressure vessel configured to store a high-pressure fire extinguishing agent. Any of commonly used fire extinguishing agents, such as a gaseous extinguishing agent, e.g., HFC-23/HFC-125/HFC227ea, CF.sub.3CF.sub.2C(O)CF(CF.sub.3).sub.2, or water, may be used as the fire extinguishing agent. The fire extinguishing agent may be stored in the agent container **110** using an

accumulation method or a pressurization method. Consequently, the internal pressure of the agent container **110** may vary depending on the country in which the fire extinguishing system is used or the type of the fire extinguishing agent (e.g., a domestic fire cylinder filling pressure range of 25 to 42 bar, an international fire cylinder filling pressure range of 25 to 34.5 bar, and 50 bar or more for a gaseous extinguishing agent (HFC-23/HFC-125/HFC227ea)). According to some embodiments, the pressure, flow rate, and spray time may be regulated by the regulator **140** if the fire extinguishing agent is discharged from the high-pressure agent container **110**. If spray of the fire extinguishing agent is determined by the controller **150**, the main valve **130** may be opened to spray the fire extinguishing agent.

[0083] The leak detector **120** may be integrally formed with the agent container **110** or coupled to the agent container **110**. The leak detector **120** may detect leakage of the fire extinguishing agent before spray of the fire extinguishing agent. For example, the leak detector **120** may be a load cell coupled to the agent container **110** to detect weight loss.

[0084] The main valve **130** may function to open and close a discharge portion of the agent container **110**. The main valve **130** may open and close the discharge portion of the agent container **110** under control of the controller **150**. If the main valve **130** is opened, the fire extinguishing agent may be discharged from the agent container **110** and may move to the regulator **140** along a discharge pipe.

[0085] The regulator **140** may function to regulate the spray pressure of the fire extinguishing agent to a final spray pressure. The final spray pressure of the fire extinguishing agent may be preset, and the regulator may be configured to implement the preset final spray pressure. For example, the final spray pressure may be set to about 2 to 5 bar. The discharge pipe may be a stainless steel (STS or SUS) tube or a flexible hose, and may be connected to the main pipe **310**, which will be described later.

[0086] The main valve **130** and the regulator **140** may be controlled by the controller **150**. Exemplarily, the controller **150** may be a kind of control board including a processor, executable memory, a communication device, and a display. The controller **150** may communicate with the first sensor **510** and the second sensor **520**, and may control the main valve **130** and the regulator **140**. In the event of a fire, the controller **150** may sense the fire through the sensing unit **500** and may open the main valve **130**. The controller **150** may control the regulator **140** to discharge the fire extinguishing agent at the preset final spray pressure and to guide the fire extinguishing agent to the fire extinguishing unit **300**.

[0087] Referring to FIGS. 2 to 4, the fire extinguishing unit **300** may include a main pipe **310**, connected to the agent container **110**, through which the fire extinguishing agent is transported, and a branch pipe **320** diverging from the main pipe **310**. The fire extinguishing unit **300** may also include a rack pipe **325** connected to the branch pipe **320** and located on each battery rack **10**, a spray pipe **330** located adjacent to each battery module **30**, and a connection pipe **340** configured to connect the pipes to each other. All of the pipes may be in the shape of a hollow pipe (in some figures, the main pipe, the branch pipe, the rack pipe, and the spray pipe are shown as having cylindrical or cuboidal shapes for ease of representation). According to some embodiments, the main pipe **310** and the branch pipes **320** may be configured to perform a single function.

[0088] The main pipe **310**, to which the plurality of pipes is connected, may extend to the energy storage system **1**. The branch pipe **320** may be coupled to the connection pipe **340** connected to the main pipe **310**, and may be installed adjacent to or on each battery rack **10**. The rack pipe **325** connected to the branch pipe **325** may be installed on each battery rack **10**. The rack pipe **325** may be connected to the plurality of branch pipes **330**, and the branch pipes **330** may be installed parallel to the battery module **30**. The connection pipe, which may be branched in two directions, three directions, four directions, and the like, may be coupled to the connection between the plurality of main pipes **310**, the connection between the main pipe **310** and the branch pipe **320**, and the connection between the branch pipe **320** and the rack pipe **325**. In the event of a fire, the

fire extinguishing agent supplied from the agent container **110** may be transported to the energy storage system **1** via the main pipe **310**, and may be supplied to the respective battery modules **30** via the branch pipe **320** and the spray pipe **330**.

[0089] One battery rack **10** will be described by way of example with reference to FIGS. **4** and **5**.

[0090] Defining the direction in which the battery modules **30** are inserted as the front of the battery rack **10**, the main pipe **310** may be coupled to the front top of the battery rack **10**. One branch pipe **320** may be connected to the main pipe **310** and located at the upper part of the battery rack **10**. The branch pipe **320** may be located in the insertion direction of the battery module **30**. For example, the branch pipe **320** may be located in the upper middle of the battery rack **10**. The rack pipe **325** may be connected to the rear of the branch pipe **320**. The rack pipe **325** may be arranged in the longitudinal direction of the battery rack **10**. For example, the rack pipe **325** may be located in the rear middle of the battery rack **10**. The spray pipe **330** may be connected to the rack pipe **325**, and the spray pipe **330** may be located adjacent to each of the battery modules **30**. The spray pipes **330** may be connected to the rack pipe **325**, or may be connected to the rack pipe **325** via a plurality of auxiliary pipes **327**. The spray pipe **330** may be coupled to the subframe **13** of the battery rack **10**. The fire extinguishing agent may be sprayed in a downward direction from the spray pipe **330** coupled to the subframe **13**. The number of spray pipes **330** may correspond to the number of rows of battery cells **33** received in the battery module **30**. For example, if two rows of battery cells **33** are located in one battery module **30**, two spray pipes **330** may be connected.

[0091] Referring to FIG. **5**, the direction of movement of the fire extinguishing agent in the event of a fire may correspond to the direction of an arrow. First, the fire extinguishing agent may be moved {circle around (1)} to the front of the battery rack **10** in the longitudinal direction of the main pipe **310**, and then the fire extinguishing agent may be moved {circle around (2)} from the front top of the battery rack **10** to the rear along the branch pipe **320**. Subsequently, the fire extinguishing agent may be moved {circle around (3)} from the rear top to the bottom of the battery rack **10** along the rack pipe **325**. Subsequently, the fire extinguishing agent may be moved {circle around (4)} toward the front of the battery rack **10** along the respective spray pipes **330** and may be supplied to the battery cell **33** where the fire has occurred. The direction of movement of the fire extinguishing agent shown in FIG. **5** may be based on an example of the installation of the pipes, and different arrangements of the pipes may result in different directions of movement of the fire extinguishing agent.

[0092] According to some embodiments, a plurality of spray holes **332** may be formed through the spray pipe **330**. The position of the spray holes **332** may correspond to the position of each battery cell **33**. However, according to some embodiments, the spray pipe **330** may be rotationally arranged such that the spray holes **332** are located in a direction diagonal to the battery module **30**. The spray holes **332** may be located in a direction diagonal to the top of each battery cell **33** corresponding to the position of each battery cell **33**. Consequently, the fire extinguishing agent moved through the spray pipe **330** may be moved to the corner of the top cover **32** of the battery module **30**, and may then be moved to the top of the battery cell **33** through the through-opening **32a** formed in the top cover **32** of the battery module **30**. A more detailed description thereof will be given later.

[0093] In a direct spray system in which the fire extinguishing agent is directly sprayed perpendicularly to the vent of the battery cell **33** to prevent or reduce heat propagation, time may be required to detect thermal runaway of a specific battery cell **33** and to spray the fire extinguishing agent, and before the fire extinguishing agent is sprayed, flames and battery cell debris caused by the thermal runaway may affect battery cells or battery modules adjacent thereto, causing secondary damage. According to some embodiments, therefore, in the event of thermal runaway in a specific battery cell **33** in each battery rack **10**, it is possible to block the entry of debris into neighboring cells and the back row through diagonal direct spray and the structure of the extension portion **13b** of the extended subframe **13**, whereby it is possible to prevent or reduce heat propagation.

[0094] Hereinafter, the structure in which the fire extinguishing agent is moved to the corner of the top cover **32** of the battery module **30** and then moved to the top of the battery cell **33** in order to prevent or reduce secondary damage will be described in more detail with reference to FIGS. **6** to **9**.

[0095] Referring to FIGS. **6** and **7**, the seating groove **13a** may be formed on the subframe **13** of the battery rack **10** in the insertion direction of the battery module **30**. The seating groove **13a** may be formed along the row in which the battery cells **33** are located, and the longitudinal direction of the seating groove **35a** may correspond to the longitudinal direction of the spray pipe **330**.

According to some embodiments, a through-hole, through which the fire extinguishing agent may pass if the fire extinguishing agent is sprayed, may be formed in the seating groove **13a**.

[0096] Referring to FIG. **8**, battery cell debris may be ejected in the direction toward the spray pipe **330** and the subframe **13** upon the occurrence of an event in a battery cell in the battery module **30** (see a dotted arrow). According to some embodiments, therefore, the spray pipe **330** may be rotationally arranged toward the interior of the battery rack **10** such that the fire extinguishing agent is sprayed diagonally.

[0097] Referring to FIGS. **8** and **9**, the spray pipe **330** may be rotationally arranged such that the spray hole **332** is located in a direction diagonal to the battery module **30**. The spray pipe **330** may be rotationally arranged such that the spray hole **332** is oriented inwardly of the battery rack **10** (center direction in FIG. **8**). That the spray pipe **330** is rotationally arranged may mean that the direction of the spray hole **332** is rotated if the spray pipe **330** is seated in the seating groove **13a** in the direction toward the through-opening **32a** and/or the vent of the battery cell **33**. The rotational angle of the spray pipe **330** will be described later.

[0098] According to some embodiments, the fire extinguishing agent may be sprayed from the spray hole **332** in the direction toward the inner edge of the seating groove **13a** (see a solid arrow in FIG. **8**). The through-hole of the seating groove **13a** may be formed at the position corresponding to the direction of the spray hole **332**. The through-hole may be formed on the edge of the seating groove **13a** (the upper surface of the battery module facing inwardly of the battery rack) so as to correspond to the spraying direction of the fire extinguishing agent.

[0099] According to some embodiments, the fire extinguishing agent sprayed from the spraying hole **332** may be sprayed in a straight line toward the through-hole. The fire extinguishing agent sprayed from the spray hole **332** may be sprayed in a straight line from the through hole toward the top cover **32**. According to some embodiments, the diameter of the spray hole **332** may be within a range of about 2 to 2.5 mm (a first range), and a second range of the diameter may be about 1 to 4 mm. The distance between the spray hole **332** and the top cover **32** may be about 8 mm to 12 mm. According to some embodiments, because the size of the spray hole **332** through which the fire extinguishing agent is sprayed is very small, and the distance from the spray hole **332** to the top cover **32** is short, it may be assumed that the fire extinguishing agent is sprayed in a straight line rather than spreading out. That the fire extinguishing agent is sprayed in a straight line may mean not only that the fire extinguishing agent is sprayed in a size within the diameter of the spray hole **332** but also that the fire extinguishing agent is sprayed within a certain range (e.g., less than about 1 mm) based on the diameter of the spray hole **332**. The spray range may refer to the extent (size) of the fire extinguishing agent after the fire extinguishing agent sprayed from the spray hole **332** reaches the seating groove **13a** or the top cover **32**.

[0100] According to some embodiments, a plurality of through-openings **32a** may be formed in the top cover **32** of the battery module **30** so as to correspond to the position of the vents of the battery cells **33**. The through-openings **32a** may be formed through the upper surface of the top cover **32** located on the upper surface of the case **31**. The through-opening **32a** may be formed in the form of a circle, an oval, a long hole, a narrow and long slit, or the like, and may be provided in at least one or in plural. Because the through-openings **32a** are formed so as to correspond to the position of the vents of the battery cells **33**, the fire extinguishing agent supplied through the spray pipe **330** may

be supplied into the case **31**. The case **31** may be provided therein with a busbar holder, and the busbar holder may be in communication with the through-openings **32a**. The busbar holder may be located at the position corresponding to the vent of each battery cell **33**. The busbar holders may serve as a path through which the fire extinguishing agent is sprayed (a vent channel).

Consequently, the fire extinguishing agent sprayed diagonally from the spray hole **332** toward the interior of the battery rack **10** may be sprayed to a position other than the through-opening **32a** of the top cover **32** and may then flow into the through-hole so as to be supplied into the case **31**.

According to some embodiments, the spray pipe **330** is described as being rotationally arranged inwardly of the battery rack **10**, but the spray pipe **330** may be rotationally arranged outwardly of the battery rack **10** according to some embodiments.

[0101] As described above, the fire extinguishing agent sprayed diagonally from the spray hole **332** toward the interior of the battery rack **10** may be sprayed to a location other than the through-opening **32a** of the top cover **32** and may then flow into the through-hole so as to be supplied into the case **31**, whereby the likelihood of the spray hole **332** being blocked by debris may be reduced. In the event of thermal runaway in the battery cell **33**, flames and debris may damage the spray pipe **330**. In order to prevent or reduce such damage, the spray hole **332** may be arranged diagonally, whereby effective fire extinguishing may be achieved.

[0102] According to some embodiments, the subframe **13** may include an extension portion **13b** extending from the seating recess **13a** inwardly of the battery rack **10** and formed in the insertion direction of the battery modules **30**. The extension portion **13b** may be diagonally bent toward the top cover **32**.

[0103] Referring to FIG. 9, according to some embodiments, because the subframe **13** may be pressed by the battery module **30** and may droop downward, the battery rack **10** may be formed such that the extension portion **13b** and the top cover **32** come into contact with each other upon insertion of the battery module **30** in the state in which the extension portion **13b** and the top cover **32** are spaced apart from each other. According to some embodiments, the bent angle A of the extension portion **13b** may be set to an angle such that the subframe **13** contacts the top cover **32** if the subframe **13** is pressed by the battery module **30**. According to some embodiments, the length D from the center of the spray pipe **330** to the end of the extension portion **13b** may be set to a length such that the bent end of the subframe **13** comes into contact with the top cover **32** if the subframe **13** is pressed by the battery module **30**.

[0104] According to some embodiments, the maximum angle C at which the spray hole **332** is rotationally arranged (the maximum spray angle of the fire extinguishing agent) may be based on the position in front of the through-opening **32a** such that the fire extinguishing agent is not sprayed to the through-opening **32a**. The minimum angle B at which the spray hole **332** is rotationally arranged (the minimum spray angle of the fire extinguishing agent) may be based on the upper surface of the top cover **32** such that the fire extinguishing agent is not sprayed out of the top cover **32**. The minimum angle B at which the spray hole **332** is rotationally arranged may be based on the point where the top cover **32** and the extension portion **13b** contact each other such that the fire extinguishing agent is not sprayed out of the top cover **32**.

[0105] According to some embodiments, the fire extinguishing agent spray angle at which the fire extinguishing agent is sprayed may have a value between the minimum angle B and the maximum angle C. Consequently, the fire extinguishing agent may not be directly sprayed to the through-opening **32a** but may indirectly sprayed, whereby it is possible to minimize damage caused by flames and debris from the battery cell **33**. The angle may be based on a transverse horizontal line passing through the center of the spray pipe **330** (see FIG. 9).

[0106] According to some embodiments, the spray angles B and C of the fire extinguishing agent from the spray hole **332** may be set based on at least one of the bent angle A of the extension portion **13b**, the distance D from the center of the spray pipe **330** to the point F where the extension portion **13b** and the top cover **32** contact each other, and the range E of the through-opening of the

top cover **32**. According to some embodiments, the minimum spray angle B of the fire extinguishing agent and the maximum spray angle C of the fire extinguishing agent may be determined after the bent angle A of the extension portion **13b**, the distance D from the center of the spray pipe **330** to the point F where the extension portion **13b** and the top cover **32** contact each other, and the range E of the through-opening of the top cover **32** are determined based on the design of the battery module **30** and the battery rack **10**.

[0107] As described above, in the event of thermal runaway in a specific battery cell **33** in each battery rack **10**, it is possible to block the entry of debris into neighboring cells and the back row through diagonal direct spray and the structure of the extension portion **13b** of the extended subframe **13**, whereby it is possible to prevent or reduce heat propagation. According to some embodiments, the fire extinguishing agent may be sprayed diagonally upon the occurrence of an event in a battery cell in the battery module **20**, whereby the likelihood of the spray hole **332** of the spray pipe **330** being blocked by debris may be reduced. According to some embodiments, the space between the battery cell where the event occurred and the battery cell of the back row may be blocked by the structure of the extension portion **13b**, whereby it is possible to prevent or reduce instances of flames and debris affecting battery cells adjacent thereto in the event of thermal runaway.

[0108] According to some embodiments, the spray pipe **330** may be provided with a thermal member **334** configured to allow the fire extinguishing agent to be selectively sprayed only in the event of a fire. Referring to FIG. **10**, the spray pipe **330** may be provided with a plurality of thermal members **334**. The thermal members **334** may wrap each of the plurality of spray holes **332** formed in the spray pipe **330** to prevent or reduce leakage of the fire extinguishing agent. One thermal member **334** may be configured to wrap one spray hole **332**. The thermal member **334** may be melted by heat generated from a fire in the event of the fire to allow the spray hole **332** to be opened. If the spray hole **332** is opened, the fire extinguishing agent sprayed through the spray pipe **330** may be moved to the top of the battery cell **33**. To this end, the through-opening **32a** may be formed so as to correspond to the position of the vent of each battery cell **33**.

[0109] As shown in FIGS. **11** and **12**, the thermal member **334** may have a shape that completely surrounds the spray hole **332** and the periphery thereof. According to some embodiments, the thermal member **334** may have a polyhedral, spherical, or hemispherical body. In some figures, the thermal member **334** is shown in a cuboidal shape, but the present disclosure is not limited thereto. The thermal member **334** may be made so as to withstand the final spray pressure of the fire extinguishing agent (e.g., about 2 to 5 bar). The thermal member **334** may be melted by heat discharged from the vent of the battery cell in the event of a fire in the battery cell **33** or by flames or sparks generated by the fire. In the event of a fire, therefore, the spray hole **332** may be opened, whereby the fire extinguishing agent may be sprayed to the fire area. According to some embodiments, the thermal member **334** may melt within a range of about 80° C. to 250° C. 80° C. may be the temperature at which the thermal member **334** begins to melt, and 250° C. may be the temperature at which the thermal member **334** completely melts. The material of the thermal member **334** may be determined by considering a temperature rise in the event of a fire in the battery module **30**. For example, the thermal member **334** may be made of a resin material such as ABS, PP, PC, PE, or PFA. The thermal member **334** may be formed by applying high injection pressure to the resin material such that the thermal member **334** is integrally formed on the spray pipe **330**.

[0110] By adjusting the thickness, material, and shape of the thermal member **334**, the time for heat, flames, or sparks to melt the thermal member **334**, thereby opening the spray hole **332**, may be adjusted. For example, by forming a thin film portion **334a** on the lower surface of the thermal member **334** corresponding to the position of the spray hole **332**, the thickness of the thermal member **334** on the spray hole **332** side may be thinner than the other parts. If heat is applied to the thermal member **334**, therefore the thin film portion **334a** may melt more quickly than the other

portions, whereby it is possible to quickly spray the fire extinguishing agent. According to some embodiments, assuming that the thickness of the thermal member **334** in the vicinity of the thin film portion **334a** is about 1 mm, the thickness of the thin film portion **334a** may be within a range of about 0.3 to 0.6 mm (first range). A second range of the thickness of the thin film portion **334a** may be about 0.2 to 0.9 mm.

[0111] According to some embodiments, a pair of spray holes **332** may be formed at each position where one thermal member **334** is provided.

[0112] FIG. **13** is an enlarged perspective view showing a part of a lower surface of a spray pipe according to some embodiments of the present disclosure. FIG. **14** is a plan view showing a part of the lower surface of the spray pipe shown in FIG. **13**.

[0113] Referring to FIGS. **13** and **14**, two spray holes **332'** covered by a thin film portion **334a'** of a thermal member **334'** may be formed in a spray pipe **330'**. The thin film portion **334a'** may have a rib **334b'** located between the two spray holes **332'**. The rib **334b'** may be shaped so as to protrude from the surface of the thin film portion **334a'** and may have a thickness greater than the thickness of the thin film portion **334a'** at the part where the spray holes **332'** are formed. The rib **334b'** may be formed so as to be thicker than the spray hole **332'** side to prevent or reduce melting between the two spray holes **332'** before the spray holes **332'** are opened. If heat is applied to the thermal member **334'**, therefore, the thin film portion **334a'** blocking the two spray holes **332a'** may be melted earlier than the rib **334b'**, whereby the spray holes **332'** may be opened to spray the fire extinguishing agent.⁸⁷

[0114] A fire extinguishing process of the fire extinguishing system according to some embodiments of the present disclosure having the above-described configuration will be described (for convenience, the description is based on the reference symbols of the first embodiment).

[0115] FIG. **15** is a schematic view briefly showing a fire extinguishing process according to some embodiments of the present disclosure.

[0116] Referring to FIG. **15**, a fire may occur in a battery cell **33** in a specific battery module **30**. A spray pipe **330**, through which a fire extinguishing agent is sprayed, may be connected to each battery module **30**, and a first sensor **510** configured to sense a fire may be provided in the battery module **30**. If the temperature in the battery module **30** increases due to heat generation by the fire, the first sensor **510** may sense the same. If the fire is sensed by the first sensor **510**, a fire sensing signal may be transmitted to a controller **150** via a BMS of the battery module **30** (the signal may be transmitted in several ways, such as wireless communication or electrical signal transmission by contacts). If the controller **150** senses the fire through the first sensor **510**, the controller may open a main valve **130** of an agent container **110**. The fire extinguishing agent discharged from the agent container **110** may be adjusted to a final spray pressure by a regulator **140** and may be discharged. The discharged fire extinguishing agent may be transported along a main pipe **310** and a branch pipe **320**.

[0117] Flames and heat may be generated in the battery cell **33** that is on fire, and the flames and the heat may cause a thermal member **334** of the spray pipe **330** adjacent thereto to melt. If the thermal member **334** melts and a spray hole **332** is opened, the pressure in that area may be lowered, whereby the fire extinguishing agent may move toward the spray pipe **330** with the open spray hole **332** based on the pressure gradient. Consequently, the fire extinguishing agent may be supplied to the battery cell **33** in which the fire has occurred and sprayed to the fire area. Because the fire is extinguished by spraying of the fire extinguishing agent, it is possible to prevent or reduce instances of the fire spreading to battery modules adjacent thereto.

[0118] In addition to sensing of the fire by the sensor described above, fire monitoring may be performed by smoke sensing.

[0119] FIG. **16** is a schematic view briefly showing a fire extinguishing system according to some embodiments of the present disclosure.

[0120] Referring to FIG. **16**, a plurality of second sensors **520** may be installed on a battery rack

10. The second sensors **520** may be used in combination with first sensors **510**, or only the second sensors **520** may be used without the first sensors **510**. The second sensors **520** may be installed in an upper region D of the battery rack **10**, taking into account the characteristic that smoke rises upward. However, because a large amount of smoke may not only rise but also spread around the fire area, the second sensors may also be installed in a lower area E of the battery rack **10** for further sensing. According to some embodiments, one second sensor **520** may be installed in the upper region D of each battery rack **10**, and one second sensor **520** may be installed between two battery racks **10**. According to some embodiments, one second sensor **520** may be installed in the upper region D of each battery rack **10**, and one or two second sensors **520** may be installed between two battery racks **10**.

[0121] If the fire extinguishing system is configured as described above, it is possible to rapidly suppress and extinguish a fire that may occur due to ground fault, short circuit, and the like caused by internal and external factors of the energy storage system and to minimize spread of the fire. Consequently, the present disclosure has the effect of protecting an expensive energy storage system and improving customer reliability.

[0122] As is apparent from the above description, according to embodiments of the present disclosure, a fire extinguishing system is capable of rapidly suppressing and extinguishing a fire that may occur due to ground fault, short circuit, and the like caused by internal and external factors of an energy storage system and minimizing spread of the fire. Consequently, it is possible to protect an expensive energy storage system and to improve customer reliability.

[0123] According to embodiments of the present disclosure, in the event of thermal runaway of a specific battery cell in each battery rack, a fire extinguishing agent may be directly sprayed in a diagonal direction, whereby it is possible to reduce the likelihood of an agent spray hole in a spray pipe being blocked by debris, and therefore it is possible to achieve effective fire extinguishing.

[0124] According to embodiments of the present disclosure, it may be possible to block the space between a battery cell where an event has occurred and a battery cell in the back row through an extended guide rail structure, thereby preventing or reducing introduction of debris into battery cells adjacent thereto and thus preventing or reducing heat propagation.

[0125] The effects of the present disclosure are not limited to those described above, and other unmentioned technical effects will be apparent to those skilled in the art from the above description of the disclosed embodiments.

[0126] The above description and corresponding figures illustrate and describe aspects of some embodiments for implementing a fire extinguishing system of an energy storage system according to some embodiments of the present disclosure, the present disclosure is not limited to the above embodiments, and there is a technical spirit of the present disclosure to the extent that various modifications can be made by anyone having ordinary skill in the art to which the present disclosure pertains without departing from the gist of the present disclosure as claimed in the following claims. Although the present disclosure has been described above with reference to limited embodiments and drawings, the present disclosure is not limited thereby and various modifications and variations may be made by a person having ordinary skill in the art to which the present disclosure pertains within the technical ideas of the present disclosure and the equivalent scope of the appended claims, and their equivalents.

Claims

1. A fire extinguishing system of an energy storage system comprising: a plurality of battery racks each configured to receive a plurality of battery modules, the fire extinguishing system comprising: a sensing unit configured to sense at least one of temperature, voltage, or smoke of each of the battery modules; and a fire extinguishing unit configured to spray a fire extinguishing agent to a battery module from among the battery modules based on at least one of values sensed by the

sensing unit being higher than a preset threshold, wherein the fire extinguishing unit comprises a spray pipe connected to a top of the battery module, the spray pipe being configured to allow the fire extinguishing agent to be sprayed therethrough, a plurality of spray holes is formed through the spray pipe so as to correspond to positions of battery cells of the battery module, and the spray pipe is rotationally arranged such that the spray holes are arranged in a direction diagonal to the battery module.

2. The fire extinguishing system as claimed in claim 1, wherein the battery module comprises a top cover having a plurality of through-openings formed so as to correspond to positions of vent holes of the battery cells, and the through-openings are formed through the top cover.

3. The fire extinguishing system as claimed in claim 2, wherein each of the battery racks comprises: a main frame on which pipes are installed; and a subframe configured to support the battery module, the subframe having a seating groove, in which the spray pipe is seated, formed therein, and the subframe comprises an extension portion extending from the seating groove inwardly of the battery rack, the extension portion being formed in an insertion direction of the battery module.

4. The fire extinguishing system as claimed in claim 3, wherein the extension portion is bent in a direction diagonal to a direction toward the top cover.

5. The fire extinguishing system as claimed in claim 3, wherein a through-hole configured to allow the fire extinguishing agent sprayed from a spray hole from among the spray holes to pass therethrough is formed in the seating groove, and the through-hole is formed at a position corresponding to a direction toward the spray hole.

6. The fire extinguishing system as claimed in claim 5, wherein the fire extinguishing system is configured to spray the fire extinguishing agent from the spray hole in a straight line toward the through-hole.

7. The fire extinguishing system as claimed in claim 5, wherein the fire extinguishing system is configured to spray the fire extinguishing agent from the spray hole in a straight line from the through-hole toward the top cover.

8. The fire extinguishing system as claimed in claim 3, wherein the battery rack is formed such that the extension portion and the top cover come into contact with each other upon insertion of the battery module in a state in which the extension portion and the top cover are spaced apart from each other.

9. The fire extinguishing system as claimed in claim 8, wherein a bent angle of the extension portion is set to an angle such that the subframe contacts the top cover based on the subframe being pressed by the battery module.

10. The fire extinguishing system as claimed in claim 8, wherein a length from a center of the spray pipe to an end of the extension portion is set to a length such that a bent end of the subframe comes into contact with the top cover based on the subframe being pressed by the battery module.

11. The fire extinguishing system as claimed in claim 3, wherein a spray angle of the fire extinguishing agent from a spray hole from among the spray holes is set based on at least one of a bent angle of the extension portion, a distance from a center of the spray pipe to a point where the extension portion and the top cover contact each other, and a range of a through-opening from among the through-openings of the top cover.

12. The fire extinguishing system as claimed in claim 3, wherein a maximum angle at which a spray hole from among the spray holes is rotationally arranged is based on a position in front of a through-opening from among the through-openings such that the fire extinguishing agent is not sprayed to the through-opening.

13. The fire extinguishing system as claimed in claim 3, wherein a minimum angle at which a spray hole from among the spray holes is rotationally arranged is based on an upper surface of the top cover such that the fire extinguishing agent is not sprayed out of the top cover.

14. The fire extinguishing system as claimed in claim 3, wherein a minimum angle at which a spray

hole from among the spray holes is rotationally arranged is based on a point where the top cover and the extension portion contact each other such that the fire extinguishing agent is not sprayed out of the top cover.

15. The fire extinguishing system as claimed in claim 1, wherein a spray hole from among the spray holes of the spray pipe is rotationally arranged inwardly of the battery rack.

16. The fire extinguishing system as claimed in claim 2, wherein a distance from the spray pipe to the top cover is in a range of 8 millimeters (mm) to 12 mm.
