

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286148

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Kang; Suhyeon et al.

ELECTRODE ASSEMBLY AND RECHARGEABLE BATTERY INCLUDING THE SAME

Abstract

An electrode assembly includes a first electrode having a first electrode uncoated portion with a protruding shape, a second electrode having a second electrode uncoated portion with a protruding shape, and a separator disposed between the first electrode and the second electrode, wherein the first electrode uncoated portion includes a first inner tab and a first outer tab separated by a cut line provided inside the first electrode uncoated portion, and wherein the second electrode uncoated portion includes a second inner tab and a second outer tab separated by a cut line provided inside the second electrode uncoated portion.

Inventors: Kang; Suhyeon (Yongin-si, KR), Kim; Duckhyun (Yongin-si, KR), Jang; Woonsuk (Yongin-si, KR)

Applicant: SAMSUNG SDI CO., LTD. (Yongin-si, KR)

Family ID: 1000008348246

Appl. No.: 18/978178

Filed: December 12, 2024

Foreign Application Priority Data

KR 10-2024-0031625

Mar. 05, 2024

Publication Classification

Int. Cl.: H01M10/0585 (20100101); H01M50/46 (20210101); H01M50/533 (20210101); H01M50/55 (20210101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to and the benefit of Korean Patent Application No. 10-2024-0031625 filed at the Korean Intellectual Property Office on Mar. 5, 2024, the entire contents of which are incorporated herein by reference.

BACKGROUND

1. Field

[0002] The present disclosure relates to an electrode assembly, a rechargeable battery including the same and a method of manufacturing the rechargeable battery.

2. Description of the Related Art

[0003] Unlike a primary battery, a rechargeable battery is a battery that is repeatedly charged and discharged. A small-capacity rechargeable battery is used in a portable small electronic device such as a mobile phone, a laptop computer, or a camcorder. A rechargeable battery with large capacity and high density is used as a power source for driving motors of a hybrid vehicle and an electric vehicle or for energy storage.

[0004] For example, the rechargeable battery may be formed by stacking a plurality of positive electrodes, a plurality of negative electrodes, and a plurality of separators. The separator is interposed between the positive electrode and the negative electrode, and the positive electrode and the negative electrode are alternately disposed with the separator interposed between them. In order to manufacture an appropriate rechargeable battery, it is necessary to align and stack the electrodes and the separators so that they do not become disturbed by matching centers of the electrodes.

[0005] In modern society where a need for the rechargeable battery is increasing, a method that may manufacture the rechargeable battery at a high speed is required to improve supply of the rechargeable battery. Thus, there is a need for a method of properly stacking the electrodes at a high speed.

[0006] However, the separator is stacked together with the electrode through a general lamination process, and then a process of fixing the electrode is additionally performed.

[0007] If a process of fixing the electrode is added, an additional facility and additional material may be required, so that a manufacturing cost and a manufacturing time are increased.

[0008] The above-described information disclosed in the technology that is the background of this disclosure is only for improving understanding of the background of the present disclosure, and thus may include information that does not constitute the prior art.

SUMMARY OF THE INVENTION

[0009] Embodiments include an electrode assembly including a first electrode including a first electrode uncoated portion with a protruding shape, a second electrode including a second electrode uncoated portion with a protruding shape, and a separator disposed between the first electrode and the second electrode, wherein the first electrode uncoated portion includes a first inner tab and a first outer tab separated by a cut line provided inside the first electrode uncoated portion, and wherein the second electrode uncoated portion includes a second inner tab and a second outer tab separated by a cut line provided inside the second electrode uncoated portion.

[0010] A protruding direction of the first electrode uncoated portion and a protruding direction of the second electrode uncoated portion may be opposite to each other.

[0011] The first outer tab and the second outer tab may be respectively bent in directions opposite to bending directions of the first inner tab and the second inner tab.

[0012] Each of the first inner tab and the second inner tab may have a circular shape.

[0013] Each of the first inner tab and the second inner tab may have a quadrangular shape.

[0014] The first inner tab and the second inner tab may be each at least two or more.

[0015] A width of each of the first inner tab and the second inner tab may be greater than or equal to 5 mm and the width of the first inner tab may be less than the width of the second outer tab.

[0016] A width interval between the first outer tab and the first inner tab, and a width interval between the second outer tab and the second inner tab may be each 10 mm or less.

[0017] Each of the first electrode, the second electrode, and the separator may be provided in a plural number, the first electrode and the second electrode may be alternately stacked along a first direction with the separator interposed therebetween, and the plurality of first electrodes, the plurality of second electrodes, and the plurality of separators may be independent of each other.

[0018] Embodiments include a rechargeable battery including the electrode assembly as claimed, a case accommodating the electrode assembly, and a cap assembly including a first electrode terminal electrically connected to the first electrode and a second electrode terminal electrically connected to the second electrode, the cap assembly being coupled to the case to cover and seal an opening of the case, wherein the first electrode terminal may be connected to the first electrode through a first current collecting plate connected to the first electrode terminal and at least one of the first inner tab and the first outer tab, and the second electrode terminal may be connected to the second electrode through a second current collecting plate connected to the second electrode terminal and at least one of the second inner tab and the second outer tab.

[0019] Embodiments include a method for manufacturing a rechargeable battery, the method including providing the electrode assembly as claimed, providing a cap assembly including a first electrode terminal, a second electrode terminal, a first current collecting plate connected to the first electrode terminal, and a second current collecting plate connected to the second electrode terminal, respectively connecting the first current collecting plate and the second current collecting plate to at least one of the first inner tab and the first outer tab and at least one of the second inner tab and the second outer tab, and inserting the electrode assembly into a case having an accommodation space and coupling the cap assembly to the case to cover an opening of the case so that the cap assembly seals the case.

[0020] However, an effect that may be obtained through the present disclosure is not limited to the above-described effect, and other technical effects not mentioned may be clearly understood by those skilled in the art from a description of the present disclosure below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] Features will become apparent to those of ordinary skill in the art by describing in detail exemplary embodiments with reference to the attached drawings, in which:

[0022] FIG. 1 is a perspective view showing a rechargeable battery according to one or more embodiments of the present disclosure;

[0023] FIG. 2 is a partial exploded perspective view of the rechargeable battery according to one or more embodiments of the present disclosure;

[0024] FIG. 3 is a cross-sectional view cut along a line III-III shown in FIG. 1;

[0025] FIG. 4 is a perspective view of an electrode assembly according to one or more embodiments of the present disclosure;

[0026] FIG. 5(a) is a partial perspective view for describing a structure of a first electrode uncoated portion according to one or more embodiments of the present disclosure;

[0027] FIG. 5(b) is a partial perspective view showing a state in which a first inner tab of the first electrode uncoated portion is bent according to one or more embodiments of the present disclosure;

[0028] FIG. 6 is a perspective view showing a state in which an inner tab and an outer tab according to one or more embodiments of the present disclosure are bent;

[0029] FIG. 7(a) is a plan view showing a case where a shape of the first inner tab is a quadrangular shape according to one or more embodiments of the present disclosure;

[0030] FIG. 7(b) is a plan view showing a case where the shape of the first inner tab is a semicircular shape according to one or more embodiments of the present disclosure;

[0031] FIG. 7(c) is a plan view showing a case where the first inner tab is provided in a plural number according to one or more embodiments of the present disclosure.

[0032] FIG. 8 is a partial plan view for describing width and length intervals of a first outer tab and the first inner tab of the electrode assembly according to one or more embodiments of the present disclosure;

[0033] FIG. 9(a) is a flowchart for describing a method for manufacturing a rechargeable battery using a comparative example; and

[0034] FIG. 9(b) is a flowchart for describing a method for manufacturing the rechargeable battery according to one or more embodiments of the present disclosure.

DETAILED DESCRIPTION

[0035] Example embodiments will now be described more fully hereinafter with reference to the accompanying drawings; however, they may be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey exemplary implementations to those skilled in the art.

[0036] It will also be understood that when a layer or element is referred to as being “on” another layer or substrate, it can be directly on the other layer or substrate, or intervening layers may also be present. Further, it will be understood that when a layer is referred to as being “under” another layer, it can be directly under, and one or more intervening layers may also be present. In addition, it will also be understood that when a layer is referred to as being “between” two layers, it can be the only layer between the two layers, or one or more intervening layers may also be present.

[0037] Below, embodiments of the present disclosure will be described in detail with reference to the attached drawings. A term or a word used in the present specification and claims should not be construed as limited to its usual or dictionary meaning, and should be interpreted as a meaning and a concept conforming to a technical idea of the present disclosure based on a principle that an inventor may properly define a concept of the term to describe his or her disclosure in the best way. Thus, the embodiments described in the present specification and a configuration shown in the drawings are only examples of the present disclosure and do not represent all of the technical idea of the present disclosure, so that it should be appreciated that there may be various equivalents and variations that may replace the embodiments and the configuration at a time at which the present application is filed.

[0038] A term “comprises”, “includes”, “comprising”, or “including” if used in the present specification, specifies presence of a shape, a number, a step, an operation, a member, an element, and/or a group thereof, but does not preclude presence or addition of one or more other shape, one or more other number, one or more other operation, one or more other number member, one or more other number element, and/or a group thereof.

[0039] If it is described that two objects are identical, this means that these objects are “substantially identical”. Therefore, the substantially identical objects may include objects having deviations considered low in the art, for example, deviations within 5%. Additionally, if it is described that certain parameters are uniform in a predetermined region, this may mean that the parameters are uniform in terms of an average.

[0040] Although terms “first”, “second”, and the like are used to describe various components, the components are not limited by the terms. The terms are only used to distinguish one component from another component, and unless otherwise stated, the first component may be the second

component.

[0041] Throughout the specification, unless otherwise stated, each component may be singular or plural.

[0042] Disposing any component at an “upper portion (or lower portion)” of or “on (or below)” another component may mean not only that the component is disposed in contact with an upper surface (or lower surface) of the other component but also that another component may be interposed between the other component and the component disposed on (or below) the other component.

[0043] Additionally, if it is described that a component is “connected” or “coupled” to another component, the components may be directly connected or accessed to each other, but it should be understood that another component may be “interposed” between the components or the components are “connected” or “coupled” through another component.

[0044] A term “and/or” used in the present specification includes any and all combinations of one or more of the associated listed items. Additionally, a use of “may” if embodiments of a present disclosure described are described relates to “one or more embodiments of the present disclosure”. An expression such as “one or more” preceding a list of components modifies an entire list of components and does not modify an individual component of the list.

[0045] Throughout the specification, if referring to “A and/or B”, it means A, B, or A and B, unless specifically stated to the contrary, and if referring to “C to D”, unless otherwise specified, it means that it is greater than or equal to C and less than or equal to D.

[0046] If a phrase such as “at least one of A, B, and C”, “at least one of A, B, or C”, “at least one selected from the group of A, B, and C”, or “at least one selected from A, B, and C” is used to specify a list of elements that are A, B, and C, the phrase may refer to all suitable combinations.

[0047] A term “use” may be considered synonymous with a term “utilize”. Terms “substantially,” “about,” and similar terms used in the present specification are used as terms of approximation rather than terms of degree, and are intended to consider intrinsic variation in a measured or calculated value that will be recognized by those skilled in the art.

[0048] Although terms “first”, “second”, “third”, etc. may be used in the present specification to describe various elements, components, regions, layers, and/or sections, the elements, components, regions, layers, and/or sections should not be limited by the terms. The terms are only used to distinguish one element, component, region, layer, or section from another element, component, region, layer, or section. Thus, a “first” element, component, region, layer, or section discussed below may be termed a “second” element, component, region, layer, or section without departing from teachings of the embodiments.

[0049] Spatially relative terms such as “beneath” “below” “lower” “above” “upper” and the like may be used herein for ease of description to describe a relationship between one element or feature to another element(s) or feature(s) as shown in the drawings. It will be understood that the spatially relative terms are intended to encompass different directions of a device in use or operation in addition to a direction depicted in the drawings. For example, if a device shown in the drawings is turned over, an element described as “below” or “beneath” another element may be understood to “above” the other element. Thus, the term “below” may encompass directions of both above and below.

[0050] The terms used in the present specification are intended to describe embodiments of the present disclosure, and are not intended to limit the present disclosure.

[0051] FIG. 1 is a perspective view showing a rechargeable battery according to one or more embodiments of the present disclosure. FIG. 2 is a partial exploded perspective view of the rechargeable battery according to one or more embodiments of the present disclosure. FIG. 3 is a cross-sectional view cut along a line III-III shown in FIG. 1.

[0052] Referring to FIGS. 1 to 3, the rechargeable battery **1000** according to the embodiments of the present disclosure may include an electrode assembly **110**, a first current collecting plate **120**, a

second current collecting plate **130**, a case **150**, and a cap assembly **160**.

[0053] The case **150** may be formed of a conductive metal such as aluminum, an aluminum alloy, or a nickel-plated steel, and may have an approximately hexahedral shape with an opening and a receiving space into which the electrode assembly **110** may be inserted and seated. For example, the case **150** may have a hexahedral box shape with at least one side open. The cap assembly **160** may be coupled to the opening of the case **150** to seal the case **150**. An inner surface of the case **150** may be insulated to prevent an electric short circuit from occurring inside the case **150**. In some embodiments, one electrode of the electrode assembly **110** may be electrically connected to the case **150** through the cap assembly **160**. Even in this case, the electric short circuit inside the case **150** may be prevented by insulation treatment inside the case **150**.

[0054] The cap assembly **160** may be coupled to an upper portion of the case **150** toward the opening of the case **150**. For example, the cap assembly **160** may include a cap plate **161**, an electrolyte injection port **162**, a safety vent **163**, a first terminal **164**, a second terminal **165**, a gasket **166**, a first terminal plate **167**, a second terminal plate **168**, a fastening plate **169**, and a lower insulating member **170**.

[0055] The cap plate **161** may be coupled to the case **150** to cover the opening of the case **150** to seal the case **150**, and, for example, the cap plate **161** may be formed of the same material as that of the case **150**. The cap plate **161** may be coupled to the case **150** by, for example, a welding method (e.g., a laser welding method). In some embodiments, the cap plate **161** may be electrically independent, or may be electrically connected to either the first current collecting plate **120** or the second current collecting plate **130**.

[0056] The electrolyte injection port **162** for injecting an electrolyte may be formed in the cap plate **161**. The electrolyte may be injected into the case **150** through the electrolyte injection port **162**, and then the electrolyte injection port **162** may be sealed by a stopper **162a** (see FIG. 3).

[0057] The safety vent **163** may be relatively thin compared with another region and may be formed at an approximately center of the cap plate **161**. The safety vent **163** may be broken to prevent the rechargeable battery **1000** from exploding if an internal pressure of the case **150** is higher than a predetermined breaking pressure.

[0058] Each of the first terminal **164** and the second terminal **165** may penetrate the cap plate **161**. The first terminal **164** may be coupled to a terminal hole formed at a terminal connection portion **125** of the first current collecting plate **120** to be electrically connected to the first current collecting plate **120**. Likewise, the second terminal **165** may be coupled to a terminal hole formed at a terminal connection portion **135** of the second current collecting plate **130** to be electrically connected to the second current collecting plate **130**.

[0059] The gasket **166** may be disposed between the first and second terminals **164** and **165** and the cap plate **161**. The gasket **166** may be formed to surround an outer side of each of the first and second terminals **164** and **165**, and may be made of an insulating material. The gasket **166** may seal between each of the first and second terminals **164** and **165** and the cap plate **161**. The gasket **166** may prevent external moisture from penetrating into the rechargeable battery **1000**, or may prevent the electrolyte included within the rechargeable battery **1000** from flowing out.

[0060] The first terminal plate **167** may be coupled to the first terminal **164** and protrude to an upper portion of the cap plate **161**. After the first terminal plate **167** is coupled to the first terminal **164**, an upper portion of the first terminal **164** may be riveted or a boundary surface between the first terminal plate **167** and the first terminal **164** may be welded so that the first terminal plate **167** is fixed to the first terminal **164**.

[0061] The second terminal plate **168** may be coupled to the second terminal **165** and protrude to the upper portion of the cap plate **161**. After the second terminal plate **168** is coupled to the second terminal **165**, an upper portion of the second terminal **165** may be riveted or a boundary surface between the second terminal plate **168** and the second terminal **165** may be welded so that the second terminal plate **168** is fixed to the second terminal **165**.

[0062] The fastening plate **169** may be disposed between the cap plate **161** and the first terminal plate **167** and between the cap plate **161** and the second terminal plate **168**. The fastening plate **169** may be formed of either an electrically conductive material or an insulating material. For example, the fastening plate **169** disposed below the first terminal plate **167** may have a conductive material, and the fastening plate **169** disposed below the second terminal plate **168** may have an insulating material. For example, the first terminal **164** may have the same polarity as that of the cap plate **161**. In one or more embodiments, if the fastening plate **169** is made of the insulating material, the first terminal **164** and the second terminal **165** may be electrically separated from the cap plate **161**.

[0063] The lower insulating member **170** may be disposed between the first current collecting plate **120** and the cap plate **161** and between the second current collecting plate **130** and the cap plate **161**, and may electrically insulate between the first and second current collecting plates **120** and **130** and the cap plate **161**.

[0064] The electrode assembly **110** may be formed by stacking a first electrode **111** with a thin plate shape or a thin film shape, a separator **113**, and a second electrode **115**. The first electrode **111** may have a first polarity, and may operate as a positive electrode. The second electrode **115** may have a second polarity, and may operate as a negative electrode. The first electrode and the second electrode may have different polarities depending on the selection of those of ordinary skill in the art.

[0065] As shown in FIG. 2, a plurality of first electrodes **111**, a plurality of separators **113**, and a plurality of second electrodes **115** may be stacked. The first electrode **111** and the second electrode **115** may be alternately stacked with the separator **113** interposed therebetween, and the first electrode **111**, the second electrode **115**, and the separator **113** may be independent of each other.

[0066] For example, an electrode assembly unit may be formed by one first electrode **111**, one second electrode **115**, and one separator **113** interposed between them. In one or more embodiments, the electrode assembly **110** may be formed by stacking a plurality of electrode assembly units and interposing the separator **113** between the electrode assembly units.

[0067] The first electrode **111** may be formed by applying a first electrode active material such as a transition metal oxide or the like to a first electrode current collector formed of a metal foil such as an aluminum foil, and may include a first electrode uncoated portion **11** that is a region where the first electrode active material is not applied that has a protruding shape, i.e., it may protrude outside the electrode assembly **110**. The first electrode uncoated portion **11** may provide a path for a current flow between the first electrode **111** and the outside. For example, the first electrode uncoated portion **11** may protrude outside a short side of the electrode assembly to be disposed toward a length direction (e.g., a left direction based on FIG. 2) of the electrode assembly **110**.

[0068] In one or more embodiments, first electrode uncoated portions **11** may overlap at the same position when the first electrodes **111** are stacked so that the first electrode uncoated portions **11** form a multi-current collecting tab structure. In the present embodiment, the first electrode uncoated portion **11** may be formed as one body with the first electrode current collector, or may be provided separately from the first electrode current collector to be welded with to the first electrode current collector so that the first electrode uncoated portion **11** forms a current collecting tab. This first electrode uncoated portion **11** may be aligned with one side of the electrode assembly **110** and protrude therefrom.

[0069] The second electrode **115** may be formed by applying a second electrode active material such as graphite, carbon, or the like to a second electrode current collector formed of a metal foil such as a copper foil or a nickel foil, and may include a second electrode uncoated portion **15** that is a region where the second electrode active material is not applied and which may protrude outside the electrode assembly **110**.

[0070] Second electrode uncoated portions **15** may overlap at the same position when the second electrodes **115** are stacked so that the second electrode uncoated portions **15** form a multi-current collecting tab structure. The second electrode uncoated portion **15** may protrude outside the short

side of the electrode assembly to be disposed toward an opposite direction (e.g., a right direction based on FIG. 2) of the length direction of the electrode assembly **110**. In the present embodiment, the second electrode uncoated portion **15** may be formed as one body with the second electrode current collector, or may be provided separately from the second electrode current collector to be welded to the second electrode current collector so that the second electrode uncoated portion **15** forms a current collecting tab.

[0071] The separator **113** may be disposed between the first electrode **111** and the second electrode **115** to serve to prevent a short circuit and enable movement of lithium ions. The separator **113** may be made of polyethylene, polypropylene, or a composite film of polyethylene and polypropylene. A material of the separator **113** is not limited in the present disclosure.

[0072] For example, after the electrodes **111** and **115** are stacked together with the plurality of separators **113**, the electrode assembly **110** may maintain a stacked state through a separate insulating tape (not shown) attached to some regions thereof. For example, the insulating tape may maintain a shape of the electrode assembly **110** so that the electrode assembly **110** may be welded to the first and second current collecting plates **120** and **130** at a correct position and a structure of the electrode assembly **110** may be maintained within the case **150** in a final completed rechargeable battery.

[0073] The electrode assembly **110** may be substantially accommodated in the case **150** together with the electrolyte. The electrolyte may be formed of a lithium salt such as LiPF_6 or LiBF_4 in an organic solvent such as ethylene carbonate (EC), propylene carbonate (PC), diethyl carbonate (DEC), ethyl methyl carbonate (EMC), or dimethyl carbonate (DMC). For example, the electrolyte may have a liquid phase, a solid phase, or a gel phase.

[0074] The current collecting plates **120** and **130** (see FIG. 3) may include the first current collecting plate **120** electrically connected to the first electrode uncoated portion **11** and the second current collecting plate **130** electrically connected to the second electrode uncoated portion **15**.

[0075] The first current collecting plate **120** may be made of a conductive material such as aluminum or the like, and may be electrically connected to the first electrode **111** by being coupled to the first electrode uncoated portion **11** protruding from one end of the electrode assembly **110**.

[0076] For example, the first current collecting plate **120** may include an electrode connection portion **121** and a terminal connection portion **125**. In one or more embodiments, the electrode connection portion **121** and the terminal connection portion **125** may be coupled to each other through, for example, welding.

[0077] The electrode connection portion **121** may be disposed in a vertical direction along one side surface of the electrode assembly **110**. The electrode connection portion **121** may be coupled through welding in a state in which the electrode connection portion **121** is in contact with the first electrode uncoated portion **11** of the electrode assembly **110** to have the same first polarity as that of the first electrode uncoated portion **11**.

[0078] The terminal connection portion **125** may be disposed at an upper portion of the electrode assembly **110**, and may be disposed parallel to the cap plate **161**. For example, the terminal connection portion **125** may have an approximately flat plate shape, and may be disposed between the electrode assembly **110** and the cap plate **161**. The terminal connection portion **125** may include a terminal hole, and for example, the first terminal **164** may be fastened to the terminal hole through a riveting method. The terminal connection portion **125** may be coupled to the electrode connection portion **121** through welding so that one first current collecting plate **120** is formed.

[0079] The second current collecting plate **130** may be formed of a conductive material such as nickel or the like, and may be electrically connected to the second electrode **115** by contacting the second electrode uncoated portion **15** protruding from the other end of the electrode assembly **110**. The second current collecting plate **130** may include an electrode connection portion **131** and a terminal connection portion **135**. Because a shape of the second current collecting plate **130** is the same as that of the first current collecting plate **120**, a redundant description thereof will be omitted.

for convenience of description.

[0080] FIG. 4 is a perspective view of an electrode assembly **110** according to one or more embodiments of the present disclosure. Since the electrode assembly **110** of FIG. 4 is the same as the electrode assembly **110** of FIGS. 1 to 3, a redundant description thereof will be omitted.

[0081] In an x-y-z coordinate axis shown in FIG. 4 and FIG. 5 (hereinafter, the x-y-z coordinate axis is equally applied in other drawings), the x-axis may have a length direction (e.g., a left direction based on the drawings is a $-x$ -axis direction and a right direction based on the drawings is a $+x$ -axis direction) of the electrode assembly **110** or length directions of the electrode uncoated portions **11** and **15**. The y-axis may have a direction perpendicular to the x-axis direction, and may have a width direction (e.g., a front direction based on the drawings is a y-axis direction and a rear direction based on the drawings is a $-y$ -axis direction) of the electrode assembly **110** or width directions of the electrode uncoated portions **11** and **15**. The z-axis may have a direction vertical to both the x-axis direction and the y-axis direction, and may have a thickness direction (e.g., an upper direction based on the drawings is a $+z$ -axis direction and a lower direction based on the drawings is a $-z$ -axis direction) of the electrode assembly **110** or thickness directions of the electrode uncoated portions **11** and **15**.

[0082] Referring to FIG. 4, the first electrode uncoated portion **11** may include a first inner tab **10** disposed inside the first electrode uncoated portion **11** and a first outer tab **20** disposed to surround the first inner tab **10**. A width of the first inner tab **10** may be smaller than a width of the first electrode uncoated portion **11**.

[0083] In one or more embodiments, the first inner tab **10** may be formed by cutting an inner region of the first electrode uncoated portion **11**. For example, the first inner tab **10** may be separated from the first outer tab **20** by a cut line CL provided inside the first electrode uncoated portion **11**. A method by which the first inner tab **10** is cut inside the first electrode uncoated portion **11** may be a method using laser molding or a mold, but the present disclosure is not limited thereto.

[0084] Likewise, the second electrode uncoated portion **15** may include a second inner tab **30** disposed inside the second electrode uncoated portion **15** and a second outer tab **40** disposed to surround the second inner tab **30**. A width of the second inner tab **30** may be less than a width of the second electrode uncoated portion **15**.

[0085] Like the first inner tab **10**, the second inner tab **30** may be formed by cutting an inner region of the second electrode uncoated portion **15**. For example, the second inner tab **30** may be separated from the second outer tab **40** by a cut line CL provided inside the second electrode uncoated portion **15**. A method by which the second inner tab **30** is formed may be a method using laser molding or a mold, but the present disclosure is not limited thereto.

[0086] FIG. 5(a) is a partial perspective view for describing a structure of the first electrode uncoated portion **11** according to one or more embodiments of the present disclosure. FIG. 5(b) is a partial perspective view showing a state in which the first inner tab **10** of the first electrode uncoated portion **11** is bent according to one or more embodiments of the present disclosure.

[0087] Referring to FIG. 5(a) and FIG. 5(b), each of the first inner tab **10** and the first outer tab **20** may be bent. For example, the first inner tab **10** may be bent in a clockwise direction CW, or may be bent in a counterclockwise direction CCW. The first outer tab **20** may be bent in the clockwise direction CW, or may be bent in the counterclockwise direction CCW.

[0088] However, the bending direction of the first inner tab **10** and the bending direction of the first outer tab **20** are not the same. For example, if the first inner tab **10** is bent in the clockwise direction CW, the first outer tab **20** may be bent in the counterclockwise direction CCW, and if the first inner tab **10** is bent in the counterclockwise direction CCW, the first outer tab **20** may be bent in the clockwise direction CW.

[0089] The first inner tab **10** and the first outer tab **20** of the first electrode uncoated portion **11** of the plurality of first electrodes **111** stacked in this way may be bent. Any one of first inner tabs **10**

may be bent so as to overlap the already bent first inner tab **10**. Likewise, any one of first outer tabs **20** may be bent to overlap the already bent first outer tab **20**.

[0090] For example, as described above, the first inner tab **10** and the first outer tab **20** may be bent in opposite directions, so that the first inner tabs **10** are supported by each other and the first outer tabs **20** are supported by each other in a state in which all of the first inner tabs **10** and the first outer tabs **20** of the plurality of first electrodes constituting the electrode assembly **110** are finally bent.

[0091] Thus, the first inner tab **10** and the first outer tab **20** may be made of a bundle-type fixation body without a separate fixing means (or a separate fixing device), so that the first electrodes **111** or the second electrodes **115** may be stacked by matching their centers. For example, the first electrodes **111** or the second electrodes **115** may be stacked while meandering of the first electrodes **111** or the second electrodes **115** is prevented. A detailed description thereof will be given subsequently.

[0092] FIG. **6** is a perspective view showing a state in which the first and second inner tabs **10** and **30** and the first and second outer tabs **20** and **40** are bent according to one or more embodiments of the present disclosure. Referring to FIG. **6**, the first inner tab **10** of the first electrode uncoated portion **11** may be bent in the counterclockwise direction CCW, and the first outer tab **20** may be bent in the clockwise direction CW. In one or more embodiments, the second inner tab **30** (obscured by the electrode assembly **110** in FIG. **6**) of the second electrode uncoated portion **15** may be bent in the clockwise direction CW, and the second outer tab **40** may be bent in the counterclockwise direction CCW. For example, the bending direction of each of the first and second inner tabs **10** and **30** and the bending direction of each of the first and second outer tabs **20** and **40** may be opposite.

[0093] In one or more embodiments, if the first and second inner tabs **10** and **30** and the first and second outer tabs **20** and **40** are bent equally in only one direction without distinction in directionality, it is possible to suppress the electrode assembly **110** from moving in the length direction (the +x-axis direction and the -x-axis direction). However, in this case, it is difficult to completely suppress the electrode assembly **110** from moving in the width direction (the +y-axis direction and the -y-axis direction). For example, the first electrode **111** and the second electrode **115** may be meandered in the width direction of the electrode assembly, so that the first electrode **111** and the second electrode **115** are likely to be stacked while being disturbed in the +y-axis direction or the -y-axis direction.

[0094] In one or more embodiments, if the first inner tab **10** and the first outer tab **20** are divided and both tabs **10** and **20** are bent in opposite directions as in the embodiment shown in FIG. **6**, the electrode assembly **110** may be suppressed from moving in the length direction (the +x-axis direction and the -x-axis direction), and the electrode assembly **110** may be prevented from moving in the width direction (the +y-axis direction and the -y-axis direction) because a bundle stack (or a bundle laminate) of the first inner tab **10** is prevented from moving by a bundle stack (or a bundle laminate) of the first outer tab **20**. Thus, when the electrode assembly **100** is formed by stacking the plurality of first electrodes **111**, the plurality of separators **113**, and the plurality of second electrodes **115**, the first electrode **111** and the second electrode **115** may be stacked so that centers of the first electrode **111** and the second electrode **115** coincide.

[0095] Likewise, the second inner tab **30** of the second electrode uncoated portion **15** may be bent in a direction opposite to the bending direction of the second outer tab **40**. For example, the second inner tab **30** may be bent in the clockwise direction CW, and the second outer tab **40** may be bent in the counterclockwise direction CCW. The second inner tab **30** and the second outer tab **40** may prevent a movement of the electrode assembly **100** in the width direction (the +y-axis direction and the -y-axis direction), and may also prevent a movement of the electrode assembly **100** in the length direction (the +x-axis direction and the -x-axis direction).

[0096] Since the inner tabs **10** and **30** and the outer tabs **20** and **40** of the electrode uncoated

portions **11** and **15** may be bent in opposite directions, the plurality of first electrodes **111** and the plurality of second electrodes **115** may be stacked so that centers thereof coincide. Thus, a process of aligning the electrode assembly **110** so that the centers of the first electrodes **111** and the second electrodes **115** coincide once again after the first electrodes **111**, the separators **113**, and the second electrodes **115** are stacked may be omitted.

[0097] Since the alignment process (e.g., a fixing process or a meandering prevention process) of the electrode assembly **110** is omitted, additional process materials and additional time required may not be required, so that efficiency of a manufacturing process of the rechargeable battery **1000** including the electrode assembly **110** is improved. For example, a cost and a time required to manufacture the rechargeable battery **1000** may be reduced.

[0098] The bending direction of each of the first inner and outer tabs **10** and **20** of the first electrode uncoated portion **11** and the bending direction of each of the second inner and outer tabs **30** and **40** of the second electrode uncoated portion **15** are not limited to the example described above, the first inner tab **10** may be bent in the clockwise direction CW and the first outer tab **20** may be bent in the counterclockwise direction CCW, and the second inner tab **30** may be bent in the counterclockwise direction CCW and the second outer tab **40** may be bent in the clockwise direction CW.

[0099] In one or more embodiments, the bending direction of the first inner tab **10** may be unrelated to the bending direction of the second inner tab **30**. For example, if the first inner tab **10** is bent in the clockwise direction CW, the second inner tab **30** may be bent in the clockwise direction CW, or may be bent in the counterclockwise direction CCW. A relationship between the bending directions is the same for the first outer tab **20** and the second outer tab **40**.

[0100] FIGS. 7(a) to 7(c) are plan views for describing a tab shape of the electrode assembly **110** according to one or more embodiments of the present disclosure, and for convenience of description, a first inner tab of the first electrode will be described as an example.

[0101] Referring to FIG. 7(a), the shape of the first inner tab **10a** of the first electrode uncoated portion **11** may be a quadrangular shape. Since all sides of the first inner tab **10a** are straight lines, a movement of the electrode assembly **100** in the width direction (the +y-axis direction and the -y-axis direction) may be more reliably suppressed.

[0102] As shown in FIG. 7(b), a shape of the first inner tab **10b** may be a semicircular shape. In this case, bending of the first inner tab **10b** may be easier. As shown in FIG. 7(c), the first inner tab **10c** may be provided in a plural number (e.g., two). In this case, a movement of the electrode assembly **100** in the width direction (the +y-axis direction and the -y-axis direction) may be more reliably suppressed. Although the shape of the inner tab is described as an example of the first inner tab, the shape of the inner tab is not limited to the shapes described above, and may be a shape within a range thought up by those of ordinary skill in the art.

[0103] FIG. 8 is a partial plan view for describing a width interval between a width W1 of the first inner tab **10** and a width W2 of the first outer tab **20**, and length interval between a length L1 of the first inner tab **10** and a length L2 of the first outer tab **20** of the electrode assembly **110** according to one or more embodiments of the present disclosure.

[0104] Referring to FIG. 8, the widths W1 and W2 of the first inner tab **10** and the first outer tab **20** of the electrode assembly **110** according to embodiments of the present disclosure may be set along the y-axis direction, and the lengths L1 and L2 of the first inner tab **10** and the first outer tab **20** may be set along the x-axis direction.

[0105] As the width W1 of the first inner tab **10** increases, a movement caused by meandering of the first electrode and the second electrode in the width direction (the y-axis direction) may be prevented. For example, as the width W1 of the first inner tab **10** is wider, welding between the first electrode uncoated portion **11** (that is, the first inner tab **10** and/or the first outer tab **20**) and the first current collecting plate **120** may be facilitated.

[0106] In one or more embodiments, the length L1 of the first inner tab **10** may be at least 5 mm or

more. If the length L1 of the first inner tab **10** is less than 5 mm, a meandering prevention effect of the first electrode and the second electrode may be insignificant.

[0107] For example, the length L1 of the first inner tab **10** may be smaller than the length L2 of the first outer tab **20**. In one or more embodiments, the length interval between the length L1 of the first inner tab **10** and the length L2 of the first outer tab **20** may be from 5 mm to 10 mm.

[0108] If the length interval between the length L1 of the first inner tab **10** and the length L2 of the first outer tab **20** is less than 5 mm, the first inner tab **10** and the first outer tab **20** may not be separated well, and a formation of the first inner tab **10** may be difficult. For example, if the length interval between the length L1 of the first inner tab **10** and the length L2 of the first outer tab **20** exceeds 10 mm, the meandering prevention effect of the first electrode and the second electrode may be insignificant.

[0109] Although the embodiments with reference to FIG. 7 and FIG. 8 are described using the first electrode uncoated portion **11** as an example, the above description may be equally applied to the second electrode uncoated portion **15**.

[0110] FIG. 9(a) is a flowchart for describing a method for manufacturing a rechargeable battery using a comparative example. FIG. 9(b) is a flowchart for describing a method for manufacturing the rechargeable battery **1000** according to one or more embodiments of the present disclosure.

[0111] Referring to FIG. 9(a), in order to manufacture the rechargeable battery in the comparative example, a step S101 of stacking a plurality of first electrodes, a plurality of separators, and a plurality of second electrodes to form an electrode assembly, a step S103 of bending an uncoated portion of each of first and second electrodes, a step S105 of aligning and fixing centers of the first and second electrodes of the electrode assembly so as to coincide the centers of the first and second electrodes, and a final step S107 of welding the uncoated portions of the first and second electrode to first and second terminals provided in a cap assembly are required.

[0112] Referring to FIG. 9(b), the rechargeable battery **1000** according to one or more embodiments of the present disclosure may be manufactured by stacking the plurality of first electrodes **111**, the plurality of separators **113**, and the plurality of second electrodes **115** to form the electrode assembly **110** (S201), dividing the inner tabs **10** and **30** and the outer tabs **20** and **40** with respect to the uncoated portions **11** and **15** of the first electrode **111** and the second electrode **115** to bend the inner tabs **10** and **30** and the outer tabs **20** and **40** (S203), and welding the electrode uncoated portions **11** and **15** (that is, the first and second inner tabs **10** and **30** and/or the first and second outer tabs **20** and **40**) to the terminals **164** and **165** (S207)

[0113] Thus, when the electrode assembly **110** is manufactured, a separate process of aligning and fixing the uncoated portions forming the tabs may be omitted. Therefore, the rechargeable battery **1000** may be efficiently manufactured. Further, a cost and a time required to manufacture the rechargeable battery **1000** may be reduced.

[0114] In embodiments of the present disclosure, a compound (i.e., a lithium intercalation compound) capable of reversible intercalation and deintercalation of lithium may be used as a positive electrode active material constituting a positive electrode active material layer of the positive electrode. For example, one or more types of composite oxides of a metal selected from cobalt, manganese, nickel, and a combination thereof and lithium may be used as the positive electrode active material.

[0115] The composite oxide may be lithium transition metal composite oxide, and for example, the composite oxide may include lithium nickel-based oxide, lithium cobalt-based oxide, lithium manganese-based oxide, a lithium iron phosphate-based compound, cobalt-free nickel-manganese-based oxide, or a combination thereof.

[0116] As an example, a compound expressed by any one of the following chemical formulas may be used as the positive electrode active material. $\text{Li}_{0.90 \leq a \leq 1.8} \text{aA}_{0 \leq b \leq 0.5} \text{bX}_{0 \leq c \leq 0.05} \text{cO}_{2-\text{D}} \text{D}_{\text{sub.c}}$ ($0.90 \leq a \leq 1.8$, $0 \leq b \leq 0.5$, $0 \leq c \leq 0.05$); $\text{Li}_{0.90 \leq a \leq 1.8} \text{aMn}_{0 \leq b \leq 0.5} \text{bX}_{0 \leq c \leq 0.05} \text{cO}_{2-\text{D}} \text{D}_{\text{sub.c}}$ ($0.90 \leq a \leq 1.8$, $0 \leq b \leq 0.5$, $0 \leq c \leq 0.05$); $\text{Li}_{0.90 \leq a \leq 1.8} \text{aNi}_{0 \leq b \leq 0.5} \text{bX}_{0 \leq c \leq 0.05} \text{cO}_{2-\alpha \text{D}} \text{D}_{\text{sub.}\alpha}$ ($0.90 \leq a \leq 1.8$, $0 \leq b \leq 0.5$,

$0 \leq c \leq 0.5$, $0 < \alpha < 2$); Li.sub.aNi.sub.1-b-cMn.sub.bX.sub.cO.sub.2- α D.sub. α ($0.90 \leq a \leq 1.8$, $0 \leq b \leq 0.5$, $0 \leq c \leq 0.5$, $0 < \alpha < 2$); Li.sub.aNi.sub.bCo.sub.cL.sub.1.sub.dO.sub.2 ($0.90 \leq a \leq 1.8$, $0 \leq b \leq 0.9$, $0 \leq c \leq 0.5$, $0 \leq d \leq 0.5$, $0 \leq e \leq 0.1$); Li.sub.aNiG.sub.bO.sub.2 ($0.90 \leq a \leq 1.8$, $0.001 \leq b \leq 0.1$); Li.sub.aCoG.sub.bO.sub.2 ($0.90 \leq a \leq 1.8$, $0.001 \leq b \leq 0.1$); Li.sub.aMn.sub.1-6G.sub.bO.sub.2 ($0.90 \leq a \leq 1.8$, $0.001 \leq b \leq 0.1$); Li.sub.aMn.sub.2G.sub.bO.sub.4 ($0.90 \leq a \leq 1.8$, $0.001 \leq b \leq 0.1$); Li.sub.aMn.sub.1-gG.sub.gPO.sub.4 ($0.90 \leq a \leq 1.8$, $0 \leq g \leq 0.5$); Li.sub.(3-f)Fe.sub.2(PO.sub.4).sub.3 ($0 \leq f \leq 2$); and Li.sub.aFePO.sub.4 ($0.90 \leq a \leq 1.8$).

[0117] In the above formulas, A may be Ni, Co, Mn, or a combination thereof; X may be Al, Ni, Co, Mn, Cr, Fe, Mg, Sr, V, a rare earth element, or a combination thereof; D may be O, F, S, P, or a combination thereof; G may be Al, Cr, Mn, Fe, Mg, La, Ce, Sr, V, or a combination thereof; and L.sub.1 may be Mn, Al, or a combination thereof.

[0118] The positive electrode according to embodiments may include a positive electrode current collector at which the positive electrode active material layer is disposed, and the positive electrode active material layer may include a binder and/or a conductive material.

[0119] A content of the positive electrode active material may be 90 wt % to 99.5 wt % based on 100 wt % of the positive electrode active material layer, and a content of each of the binder and the conductive material may be 0.5 wt % to 5 wt % based on 100 wt % of the positive electrode active material layer.

[0120] Aluminum (Al) may be used as the positive electrode current collector, but the present disclosure is not limited thereto.

[0121] In one or more embodiments of the present disclosure, a negative electrode active material constituting a negative electrode active material layer of the negative electrode may include a material capable of reversible intercalation and deintercalation of a lithium ion, a lithium metal, an alloy of the lithium metal, a material capable of doping and dedoping lithium, or transition metal oxide.

[0122] For example, the material capable of reversible intercalation and deintercalation of the lithium ion may include a carbon-based negative electrode active material (for example, crystalline carbon, amorphous carbon, or a combination thereof). An example of the crystalline carbon may include graphite such as natural graphite or artificial graphite, and an example of the amorphous carbon may include soft carbon, hard carbon, mesophase pitch carbide, fired cokes, or the like.

[0123] A Si-based negative electrode active material or a Sn-based negative electrode active material may be used as the material capable of doping and dedoping lithium. The Si-based negative electrode active material may be silicon, a silicon-carbon composite, SiO_x ($0 < x < 2$), a Si-based alloy, or a combination thereof.

[0124] The silicon-carbon composite may be a composite of silicon and amorphous carbon. According to an embodiment, the silicon-carbon composite may have a form in which the amorphous carbon is coated on a surface of a silicon particle.

[0125] The silicon-carbon composite may further include crystalline carbon. For example, the silicon-carbon composite may include a core including the crystalline carbon and the silicon particle and an amorphous carbon coating layer disposed on a surface of the core.

[0126] The negative electrode according to embodiments may include a negative electrode current collector at which the negative electrode active material layer is disposed, and the negative electrode active material layer may include a binder and/or a conductive material.

[0127] For example, the negative electrode active material layer may include 90 wt % to 99 wt % of the negative electrode active material based on 100 wt % of the negative electrode active material, 0.5 wt % to 5 wt % of the binder, and 0 wt % to 5 wt % of the conductive material.

[0128] A non-aqueous binder, an aqueous binder, a dry binder, or a combination thereof may be used as the binder. If the aqueous binder is used as the binder, it may further include a cellulose-based compound capable of imparting viscosity.

[0129] The negative electrode current collector may be selected from a copper foil, a nickel foil, a

stainless-steel foil, a titanium foil, a nickel foil, a copper foam, a polymer substrate coated with a conductive metal, and a combination thereof.

[0130] The electrolyte for a lithium rechargeable battery may include a non-aqueous organic solvent and a lithium salt.

[0131] The non-aqueous organic solvent may serve as a medium through which ions involved in an electrochemical reaction of the battery may move.

[0132] The non-aqueous organic solvent may be a carbonate-based solvent, an ester-based solvent, an ether-based solvent, a ketone-based solvent, an alcohol-based solvent, an aprotic solvent, or a combination thereof, and the materials may be used alone or in combination of two or more types.

[0133] If the carbonate-based solvent is used, a mixture of cyclic carbonate and linear carbonate may be used.

[0134] Depending on a type of the lithium rechargeable battery, the separator may exist between the positive electrode and the negative electrode. Polyethylene, polypropylene, polyvinylidene fluoride, or a multilayer film with two or more layers thereof may be used as the separator.

[0135] The separator may include a porous substrate and a coating layer including an organic material, an inorganic material, or a combination thereof disposed on one surface or both surfaces of the porous substrate.

[0136] The organic material may include a polyvinylidene fluoride-based polymer or a (metha)acryl-based polymer.

[0137] The inorganic material may include an inorganic particle selected from Al_2O_3 , SiO_2 , TiO_2 , SnO_2 , CeO_2 , MgO , NiO , CaO , GaO , ZnO , ZrO_2 , Y_2O_3 , SrTiO_3 , BaTiO_3 , $\text{Mg}(\text{OH})_2$, boehmite, and a combination thereof, but the present disclosure is not limited thereto.

[0138] The organic material and the inorganic material may be mixed in one coating layer, or a coating layer including the organic material and a coating layer including the inorganic material may be stacked.

[0139] The present disclosure provides, for example, an electrode assembly configured so as not to require separate electrode fixation when an electrode assembly for a rechargeable battery is manufactured.

[0140] Although the present disclosure has been described above by limited embodiments and the drawings, the present disclosure is not limited thereto, and various modifications and variations may be made within an equivalent scope of the technical idea of the present disclosure and claims to be described below by those of ordinary skill in the art.

[0141] Example embodiments have been disclosed herein, and although specific terms are employed, they are used and are to be interpreted in a generic and descriptive sense only and not for purpose of limitation. In some instances, as would be apparent to one of ordinary skill in the art as of the filing of the present application, features, characteristics, and/or elements described in connection with a particular embodiment may be used singly or in combination with features, characteristics, and/or elements described in connection with other embodiments unless otherwise specifically indicated. Accordingly, it will be understood by those of skill in the art that various changes in form and details may be made without departing from the spirit and scope of the present invention as set forth in the following claims.

DESCRIPTION OF SYMBOLS

[0142] **10**: first inner tab [0143] **11**: first electrode uncoated portion [0144] **15**: second electrode uncoated portion [0145] **20**: first outer tab [0146] **30**: second inner tab [0147] **40**: second outer tab [0148] **110**: electrode assembly [0149] **111**: first electrode [0150] **113**: separator [0151] **115**: second electrode [0152] **120**: first current collecting plate [0153] **130**: second current collecting plate [0154] **150**: case [0155] **160**: cap assembly [0156] **1000**: rechargeable battery [0157] **W1**: width of first inner tab [0158] **W2**: width of first outer tab [0159] **L1**: length of first inner tab [0160] **L2**: length of first outer tab

Claims

1. An electrode assembly comprising: a first electrode comprising a first electrode uncoated portion with a protruding shape; a second electrode comprising a second electrode uncoated portion with a protruding shape; and a separator disposed between the first electrode and the second electrode, wherein the first electrode uncoated portion comprises a first inner tab and a first outer tab separated by a cut line provided inside the first electrode uncoated portion, and wherein the second electrode uncoated portion comprises a second inner tab and a second outer tab separated by a cut line provided inside the second electrode uncoated portion.
2. The electrode assembly as claimed in claim 1, wherein a protruding direction of the first electrode uncoated portion and a protruding direction of the second electrode uncoated portion are opposite to each other.
3. The electrode assembly as claimed in claim 1, wherein the first outer tab and the second outer tab are respectively bent in directions opposite to bending directions of the first inner tab and the second inner tab.
4. The electrode assembly as claimed in claim 1, wherein each of the first inner tab and the second inner tab has a circular shape.
5. The electrode assembly as claimed in claim 1, wherein each of the first inner tab and the second inner tab has a quadrangular shape.
6. The electrode assembly as claimed in claim 1, wherein the first inner tab and the second inner tab are each at least two or more.
7. The electrode assembly as claimed in claim 1, wherein a width of each of the first inner tab and the second inner tab is greater than or equal to 5 mm and the width of the first inner tab is less than the width of the second outer tab.
8. The electrode assembly as claimed in claim 7, wherein a width interval between the first outer tab and the first inner tab, and a width interval between the second outer tab and the second inner tab are each 10 mm or less.
9. The electrode assembly as claimed in claim 1, wherein each of the first electrode, the second electrode, and the separator is provided in a plural number, the first electrode and the second electrode are alternately stacked along a first direction with the separator interposed therebetween, and the plurality of first electrodes, the plurality of second electrodes, and the plurality of separators are independent of each other.
10. A rechargeable battery comprising: the electrode assembly as claimed in claim 1; a case accommodating the electrode assembly; and a cap assembly comprising a first electrode terminal electrically connected to the first electrode and a second electrode terminal electrically connected to the second electrode, the cap assembly being coupled to the case to cover and seal an opening of the case, wherein the first electrode terminal is connected to the first electrode through a first current collecting plate connected to the first electrode terminal and at least one of the first inner tab and the first outer tab, and the second electrode terminal is connected to the second electrode through a second current collecting plate connected to the second electrode terminal and at least one of the second inner tab and the second outer tab.
11. A method for manufacturing a rechargeable battery, the method comprising: providing the electrode assembly as claimed in claim 1; providing a cap assembly comprising a first electrode terminal, a second electrode terminal, a first current collecting plate connected to the first electrode terminal, and a second current collecting plate connected to the second electrode terminal; respectively connecting the first current collecting plate and the second current collecting plate to at least one of the first inner tab and the first outer tab and at least one of the second inner tab and the second outer tab; and inserting the electrode assembly into a case having an accommodation space

and coupling the cap assembly to the case to cover an opening of the case so that the cap assembly seals the case.
