

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397949
Kind Code	B1
Date of Patent	August 26, 2025
Inventor(s)	Yisha; Richard W. et al.

Pill feed apparatus for packaging machine

Abstract

A pill feed apparatus (30) is configured to be utilized in connection with a unit dose packaging machine (10) or other device. The exemplary apparatus includes a plurality of feeder discs (104, 150, 174) that include a plurality of pill engaging apertures (120, 152, 176) that are sized for holding pills of different respective pill configurations. The respective feeder discs are rotatably movable within a base interior area (238) that is bounded by a base ring (42). A cover (66) is in supporting connection with a plurality of deformable brushes (234, 240, 242, 244, 246, 248) that are configured to engage pills that move with a feeder disc. Rotation of a feeder disc causes pills positioned within the interior area to be moved into sequential engagement with the brushes such that a single pill is caused to be engaged with each respective aperture. Pills are delivered individually and in a controlled manner from the apertures for inclusion in packages.

Inventors: Yisha; Richard W. (Medina, OH), Yeo; Kevin Paul (Ashland, OH)

Applicant: Innovative Technology, Inc. (Ashland, OH)

Family ID: 1000007225985

Assignee: ACCU-CHART PLUS HEALTH CARE SYSTEMS, INC. (St. Petersburg, FL)

Appl. No.: 18/213617

Filed: June 23, 2023

Related U.S. Application Data

us-provisional-application US 63398280 20220816

us-provisional-application US 63357676 20220701

Publication Classification

Int. Cl.: B65B35/08 (20060101); B65B35/26 (20060101); B65B65/02 (20060101)

U.S. Cl.:

CPC **B65B35/08** (20130101); **B65B35/26** (20130101); **B65B65/02** (20130101);

Field of Classification Search

CPC: B65B (5/103); B65B (35/08); A61J (7/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1579247	12/1925	Rohlfing	72/142	B21F 3/04
2225957	12/1939	Korff	475/263	F16H 1/32
2801025	12/1956	Cookson	221/68	B65B 5/103
4693057	12/1986	Rittinger	53/247	B65B 35/08
5086945	12/1991	Corella	221/265	B65B 5/103
7392640	12/2007	Vasquali	53/247	B65B 5/103
2002/0092275	12/2001	Kim	53/493	B65B 5/103
2006/0021316	12/2005	Harkcom	56/255	A01D 34/664
2009/0087257	12/2008	Harkcom	403/359.1	A01D 75/182
2011/0030314	12/2010	Baroncini	53/254	B65B 35/08
2013/0008131	12/2012	Baroncini	53/235	B65B 59/04
2013/0284755	12/2012	Yuyama	221/277	B65D 83/04
2015/0217930	12/2014	Holmes	221/1	G07F 11/32

Primary Examiner: Leeds; Daniel Jeremy

Attorney, Agent or Firm: WALKER & JOCKE

Background/Summary

TECHNICAL FIELD

(1) Exemplary arrangements relate to packaging equipment. Exemplary arrangements specifically relate to an apparatus that is operative to separate and deliver pills or similar articles one at a time for packaging.

BACKGROUND

(2) Solid medications such as pills of various shapes, capsules and caplets (all of which are referred to herein as pills) are commonly placed in unit dose packaging. This is done to protect the pills from contaminants until the medication is to be taken by the patient. Such packaging is also provided so that the packaging can be labeled with information about the medication.

(3) To successfully place pills in unit dose packaging, the pills must be separated and delivered one at a time in a coordinated manner to a mechanism that encapsulates each pill within a unit dose package. In some exemplary arrangements pills are required to be moved and positioned by a human operator to place the pills into individual receptacles from which they can be extracted for packaging. An example of such a packaging machine is shown in U.S. Pat. No. 4,493,178, the disclosure of which is incorporated herein by reference in its entirety. Machines which operate

using these principles are commercially available from Euclid Medical Products of Apple Creek, Ohio.

(4) Unit dose packaging machines and other pill handling apparatus may benefit from improvements.

SUMMARY

(5) Exemplary arrangements provide an apparatus that receives a batch comprising a plurality of loose pills and which operates to separate each pill from the others, and positions it in a respective receptacle which is alternatively referred to herein as a pill engaging aperture. The receptacles are moved in a coordinated manner so that each pill is delivered from the respective receptacle in which it is positioned into a mechanism that incorporates the pill into a unit dose package.

(6) The exemplary arrangements are configured to operate with pills of numerous different sizes and shapes (for purposes of this disclosure different sizes of pills and different shapes of pills will each be referred to as different configurations). Further some exemplary arrangements are configured to be installed on existing unit dose medication packaging machines to eliminate the need for a human operator to move and position individual pills.

(7) Additional features of exemplary arrangements will be made apparent in the following Detailed Description and the attached drawings.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a front left perspective view of a prior art unit dose packaging machine for solid medications.

(2) FIG. 2 is a front right perspective view of the prior art machine shown in FIG. 1.

(3) FIG. 3 is a front left perspective view of the machine of FIG. 1 with its manual fill pill disc removed.

(4) FIG. 4 is a front right perspective view of the machine with the pill disc removed.

(5) FIG. 5 is a front right perspective view of the machine with its pill disc and pill supporting tray removed.

(6) FIG. 6 is a front left perspective view of the unit dose packaging machine of FIG. 1 with the pill disc and pill supporting tray replaced with a pill feed apparatus of an exemplary arrangement.

(7) FIG. 7 is an exploded view of the pill feed apparatus shown in FIG. 6.

(8) FIG. 8 is a top front perspective view of an exemplary base ring of the exemplary pill feed apparatus.

(9) FIG. 9 is a top view of the base ring.

(10) FIG. 10 is a back view of the base ring.

(11) FIG. 11 is a side view of the base ring.

(12) FIG. 12 is a diametric cross-sectional view of an exemplary feeder disc, drive platter and drive pin of the exemplary pill feed apparatus.

(13) FIG. 13 is a top front perspective view of the exemplary drive platter.

(14) FIG. 14 is a top plan view of the drive platter.

(15) FIG. 15 is a side view of the drive platter.

(16) FIG. 16 is a top view of an exemplary feeder disc.

(17) FIG. 17 is a cross-sectional view taken along line 17-17 in FIG. 16.

(18) FIG. 18 is an enlarged cross-sectional view of the exemplary drive platter and drive pin.

(19) FIG. 19 is a top right perspective view of the exemplary drive pin.

(20) FIG. 20 is a front view of the drive pin with a drive post which rotationally moves the drive pin shown in phantom.

(21) FIG. 21 is a right side view of the drive pin and drive post.

- (22) FIG. 22 is a top front perspective view of an exemplary feeder disc.
- (23) FIG. 23 is a top view of the feeder disc shown in FIG. 22.
- (24) FIG. 24 is a cross-sectional view of the feeder disc taken along line 24-24 in FIG. 23.
- (25) FIG. 25 is a top plan view of another feeder disc which is configured to separate and deliver pills having a larger diameter than the feeder disc shown in FIGS. 22-24.
- (26) FIG. 26 is a cross-sectional view taken along line 26-26 in FIG. 25.
- (27) FIG. 27 is a top plan view of another feeder disc which is configured to separate and deliver pills having an elongated capsule configuration.
- (28) FIG. 28 is a cross-sectional view taken along line 28-28 in FIG. 27.
- (29) FIG. 29 is a front top right perspective view of an exemplary inserter of the pill feed apparatus.
- (30) FIG. 30 is a top view of the inserter.
- (31) FIG. 31 is a front view of the inserter.
- (32) FIG. 32 is a bottom view of the inserter.
- (33) FIG. 33 is a top front right perspective view of a pill sizer of the exemplary apparatus.
- (34) FIG. 34 is a front view of the exemplary pill sizer.
- (35) FIG. 35 is a cross-sectional view taken along lines 35-35 in FIG. 34.
- (36) FIG. 36 is a top transparent view of the exemplary pill feed apparatus showing the exemplary internal brushes and with arrows showing the paths along which pills move relative to the feeder disc.
- (37) FIG. 37 is a front plan view of an exemplary brush used in the pill feed apparatus referred to for convenience herein as brush A.
- (38) FIG. 38 is a front plan view of a further exemplary brush referred to for convenience herein as brush B.
- (39) FIG. 39 is a front plan view of a further exemplary brush referred to for convenience herein as brush C.
- (40) FIG. 40 is a front plan view of a further exemplary brush referred to for convenience herein as brush D.
- (41) FIG. 41 is a front plan view of a further exemplary brush referred to for convenience herein as brush E.
- (42) FIG. 42 is a front plan view of a further exemplary brush referred to for convenience herein as brush F.
- (43) FIG. 43 is a top transparent view of the exemplary pill feed apparatus with a feeder disc installed therein.
- (44) FIG. 44 is a cross-sectional view along each of lines 44-44 in FIG. 43 and with the inserter and the feeder disc shown in phantom.
- (45) FIG. 45 is a front view of brush A and the mount portion thereof.
- (46) FIG. 46 is a cross-sectional view taken along line 46-46 in FIG. 45.
- (47) FIG. 47 is a top transparent view of area A shown in FIG. 44 with a plurality of pills adjacent to brush A.
- (48) FIG. 48 is a top transparent view of area A shown in FIG. 44 with a plurality of capsules and a corresponding feeder disc for handling capsules adjacent to brush A.
- (49) FIG. 49 is a top transparent view of the exemplary pill feed apparatus.
- (50) FIG. 50 is a cross-sectional view taken along line 50-50 in FIG. 49 and with the feeder disc and inserter shown in phantom.
- (51) FIG. 51 is a front view of brush B including the mount portion thereof.
- (52) FIG. 52 is a cross-sectional view taken along line 52-52 in FIG. 51.
- (53) FIG. 53 is a top transparent view showing pills and a corresponding feeder disc in area B in FIG. 49.
- (54) FIG. 54 is a top transparent view showing capsules and a corresponding feeder disc in area B in FIG. 49.

(55) FIG. 55 is a top transparent view of the exemplary pill feed mechanism.

(56) FIG. 56 is a cross-sectional view taken along line 56-56 in FIG. 55 and with the inserter and the feeder disc shown in phantom.

(57) FIG. 57 is a front view of brush C including the mount portion thereof.

(58) FIG. 58 is a cross-sectional view taken along line 58-58 in FIG. 57.

(59) FIG. 59 is a top transparent view of area C shown in FIG. 55 with a plurality of pills and a corresponding feeder disc.

(60) FIG. 60 is a top transparent view of area C shown in FIG. 55 with a plurality of capsules and a corresponding feeder disc.

(61) FIG. 61 is a top transparent view of the exemplary pill feed assembly.

(62) FIG. 62 is a cross-sectional view taken along line 62-62 in FIG. 61 and with the inserter and feeder disc shown in phantom.

(63) FIG. 63 is a front view of brush D including the mount portion thereof.

(64) FIG. 64 is a cross-sectional view taken along line 64-64 in FIG. 63.

(65) FIG. 65 is a top transparent view of area D in FIG. 61 with a plurality of pills and a corresponding feeder disc.

(66) FIG. 66 is a top transparent view of area D in FIG. 61 with a plurality of capsules and a corresponding feeder disc.

(67) FIG. 67 is a top transparent view of the exemplary pill feed apparatus.

(68) FIG. 68 is a cross-sectional view taken along lines 68-68 in FIG. 67 with the inserter and the feeder disc shown in phantom.

(69) FIG. 69 is a front view of brush E including the mount portion thereof.

(70) FIG. 70 is a cross-sectional view taken along line 70-70 in FIG. 69.

(71) FIG. 71 is a top transparent view of area E in FIG. 67 with a plurality of pills and a corresponding feeder disc.

(72) FIG. 72 is a top transparent view of area E in FIG. 67 of the plurality of capsules and a corresponding feeder disc.

(73) FIG. 73 is a top transparent view of the exemplary pill feed mechanism.

(74) FIG. 74 is a cross-sectional view along line 74-74 in FIG. 73 with the inserter and the feeder disc shown in phantom.

(75) FIG. 75 is a front view of brush F including the mount portion thereof.

(76) FIG. 76 is a cross-sectional view taken along line 76-76 in FIG. 75.

(77) FIG. 77 is a top transparent view of area F in FIG. 73 with a plurality of pills and a corresponding feeder disc.

(78) FIG. 78 is a top transparent view of area F in FIG. 73 with a plurality of pills and a corresponding feeder disc.

(79) FIG. 79 is a top transparent view of the exemplary pill feed apparatus.

(80) FIG. 80 is a cross-sectional view taken along line 80-80 in FIG. 79 with the inserter and the feeder disc shown in phantom.

(81) FIG. 81 is a top transparent view of area DV in FIG. 79 showing the diverter, a plurality of pills and a corresponding feeder disc.

(82) FIG. 82 is a top transparent view of area DV in FIG. 79 showing a diverter, a plurality of capsules and a corresponding feeder disc.

(83) FIG. 83 is a top front right perspective view of a unit dose packaging machine similar to those previously described but with a mechanism suitable for packaging two pills simultaneously, and with the pill disc and pill supporting tray replaced with an alternative dual pill feed apparatus of an alternative arrangement.

(84) FIG. 84 is an exploded view of the dual pill feed apparatus shown in FIG. 83.

(85) FIG. 85 is a top plan view of an exemplary dual pill feeder disc.

(86) FIG. 86 is a cross-sectional view of the feeder disc shown in FIG. 85 taken along line 86-86.

(87) FIG. **87** is a top plan view of an alternative dual pill feeder disc.

(88) FIG. **88** is a cross-sectional view of the feeder disc shown in FIG. **87** taken along line **88-88**.

(89) FIG. **89** is a top view of a further alternative dual pill feeder disc.

(90) FIG. **90** is a cross-sectional view of the feeder disc shown in FIG. **89** taken along line **90-90**.

(91) FIG. **91** is a top transparent view of the exemplary dual pill feed apparatus showing the exemplary internal brushes and with arrows showing the paths along which pills move relative to the feeder disc.

(92) FIG. **92** is a front plan view of an exemplary brush used with the dual pill feed apparatus referred to for convenience herein as brush AA.

(93) FIG. **93** is a front plan view of an exemplary brush used in the dual pill feed apparatus referred to for convenience herein as brush BB.

(94) FIG. **94** is a front plan view of an exemplary brush used in the dual pill feed apparatus referred to for convenience herein as brush CC.

(95) FIG. **95** is a front plan view of an exemplary brush used in the dual pill feed apparatus referred to for convenience herein as brush DD.

(96) FIG. **96** is a front plan view of an exemplary brush used in the dual pill feed apparatus referred to for convenience herein as brush EE.

(97) FIG. **97** is a front plan view of an exemplary brush used in the dual pill feed apparatus referred to for convenience herein as brush FF.

(98) FIG. **98** is a front plan view of an exemplary brush used in the dual pill feed apparatus referred to for convenience herein as brush GG.

(99) FIG. **99** is a transparent top plan view of the exemplary dual pill feed apparatus.

(100) FIG. **100** is a cross-sectional view of the dual pill feed apparatus taken along lines **100-100** in FIG. **99**.

(101) FIG. **101** is a front view of brush AA and a mount portion thereof.

(102) FIG. **102** is a cross-sectional view taken along line **102-102** in FIG. **101**.

(103) FIG. **103** is a top transparent view of the dual pill feed apparatus showing a plurality of circular pills adjacent to brush AA.

(104) FIG. **104** is a top transparent view of the dual pill feed apparatus showing a plurality of pills in the form of capsules adjacent to brush AA.

(105) FIG. **105** is a top transparent view of the dual pill feed apparatus.

(106) FIG. **106** is a cross-sectional view of the dual pill feed apparatus taken along line **106-106** in FIG. **105**.

(107) FIG. **107** is a front view of brush BB and the mount portion thereof.

(108) FIG. **108** is a cross-sectional view taken along line **108-108** in FIG. **107**.

(109) FIG. **109** is a top transparent view of the exemplary dual pill feed apparatus and brush BB configured for engaging pills in the configuration of capsules.

(110) FIG. **110** is a top transparent view of the exemplary dual pill feed apparatus and brush BB configured for engaging circular pills.

(111) FIG. **111** is a top transparent view of the exemplary dual pill feed apparatus.

(112) FIG. **112** is a cross-sectional view taken along line **112-112** in FIG. **111**.

(113) FIG. **113** is a front view of brush CC including the mount portion thereof.

(114) FIG. **114** is a cross-sectional view taken along line **114-114** in FIG. **113**.

(115) FIG. **115** is a top transparent view of brush CC engaged with circular pills.

(116) FIG. **116** is a top transparent view of brush CC engaged with pills having the configuration of capsules.

(117) FIG. **117** is a top transparent view of the dual pill feed apparatus.

(118) FIG. **118** is a cross-sectional view taken along line **118-118** in FIG. **117**.

(119) FIG. **119** is a front view of brush DD including the mount portion thereof.

(120) FIG. **120** is a cross-sectional view taken along lines **120-120** in FIG. **119**.

(121) FIG. **121** is a top transparent view of the dual pill feed mechanism with circular pills in engagement with brush DD.

(122) FIG. **122** is a top transparent view of the dual pill feed mechanism with pills having the configuration of capsules in engagement with brush DD.

(123) FIG. **123** is a top transparent view of the exemplary dual pill feed apparatus.

(124) FIG. **124** is a cross-sectional view taken along line **124-124** in FIG. **123**.

(125) FIG. **125** is a front view of brush EE including the mount portion thereof.

(126) FIG. **126** is a cross-sectional view taken along line **126-126** in FIG. **125**.

(127) FIG. **127** is a top transparent view of the exemplary dual pill feed apparatus showing brush EE in engagement with circular pills.

(128) FIG. **128** is a top transparent view of the exemplary dual pill feed apparatus showing brush EE in engagement with pills that are configured as capsules.

(129) FIG. **129** is a top transparent view of the exemplary dual pill feed apparatus.

(130) FIG. **130** is a cross-sectional view taken along line **130-130** in FIG. **129**.

(131) FIG. **131** is a front view of brush FF including the mount portion thereof.

(132) FIG. **132** is a cross-sectional view taken along line **132-132** in FIG. **131**.

(133) FIG. **133** is a top transparent view of the exemplary dual pill feed apparatus with brush FF extending in overlying relation of a feeder disc configured for feeding circular pills.

(134) FIG. **134** is a top transparent view similar to FIG. **133** with brush FF extending in overlying relation of a feeder disc configured for feeding pills having a capsule configuration.

(135) FIG. **135** is a view similar to FIG. **133** showing brush FF in engagement with circular pills.

(136) FIG. **136** is a view similar to FIG. **134** showing brush FF in engagement with pills having the configuration of capsules.

(137) FIG. **137** is a top transparent view of the exemplary dual pill feed apparatus.

(138) FIG. **138** is a cross-sectional view taken along line **138-138** in FIG. **137**.

(139) FIG. **139** is a front view of brush GG including the mount portion thereof.

(140) FIG. **140** is a cross-sectional view taken along line **140-140** in FIG. **139**.

(141) FIG. **141** is a top transparent view showing brush GG in overlying relation of a feeder disc configured for feeding circular pills.

(142) FIG. **142** is a top transparent view showing brush GG in overlying relation of a feeder disc configured for feeding pills having the configuration of capsules.

(143) FIG. **143** is a top transparent view similar to FIG. **141** showing brush GG in engagement with circular pills.

(144) FIG. **144** is a view similar to FIG. **142** showing brush GG in engagement with pills having the configuration of capsules.

(145) FIG. **145** is a top transparent view of the exemplary dual pill feed apparatus.

(146) FIG. **146** is a cross-sectional view taken along line **146-146** in FIG. **145** and showing the inner diverter and the outer diverter in cross-section.

(147) FIG. **147** is a top view of the exemplary inner diverter.

(148) FIG. **148** is a side view of the exemplary inner diverter.

(149) FIG. **149** is a top view of the exemplary outer diverter.

(150) FIG. **150** is a side view of the exemplary outer diverter.

(151) FIG. **151** is a top transparent view of the inner and outer diverters in overlying relation of a dual feeder disc configured for feeding circular pills.

(152) FIG. **152** is a view similar to FIG. **151** showing the inner and outer diverters in overlying relation of a dual feeder disc configured for feeding pills in the configuration of capsules.

(153) FIG. **153** is a top transparent view showing the inner and outer diverters in engagement with circular pills.

(154) FIG. **154** is a top transparent view showing the inner and outer diverters in engagement with pills having the configuration of capsules.

DETAILED DESCRIPTION

(155) Referring now to the drawings and particularly to FIG. **1** there is shown therein an exemplary unit dose pill packaging machine **10** of a prior art configuration. The exemplary packaging machine **10** includes features described in the incorporated disclosure. The exemplary machine includes a body **12**. A pill supporting tray **14** is releasably connected to the body **12** by fasteners **16**. A rotatable pill disc **18** includes a plurality of apertures **20** therein. The apertures **20** are sized for each receiving a respective individual pill therein. All the apertures of the pill disc are configured for receiving the same size and configuration of pill.

(156) The body **12** of the exemplary machine **10** is configured to support a first roll **22** of packaging material thereon. The body of the machine is also configured to support a second roll **24** of packaging material. The exemplary materials of the rolls **22** and **24** are configured to be joined together to produce a strip **26** of unit dose packages **25** each of which houses a single pill. In exemplary arrangements the materials are joined by suitable adhesive materials and/or heat welding to encapsulate pills in the unit dose packages in air tight relation. Further in exemplary arrangements the strip may be perforated so that each unit dose package **25** can be readily separated from the others in the strip. The exemplary machine further includes a thermal transfer printhead or other suitable printing device that enables printing indicia on the unit dose packages.

(157) In the exemplary operation of the machine **10** a human operator places a plurality of pills in supported connection with the tray **14**. The operator then uses a suitable instrument to manipulate the pills such that each pill is engaged in one of the apertures **20**. Pills positioned in the apertures are separated on a top surface of a support plate **27**. The exemplary support plate has a plate upper surface **29**. The pill disc **18** rotates in an indexing manner such that each aperture is placed in overlying relation of a drop opening **28** as shown in FIG. **3**. When a respective aperture of the pill disc **18** rotates so as to be placed in aligned relation with the drop opening, the pill in the aperture falls into an area of a mechanism within the machine in which the pill is encapsulated between the strips of packaging material, sealed and integrated into a unit dose package **25** in the strip **26**.

(158) Packaging machines of the type shown will commonly operate to package about 60 pills per minute. As a result the human operator must be skilled in the manipulation of the pills in order to assure that the apertures are filled so that the unit dose packages are produced.

(159) As represented in FIG. **3** at least some exemplary prior art machines include removable pill discs which can be interchanged with pill discs with apertures that accommodate pills of other configurations. As a result some exemplary prior art machines can be reconfigured to produce single dose packages of pills of different types. Further in exemplary arrangements the tray **14** on which the pills are supported prior to being engaged in the apertures of the pill disc is also removable through disengagement of the fasteners **16** as shown in FIG. **5**. Of course it should be understood that this configuration is exemplary and in other arrangements other machine configurations, structures and operations may be utilized.

(160) The pill disc **18** and pill supporting tray **14** may be removed from an exemplary prior art machine and replaced with a pill feed apparatus **30** of an exemplary arrangement which is shown in FIG. **6**. The exemplary apparatus enables a plurality of pills to be automatically separated and individually delivered into the existing packaging mechanism of the packaging machine so that the pills are included in unit dose packages. The exemplary pill feed apparatus is engaged with the machine **10** through the existing releasable fasteners **16**. The exemplary apparatus facilitates the reliable delivery and packaging of pills having various configurations. The exemplary apparatus further reduces the effort required by the operator to successfully operate the packaging machine. Further the exemplary arrangement makes it easier to change the machine operation from one pill configuration to another while minimizing potential errors.

(161) As shown in FIG. **7** the exemplary pill feed apparatus includes a deck **32**. The deck **32** is engageable with the upper surface of the machine **10**. The exemplary deck **32** is positioned in place of the prior tray **14**. The exemplary deck **32** has in attached connection therewith a pill sizer **34**

which is later discussed in detail. The pill sizer is usable by an operator to determine the particular feeder disc to be used with a particular pill configuration. The deck further includes in operative connection therewith a plurality of disc holders **36**. The exemplary disc holders **36** include a plurality of aligned feeder disc accepting recesses **38**. A respective feeder disc among the plurality of discs **40** that are usable in the machine, may be stored in the respective recess as shown in FIG. **6**.

(162) The exemplary pill feed apparatus **30** further includes an annular base ring **42** which is alternatively referred to herein as a base. The exemplary base ring **42** includes a generally circular annular internal wall **44** as shown in FIG. **8**. When used herein generally circular means that the majority of the item referred to has a circular shape. The exemplary base ring **42** further includes a clean out opening **46** that extends radially through the annular wall **44**. The exemplary clean out opening **46** is sized to be closed by a removable access cover **48** during operation of the assembly. The side walls of the exemplary access cover and the walls bounding the clean out opening include interengaging projections and recesses. This exemplary releasable engaging mechanism enables the access cover to be held in the opening **46**, and readily removed by relative upward movement. An external pill holding pocket **50** extends externally on the base ring in radial outward alignment with the clean out opening **46**. The pill pocket **50** includes a bottom opening **52**. The bottom opening **52** enables pills that have been removed from the interior area of the base ring through the clean out opening **46**, to be directed downward through the opening and into a suitable container.

(163) The exemplary base ring **42** further includes a suitable bracket portion **54**. Bracket portion **54** is configured to engage with releasable fasteners **16** to enable the base ring to be releasably positioned in engagement with the body **12** of the machine. The exemplary base ring **42** further includes a mounting opening **56**. The mounting opening **56** is configured to receive a threaded thumbscrew **58** or other releasable fastener therein. The thumbscrew **58** is configured to engage a lower clamp **60**. The lower clamp **60** is configured to engage a projecting surface of the existing machine to hold the base ring in engagement with the body **12**. Of course it should be understood that this configuration of the base ring and the mounting thereof on the packaging machine is exemplary and in other arrangements other approaches may be used.

(164) The exemplary base ring further includes a pair of hinge posts **62**. The inward extending hinge posts are configured to engage respective **64** cars of an inserter **66**, which is alternatively referred to herein as a cover. The exemplary engaged hinge posts **62** and cars **64** comprise a hinge that enables the inserter **66** to be rotationally movably mounted in operative connection with the base ring. In the exemplary arrangement the inserter **66** is movable between a closed position in which the inserter operates to close and vertically bound the base interior area **43** within the base ring **42**, and an open position. In the open position the inserter is at least partially moved away from the base ring opening **45** of the base interior area **43** so that the base interior area is accessible from outside the base ring. This exemplary arrangement enables the interior area **43** of the base ring to be readily accessed for purposes of changing the configuration of the device to handle different pill sizes and for other purposes as later discussed.

(165) The exemplary pill feed apparatus **30** is configured to be driven by the drive mechanism of the existing packaging machine which was previously utilized to rotate and index the pill disc **18**. The exemplary assembly includes a drive pin **68**. As shown in greater detail in FIGS. **19-21** the exemplary drive pin **68** includes a lower U-shaped portion **70**. The U-shaped portion **70** includes a pair of radially disposed spaced apart legs **72**. The legs **72** bound a recess **74**. Recess **74** is configured to receive and engage therein a drive post **76** of the existing drive of the machine which is shown in phantom. The drive post **76** rotates in an indexing manner in coordination with the pill encapsulating mechanism within the machine.

(166) The exemplary drive pin **68** further includes and terminates upwardly at a head **78**. In the exemplary arrangement the head comprises a square portion in a top view that in the operative position extends above the U-shaped portion **70**. In the exemplary arrangement the head **78** is

configured to releasably be engaged in a corresponding square-shaped recess **80** on a lower side of a drive platter **82** as shown in FIG. **12** for example. The exemplary configuration provides for the drive pin **68** to be releasably engaged with the drive platter **82** without any significant rotational play or lash between the drive post **76** and the drive platter **82**. This helps to assure accurate positioning and coordinated rotational movement of the drive platter and the feeder discs as later discussed.

(167) Further in the exemplary arrangement the legs **72** of the U-shaped portion **70** of the drive pin **68** are configured to be frangible. As a result if the head **78** of the drive pin **68** encounters resistance to rotational movement above a force threshold, the legs **72** will deform and/or fracture (each of which condition is referred to therein as a break) in response to the force imparted by the drive post **76**. This reduces the risk of damaging the drive post or other mechanisms within the packaging machine. Further as can be appreciated in this exemplary arrangement, if the drive pin **68** is damaged due to encountering an excessive resistance force, the drive pin can be readily replaced with a new drive pin. Of course this approach is exemplary and in other arrangements other approaches may be used.

(168) As shown in FIGS. **12-18** the exemplary drive platter **82** includes a base portion **84** which is bounded by a circular outer surface **86**. The base portion **84** includes a lower face **88** in which the square-shaped recess **80** extends. The base portion **84** further includes an upper face **90** that is on an opposed side of the base portion from the lower face **88**. A central axially centered cylindrical projection **92** extends outward from the outer surface **86**.

(169) In the exemplary arrangement a plurality of equally angularly spaced upward extending projections **94** extend vertically from the upper face **90**. The exemplary projections **94** are radially disposed away from the cylindrical projection **92** and terminate outwardly at the outer surface **86**. In the exemplary arrangement each of the projections **94** includes in circumferential transverse cross-section, a tapered leading wall **96**. Each tapered leading wall **96** is tapered at an obtuse angle relative to the upper face **90**. The tapered leading wall **96** of a respective projection **94** terminates outwardly at an outer surface **98**. Each respective projection is further bounded in transverse cross-section by a trailing wall **100**. In the exemplary arrangement the trailing wall **100** extends in a plane parallel to a central axis **102** of rotation of the drive platter **82**. In the exemplary arrangement the tapered leading wall **96** of each projection **94** is on the leading side of the respective projection **94** as the drive platter **82** rotates during operation in a rotational direction as represented by Arrow R.

(170) As shown in FIGS. **12** and **17** each respective feeder disc used in the exemplary arrangement is configured to engage with the drive platter **82**. As represented by the exemplary feeder disc **104** shown in FIGS. **12** and **17**, the feeder disc includes a circular lower disc surface **106** with an axially centered disc recess **108** therein. Disc recess **108** includes a lower portion **110** which is configured to receive the base portion **84** of the drive platter therein. The lower portion **110** is bounded by a radially inward extending step face **112** which is configured to engage the upper face **90** of the drive platter. A plurality of angularly spaced upward extending projection engaging recesses **114** are positioned at the radially outer periphery of the step face **112**. The projection engaging recesses **114** are configured to each receive therein a respective projection **94** of the drive platter **82**. In the exemplary arrangement the engagement of each projection **94** of the drive platter **82** and a respective projection engaging recess **114** of the feeder disc **104** causes the feeder disc to rotate in engagement with the drive platter **82** and the drive pin **68** without relative rotational movement during normal operation. Of course this approach is exemplary and in other arrangements other approaches may be used.

(171) The exemplary disc recess **108** of the feeder disc **104** includes an upper portion **116**. The upper portion **116** is sized to receive the cylindrical projection **92** therein in centered relation. The exemplary upper portion **116** includes an upper opening **118** through which the central projection **92** extends. As shown in FIG. **12** the central projection **92** is engaged in close-fitting relation with the walls bounding the upper portion **116** and the upper opening **118**. This helps to assure that the

feeder disc and drive platter are each positioned in centered relation relative to the axis of rotation **102** when the feeder disc and the drive platter are in operative connection. This helps to assure that the feeder disc **104** and the pill engaging apertures **120** that extend therethrough, are enabled to be accurately moved and positioned by the drive mechanism including the drive post **76** in the machine. In other arrangements other configurations of interengaging projections and recesses may be used to maintain the feeder disc and drive platter in axially centered positions. For example in other arrangements the drive platter may include an axially centered recess that is configured to engage an axially centered projection on the feeder disc. Such interengaging projections and recesses may have numerous different configurations. The use of the interengaging projections and recesses helps to assure that the drive platter in the feeder disc are maintained in an axially centered arrangement even in circumstances where the feeder disc encounters resistance to rotational movement and the feeder disc and drive platter undergo relative rotational and vertical movement in a manner like that later described.

(172) Further as shown in FIG. **17** each of the exemplary projection engaging recesses **114** is bounded in circumferential transverse cross section by a tapered engaging wall **122**. The tapered engaging wall in the exemplary arrangement extends at substantially the same angle as the tapered leading wall **96** of each respective projection **94** of the drive platter **82**. As a result in the exemplary arrangement the tapered leading wall **96** of a projection **94** is in flush abutting engagement with a tapered engaging wall **122** as shown in FIG. **17**. Each projection engaging recess **114** is further bounded in transverse cross-section by an upper surface **124**. The upper surface **124** of the exemplary arrangement extends a distance away from the outer surface **98** of the projection **94**. Each projection engaging recess **114** is further bounded by a back wall **126**. The exemplary back wall **126** in the operative position is disposed slightly away from the trailing wall **100** of the engaged projection **94**. Of course it should be understood that this configuration is exemplary and in other arrangements other approaches and wall configurations may be used.

(173) The exemplary arrangement of the drive platter **82** and feeder discs such as feeder disc **104**, operate to provide a torque limiting clutch as the drive platter imparts rotational force to the feeder disc. This torque limiting clutch arrangement assures accurate movement of the feeder disc and reduces the risk of damage to the pill feed apparatus in the event of a jam or other malfunction which prevents or increases resistance to the rotation of the feeder disc **104**. As can be appreciated, during normal operation the tapered leading walls **96** of each of the projections **94** engage the tapered engaging walls **122** of the projection engaging recesses **114** so that the tapered leading walls **96** impart rotational force and move the feeder disc **104**. In the event that rotation of the feeder disc **104** is prevented or the disc encounters a higher resistance due to malfunction or a jam in the pills being moved by the apparatus, the tapered leading walls **96** of the projections **114** will move relative to the tapered engaging walls **122** of the recesses **114**, allowing rotational movement of the drive platter **82** relative to the feeder disc. Further as can be appreciated such relative motion will cause the feeder disc to move upwardly relative to the drive platter until the degree of relative rotational movement between the drive platter in the feeder disc reaches the point where the projections engage in the next successive recesses. When that occurs the feeder disc will move downward as the projections **94** engage in the recesses **114**. Such movement of the feeder disc may in some instances cause the condition that prevents rotation of the feeder disc to be cleared, and the feeder disc will thereafter rotate in synchronized relation with the drive platter. Alternatively, if the condition which prevented the movement of the feeder disc has persisted, the drive platter will again cause the projections to disengage from the current projection engaging recesses, and reengage in the next recesses. When the feeder disc and the drive platter undergo relative rotational and vertical movement the interengaging central projection **92** on the drive platter and recess **118** on the feeder disc assure that the drive platter and feeder disc maintain their respective axially centered positions. Thus the exemplary arrangement reduces the risk of damage to the assembly or the mechanism within the packaging machine. Of course these approaches are exemplary and in

other arrangements other torque limiting connections may be utilized.

(174) The exemplary pill feed apparatus **30** may be utilized to separate numerous different pill sizes and configurations. This is achieved in the exemplary arrangement by using respective feeder discs that correspond to the particular pill configurations. Of course as can be appreciated each of the feeder discs include certain common features that enable them to be utilized in the apparatus. Referring to FIGS. **22-24** feeder disc **104** is shown in greater detail. The feeder disc **104** includes the plurality of evenly angularly spaced pill engaging apertures **120** as previously discussed. Each of the pill engaging apertures extend vertically through the feeder disc and are arranged in an axially centered annular portion **128** of the feeder disc. The exemplary apertures extend in a generally planar annular portion **128** of the upper surface **130** of the feeder disc. For purposes hereof generally planar means that the area is mostly flat other than the areas that are occupied by the pill engaging apertures **120**. As shown in FIG. **22** the exemplary apertures are configured with an inwardly tapered upper portion **132** and a lower portion **134**. In the exemplary arrangement the lower portion is horizontally bounded by walls that extend vertically in a transverse cross-section. The lower portion **134** is configured to receive and hold a pill therein such that the central axis of a generally cylindrical pill is positioned so as to extend vertically in the lower portion. In the exemplary arrangement pills that are positioned within a respective pill engaging aperture are vertically supported by operative engagement with the plate upper surface **29** of the support plate **27**. The pill engaging apertures **120** are configured to hold the pill therein in a stable manner as the feeder disc **104** is rotated.

(175) In the exemplary arrangement the tapered upper portions **132** of the pill engaging apertures are configured such that any pills which vertically overlies pills that are already positioned within the lower portion **134** can be disengaged from the tapered upper portion through engagement with one or more brushes that are attached to the inserter in a manner like that later discussed. Further the exemplary tapered upper portions are configured so that in the event that a generally cylindrical pill is positioned in the aperture **120** but with its central axis positioned in other than in the vertical direction, one or more brushes attached to the inserter are operative to engage the pill and cause it to move to have its central axis extend vertically and the pill to move downward into the lower portion so it is positioned in the pill engaging aperture. For example FIG. **24** shows a pill **143** positioned in the lower portion **134**. In exemplary arrangements the contours of the tapered upper portions **132** are configured to avoid sharp edges or other similar features that may cause pills to be caught or crushed through the brushing action which causes individual pills to be positioned in each respective lower portion of the apertures. In exemplary arrangements in which the pills have a configuration of an elongated capsule or similar pill configuration, the pill engaging apertures of the feeder disc are configured so that pills are positioned in respective apertures with the elongated axis extending horizontally within the respective pill engaging aperture. When used herein a reference to a pill being positioned or being positionable in a pill engaging aperture refers to the pill occupying the respective aperture in a nested manner so that the outer surface of the pill extends continuously adjacent to the surface that bounds the pill engaging aperture and no other pill can extend within the respective aperture without the other pill being swept away from the respective aperture by the brushes during feeder disc rotation in a manner that is later discussed. Of course it should be understood that the described approaches are exemplary and in other arrangements other approaches may be used.

(176) In the exemplary configuration of feeder disc **104** the upper surface of the disc **130** radially inward from the apertures includes a conical radially tapered annular inner portion **136**. The annular inner portion is bounded upwardly by an annular inner portion surface **137** that tapers outward and downward with radial distance away from the central axis **102** toward the planar portion **128**. The exemplary upper surface of the feeder disc further includes a tapered annular outer portion **138**. The outer portion **138** is bounded upwardly by an annular outer portion surface **139** that in transverse cross-section is tapered downwardly with increasing radial proximity to the

apertures and the axis **102**, from an outer periphery **140** which is alternatively referred to as annular disc edge. The outer periphery is immediately adjacent to the circular annular internal wall **44** of the base ring **42** when the feeder disc is in the operative position. In the exemplary arrangement the annular disc edge **140** is disposed radially inward from the annular internal wall **44** of the base ring by no more than a radial distance that is less than the smallest dimension of each respective pill having the configuration that is to be positioned in the pill engaging apertures of the feeder disc being used. This exemplary approach helps to assure that no pills may extend between the annular disc edge and the annular internal wall and avoids pills being caught or damaged during operation of the apparatus. The exemplary annular outer tapered portion surface **139** extends downwardly tapered to the level of the planar portion **128** on an opposed side of the annular inner portion **136**. As is subsequently explained, the inward tapered conical surface and the outer tapered conical surface of the feeder disc facilitates the movement of the pills so they are positioned in the pill engaging apertures **120** during operation of the pill feed apparatus. Of course it should be understood that this configuration is exemplary and in other arrangements other approaches may be used.

(177) The exemplary feeder disc **104** further includes a central annular projection **142**. The annular projection which is alternatively referred to as an annular feeder disc projection, extends upwardly in the operative position of the feeder disc, from the radially innermost area of the inward conical portion **136**. The annular projection terminates upwardly at the top surface **144**. As later discussed the top surface **144** of the annular projection is configured to be positioned in close proximity to a lower surface of an annular skirt projection on the inserter during operation to maintain the pills in supported connection with the feeder disc in the base interior area radially outward of the annular projection. In the exemplary arrangement the feeder disc includes a ring surface **146**. The ring surface **146** extends radially outward from the upper opening **118** to the inside of the annular projection **142**. In the exemplary arrangement the ring surface **146** includes visible indicia **148**. The visible indicia **148** is usable to identify the particular disc and corresponds to the pill configuration that the feeder disc is made to handle and separate. As later discussed this makes it easier for the operator to install the feeder disc that corresponds to the configuration of a pill that the operator wishes the process. Of course this approach is exemplary and in other arrangements other approaches may be used.

(178) FIGS. **25-26** show an alternative feeder disc **150**. Feeder disc **150** is configured to separate a different pill configuration than feeder disc **104**. Feeder disc **150** separates cylindrical pills that have a larger diameter than pill **143** which is handled by feeder disc **104**. Feeder disc **150** includes a plurality of equally angularly spaced pill engaging apertures **152**. The apertures **152** extend in a generally planar portion **154** of an upper surface **156** of the feeder disc. Similar to the previously described feeder disc, disc **150** includes a conical annular inner portion **158** with a tapered inner portion surface that extends radially inward of the apertures and the planar portion **154**. An annular outer portion **160** extends radially outward of the apertures and the planar portion **154** and includes a tapered annular outer portion surface. The exemplary pill engaging apertures **152** each include a tapered upper portion **162** which is configured to facilitate aligning the pill within the aperture through engagement with the deformable brushes of the inserter. Each pill engaging aperture further includes a lower portion **164** which is configured to horizontally hold a cylindrical pill **166** with central axis thereof extending vertically in the aperture. The lower surface of pill **166** is in supported engagement with the plate upper surface **29**.

(179) The exemplary feeder disc **150** further includes an annular projection **168**. Annular projection **168** is similar to annular projection **142** previously discussed. The disc further includes a ring surface **170** which is similar to ring surface **146**. Indicia **172** which has a corresponding relationship to the particular disc and the pill configuration that the feeder disc is utilized to handle is included on the exemplary ring surface.

(180) FIGS. **27** and **28** show a further alternative feeder disc **174**. Feeder disc **174** is configured to

handle pills having an elongated capsule or caplet configuration. The exemplary feeder disc **174** includes a plurality of equally angularly spaced pill engaging apertures **176**. In this exemplary arrangement the pill engaging apertures **176** extend vertically through an axially centered annular portion of the disc which has an upper planar surface **178**. The exemplary pill engaging apertures are positioned such that the central axis of the capsule extends radially relative to the axis of rotation **102**. Each pill engaging aperture includes a tapered upper portion **180** to facilitate the pills engaging within the aperture, as well as a respective lower portion **182** for holding the pill **184** therein with the longitudinal axis of the pill extending horizontally in the aperture as the feeder disc rotates.

(181) The exemplary feeder disc **174** includes an upper surface **186** which includes an inward conical annular inner portion **188**. The upper surface **186** further includes an outer tapered annular outer portion **190**, which in this arrangement extends a relatively shorter distance radially inward from the outer periphery **192** of the feeder disc. Similar to the other described feeder discs, disc **174** includes an annular projection **194** that extends upwardly from the upper surface. A ring surface **196** extends radially inwardly from the annular projection to the opening which accepts the cylindrical projection **92** therein. The ring surface **196** includes indicia **198** which is usable to identify the particular feeder disc and corresponds to the pill configuration that the feeder disc is configured to handle.

(182) Of course it should be appreciated that in exemplary arrangements numerous additional feeder discs may be utilized that are configured for handling pills with the other pill configurations that may be processed using the pill feed apparatus.

(183) The exemplary inserter **66** which is alternatively referred to herein as a cover, is comprised of a generally circular plate that is configured to extend in overlying relation of the base ring **42**. The inserter is configured to close and upwardly bound the circular base ring opening **45** to the base interior area that is horizontally bounded by the circular wall **44** of the base ring when the inserter is in the operative position. The inserter **66** is movably mounted through engagement of the pivot posts **62** on the base ring in openings **200** in cars **64** of the inserter which serve as a hinge and enable the inserter to be movable between the closed, operative position in which the inserter extends generally horizontally and overlies the chamber horizontally bounded by the base ring **42**, and an open, access position in which the inserter extends generally vertically and the chamber bounded by the base ring is accessible through the base ring opening **45**. A handle projection **202** is positioned on the inserter diametrically opposite to the cars to facilitate inserter movement. As can be appreciated in the open position of the inserter the feeder disc that is currently within the base ring is manually accessible. This enables an operator to remove the feeder disc that is currently in place bounding the lower side of the base interior area, and to replace it with a different feeder disc. In the exemplary arrangement the changing of the feeder disc is all that is required for an operator to change between handling one pill configuration and another. No changes to the position of any of the plurality of brushes that are in fixed operative connection with the inserter as later described in detail, are required to be made to enable the apparatus to operate with any of the exemplary different feeder discs that are each respectively configured to handle a different pill configuration. Of course this approach is exemplary and in other arrangements other approaches may be used.

(184) The exemplary inserter includes a top opening **204** that extends therethrough. The top opening **204** is configured to receive and engage a lower end of a funnel **206** therein. Funnel **206** is configured to enable pills to be introduced into the base interior area that is vertically bounded upwardly by the inside face **208** of the inserter and downwardly the feeder disc, and horizontally by the circular annular internal wall **44** of the base ring. An axially centered annular skirt projection **210** extends downward from the inside face **208**. In the operative position of the inserter the skirt projection terminates downwardly in an inner annular surface **212**. In the operative position of the inserter the inner annular surface **212** of the skirt projection **210** is positioned in vertically close adjacent relation with the upward extending annular projection of the feeder disc that is installed

within the base interior area base ring. This is for example annular projection **142** of feeder disc **104**. In exemplary arrangements the skirt projection **210** along with the annular projection on the feeder disc helps to maintain pills being processed in the area radially outward of the annular projection and the skirt projection.

(185) The inner face **208** of the inserter further includes a plurality of brush engaging mounts thereon. The brush engaging mounts are configured to releasably engage respective deformable brushes that in the operative position of the inserter **66** extend vertically downward in the base interior area toward the feeder disc and which are configured to engage pills in a manner that cause one respective pill to be individually positioned in each pill engaging aperture of the respective feeder discs. In the exemplary arrangement mounts **214** and **216** are positioned on the inside face **208** and on angularly opposed sides of top opening **204**. A further mount **218** is positioned angularly disposed in the direction that the feeder disc rotates relative to the inserter from the mount **216**.

(186) A further mount **220** is positioned angularly disposed in the rotational direction that the feeder disc rotates from the mount **218**. Further angularly disposed in the direction that the feeder disc rotates is a further mount **222**. Mount **224** is positioned angularly in the direction of feeder disc rotation from the mount **222** followed by a further mount **226**. It should be noted that in this exemplary arrangement the mounts **214**, **216**, **220** and **208** extend generally radially outward from the skirt projection **210**. The mounts **218** and **222** extend outward from the skirt projection but do not extend directly radially. Rather mounts **218** and **222** extend at an acute angle relative to the directly radial direction. The mount **226** extends inwardly from an outer periphery **228** of the inserter and is disposed radially away from the skirt projection. The purpose of this configuration in the exemplary arrangement will be discussed in the following description of the operation of the exemplary inserter. The exemplary inserter further includes a diverter support post **230**. The diverter support post extends generally perpendicular to the inside face **208** of the inserter. The diverter support post **230** is configured to hold a diverter **232** in vertically movable engagement therewith.

(187) In the exemplary arrangement each of mount **214** and mount **216** are configured to have a respective deformable brush **234** in engagement therewith. Brush **234** which is shown in FIG. **37** is alternatively referred to as brush A herein. Exemplary brush **234** comprises a plurality of separated, adjacent strips which are comprised of a deformable but substantially rigid plastic material. Brush A includes a mounting portion **236** that is configured to releasably engage with each of mounts **214** and **216**. In the operative position of brush A and the other brushes discussed herein, the brush extends vertically downward from the inserter into the base interior area **238** in which the pills are processed which area/chamber is bounded by the inside face **208** of the inserter, the upper surface of the respective feeder disc, and the circular annular internal wall **44** of the base ring **42**.

(188) A brush **240** that is shown in FIG. **38** is configured to releasably engage mount **216**. Brush **240** is alternatively referred to herein as brush B. Similar to brush A, brush B is comprised of a plurality of adjacent generally rigid but flexible deformable plastic strips. A deformable brush **242** is shown in FIG. **39**. Brush **242** is configured to releasably engage mount **220**. Brush **242** is alternatively referred to herein as brush C. Releasably engageable with the mount **222** is a deformable brush **244** which is shown in FIG. **40**. Brush **244** is alternatively referred to herein as brush D.

(189) A further deformable brush **246** is releasably engaged with mount **224**. Brush **246** is alternatively referred to herein as brush E. Releasably engaged with mount **226** is a deformable brush **248**. Brush **248** is alternatively referred to as brush F. Each of the brushes A through F are attached to the mounts of the inserter via a mounting portion similar to the mounting portion **236** of brush A. Brush **248**, which is brush F, in the exemplary arrangement is not comprised of strips and is thus less readily deformable than some of the other brushes for reasons that will be subsequently discussed.

(190) FIG. 36 is a top transparent view through the inserter 66 into the base interior area/chamber 238. In this exemplary arrangement the feeder disc 104 is shown installed in operative connection with the drive platter within the chamber 238. In this exemplary arrangement brushes 234 (brush A) are installed on angularly opposed sides of the top opening 204 that extends through the inserter 66. Brush 240 (brush B) is installed in the chamber and angularly disposed from the brush A 234 that is positioned on the side of the opening in the direction of rotation of the feeder disc indicated by Arrow R.

(191) Further in the direction of feeder disc rotation from the brush 240 is the brush 242 (brush C). Brush D which is brush 244 is next positioned in the direction of feeder disc rotation. Brush 246 which is brush E is positioned further along the rotational direction, followed by brush 248 which is brush F. The diverter 232 which has an elongated pill guiding face 250 is positioned further in the direction of rotation. It should be noted in FIG. 36 that the diverter 250 includes an opening 252 which receives the diverter support post 230 therein. The exemplary diverter is enabled to move vertically in engaged relation with the support post 230 and is biased downwardly by gravity toward the upper surface of the feeder disc.

(192) As shown in FIGS. 43 and 44, a pair of brushes 234 (brush A) are positioned in the chamber 238 on opposed angular sides below the top opening 204 into which a plurality of pills in a batch to be processed are introduced into the chamber. As shown in FIG. 44 the brushes 234 include tapered inward surfaces 252 of the inward extending strips of which the brush is comprised. In the operative position the inward surfaces extend generally parallel to and are in close proximity to the inward conical portion 136 of the upper surface 130 of disc 104. The exemplary configuration of brush 234 provides an open area within the chamber 238 radially outward from the brush and above the pill engaging apertures 120 and the outer annular tapered portion 138.

(193) As shown in FIG. 47 during rotation of the disc 104 pills 254 are caused to move by engagement with the upper surface 130 of the disc 104 in the area designated A in FIG. 43. Upon engagement with the brush 234 the pills are urged to move radially outwardly by the inward conical portion 136. As a result the pills are repositioned in overlying relation of the planar surface 128 and the pill engaging apertures 120. This facilitates moving the pills in overlying relation of the pill engaging apertures so that at least one pill will be engaged with and positioned within the pill engaging apertures. Pills engaged in the pill engaging apertures are moved by the feeder disc in supported connection with the underlying plate upper surface 29 of the support plate 27. As can be appreciated the brush 234 which is positioned in advance of the top opening 204 is operated to move the pills 254 into the area radially outward from the brush 234, and the similar brush 234 after the top opening operates to move any additional pills that have been inserted into the chamber 238 through the funnel to a similar radially outward location.

(194) FIG. 48 shows the brush 234 in the operative position when utilized in connection with a feeder disc for pills having a capsule configuration such as feeder disc 174. The pills 256 shown in FIG. 48 are moved supported on the upper surface of the feeder disc radially outward into the area overlying the pill engaging apertures 176. Thus it can be appreciated that the brush A of the exemplary configuration performs the desired function of moving and positioning the pills within the chamber regardless of the pill configuration and the corresponding feeder disc which is utilized.

(195) Further it should be appreciated that in the event that for some reason the force that acts on the inward surfaces 252 of the brush 234 becomes greater than the force of the strips resisting deformation, the strips will deform enabling the pills or other object to move past the brush without causing any damage, after which the brush will return to its original undeformed condition. Of course it should be understood that this brush configuration is exemplary and in other arrangements other brush configurations and approaches may be used.

(196) FIG. 49 shows a further top transparent view of the exemplary pill feed apparatus and chamber 238. Brush 240 (brush B) which is engaged by pills that have been moved in operative engagement with feeder disc 104 past brush 234, extends downward from the inside face 208 of the

insert **66**. As shown in FIG. **50** the strips which comprise brush **240** include inward surfaces **258** which are disposed adjacent to the planar portion **128** and the annular tapered outer portion **138** of feeder disc **104**.

(197) As shown in FIG. **53** in area B shown in FIG. **49**, brush B operates to further cause the pills to move in a manner that facilitates filling the pill engaging apertures. Brush **240** operates to block pill movement and hold the pills **254** over the pill engaging apertures **120** as the disc rotates. This urges pills to engage and be positioned in the pill engaging apertures. The brush **240** further is positioned at an angle that urges the pills that are not engaged in a pill engaging apertures to move radially inward of the brush **240** onto the inward conical portion of the upper surface of the feeder disc to enable the pills to move past the brush **240**. Further as can be appreciated, the angle of the exemplary brush **240** facilitates holding back the movement of pills relative to the moving feeder disc so as to increase the chances for pill engagement in each of the pill engaging apertures.

(198) FIG. **54** shows the exemplary brush **240** operating in conjunction with pills **256** having a capsule configuration and in conjunction with feeder disc **174**. As shown in this Figure the brush **240** operates in a manner similar to that previously described in connection with pills **254**, to cause the pills **256** to be held from movement and backed up over the pill engaging apertures **176** to increase the chances for filling the apertures with pills. Further the pills **256** that are not engaged in a pill engaging aperture **176** are urged to move radially inward to rotationally move with the feeder disc past the brush **240**.

(199) FIG. **55** is a further transparent view showing area C within the chamber **238**. In area C the pills which have moved past brush **240** (brush B) engage with brush **242** (brush C). As shown in FIG. **56** exemplary brush **242** includes a pair of radially spaced strips. One of the strips has an inward surface **260** that is disposed in engagement with the planar portion **128** that includes the pill engaging apertures **120**. The radially inwardly disposed strip includes an inward surface **262** that is engaged with the inward conical portion **136** of the upper surface of the feeder disc **104**.

(200) As shown in FIG. **59** the inward surface **260** sweeps over the pill engaging apertures **120**. This sweeping action of brush C operates to remove any pills which are extending in vertically overlying relation of another pill that is already positioned within a pill engaging aperture **120**. The sweeping action of the inward surface **260** of the brush further causes pills which may be standing upright or without the central axis positioned vertically, to be moved so as to be in alignment with the pill engaging apertures so that the pill can move downward into the lower portion of the pill engaging aperture and be positioned within the aperture. Further as shown in FIG. **49** the inward surface **262** of the radially inward strip of brush **242** provides for spreading the pills that are not in a pill engaging aperture over the upper surface of the feeder disc **104**.

(201) FIG. **60** shows how brush **242** performs the same function when processing pills **256** in a capsule configuration that are moved into pill engaging apertures **176** of feeder disc **174**. In this exemplary arrangement the inward surface **260** of the brush performs the function of removing pills that are overlying a pill already positioned in an aperture and also helps to cause a pill that may be partially engaged in an aperture to move into alignment with and into the lower portion of the aperture and be positioned in the aperture. Inward surface **262** on the radially inward disposed strip operates to spread the remaining pills that are not positioned in an aperture over the surface of the disc.

(202) FIG. **61** is a further transparent view of the exemplary apparatus and the brush **244** (brush D) in an area labeled D within the chamber **238**. Pills carried on the upper surface of the feeder disc **104** are moved into engagement with brush **244** after being moved past brush **242**. As shown in FIG. **62** brush **244** has inward surfaces **264** of the inward extending strips that extend in close overlying relation of the planar portion **128** and the pill engaging apertures **120** of the feeder disc. The inward surfaces also extend in close proximity and in overlying relation of the outer annular tapered portion **138**.

(203) As shown in FIG. **65** the pills **254** when engaging brush **244** are temporarily held from

movement above the path of the moving pill engaging apertures **120**. The angle of the exemplary brush **244** (brush D) holds the pills by backing them up for a period of time as the feeder disc continues to move such that any open pill engaging apertures are filled with a respective pill. Further the exemplary brush **244** aggressively sweeps over the upper surface of the pill engaging apertures. This is done to remove any pills that may be overlying a pill already positioned in the lower portion of a pill engaging aperture. Further the aggressive sweeping action of brush **244** operates to move and reposition cylindrical pills that are engaged in the pill engaging aperture but that do not have the central axis thereof extending vertically. Further brush **244** urges the pills that are not engaged in the pill engaging apertures to move radially inwardly so they move rotationally past the brush **244**.

(204) FIG. **66** shows the operation of brush **244** in engagement with pills in the configuration of capsules **256**. The brush performs the function of aggressively sweeping over the pill engaging apertures **176** in the feeder disc **174**. Again the same brush D operates to aggressively sweep away any pills overlying a pill that is already within a pill engaging aperture and to reposition pills that may be engaged in the aperture but not properly positioned within the aperture, while remaining pills are moved radially inwardly to be carried past the brush **244**.

(205) FIG. **67** is a further top transparent view showing the chamber **238** and an area E thereof in which brush **246** acts upon the pills that are supported on the upper surface of the feeder disc **104**. Brush **246** (brush E) is shown in greater detail in FIG. **68**. The inward surfaces **266** of brush **246** are positioned in close proximity to the planar portion **128** which includes the pill engaging apertures **120** and also the outer annular tapered portion **138** of the feeder disc. The exemplary brush **246** further aggressively sweeps over the pill engaging apertures **120** to remove any pills overlying a pill that is already positioned by being nested in the lower portion of the aperture. The sweeping action of the inward surfaces **266** further reorients any pills that are engaged in the aperture but not properly positioned. As can be appreciated the inward surfaces **266** of brush **246** provide open space radially inward of the planar portion **128** which enable the passage of pills therethrough.

(206) In FIG. **71** the pills **254** are shown as being urged by the brush **246** to move radially inward to move past the brush. Further the inward surfaces of the brush **244** engage pills in the pill engaging apertures **120** to remove any overlying double pills and to reorient pills that may be not properly oriented and positioned within the respective apertures.

(207) FIG. **72** shows the operation of brush **244** in moving pills **256** in the capsule configuration into the apertures **176** of feeder disc **174**. As is the case with the pills **254**, brush E operates to remove pills overlying pills that are already properly positioned in a pill engaging aperture, as well as to reorient pills that are engaged but not properly oriented within the apertures. Further brush **244** operates to cause the pills that are not positioned in an aperture to move radially inward on the inward surface of the feeder disc **174** to move past the brush.

(208) FIG. **73** is a further top transparent view of the inserter showing the chamber **238**. FIG. **73** highlights an area designated F within the chamber in which brush **248** is positioned. As shown in FIG. **74** brush **248** (brush F) is angled inwardly from the outer periphery of the base interior area/chamber and has an inward surface **268** that is in close engagement with the corresponding upper surface of the feeder disc **104**. The exemplary brush **248** extends substantially across the radially outward portion of the feeder disc and in overlying relation of the pill engaging apertures **120**. Further the brush **248** of the exemplary arrangement is not comprised of inward extending strips but rather a continuous material which is more resistant to deflection and deformation than some of the inward surfaces of other brushes used in the exemplary arrangement.

(209) As shown in FIG. **77** the exemplary brush **248** operates to engage and guide pills **254** which are moving in engaged relation with the upper surface of the feeder disc, further radially inward from the radial position to which the pills are moved by the preceding brush **248**. The exemplary brush **248** (brush F) guides the pills further radially inward beyond the pill guiding face **250** of the

diverter **232**. Thus in this exemplary arrangement the brush **248** moves all the other pills that are not positioned in a pill engaging aperture radially inward such that the pills are disposed away from the pill engaging apertures. This helps to position the pills so that they are away from the apertures **120** when the apertures move to be in vertically overlying relation of the drop opening **28** in which the pills are delivered into the packaging encapsulation mechanism.

(210) FIG. **78** shows the similar operation of brush **248** in the processing of pills **256** which are in the configuration of capsules which are positioned in apertures **176** of feeder disc **174**. In this configuration the brush F operates in a similar fashion to move the pills further radially inward beyond the pill guiding face **250** of the diverter **232**. The brush F further helps to assure that no pills other than those that are positioned within the pill engaging apertures reach the area vertically above the drop opening **28**.

(211) FIG. **79** is a further transparent view of the chamber **238** in which the pills are separated and individually delivered to the exemplary pill encapsulating mechanism that places the pills in individual unit dose packages. FIG. **79** highlights an area designated DV in which the diverter **232** operates to hold the pills that are not positioned within a pill engaging aperture radially inward away from area of the drop opening **28**. The diverter **232** includes pill guiding face **250** which is disposed slightly radially outward from the innermost end of the pill guiding surface on brush **240** (brush F). Further the diverter **232** is movably mounted vertically in guided connection on the diverter support post **230** which extends downward from the inside face **208** of the inserter **66**. The exemplary pill guiding face **250** of the diverter extends angularly across the upper surface of the feeder disc **104** to an angular position in the rotational direction that is beyond the drop opening **28** in the machine. This helps to assure that only those pills that are positioned within a pill engaging aperture **120** will move individually downward into the drop opening to the encapsulation mechanism within the packaging machine.

(212) As shown in FIG. **80** the inward surface **270** of the pill guiding face **250** of the diverter **232** rides in abutting engagement with the inward conical portion **136** of the feeder disc **104**. This helps to maintain the pills radially inward from the pill engagement apertures. This is shown in FIG. **81** in which pills **254** are held radially inward away from apertures **120** as each aperture with a respective pill positioned therein moves vertically above the drop opening **28**. After the remaining pills **254** have moved in engagement with the upper surface of the feeder disc in the rotational direction of the feeder disc beyond the drop opening, the pills **254** are enabled to disengage from the pill guiding face **250** and again move radially outward. It is shown in FIG. **82** how the exemplary diverter **232** operates in a similar manner in connection with pills **256** that have a capsule configuration. The pill guiding face **250** operates to maintain all the pills **256** other than those that are engaged in the pill engaging apertures **176**, radially inwardly away from the pill engaging apertures as the apertures pass in overlying relation of the drop opening.

(213) It should be understood that the arrangement shown is exemplary and in some other arrangements the functions carried out by the diverter may alternatively be achieved through use of one or more deformable brushes that move the pills that are not positioned within a respective pill engaging aperture radially away from each aperture as it is in vertically overlying relation of the drop opening. Further it should be understood while the exemplary pill engaging surface of the diverter provides a generally straight surface along which pills may travel while in engaged relation with the tapered inner annular surface of the feeder disc, other arrangements may utilize other surface configurations to position pills away from the apertures in vertically overlying relation of the drop opening, and to subsequently enable pill movement radially toward the pill engaging apertures after apertures have moved past the drop opening.

(214) As can be appreciated those pills that were not delivered into the drop opening and are remaining in engagement with the upper surface of the feeder disc are carried therewith into engagement with the brush **234** that is spaced ahead of the top opening **204** in the inserter. These remaining pills are then moved to a radially outward position on the top surface of the feeder disc

and in overlying relation of the now empty pill engaging apertures **120**. This causes further pills to be engaged in the pill engaging apertures through repetition of the engagement of the pills with brushes A through F as the feeder disc rotates.

(215) As can be appreciated the exemplary apparatus is operative to cause a respective one pill to be positioned in each respective pill engaging aperture with each rotation of the feeder disc. In the exemplary operation of the apparatus each rotation begins when the respective pill engaging aperture is empty due to having passed in overlying relation of the drop opening which has caused the pill previously positioned in the aperture to fall into the drop opening. The rotation of the pill engaging aperture then continues as discussed, past each of the plurality of deformable brushes until a pill is positioned in the aperture. A respective pill may be positioned in the respective aperture at any point during the rotation after the respective aperture has moved past the diverter. The engagement of pills with the brushes operates to move pills so that they are positioned in the respective aperture, and once a pill has been positioned in the aperture, to move other pills away from the aperture as the rotation continues to the point where the respective aperture extends again in overlying relation of the drop opening and the rotation is completed. The exemplary configuration of the deformable brushes which move pills circumferentially and radially inward and outward relative to each respective pill engaging aperture during each single feeder disc rotation help to assure that a pill is always positioned within the respective aperture as the aperture moves into a position extending in overlying relation of the drop opening. In addition the pill engaging aperture configurations of the exemplary arrangement help to assure that pills fall into the drop opening from the apertures in an orientation that is suitable for integration into packages provided by the exemplary packaging machine.

(216) In exemplary arrangements the inserter is operative to reliably cause pills to be positioned in the pill engaging apertures for a wide variety of pill configurations without the need to change the position or configuration of any of the brushes. This facilitates the utilization of the pill feed apparatus because the only activity necessary to change from feeding one pill type to another is to change the corresponding feeder disc to the one corresponding to the configuration of pills to be processed. Further in the exemplary arrangement in the event of a problem which causes damage to one or more of the brushes, the mounting configuration of each brush to the inside face of the inserter enables the brushes to be readily replaced. This helps to reduce machine downtime. Of course it should be understood that the approaches described herein are exemplary and in other arrangements other approaches may be used.

(217) The utilization of the exemplary pill feed assembly is further facilitated through the use of the pill sizer **34** that is included therewith. In the exemplary pill sizer **34** is in fixed operative connection with the deck **32**. As shown in FIGS. **33-35** the exemplary pill sizer includes an upper face **272** that has a plurality of different openings therethrough. Each of the openings is sized to correspond to a particular pill configuration. Further each opening has associated indicia adjacent thereto which corresponds to the particular pill configuration, as well as the particular feeder disc that is utilized in processing the particular pill configuration. For example the opening **274** in upper face **272** corresponds to the feeder disc identified with the indicia "5". Similarly the opening **276** corresponds to a pill configuration that corresponds to the feeder disc labeled with the indicia "9".

(218) The exemplary pill sizer includes a ramp surface **278** that vertically underlies the upper face and the openings therein. The ramp surface **278** includes convergent guides **280** that extend to a central outlet opening **282**. As a result pills that have been passed through the openings fall downward onto the ramp surface **278** and are guided out of the pill sizer through the outlet opening **282**. This process is represented in FIG. **35** in which a pill **284** is passed through the opening **276** to determine the size thereof. The indicia adjacent to the smallest opening that a particular pill will pass through in an orientation that corresponds to a horizontal orientation is indicative of the particular feeder disc that can be used to satisfactorily process the particular pill configuration.

(219) In the use of the exemplary pill sizer the pill **284** is moved along a path **286** through the

opening **276** to determine the appropriate pill size and feeder disc. In the use of the pill sizer the operator can accurately determine the corresponding feeder disc by attempting to pass the pill through the smallest opening, and sequentially trying larger openings until one is found through which the pill can pass without incurring any deformation of the pill. Once the numerical indicia associated with the smallest opening through which the pill may pass has been identified, the user may select the appropriate feeder disc from the plurality of discs stored in the recesses which comprise the respective disc holders **36** on the deck **32** of the pill feed apparatus.

(220) Of course once the appropriate feeder disc has been determined the operator may install the disc by moving the inserter **66** to the upward position so that it is disposed away from the base ring **42**. The operator can then remove the currently installed feeder disc and replace it with the one that is appropriate for the particular pill configuration that is desired to be processed. Once the chosen feeder disc is installed within the base ring and engaged with the drive platter **82**, the inserter can be lowered into the operative position and the pills to be processed placed within the chamber. Of course it should be understood that to change the particular pills processed by the machine in some arrangements may require reprogramming of the labeling mechanism of the packing to mark the unit dose packages with the correct pill information as well as changing the packaging material which is utilized in connection with the packaging machine.

(221) A further useful aspect of the exemplary arrangement of the pill feed apparatus is that it is driven by the existing mechanism of a packaging machine. The exemplary arrangement does not include additional drive motors, sensors or other items which have to be connected and integrated into the circuitry of the packaging machine. Of course it should be understood that in other exemplary arrangements pill feed devices that employ the principles described herein may incorporate motors, sensors or other components which facilitate the operation of the pill feed apparatus.

(222) Further while the exemplary arrangement has been described as utilized in connection with an existing single dose packaging machine, other exemplary arrangements may be integrated into machines having other configurations and that integrate the components of the pill feeding apparatus therein. Additionally, exemplary arrangements of the apparatus may be comprised of environmentally friendly materials such as biodegradable plastics. Components of the exemplary arrangements may be comprised of such materials which can be safely disposed of after their useful life without harm to the environment.

(223) Alternative exemplary arrangements of a pill feed apparatus that utilizes the principles previously described may also be used in connection with packaging machines that package two pills of the same type simultaneously. Such an exemplary pill feed apparatus **288** is shown in FIGS. **83** and **84**. The exemplary apparatus includes features similar to previously described pill feed apparatus **30** except as otherwise mentioned.

(224) The exemplary pill feed apparatus includes a deck **290** which is similar to the previously discussed deck **32**. Deck **290** has in operative connection therewith disc holders **292** with recesses **294** extending therebetween. The disc holders **292** are configured to hold respective dual feeder discs **296** as later discussed. The exemplary deck **290** further has in connection therewith a pill sizer **298** which may be similar to pill sizer **34** previously discussed. Of course these components are exemplary and in other arrangements other components and arrangements may be used.

(225) The exemplary dual pill feed apparatus **288** also has associated therewith a drive pin **300**. The drive pin in this arrangement may be similar to previously described drive pin **68**. A drive platter **302** is engaged with the drive pin **300** in the operative position thereof. The drive pin and drive platter are rotatable about an axis **304**. The exemplary drive platter **302** includes a central cylindrical projection and torque limiting tapered projections similar to the previously described drive platter. Of course it should be understood that in other arrangements other features which accomplish comparable functions or that provide different features and functions may be used.

(226) The exemplary dual pill feed apparatus further includes a base ring **306**. Base ring of this

exemplary arrangement extends above the deck **290** and may be similar to base ring **42** of the previously described arrangement. Base ring **306** includes a clean out opening **308** that is closable by an access cover **310** similar to the previously described arrangement. The exemplary base ring further includes an external pill holding pocket **312** that functions similar to the pill holding pocket associated with base ring **42**. Base ring **306** also includes suitable mounting components for mounting the pill feed apparatus to the packaging machine. This may include a mechanism including a thumbscrew **314** and a lower clamp **316** that hold the base ring in position by the thumbscrew extending through a mounting opening **318**. Of course it should be understood that different types of mounting approaches for the pill feed apparatus may be used depending on the nature of the packaging machine.

(227) Base ring **306** further includes hinge posts **320** which are configured to engage cars **322** of an inserter **324** which is alternatively referred to herein as a cover. Similar to the previously described arrangement the inserter **324** is movably mounted in connection the base ring **306** so that the interior area bounded by the inner wall of the base ring is selectively accessible. Similar to the previously discussed inserter **66**, inserter **324** has in mounted relation to an inside surface thereof a plurality of deformable brushes which are operative to engage and position pills within the pill engaging apertures of dual pill feeder discs having various configurations. The exemplary inserter **324** further includes a top opening **326** therein. The top opening is configured to engage a pill receiving funnel **328**. Similar to the previously described inserter arrangement, the pill receiving funnel is configured to receive pills that are to be separated and delivered by the feed apparatus one at a time into respective drop openings in the packaging machine.

(228) In addition to the pill engaging brushes that are later described in detail herein, the exemplary inserter includes a pair of diverters **390** and **392**. Each of diverters **390** and **392** perform a similar function to diverter **232** previously discussed. Further each diverter is movably mounted vertically on a respective support post which is attached to the inserter. Diverters **390** and **392** are radially aligned with one another and are movable vertically in the operative position. Diverter **390** is disposed radially inward of diverter **392**. Each of the diverters is enabled to maintain contacting engagement with an upper surface of the underlying dual pill feeder disc when the inserter and the disc are in the operative positions.

(229) The exemplary dual pill feed apparatus is used in connection with different dual pill feeder discs such as for example dual pill feeder disc **330**. The exemplary feeder discs used with the dual pill feed apparatus **288** include features similar to the feeder discs previously described. However the dual pill feeder discs utilized in this exemplary arrangement include pill engaging apertures **332** that are arranged in a pair of axially centered concentric circular portions **334**, **336** on the feeder disc. In exemplary arrangements the pill engaging apertures **332** in each of the circular portions are aligned radially. This configuration is used in the exemplary arrangement because the exemplary packaging machine in which the dual pill feed apparatus **288** is utilized includes a plate upper surface **229** which includes a pair of radially aligned drop openings (**331**, **333**) into which pills positioned in the apertures **332** fall downward into the packaging mechanism. In some arrangements this may be similar to the drop openings and packaging mechanisms utilized in the previously described arrangement. However in the exemplary dual pill feed arrangement a pair of pills are enabled to each be individually delivered into the respective packaging mechanisms simultaneously as the dual pill feeder disc moves to a position in which each of a respective pair of apertures are each aligned in overlying relation with one respective drop opening. Of course it should be understood that this configuration is suitable for use with packaging machines that have drop opening configurations of this type, and in other packaging machine arrangements other types of feeder configurations utilizing the principles described herein may be used.

(230) The exemplary dual pill feeder disc **330** is shown in greater detail in FIGS. **85** and **86**. In this exemplary arrangement the pill engaging apertures **332** in the inner circular portion **334** extend through the disc and are positioned in a circular surface portion **338**. The pill engaging apertures

332 in the outer circular portion **336** extend through the disc and are positioned in a circular surface portion **340**. The exemplary circular surface portions **338**, **340** include tapered bounding surfaces which facilitate positioning of a single pill **342** of a designated configuration in each respective pill engaging aperture **332**.

(231) The exemplary dual pill feeder disc **330** includes an annular conical portion **344**. The annular conical portion **344** has an upper surface that is downwardly and outwardly tapered in radially transverse cross-section toward the inner apertures **332** and circular portion **338**. An intermediate inner annular tapered portion **346** is positioned radially outward from the circular surface portion **338**. Intermediate inner annular portion **346** in radially transverse cross-section is bounded by an upper surface that is tapered radially inwardly downward toward circular portion **338**. This facilitates the movement of pills **342** into respective pill engaging apertures **332** of the inner circular portion **334** in a manner like that later discussed.

(232) The exemplary dual pill feeder disc **330** further includes an intermediate outer annular portion **348**. Intermediate outer annular portion **348** in radially transverse cross-section is bounded upwardly by a surface that is tapered outwardly and downward toward the outer circular portion **336** and the outer pill engaging apertures **332** that extend therein. An outer annular tapered portion **350** is positioned radially outward of circular portion **340**. In radially transverse cross-section as shown in FIG. **86** outer annular tapered portion **350** is bounded upwardly by a surface that is tapered radially inwardly and downward toward the circular surface portion **340** and the pill engaging apertures **332** therein. This exemplary configuration facilitates the movement of pills **342** into respective pill engaging apertures **332** in the outer circular portion **336** in a manner like that later described.

(233) Of course it should be understood that in the exemplary arrangement as shown in FIGS. **85** and **86** the pill engaging apertures **332** are arranged in radially aligned relation in respective pairs such as pair **352** for example. This radially aligned pair configuration assures that each pill engaging aperture **232** in a respective pair is positioned over a respective drop opening of the packaging machine at the same time as the other aperture **332** of the pair. This assures that each of the two pills are delivered individually into the respective drop openings simultaneously during pill feeding operation of the exemplary arrangement. Of course it should be understood that other feeder disc configurations may be utilized with different packaging machine arrangements.

(234) FIGS. **87** and **88** show an alternative dual pill feeder disc **354**. Feeder disc **354** is similar to feeder disc **330** but is configured to hold and deliver pills **356** of a different configuration. Pills **356** are generally cylindrical and have a larger size than pills **342**. In this arrangement, dual pill feeder disc **354** has pill engaging apertures **358** positioned in an inner circular portion **360** comprising an inner circle of pill engaging apertures **358**, and an outer circular portion **362** comprising an outer circle of pill engaging apertures **358**.

(235) Dual pill feeder disc **354** includes an annular radially innermost conical portion **364**. Conical portion **364** in transverse radial cross-section as shown in FIG. **88** is bounded upward by a surface that is tapered so that in the operative position the surface thereof is tapered downward toward the pill engaging apertures **358** in the inner circular portion **360**. An intermediate inner annular portion **366** is positioned radially outwardly from inner circular portion **360**. In transverse cross-section intermediate inner annular portion **366** is bounded upwardly by a surface that is tapered downwardly radially inward toward the pill engaging apertures **358** in inner circular portion **360**.

(236) Dual pill feeder disc **354** further includes an intermediate outer annular portion **368**. In the operative position and in radially transverse cross-section as shown in FIG. **88**, the intermediate outer annular portion **368** is bounded upwardly by a surface that is tapered downwardly with increasing radial proximity to the outer circular portion **362**. An outer annular tapered portion **370** is positioned radially outwardly of the outer circular portion **362**. In radially transverse cross-section the outer annular tapered portion **370** is bounded upwardly by a surface that is tapered downwardly with increased radial proximity to the outer circular portion **362**. As later discussed,

this configuration facilitates the engagement of pills **356** in the pill engaging apertures **358** of feeder disc **354** to enable the reliable individual delivery of each pill into the packaging machine. (237) FIGS. **89** and **90** show a further exemplary dual pill feeder disc **372**. Dual pill feeder disc **372** is similar to feeder discs **330** and **354** but is configured for receiving pills **374** having a capsule configuration. In the exemplary arrangement feeder disc **372** includes radially elongated pill engaging apertures **376**. The pill engaging apertures **376** extend through the disc and are arranged in an inner circular portion **378** and in an outer circular portion **380**.

(238) In radially transverse cross-section and in the operative position as shown in FIG. **90**, the dual pill feeder disc **372** includes an annular inner conical portion **382**. As shown in FIG. **90** the annular inner conical portion **382** is bounded by an upper surface that is tapered downwardly with proximity to the inner circular portion **378** and the pill engaging apertures **376** therein. Feeder disc **372** further includes an intermediate inner annular portion **384**. Intermediate inner annular portion **384** is bounded by an upper surface that is tapered downwardly with radial proximity to the inner circular portion **378** and the pill engaging apertures **376** therein.

(239) Dual pill feeder disc **372** further includes an intermediate outer annular portion **386**. Intermediate outer annular portion **386** has an upper surface that is tapered downwardly with radial proximity to outer circular portion **380** and the pill engaging apertures **376** therein. Feeder disc **372** further includes an outer annular tapered portion **388**. Outer annular tapered portion **388** has an upper surface that is tapered downward with radial proximity to outer circular portion **380** and the pill engaging apertures **376** therein. As later discussed, this exemplary configuration of the dual pill feeder disc **372** facilitates positioning of pills **374** in the respective pill engaging apertures **376** to cause the pills to be individually delivered into the packaging mechanisms of the packaging machine. Of course this configuration is exemplary and in other arrangements other configurations may be used.

(240) Further it should be understood that the dual pill feeder discs **330**, **354** and **372** discussed are examples of numerous dual pill feeder discs which may be used to deliver one pill at a time in two separate locations into a packaging machine. As with the single pill feeder discs previously described, a different feeder disc configuration is used for each pill configuration. However as with the single pill feeder discs, the exemplary inserter, deformable brushes and other structures described herein are suitable for use with each feeding disc and pill configuration.

(241) FIG. **91** is a top transparent view of the exemplary dual pill feed apparatus **288**. FIG. **91** shows the brushes of the exemplary arrangement that are mounted to the inside surface of the inserter **324**. In this example the dual pill feeder disc **354** is shown installed in the operative position. In FIG. **91** the shaded area **394** corresponds to the top opening **326** in which pills are received into the interior of the base ring through the funnel **328**. The shaded area **396** corresponds to the areas in which the drop openings in a support plate for receiving pills in the packaging mechanisms are located.

(242) A plurality of deformable brushes are in removably mounted relation with the inside face of the inserter. These include brushes **398**. Brushes **398** which are shown in greater detail in FIG. **92** are disposed on each angular side of the shaded area **394** into which pills enter the interior area of the base ring. These brushes each extend generally radially in the interior area of the base ring. Brushes **398** are alternatively referred to herein as brushes AA for convenience.

(243) As pills operatively engaged with the upper surface of feeder disc **354** move in the base interior area of the base ring in the direction of Arrow R, the pills, which have moved past brush **398**, next encounter brush **400**. Brush **400** is shown in greater detail in FIG. **93**. The exemplary brush **400** is mounted to extend radially but also so that the radially outward portion is positioned to contact pills angularly in advance of the radially inner portion. Brush **400** is alternatively referred to as brush BB. As the pills move in the interior area in the direction of Arrow R past brush **400** the pills next encounter brush **402**. Brush **402** is shown in greater detail in FIG. **94** and is alternatively referred to herein as brush CC. As shown in FIG. **91** brush **402** extends generally

radially.

(244) A brush that is next encountered by the pills moving in supported connection with the feeder disc **354**, is brush **404**. Brush **404** is shown in greater detail in FIG. **95** and is alternatively referred to as brush DD. Brush **404** extends radially but similar to brush **400** has its radially outward portion angularly advanced toward the direction of rotation compared to the radially inner portion. Next encountered by pills moving in the interior area of the base ring is brush **406** which is shown in greater detail in FIG. **96**. Brush **406** extends radially and is alternatively referred to herein as brush EE.

(245) A brush **408** extends radially inward from the outer wall of the base ring. Brush **408** which is shown in greater detail in FIG. **97** is alternatively referred to as brush FF. Radially disposed outwardly from brush **408** is a brush **410**. Brush **410** which is alternatively referred to as brush GG extends radially inward away from the inner wall of the base ring. As can be appreciated from FIG. **91** the pill engaging surface of brush **410** directs pills to a guiding surface **414** on the outer diverter **392**. The pill engaging surface on brush **408** guides pills to a guiding surface **412** on the inner diverter **390**.

(246) In this exemplary arrangement after pills move past the diverters **390** and **392** they engage the brush AA which is positioned in advance of the shaded area **394** in which additional pills are received. As with the prior exemplary arrangement this brush AA distributes the pills in the desired manner in advance of the pill receiving area. As shown in FIG. **91** the Arrows P are indicative of the paths along which pills are urged to move through engagement with each of the respective brushes. As shown the brushes are operative to cause the pills to move radially inward and outward relative to each of the pill engaging apertures and in overlying relation thereof. This movement causes one respective pill to be positioned in each respective pill engaging aperture. Further the exemplary arrangement of deformable brushes operates so that when one respective pill is engaged within a pill engaging aperture, the pill is moved by engagement with at least one respective brush so that it is positioned properly within the aperture. Further once a pill is properly positioned within a respective pill engaging aperture, other pills that may vertically overlie the pill positioned in the aperture are moved away from the pill engaging aperture to facilitate the pill in the respective aperture being delivered individually as it falls downward from the respective aperture when the aperture moves into overlying relation with the drop opening.

(247) Further in this exemplary arrangement similar to the previously described brush arrangements, brushes AA through GG may be comprised of one or more deformable resilient plastic strips. Such plastic strips may be separated by spaces to facilitate flexibility. Such brushes also may include the absence of spaces and/or the inclusion of flanged edges to provide enhanced rigidity.

(248) FIG. **99** shows a top transparent view of the dual pill feed apparatus **288** including the pair of identical brushes **398** which are positioned on each angular side of the base interior area into which pills are introduced to the interior area of the base ring **306**. Each brush **398** is releasably attached to the inserter through a mounting portion **416**. Brush **398** is further comprised of resilient strips with contact portions at the lower ends thereof. As shown in FIG. **100** the contact portions are in close adjacent relation with the annular inner conical portion **364** of the feeding disc **354** as well as intermediate inner annular portion **366** and intermediate outer annular portion **368** of the feeding disc.

(249) As shown in FIG. **103** the exemplary brush **398** operates to engage pills **356** and direct the pills moved by the feeder disc to be in overlying relation of the inner circular portion **360** and the outer circular portion **362** in which the pill engaging apertures **358** are located. Directing the pills into such areas helps to cause pills to be located in such areas and adjacent to the pill engaging apertures. The movement of the pills is a first step towards helping to assure that each pill engaging aperture eventually has a pill positioned in nested relation therein. FIG. **104** further shows the action of brush **398** in connection with alternative dual pill feeder disc **372**. Again in this case brush

398 urges the pills **374** to be positioned in overlying relation of the inner circular portion **378** and the outer circular portion **380** in which the pill engaging apertures **376** are located. This helps to position the pills so that they will be engaged in respective apertures. Of course it should be understood that these approaches are exemplary and other arrangements other approaches may be used.

(250) FIG. **105** is a top transparent view again showing the pill feed apparatus **288** and the next brush which is encountered by the pills after passing from the area in which pills are added and brush AA, which is brush **400** (brush BB). As shown in FIG. **107** brush **400** includes a mounting portion **420** which enables releasably operatively engaging the brush with the inside face of the inserter. Brush **400** also includes strips which include contact portions **422**. As shown in FIG. **106** the contact portions **422** are disposed somewhat above the pill accepting apertures in the inner circular portion **360** and the outer circular portion **362** of the feeder disc **354**. In the exemplary arrangement the contact surfaces **422** are operative to engage pills that may be partially within a pill engaging aperture **358** and urges the pill to move to be in positioned aligned nested relation within the aperture. The contact surfaces are further operative in the exemplary arrangement to move other pills that may be adjacent to a pill that is already positioned within a pill engaging aperture away from the pill that is already positioned within the aperture.

(251) As shown in FIG. **110** brush **400** operates to cause the pills **356** that are engaged in pill engaging apertures **358** to be moved so as to be fully downward and positioned in nested relation in the apertures. The contact portions **422** also operate to cause the pills that are not positioned in the apertures to move angularly inward which serves to fill any pill engaging apertures that do not have a pill **356** engaged therein. The contact surfaces further cause the excess pills to be moved in engagement with the pill feeder disc **354** so that the pills move past brush **400**. FIG. **109** shows the similar action that is carried out by brush **400** in connection with pill feeder disc **372** and the pills **374** having a capsule configuration.

(252) FIGS. **111** through **116** show the operation of brush **402** (brush CC). As shown in FIG. **112** the exemplary brush **402** includes contact portions **424** which are disposed slightly away from the inner circular portion **360** and the outer circular portion **362** of the feeder disc. The contact portions **424** also engage the area of the disc surface in which the intermediate inner and outer portions **366**, **368** are immediately adjacent. Brush **402** is operatively engaged with the inserter via a mounting portion **426**. Similar to the other brushes, brush **402** is releasably engageable with the inserter **324**.

(253) As represented in FIG. **115** brush **402** further operates to circumferentially sweep the inner circular area **360** and the outer circular area **362**. The contact portions **424** operate to help to position a respective pill in a pill engaging aperture **358** while moving other overlying pills away from the pill engaging apertures. Brush **402** further operates to move excess pills onto the intermediate inner annular portion **366** and intermediate outer annular portion **368**. FIG. **116** further shows the operation of brush **402** in connection with pill feeder disc **372** and the movement of pills that have a capsule configuration when engaged with the contact portions **426** of the brush.

(254) After moving past brush CC the pills next engage brush **404** (brush DD). As represented in FIG. **118** brush **404** includes contact portions **428** that are closely adjacent to the inner circular portion **360** and the outer circular portion **362**. Brush **404** further is angled relative to the radial direction so as to transversely move excess pills that are not positioned within a pill engaging aperture **358** in a radially inward direction.

(255) Brush **404** includes a mount portion **430** which enables releasably engaging brush **404** with the inserter **324**. As represented in FIG. **121** pills **356** that are engaged with the contact portions of brush **404**, are urged to nest and be positioned within the pill engaging apertures **358** while pills that are not positioned within the apertures are moved transversely away from the apertures. This further helps to assure that each pill engaging aperture includes a single pill that is positioned properly by being fully nested therein, and that additional pills are not engaged with the respective aperture. FIG. **122** shows the similar action of brush **404** in operative connection with feeding disc

372. As represented in this Figure the contact portions of brush 404 cause similar movements of pills 374 to assure the presence of a single pill in each pill engaging aperture 378 while minimizing the risk of other pills that are not properly positioned being engaged in a respective aperture.

(256) FIG. 123 is a top transparent view showing brush 406 (brush EE) in overlying relation of dual pill feeder disc 354. Brush 406 is encountered by pills that have moved past brush 404. Brush 406 is in removable connection with inserter 324 through a mount portion 432. As shown in FIG. 124, brush 406 includes contact portions 434 that extend in close adjacent relation with the inner circular portion 360 and the outer circular portion 362.

(257) As shown in FIG. 127 brush 406 operates to circumferentially sweep the pills 356 that are positioned in nested relation in the pill engaging apertures 358 to assure that the pills are aligned and properly positioned within the apertures. The contact portions further help to assure that other pills that may be partially engaged with the apertures are moved away from the apertures and directed radially away therefrom. FIG. 128 further shows how brush 406 in operative engagement with pill feeder 372 performs a similar function with regard to pills 374 and apertures 376.

(258) FIG. 129 is a top transparent view showing brush 408 (brush FF). As shown in FIG. 130 brush 408 extends radially outward away from the center of the feeder disc. Brush 408 includes a mount portion 436 through which the brush is releasably engaged with the inserter 324. Brush 408 includes an elongated angled contact portion 438. Contact portion 138 extends in close adjacent relation with the annular inner conical portion 364 of disc 354.

(259) As shown in FIG. 129 and in FIGS. 133 and 134, the pill engaging surface 440 of brush 408 is operative to urge the pills in engagement therewith to move radially outwardly beyond the guiding surface 412 of the inner diverter 390. Thus as shown in FIG. 135 the pills 356 which are not positioned in the pill engaging apertures 358 of the inner circular portion 360, move radially outwardly away from the pill engaging apertures. The excess pills are guided away from the pill engaging apertures by the guiding surface 412 of the inner diverter 390 while pills that are positioned in the pill engaging apertures reach a position in which they are in overlying relation of the inner drop opening and fall downward through the opening and into the packaging mechanism. FIG. 136 shows how the brush 408 performs a similar function with pills configured as capsules in connection with feeder disc 372. Thus this configuration helps to assure that pills engaged in the pill engaging apertures of the inner circular portion 360 are reliably individually delivered one at a time into the drop opening.

(260) FIG. 137 is a top transparent view of the exemplary dual pill feed apparatus including the exemplary brush 410 (brush GG). Similar to the other brushes, brush 410 includes a mount portion 442 that is releasably engaged with the inserter 324. The exemplary brush 410 includes an elongated continuous contact portion 444. Contact portion 444 extends radially inward from the wall bounding the base ring and across the pill engaging apertures 358 in the outer circular portion 362.

(261) Brush 410 includes a pill engaging surface 446 that operates to urge the pills that are not positioned within a pill engaging aperture 358 to move radially inward on the feeder disc 354. The excess pills are moved radially inwardly such that they are moved into engagement with the guiding surface 414 of the outer diverter 392. This configuration helps to assure that the excess pills are moved away from the pills that are positioned in the pill engaging apertures, so that the pills in the apertures are reliably delivered individually into the respective outer drop opening that corresponds to the outer circular portion 362. This operational capability of brush 410 is shown with regard to circular pills in FIG. 143 and with regard to pills having the configuration of capsules in FIG. 144.

(262) FIG. 145 is a top transparent view showing the exemplary inner diverter 390 and the exemplary outer diverter 392. As shown in FIG. 146 the inner diverter 390 is movably mounted in operative connection with the inserter 324. Diverter 390 is movably mounted in guided relation with an inner diverter post 446. Outer diverter 392 is also vertically movable in operative

connection with the inserter **324**. Outer diverter **392** is movable in guided relation with an outer diverter post **448**.

(263) Inner diverter **390** includes an inward surface **450**. The inward surface **450** is configured to engage the upper surface of the feeder disc **354** adjacent to the inner circular portion **360**. Similarly the outer diverter includes an inward surface **452** that is configured to engage the upper surface of the feeder disc adjacent to the outer circular portion **362**. In the exemplary arrangement each of the inner diverter **390** and the outer diverter **392** are biased by gravity into engagement with the surface of the feeder disc. This helps to assure that pills that are not positioned in pill engaging apertures are moved to a position radially between guiding surface **412** of the inner diverter **390** and guiding surface **414** of the outer diverter **392**.

(264) The movement of cylindrical pills **356** moved in engagement with feeder disc **354** past the inner diverter **390** and the outer diverter **392** is represented in FIG. **153**. As shown, all the pills that are not positioned in the pill engaging apertures **358** are moved radially away from the apertures. This assures that pills are reliably individually delivered from the apertures into the drop openings in area **396**. FIG. **154** shows how diverter **390** and **392** operate in a similar manner in connection with feeder disc **372** and with pills **374** which have a capsule configuration. As a result only the pills **374** that are positioned in the pill engaging apertures **376** can reach the drop openings in area **396**. All of the excess pills move past the diverters and are then engaged by brush **398** that is encountered by the pills before reaching the area **394** in which additional pills may be added into the interior area of the base ring.

(265) It should be understood that the arrangements of inserters, the deformable brushes, the diverters, the feeder discs and other structures that have been described herein are exemplary. In other arrangements other types and configurations of pill directing, containing, holding, releasing and packaging structures may be utilized.

(266) Thus similar to the previously described exemplary arrangement in which single pills are delivered into a packaging mechanism of a packaging machine, the principles described herein may be utilized to deliver multiple pills concurrently into packaging mechanisms. Further the exemplary arrangements enable the use of the dual pill feed apparatus with many different sizes and configurations of pills. This is accomplished by changing the feeder disc to correspond with the appropriate pill type in a manner like that previously discussed.

(267) Thus the exemplary arrangements described herein achieve improved operation, eliminate difficulties encountered in the use of prior devices and systems, and attain the useful results described herein.

(268) In the foregoing description, certain terms have been used for brevity, clarity and understanding. However no unnecessary limitations are to be implied therefrom because such terms are used for descriptive purposes and are intended to be broadly construed. Moreover the descriptions and illustrations herein are by way of examples and the new and useful features are not limited to the exact features that have been shown and described.

(269) Further it should be understood that features and relationships associated with one described arrangement can be combined with the features and relationships of another arrangement. That is, various features and/or relationships from the various arrangements that have been described can be combined to produce further arrangements, and the new and useful scope of the disclosure is not limited only to the arrangements that have been shown and described herein.

(270) Having described features, discoveries and principles of the exemplary arrangements, the manner in which they are constructed and operated, and the advantages and useful results attained, the new and useful features, devices, elements, arrangements, parts, combinations, systems, equipment, operations, methods, processes and relationships are set forth in the appended claims.

Claims

1. Apparatus comprising: a base ring, wherein the base ring includes a generally circular annular internal wall, wherein the annular internal wall extends in centered relation about an axis, and bounds a base interior area, a base ring opening through which the base interior area is accessible from above the base ring, a feeder disc, wherein the feeder disc is rotatable about the axis within the base interior area below the base ring opening, includes a plurality of pill engaging apertures, wherein each pill engaging aperture extends vertically through the feeder disc in an axially centered annular portion, is angularly spaced from each other pill engaging aperture, and is configured to have only one respective pill positioned within the respective pill engaging aperture, wherein during rotation of the feeder disc each one respective pill within a respective pill engaging aperture is moved while being vertically supported within the respective pill engaging aperture by operative engagement with a plate upper surface of a support plate that extends below the feeder disc, wherein the plate upper surface includes a drop opening, wherein the drop opening is configured to enable one respective pill in a respective pill engaging aperture to drop individually into the drop opening when the respective pill engaging aperture is in overlying relation with the drop opening during rotation of the feeder disc, a cover, wherein the cover includes a top opening that is configured to enable pills to pass through the cover to the base interior area, and except for the top opening is configured to fully close the base ring opening, a plurality of deformable brushes, wherein each of the brushes is in fixed operative supported connection with the cover, extends vertically downward in the base interior area, is configured to engage pills in the base interior area, wherein rotation of the feeder disc is operative to cause a plurality of pills within the base interior area to be moved by operative engagement with the feeder disc and the plurality of brushes so that one respective pill is caused to be positioned in each respective pill engaging aperture as the feeder disc rotates, and the one respective pill in the respective pill engaging aperture to drop individually into the drop opening when the respective pill engaging aperture is positioned in overlying relation with the drop opening.

2. The apparatus according to claim 1, and further comprising: a packaging machine, wherein the packaging machine is in operative connection with the drop opening, wherein the packaging machine is operative to cause each pill that individually drops into the drop opening to be included in a unit dose package.

3. The apparatus according to claim 1 wherein the feeder disc is removably positionable in the base interior area, is removable from and positionable in the base ring interior area through the base ring opening, and further comprising: a plurality of further feeder discs, wherein each further feeder disc is removably positionable in the base interior area, is removable from and positionable in the base interior area through the base ring opening, when positioned in the base interior area is rotatable about the axis below the base ring opening, includes a plurality of further pill engaging apertures, wherein each further pill engaging aperture extends vertically through the respective further feeder disc in a further axially centered annular portion, is angularly spaced from each other further pill engaging aperture in the respective further axially centered annular portion, is configured to have only one respective further pill within the respective further pill engaging aperture, wherein each of the respective further pills that is positionable in each further pill engaging aperture is of a different configuration than the pills, and of a different configuration than each of the respective further pills that are positionable in the respective pill engaging apertures of each respective further feeder disc, wherein without changing a position of any of the plurality of brushes that are each in fixed operative connection with an inside face of the cover, from when respective pills are moved into respective pill engaging apertures through rotation of the feeder disc, rotation of each respective further feeder disc is operative to cause a plurality of respective further pills that are positionable in the pill engaging apertures of the respective further feeder disc to be moved in engagement with the further feeder disc and the plurality of brushes so that one respective further pill is positioned in each respective further pill engaging aperture, and the one respective further pill in the respective

further pill engaging aperture to be moved with the further feeder disc and to drop individually into the drop opening when the respective further pill engaging aperture is in overlying relation of the drop opening.

4. The apparatus according to claim 1 wherein the cover is movably mounted in operative connection with the base ring through a hinge, wherein the cover is movable to alternatively selectively open and bound the base ring opening and to correspondingly cause the plurality of brushes to be selectively positioned either outside or within the base interior area.

5. The apparatus according to claim 1 wherein the feeder disc further includes a tapered annular inner portion, wherein the tapered annular inner portion is axially centered, extends continuously for 360° on the feeder disc, is positioned radially inward of the pill engaging apertures, and is upwardly bounded by an annular inner portion surface that is tapered toward the pill engaging apertures.

6. The apparatus according to claim 1 wherein the feeder disc further includes a tapered annular outer portion, wherein the tapered annular outer portion is axially centered, extends continuously for 360° on the feeder disc, is positioned radially outward of the pill engaging apertures, and is upwardly bounded by a tapered annular outer portion surface that is tapered toward the pill engaging apertures.

7. The apparatus according to claim 1 wherein the feeder disc further includes a tapered annular inner portion, wherein the tapered annular inner portion is axially centered, extends continuously for 360° on the feeder disc, is positioned radially inward of the pill engaging apertures, and is upwardly bounded by an annular inner portion surface that is tapered toward the pill engaging apertures, a tapered annular outer portion, wherein the tapered annular outer portion is axially centered, extends continuously for 360° on the feeder disc, is positioned radially outward of the pill engaging apertures, and is upwardly bounded by a tapered annular outer portion surface that is tapered toward the pill engaging apertures.

8. The apparatus according to claim 1 wherein the feeder disc includes an axially centered upward extending annular feeder disc projection, wherein the annular feeder disc projection is configured to contain pills in the base interior area radially between the annular feeder disc projection and the annular internal wall.

9. The apparatus according to claim 1 wherein the cover includes an axially centered downward extending annular skirt projection, wherein the annular skirt projection extends 360° and is configured to contain pills in the base interior area radially between the annular skirt projection and the annular internal wall.

10. The apparatus according to claim 1 wherein the feeder disc includes an axially centered upward extending annular feeder disc projection, wherein the cover includes a downward extending annular skirt projection that extends 360°, wherein the annular skirt projection and the annular feeder disc projection are configured to contain pills in the base interior area radially between each of the annular feeder disc projection and the annular skirt projection, and the annular internal wall.

11. The apparatus according to claim 1 wherein the cover is movably mounted on the base ring, wherein the cover is movable between an open cover position and a closed cover position, wherein in the closed cover position the cover closes the base ring opening except for the top opening, and in the open cover position the cover is disposed away from the base ring opening, and further comprising: a diverter, wherein the diverter is in operative supported connection with the cover, is configured only in the closed cover position to cause pills other than a respective pill positioned in a respective pill engaging aperture and in overlying relation of the drop opening, to be positioned on the feeder disc away from the respective pill engaging aperture.

12. The apparatus according to claim 1 wherein the cover is movably mounted on the base ring, wherein the cover is movable between an open cover position and a closed cover position, wherein in the closed cover position the cover closes the base ring opening except for the top opening, and in the open cover position the cover is disposed away from the base ring opening, and further

comprising: a diverter, wherein the diverter includes a pill guiding face, is movably mounted in operative supported connection with the cover, wherein only in the closed cover position the pill guiding face is vertically movable in engaged relation with the feeder disc, wherein only in the closed cover position the pill guiding face is configured to engage and cause pills other than a respective pill positioned in a respective pill engaging aperture and in overlying relation of the drop opening to be positioned on the feeder disc away from the respective pill engaging aperture.

13. The apparatus according to claim 1 wherein the feeder disc is rotatable in a rotational direction within the base interior area, wherein the top opening in the cover is disposed in the rotational direction away from the drop opening.

14. The apparatus according to claim 1 and further comprising: a rotational drive platter, wherein the rotational drive platter, is rotatable in a rotational direction about the axis, extends below and in engaged contacting relation with a lower face of the feeder disc, and rotates to cause rotation of the feeder disc and is rotationally movable relative to the feeder disc responsive to the feeder disc encountering resistance to rotation in the rotational direction.

15. The apparatus according to claim 1 wherein the feeder disc includes one of an axially centered interengaging projection or recess, and further comprising: a rotational drive platter, wherein the rotational drive platter, is rotatable about the axis, includes the other of the axially centered interengaging projection or recess, extends below and in engaged contacting relation with a lower face of the feeder disc, and rotates in a rotational direction to cause rotation of the feeder disc and is rotationally movable relative to the feeder disc responsive to the feeder disc encountering resistance to rotation in the rotational direction, wherein while the drive platter and feeder disc relatively rotationally move the interengaging projection and recess cause each of the feeder disc and the drive platter to each remain axially centered.

16. The apparatus according to claim 1 and further comprising: a rotational drive platter, wherein the rotational drive platter, is rotatable about the axis, includes a plurality of either projections or recesses, wherein the projections or recesses extend vertically and are radially disposed away from and uniformly angularly spaced about the axis, wherein each projection or recess is configured to releasably engage a respective recess or projection that extends vertically on a lower face of the feeder disc wherein drive platter rotation is operative to cause rotation of the feeder disc in a rotational direction, wherein during drive platter rotation the feeder disc is relatively movable rotationally and vertically relative to the drive platter responsive to the feeder disc encountering resistance to rotation in the rotational direction.

17. The apparatus according to claim 1 and further comprising: a frangible drive pin, wherein the frangible drive pin is configured to operatively rotatably connect the feeder disc and a drive, wherein the drive pin is configured to break responsive to the feeder disc encountering resistance to rotation.

18. The apparatus according to claim 1 and further comprising: a rotational drive platter, wherein the rotational drive platter, is rotatable about the axis, extends below and in engaged contacting relation with a lower face of the feeder disc, and rotates to cause rotation of the feeder disc in a rotational direction and is rotationally movable relative to the feeder disc responsive to the feeder disc encountering resistance to rotation in the rotational direction, a frangible drive pin, wherein the frangible drive pin includes a head, wherein the head is releasably engageable with the drive platter, is configured to operatively rotationally connect a drive and the drive platter, wherein the drive pin is configured to break responsive to the drive platter encountering resistance to rotation.

19. The apparatus according to claim 1 and further comprising: a rotational drive platter, wherein the rotational drive platter, is rotatable about the axis, extends below and in engaged contacting relation with a lower face of the feeder disc, and rotates to cause rotation of the feeder disc in a rotational direction and is rotationally movable relative to the feeder disc responsive to the feeder disc encountering resistance to rotation in the rotational direction, a frangible drive pin, wherein the frangible drive pin includes a head, wherein the head is releasably engageable with the drive

platter, is configured to operatively rotationally connect a radially extending rotatable drive post and the drive platter, wherein the drive pin includes a pair of radially disposed apart legs, wherein the legs are configured to receive the drive post in intermediate relation of the legs, wherein at least one of the legs is configured to break responsive to the drive platter encountering resistance to rotation.

20. The apparatus according to claim 1 wherein each of the plurality of brushes has a respective upper end that is in fixed operatively attached connection with an inside face of the cover, wherein at least one of the brushes is configured to direct pills in the base interior area radially toward the pill engaging apertures, wherein one respective pill is caused to be positioned in each respective pill engaging aperture during each full rotation of the feeder disc.

21. The apparatus according to claim 1 wherein the feeder disc is rotatable in a rotational direction, wherein each of the plurality of brushes has a respective upper end that is in fixed operatively attached connection with an inside face of the cover, wherein at least one brush is configured to direct pills in the base interior area radially outward toward the pill engaging apertures, and wherein at least one other brush that is disposed in the rotational direction from the at least one brush that is configured to direct pills radially outward toward the pill engaging apertures, is configured to direct pills in the base interior area radially inward and away from the pill engaging apertures.

22. The apparatus according to claim 1 wherein the feeder disc is rotatable in a rotational direction, wherein the top opening in the cover is disposed in the rotational direction away from the drop opening, wherein each of the plurality of brushes has a respective upper end that is in fixed operatively attached connection with an inside face of the cover, wherein at least one brush that is disposed in the rotational direction away from the top opening is configured to direct pills in the base interior area radially outward toward the pill engaging apertures, and wherein at least one further brush that is disposed in the rotational direction away from the at least one brush configured to direct pills radially outward toward the pill engaging apertures and that is disposed in the rotational direction ahead of the drop opening, is configured to direct pills in the base interior area radially inward away from the pill engaging apertures.

23. The apparatus according to claim 1 wherein feeder disc is bounded radially outwardly by an annular disc edge, wherein the annular disc edge is disposed radially inwardly from the annular internal wall by no more than a radial distance, wherein the radial distance is less than a smallest dimension of each pill, whereby no pills may extend radially between the annular disc edge and the annular internal wall.

24. The apparatus according to claim 1 wherein the base ring includes a cleanout opening sized for removal of pills from the base interior area through the cleanout opening, wherein the cleanout opening extends vertically below the cover, and radially through the base ring and the annular internal wall, a cleanout opening access cover, wherein the cleanout opening access cover is configured to selectively open and close the cleanout opening.

25. The apparatus according to claim 1 and further comprising: a deck, wherein the base ring is configured to extend above the deck, wherein the deck includes a plurality of disposed recesses, wherein each recess is configured to releasably hold a respective further feeder disc, wherein each further feeder disc is usable in the apparatus in place of the feeder disc, and is not usable when positioned in a respective recess, wherein each further feeder disc has the same external shape as the feeder disc that is positioned within the base interior area.

26. The apparatus according to claim 1 and further comprising: a plurality of further feeder discs, wherein each respective further feeder disc is usable in the apparatus in place of the feeder disc, and includes a plurality of respective further pill engaging apertures each configured to have one respective further pill of a different configuration from the pills, positionable in the apertures of the feeder disc and the respective further pills that are positionable in the respective further pill engaging apertures of each respective other further feeder disc, positioned in the respective pill

engaging apertures of the respective further feeder disc, wherein each respective further feeder disc includes thereon respective disc indicia indicative of the configuration of the respective of further pills that are configured to be positioned in the respective further pill engaging apertures of the respective further feeder disc when the respective further feeder disc is used in place of the feeder disc.

27. The apparatus according to claim 1 wherein the feeder disc further includes a further plurality of further pill engaging apertures, wherein each further pill engaging aperture extends vertically in a further axially centered annular portion, wherein the further axially centered annular portion is radially disposed from the axially centered annular portion, is angularly spaced from each other further pill engaging aperture in the further axially centered annular portion, and is configured to have only one respective pill positioned within the respective further pill engaging aperture, wherein during rotation of the feeder disc each one respective pill positioned within a respective further pill engaging aperture is moved while being vertically supported within the respective further pill engaging aperture by operative engagement with the plate upper surface, and wherein the plate upper surface includes a further drop opening, wherein the further drop opening is radially disposed from the drop opening and is configured to enable one respective pill in a respective further pill engaging aperture to drop individually into the further drop opening when the respective further pill engaging aperture is in vertically overlying relation with the further drop opening during rotation of the feeder disc.

28. Apparatus comprising: a base, including a base interior area therein, wherein the base interior area is bounded horizontally by a generally circular annular internal base wall, wherein the annular internal base wall extends in centered relation relative to an axis, is bounded vertically upward by a cover, and is bounded vertically downward by a feeder disc, wherein the feeder disc is rotatable about the axis in the base interior area, includes a plurality of pill engaging apertures, wherein each pill engaging aperture extends vertically through an axially centered annular portion of the feeder disc, is angularly spaced from each other pill engaging aperture in the annular portion, and is configured to have only one respective pill positioned within the respective pill engaging aperture, a plurality of deformable brushes, wherein each of the brushes has an upper end that is in immovable fixed operative connection with an inside face of the cover, extends below the cover and vertically downward in the base interior area, and has a lower end that is configured to engage a plurality of pills within the base interior area, wherein each of the plurality of pills have the same pill configuration, is in operative supported connection with the feeder disc, and is caused to move within the base interior area responsive to rotation of the feeder disc, wherein rotation of the feeder disc is operative to cause the plurality of pills within the base interior area to be moved responsive to operative engagement with the feeder disc and the plurality of brushes such that only one respective pill is caused to be positioned in each respective pill engaging aperture responsive to each feeder disc rotation, and the one respective pill that is positioned in the respective pill engaging aperture upon each feeder disc rotation, to drop individually into a drop opening upon completion of the respective feeder disc rotation, when the respective pill engaging aperture is positioned in vertically overlying relation with the drop opening.

29. The apparatus according to claim 28 wherein the cover is movably mounted relative to the base, wherein the cover is selectively movable between a closed position in which the cover vertically upwardly bounds the base interior area, and an open position in which the cover is at least partially disposed away from the base interior area and the base interior area is accessible from outside the base, wherein in the closed position of the cover the feeder disc in the base interior area is manually inaccessible and in the open position of the cover the feeder disc is enabled to be manually removed from the base interior area and replaced with a further feeder disc, wherein the further feeder disc is the same as the feeder disc except that the further feeder disc includes a plurality of further pill engaging apertures, wherein each of the further pill engaging apertures is configured to have one respective further pill of a different configuration than the pills positioned therein,

wherein with the further feeder disc within the base interior area and the cover in the closed position, and without changing a respective position of any of the brushes from the respective brush positions which operate to cause a respective pill to be positioned in a respective pill engaging aperture of the feeder disc responsive to rotation of the feeder disc, rotation of the further feeder disc is operative to cause a plurality of further pills within the base interior area to be moved responsive to operative engagement with the further feeder disc and the plurality of brushes such that only one respective further pill is positioned in each respective further pill engaging aperture responsive to each further feeder disc rotation, and one respective further pill that is positioned in the respective further pill engaging aperture upon each feeder disc rotation, to drop individually into the drop opening upon completion of the respective further feeder disc rotation, when the respective further pill engaging aperture is positioned in vertically overlying relation of the drop opening.

30. Apparatus comprising: a base ring, wherein a generally circular annular wall that is in centered relation with an axis horizontally bounds a base interior area within the base ring, a cover, wherein the cover is movably mounted in operative connection with the base ring, and is movable between a closed position in which the cover bounds vertically upward the base interior area, and an open position in which the cover is disposed at least partially away from the base interior area and the base interior area is accessible from outside the base interior area, a feeder disc, wherein the feeder disc is removably positionable within the base interior area, in an operative position of the feeder disc bounds vertically downward the base interior area, is rotatable about the axis within the base interior area, includes a plurality of pill engaging apertures, wherein each pill engaging aperture is positioned in an axially centered annular portion of the feeder disc, extends vertically through the axially centered annular portion, is angularly spaced from each other pill engaging aperture, and is configured to hold only one respective pill positioned within the respective pill engaging aperture, a plurality of deformable brushes, wherein each of the plurality of brushes is in operative fixed connection with the cover and in the closed position of the cover extends vertically in the base interior area, wherein rotation of the feeder disc and the plurality of brushes which are rotationally stationary in the closed position of the cover are operative at least in part to cause a plurality of pills positioned within the base interior area to be moved by operative engagement with the feeder disc and plurality of brushes such that only one respective pill is positioned in each respective pill engaging aperture when the respective pill engaging aperture moves into vertically overlying relation with a drop opening, wherein the respective pill drops from the respective pill engaging aperture individually into the drop opening.

31. Apparatus comprising: a base ring, wherein the base ring includes a generally circular annular internal wall, wherein the annular internal wall extends in centered relation about an axis, and bounds a base interior area, a base ring opening through which the base interior area is accessible from above the base ring, a feeder disc, wherein the feeder disc is rotatable in a rotational direction about the axis within the base interior area below the base ring opening, includes a lower face, wherein the lower face includes a plurality of either disc projections or disc recesses, wherein the disc projections or disc recesses extend vertically on the lower face, includes a plurality of pill engaging apertures, wherein each pill engaging aperture extends vertically through the feeder disc in an axially centered annular portion, is angularly spaced from each other pill engaging aperture, and is configured to have only one respective pill positioned within the respective pill engaging aperture, wherein during rotation of the feeder disc each one respective pill within a respective pill engaging aperture is moved while being vertically supported within the respective pill engaging aperture by operative engagement with a plate upper surface of a support plate that extends below the feeder disc, wherein the plate upper surface includes a drop opening, wherein the drop opening is configured to enable one respective pill in a respective pill engaging aperture to drop individually into the drop opening when the respective pill engaging aperture is in overlying relation with the drop opening during rotation of the feeder disc, a rotational drive platter, wherein

the rotational drive platter, is rotatable about the axis, includes a plurality of either platter projections or platter recesses, wherein the platter projections or platter recesses extend vertically and are radially disposed away from and uniformly angularly spaced about the axis, wherein each platter projection or platter recess is configured to releasably engage a respective disc recess or disc projection on the lower face of the feeder disc, whereby the feeder disc is rotatable in engagement with the drive platter, wherein the drive platter is rotatable in the rotational direction, and wherein at least one of each platter projection or platter recess is bounded in a direction transverse to the rotational direction by a respective tapered face surface, wherein the tapered face surfaces are operative to cause the feeder disc to move vertically away from the drive platter responsive to the feeder disc encountering resistance to movement in the rotational direction, a cover, wherein the cover is configured to cover at least a portion of the base ring opening, a plurality of deformable brushes, wherein each of the brushes is in fixed operative supported connection with the cover, extends vertically downward in the base interior area, is configured to engage pills in the base interior area, wherein rotation of the feeder disc in the rotational direction is operative to cause a plurality of pills within the base interior area to be moved by operative engagement with the feeder disc and the plurality of brushes so that one respective pill is caused to be positioned in each respective pill engaging aperture as the feeder disc rotates, and the one respective pill in the respective pill engaging aperture to drop individually into the drop opening when the respective pill engaging aperture is positioned in overlying relation with the drop opening.

32. Apparatus comprising: a base ring, wherein the base ring includes a generally circular annular internal wall, wherein the annular internal wall extends in centered relation about an axis, and bounds a base interior area, a base ring opening through which the base interior area is accessible from above the base ring, a cleanout opening, wherein the cleanout opening extends vertically below the base ring opening, and radially through the base ring and the annular internal wall, a pill pocket configured to have at least one pill therein, wherein the pill pocket extends externally on the base ring, and radially outward from the cleanout opening, a cleanout opening access cover, wherein the cleanout opening access cover is configured to selectively open and close the cleanout opening, whereby in the open condition of the cleanout opening, pills are movable from the base interior area through the cleanout opening and into the pill pocket, a feeder disc, wherein the feeder disc is rotatable about the axis within the base interior area below the base ring opening, includes a plurality of pill engaging apertures, wherein each pill engaging aperture extends vertically through the feeder disc in an axially centered annular portion, is angularly spaced from each other pill engaging aperture, and is configured to have only one respective pill positioned within the respective pill engaging aperture, wherein during rotation of the feeder disc each one respective pill within a respective pill engaging aperture is moved while being vertically supported within the respective pill engaging aperture by operative engagement with a plate upper surface of a support plate that extends below the feeder disc, wherein the plate upper surface includes a drop opening, wherein the drop opening is configured to enable one respective pill in a respective pill engaging aperture to drop individually into the drop opening when the respective pill engaging aperture is in overlying relation with the drop opening during rotation of the feeder disc, a cover, wherein the cover is configured to cover at least a portion of the base ring opening, wherein the cleanout opening extends vertically below the cover, a plurality of deformable brushes, wherein each of the brushes is in fixed operative supported connection with the cover, extends vertically downward in the base interior area, is configured to engage pills in the base interior area, wherein rotation of the feeder disc is operative to cause a plurality of pills within the base interior area to be moved by operative engagement with the feeder disc and the plurality of brushes so that one respective pill is caused to be positioned in each respective pill engaging aperture as the feeder disc rotates, and the one respective pill in the respective pill engaging aperture to drop individually into the drop opening when the respective pill engaging aperture is positioned in overlying relation with the drop opening.

33. Apparatus comprising: a base ring, wherein the base ring includes a generally circular annular internal wall, wherein the annular internal wall extends in centered relation about an axis, and bounds a base interior area, a base ring opening through which the base interior area is accessible from above the base ring, a feeder disc, wherein the feeder disc is rotatable about the axis within the base interior area below the base ring opening, includes a plurality of pill engaging apertures, wherein each pill engaging aperture extends vertically through the feeder disc in an axially centered annular portion, is angularly spaced from each other pill engaging aperture, and is configured to have only one respective pill positioned within the respective pill engaging aperture, wherein during rotation of the feeder disc each one respective pill within a respective pill engaging aperture is moved while being vertically supported within the respective pill engaging aperture by operative engagement with a plate upper surface of a support plate that extends below the feeder disc, wherein the plate upper surface includes a drop opening, wherein the drop opening is configured to enable one respective pill in a respective pill engaging aperture to drop individually into the drop opening when the respective pill engaging aperture is in overlying relation with the drop opening during rotation of the feeder disc, a cover, wherein the cover is configured to cover at least a portion of the base ring opening, a plurality of deformable brushes, wherein each of the brushes is in fixed operative supported connection with the cover, extends vertically downward in the base interior area, is configured to engage pills in the base interior area, wherein rotation of the feeder disc is operative to cause a plurality of pills within the base interior area to be moved by operative engagement with the feeder disc and the plurality of brushes so that one respective pill is caused to be positioned in each respective pill engaging aperture as the feeder disc rotates, and the one respective pill in the respective pill engaging aperture to drop individually into the drop opening when the respective pill engaging aperture is positioned in overlying relation with the drop opening, and further comprising: a plurality of further feeder discs, wherein each respective further feeder disc includes a plurality of respective pill engaging apertures each configured to have respective pills of a different configuration from the feeder disc and each other further feeder disc, positioned in the respective pill engaging apertures of the respective further feeder disc, wherein the feeder disc and each respective further feeder disc includes thereon respective disc indicia indicative of the configuration of the respective pills that are configured to be positioned in the respective pill engaging apertures of the respective feeder disc, a deck, wherein the deck includes a plate, wherein the plate is in operatively supported connection with the deck, wherein the plate includes a plurality of openings through the plate, wherein each respective opening corresponds to one respective pill configuration, wherein a respective pill having the one respective configuration is the largest pill that will pass through the respective opening, wherein each respective opening has respective plate indicia adjacent thereto, wherein the plate indicia adjacent to a respective opening has a corresponding relationship to the disc indicia on the respective feeder disc or further feeder disc that is used with the respective pill having the configuration that is the largest pill that will pass through the respective opening.

34. Apparatus comprising: a base ring, wherein the base ring includes a generally circular annular internal wall, wherein the annular internal wall extends in centered relation about an axis, and bounds a base interior area, a base ring opening through which the base interior area is accessible from above the base ring, a feeder disc, wherein the feeder disc is rotatable about the axis within the base interior area below the base ring opening, includes a plurality of pill engaging apertures, wherein each pill engaging aperture extends vertically through the feeder disc in an axially centered annular portion, is angularly spaced from each other pill engaging aperture, and is configured to have only one respective pill positioned within the respective pill engaging aperture, wherein during rotation of the feeder disc each one respective pill within a respective pill engaging aperture is moved while being vertically supported within the respective pill engaging aperture by operative engagement with a plate upper surface of a support plate that extends below the feeder disc, wherein the plate upper surface includes a drop opening, wherein the drop opening is configured to

enable one respective pill in a respective pill engaging aperture to drop individually into the drop opening when the respective pill engaging aperture is in overlying relation with the drop opening during rotation of the feeder disc, a cover, wherein the cover is configured to cover at least a portion of the base ring opening, wherein the base ring, the feeder disc and the cover are configured to be installed in operatively attached connection with a packaging machine in place of a removed tray and rotatable pill disc of the machine, a plurality of deformable brushes, wherein each of the brushes is in fixed operative supported connection with the cover, extends vertically downward in the base interior area, is configured to engage pills in the base interior area, wherein rotation of the feeder disc is operative to cause a plurality of pills within the base interior area to be moved by operative engagement with the feeder disc and the plurality of brushes so that one respective pill is caused to be positioned in each respective pill engaging aperture as the feeder disc rotates, and the one respective pill in the respective pill engaging aperture to drop individually into the drop opening when the respective pill engaging aperture is positioned in overlying relation with the drop opening.
