

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398027
Kind Code	B1
Date of Patent	August 26, 2025
Inventor(s)	Christensen; Hans Martin

Jack support apparatus and method of use

Abstract

A jack support apparatus has an outer tube having an outer tube body with an outwardly-extending outer tube jack cradle and an opposite outer tube opening, an inner tube having an inner tube body with a plurality of spaced-apart inner tube holes and an outwardly-extending inner tube jack cradle, the inner tube body slidably received within the outer tube body through the outer tube opening, the outer and inner tube jack cradles configured to each selectively engage one of the wheel axle and the cup axle of the jack, and a pin operable through an outer tube hole for selectively engaging any of the plurality of inner tube holes.

Inventors:	Christensen; Hans Martin (Escondido, CA)
Applicant:	AGA Tools & Products, Inc. (Escondido, CA)
Family ID:	1000006766930
Assignee:	AGA Tools & Products, Inc. (Escondido, CA)
Appl. No.:	17/982568
Filed:	November 08, 2022

Related U.S. Application Data

continuation-in-part parent-doc US 17726358 20220421 US 11505440 child-doc US 17982568

Publication Classification

Int. Cl.: **B66F1/02 (20060101)**

U.S. Cl.:

CPC **B66F1/02 (20130101); B66F2700/025 (20130101)**

Field of Classification Search

CPC: B66F (1/02); B66F (2700/025)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3355136	12/1966	Staples	248/352	F16M 11/046
4796864	12/1988	Wilson	254/425	B60S 9/08
5423518	12/1994	Baxter	254/419	B60S 9/08
5794907	12/1997	Bellia	248/354.7	B66F 5/04
11505440	12/2021	Christensen	N/A	B66F 13/00

Primary Examiner: Hong; Seahee

Attorney, Agent or Firm: Master Key IP, LLP

Background/Summary

RELATED APPLICATIONS (1) This is a continuation-in-part application and so claims the benefit pursuant to 35 U.S.C. § 120 of a prior filed and co-pending U.S. Non-Provisional patent application Ser. No. 17/726,358 filed Apr. 21, 2022, and entitled “Jack Support Apparatus and Method of Use.” The contents of the aforementioned application are incorporated herein by reference.

BACKGROUND

- (1) The subject of this patent application relates generally to tools and equipment, and more particularly to a jack support apparatus configured for providing mechanical “fail-safe” support to hydraulic floor jacks.
- (2) The following description includes information that may be useful in understanding the present invention. It is not an admission that any of the information provided herein is prior art or relevant to the presently claimed invention, or that any publication specifically or implicitly referenced is prior art.
- (3) Applicant(s) hereby incorporate herein by reference any and all patents and published patent applications cited or referred to in this application, to the same extent as if each individual publication or patent application were specifically and individually indicated to be incorporated by reference. Where a definition or use of a term in an incorporated reference is inconsistent or contrary to the definition of that term provided herein, the definition of that term provided herein applies and the definition of that term in the reference does not apply.
- (4) By way of background, in a variety of contexts but particularly the automotive context, a jack is often needed or employed to lift a portion of the vehicle to change a tire or the oil or to perform other repairs. Most vehicles come equipped with a mechanical scissor-lift jack for jacking up a portion of the vehicle, as by positioning such a jack on the ground under the vehicle with its lift surface adjacent to a frame member or jack point and then actuating the jack as by rotating the lead screw to cause the jack to extend upwardly, make contact with the vehicle, and then lift the vehicle as the jack's lead screw is further rotated. While such scissor-lift jacks, screw-type jacks, and other mechanical jacks are generally effective, they are relatively time consuming to operate, typically

have smaller weight capacity than other kinds of jacks, and are relatively less safe due to their relatively small base.

(5) Alternatively and certainly in more common use by auto mechanics in shops and regular do-it-yourselfers at home are hydraulic floor jacks, which have a relatively larger wheeled base and a lift arm that is pivotably installed on the base operably in conjunction with a hydraulic cylinder and piston and related handle that may be used to push or pull the jack into position and then actuated or pumped up and down via its yoke mechanism to operate a valve and push hydraulic fluid into the cylinder and pressurize it, thereby pushing the lifting piston up or out of the cylinder. When the hydraulic jack is thus positioned as desired under a vehicle with its lift cup at the free end of the lift arm adjacent to the lift point on the underside of the vehicle, as the handle is continually pumped, the lifting piston is gradually extended from the cylinder such that its mechanical coupling with the arm causes the arm to pivot upwardly relative to the base and hence to lift the vehicle. When the job is completed and the vehicle is to again be lowered, typically, the handle is simply slowly rotated to open the valve and gradually release pressure in the hydraulic cylinder and thus gradually lower the vehicle. It will be appreciated that the key to safe and effective operation of such hydraulic jacks is creating and maintaining the required pressure in the cylinder and that if such pressure were suddenly lost such as due to a valve, seal or o-ring, or other mechanical failure, the jack would lose all power and no longer be able to support the vehicle, causing the vehicle to suddenly drop, which of course would be extremely dangerous and even deadly.

(6) Oftentimes, whether for safety reasons or because both sides or two portions of a vehicle are to be lifted, one or more jack stands may be employed to support a portion of the vehicle once it is lifted to a sufficient height by a jack. An automotive jack stand is typically formed having flared legs or a somewhat pyramid-shaped base with a central vertical passage in which is slidably installed a shaft having a lift surface at its upper end and horizontal teeth along the shaft that may be selectively engaged by a cross-pin passing through the jack stand base so as to intersect the passage and thus seat against a tooth of the shaft to effectively lock the shaft at a desired vertical position relative to the base and thus become a somewhat rigid weight-bearing structure at a desired pre-set height. Thus, with the jack stand so configured and positioned at a desired location on the ground underneath the vehicle, the employed jack can be slowly lowered until the weight of that portion of the vehicle is on the jack stand rather than the jack, allowing the jack to be removed and, as needed, to be used elsewhere such as to lift another portion of the vehicle.

(7) Accordingly, jack stands have the advantage of supporting the weight of at least a portion of a vehicle with effectively no moving parts, or certainly only mechanical parts that are less likely to fail, while not relying on and tying up a jack at all times while a vehicle is being supported. But even so, such jack stands have a number of shortcomings. For one, due to the structure and the minimum height of a typical jack stand, it cannot be inserted until the vehicle is a minimum height off the ground at the desired location, which can create complexities even if just one side is to be lifted and particularly if both sides of the vehicle must be lifted, requiring that the vehicle be “walked up” by gradually jacking up one side and then the other in alternating fashion while gradually increasing the height setting of each jack stand until both jack stands on opposite sides of the vehicle are safely positioned at the same final height. Further, and perhaps more significantly, it will be appreciated that the locations of a traditional jack stand and of the jack itself must be different. For many older vehicles that have significant areas of the frame or chassis available or lengthwise pinch welds along the length of the chassis or frame to serve as jack points, the jack and jack stand locations being different is not problematic even if still not ideal when it is desired to jack up and then support a vehicle in the same vicinity (e.g., the front left if the driver's side front tire were to be changed). But for many newer vehicles with weight-reduction designs, composite panels, and somewhat hidden frame and chassis features, only a select few jack points are provided by the manufacturer that alone must be used to jack up the vehicle else damage the vehicle or have it fall, such as four total jack points at the respective four “corners” of the vehicle. In such vehicles

that have dedicated jack points, which are usually no larger than the jack surface itself, it is thus impossible to both jack up the vehicle at a particular jack point and place a jack stand at that same jack point.

(8) To address such challenges of employing jack stands at dedicated jack points on newer or exotic vehicles or when there is simply not much room to employ a jack and jack stand separately side-by-side, one proposed product is effectively a jack stand that may be assembled and disassembled and thus be employed with a hydraulic floor jack as the vehicle is lifted so that the jack and jack stand can be at the same location. One such product, known as the “RennStand” manufactured and sold by Safe Jack in Pasco, Washington, has a crossbar that may be disassembled from its two opposite legs and positioned on or across the jack surface or floor jack cup, between the jack surface and the vehicle jack point, which crossbar may also accept on its top side various adapters depending on the jack point configuration. By positioning the jack and thus the crossbar and jack surface appropriately under the vehicle and raising the jack until the crossbar or any related adapter is in contact with the vehicle jack point, further actuation of the jack will lift the crossbar and that portion of the vehicle to the desired height or ground clearance. With the jack and vehicle so lifted, height-adjustable legs of the RennStand may be assembled onto opposite ends of the crossbar and adjusted to a desired height at or above the ground via clevis pins and corresponding cross-holes in the crossbar and legs, and then the jack may be lowered until the weight of that portion of the vehicle is on the RennStand and the jack can be removed, the splayed legs of the RennStand effectively straddling the floor jack. As such, while the RennStand is aimed at solving the problem of locating a jack stand at the same jack point at which a vehicle is to be lifted or jacked up, it does so through a system of removable parts and pins that is relatively cumbersome, which separable parts or pins may fail or be lost, rendering the RennStand inoperable, and which assembled RennStand results in a jack “bridge” of sorts that has a wider base or “footprint” than the floor jack itself, a disadvantage for certain automobiles and automotive repairs where tight spaces are involved.

(9) What has been needed and heretofore unavailable is a compact and easy-to-use tool or piece of equipment that effectively converts a hydraulic floor jack into a jack stand, thereby more safely, quickly, and effectively supporting a vehicle especially with limited jack points and limited space. Aspects of the present invention fulfill these needs and provide further related advantages as described in the following summary.

SUMMARY

(10) Aspects of the present invention teach certain benefits in construction and use which give rise to the exemplary advantages described below.

(11) The present invention solves the problems described above by providing a jack support apparatus for selectively locking a hydraulic floor jack against further downward movement. In at least one embodiment, the apparatus comprises an outer tube having an outer tube body comprising at least one outer tube wall with an outer tube hole formed in the outer tube wall, an outwardly-extending outer tube jack cradle, and an outer tube opening opposite the outer tube jack cradle, the outer tube jack cradle configured to selectively engage one of the wheel axle and the cup axle, an inner tube having an inner tube body comprising at least one inner tube wall with a plurality of spaced-apart inner tube holes formed in the inner tube wall and an outwardly-extending inner tube jack cradle, the inner tube body slidably received within the outer tube body through the outer tube opening with the inner tube wall adjacent to the outer tube wall, the inner tube jack cradle configured to selectively engage one of the wheel axle and the cup axle, the outer tube jack cradle and the inner tube jack cradle being opposite and symmetrical, and a pin operable through the outer tube hole for selectively engaging any of the plurality of inner tube holes, wherein selective operation of the pin by shifting the pin away from the inner tube disengages the pin from any of the plurality of inner tube holes and allows the inner tube to shift relative to the outer tube as by the inner tube body sliding within the outer tube body, and further wherein selective operation of the

pin by shifting the pin toward the inner tube engages the pin in one of the plurality of inner tube holes as the inner tube shifts relative to the outer tube as by the inner tube body sliding within the outer tube body to align the outer tube hole with a select one of the plurality of inner tube holes to prevent further relative movement between the outer tube and the inner tube, whereby the apparatus is configured to temporarily form a rigid linkage between the wheel and cup axles upon engagement therebetween by the outer tube and inner tube jack cradles to effectively lock the jack against further downward movement.

(12) Other objects, features, and advantages of aspects of the present invention will become more apparent from the following detailed description, taken in conjunction with the accompanying drawings, which illustrate, by way of example, the principles of aspects of the invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The accompanying drawings illustrate aspects of the present invention. In such drawings:
- (2) FIG. 1 is a perspective view of an exemplary jack support apparatus in a first position, in accordance with at least one embodiment;
- (3) FIG. 2 is a cross-sectional perspective view thereof, in accordance with at least one embodiment;
- (4) FIG. 3 is an enlarged cross-sectional perspective view of an outer tube thereof, in accordance with at least one embodiment;
- (5) FIG. 4 is an enlarged cross-sectional perspective view of an inner tube thereof, in accordance with at least one embodiment;
- (6) FIG. 5 is an enlarged partial and partially cutaway perspective view of the exemplary jack support apparatus of FIG. 1 in the first position, in accordance with at least one embodiment;
- (7) FIG. 6 is a perspective view of the exemplary jack support apparatus of FIG. 1 in a second position, in accordance with at least one embodiment;
- (8) FIG. 7 is a cross-sectional perspective view thereof, in accordance with at least one embodiment;
- (9) FIG. 8 is a reduced scale perspective view of the exemplary jack support apparatus of FIG. 1 as employed with a floor jack in a first operational mode, in accordance with at least one embodiment;
- (10) FIG. 9 is a further perspective view thereof in a second operational mode, in accordance with at least one embodiment;
- (11) FIG. 10 is a further perspective view thereof in a third operational mode, in accordance with at least one embodiment;
- (12) FIG. 11 is a reduced scale perspective view of the exemplary jack support apparatus of FIG. 1 as employed with a floor jack in supporting a vehicle, in accordance with at least one embodiment.
- (13) FIG. 12 is a rear perspective view of an alternative exemplary jack support apparatus, in accordance with at least one embodiment;
- (14) FIG. 13 is a front perspective view thereof, in accordance with at least one embodiment;
- (15) FIG. 14 is a perspective view of a further alternative exemplary jack support apparatus, in accordance with at least one embodiment;
- (16) FIG. 15 is a cross-sectional perspective view thereof, in accordance with at least one embodiment;
- (17) FIG. 16 is a perspective view of a still further alternative exemplary jack support apparatus, in accordance with at least one embodiment;
- (18) FIG. 17 is a cross-sectional perspective view thereof, in accordance with at least one embodiment;
- (19) FIG. 18 is a perspective view of a still further alternative exemplary jack support apparatus, in

accordance with at least one embodiment; and

(20) FIG. **19** is a cross-sectional perspective view thereof, in accordance with at least one embodiment.

(21) The above described drawing figures illustrate aspects of the invention in at least one of its exemplary embodiments, which are further defined in detail in the following description. Features, elements, and aspects of the invention that are referenced by the same numerals in different figures represent the same, equivalent, or similar features, elements, or aspects, in accordance with one or more embodiments. More generally, those skilled in the art will appreciate that the drawings are schematic in nature and are not to be taken literally or to scale in terms of material configurations, sizes, thicknesses, and other attributes of an apparatus according to aspects of the present invention and its components or features unless specifically set forth herein.

DETAILED DESCRIPTION

(22) The following discussion provides many exemplary embodiments of the inventive subject matter. Although each embodiment represents a single combination of inventive elements, the inventive subject matter is considered to include all possible combinations of the disclosed elements. Thus, if one embodiment comprises elements A, B, and C, and a second embodiment comprises elements B and D, then the inventive subject matter is also considered to include other remaining combinations of A, B, C, or D, even if not explicitly disclosed.

(23) While the inventive subject matter is susceptible of various modifications and alternative embodiments, certain illustrated embodiments thereof are shown in the drawings and will be described below in detail. It should be understood, however, that there is no intention to limit the invention to any specific form disclosed, but on the contrary, the inventive subject matter is to cover all modifications, alternative embodiments, and equivalents falling within the scope of the claims.

(24) Turning now to FIG. **1**, there is shown a perspective view of an exemplary embodiment of a jack support apparatus **20** according to aspects of the present invention. The apparatus **20** comprises, in the exemplary embodiment, an outer tube **30**, an inner tube **50** telescopically or slidably received in the outer tube **30**, and a handle assembly **80** and a pin assembly **100** that cooperate to selectively adjust the overall height of the apparatus **20** in use. An outer tube jack cradle **42** at a first end **22** of the apparatus **20** and an inner tube jack cradle **62** at an opposite second end **24** of the apparatus **20** define the points of mechanical engagement with features of a hydraulic floor jack J (FIGS. **8-11**) as explained further below. At a high level, it will be appreciated that the general functional configuration of the jack support apparatus **20** as shown and described herein is illustrative and non-limiting and such device can take other forms and employ other mechanical means now known or later developed without departing from the spirit and scope of the invention as set forth herein. For example, while the outer and inner tubes **30**, **50** are shown as each having a rectangular profile or cross-section with flat or planar walls, a number of other shapes for such telescoping tubes **30**, **50**, including but not limited to annular, are possible according to aspects of the present invention. Similarly, the shape or configuration of the outer and inner tube jack cradles **42**, **62** may vary to suit particular applications or contexts, such as different types or styles of jacks and engagement points thereon. And while particular configurations or mechanical arrangements of the handle and pin assemblies **80**, **100** are shown and described herein as the means for selectively extending and locking the jack support apparatus **20** at a desired position or length, it will be appreciated that a variety of other mechanical means may similarly be employed without departing from the spirit and scope of the invention, as will be further appreciated with reference to the alternative exemplary embodiments shown in FIGS. **12-19** and the related discussion further below, including the alternative lever assembly **130** in the embodiment of FIGS. **18** and **19** as effectively a substitute for the cooperating handle and pin assemblies **80**, **100**. Fundamentally, what is shown and described herein in various exemplary embodiments is a new and novel telescoping assembly for selectively mechanically engaging a hydraulic floor jack or the like to effectively convert the

jack into a jack stand or effectively prevent the unwanted downward movement or collapse of the jack under load thereby providing a “fail-safe” for the floor jack. Once again, those skilled in the art will appreciate that such can be accomplished by a jack support apparatus **20** according to aspects of the present invention and other such mechanical arrangements that operate on essentially the same principle of selectively and temporarily providing a structural strut or support member between points on the jack to prevent its unintended collapse and so can take a variety of forms to do so beyond the exemplary embodiments. Even so, a number of functional benefits are derived from the exemplary jack support apparatus **20** in assembly and use that render it particularly safe, quick, and effective as will be appreciated from the present disclosure.

(25) With continued reference to FIG. **1** and now with reference also to the cross-sectional view of FIG. **2**, the exemplary jack support apparatus **20** again includes the main outer and inner tubes **30**, **50** that telescopically slide relative to each other so as to extend or retract, or lengthen or shorten, the overall apparatus **20**. Once more, as illustrated, both the outer tube body **32** and the inner tube body **52** are formed as hollow, substantially rectangular cross-section members that are sized such that the inner tube **50** is slidably received within the outer tube **30** in a somewhat net-fit arrangement, at least on three sides, the outer tube body **32** being formed with or defining an outer tube opening **34** for receipt of the inner tube body **52**. Spaced-apart holes **68** are formed along a side wall **56** of the inner tube body **52** configured to be selectively engaged by a pin **102** of the pin assembly **100** that is installed on a corresponding side wall **36** of the outer tube body **32** so as to lock the inner tube **50** relative to the outer tube **30** in a desired position, thereby setting the overall length of the apparatus **20**, an exemplary intermediate position between fully extended and fully retracted positions being shown. The pin **102** is biased inwardly by a pin spring **120** so as to force the pin **102** toward the inner tube body **52** and into a corresponding hole **68** of the inner tube **50** once aligned such that the default is for the apparatus **20** to lock in position, more about which is said below, particularly in connection with FIGS. **8-11** regarding use of the jack support apparatus **20**. In order to lift the pin **102** out of engagement with or in a particular inner tube hole **68** against the biasing effect of the pin spring **120** and so enable adjustment of the length of the apparatus **20**, a handle assembly **80** is installed on the outer tube body **32** adjacent to and operably engaged with the pin assembly **100**. Specifically, a pivotable handle **82** is configured having a tip **88** that engages an undercut **106** of the pin **102** such that squeezing the handle **82** to shift the grip **86** toward the outer tube **30** alternately lifts the tip **88** and thus the pin **102** until it is retracted from the inner tube hole **68** it was seated in, thereby allowing the inner tube **50** to slide or move freely relative to the outer tube **30**, or specifically the inner tube body **52** relative to the outer tube body **32**. As also shown, the inner tube **50** is biased away from the outer tube **30** axially, or the jack support apparatus **20** is biased toward its fully-extended position, by an axial or lengthwise tube spring **70** operably installed within the telescoping assembly of the outer and inner tubes **30**, **50**. Specifically, the tube spring **70** seats at its opposite ends on the respective outer tube and inner tube end walls **40**, **60** and thereby exerts an axially outward spring force on or between the outer and inner tubes **30**, **50** and is thereby axially compressed as the inner tube **50** is slid inwardly or toward the outer tube **30**. To facilitate such seating of the tube spring **70** and prevent unwanted flexing, kinking, or “walking” of the tube spring **70**, an outer tube sleeve **44** extends inwardly and axially from the outer tube end wall **40** toward the outer tube opening **34** parallel to the outer tube body **32**, and a corresponding inner tube rod **64** extends inwardly and axially from the inner tube end wall **60** toward an opposite inner tube opening **54** parallel to the inner tube body **52** such that the inner tube rod **64** is slidably or telescopically received within the outer tube sleeve **44** just as the inner tube body **52** is slidably or telescopically received within the outer tube body **32**, with the tube spring **70** positioned about the outer tube sleeve **44** and the inner tube rod **64** so as to be axially stabilized and spatially constrained thereby, in the exemplary embodiment the outer tube sleeve **44**, inner tube rod **64**, and tube spring **70** being substantially annular, and in any case the outer tube sleeve **44** and inner tube rod **64** together serving as a spring guide for the tube spring **70**. It will thus be

appreciated that the slidable engagement between the outer and inner tube bodies **32**, **52** and the outer tube sleeve **44** and inner tube rod **64** cooperate to axially align and facilitate telescopic movement between the outer and inner tubes **30**, **50**, which again are biased apart or toward a fully-extended position of the jack support apparatus **20** by the internally-contained tube spring **70**. It will also be appreciated that instead of the exemplary arrangement the sleeve could be installed in the inner tube and the rod in the outer tube. As also shown in FIG. 2, an inwardly-projecting outer tube stop **46** may be formed on a side wall **38** of the outer tube body **32** near the outer tube opening **34** and a corresponding inwardly-projecting inner tube stop **66** may be formed on a side wall **58** of the inner tube body **52** near the inner tube opening **54** such that the outer and inner tube stops **46**, **66** make contact with each other at the fully-extended position of the apparatus **20** as shown in FIGS. 6 and 7 so as to prevent separation of the outer and inner tubes **30**, **50** during use. It will also be appreciated that the outer and inner tube stops **46**, **66** provide stand-offs between the outer tube side wall **38** and the inner tube side wall **58** to effectively set the somewhat net-fit sliding arrangement of the outer and inner tube bodies **32**, **52** opposite the first side walls **36**, **56** that are immediately adjacent in the exemplary embodiment. As also seen in FIGS. 1 and 2, the outer tube end wall **40** in part exteriorly forms or defines the outer tube jack cradle **42** and the inner tube end wall **60** in part exteriorly forms or defines the inner tube jack cradle **62**, more about which is said below in connection with FIGS. 8-11 regarding the jack support apparatus **20** in use.

(26) Referring next to FIG. 3, there is shown an enlarged cross-sectional view of the outer tube **30** of the exemplary jack support apparatus **20** (FIGS. 1 and 2) according to aspects of the present invention. In the exemplary embodiment, the outer tube **30** comprises an outer tube body **32** having one side wall **36** on which are installed both the handle assembly **80** and the pin assembly **100** and an opposite side wall **38** on which is installed the outer tube stop **46** near the outer tube opening **34**. And again, extending inwardly and axially from the outer tube end wall **40** opposite from and toward the outer tube opening **34** is the outer tube sleeve **44** configured for slidable receipt therein of the inner tube rod **64** (FIGS. 2 and 4) and thereabout of the tube spring **70** (FIG. 2). The pin assembly **100** is shown as comprising a hollow pin housing **110** installed on the outer tube side wall **36** substantially in or about a corresponding outer tube hole **48** with the pin **102** slidably and operably installed within the housing **110** and hole **48**. In a bit more detail, the pin housing **110** is shown as having an annular side wall **112** and an end wall **116** opposite the hole **48** and the pin **102** as having a cylindrical pin body **104**, an intermediate circumferential undercut **106** formed in the pin body **104**, and a proximal pin head **108** on which is seated the biasing pin spring **120**, between the pin **102** and the pin housing end wall **116**. The pin **102** may thus be somewhat of a net fit in slidably operating within the pin housing **110**, or more particularly, the outside diameter of the pin body **104** and the inside diameter of the pin housing side wall **112** may be approximately the same, though with at least a few thousandths of an inch (0.002 in.) clearance depending the materials, smoothness, and other factors, more about which is said below. To prevent any pressure build-up (positive or negative (i.e., vacuum)) within the pin housing **110** in the area trapped between the sliding pin **102** and the side and end walls **112**, **116** of the housing **110**, where the pin spring **120** is positioned and operates, an opening **118** may be formed in the housing end wall **116** to allow for air flow in or out. And in order for the tip **88** of the handle **82** of the handle assembly **80** to operably engage the pin undercut **106**, an opening **114** is formed in the pin housing side wall **112** as shown. The handle assembly **80** is then formed once again as generally comprising a handle **82** having an elongate handle body **84** having a proximal grip **86** and an opposite distal tip **88**, with an intermediate cross-hole **90** formed in the handle body **84** so as to pivotally install the handle **82** on a handle base **92** as by passing a bolt or cross-pin **94** (FIG. 1) through the handle base **92** and the cross-hole **90** of the handle body **84** so that the handle **82** then pivots on the handle base **92** about the cross-pin **94**. Notably, the handle cross-hole **90** and the handle base **92** are so positioned that the handle tip **88** is operably seated within the pin undercut **106** as shown. By way of further illustration and not limitation, while the handle assembly **80**, and particularly the base **92** thereof, is

shown as installed on the outer tube body side wall **36**, it will be appreciated that it may be installed instead or in addition on other portions of the outer tube body **32**. It will once again be appreciated by those skilled in the art that the handle and pin assemblies **80**, **100** may be configured in other ways employing materials and mechanisms now known or later developed so as to selectively engage or lock the outer and inner tubes **30**, **50** relative to each other in setting the desired height or position of the jack support apparatus **20**, such that the exemplary handle and pin assemblies **80**, **100** and the overall outer and inner tubes **30**, **50** are to be understood as illustrative and non-limiting.

(27) Similarly, in FIG. **4** there is shown an enlarged cross-sectional view of the inner tube **50** of the exemplary jack support apparatus **20** (FIGS. **1** and **2**) according to aspects of the present invention, in the exemplary embodiment the inner tube **50** comprising an inner tube body **52** having one side wall **56** in which are formed the series of spaced-apart holes **68** configured for selective engagement by the pin **102** of the outer tube pin assembly **100** and an opposite side wall **58** on which is installed the inner tube stop **66** near the inner tube opening **54**. And again, extending inwardly and axially from the inner tube end wall **60** opposite from and toward the inner tube opening **54** is the inner tube rod **64** configured for slidable receipt within the outer tube sleeve **44** (FIGS. **2** and **3**) and partially thereabout of the tube spring **70** (FIG. **2**).

(28) Turning to FIG. **5**, there is shown a further enlarged partial perspective view of the exemplary jack support apparatus **20** of FIGS. **1** and **2**, partially cut-away to reveal and further illustrate the handle and pin assemblies **80**, **100** and particularly the interaction of the handle **82** with the pin **102**. Once more, the handle assembly **80** is installed on the outer tube **30** such that the handle tip **88** is operably positioned as passing through the pin housing side wall opening **114** and into the pin body undercut **106**. It will be appreciated that by forming the undercut **106** circumferentially about the pin body **104**, no matter how the pin **102** is rotated within the pin housing **110**, the same engagement between the handle tip **88** and the pin undercut **106** is achieved. In operation, when the handle **82** is not actuated and the handle grip **86** is released or not manipulated, the pin **102** will be pushed toward the inner tube **50** under the biasing influence of the pin spring **120**. If the pin body **104** is not aligned with one of the holes **68** formed in the side wall **56** of the inner tube body **52**, it will be appreciated that the pin body **104** will stop against the side wall **56** itself and ride therealong as the inner tube **50** is slid or shifted relative to the outer tube **30** until the pin body **104** is positioned adjacent to or clears an inner tube hole **68**, at which time, again under the influence of the pin spring **120**, the pin **102** will be shifted further toward the inner tube **50** and the pin body **104** will enter and seat within the adjacent hole **68** so as to lock the apparatus **20** as shown, which is effectively the default or “at rest” configuration of the apparatus **20**, irrespective of which hole **68** the pin **102** is seated within. It is also noted that by virtue of the continual engagement of the handle tip **88** within the pin undercut **106**, the travel of the pin **102** along the pin housing **110** is limited, on which basis the handle tip **88** effectively serves as a “keeper” for the pin **102** within the pin housing **110**, with the travel of the tip **88** limited by the handle body **84** itself as it comes into contact with the outer tube side wall **36** and/or a portion of the handle base **92** so as to limit or prevent further travel of the handle **82** and thus of the pin **102**. Whereas, when the jack support apparatus **20** is to be adjusted or set to a different length, the proximal handle grip **86** is shifted toward the outer tube **30**, and the outer tube side wall **36** specifically, via the handle **82** pivoting about the intermediate cross-pin **94**, as by pushing on or squeezing the grip **86**, causing the distal handle tip **88** opposite the grip **86** to pivot away from the outer tube **30** and thereby lift the pin **102** or shift the pin **102** away from the outer and inner tubes **30**, **50** and out of engagement with the corresponding hole **68** in the inner tube **50**. Those skilled in the art will appreciate that by having a length or portion of the handle body **84** indicated as the grip **86** extend beyond the handle cross-hole **90** (FIG. **3**) and related handle cross-pin **94** further than the handle body **84** extends from the cross-pin **94** to the handle tip **88**, there is increased leverage via the handle grip **86**, and increasingly so the further from the pivot point or cross-pin **94**, relative to the biasing effect of the

pin spring **120** (FIGS. 2 and 3) acting on the pin **102**, the handle body **84** and particularly the grip portion **86** thereof serving as a mechanical lever for lifting or actuating the locking pin **102**.

Accordingly, those skilled in the art will appreciate that by so forming the handle assembly **80** relative to the pin assembly **100** even a relatively strong spring force of the pin spring **120** can be overcome by relatively low force applied to the handle grip **86** during use of the apparatus **20** as through actuation of the handle **82**. Moreover, it will be appreciated that a relatively strong spring force of the pin spring **120** is desirable to produce relatively rapid insertion of the pin body **104** into the corresponding inner tube hole **68** and thus relatively rapid locking of the apparatus **20** in the case of even rapid jack lowering, more about which is said below in connection with FIGS. 8-11. Relatedly, as shown, the inner tube holes **68** may be formed having a somewhat oval or oblong profile rather than being perfectly round, which it will be appreciated will assist with the spring-forced insertion of the pin body **104** in such hole **68** even while the inner tube **50** is still in motion or sliding relative to the outer tube **30**.

(29) Briefly referring to FIGS. 6 and 7, there are shown perspective and cross-sectional perspective views of the exemplary jack support apparatus **20** of FIGS. 1 and 2 now in a second position as by actuating the handle **82** of the handle assembly **80** to lift the pin **102** of the pin assembly **100** out of engagement with a hole **68** of the inner tube **50**, which it will be appreciated from the foregoing is accomplished by shifting or squeezing the grip **86** of the handle **82** toward the outer tube **30** to thereby cause or allow the inner tube **50** to slide axially relative to the outer tube **30** under the biasing effect of the tube spring **70** until the outer tube and inner tube stops **46**, **66** make contact as shown, unless the outer and inner tube jack cradles **42**, **62** made contact with the structure of a jack or the like before the outer tube and inner tube stops **46**, **66** were able to make contact. With the apparatus **20** so operated with the handle **80** remaining actuated or “squeezed,” it will be appreciated that the inner tube **50** can be freely slid against the tube spring **70** relative to or toward the outer tube **30** until the relative positions of the outer and inner tubes **30**, **50** or the overall length of the apparatus **20** is as desired, at which point the handle grip **86** may be released and the pin body **104** will again enter into an adjacent inner tube hole **68** based on slight further relative movement between the outer and inner tubes **30**, **50** until the pin **102** effectively “clicks” into place to lock the apparatus **20** in position or at the desired overall length. It will also be appreciated that at all such positions or lengths of the jack support apparatus **20**, the outer and inner tubes **30**, **50** remain sufficiently engaged for functional integrity under vertical load, with the outer tube sleeve **44** and inner tube rod **64** also remaining slidably engaged even at the fully-extended position of the apparatus **20**, at all times providing lateral stability and serving as a spring guide for the tube spring **70** as shown.

(30) With reference to FIGS. 1-7, in forming the exemplary jack support apparatus **20**, and particularly the outer and inner tubes **30**, **50**, and the various components thereof, it will be appreciated that any appropriate materials and methods of construction now known or later developed may be employed, including but not limited to metals and metal alloys such as iron, steel, aluminum, and the like and potentially even a variety of sufficiently strong and stiff plastics and composites such as polytetrafluoroethylene (“PTFE”), polyether ether ketone (“PEEK”), polyetherimide (“PEI”), polyamide-imide (“PAI”), polybenzimidazole (“PBI”), polypropylene, polystyrene, polyvinyl chloride (“PVC”), acrylonitrile butadiene styrene (“ABS”), polyethylenes such as high density polyethylene (“HDPE”) and low density polyethylene (“LDPE”), polycarbonate, polyurethane, and other such plastics, thermoplastics, thermosetting polymers, and the like, any such components being fabricated or formed as through machining, casting, forging, extrusion, stamping, forming, injection molding, or any other such technique now known or later developed. Relatedly, such components may be formed integrally or may be formed separately and then assembled in any appropriate secondary operation employing any assembly technique now known or later developed, including but not limited to fastening, as through screws or the like, bonding, welding, press-fitting, snapping, over-molding or coining, or any other such technique

now known or later developed. Those skilled in the art will fundamentally appreciate that any such materials and methods of construction are encompassed within the scope of the invention, any exemplary materials and methods in connection with any and all embodiments thus being illustrative and non-limiting. In the exemplary embodiment, the outer tube body **32**, the inner tube body **52**, the outer and inner tube end walls **40**, **60** and associated jack cradles **42**, **62**, and the locking pin **102** are formed of mild steel (e.g., 4130 steel), which is to say the load-bearing components of the jack support apparatus **20**. Other components such as the handle assembly **80**, including the handle **82** and handle bracket or base **92**, the pin housing **110**, the outer and inner tube stops **46**, **66**, and the outer tube sleeve **44** and inner tube post **64** may also be made of 4130 or other steel or of aluminum (e.g., 6061 aluminum). Dimensionally, in the exemplary embodiment, the outer tube body **32** is nominally 1 in.×2 in. on its outer profile and 7.5 in. long, with a wall thickness of 0.12 in., setting its nominal interior dimensions at 0.88 in.×1.88 in., while the inner tube body **52** is nominally 0.75 in.×1.5 in. on its outer profile and 7.625 in. long, with a wall thickness again of 0.12 in., resulting in a lateral clearance between the outer and inner tube bodies **32**, **52** of approximately 0.065 in. $((0.88 \text{ in.} - 0.75 \text{ in.})/2)$. The locking pin **102** and particularly its body **104** is 0.48 in. diameter and nominally 1 in. long, with the distal portion of the body **104** that engages the inner tube holes **68** being 0.5 in. long, the width of the undercut **106** being 0.25 in. with a depth of roughly 0.15 in., and the pin head **108** on which the pin spring **120** seats being generally 0.25 in. in length along the pin **102**, with a stepped proximal edge to provide a spring seat and the distal end of the pin body **104** being chamfered about its circumferential edge for assistance with the pin body **104** seating within the inner tube locking holes **68**. The pin housing **110** is nominally 1.325 in. tall or long and 0.75 in. diameter with a wall thickness of 0.125 in., the inside bore length thus being approximately 1.2 in. and the inside or bore diameter in which the pin **102** slidably operates thereby being 0.5 in., thus setting a clearance between the pin body **104** outside diameter and the pin housing **110** inside diameter of about 0.01 in. $((0.5 \text{ in.} - 0.48 \text{ in.})/2)$, with the pin housing side wall opening **114** being approximately 0.625 in. tall and approximately 0.275 in. deep for access to and operable engagement with the pin undercut **106** by the handle tip **88**. And the locking holes **68** formed along the inner tube body **52** are nominally 0.5 in. wide or in diameter and 0.65 in. long, or slightly oval or oblong, allowing for approximately 0.01 in. clearance for the pin body **104** $((0.5 \text{ in.} - 0.48 \text{ in.})/2)$ widthwise and approximately 0.17 in. or about a sixth inch clearance lengthwise to again assist with the pin **102** seating within a respective locking hole **68** even while the outer and inner tubes **30**, **50** are in relative motion, with the holes **68** again nominally spaced 1 in. apart, center-to-center, along the inner tube body **52**, and its side wall **56** specifically, which would be the furthest a jack **J** could “fall” before the apparatus **20** locks in place. Relatedly, with the wall thicknesses of the outer and inner tube bodies **32**, **52** being 0.12 in. or nominally an eighth inch and with the diameter of the cylindrical pin body **104** being nominally a half inch, the effective shear strength of the pin body **104** at the interface between the outer and inner tube bodies **32**, **52**, or specifically the respective adjacent outer and inner tube side walls **36**, **56** where the pin body **104** is seated within a locking hole **68**, and the compressive load-bearing capacity of the eighth-inch-thick outer and inner tube bodies **32**, **52** themselves and of the opposite outer and inner tube jack cradles **42**, **62** that are also nominally an eighth inch thick as well, is such that the jack support apparatus **20** is rated at two (2) tons, with a factor of safety likely of two to six times. The outer tube sleeve **44** is nominally 0.375 in. outside diameter by 0.25 in. inside diameter and 7.25 in. long, while the inner tube rod **64** is nominally 0.188 in. diameter and 7.5 in. long, resulting in clearance therebetween of approximately 0.031 in. $((0.25 \text{ in.} - 0.188 \text{ in.})/2)$. The nominal thickness of the outer and inner tube stops **46**, **66** is 0.25 in., thus setting a widthwise or front-to-back clearance between the outer and inner tube bodies **32**, **52** of approximately 0.13 in. $(1.88 \text{ in.} - 1.5 \text{ in.} - 0.25 \text{ in.})$. And finally, regarding the handle **82**, the body **84** is nominally 4.25 in. long by 0.5 in. square or round, with the handle cross-hole **90** located approximately 2.75 in. from the proximal end or grip **86** and thus approximately 1.5 in. from the handle tip **88**, which tip **88** is

nominally 0.2 in. thick for seating in the 0.25 in. wide pin undercut **106**. Staying with the exemplary embodiment, it will be appreciated that the outer and inner tube bodies **32**, **52** may be extruded in longer sections and cut to length, with the hole **48** in the outer tube body **32** for installation of the pin housing **110** in forming the pin assembly **100** as well as any holes such as for installation of the outer tube stop **46** machined in the outer tube body **32** and then the pin housing **110**, the handle base **92**, and the end wall **40** defining the outer tube jack cradle **42** welded on the outer tube body **32** and the outer tube stop **46** fastened on the outer tube body **32** as by screws, with the outer body sleeve **44** being installed on the outer tube end wall **40** via welding or a screw-type fastener, and similarly with the pattern of spaced-apart locking holes **68** machined in the inner tube body **52** again along with any holes such as for installation of the inner tube stop **66**, and with the inner tube end wall **60** defining the inner tube jack cradle **62** welded on the inner tube body **52**, the inner tube stop **66** fastened on the inner tube body **52** as by screws, and the inner tube rod **64** being installed on the inner tube end wall **60** via welding or a screw-type fastener. It will be appreciated that all such fabrication steps may occur first in any appropriate order and then the jack support apparatus **20** may be assembled as by inserting the pin spring **120** and pin **102** into the pin housing **110** from within the outer tube body **32** via the hole **48**, securing the pin **102** in place by engaging the handle tip **88** with the pin undercut **106** through the pin housing side wall opening **114**, and then pivotally securing the handle **82** on the handle base **92** as through an inserted handle bolt or cross-pin **94**, thereby completing the operable assembly of the handle and pin assemblies **80**, **100** on the outer tube **30**, with all that then remains to complete assembly of the jack support apparatus **20** being to slide the tube spring **70** within the outer tube body **32** over the outer tube sleeve **44** and then mating the inner tube **50** with the outer tube **30** as by squeezing the handle **82** so as to lift or retract the locking pin **102** and sliding the inner tube body **52** within the outer tube body **32** while simultaneously sliding the inner tube rod **64** down through the tube spring **70** and the outer tube sleeve **44**, and then locking the apparatus **20** in any position as by releasing the handle **82** and sliding the inner tube **50** relative to the outer tube **30** until the pin body **104** enters and locks within one of the inner tube locking holes **68**, with the final step in preventing the inner tube **50** from disconnecting from the outer tube **30** under the influence of the tube spring **70** or otherwise being to secure the outer tube stop **46** on the outer tube body **32**. The biasing coil-type tube spring **70** is formed from 0.041 in. diameter 302 stainless steel wire having a spring rate of about 7.5 lbs./in. at its installed height that ranges from about 8 in. to 13 in., having a nominal length of 20 in. and diameter of 0.44 in., and the biasing pin spring **120** is formed from 0.045 in. diameter 302 stainless steel wire having a spring rate of about 19 lbs./in. at its installed height that ranges from about 0.3 in. to 0.5 in., having a nominal length of 0.75 in. and diameter of 0.48 in. and 3.3 active coils and 5.3 total coils including the closed ends. Those skilled in the art will again appreciate that a variety of configurations and materials of construction, whether now known or later developed, are possible according to aspects of the present invention, such that any particular configurations and materials employed in the jack support apparatus **20** and its various components and assemblies are to be understood as illustrative and non-limiting, though it will be further appreciated that in the exemplary hydraulic floor jack automotive context, the disclosed design is the preferred embodiment having attendant benefits in construction and use in such context as set forth herein. Even so, those skilled in the art will also appreciate that, for example, other locking mechanisms now known or later developed beyond the illustrated handle and pin assemblies **80**, **100** are possible according to aspects of the present invention, such as ratchet mechanisms and manual cross-pins. Accordingly, the locking pin **102** should be understood as potentially taking and so encompassing a variety of forms in selectively mechanically coupling the outer and inner tubes **30**, **50** so as to prevent their relative movement in temporarily locking or rigidly supporting a floor jack or the like.

(31) Turning now to FIGS. **8-10**, there are shown perspective views of the exemplary jack support apparatus **20** in three operational modes as used in connection with a conventional hydraulic floor

jack J such as being rated at 1.5 to 3 tons and having a lift or height range from 3.5 to 14 inches. First, as shown in FIG. 8, the hydraulic floor jack J is operated via its handle H to lift the arms M and thus the lift pad or cup C to a desired height, such as in lifting a vehicle V as shown and described below in connection with FIG. 11. Once the jack J is at the desired position, the jack support apparatus 20 in a collapsed configuration or, as shown, any intermediate, sufficiently short configuration can be positioned adjacent to or in engagement with the jack J such that either of the jack cradles 42, 62 is in contact with one of the jack axles A1, A2, or such that the entire apparatus 20, and particularly the opposite jack cradles 42, 62, is located between the two jack axles A1, A2. The apparatus 20 is shown oriented with the outer tube 30 down and so with the first end 22 of the apparatus 20 and thus the outer tube jack cradle 42 down or toward the axle A1 of the axled wheels W1 mounted on the jack base B opposite the swivel or castor wheels W2 and with the inner tube 50 up and so with the second end 24 of the apparatus 20 and thus the inner tube jack cradle 62 up or toward the axle A2 that pivotally supports the jack lift cup C. Those skilled in the art will appreciate that the apparatus 20 can just as easily be positioned with the first end 22 and outer tube 30 up and the second end 24 or inner tube 50 down, since the device is spring and not gravity assisted for its operation and the outer and inner tube jack cradles 42, 62 are identical or symmetrical. Notably, once the handle 82 is squeezed to lift the internal locking pin 102 (FIGS. 2, 3, 5 and 7) out of engagement with the inner tube 50, the inner tube 50 will be free to slide relative to the outer tube 30 under the biasing effect of the tube spring 70 (FIGS. 2 and 7), such that it is preferable that the inner tube jack cradle 62 already be in contact with the appropriate structure of the jack J, the cup axle A2 in the illustrated embodiment, so that the inner tube 50 and its cradle 62 do not slam into any part of the jack J structure unintentionally. Thus, as illustrated in FIG. 8, the inner tube jack cradle 62 can first be nested against the jack cup axle A2 before the handle 82 is actuated to unlock the jack support apparatus 20. Then, with reference to FIG. 9, when the handle 82 is squeezed or actuated so as to unseat the locking pin 102 and unlock the apparatus 20 so that the outer and inner tubes 30, 50 can slide relative to each other, the apparatus 20 can be manipulated in a controlled extension as by simply holding the handle 82 in while also grasping the outer tube 30 and “stretching” or lengthening the apparatus 20 as by shifting the outer tube 30 down until the outer tube jack cradle 42 seats or nests on the wheel axle A1, it being appreciated that at all times the biasing effect of the internal tube spring 70 will keep the inner tube jack cradle 62 nested in contact with the cup axle A2. At that point, with the jack support apparatus 20 so extended that both the outer and inner tube jack cradles 42, 62 are in contact with the jack J structure, here the respective wheel and cup axles A1, A2, the handle 82 may be released. It will be appreciated that unless the extended configuration or length of the apparatus 20, and thus the particular height or position of the jack J, just so happens to position the locking pin 102 of the pin assembly 100 adjacent to one of the inner tube locking holes 68 (FIGS. 1, 2, and 4-7), the handle 82 will remain in its actuated position as shown in FIG. 9. Even so, it will also again be appreciated that the outward biasing effect of the tube spring 70 will keep the outer and inner tubes 30, 50 extended and the outer and inner tube jack cradles 42, 62 nested in contact with the respective wheel and cup axles A1, A2 and thus the jack support apparatus 20 in place on the jack J as shown in FIG. 9, once more, even without the apparatus 20 yet being “locked” as by pin 102 clicking into a hole 68 in the inner tube 50. Then, referring now to FIG. 10, with slight twisting of the jack handle H, shown in this example as counterclockwise by the related arrow, the jack arms M and thus the lift cup C and related lift cup axle A2 will be slightly and slowly lowered causing the inner tube 50 to slide toward or inwardly relative to the outer tube 30 until indeed the locking pin 102 is aligned with the next closest inner tube locking hole 68 and snaps into engagement therewith under the biasing effect of the pin spring 110 (FIGS. 2, 3 and 7), thus locking the jack support apparatus 20 in place as a mechanical member rigidly supporting the lift cup C and arms M in the event of a hydraulic or other failure of the jack J. Those skilled in the art will appreciate that with the exemplary jack support apparatus 20 according to aspects of the present invention and its nominal

one-inch spacing of the inner tube locking holes **68**, one inch is effectively the furthest the jack **J** would have to be lowered or the lift cup **C** and axle **A2** would have to travel in order to lock the apparatus **20** in place and thus provide a “fail-safe” for the hydraulic floor jack **J**. Relatedly, if an operator even forgot to perform the last step illustrated in FIG. **10** of rotating the handle **H** slightly to lower the jack **J** until the pin **102** clicked into a hole **68** as evidenced by the handle **82** shifting outwardly to its at-rest, non-actuated position as shown in FIGS. **8** and **10** and so locking the jack support apparatus **20**, thus leaving the jack **J** and apparatus **20** in the configuration as illustrated in FIG. **9**, it will be appreciated that even so a failure of the jack **J** would be “caught” by the apparatus **20** due to the pin **102** engaging the next locking hole **68** under the effect of the pin spring **120** even as the jack **J** and thus the inner tube **50** was “falling” relative to the outer tube **30**, thus still preventing the jack **J** from moving or collapsing more than basically one inch even if the hydraulic cylinder or related valve of the jack **J** completely failed and the jack support apparatus **20** was not previously locked. Thus, it will be appreciated that the jack support apparatus **20** is a compact and easy-to-use tool that provides a “fail-safe” for a hydraulic floor jack **J** and thus numerous advantages in use.

(32) Briefly, then, with reference to FIG. **11**, there is shown an exemplary jack support apparatus **20** in use with a hydraulic floor jack **J** in lifting or supporting at least a portion of a vehicle **V**. The jack **J** in a lowered position is first located under the vehicle **V** as by manipulating or rolling it on its axled and castor wheels **W1**, **W2** operably installed on the jack base **B** employing the jack handle **H** or otherwise. Once the jack **J** is in position with the lift cup **C** adjacent to a jack point **P** on the underside of the vehicle **V**, the jack **J** is operated in conventional fashion as by pumping the handle **H** to raise the arms **M** and thus the lift cup **C** into contact with the jack point **P**, with continued pumping of the handle **H** and raising of the jack **J** and particularly the jack lift cup **C** thus raising or “jacking up” the vehicle **V** to a desired height. Then, with the jack **J** so configured, as shown, and as described above in connection with FIGS. **8-10**, the jack support apparatus **20** is simply configured at an appropriate length to position it between the wheel and cup axles **A1**, **A2** of the jack **J**, its handle **82** is actuated to allow the apparatus **20** to extend until the opposite jack cradles **42**, **62** are nested against the respective wheel and cup axles **A1**, **A2**, the apparatus handle **82** is released, and as needed the jack handle **H** is rotated or manipulated to slightly lower the jack **J** until the apparatus locking pin **102** seats in a hole **68** in the apparatus inner tube **50** so as to lock the apparatus **20** and thus the jack **J**, thereby effectively converting such a conventional hydraulic floor jack **J** into a jack stand and, again, whether or not the final step of slightly lowering the jack **J** to lock the apparatus **20** is performed, a “fail-safe” is still provided. Accordingly, those skilled in the art will appreciate that the exemplary jack support apparatus **20** according to aspects of the present invention is configured as a compact and easy-to-use tool that provides rigid mechanical support to a hydraulic floor jack **J** under load in the event of a failure of the jack **J**, thereby more safely, quickly, and effectively supporting a vehicle **V** especially with limited jack points and/or limited space within which to work. Once again, it will be appreciated that the jack support apparatus **20** can take other forms or configurations or employ other components or mechanisms, materials, and dimensions to suit particular contexts without departing from the spirit and scope of the invention, as will be appreciated from the following discussion of various alternative exemplary embodiments as shown in FIGS. **12-19**, such that the exemplary apparatus **20** of FIGS. **1-11** is to be understood as illustrative and non-limiting.

(33) Referring next to FIGS. **12** and **13**, there are shown front and back perspective views of an alternative exemplary embodiment of a jack support apparatus **20** according to aspects of the present invention. The apparatus **20** again comprises, in the exemplary embodiment, an outer tube **30**, an inner tube **50** telescopically or slidably received in the outer tube **30**, and a handle assembly **80** and a pin assembly **100** that cooperate to selectively adjust the overall height of the apparatus **20** in use. Once more, an outer tube jack cradle **42** at a first end **22** of the apparatus **20** and an inner tube jack cradle **62** at an opposite second end **24** of the apparatus **20** define the points of

mechanical engagement with features of a hydraulic floor jack J as explained above in connection with the first exemplary embodiment as illustrated in use in FIGS. 8-11. Essentially, in the alternative exemplary embodiment of FIGS. 12 and 13, the jack support apparatus 20 is in all respects configured as in the first exemplary embodiment particularly shown in FIGS. 1 and 2, except that here a second pin or particularly a cross-pin 122 is employed as a further “fail-safe” or additional “factor of safety” for the apparatus 20 in selectively locking or fixing the positions of the outer and inner tubes 30, 50 relative to each other and thus the overall length of the apparatus 20 in then “locking” the floor jack J. In a bit more detail, and by way of illustration and not limitation, such cross-pin 122 has a cross-pin body 124 configured to pass through cross-holes 49 formed in opposite front and back walls 37, 39 of the outer tube body 32 and selectively through a pair of cross-holes 69 similarly formed in opposite front and back walls 57, 59 of the inner tube body 52 so as to again further lock the position of the outer tube 30 relative to the inner tube 50. As illustrated, such cross-pin 122 and specifically its body 124 is a basic solid annular rod that may be manually inserted or pushed through the aligned cross-holes 69 of the outer and inner tubes 30, 50 when the apparatus 20 is in a desired position. Particularly, the apparatus 20 and floor jack J would be operated as described herein, up to the point of the primary locking pin 102 seating in a hole 68 in the inner tube body 52 under the biasing effect of the pin spring 120 so as to lock the apparatus 20 and thus the jack J, whether or not involving slightly lowering the jack J to lock the apparatus 20 as by aligning the primary locking pin 102 with a hole 68 in the inner tube side wall 56, thereby effectively converting such a conventional hydraulic floor jack J into a jack stand, and thereafter the secondary cross-pin 122 would simply be inserted through the outer tube body 32 and the corresponding aligned inner tube cross-holes 69 to further lock the relative position of the outer and inner tubes 30, 50 and thus the jack support apparatus 20 as a still further “fail-safe,” such that even were the primary locking pin 102 to fail, or more likely were it to have potentially failed but for the additional load bearing capacity of the cross-pin 122, the jack support apparatus 20 is further rendered safe and effective under potentially even greater loads, all of course assuming failure of the hydraulic floor jack J itself. It will be appreciated by those skilled in the art that the locations of the inner tube cross-holes 69 along the inner tube body 52 and particularly its front and back walls 57, 59 is such that for any given position of the inner tube 50 relative to the outer tube 30 as by the primary locking pin 102 engaging a side hole 68 of the inner tube 50, the inner tube cross-holes 69 are thereby similarly aligned with the cross-holes 49 formed in the outer tube 30 and thus the cross-pin 122. While as illustrated in FIGS. 12 and 13 the cross-pin 122 is inserted from the back of the apparatus 20 or starts by passing through the back walls 39, 59 of the outer and inner tube bodies 32, 52, it will be appreciated that the cross-pin 122 can just as easily be inserted from the front. By way of further illustration and not limitation, the cross-pin body 124 may be a nominally three-eighths inch (0.375 in.) diameter mild steel (e.g., 4130 steel) rod, though again, other sizes and materials of the cross-pin 122 and configurations in terms of its location on the apparatus 20 are possible according to aspects of the present invention without departing from its spirit and scope. Indeed, the location of the cross-pin 122 as shown near the top of the outer tube body 32 is to be understood as exemplary, though it will be appreciated that the cross-pin 122 being shifted to one side rather than centered on the outer tube front and back walls 37, 39 allows the cross-pin 122 to clear the central internal biasing tube spring 70 and any related outer tube sleeve 44 and inner tube rod 64.

(34) Turning to FIGS. 14 and 15, there are shown full and cross-sectional perspective views of a further alternative exemplary embodiment of a jack support apparatus 20 according to aspects of the present invention. The apparatus 20 again comprises an outer tube 30, an inner tube 50 telescopically or slidably received in the outer tube 30, and an outer tube jack cradle 42 at a first end 22 of the apparatus 20 and an inner tube jack cradle 62 at an opposite second end 24 of the apparatus 20 that together define the points of mechanical engagement with features of a hydraulic floor jack J, though here the apparatus 20 being without any handle assembly 80 and pin assembly

100 that cooperate to selectively adjust and lock the overall height of the apparatus **20** or any internal biasing tube spring **70** that shifts the outer and inner tubes **30**, **50** apart during use, instead the apparatus **20** simply having a cross-pin **122** for manually and mechanically locking the relative position of the outer and inner tubes **30**, **50** and thus setting the overall length of the apparatus **20**. Once more, the cross-pin **122** has a cross-pin body **124** configured to pass through cross-holes **49** formed in opposite front and back walls **37**, **39** of the outer tube body **32** and selectively through a pair of cross-holes **69** similarly formed in opposite front and back walls **57**, **59** of the inner tube body **52** so as to lock the position of the outer tube **30** relative to the inner tube **50**. As illustrated, such cross-pin **122** and specifically its body **124** is a basic solid annular rod that may be manually inserted or pushed through the aligned cross-holes **69** of the outer and inner tubes **30**, **50** when the apparatus **20** is in a desired position; here, the cross-pin **122** as shown as inserted from the front or as first passing through the outer and inner tube front walls **37**, **57**, though it will again be appreciated that the cross-pin **122** may be installed from either direction. It will also be appreciated that the cross-pin **122** and related cross-holes **69** along the outer and inner tube bodies **32**, **52** may be positioned in a variety of locations, particularly laterally since in the alternative exemplary embodiment there are no internal components that the cross-pin **122** must clear, though being somewhat centered on the front and back walls **37**, **39**, **57**, **59** as shown encourages even or symmetrical operation and loading. In use of the alternative exemplary jack support apparatus **20** of FIGS. **14** and **15**, as illustrated in FIG. **8**, the floor jack **J** would be operated as normally and then once at a desired height, the apparatus **20** in a collapsed or any intermediate, sufficiently short configuration as by having the cross-pin **122** initially removed can be positioned adjacent to or in engagement with the jack **J** such that either of the jack cradles **42**, **62** is in contact with one of the jack axles **A1**, **A2**, or such that the entire apparatus **20**, and particularly the opposite jack cradles **42**, **62**, is located between the two jack axles **A1**, **A2**. Rather than an internal spring then biasing the outer and inner tubes **30**, **50** apart so as to bring the opposite jack cradles **42**, **62** into contact with or adjacent to the respective jack axles **A1**, **A2**, the two tubes **30**, **50** would be manually telescoped until the jack cradles **42**, **62** are each as close as possible to the respective jack axles **A1**, **A2** while aligning the inner tube cross-holes **69** with the outer tube cross-holes **49** to allow for insertion therethrough of the cross-pin **122** to thus fix the length of the apparatus **20** and provide a “fail-safe” for the jack **J** as herein described. The jack **J** and the jack support apparatus **20** may thus remain in such operable configuration, or once the cross-pin **122** has been installed as shown in FIGS. **14** and **15**, to fully seat the jack axles **A1**, **A2** in the respective opposite jack cradles **42**, **62**, the jack **J** may be lowered slightly as needed.

(35) Referring briefly to FIGS. **16** and **17**, there are shown full and cross-sectional perspective views of a still further alternative exemplary embodiment of a jack support apparatus **20** according to aspects of the present invention, again comprising an outer tube **30**, an inner tube **50** telescopically or slidably received in the outer tube **30**, and an outer tube jack cradle **42** at a first end **22** of the apparatus **20** and an inner tube jack cradle **62** at an opposite second end **24** of the apparatus **20** that together define the points of mechanical engagement with features of a hydraulic floor jack **J**, here the apparatus **20** having two opposed handle assemblies **80** and pin assemblies **100** that cooperate to selectively adjust and lock the overall height of the apparatus **20**, rather than one such handle assembly **80** and related pin assembly **100** as in the exemplary embodiment of FIGS. **1-11** or one such handle assembly **80** and related pin assembly **100** along with a secondary cross-pin **122** as in the alternative exemplary embodiment of FIGS. **12** and **13** or just a cross-pin **122** as in the further alternative exemplary embodiment of FIGS. **14** and **15**. Accordingly, it will be appreciated that the still further alternative exemplary embodiment of FIGS. **16** and **17** is in all respects like that of FIGS. **1-11**, including the internal biasing tube spring **70** that shifts the outer and inner tubes **30**, **50** apart during use, here simply adding a second set of handle and pin assemblies **80**, **100** to the opposite side of the apparatus **20** to effectively double the load capacity of the apparatus **20**. More particularly, the two sets of handle and pin assemblies **80**, **100** are

operably installed on opposite outer tube side walls **36, 38** and thus the inner tube holes **68** are correspondingly formed in the respective opposite inner tube side walls **56, 58**. Those skilled in the art will further appreciate that such an alternative configuration of a jack support apparatus **20** according to aspects of the present invention still has the advantages of being operated by one hand, as by squeezing opposite handles **86** with or between a user's thumb and fingers, and having both the expansion of the apparatus **20** and the engagement of the opposite pins **102** within opposite respective inner tube holes **68** being spring-assisted and thus somewhat automated, while now again effectively being doubled in its load bearing capacity, for example. It will be appreciated that a variety of other such configurations and combinations of locking pin(s) **102** and/or cross-pin(s) are possible according to aspects of the present invention without departing from its spirit and scope.

(36) Turning finally to FIGS. **18** and **19**, there are shown full and cross-sectional perspective views of a still further alternative exemplary embodiment of a jack support apparatus **20** according to aspects of the present invention, again comprising an outer tube **30**, an inner tube **50** telescopically or slidably received in the outer tube **30**, and an outer tube jack cradle **42** at a first end **22** of the apparatus **20** and an inner tube jack cradle **62** at an opposite second end **24** of the apparatus **20** that together define the points of mechanical engagement with features of a hydraulic floor jack **J**. Here, the apparatus **20** has a pair of opposite lever assemblies **130** somewhat analogous to the handle assembly **80** and thus to the alternative exemplary embodiment of FIGS. **16** and **17** having two such opposed handle assemblies **80**. Spaced-apart holes **68** are again formed along the side walls **56, 58** of the inner tube body **52**, here once again on opposite short sides, each such hole **68** configured to be selectively engaged by a tip **138** of a pivoting lever **132** operably installed as part of a lever assembly **130** on the respective outer tube side walls **36, 38** in order to fix the position of the inner tube **50** relative to the outer tube **30**. In more detail, each lever assembly **130** comprises a lever **132** having a lever body **134** that is pivotally installed on a lever base **142** via a lever cross-pin **144**, with the lever body **134** having a proximal lever grip **136** for selectively grasping, pressing, squeezing, or otherwise operating the lever **132** of the lever assembly **130** and a distal lever tip **138** formed at angle to the lever body **134** on an end opposite of the lever grip **136** and relatively closer to the lever cross-pin **144** pivot point, with the lever tip **138** so configured as to operate somewhat laterally within a corresponding outer tube hole **48** formed in the respective outer tube side wall **36, 38**, whereby squeezing or otherwise shifting the lever grip **136** inwardly or toward the respective outer tube side wall **36, 38** serves to shift the opposite distal lever tip **138** operating within the outer tube hole **48** outwardly or away from the respective outer and inner tube side walls **36, 38, 56, 58** and thus out of any engagement within a corresponding inner tube hole **68** so as to thus “unlock” the apparatus **20** and allow for relative movement between the outer and inner tubes **30, 50**. Whereas releasing the lever grips **136** causes the lever grips **136** or the proximal ends of the lever bodies **134** to shift outwardly or away from the respective outer tube side wall **36, 38** under the biasing effect of the compression spring **150** operably positioned between each lever grip **136** and the respective outer tube side wall **36, 38** so as to thereby cause each distal lever tip **138** to shift inwardly or toward the respective outer and inner tube side walls **36, 38, 56, 58** and thus through the respective outer tube hole **48** and into engagement within a corresponding inner tube hole **68** so as to thus “lock” the apparatus **20**, thereby setting the overall length of the apparatus **20** in use, an exemplary intermediate position between fully extended and fully retracted positions being shown. It will be appreciated that with the lever tips **138** biased inwardly so as to force the tips **138** toward the inner tube body **52** and into a corresponding hole **68** of the inner tube **50** once aligned, the default is for the apparatus **20** to lock in position as in other exemplary embodiments shown and described herein, though it will be appreciated that such is not necessarily the case. In any event, it will be further appreciated that the lever tip **138** thus functions as or defines the pin **102** as in other exemplary embodiments. Relatedly, in the alternative exemplary embodiment of FIGS. **18** and **19**, there is not shown any internal biasing spring or the like to bias

the outer and inner tubes **30**, **50** apart, such that when the apparatus **20** is released as by squeezing or operating each lever assembly **130** this allows the inner tube **50** to manually slide or move freely relative to the outer tube **30**, or specifically the inner tube body **52** relative to the outer tube body **32**, though again, an internal or other biasing component or assembly may be incorporated in the apparatus **20** as well without departing from the spirit and scope of the invention. Those skilled in the art will appreciate that other such arrangements of the one or more lever assembly **130**, alone or in combination with other assemblies, including but not limited to the exemplary handle and pin assemblies **80**, **100**, or other locking features, including but not limited to the cross-pin **122**, may be employed according to aspects of the present invention. And even with the exemplary lever assembly **130**, it will be appreciated that while two such opposed assemblies **130** are illustrated, one or even three or more may instead be employed. And once again, any such locking mechanisms as disclosed herein may be modified or combined in forming a jack support apparatus **20** according to aspects of the present invention without departing from its spirit and scope. By way of further illustration and not limitation, a cross-pin **122** as shown in FIGS. **12-15** may be employed in the alternative exemplary apparatus of FIGS. **18** and **19**, as well as the alternative exemplary apparatus of FIGS. **16** and **17**. Accordingly, all such exemplary configurations of a jack support apparatus **20** according to aspects of the present invention are to be understood as illustrative and non-limiting.

(37) Aspects of the present specification may also be described as follows:

(38) 1. A jack support apparatus for operably engaging and selectively locking a hydraulic floor jack having a wheel axle and a cup axle, the apparatus comprising an outer tube having an outer tube body comprising at least one outer tube wall with an outer tube hole formed in the outer tube wall, an outwardly-extending outer tube jack cradle, and an outer tube opening opposite the outer tube end wall, the outer tube jack cradle configured to selectively engage one of the wheel axle and the cup axle, an inner tube having an inner tube body comprising at least one inner tube wall with a plurality of spaced-apart inner tube holes formed in the inner tube wall and an outwardly-extending inner tube jack cradle, the inner tube body slidably received within the outer tube body through the outer tube opening with the inner tube wall adjacent to the outer tube wall, the inner tube jack cradle configured to selectively engage one of the wheel axle and the cup axle, the outer tube jack cradle and the inner tube jack cradle being opposite and symmetrical, and a pin operable through the outer tube hole for selectively engaging any of the plurality of inner tube holes, wherein selective operation of the pin by shifting the pin away from the inner tube disengages the pin from any of the plurality of inner tube holes and allows the inner tube to shift relative to the outer tube as by the inner tube body sliding within the outer tube body, and further wherein selective operation of the pin by shifting the pin toward the inner tube engages the pin in one of the plurality of inner tube holes as the inner tube shifts relative to the outer tube as by the inner tube body sliding within the outer tube body to align the outer tube hole with a select one of the plurality of inner tube holes to prevent further relative movement between the outer tube and the inner tube, whereby the apparatus is configured to temporarily form a rigid linkage between the wheel and cup axles upon engagement therebetween by the outer tube and inner tube jack cradles to effectively lock the jack against further downward movement.

(39) 2. The apparatus of embodiment 1 further comprising a pin assembly having a pin housing located on the outer tube wall about the outer tube hole, the pin slidably inserted within the pin housing, the pin assembly further having a pin spring operably seated within the pin housing so as to bias the pin toward the inner tube through the outer tube wall.

(40) 3. The apparatus of embodiment 1 or embodiment 2 wherein the pin comprises a pin body having an intermediate pin undercut.

(41) 4. The apparatus of embodiment 3 wherein the pin body is annular and the pin undercut is circumferential.

(42) 5. The apparatus of any of embodiments 2-4 wherein the pin housing is formed having a pin housing side wall opening.

- (43) 6. The apparatus of embodiment 5 further comprising a handle assembly having a handle pivotally mounted on a handle base located on the outer tube body, the handle having a handle body comprising a handle grip, an opposite handle tip, and an intermediate handle cross-hole for pivotally-mounting the handle on the handle base, the handle tip operably engaging the pin undercut through the pin housing side wall opening, whereby selective actuation of the handle by shifting the handle grip toward the outer tube lifts the handle tip and the pin away from the inner tube against the biasing effect of the pin spring so as to disengage the pin body from any of the plurality of inner tube holes, and further whereby selective release of the handle by releasing the handle grip allows the pin to slidably shift toward the inner tube under the biasing effect of the pin spring so as to engage the pin body in one of the plurality of inner tube holes as the inner tube is shifted relative to the outer tube as by the inner tube body sliding within the outer tube body until the pin body enters one of the plurality of inner tube holes.
- (44) 7. The apparatus of embodiment 6 wherein the handle is approximately 4.25 inches long from the handle grip to the handle tip.
- (45) 8. The apparatus of embodiment 6 or embodiment 7 wherein the handle cross-hole is approximately 1.25 inches from the handle tip.
- (46) 9. The apparatus of any of embodiments 6-8 wherein the distance from the handle cross-hole to the handle tip is no more than 40% of the overall length of the handle from the handle grip to the handle tip.
- (47) 10. The apparatus of any of embodiments 6-9 wherein a handle cross-pin is inserted through the handle cross-hole to pivotally mount the handle on the handle base.
- (48) 11. The apparatus of any of embodiments 6-10 wherein the handle tip is approximately 0.2 inch thick.
- (49) 12. The apparatus of any of embodiments 6-11 wherein the handle is aluminum.
- (50) 13. The apparatus of any of embodiments 6-12 comprising two opposed pin assemblies and respective two opposed handle assemblies, whereby relative movement between the outer tube and the inner tube is further prevented.
- (51) 14. The apparatus of any of embodiments 3-13 wherein the pin body is annular having a diameter of approximately 0.5 inch.
- (52) 15. The apparatus of embodiment 14 wherein the pin body diameter is 0.48 inch.
- (53) 16. The apparatus of any of embodiments 3-15 wherein the pin undercut is approximately 0.15 inch deep.
- (54) 17. The apparatus of any of embodiments 3-16 wherein the pin body has a pin head proximal of the pin undercut for engagement with the pin spring.
- (55) 18. The apparatus of any of embodiments 3-17 wherein the width of the pin body is no more than 85% of the length of the inner tube hole.
- (56) 19. The apparatus of any of embodiments 5-18 wherein the pin housing further comprises a pin housing end wall opposite the outer tube hole, the pin spring seating between the pin and the pin housing end wall.
- (57) 20. The apparatus of embodiment 19 wherein the pin housing end wall is formed with a pin housing end wall opening.
- (58) 21. The apparatus of embodiment 19 or embodiment 20 wherein the pin housing end wall and the pin housing side wall are approximately 0.12 inch thick.
- (59) 22. The apparatus of any of embodiments 2-21 wherein the pin housing is steel.
- (60) 23. The apparatus of embodiment 22 wherein the pin housing is welded onto the outer tube side wall.
- (61) 24. The apparatus of any of embodiments 2-23 wherein the pin spring has a free length of approximately 0.75 in. and an outside diameter of approximately 0.48 in. and a spring rate of approximately 19 lbs./in. at an installed height ranging from approximately 0.3 to 0.5 in.
- (62) 25. The apparatus of any of embodiments 1-24 further comprising a lever assembly having a

lever pivotally mounted on a lever base located on the outer tube body, the lever having a lever body comprising a lever grip, an opposite lever tip, and an intermediate lever cross-pin for pivotally-mounting the lever on the lever base, the lever tip selectively operably engaging one of the plurality of inner tube holes through the outer tube hole, the lever with lever tip thereby defining the pin, whereby selective actuation of the lever by shifting the lever grip toward the outer tube lifts the lever tip away from the inner tube against the biasing effect of a lever spring seated between the lever grip and the outer tube body so as to disengage the lever tip from any of the plurality of inner tube holes, and further whereby selective release of the lever by releasing the lever grip allows the lever tip to shift toward the inner tube under the biasing effect of the lever spring so as to engage the lever tip in one of the plurality of inner tube holes as the inner tube is shifted relative to the outer tube as by the inner tube body sliding within the outer tube body until the lever tip enters one of the plurality of inner tube holes.

(63) 26. The apparatus of embodiment 25 comprising two opposed lever assemblies, whereby relative movement between the outer tube and the inner tube is further prevented.

(64) 27. The apparatus of embodiment 25 or embodiment 26 wherein the lever is steel.

(65) 28. The apparatus of any of embodiments 1-27 further comprising a tube spring operable between the outer tube body and the inner tube body to bias the outer tube and the inner tube apart.

(66) 29. The apparatus of embodiment 28 wherein the tube spring is installed within the outer and inner tube bodies operable between an outer tube end wall formed on the outer tube opposite the outer tube opening and an inner tube end wall formed on the inner tube opposite an inner tube opening.

(67) 30. The apparatus of embodiment 29 wherein the outer tube end wall and the outer tube jack cradle are integral and the inner tube end wall and the inner tube jack cradle are integral.

(68) 31. The apparatus of embodiment 29 or embodiment 30 wherein the outer and inner tube end walls and the outer and inner tube jack cradles are welded onto the respective outer and inner tube bodies.

(69) 32. The apparatus of any of embodiments 29-31 further comprising an outer tube sleeve installed on the outer tube end wall so as to extend within the outer tube body toward the outer tube opening, an inner tube opening formed in the inner tube body opposite the inner tube end wall, and an inner tube rod installed on the inner tube end wall so as to extend within the inner tube body toward the inner tube opening, the inner tube rod slidably received within the outer tube sleeve as the inner tube body is slidably received within the outer tube body, wherein the tube spring is installed about the outer tube sleeve and the inner tube rod through the outer tube and inner tube openings, whereby the outer tube sleeve and inner tube rod provide lateral stability for the tube spring.

(70) 33. The apparatus of embodiment 32 wherein the outer tube sleeve is approximately 0.25 inch in inside diameter and the inner tube rod is approximately 0.188 inch in outside diameter.

(71) 34. The apparatus of embodiment 32 or embodiment 33 wherein the outer tube sleeve and the inner tube rod are approximately 7.5 inches long.

(72) 35. The apparatus of any of embodiments 29-34 wherein the outer and inner tube end walls are approximately 0.125 inch thick.

(73) 36. The apparatus of any of embodiments 28-35 wherein the tube spring has a free length of approximately 20 in. and an outside diameter of approximately 0.44 in. and a spring rate of approximately 7.5 lbs./in. at an installed height ranging from approximately 8 to 13 in.

(74) 37. The apparatus of any of embodiments 1-36 further comprising an outer tube stop installed on the outer tube body proximal the outer tube opening and an inner tube stop installed on the inner tube body proximal an inner tube opening formed in the inner tube body opposite the inner tube end wall, wherein the outer tube and inner tube stops cooperate to prevent the inner tube body from slidably disengaging from the outer tube body.

(75) 38. The apparatus of embodiment 37 wherein the outer tube and inner tube stops are

approximately 0.25 inch thick.

(76) 39. The apparatus of any of embodiments 1-38 further comprising an outer tube cross-hole formed in the outer tube wall offset from the outer tube hole, a plurality of spaced-apart inner tube cross-holes formed in the inner tube wall offset from the plurality of inner tube holes, and a cross-pin configured to be selectively inserted through the outer tube cross-hole and an aligned one of the plurality of spaced-apart inner tube cross-holes, whereby relative movement between the outer tube and the inner tube is further prevented.

(77) 40. The apparatus of embodiment 39 wherein the cross-pin is steel.

(78) 41. The apparatus of embodiment 39 or embodiment 40 wherein the cross-pin is approximately 0.375 inch thick.

(79) 42. The apparatus of any of embodiments 1-41 wherein the outer and inner tube jack cradles are approximately 0.125 inch thick.

(80) 43. The apparatus of any of embodiments 1-42 wherein the outer and inner tube bodies have a rectangular profile, whereby the at least one outer tube wall defines opposite outer tube side walls, an outer tube front wall, and an opposite outer tube back wall and the at least one inner tube wall defines opposite inner tube side walls, an inner tube front wall, and an opposite inner tube back wall.

(81) 44. The apparatus of embodiment 43 wherein the outer tube body is approximately 1 inch by 2 inch in outer profile with a wall thickness of approximately 0.12 inch, whereby the outer tube body is approximately 0.88 inch by 1.88 inch in inner profile.

(82) 45. The apparatus of embodiment 44 wherein the inner tube body is approximately 0.75 inch by 1.5 inch in outer profile with a wall thickness of approximately 0.12 inch, resulting in a lateral clearance between the outer and inner tube bodies of approximately 0.065 inch.

(83) 46. The apparatus of any of embodiments 1-42 wherein the outer and inner tube bodies have an annular cross-section, whereby the at least one outer tube wall and the at least one inner tube wall are both annular.

(84) 47. The apparatus of any of embodiments 1-46 wherein the outer and inner tube bodies are approximately 7.5 inches long.

(85) 48. The apparatus of any of embodiments 1-47 wherein each of the plurality of inner tube holes has a width of approximately 0.5 inch and a length of approximately 0.65 inch.

(86) 49. The apparatus of any of embodiments 1-48 wherein the outer and inner tube bodies are steel.

(87) 50. A method of employing a jack support apparatus as defined in any one of embodiments 1-49, the method comprising the steps of positioning the apparatus adjacent to the jack between the wheel axle and the cup axle when the jack is in a raised position, shifting the apparatus such that the inner tube jack cradle is in contact with one of the wheel axle and the cup axle, retracting the pin so as to be disengaged from any of the plurality of inner tube holes to allow relative movement between the outer tube and the inner tube, sliding the outer tube body relative to the inner tube body so as to extend the apparatus until the outer tube jack cradle is in contact with one of the wheel axle and the cup axle, and inserting the pin so as to engage one of the plurality of inner tube holes to prevent relative movement between the outer tube and the inner tube.

(88) 51. The method of embodiment 50 comprising the further step, prior to the step of positioning the apparatus adjacent to the jack, of setting the length of the apparatus shorter than the distance between the wheel axle and the cup axle based on the raised position of the jack.

(89) 52. The method of embodiment 51 wherein the step of setting the length of the apparatus comprises retracting the pin so as to be disengaged from any of the plurality of inner tube holes, sliding the inner tube body relative to the outer tube body, and reinserting the pin into an inner tube hole to lock the apparatus at a desired length.

(90) 53. The method of any of embodiments 50-52 wherein the step of retracting the pin comprises squeezing the pivotable handle inwardly to lift the pin outwardly away from the inner tube.

(91) 54. The method of any of embodiments 50-53 comprising the further step, after the step of sliding the outer tube body relative to the inner tube body, of releasing the handle to allow the pin to shift inwardly toward the inner tube.

(92) 55. The method of embodiment 54 comprising the further step, after the step of releasing the handle, of slightly lowering the jack to cause the inner tube body to slide inwardly relative to the outer tube body until the pin is positioned adjacent to and may then enter an inner tube hole, wherein the apparatus and thereby the jack is locked.

(93) 56. The method of any of embodiments 50-55 comprising the further step, after the step of inserting the pin so as to engage one of the plurality of inner tube holes, of inserting a cross-pin through outer tube cross-holes formed in the outer tube body and aligned inner tube cross-holes of a plurality of spaced-apart inner tube cross-holes formed in the inner tube body to further prevent relative movement between the outer tube and the inner tube.

(94) 57. The method of any of embodiments 50-56 wherein the step of retracting the pin further comprises configuring the pin as a lever tip and squeezing a pivotable lever inwardly to lift the lever tip outwardly away from the inner tube.

(95) 58. A kit comprising a jack support apparatus as defined in any one of embodiments 1-49.

(96) 59. The kit of embodiment 58, further comprising instructional material.

(97) 60. The kit of embodiment 59, wherein the instructional material provides instructions on how to perform the method as defined in any one of embodiments 50-57.

(98) 61. Use of a jack support apparatus as defined in any one of embodiments 1-49 to selectively lock the jack against further downward movement.

(99) 62. The use of embodiment 61, wherein the use comprises a method as defined in any one of embodiments 50-57.

(100) In closing, regarding the exemplary embodiments of the present invention as shown and described herein, it will be appreciated that a jack support apparatus is disclosed and configured for selectively locking a hydraulic floor jack against further downward movement. Because the principles of the invention may be practiced in a number of configurations beyond those shown and described, it is to be understood that the invention is not in any way limited by the exemplary embodiments, but may take numerous forms without departing from the spirit and scope of the invention. It will also be appreciated by those skilled in the art that the present invention is not limited to the particular geometries and materials of construction disclosed, but may instead entail other functionally comparable structures or materials, now known or later developed, without departing from the spirit and scope of the invention.

(101) Certain embodiments of the present invention are described herein, including the best mode known to the inventor(s) for carrying out the invention. Of course, variations on these described embodiments will become apparent to those of ordinary skill in the art upon reading the foregoing description. The inventor(s) expect skilled artisans to employ such variations as appropriate, and the inventor(s) intend for the present invention to be practiced otherwise than specifically described herein. Accordingly, this invention includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described embodiments in all possible variations thereof is encompassed by the invention unless otherwise indicated herein or otherwise clearly contradicted by context.

(102) Groupings of alternative embodiments, elements, or steps of the present invention are not to be construed as limitations. Each group member may be referred to and claimed individually or in any combination with other group members disclosed herein. It is anticipated that one or more members of a group may be included in, or deleted from, a group for reasons of convenience and/or patentability. When any such inclusion or deletion occurs, the specification is deemed to contain the group as modified thus fulfilling the written description of all Markush groups used in the appended claims.

(103) In some embodiments, the numbers expressing quantities of components or ingredients,

properties such as dimensions, weight, concentration, reaction conditions, and so forth, used to describe and claim certain embodiments of the inventive subject matter are to be understood as being modified in some instances by terms such as “about,” “approximately,” or “roughly.”

Accordingly, in some embodiments, the numerical parameters set forth in the written description and attached claims are approximations that can vary depending upon the desired properties sought to be obtained by a particular embodiment. In some embodiments, the numerical parameters should be construed in light of the number of reported significant digits and by applying ordinary rounding techniques. Notwithstanding that the numerical ranges and parameters setting forth the broad scope of some embodiments of the inventive subject matter are approximations, the numerical values set forth in any specific examples are reported as precisely as practicable. The numerical values presented in some embodiments of the inventive subject matter may contain certain errors necessarily resulting from the standard deviation found in their respective testing measurements.

(104) Unless the context dictates the contrary, all ranges set forth herein should be interpreted as being inclusive of their endpoints and open-ended ranges should be interpreted to include only commercially practical values. The recitation of numerical ranges of values herein is merely intended to serve as a shorthand method of referring individually to each separate value falling within the range. Unless otherwise indicated herein, each individual value of a numerical range is incorporated into the specification as if it were individually recited herein. Similarly, all lists of values should be considered as inclusive of intermediate values unless the context indicates the contrary.

(105) Use of the terms “may” or “can” in reference to an embodiment or aspect of an embodiment also carries with it the alternative meaning of “may not” or “cannot.” As such, if the present specification discloses that an embodiment or an aspect of an embodiment may be or can be included as part of the inventive subject matter, then the negative limitation or exclusionary proviso is also explicitly meant, meaning that an embodiment or an aspect of an embodiment may not be or cannot be included as part of the inventive subject matter. In a similar manner, use of the term “optionally” in reference to an embodiment or aspect of an embodiment means that such embodiment or aspect of the embodiment may be included as part of the inventive subject matter or may not be included as part of the inventive subject matter. Whether such a negative limitation or exclusionary proviso applies will be based on whether the negative limitation or exclusionary proviso is recited in the claimed subject matter.

(106) The terms “a,” “an,” “the” and similar references used in the context of describing the present invention (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. Further, ordinal indicators—such as “first,” “second,” “third,” etc.—for identified elements are used to distinguish between the elements, and do not indicate or imply a required or limited number of such elements, and do not indicate a particular position or order of such elements unless otherwise specifically stated.

(107) All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., “such as”) provided with respect to certain embodiments herein is intended merely to better illuminate the inventive subject matter and does not pose a limitation on the scope of the inventive subject matter otherwise claimed. No language in the application should be construed as indicating any non-claimed element essential to the practice of the invention.

(108) It should be apparent to those skilled in the art that many more modifications besides those already described are possible without departing from the inventive concepts herein. The inventive subject matter, therefore, is not to be restricted except in the spirit of the appended claims.

Moreover, in interpreting both the specification and the claims, all terms should be interpreted in the broadest possible manner consistent with the context. In particular, the terms “comprises” and “comprising” should be interpreted as referring to elements, components, or steps in a non-

exclusive manner, indicating that the referenced elements, components, or steps may be present, or utilized, or combined with other elements, components, or steps that are not expressly referenced. Where the specification claims refers to at least one of something selected from the group consisting of A, B, C . . . and N, the text should be interpreted as requiring only one element from the group, not A plus N, or B plus N, etc.

(109) While aspects of the invention have been described with reference to at least one exemplary embodiment, it is to be clearly understood by those skilled in the art that the invention is not limited thereto. Rather, the scope of the invention is to be interpreted only in conjunction with the appended claims and it is made clear, here, that the inventor(s) believe that the claimed subject matter is the invention.

Claims

1. A jack support apparatus for operably engaging and selectively locking a hydraulic floor jack having a wheel axle and a cup axle, the apparatus comprising: an outer tube having an outer tube body comprising at least one outer tube wall with an outer tube hole formed in the outer tube wall, an outwardly-extending outer tube jack cradle, and an outer tube opening opposite the outer tube jack cradle, the outer tube jack cradle configured to selectively engage one of the wheel axle and the cup axle; an inner tube having an inner tube body comprising at least one inner tube wall with a plurality of spaced-apart inner tube holes formed in the inner tube wall and an outwardly-extending inner tube jack cradle, the inner tube body slidably received within the outer tube body through the outer tube opening with the inner tube wall adjacent to the outer tube wall, the inner tube jack cradle configured to selectively engage one of the wheel axle and the cup axle; a tube spring operable between the outer tube body and the inner tube body to bias the outer tube and the inner tube apart; and a pin operable through the outer tube hole for selectively engaging any of the plurality of inner tube holes, wherein selective operation of the pin by shifting the pin away from the inner tube disengages the pin from any of the plurality of inner tube holes and allows the inner tube to shift relative to the outer tube as by the inner tube body sliding within the outer tube body under the biasing effect of the tube spring; and further wherein selective operation of the pin by shifting the pin toward the inner tube engages the pin in one of the plurality of inner tube holes as the inner tube shifts relative to the outer tube as by the inner tube body sliding within the outer tube body to align the outer tube hole with a select one of the plurality of inner tube holes to prevent further relative movement between the outer tube and the inner tube, whereby the apparatus is configured to temporarily form a rigid linkage between the wheel and cup axles upon engagement therebetween by the outer tube and inner tube jack cradles to effectively lock the jack against further downward movement.

2. The apparatus of claim 1 further comprising a pin assembly having a pin housing located on the outer tube wall about the outer tube hole, the pin slidably inserted within the pin housing, the pin assembly further having a pin spring operably seated within the pin housing so as to bias the pin toward the inner tube through the outer tube wall.

3. The apparatus of claim 2 wherein the pin comprises a pin body having an intermediate pin undercut.

4. The apparatus of claim 3 further comprising a handle assembly having a handle pivotally mounted on a handle base located on the outer tube body, the handle having a handle body comprising a handle grip, an opposite handle tip, and an intermediate handle cross-hole for pivotally-mounting the handle on the handle base, the handle tip operably engaging the pin undercut through a pin housing side wall opening formed in the pin housing, whereby selective actuation of the handle by shifting the handle grip toward the outer tube lifts the handle tip and the pin away from the inner tube against the biasing effect of the pin spring so as to disengage the pin body from any of the plurality of inner tube holes, and further whereby selective release of the

handle by releasing the handle grip allows the pin to slidably shift toward the inner tube under the biasing effect of the pin spring so as to engage the pin body in one of the plurality of inner tube holes as the inner tube is shifted relative to the outer tube as by the inner tube body sliding within the outer tube body until the pin body enters one of the plurality of inner tube holes.

5. The apparatus of claim 4 further comprising: an outer tube cross-hole formed in the outer tube wall offset from the outer tube hole; a plurality of spaced-apart inner tube cross-holes formed in the inner tube wall offset from the plurality of inner tube holes; and a cross-pin configured to be selectively inserted through the outer tube cross-hole and an aligned one of the plurality of spaced-apart inner tube cross-holes, whereby relative movement between the outer tube and the inner tube is further prevented.

6. The apparatus of claim 4 comprising opposed two of the pin assemblies and respective opposed two of the handle assemblies, whereby relative movement between the outer tube and the inner tube is further prevented.

7. The apparatus of claim 2 wherein the pin housing comprises a pin housing side wall and a pin housing end wall opposite the outer tube hole, the pin spring seating between the pin and the pin housing end wall.

8. The apparatus of claim 1 further comprising: an outer tube cross-hole formed in the outer tube wall; a plurality of spaced-apart inner tube cross-holes formed in the inner tube wall; and a cross-pin configured to be selectively inserted through the outer tube cross-hole and an aligned one of the plurality of inner tube cross-holes, whereby relative movement between the outer tube and the inner tube is prevented.

9. The apparatus of claim 1 further comprising a lever assembly having a lever pivotally mounted on a lever base located on the outer tube body, the lever having a lever body comprising a lever grip, an opposite lever tip, and an intermediate lever cross-pin for pivotally-mounting the lever on the lever base, the lever tip selectively operably engaging one of the plurality of inner tube holes through the outer tube hole, the lever with the lever tip thereby defining the pin, whereby selective actuation of the lever by shifting the lever grip toward the outer tube lifts the lever tip away from the inner tube against the biasing effect of a lever spring seated between the lever grip and the outer tube body so as to disengage the lever tip from any of the plurality of inner tube holes, and further whereby selective release of the lever by releasing the lever grip allows the lever tip to shift toward the inner tube under the biasing effect of the lever spring so as to engage the lever tip in one of the plurality of inner tube holes as the inner tube is shifted relative to the outer tube as by the inner tube body sliding within the outer tube body until the lever tip enters one of the plurality of inner tube holes.

10. The apparatus of claim 9 comprising opposed two of the lever assemblies, whereby relative movement between the outer tube and the inner tube is further prevented.

11. The apparatus of claim 1 wherein the tube spring is installed within the outer and inner tube bodies operable between an outer tube end wall formed on the outer tube opposite the outer tube opening and an inner tube end wall formed on the inner tube opposite an inner tube opening.

12. The apparatus of claim 11 wherein the outer tube end wall and the outer tube jack cradle are integral and the inner tube end wall and the inner tube jack cradle are integral.

13. The apparatus of claim 11 further comprising: an outer tube sleeve installed on the outer tube end wall so as to extend within the outer tube body toward the outer tube opening; and an inner tube rod installed on the inner tube end wall so as to extend within the inner tube body toward the inner tube opening, the inner tube rod slidably received within the outer tube sleeve as the inner tube body is slidably received within the outer tube body, wherein the tube spring is installed about the outer tube sleeve and the inner tube rod through the outer tube and inner tube openings, whereby the outer tube sleeve and inner tube rod provide lateral stability for the tube spring.

14. The apparatus of claim 1 further comprising: an outer tube stop installed on the outer tube body proximal the outer tube opening; and an inner tube stop installed on the inner tube body proximal

an inner tube opening formed in the inner tube body opposite the inner tube jack cradle, wherein the outer tube and inner tube stops cooperate to prevent the inner tube body from slidably disengaging from the outer tube body under the biasing influence of the tube spring.

15. The apparatus of claim 1 wherein the outer and inner tube bodies have a rectangular profile, whereby the at least one outer tube wall defines opposite outer tube side walls, an outer tube front wall, and an opposite outer tube back wall and the at least one inner tube wall defines opposite inner tube side walls, an inner tube front wall, and an opposite inner tube back wall.

16. A method of employing the jack support apparatus of claim 1 to selectively lock the jack, the method comprising the steps of: positioning the apparatus adjacent to the jack between the wheel axle and the cup axle when the jack is in a raised position; shifting the apparatus such that the inner tube jack cradle is in contact with one of the wheel axle and the cup axle; retracting the pin so as to be disengaged from any of the plurality of inner tube holes to allow relative movement between the outer tube and the inner tube; sliding the outer tube body relative to the inner tube body so as to extend the apparatus until the outer tube jack cradle is in contact with one of the wheel axle and the cup axle; and inserting the pin so as to engage the one of the plurality of inner tube holes to prevent relative movement between the outer tube and the inner tube.

17. The method of claim 16 comprising the further step, prior to the step of positioning the apparatus adjacent to the jack, of setting the length of the apparatus shorter than the distance between the wheel axle and the cup axle based on the raised position of the jack.

18. The method of claim 17 wherein the step of setting the length of the apparatus comprises retracting the pin so as to be disengaged from any of the plurality of inner tube holes, sliding the inner tube body relative to the outer tube body, and reinserting the pin into another one of the inner tube holes to lock the apparatus at a desired length.

19. The method of claim 18 wherein the step of retracting the pin comprises squeezing a pivotable handle inwardly to lift the pin outwardly away from the inner tube.

20. The method of claim 19 comprising the further step, after the step of sliding the outer tube body relative to the inner tube body, of releasing the handle to allow the pin to shift inwardly toward the inner tube.

21. The method of claim 20 comprising the further step, after the step of releasing the handle, of slightly lowering the jack to cause the inner tube body to slide inwardly relative to the outer tube body until the pin is positioned adjacent to and may then enter the another one of the inner tube holes, wherein the apparatus and thereby the jack is locked.

22. The method of claim 16 comprising the further step, after the step of inserting the pin so as to engage one of the plurality of inner tube holes, of inserting a cross-pin through outer tube cross-holes formed in the outer tube body and aligned inner tube cross-holes of a plurality of spaced-apart inner tube cross-holes formed in the inner tube body to further prevent relative movement between the outer tube and the inner tube.

23. The method of claim 16 wherein the step of retracting the pin further comprises configuring the pin as a lever tip and squeezing a pivotable lever inwardly to lift the lever tip outwardly away from the inner tube.

24. A jack support apparatus for operably engaging and selectively locking a hydraulic floor jack having a wheel axle and a cup axle, the apparatus comprising: an outer tube having an outer tube body comprising at least one outer tube wall with an outer tube hole formed in the outer tube wall, an outwardly-extending outer tube jack cradle, and an outer tube opening opposite the outer tube jack cradle, the outer tube jack cradle configured to selectively engage one of the wheel axle and the cup axle; an inner tube having an inner tube body comprising at least one inner tube wall with a plurality of spaced-apart inner tube holes formed in the inner tube wall and an outwardly-extending inner tube jack cradle, the inner tube body slidably received within the outer tube body through the outer tube opening with the inner tube wall adjacent to the outer tube wall, the inner tube jack cradle configured to selectively engage one of the wheel axle and the cup axle; a pin assembly

having a pin housing located on the outer tube wall about the outer tube hole and a pin slidably inserted within the pin housing and operable through the outer tube hole for selectively engaging any of the plurality of inner tube holes, the pin assembly further having a pin spring operably seated within the pin housing so as to bias the pin toward the inner tube through the outer tube wall; and a handle assembly having a handle pivotally mounted on a handle base located on the outer tube body, the handle having a handle body comprising a handle grip, an opposite handle tip, and an intermediate handle cross-hole for pivotally-mounting the handle on the handle base, the handle tip operably engaging the pin through a pin housing side wall opening formed in the pin housing, whereby selective actuation of the handle by shifting the handle grip toward the outer tube lifts the handle tip and the pin away from the inner tube against the biasing effect of the pin spring so as to disengage the pin from any of the plurality of inner tube holes, and further whereby selective release of the handle by releasing the handle grip allows the pin to slidably shift toward the inner tube under the biasing effect of the pin spring so as to engage the pin in one of the plurality of inner tube holes as the inner tube is shifted relative to the outer tube as by the inner tube body sliding within the outer tube body until the pin enters one of the plurality of inner tube holes, wherein selective operation of the pin by shifting the pin away from the inner tube disengages the pin from any of the plurality of inner tube holes and allows the inner tube to shift relative to the outer tube as by the inner tube body sliding within the outer tube body; and further wherein selective operation of the pin by shifting the pin toward the inner tube engages the pin in one of the plurality of inner tube holes as the inner tube shifts relative to the outer tube as by the inner tube body sliding within the outer tube body to align the outer tube hole with a select one of the plurality of inner tube holes to prevent further relative movement between the outer tube and the inner tube, whereby the apparatus is configured to temporarily form a rigid linkage between the wheel and cup axles upon engagement therebetween by the outer tube and inner tube jack cradles to effectively lock the jack against further downward movement.

25. A jack support apparatus for operably engaging and selectively locking a hydraulic floor jack having a wheel axle and a cup axle, the apparatus comprising: an outer tube having an outer tube body comprising at least one outer tube wall with an outer tube hole formed in the outer tube wall, an outwardly-extending outer tube jack cradle, and an outer tube opening opposite the outer tube jack cradle, the outer tube jack cradle configured to selectively engage one of the wheel axle and the cup axle; an inner tube having an inner tube body comprising at least one inner tube wall with a plurality of spaced-apart inner tube holes formed in the inner tube wall and an outwardly-extending inner tube jack cradle, the inner tube body slidably received within the outer tube body through the outer tube opening with the inner tube wall adjacent to the outer tube wall, the inner tube jack cradle configured to selectively engage one of the wheel axle and the cup axle; a pin operable through the outer tube hole for selectively engaging any of the plurality of inner tube holes; and a handle assembly having a handle pivotally mounted on the outer tube body, the handle having a handle body comprising a handle grip and an opposite handle tip operably engaging the pin, whereby selective actuation of the handle by shifting the handle grip toward the outer tube lifts the handle tip and the pin away from the inner tube so as to disengage the pin from any of the plurality of inner tube holes, and further whereby selective release of the handle by releasing the handle grip allows the pin to slidably shift toward the inner tube so as to engage the pin in one of the plurality of inner tube holes as the inner tube is shifted relative to the outer tube as by the inner tube body sliding within the outer tube body until the pin enters one of the plurality of inner tube holes, wherein selective operation of the pin by shifting the pin away from the inner tube disengages the pin from any of the plurality of inner tube holes and allows the inner tube to shift relative to the outer tube as by the inner tube body sliding within the outer tube body; and further wherein selective operation of the pin by shifting the pin toward the inner tube engages the pin in one of the plurality of inner tube holes as the inner tube shifts relative to the outer tube as by the inner tube body sliding within the outer tube body to align the outer tube hole with a select one of the plurality

of inner tube holes to prevent further relative movement between the outer tube and the inner tube, whereby the apparatus is configured to temporarily form a rigid linkage between the wheel and cup axles upon engagement therebetween by the outer tube and inner tube jack cradles to effectively lock the jack against further downward movement; the apparatus further comprising an outer tube cross-hole formed in the outer tube wall offset from the outer tube hole; a plurality of spaced-apart inner tube cross-holes formed in the inner tube wall offset from the plurality of inner tube holes; and a cross-pin configured to be selectively inserted through the outer tube cross-hole and an aligned one of the plurality of spaced-apart inner tube cross-holes, whereby relative movement between the outer tube and the inner tube is further prevented.

26. A jack support apparatus for operably engaging and selectively locking a hydraulic floor jack having a wheel axle and a cup axle, the apparatus comprising: an outer tube having an outer tube body comprising at least one outer tube wall with opposite outer tube holes formed in the outer tube wall, an outwardly-extending outer tube jack cradle, and an outer tube opening opposite the outer tube jack cradle, the outer tube jack cradle configured to selectively engage one of the wheel axle and the cup axle; an inner tube having an inner tube body comprising at least one inner tube wall with a plurality of opposite spaced-apart inner tube holes formed in the inner tube wall and an outwardly-extending inner tube jack cradle, the inner tube body slidably received within the outer tube body through the outer tube opening with the inner tube wall adjacent to the outer tube wall, the inner tube jack cradle configured to selectively engage one of the wheel axle and the cup axle; opposed two pin assemblies each having a pin housing located on the outer tube wall about the respective opposite outer tube holes and a pin slidably inserted within the pin housing and operable through the respective outer tube hole for selectively engaging any of the plurality of respective inner tube holes, each pin assembly further having a pin spring operably seated within the pin housing so as to bias the pin toward the inner tube through the outer tube wall; and opposed two handle assemblies each having a handle pivotally mounted on the outer tube body, the handle having a handle body comprising a handle grip and an opposite handle tip operably engaging the respective pin, whereby selective actuation of the handles by shifting the handle grips toward the outer tube lifts the handle tips and the respective pins away from the inner tube so as to disengage the pins from any of the plurality of respective inner tube holes, and further whereby selective release of the handles by releasing the handle grips allows the pins to slidably shift toward the inner tube so as to engage the pins in one of the plurality of respective inner tube holes as the inner tube is shifted relative to the outer tube as by the inner tube body sliding within the outer tube body until the pins enter one of the plurality of respective inner tube holes, wherein selective operation of the pins by shifting the pins away from the inner tube disengages the pins from any of the plurality of respective inner tube holes and allows the inner tube to shift relative to the outer tube as by the inner tube body sliding within the outer tube body; and further wherein selective operation of the pins by shifting the pins toward the inner tube engages the pins in one of the plurality of respective inner tube holes as the inner tube shifts relative to the outer tube as by the inner tube body sliding within the outer tube body to align the outer tube hole with a select one of the plurality of inner tube holes to prevent further relative movement between the outer tube and the inner tube, whereby the apparatus is configured to temporarily form a rigid linkage between the wheel and cup axles upon engagement therebetween by the outer tube and inner tube jack cradles to effectively lock the jack against further downward movement.

27. A jack support apparatus for operably engaging and selectively locking a hydraulic floor jack having a wheel axle and a cup axle, the apparatus comprising: an outer tube having an outer tube body comprising at least one outer tube wall with an outer tube hole formed in the outer tube wall, an outwardly-extending outer tube jack cradle, and an outer tube opening opposite the outer tube jack cradle, the outer tube jack cradle configured to selectively engage one of the wheel axle and the cup axle; an inner tube having an inner tube body comprising at least one inner tube wall with a plurality of spaced-apart inner tube holes formed in the inner tube wall and an outwardly-extending

inner tube jack cradle, the inner tube body slidably received within the outer tube body through the outer tube opening with the inner tube wall adjacent to the outer tube wall, the inner tube jack cradle configured to selectively engage one of the wheel axle and the cup axle; and a lever assembly having a lever pivotally mounted on a lever base located on the outer tube body, the lever having a lever body comprising a lever grip, an opposite lever tip, and an intermediate lever cross-pin for pivotally-mounting the lever on the lever base, the lever tip selectively operably engaging one of the plurality of inner tube holes through the outer tube hole, whereby selective actuation of the lever by shifting the lever grip toward the outer tube lifts the lever tip away from the inner tube against the biasing effect of a lever spring seated between the lever grip and the outer tube body so as to disengage the lever tip from any of the plurality of inner tube holes, and further whereby selective release of the lever by releasing the lever grip allows the lever tip to shift toward the inner tube under the biasing effect of the lever spring so as to engage the lever tip in one of the plurality of inner tube holes as the inner tube is shifted relative to the outer tube as by the inner tube body sliding within the outer tube body until the lever tip enters one of the plurality of inner tube holes, wherein selective operation of the lever assembly by squeezing the lever disengages the lever tip from any of the plurality of inner tube holes and allows the inner tube to shift relative to the outer tube as by the inner tube body sliding within the outer tube body; and further wherein selective operation of the lever assembly by releasing the lever engages the lever tip in one of the plurality of inner tube holes as the inner tube shifts relative to the outer tube as by the inner tube body sliding within the outer tube body to align the outer tube hole with a select one of the plurality of inner tube holes to prevent further relative movement between the outer tube and the inner tube, whereby the apparatus is configured to temporarily form a rigid linkage between the wheel and cup axles upon engagement therebetween by the outer tube and inner tube jack cradles to effectively lock the jack against further downward movement.

28. A jack support apparatus for operably engaging and selectively locking a hydraulic floor jack having a wheel axle and a cup axle, the apparatus comprising: an outer tube having an outer tube body comprising at least one outer tube wall with an outer tube hole formed in the outer tube wall, an outer tube end wall, an outwardly-extending outer tube jack cradle integral with the outer tube end wall, and an outer tube opening opposite the outer tube jack cradle, the outer tube jack cradle configured to selectively engage one of the wheel axle and the cup axle; an inner tube having an inner tube body comprising at least one inner tube wall with a plurality of spaced-apart inner tube holes formed in the inner tube wall, an inner tube end wall, and an outwardly-extending inner tube jack cradle integral with the inner tube end wall, the inner tube body slidably received within the outer tube body through the outer tube opening with the inner tube wall adjacent to the outer tube wall, the inner tube jack cradle configured to selectively engage one of the wheel axle and the cup axle; a tube spring operable between the outer tube body and the inner tube body to bias the outer tube and the inner tube apart; and a pin operable through the outer tube hole for selectively engaging any of the plurality of inner tube holes, wherein selective operation of the pin by shifting the pin away from the inner tube disengages the pin from any of the plurality of inner tube holes and allows the inner tube to shift relative to the outer tube as by the inner tube body sliding within the outer tube body under the biasing effect of the tube spring; and further wherein selective operation of the pin by shifting the pin toward the inner tube engages the pin in one of the plurality of inner tube holes as the inner tube shifts relative to the outer tube as by the inner tube body sliding within the outer tube body to align the outer tube hole with a select one of the plurality of inner tube holes to prevent further relative movement between the outer tube and the inner tube, whereby the apparatus is configured to temporarily form a rigid linkage between the wheel and cup axles upon engagement therebetween by the outer tube and inner tube jack cradles to effectively lock the jack against further downward movement.
