

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399217
Kind Code	B1
Date of Patent	August 26, 2025
Inventor(s)	Rauer; Robert Eric et al.

Electronic device testing system and method of use

Abstract

An electronic device testing system, including: a standardized control system, an in-circuit tester configured to mate with the standardized control system and a device, a remote cloud system, a user interface, and/or any other suitable components. The user interface can optionally be configured to send a test plan to the remote processing system and/or to receive a test report associated with the device from the remote processing system.

Inventors: Rauer; Robert Eric (San Francisco, CA), Staples; Peter Ethan (San Francisco, CA)

Applicant: Blue Clover Design, LLC (San Francisco, CA)

Family ID: 1000006419283

Assignee: Blue Clover Design, LLC (San Francisco, CA)

Appl. No.: 17/717810

Filed: April 11, 2022

Related U.S. Application Data

us-provisional-application US 63173040 20210409

Publication Classification

Int. Cl.: G06F21/00 (20130101); G01R31/30 (20060101); G01R31/302 (20060101); G01R31/317 (20060101); G01R31/3181 (20060101); G01R31/319 (20060101); H04L9/32 (20060101)

U.S. Cl.:

CPC **G01R31/31713** (20130101); **G01R31/3004** (20130101); **G01R31/3025** (20130101);
G01R31/31813 (20130101); **G01R31/31912** (20130101); **G06F21/00** (20130101);
H04L9/3213 (20130101);

Field of Classification Search

CPC: G01R (31/31713); G01R (31/3004); G01R (31/3025); G01R (31/31813); G01R
(31/31912); G01R (31/30); G01R (21/302); G06F (21/00); H04L (9/3213); H04L (9/32)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2007/0022323	12/2006	Loh	714/38.14	G01R 31/318314
2007/0253553	12/2006	Abdul Rahman	380/259	G06Q 20/4014
2016/0373816	12/2015	Kashikar	N/A	H04N 21/4113
2018/0328982	12/2017	Rezgui	N/A	G10L 19/02
2021/0203568	12/2020	Yu	N/A	H04L 63/20
2022/0247748	12/2021	Kim	N/A	H04L 63/0209

Primary Examiner: Jhaveri; Jayesh M

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims the benefit of U.S. Provisional Application No. 63/173,040 filed Apr. 9, 2021, which is incorporated in its entirety by this reference.

TECHNICAL FIELD

(1) This invention relates generally to the electronics field, and more specifically to a new and useful electronic device testing system in the electronics field.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) FIG. 1 is a schematic representation of a variant of the system.
- (2) FIG. 2 is a schematic representation of an illustrative example of data transfer between components of the system.
- (3) FIG. 3 is a schematic representation of an example of a production line tool.
- (4) FIG. 4 is a schematic representation of an example of test plans.
- (5) FIGS. 5A and 5B depict illustrative examples of test plans.
- (6) FIG. 6A depicts a first illustrative example of a test report, including a test score for each test item.
- (7) FIG. 6B depicts a second illustrative example of a test report, including a test score for each test step.
- (8) FIGS. 7A and 7B depict examples of a production line tool.
- (9) FIGS. 8A and 8B depict examples of an in-circuit tester standardized hardware interface and an

in-circuit tester cassette.

(10) FIG. 9A depicts an example of an in-circuit tester fixture.

(11) FIG. 9B depicts an example of an in-circuit tester.

(12) FIGS. 10A and 10B depict illustrative examples of an in-circuit tester with a device under test.

(13) FIGS. 11A, 11B, and 11C depict illustrative examples of the remote user interface.

DETAILED DESCRIPTION

(14) The following description of the embodiments of the invention is not intended to limit the invention to these embodiments, but rather to enable any person skilled in the art to make and use this invention.

1. Overview

(15) As shown in FIG. 1, the electronic device testing system can include: a production line tool (PLT) **100**, an in-circuit tester (ICT) **200**, a remote cloud system **300**, a remote user interface **400**, and/or any other suitable components. In variants, the system can function to automatically test electronic devices, to remotely design and deploy a testing plan for the PLT **100** to implement and/or to remotely acquire test reports.

2. Examples

(16) In an example, a set of identical production line tools (PLT) can be associated with an organization, wherein each PLT is situated in a production line to perform tests on a device (e.g., a series of test steps within a test plan). A PLT can include a power supply, an integrated circuit programmer, a digital multimeter (and/or set of other measurement instruments), a computer, a PLT hardware interface, and/or any other suitable components. The PLT is removably mated to a custom in-circuit tester (ICT) that includes: a standardized hardware interface configured to mate with the PLT hardware interface and a custom cassette configured to mate with the device, enabling the PLT to perform electronic tests on the device and/or upload software to the device. To utilize a PLT (e.g., the same PLT or a different, identical PLT) to perform tests on a new device, a new custom cassette can be manufactured to mate with the new device (e.g., used with a new or old ICT). Each PLT can be continuously and securely connected to a remote cloud system, wherein test reports generated by PLTs are uploaded to the remote cloud system in real-time (e.g., wherein the test reports can be encrypted by a symmetric or asymmetric key and/or unencrypted). The remote cloud system is additionally connected to a remote user interface which is accessible by authenticated users. The remote user interface can be used to design and deploy test plans, wherein a test plan includes an ordered set of commands selected from a library of commands (e.g., wherein the library of commands is associated with the device). Commands can optionally be modified for a given device and/or ICT. Test reports (e.g., including a binary success score for each test step in a test plan) can be viewed at the remote user interface, wherein notifications are sent to one or more users in response to a failure of a test step.

3. Technical Advantages

(17) Variants of the technology can confer one or more advantages over conventional technologies.

(18) Conventional methods of electronic device testing require an expensive, entirely custom-built testing tool with manually developed software for each test across multiple stages of electronic assembly manufacturing. This conventional method is often performed with two separate companies (one for the software development and one for the hardware development), which lacks the technological and economic advantages of implementing the software and hardware development in tandem. Furthermore, the iteration and deployment of the software and hardware are conventionally performed on-site, which can increase costs and time.

(19) First, variants of the technology can drastically reduce the time to develop and implement software to test a device under test (DUT). In a first example, software can be remotely designed and uploaded to a production line tool (PLT), which can enable quick iterations of the software commands and rapid deployment of a test. In a second example, the software command design process can be significantly simplified for a user by providing the user with a library of pre-

designed commands (e.g., commands relevant to the DUT). In this example, by using a standardized PLT that can receive and implement the software (e.g., implement in conjunction with a custom in-circuit tester) rather than a fully custom device, the commands in the library can be pre-designed to properly interface with the PLT. In particular, users can modify specific sections of a command (e.g., a target resistance threshold for a test, pin locations used on the standardized hardware interface **210** and/or cassette **220** of the ICT, test locations on the DUT, etc.) without needing to design the software from scratch.

(20) Second, variants of the technology can drastically reduce the time to develop and implement hardware to test a DUT. In variants, the system implements a PLT that includes the bulk of the hardware required to implement a given DUT test, wherein the PLT is standardized across different DUTs. Additionally, in variants, the system implements an in-circuit tester (ICT), wherein a portion of the ICT is standardized (e.g., to mate with the PLT) and wherein a custom cassette of the ICT can be custom manufactured to mate with a specific DUT and/or to perform a specific test. Thus, a significant section of the hardware development time is eliminated through the use of standardized components. In an example, in the event of a DUT modification, only the cassette and/or an ICT fixture requires modifications. This can enable the same PLT, and, in variants, the same ICT, to test different DUTs (e.g., from different manufacturers, with different I/O or trace layouts, etc.).

(21) Third, variants of the technology can provide a remote interface for users to view test reports and/or receive notifications based on the test reports. For example, remote users can automatically receive a notification when a test has failed. Furthermore, variants of the technology can implement a tiered authentication system such that different users can have differing authentication credentials that enable test report viewing and/or test plan editing for each PLT and/or set of PLTs.

(22) However, further advantages can be provided by the system and method disclosed herein.

4. System

(23) As shown in FIG. 1, the electronic device testing system can include: a production line tool (PLT) **100**, an in-circuit tester (ICT) **200**, a remote cloud system **300**, a remote user interface **400**, and/or any other suitable components. Communication between system components can be performed in real time (e.g., responsive to a request, responsive to a test report generation, responsive to a test failure, etc.), iteratively, asynchronously, periodically, and/or at any other suitable time. An illustrative example of data transfer between system components is shown in FIG. 2.

(24) The PLT **100** functions to perform one or more electronic tests on a device under test (DUT) in a manufacturing production line. Additionally or alternatively, The PLT **100** can function to program a device (e.g., firmware programming, device provisioning, etc.). The PLT **100** (e.g., a standardized control system) can include: a power supply **110**, a PLT hardware interface **120**, a programmer **130**, a digital multimeter **140**; a computer **150**, and/or any other suitable components. An example of this is shown in FIG. 3. Examples of a DUT can include: a chip, circuit board (e.g., PCB), electronic product (e.g., mobile device, computer, etc.), any electronics assembly, and/or any other target.

(25) The PLT **100** can be one of a set of PLTs (e.g., a set of identical or different PLTs, each with a unique identifier) associated with an organization, platform (e.g., remote computing system), and/or other entity. The set of PLTs can be divided into subsets based on deployment groups, projects, and/or any other group. In a first embodiment, a subset of PLTs are configured to run the same test plan (e.g., on instances of the same device, on multiple devices, etc.). For example, a first deployment group of the set of PLTs can be used for in-circuit testing (e.g., during manufacturing, prototyping, etc.) and a second deployment group of the set of PLTs can be used for Final Assembly, Test and Pack-out (FATP) testing. In a second embodiment, a subset of PLTs are configured to run tests (e.g., from one or more test plans) on instances of the same device. For example, a first deployment group of the set of PLTs can be used for testing a first DUT and a second deployment group of the set of PLTs can be used for testing a second DUT. In a specific

example, the first DUT and second DUT can be two stages of the same product during manufacturing.

(26) The power supply **110** functions to supply power to the PLT **100**, to the DUT via the PLT **100**, and/or to any other system component. The power supply **110** can be connected to the computer **150** and/or any other PLT **100** component. The power supply **110** can include a wired connection (e.g., AC power), wireless connection (e.g., inductive charger, RFID charging, etc.), a battery (e.g., secondary or rechargeable battery, primary battery, etc.), and/or any other suitable system. In variants, the power supply **110** can be programmable (e.g., manually programmable, controlled via the computer **150**, etc.).

(27) The PLT hardware interface **120** functions to connect the PLT **100** to a DUT. The PLT hardware interface **120** preferably connects the DUT to the programmer **130**, the digital multimeter **140**, and/or the computer **150**, but can alternatively connect the DUT to any other system component. In a first variant, the PLT hardware interface **120** connects the PLT **100** to the standardized hardware interface **210** of the ICT **200**, wherein the cassette **220** of the ICT **200** is connected to the DUT. In a second variant, the PLT hardware interface **120** directly connects the PLT **100** to the DUT. The PLT hardware interface **120** can include removable cable connections (e.g., a 762 mm HD78 male-to-male cable), permanent wired connections, and/or any other connector. An example is shown in FIG. 7B. In a third variant, the PLT hardware interface **120** can connect to auxiliary sensors and/or instruments, which, in turn, can connect to the DUT. However, the PLT hardware interface **120** can be otherwise configured.

(28) The programmer **130** functions to communicate with the DUT and/or test the DUT (e.g., via the ICT **200**). The programmer **130** (e.g., an integrated circuit programmer) can be connected to the computer **150**, the PLT hardware interface **120**, the ICT **200**, any PLT **100** component, and/or any other system component. In a first example, the programmer **130** flashes firmware onto one or more processors associated with the DUT (e.g., as part of a test step in a test plan, prior to a test step, for device provisioning, etc.). In a second example, the programmer **130** monitors and/or controls pins on the DUT (e.g., to test for shorts and/or opens in the DUT, detect defects in the DUT, etc.). In this example, the programmer **130** can monitor the pins via the digital multimeter **140**. In a third example, the programmer **130** can test internal logic of the DUT (e.g., to debug firmware and/or a circuit). However, the programmer **130** can be otherwise configured.

(29) The digital multimeter **140** functions to take electrical measurements of the DUT (e.g., via the ICT **200**). The digital multimeter **140** can be connected to the computer **150**, the programmer **130**, the PLT hardware interface **120**, the ICT **200**, any PLT **100** component, and/or any other system component. Electrical measurements can include voltage, current, resistance, impedance, and/or any other electrical quantity. However, the digital multimeter **140** can be otherwise configured. However, the PLT **100** can include any other suitable set of measurement instruments.

(30) The computer **150** functions to control PLT **100** components, execute test plans, and/or communicate with the remote cloud system **300**. The computer **150** can be connected to the power supply **110**, the programmer **130**, the digital multimeter **140**, the remote cloud system **300**, and/or any other system component. The computer **150** can include a processor module **151**, a communication module **152**, and/or any other suitable computing components.

(31) The processor module **151** functions to execute test plans (e.g., received via the communication module **152**), generate test reports, control the local user interface **160**, and/or provide other local functionalities local to the PLT **100**. The processor module **151** can include one or more: CPUs, GPUs, custom FPGA/ASICs, microprocessors, and/or any other suitable components.

(32) A test plan can include an ordered set of test commands to control any component of the PLT **100** (e.g., wherein the PLT **100** can control the ICT **200** and/or DUT). Optionally, the test plan can be organized into test items wherein each item comprises one or more test steps (e.g., wherein each test step is a single command, wherein each test step is multiple commands, etc.). The commands

can be written in YAML script and/or any other language. Examples of test steps can include: electrical measurements (e.g., voltage, current, resistance and/or impedance, capacitance, frequency, etc.), logic measurements, UART tests, CAN Bus tests, DUT programming (e.g., erase, software upload, reset, restart, etc.; an example is shown in FIG. 5B), DUT identification, and/or any other electrical device task. In variants, a test plan can evaluate whether a DUT assembly was fabricated correctly (e.g., by checking for resistance, capacitance, shorts, opens, etc.). A test plan can be executed automatically, periodically, in response to a request (e.g., a user request local at the PLT **100**, a remote user request via the remote user interface **400**, etc.), and/or can be otherwise executed.

(33) A test report can be generated during and/or after a test plan is executed. The test report can include a test score for the entire test plan, for a subset of the test plan (e.g., a subset of test items, test steps, and/or commands), and/or for each test step in the test plan. The test score can be continuous, discrete, binary, categorical, and/or otherwise defined. In a first example, the test score is an electrical measurement value of the DUT (e.g., obtained via an electrical measurement of the ICT **200**). In a second example, the test score is a logic result acquired from a logic test. In a third example, the test score is a binary success or fail score based on whether a measurement is above or below a threshold value. Optionally, for any binary test score, if a single test step fails, the test item and/or the entire test plan fails. Examples are shown in FIG. 6A and FIG. 6B.

(34) In a first variant, a generated test report can be uploaded to the remote cloud system **300** (e.g., via the communication module **152**). The test report can be uploaded: in real-time (e.g., after the test plan is complete, after each test step is complete, etc.), periodically in batches, in response to a request, in response to a test score indicating a test failure, and/or at any other time. In a second variant, the test report can be locally stored at the PLT **100** (e.g., on a solid-state device). In a first example, the test report is stored locally and, additionally, uploaded to the remote cloud system **300**. In a second example, the test report can be stored locally without uploading to the remote cloud system **300**. In a third example, the test report can be stored locally when the communication module **152** is not connected to the remote cloud system **300**.

(35) However, the processor module **151** can be otherwise configured.

(36) The communication module **152** functions to facilitate communication with the remote cloud system **300**. The communication module **152** can send test reports (e.g., including notifications of test step failures) and/or any other information. The communication module **152** can receive software (e.g., firmware, test plans, etc.) and/or any other information.

(37) The communication module **152** can facilitate wired and/or wireless communication. The communication module **152** can use: 802.11x, Wi-Fi, Wi-Max, WLAN, NFC, RFID, Bluetooth, Bluetooth Low Energy, BLE long range, ZigBee, cellular telecommunications (e.g., 2G, 3G, 4G, LTE, etc.), radio (RF), microwave, IR, audio, optical, wired connection (e.g., USB), and/or any other suitable communication system. Preferably, the connection between the communication module **152** and the remote cloud system **300** is continuous, but can alternatively be noncontinuous.

(38) Communications can be encrypted (e.g., using cryptographic datum, such as a shared symmetric key or asymmetric key pairs, etc.), unencrypted (e.g., cleartext), signed (e.g., with a key), or unsigned. Authentication (e.g., a secure two-way authentication) can occur between the communication module **152** and the remote cloud system **300** prior to connection, prior to sending and/or receiving information, and/or at any other time. Authentication can include locally storing a cloud identifier associated with the remote cloud system **300** (e.g., storing the identifier at the communication module **152**, the processor module **151**, and/or any other PLT **100** component), wherein the communication module **152** authenticates the remote cloud system **300** by using the stored cloud identifier (e.g., by comparing the cloud identifier to an identifier received from the remote cloud system **300**). Additionally or alternatively, the remote cloud system **300** can store a PLT identifier associated with the PLT **100**, wherein the remote cloud system **300** authenticates the

communication module **152** by using the stored PLT identifier (e.g., by comparing the PLT identifier to an identifier sent by the communication module **152**). Each PLT **100** can be associated with one or more unique PLT identifiers. Additionally or alternatively, the remote cloud system **300** and the PLT **100** can store complimentary keys (e.g., cryptographic datum) (e.g., the PLT **100** stores the private key and the remote cloud system **300** stores the public key; both store a symmetric key; etc.), wherein the receiving system can verify the authenticity and/or decrypt the received communication using the locally-stored key. In a specific example, the authentication includes TLS mutual authentication and/or any other mutual authentication technology. In variants, the communication module **152** is configured to only allow remote cloud connection with the remote cloud system **300**.

(39) However, the communication module **152** can be otherwise configured.

(40) However, the computer **150** can be otherwise configured.

(41) Optionally, the PLT **100** can include a local user interface **160** which can function to facilitate interaction with a user local to the PLT **100**. The local user interface **160** can be connected to the computer **150** and/or any other PLT **100** component. The local user interface **160** can include one or more outputs, including: displays (e.g., LED display, OLED display, LCD, etc.), audio speakers, lights (e.g., LEDs), tactile outputs (e.g., vibratory motors, etc.), printers, and/or any other suitable output. In a first example, the local user interface outputs can display a test status (e.g., a test report, an identifier of the currently deployed test plan, an identifier of a currently executing test step in the test plan, a time since last test step, a time until the next test step, etc.). In a second example, the local user interface outputs can display a remote cloud system connection status (e.g., a binary status if the connection is present, a strength of the connection, etc.). In a third example, the local user interface outputs can provide notifications to a user (e.g., via visual or auditory output). Notifications can occur in response to failure of a test step and/or test plan, a test score below or above a threshold, a break in connection to the remote cloud system **300**, and/or at any other time. The local user interface **160** can additionally or alternatively include one or more inputs, including: buttons, touchscreens (e.g., capacitive, resistive, etc.), a mouse, a keyboard, and/or any other suitable input. In an example, the local user interface inputs can enable a user to execute a test plan (e.g., starting and/or stopping a test plan, starting and/or stopping one or more test steps in a test plan, etc.). Preferably, the inputs do not enable a user to design a test plan at the PLT **100**, but can alternatively enable a user to design a test plan at the PLT **100**. An example is shown in FIG. 7A. However, the local user interface **160** can be otherwise configured.

(42) Optionally, the PLT **100** can include a location module which can function to determine the location of the PLT **100** (e.g., a geographic location, a specific location within a manufacturing plant, etc.). The location module can be connected to the computer **150** and/or any other PLT **100** component. The location module can include a GPS unit, a Bluetooth positioning unit, a RFID unit, a GNSS unit, a triangulation unit, a Wi-Fi connection location unit, a WHOIS unit (e.g., performed on IP address or MAC address), a GSM/CDMA cell identifier, a self-reporting location information unit, and/or any other suitable location systems. However, the location module can be otherwise configured.

(43) Optionally, the PLT **100** can include one or more accessory components. Any accessory component can be connected to any PLT **100** component. Accessory components can function to test a DUT, program a DUT, identify a DUT, and/or to otherwise interact with one or more DUTs. Examples of accessory components include: a barcode scanner, an NFC tag reader and/or writer, a motion sensor, a camera, a temperature sensor, and/or any other suitable components.

(44) However, the PLT **100** can be otherwise configured.

(45) The in-circuit tester (ICT) **200** functions to interact directly with the DUT, including executing one or more test steps in the test plan. The ICT **200** is connected to the DUT (e.g., via the cassette **220**) and the PLT **100** (e.g., via the PLT hardware interface **120**). The ICT **200** can include a standardized hardware interface **210** (e.g., a first hardware interface), a cassette **220** (e.g., a second

hardware interface). The ICT **200** can optionally include a fixture **230** and/or a computer **240**. All or a subset of the ICT components can be removable from the ICT (e.g., the ICT housing) and/or permanently affixed to the ICT (e.g., the ICT housing).

(46) The standardized hardware interface **210** is configured to mate with the PLT hardware interface **120**, enabling the transfer of information (e.g., commands in the test plan, test scores, etc.) between the ICT **200** and the PLT **100**. However, the standardized hardware interface **210** can be otherwise configured.

(47) The cassette **220** is configured to mate with the DUT. Preferably, the cassette **220** is custom designed for a DUT, but can alternatively be generic across multiple DUTs. The cassette **220** can be custom for a test plan and/or generic across test plans. Preferably, the cassette **220** implements a physical connection with the DUT, but alternatively does not use a physical connection. In a first variant, the cassette **220** is a bed-of-nails fixture. The size of the bed-of-nails fixture, the position of each nail, and/or the position of the bed-of-nails fixture in relation to the DUT can optionally be determined based on the DUT and/or based on the test plan (e.g., wherein the minimum number of nails are used to line up with test points of the DUT required for the test plan). In a second variant, the cassette **220** is a pogo-pin cassette (PPC), wherein the PPC includes a spring-loaded mechanism that physically connects the pogo-pins to the DUT. Preferably, the pogo-pins are removable, but can alternatively be permanent. The PPC can optionally be modular, wherein pogo-pins that are not needed for a given DUT or test plan are removed. The size of the PPC, the position of any pogo pin, and/or the position of the PPC in relation to the DUT can optionally be determined based on the DUT and/or based on the test plan (e.g., wherein the minimum number of pogo pins are used to line up with test points of the DUT required for the test plan). In a first example, a top plate of the PPC is spring-loaded and includes holes wherein the pogo-pins are exposed when the top plate is compressed. In a second example, the spring-loaded mechanism includes individual spring-loaded pogo-pins. In a third variant, the cassette **220** can include flying probes (e.g., for a flying probe ICT and/or other fixtureless ICT), wherein the probes can be controlled using the PLT computer **150** and/or the ICT computer **240**. Examples are shown in FIG. **8A** and FIG. **8B**. However, the cassette **220** can be otherwise configured.

(48) The fixture **230** functions to couple the cassette **220** to a DUT (e.g., to ensure a consistent physical connection between the DUT and the cassette **220**, to ensure proper relative positioning between the DUT and the cassette **220**, etc.). The fixture **230** can be standardized across varying DUTs, standardized across DUTs of similar sizes, custom to each individual DUT, and/or otherwise configured. The fixture **230** can optionally include a manual and/or automatic mechanism to secure the DUT to the cassette **220**. In an illustrative example, the fixture **230** is designed with a custom pressing plate based on the DUT and/or cassette **220** to press the DUT onto the cassette **220** (e.g., wherein pressing the DUT onto the cassette **220** vertically shifts a spring-loaded top plate of the cassette **220** such that the pogo-pins are exposed and in contact with the DUT). Examples of the fixture **230** are shown in FIG. **9A**, FIG. **9B**, FIG. **10A**, and FIG. **10B**.

(49) Optionally, the ICT **200** can include a computer **240** (e.g., a single-board computer and/or any other computing system). The ICT computer **240** can function to enable “twinning” with the PLT computer **150** such that a user at the production site can run test plans (e.g., nonstandard, organization-specific test plans) without additional setup. However, the computer **240** can be otherwise configured.

(50) However, the ICT **200** can be otherwise configured.

(51) The remote cloud system **300** can function to facilitate information transfer between the remote user interface **400** and the PLT **100** (e.g., via the communication module **152** of the PLT **100**). Information transfer via the remote cloud system **300** and/or information storage at the remote cloud system **300** can be performed automatically (e.g., responsive to a request), manually, semi-automatically, and/or otherwise performed.

(52) Information transfer between the remote cloud system **300** and the remote user interface **400**

can include receiving software (e.g., firmware, test plans, etc.) from the user interface **400** and/or sending test reports to the user interface **400**. Information transfer between the remote cloud system **300** and the PLT **100** can include deploying software to the PLT **100** and/or receiving test reports from the PLT **100**.

(53) When information or data is transferred or stored, the information or data can be: cleartext, hashes, in an encrypted format (e.g., encrypted with a key associated with the PLT **100**, the remote cloud system **300**, a user, etc.), signed (e.g., with a verification key associated with the PLT **100**, the remote cloud system **300**, a user, etc.), and/or otherwise transmitted. The sending systems can be authenticated, authorized, and/or otherwise verified by the receiving systems before establishing a communication channel (e.g., using credentials, tokens, passwords, or other authentication or authorization mechanisms); alternatively, the sending systems can be unauthorized and/or unauthenticated. Authentication can be one-way or mutual.

(54) Authentication can be used for information transfer with PLT communication module **152** (e.g., as previously described) and/or with the remote user interface **400**. In a first variant, authentication between the remote cloud system **300** and the remote user interface **400** can include a tiered authentication system based on user groups. For example, the user groups (e.g., within a single organization and/or across multiple organizations) can include administrators, managers, and viewers, wherein administrators have the highest access level and viewers have the lowest access level. In an illustrative example, administrators can view test reports for all PLT deployment groups as well as design and deploy test plans for all PLT deployment groups; managers can view test reports for one or more assigned PLT deployment groups as well as design and deploy test plans for one or more assigned PLT deployment groups; and viewers can view test reports for one or more assigned PLT deployment groups (e.g., without access to design and/or deploy new test plans). Each user can have a unique authentication token and/or can be associated with an authentication token for the user group, wherein the remote cloud system **300** stores a mapping between authentication tokens and PLTs (e.g., PLT deployment groups). In a second variant, authentication between the remote cloud system **300** and the remote user interface **400** is performed at a single tier. In a first example, an organization is associated with one or more authentication tokens that enable any user in the organization access to test reports and/or test plans for each PLT **100** associated with the organization. In a second example, authentication occurs on a per-user basis, wherein each user is independently associated with a unique authentication token and a set of accessible PLTs. However, any suitable authentication system can be used.

(55) Optionally, the remote cloud system **300** can function to store and/or organize information, including: test reports; test plans; command libraries; PLT connection status to the remote cloud system **300**; PLT locations; identifiers and/or authentication tokens for PLTs, ICTs, DUTs, and/or users; PLT **100** and/or user associations with organizations, projects, deployment groups, user groups, users, PLTs, ICTs, and/or DUTs; and/or any other information.

(56) However, the remote cloud system **300** can be otherwise configured.

(57) The remote user interface **400** can function to enable a user to design and/or upload test plans remotely to a PLT **100** and/or to remotely view test reports for a PLT **100**. The remote user interface **400** can be connected to the remote cloud system **300** and/or any other system component. The remote user interface **400** can be hosted on a computer, a mobile device, and/or any other suitable system. Preferably, the remote user interface **400** is hosted remotely from a PLT **100**, but can alternatively be hosted locally to a PLT **100**.

(58) Designing (e.g., writing, editing, etc.) test plans at the remote user interface **400** can include accessing pre-designed commands from a library of commands and arranging the commands in an order according to a series of test steps (e.g., wherein groups of test steps form test items in the test plan). The library of commands can optionally be associated with a device class, wherein commands used for a given device are selected from the library associated with the corresponding device class. Illustrative examples of device classes include: Raspberry Pi, Raspberry Pi Compute

Module, Variscite, Variscite DART-MX8M-MINI, BeagleBone Black, ATECC508a, and/or any other category of devices and/or device components. An example is shown in FIG. 4. Alternatively, test plans and/or any command within a test plan can be designed from scratch.

(59) In a first variant, the commands in the test plan are not edited after selection from the library. In a second variant, the commands can be modified based on a desired test purpose, the DUT, and/or the associated ICT **200**. In a specific example, sections of the commands are locked (e.g., fixed) from user editing while other sections are editable. In a third variant, the commands remain unedited while separate arguments in the test plan can be added and/or modified based on the desired test purpose, the DUT, and/or the associated ICT **200**. Examples of modifications (e.g., to commands and/or test plan arguments) include: setting location values (e.g., pin mapping locations) based on the ICT **200**, setting threshold values (e.g., voltage threshold, impedance threshold, etc.), setting calibration parameters (e.g., previously determined values), setting testing sequences (e.g., current patterns, voltage patterns, pattern parameters, such as wave shape, etc.), and/or any other modifications (e.g., specifying values for one or more test parameters). For example, the test plan can specify a location (e.g., pin identifier) on the standard hardware interface and/or a location (e.g., pin identifier) on the cassette. An example is shown in FIG. 5A. Additionally or alternatively, a pre-written test plan (e.g., a prior test plan iteration) can be accessed and edited. In a fourth variant, a portion of the commands are editable (e.g., test-specific commands), while others are not (e.g., communication commands, authentication commands, etc.).

(60) Deploying a test plan to a set of PLTs from the remote user interface **400** can include uploading the test plan to the remote cloud system **300**, wherein the remote cloud system **300** uploads the test plan to the set of PLTs. The set of PLTs can be all PLTs in a PLT deployment group (e.g., selected at the remote user interface **400**) and/or any other PLT group. Optionally, additional software (e.g., PLT software, DUT software, etc.) can be deployed from the remote user interface **400** via the remote cloud system **300**. An example is shown in FIG. 11B.

(61) Viewing a test report at the remote user interface **400** can include receiving (e.g., accessing) the test report from the remote cloud system **300** and displaying the test report. Test reports can be organized at the remote user interface **400** based on: PLT identifier, PLT deployment group, date of test plan execution, DUT, project, organization, test plan, test score, and/or any other information. An example is shown in FIG. 11C.

(62) The remote user interface **400** can optionally be used to view additional information, including: PLT status (e.g., whether a PLT **100** is connected to the cloud, time and/or identification of previous tests, current deployed test plan, deployment group, location, etc.), user groups, PLT groups, identifiers (e.g., for users, PLTs, DUTs, ICTs, etc.), test plan iterations, and/or any other system information. An example is shown in FIG. 11A.

(63) The remote user interface **400** can optionally provide notifications to a user. The remote user interface **400** can use visual, auditory, and/or haptic outputs to notify the user. The notifications can be provided in response to: failure of a test step and/or test plan, a test score below or above a threshold, a threshold number of test step and/or test item failures (e.g., within a PLT deployment group), a connection break between a PLT **100** and the remote cloud interface **300**, and/or at any other time.

(64) However, the remote user interface **400** can be otherwise configured.

(65) The method can optionally include an application (e.g., native application, browser application, etc.) executable on a user device which can function to provide notifications to a user. The user device can be a mobile device (e.g., mobile computing device) associated with the user, including mobile phones, laptops, smartphones, tablets, watches, and/or any other suitable mobile device. The user device can be connected to the remote cloud system **300** and/or the remote user interface **400**. Preferably, the application can be used to send notifications to one or more users (e.g., as described for the remote user interface **400**), but can alternatively perform any other functionality of the remote user interface **400**. However, the application can be otherwise

configured.

(66) Different subsystems and/or modules discussed above can be operated and controlled by the same or different entities. In the latter variants, different subsystems can communicate via: APIs (e.g., using API requests and responses, API keys, etc.), requests, and/or other communication channels.

(67) Alternative embodiments implement the above methods and/or processing modules in non-transitory computer-readable media, storing computer-readable instructions that, when executed by a processing system, cause the processing system to perform the method(s) discussed herein. The instructions can be executed by computer-executable components integrated with the computer-readable medium and/or processing system. The computer-readable medium may include any suitable computer readable media such as RAMs, ROMs, flash memory, EEPROMs, optical devices (CD or DVD), hard drives, floppy drives, non-transitory computer readable media, or any suitable device. The computer-executable component can include a computing system and/or processing system (e.g., including one or more collocated or distributed, remote or local processors) connected to the non-transitory computer-readable medium, such as CPUs, GPUs, TPUS, microprocessors, or ASICs, but the instructions can alternatively or additionally be executed by any suitable dedicated hardware device.

(68) Embodiments of the system and/or method can include every combination and permutation of the various system components and the various method processes, wherein one or more instances of the method and/or processes described herein can be performed asynchronously (e.g., sequentially), contemporaneously (e.g., concurrently, in parallel, etc.), or in any other suitable order by and/or using one or more instances of the systems, elements, and/or entities described herein. Components and/or processes of the following system and/or method can be used with, in addition to, in lieu of, or otherwise integrated with all or a portion of the systems and/or methods disclosed in the applications mentioned above, each of which are incorporated in their entirety by this reference.

(69) As a person skilled in the art will recognize from the previous detailed description and from the figures and claims, modifications and changes can be made to the preferred embodiments of the invention without departing from the scope of this invention defined in the following claims.

Claims

1. A system for modular electronic testing, comprising: a standardized control system, comprising a power supply, an integrated circuit (IC) programmer, a digital multimeter, and a computer; a first in-circuit tester (ICT) comprising a standardized hardware interface configured to mate with the standardized control system and a first hardware interface configured to mate with a first device; a second ICT comprising the standardized hardware interface and a second hardware interface configured to mate with a second device; a remote cloud system configured to connect to a user interface and to the standardized control system, wherein the remote cloud system is configured to connect to the user interface using a tiered authentication, the tiered authentication comprising: the remote cloud system authenticating an administrator user associated with a first security credential, wherein authenticating the administrator user grants the administrator user access at the user interface to view test reports and edit test plans for all standardized control systems in a set of standardized control systems associated with the administrator user; and the remote cloud system authenticating a manager user associated with a second security credential, wherein authenticating the manager user grants the manager user access at the user interface to view test reports and edit test plans for only a subset of the set of standardized control systems, wherein the subset is associated with a deployment group; and the user interface, configured to: send a first test plan to the remote cloud system, wherein the first test plan comprises a set of commands selected from a library of commands, wherein a command in the set of commands is modified using a first value

associated with the first ICT; send a second test plan to the remote cloud system, wherein the second test plan comprises the set of commands, wherein a command in the set of commands is modified using a second value associated with the second ICT; receive a first test report associated with the first device from the remote cloud system; and receive a second test report associated with the second device from the remote cloud system.

2. The system of claim 1, wherein the first value comprises a first location on the standardized hardware interface, and wherein the second value comprises a second location on the standardized hardware interface.
3. The system of claim 1, wherein the command in the set of commands is configured to determine whether a voltage measured with the digital multimeter is above a voltage threshold, wherein the first value further comprises a first voltage threshold value associated with the first device, and wherein the second value further comprises a second voltage threshold value associated with the second device.
4. The system of claim 1, wherein the first test report comprises at least one test score for each step of the first test plan and the second test report comprises at least one test score for each step of the second test plan.
5. The system of claim 4, wherein each step of the first and second test plans corresponds to an individual command of the set of commands.
6. The system of claim 4, wherein the user interface is configured to notify a user when a test score indicates failure.
7. The system of claim 6, wherein the system further comprises an application executable on a mobile computing device, wherein the remote cloud system is configured to notify the user at the application when the test score indicates failure.
8. The system of claim 1, wherein the remote cloud system is configured to receive the test reports from a set of standardized control systems comprising the standardized control system, wherein each of the set of standardized control systems is configured to generate test reports.
9. The system of claim 1, wherein the remote cloud system is configured to receive a test report from the standardized control system in real-time, in response to generation of the test report.
10. The system of claim 1, wherein, in response to detection that the standardized control system is not connected to the remote cloud system, the standardized control system locally stores generated test reports.
11. The system of claim 1, wherein the standardized control system is continuously connected to the remote cloud system.
12. The system of claim 1, wherein the first test plan comprises the set of commands in an ordered arrangement, and wherein the second test plan comprises the set of commands in the ordered arrangement.
13. The system of claim 1, wherein the remote cloud system is configured to connect to the standardized control system using a secure two-way authentication.
14. The system of claim 13, wherein the standardized control system locally stores a first cryptographic datum associated with remote cloud system, and the remote cloud system stores a second cryptographic datum associated with the standardized control system, wherein the secure two-way authentication comprises: the remote cloud system authenticating the standardized control system using the second cryptographic datum; and the standardized control system authenticating the remote cloud system using the first cryptographic datum.
15. The system of claim 1, wherein the deployment group is associated with the first device.
16. The system of claim 1, wherein the tiered authentication further comprises: the remote cloud system authenticating a viewer user associated with a third authentication token, wherein authenticating the viewer user grants the viewer user access at the user interface to view test reports for the subset of the set of standardized control systems.
17. The system of claim 1, wherein a section of each command in the set of commands is editable

by a user and a section of each command in the set of commands is fixed.

18. The system of claim 1, wherein the first and second devices share a device class, wherein the library of commands is associated with the device class.

19. A system for modular electronic testing, comprising: a standardized control system, comprising a power supply, an integrated circuit (IC) programmer, a digital multimeter, and a computer; a first in-circuit tester (ICT) comprising a standardized hardware interface configured to mate with the standardized control system and a first hardware interface configured to mate with a first device; a second ICT comprising the standardized hardware interface and a second hardware interface configured to mate with a second device; a remote cloud system configured to connect to a user interface and to the standardized control system, wherein the remote cloud system is configured to connect to the user interface using a tiered authentication, the tiered authentication comprising: the remote cloud system authenticating an administrator user associated with a first authentication token, wherein authenticating the administrator user grants the administrator user access at the user interface to view test reports and edit test plans for all standardized control systems in a set of standardized control systems associated with the administrator user; and the remote cloud system authenticating a manager user associated with a second authentication token, wherein authenticating the manager user grants the manager user access at the user interface to view test reports and edit test plans for only a subset of the set of standardized control systems, wherein the subset is associated with a deployment group; and user interface, configured to: send a first test plan to the remote cloud system, wherein the first test plan comprises a set of commands selected from a library of commands, wherein a command in the set of commands is modified using a first value associated with the first ICT; send a second test plan to the remote cloud system, wherein the second test plan comprises the set of commands, wherein a command in the set of commands is modified using a second value associated with the second ICT; receive a first test report associated with the first device from the remote cloud system; and receive a second test report associated with the second device from the remote cloud system.

20. The system of claim 19, wherein the deployment group is associated with the first device.

21. The system of claim 19, wherein the tiered authentication further comprises: the remote cloud system authenticating a viewer user associated with a third authentication token, wherein authenticating the viewer user grants the viewer user access at the user interface to view test reports for the subset of the set of standardized control systems.
