

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12400766

Kind Code

B1

Date of Patent

August 26, 2025

Inventor(s)

Mortensen; Marius K. et al.

Systems and methods for electronically collecting and linking standardized case data in a data warehouse

Abstract

A method for collecting case data in a central case data storage system. The method includes receiving health agency case data from a health agency case repository and cleaning the health agency case data. The method further includes receiving multiple adverse event identifiers and medical product data. The method further includes combining the cleaned health agency case data with the medical product data and an adverse event identifier. The method further includes selecting trusted case data from a trusted case repository. The method further includes determining the combined health agency case data and the trusted case data at least partially match and generating one or more digital connections between the combined health agency case data and the trusted case data. The method further includes storing the combined health agency case data, the trusted case data, and the one or more digital connections in a central case data warehouse.

Inventors: Mortensen; Marius K. (Burlington, CA), Tan; Zhen (North York, CA), Woolven; Eric Mitchell (Toronto, CA), Komadinic; Sandra (Hamilton, CA), Srivastava; Shanul (Brampton, CA)

Applicant: Veeva Systems Inc. (Pleasanton, CA)

Family ID: 1000006536940

Assignee: Veeva Systems Inc. (Pleasanton, CA)

Appl. No.: 17/871516

Filed: July 22, 2022

Publication Classification

Int. Cl.: G16H50/70 (20180101); G06F16/215 (20190101)

U.S. Cl.:

Field of Classification Search

CPC: G16H (50/70); G06F (16/215)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9147047	12/2014	Grun et al.	N/A	N/A
9239722	12/2015	Calahan et al.	N/A	N/A
9619624	12/2016	Jackson et al.	N/A	N/A
9626479	12/2016	Zaleski	N/A	N/A
10901962	12/2020	Gubau i Forné et al.	N/A	N/A
10942936	12/2020	Tan et al.	N/A	N/A
2002/0165853	12/2001	Gogolak	N/A	G16H 70/40
2006/0059137	12/2005	Walker	707/E17.14	G06F 16/258
2006/0111847	12/2005	Pearson et al.	N/A	N/A
2008/0300902	12/2007	Smith et al.	N/A	N/A
2009/0055378	12/2008	Alecu	707/999.005	G06F 16/313
2009/0158211	12/2008	Gogolak	N/A	N/A
2009/0216555	12/2008	Mitchell et al.	N/A	N/A
2009/0319299	12/2008	De Vries	705/3	G16H 15/00
2012/0036170	12/2011	Triebel	707/822	G06F 16/24556
2012/0143776	12/2011	Jaffe et al.	N/A	N/A
2013/0179187	12/2012	Jackson et al.	N/A	N/A
2013/0225607	12/2012	Gillies et al.	N/A	N/A
2014/0122523	12/2013	Aggarwal	707/769	G06F 16/245
2014/0358576	12/2013	Hoffman	705/2	G16Z 99/00
2015/0032679	12/2014	Joseph et al.	N/A	N/A
2016/0378950	12/2015	Reiner	N/A	N/A
2018/0004902	12/2017	Aronow et al.	N/A	N/A
2018/0239991	12/2017	Weller et al.	N/A	N/A
2018/0330300	12/2017	Runkana et al.	N/A	N/A
2020/0294681	12/2019	Routray	N/A	G06N 5/022
2021/0315859	12/2020	Bowen et al.	N/A	N/A
2023/0048663	12/2022	Doppalapudi	N/A	G06F 16/27

OTHER PUBLICATIONS

Postigo, R., Brosch, S., Slattery, J. et al. EudraVigilance Medicines Safety Database: Publicly Accessible Data for Research and Public Health Protection. Drug Saf 41, 665-675 (2018). cited by examiner

Oracle Health Emperica Signal Sector Map, Internet Citation, 2 pages, URL:

[https://docs.oracle.com/health-sciences/empirica-signal-](https://docs.oracle.com/health-sciences/empirica-signal-90/ESIUG/Home_page.htm#About_Signal_Configurations.htm)

90/ESIUG/Home_page.htm#About_Signal_Configurations.htm, 2019. cited by applicant

Oracle Health Sciences Empirica Signal and Topics User Guide, Release 8.1, E70269-01, 2016. cited by applicant

Primary Examiner: Hamilton; Matthew L

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to systems and methods for electronically collecting and linking standardized case datasets in a data warehouse.

BACKGROUND

(2) Researchers, scientists, industry players, academics, government regulators, and other stakeholders are increasingly in need of a central source of standardized case data for determining and analyzing signals in the field of Pharmacovigilance.

SUMMARY

(3) One embodiment relates to a method for collecting case data in a central case data storage system. The central case data storage system includes a provider computing system including a trusted case repository and a central case data warehouse. The method includes receiving health agency case data associated with one or more health agency cases from a health agency case repository. The method further includes cleaning the health agency case data. The method further includes receiving multiple adverse event identifiers and medical product data associated with one or more medical products. The method further includes combining the cleaned health agency case data with the medical product data and an adverse event identifier of the multiple adverse event identifiers to generate combined health agency case data. The method further includes selecting trusted case data associated with one or more Pharmacovigilance (PV) cases from the trusted case repository. The method further includes determining the combined health agency case data and the trusted case data at least partially match based on at least one of the one or more health agency cases matching at least one of the one or more PV cases. The method further includes generating one or more digital connections between the combined health agency case data and the trusted case data. The one or more digital connections include a digital connection for each matching PV case and health agency case. The method further includes storing the combined health agency case data, the trusted case data, and the one or more digital connections in the central case data warehouse.

(4) Another embodiment relates to a method for collecting case data in a central case data storage system. The central case data storage system includes a provider computing system including a central case data warehouse. The method includes receiving health agency case data associated with one or more health agency cases from a health agency case repository. The method further includes cleaning the health agency case data. The method further includes receiving multiple adverse event identifiers and medical product data associated with one or more medical products. The method further includes combining the cleaned health agency case data with the medical product data and an adverse event identifier of the multiple adverse event identifiers to generate combined health agency case data. The method further includes selecting trusted case data associated with one or more Pharmacovigilance (PV) cases from the central case data warehouse. The method further includes determining the combined health agency case data and the trusted case data at least partially match based on at least one of the one or more health agency cases matching at least one of the one or more PV cases. The method further includes generating one or more digital connections between the combined health agency case data and the trusted case data. The one or more digital connections include a digital connection for each matching PV case and health

agency case. The method further includes storing the combined health agency case data, the trusted case data, and the one or more digital connections in the central case data warehouse.

(5) This summary is illustrative only and is not intended to be in any way limiting. Other aspects, inventive features, and advantages of the devices or processes described herein will become apparent in the detailed description set forth herein, taken in conjunction with the accompanying figures, wherein like reference numerals refer to like elements.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) FIG. 1 is a component diagram of a standardized case dataset collection and signal detection system, according to an example embodiment.

(2) FIG. 2 is a flow diagram of a method for electronically collecting and linking standardized case data in a data warehouse, according to an example embodiment.

(3) FIG. 3 is a flow diagram of a method of dynamically querying standardized case data from a data warehouse and determining one or more potential signals, according to an example embodiment.

(4) FIG. 4 is an illustration of some aspects of a user interface generated by the standardized case dataset collection and signal detection system of FIG. 1 to manage a signal product profile of one or more medical products, according to an example embodiment.

(5) FIGS. 5A-5B are illustrations of some aspects of a user interface generated by the standardized case dataset collection and signal detection system of FIG. 1 to manage determined potential signals, according to an example embodiment.

(6) FIG. 6 is an illustration of some aspects of a user interface generated by the standardized case dataset collection and signal detection system of FIG. 1 to monitor a specific potential signal, according to an example embodiment.

(7) FIGS. 7A-7B are illustrations of some aspects of a user interface generated by the standardized case dataset collection and signal detection system of FIG. 1 to analyze a specific potential signal, according to an example embodiment.

(8) FIG. 8 is an illustration of some aspects of a user interface through which the standardized case dataset collection and signal detection system of FIG. 1 receives a request to copy trusted case data from a trusted case repository to a central case data warehouse, according to an example embodiment.

(9) FIGS. 9A-9C are component diagrams of a central case data warehouse of the standardized case dataset collection and signal detection system of FIG. 1, according to an example embodiment.

DETAILED DESCRIPTION

(10) Referring generally to the figures, systems and methods for electronically collecting and linking standardized case datasets in a data warehouse and detecting signals based on the linked case datasets are disclosed. The systems and methods described herein provide for higher quality and more available case data being stored within a central case data warehouse, which results in better quality signals and signal detection, thereby helping and improving the pharmacovigilance industry by more accurately and swiftly reporting signals to health authorities. For example, by standardizing received case data (and other additional case data) such that it is in a standard format, the present systems and methods can utilize multiple different data sources (including external sources) or repositories to collect case data for the central case data warehouse, which provides for more case data available when determining potential signals. In comparison, typical signal detection data management systems typically only utilize a single data source (e.g., so all the received case data is structured the same). As a result, the present systems and methods can more quickly and accurately determine potential signals and report the potential signals to health

authorities. Further, by cleaning the case data by removing special characters and converting each field of the case data to a specific data type, the present systems and methods provide for a more reliable, trusted, and error-free data source, that can be used without having to handle and store invalid data. Because external case data can come from a variety of sources, the case data can typically include a large number of errors, invalid data, and be unreliable. In a typical signal detection data management system, these errors and invalid data may be stored within the case repository and utilized when detecting signals, which can provide or cause for inaccurate and unreliable signal detection. In comparison, the present systems and methods clean the case data by removing special characters, deduplicating the data, and converting each field of the case data to a specific data type which removes the errors and invalid data. By doing so, the central case data warehouse does not store the invalid data saving on memory and processing power and produces more valid and standardized case data which provides for more accurate and reliable signal detection overall.

(11) Additionally, by determining matching portions (e.g., cases) of the received case data and then linking/merging the case data such that it is interconnected before outputting the case data, the present systems and methods output the maximum amount of case data possible while preventing duplicate cases from being included within the output case data, thereby providing an improvement to case data warehousing and querying systems and a technical solution to the technical problem of case duplication. For example, by preventing the output of duplicate case data by linking the case data and only outputting a single version of each case, the present systems and methods prevent duplicate bias which skews the signals and statistical values generated toward the duplicate data. Further, by outputting the case data based on a priority of the type of the case data, the present systems and methods select the maximum amount of case data that reflects the priority while not including duplicate cases. In typical case data warehousing and querying systems, a single data source is utilized such that linking/combining of the case data is not required, which provides for a much smaller set of case data. In comparison, by including the maximum amount of case data while still removing/preventing duplicate data, the present systems and methods provide for more accurate signal detection and overall better statistical values by including multiple sources/types of case data.

(12) Additionally, by utilizing a central source of case data, the present systems and methods provide a single trusted data warehouse from which a wide variety of case data can be selected and output. In this regard, the present systems and methods use less processing power and memory by providing for a single central source of case data, as compared to typical case data systems. For instance, in typical case data systems, each type of case data may be stored separately in an individual location and then output from the individual location. In comparison, the present systems and methods utilize a single and central location that contains all of the case data. By doing so, the present systems and methods require less processing power to retrieve case data (e.g., by not having to determine which location(s) to retrieve data from) and memory with which to store the case data (e.g., by not having to replicate the same case in multiple separate locations).

(13) As used herein, the term “event,” “medical event,” or “adverse event” can include any untoward medical occurrence which happens to either a patient or a subject in a clinical investigation or during regular use of a medical product that has been given to that person. For example, the “event,” “medical event,” or “adverse event” may encompass any signs which are unfavorable and unexpected for the patient or subject, including any abnormal laboratory findings such as a high blood pressure, a rapid heart rate, etc. The “event,” “medical event,” or “adverse event” could be symptoms, or a disease temporally associated with the use of a medical product and does not have to have been previously associated with that product. The term “event,” “medical event,” or “adverse event” can further encompass adverse reactions and serious adverse events such as death, life-threatening adverse experiences, inpatient hospitalization, congenital birth defects, disabilities, etc. Further, each “event,” “medical event,” or “adverse event” may be

defined by the Medical Dictionary for Regulatory Activities (MedDRA) (or other medical event dictionaries) and associated with a specific MedDRA code. Moreover, “event information” “medical event information” “adverse event information” “event data” “medical event data” or “adverse event data” can include information associated with the event such as the date of onset of the event, the date of cessation of the event, the type of event, the dictionary term (e.g., MedDRA term), the dictionary code (e.g., MedDRA code), event comments, the outcome of the event, the location of the event (e.g., country where the event occurred), the event duration, patient data for a patient who endured or to which the event occurred, medical products that the patient consumed and/or dosages for the consumed medical products, the event rank, event contacts, the event type, and any associated event documents.

(14) As used herein, the term “case” or “case dataset” can include an Individual Case Safety Report (ICSR) as defined by the standard ISO/HL7 27953 of the International Standards Organization (ISO) as well as any past or future standards governing ICSRs of the ISO, the World Health Organization (WHO), the Food and Drug Administration (FDA), the European Medicines Agency (EMA), or other national health agencies governing ICSRs. Moreover, “case information” “case data” or “case dataset” can include information associated with or included in the case such as adverse event data, case contact data, case priority data, case seriousness data, case documents, medical product registrations, patient data, and other data associated with a case as defined by the standard ISO/HL7 27953 as well as any past or future standards governing ICSRs of the ISO, the WHO, the Food and Drug Administration (FDA), the European Medicines Agency (EMA), or other national health agencies governing ICSRs.

(15) As used herein, the term “signal” can include a signal as defined by the WHO, the FDA, the EMA, or other health agencies. Further, the term “signal” can include information on a new or known adverse event that is likely caused by a medical product and may be generated from more than a single case associated with the adverse event.

(16) As used herein, the term “substance” can include a substance as defined by the WHO, the FDA, the EMA, or other health agencies. Further, the term “substance” can include an active ingredient or any component of a medical product that provides a pharmacological activity or other direct effect in the diagnosis, cure, mitigation, treatment, or prevention of disease, or to affect the structure or any function of the body of man or animals. In this regard, the “substance” may be a component responsible for the pharmacological activity of a medical product.

(17) Additionally, as used herein the terms “information” and “data” may be used interchangeably such that one may be substituted for the other and vice versa.

(18) Referring now to FIG. 1, a system **100** for electronically collecting and linking standardized case datasets in a data warehouse to determine one or more potential signals is shown, according to an example embodiment. The system **100** includes a provider computing system **104**, one or more user computing devices **108**, and multiple health agency or authority computing systems **112** connected by a secure network (e.g., a network **118**).

(19) The network **118** communicably and operably couples the provider computing system **104**, the user computing devices **108**, and the health agency computing systems **112** such that communicable and operable computing may be provided between the provider computing system **104**, the user computing devices **108**, and/or the health agency computing systems **112** over the network **118**. In various embodiments, the network **118** includes any combination of a local area network (LAN), an intranet, the Internet, or any other suitable communications network, directly or through another interface.

(20) The provider computing system **104** may be operated and managed by a provider (e.g., a software as a service (SaaS) provider, a cloud services provider, a software provider, a service provider, etc.) and may include a computer system (e.g., one or more servers (e.g., a cloud computing server) each with one or more processing circuits). In some embodiments, the provider computing system **104** may act as a host and provide an application (e.g., a web-based application,

a mobile application, etc.) to each of the user computing devices **108** over the network **118** in response to authenticating the respective user computing device **108**. As shown, the provider computing system **104** may include a network interface **126**, a processing circuit **128**, a central case warehouse **130**, and a medical product repository **134**. In some embodiments, the provider computing system **104** may include an input/output circuit (e.g., similar to or the same as an input/output circuit **162** that will be described further herein).

(21) The network interface **126** is structured to establish connections with the user computing devices **108** and the health agency computing systems **112** by way of the network **118**. The network interface **126** includes program logic and/or hardware-based components that connect the provider computing system **104** to the network **118**. For example, the network interface **126** may include any combination of a wireless network transceiver (e.g., a cellular modem, a broadband modem, a Bluetooth transceiver, a Wi-Fi transceiver, a Li-Fi transceiver, etc.) and/or a wired network transceiver (e.g., an Ethernet transceiver). In some embodiments, the network interface **126** includes the hardware and machine-readable media structured to support communication over multiple channels of data communication (e.g., wireless, Bluetooth, near-field communication (NFC)). In some embodiments, the network interface **126** includes cryptography logic and capabilities to establish a secure communications session.

(22) Additionally, the network interface **126** may include AS2 gateway logic that includes programmable instructions that facilitate communication (transmission and receipt) using the AS2 Gateway communication protocol (as specified in Request for Comment (RFC) 4130) over the network **118** via the network interface **126**. For example, using the AS2 gateway logic, the network interface **126** may transmit or receive electronic files (e.g., a source file including adverse event data, a case, a case dataset, etc.) or other data to the health agency computing systems **112** and/or the user computing devices **108** using the AS2 Gateway protocol.

(23) The processing circuit **128**, as shown, comprises a memory **136**, a processor **137**, a case intake circuit **138**, a case linking circuit **140**, a signal analyzation circuit **142**, and a pharmacovigilance (PV) or case reporting circuit **144**. The memory **136** includes one or more memory devices (e.g., RAM, NVRAM, ROM, flash memory, hard disk storage, etc.) that store data and/or computer code for facilitating the various processes described herein. That is, in operation and use, the memory **136** stores at least portions of instructions and data for execution by the processor **137** to control the processing circuit **128**. The memory **136** may be or include tangible, non-transient volatile memory and/or non-volatile memory. The processor **137** may be implemented as a general-purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a digital signal processor (DSP), a group of processing components, or other suitable electronic processing components.

(24) The case intake circuit **138** is structured or configured to intake, clean (e.g., standardize, deduplicate, etc.), and manage case data received from one or more sources that may be provided to the provider computing system **104** (e.g., from the health agency computing systems **112**). For example, the case intake circuit **138** may receive case data (e.g., health agency case data) associated with multiple cases from the health agency computing systems **112**. Each case may be associated with a medical product and an adverse event. In response, the case intake circuit **138** may clean the health agency case data (e.g., remove unnecessary portions that take up memory, standardize the health agency case data, deduplicate the health agency case data, and the like), match or combine the health agency case data with medical product data of the medical product repository **134**, and match the health agency case data with adverse event identifier(s) associated with one or more adverse events. For example, the case intake circuit **138** may determine the health agency case data includes a first National Drug Code (NDC) and the medical product data includes the same first NDC. In response, the case intake circuit **138** may combine the health agency case data associated with the first NDC and the medical product data associated with the first NDC. In some embodiments, the case intake circuit **138** may link or otherwise digitally connect (e.g., via an

object pointer) the matching health agency case data and the medical product data. In another example, the case intake circuit **138** may determine the health agency case data includes a first adverse event code and the adverse event identifier is the same first adverse event code. In some embodiments, the case intake circuit **138** may link or otherwise digitally connect the matching health agency case data and the adverse event identifier. In response, the case intake circuit **138** may combine the health agency case data associated with the first adverse event and the adverse event identifier(s) associated with the first adverse event. Once the case data is cleaned and combined or matched with adverse event identifier(s) and medical product data, the case intake circuit **138** may store the case data within the central case warehouse **130** (e.g., within the one or more health agency repositories **131**) and/or provide the case data to the case linking circuit **140**.

(25) The case linking or matching circuit **140** is structured or configured to receive the intaken (e.g., cleaned, standardized, deduplicated) case data from various sources, determine matching portions of the case data (e.g., cases), and link the matching portions. For example, the case linking circuit **140** may receive intaken health agency case data and trusted case data. The health agency case data may be associated with a first case and matched with a first medical product and a first adverse event and include first date/time data. Likewise, the trusted case data may be associated with a second case and include or be matched with a second medical product, a second adverse event, and include second date/time data. Then, by determining the first medical product is the same as the second medical product, the first adverse event is the same as the second adverse event, and the first date/time data is the same as the second date/time data, the case matching circuit **140** may determine the first case is a match with the second case (i.e., are the same case). In some embodiments, the case matching circuit **140** may determine the first case is a match with the second case (i.e., are the same case) based on a case identifier of the first case and the second matching (e.g., being the same). In some embodiments, for matching cases, the case linking circuit **140** may generate and include a link to the matched case within the respective case data. For instance and using the example above, the case linking circuit **140** may generate and include a link or other digital connection to the first case in the case data of the second case and vice versa. Once the link is generated and included in the case data associated with each of the respective cases, the case linking circuit **140** may store the case data in the central case warehouse **130** (e.g., within the one or more health agency repositories **131**, within the one or more PV repositories **132**, within the one or more additional case repositories **133**, within the central case repository **195**, etc.).

(26) The signal analyzation circuit **142** is structured or configured to retrieve a specified set of case data from the central case warehouse **130** (based on one or more specified filters, sources, etc.) and analyze the specified set of case data for potential signals and statistical values. For example, the signal analyzation circuit **142** may determine one or more statistical values based on the case data. The statistical values may be provided to the user computing device **108**. In response, the user computing device **108** may provide verification the potential signal is a signal or is not a signal. For instance, the signal analyzation circuit **142** may determine a first potential signal associated with the adverse event “Headache” and the medical product “Drug X” based on case data received from the central case warehouse **130**. For instance, the signal analyzation circuit **142** may determine one or more statistical values (e.g., case count, disproportionality analysis values, etc.) such as a Proportional Reporting Ratio (PRR) statistical value, a chi-squared (χ^2) test statistical value, and/or multiple Empirical Bayes (EB) statistical values. The signal analyzation circuit **142** may then provide the potential signal and/or the statistical values to the user computing device **108** for verification. In some embodiments, the signal analyzation circuit **142** may monitor the case data of the central case warehouse **130** for a change to a signal (e.g., new cases associated with the medical product and the adverse event, changes to the one or more statistical values, and the like). In some embodiments, the signal analyzation circuit **142** may store the signal and the one or more statistical values within a signal repository (not shown) of the provider computing system **104**. In some embodiments, the signal analyzation circuit **142** may generate a signal data object associated with a

medical product and an adverse event, in response to receiving a request to do so.

(27) The (PV) or case reporting circuit **144** is structured or configured to intake adverse event data associated with a medical product and an adverse event (e.g., from the user computing device **108**), generate a case, and output the case to the relevant health agencies. For example, the PV circuit **144** may receive adverse event data associated with “Drug X” and the adverse event “Headache”. The PV circuit **144** may then process the adverse event data, generate a case including case data, and output the case to the health agency computing system **112** associated with the FDA. Further, the PV circuit **144** may include a trusted case repository **146** in which the cases and associated trusted case data are stored. In some embodiments, the PV circuit **144** may not output the case to the health agency computing systems **112**, if not required. For example, the PV circuit **144** may determine the case does not require reporting to the FDA because it is a non-serious case. However, the PV circuit **144** may still store the case within the trusted case repository **146**, making it available for signal detection and management.

(28) The trusted case repository **146** is a repository (e.g., a database, cloud storage, etc.) that is structured or configured to receive, store, and manage case data associated with a medical product and adverse event of cases processed by the PV circuit **144**. For example, the trusted case repository **146** may receive case data associated with a specific case dataset, a medical product, and an adverse event and store/manage the case data. In another example, the trusted case repository **146** may receive the case data and an associated data object (e.g., a case data object). For each case dataset stored within the trusted case repository **146**, the trusted case repository **146** may further generate or receive/determine version data associated with each case dataset as well as date data indicating when the version of the case was active. For example, the trusted case repository **146** may receive a first case dataset on a first date and store the case dataset and associated case data within the trusted case repository **146** as version 1.0. Then, the trusted case repository **146** may receive a follow-up case dataset on a second date and combine the first case dataset with the follow-up case dataset. The trusted case repository **146** may store the combined case dataset within the trusted case repository **146** as version 2.0. In this example, the first version of the case was active from the first date to the second date, and the second version of the case was active from the second date on. The active dates may be used by the providing computing system **104** for retrieving case data from the central case warehouse **130** as will be described further herein.

(29) Additionally, the trusted case repository **146** can be structured according to various database types, such as relational, hierarchical, network, flat, point-in time, and/or object relational. In some embodiments, the trusted case repository **146** includes a plurality of nonvolatile/non-transitory storage media such as solid-state storage media, hard disk storage media, virtual storage media, cloud-based storage drives, storage servers, and/or the like.

(30) The trusted case repository **146** acts as a trusted or valid source of case data because of the quality of case data that is processed and generated by the PV circuit **144**. For example, the PV circuit **144** typically receives adverse event data directly from the user computing device **108**. Further, the PV circuit **144** may require multiple steps of validation and verification of the adverse event data before generating the case dataset.

(31) The central case warehouse **130** is one or more repositories (e.g., one or more databases, cloud storage, etc.) that are structured or configured to receive, store, and manage case data (e.g., trusted case data, health agency case data, external case data, etc) associated with one or more cases. For example, the central case warehouse **130** may receive trusted case data intaken and managed by the PV circuit **144**, additional case data intaken by the case intake circuit **138**, and health agency case data from the health agency case repository **184** intaken by the case intake circuit **138** and store/manage the case data therein. As shown in FIGS. **9A-9C** and discussed further herein, the central data warehouse **130** may include one or more central health agency repositories **131**, one or more central PV case repositories **132**, and one or more additional case repositories **133**. In some embodiments, the central data warehouse **130** includes a single central repository **195**.

(32) In some embodiments, the central case warehouse **130** may be a part of (e.g., included in) the processing circuit **128** and utilize the memory **136** and the processor **137** to perform the data operations described herein (e.g., intake, management). In other embodiments, the central case warehouse **130** may include a memory (e.g., similar or the same as the memory **136**) and a processor (e.g., similar or the same as the processor **137**) to perform the data operations described herein. The central case data warehouse will be described further herein within regard to FIGS. **9A-9C**.

(33) By being a central source of case data, the central case warehouse **130** provides a single trusted location from which a wide variety of case data can be selected and output. In this regard, the central case warehouse **130** reduces processing power and memory by providing for a single central source of case data, as compared to typical case data systems. For instance, in typical case data systems, each type of case data may be stored in separate locations and then output or requested from the individual location. In comparison, the central case warehouse **130** is a single central location which contains all of the case data. By doing so, the central case warehouse **130** and the provider computing system **104** require less processing power to retrieve case data (e.g., by not having to determine which location to retrieve data from) and memory with which to store the case data (e.g., by not having to replicate the same case in multiple locations and utilizing a single location for case data storage).

(34) The medical product repository **134** is a repository (e.g., a database, cloud storage, etc.) that is structured or configured to receive, store, and manage medical product data associated with medical products (e.g., marketed drugs, marketed medical devices, etc.). For example, the medical product repository **134** may receive medical product data associated with a specific medical product (e.g., drug name, one or more substances included in the medical product, trade name, threshold statistical values associated with the medical product, a primary data source, identifiers (e.g., application number, NDC, etc.), medical product registration data (e.g., marketed medical product registrations for each country), associated clinical studies or trials, and the like) and store/manage the medical product data. In another example, the medical product repository **134** may receive the medical product data and an associated data object (e.g., a medical product data object). Further, the medical product repository **134** can be structured according to various database types, such as relational, hierarchical, network, flat, point-in time, and/or object relational. In some embodiments, the medical product repository **134** includes a plurality of nonvolatile/non-transitory storage media such as solid-state storage media, hard disk storage media, virtual storage media, cloud-based storage drives, storage servers, and/or the like.

(35) In some embodiments, each different data or information type (e.g., case data, medical product data, adverse event data, signal data, substance data, etc.) may be stored in, and the provider computing system **104** may include a separate repository for each (not shown). For example, the provider computing system **104** may include a signal repository in which generated and/or verified signals (e.g., signal data objects) and associated signal data are stored. In another example, the provider computing system **104** may include an adverse event identifier repository or dictionary in which adverse event identifiers (e.g., a MedDRA term, a MedDRA code, associated MedDRA classes, etc.) are stored. Each repository may be similar to or structured the same as the medical product repository **134**.

(36) Still referring to FIG. **1**, each of the one or more user computing devices **108** can be any type of computing device or computing system. For instance, each of the user computing devices **108** can be one or more of a mobile phone, a tablet computer, a laptop computer, a smart watch, a server computer system, or any other internet-connected device. In operation, the user computing devices **108** may communicate and interface with the provider computing system **104** via the network **118** to generate and provide a request to receive case data. For example, the user of one or more of the user computing devices **108** may interface with the provider computing system **104** to indicate the provider computing system **104** is to provide case data from any source within a first timeframe as

well as determine potential signals based on the resulting case data. As shown, the user computing device **108** may include a network interface **156**, a processing circuit **160**, and the input/output (I/O) circuit **162**.

(37) The network interface **156** is structured to establish connections with the provider computing system **104** and/or the health agency computing systems **112** by way of the network **118**. The network interface **156** includes program logic and/or hardware-based components that connect the user computing device **108** to the network **118**. For example, the network interface **156** may include any combination of a wireless network transceiver (e.g., a cellular modem, a broadband modem, a Bluetooth transceiver, a Wi-Fi transceiver, a Li-Fi transceiver, etc.) and/or a wired network transceiver (e.g., an Ethernet transceiver). In some embodiments, the network interface **156** includes the hardware and machine-readable media structured to support communication over multiple channels of data communication (e.g., wireless, Bluetooth, near-field communication (NFC)). In some embodiments, the network interface **156** includes cryptography logic and capabilities to establish a secure communications session.

(38) The processing circuit **160**, as shown, comprises a memory **168**, a processor **170**, and a user interface generation or rendering circuit **174**. The memory **168** includes one or more memory devices (e.g., RAM, NVRAM, ROM, flash memory, hard disk storage, etc.) that store data and/or computer code for facilitating the various processes described herein. That is, in operation and use, the memory **168** stores at least portions of instructions and data for execution by the processor **170** to control the processing circuit **160**. The memory **168** may be or include tangible, non-transient volatile memory and/or non-volatile memory. The processor **170** may be implemented as a general-purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a digital signal processor (DSP), a group of processing components, or other suitable electronic processing components.

(39) The user interface generation or rendering circuit **174** may be configured to receive a user interface (e.g., a web interface in an HTML file and related files, a downloaded graphical user interface, etc.) from the provider computing system **104** and render the user interface on the user computing device **108** via the I/O circuit **162**. In this way, the provider computing system **104** may generate one or more user interfaces and provide the one or more user interfaces to the user interface generation circuit **174** to be rendered on the user computing device **108** (e.g., on a display of the I/O circuit **162** of the user computing device **108**).

(40) The I/O circuit **162** is structured to receive communications from and provide communications to the user of one or more of the user computing devices **108** (e.g., the user). In this regard, the I/O circuit **162** is structured to exchange data with the processing circuit **160** to provide output to the user and to receive input from the user. As a result, the I/O circuit **162** may include a display that may be manipulated by the application. In some embodiments, the I/O circuit **162** may also include a keyboard, a mouse, a joystick, a touch screen, touch areas, soft keys, a microphone, a speaker, a vibration mechanism, a sensor, a RFID scanner, or other input or output devices described herein.

(41) Still referring to FIG. **1**, the health agency computing systems **112** can be any type of computing device or computing system and may be associated or managed by a health agency (e.g., the FDA, the EMA, Health Canada, etc.). For instance, at least one of the health agency computing systems **112** may be the Electronics Submission Gateway (ESG) of the FDA through which one or more E2B XML files and/or an FDA **3500A** PDF files (e.g., case datasets) may be received from or provided to. In operation, each health agency computing system **112** may communicate with the provider computing system **104** or the user computing devices **108** to send and/or receive case data associated with case datasets (e.g., within E2B files). Further, the health agency computing system **112** is shown to include a network interface **178**, a processing circuit **182**, and a health agency case repository **184**.

(42) The network interface **178** is structured to establish connections with the provider computing system **104** and/or the user computing device **108** by way of the network **118**. The network

interface **178** includes program logic (e.g., AS2 Gateway logic) and/or hardware-based components that connect the health agency computing system **112** to the network **118**. For example, the network interface **178** may include any combination of a wireless network transceiver (e.g., a cellular modem, a broadband modem, a Bluetooth transceiver, a Wi-Fi transceiver, a Li-Fi transceiver, etc.) and/or a wired network transceiver (e.g., an Ethernet transceiver). In some embodiments, the network interface **178** includes the hardware and machine-readable media structured to support communication over multiple channels of data communication (e.g., wireless, Bluetooth, near-field communication (NFC)). In some embodiments, the network interface **178** includes cryptography logic and capabilities to establish a secure communications session.

(43) The processing circuit **182**, as shown, comprises a memory **190** and a processor **194**. The memory **190** includes one or more memory devices (e.g., RAM, NVRAM, ROM, flash memory, hard disk storage, etc.) that store data and/or computer code for facilitating the various processes described herein. That is, in operation and use, the memory **190** stores at least portions of instructions and data for execution by the processor **194** to control the processing circuit **182**. The memory **190** may be or include tangible, non-transient volatile memory, and/or non-volatile memory. The processor **194** may be implemented as a general-purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a digital signal processor (DSP), a group of processing components, or other suitable electronic processing components.

(44) The health agency case repository **184** is a repository (e.g., a database, cloud storage, etc.) that is structured or configured to receive, store, and manage case data (e.g., health agency case data) associated with one or more cases. For example, the health agency case repository **184** may store and manage health agency case data received and processed by the health agency computing system **112**. For instance, the health agency case repository **184** may be the FDA Adverse Event Reporting System (FAERS) which is a public database or repository that stores and manages portions of case datasets received by the FDA. In another example, the health agency case repository **184** may be the EMA's Eudra Vigilance System (EVDAS), the WHO's Vigibase, and the like. Further, the health agency case repository **184** can be structured according to various database types, such as relational, hierarchical, network, flat, point-in time, and/or object relational. In some embodiments, the health agency case repository **184** includes a plurality of nonvolatile/non-transitory storage media such as solid-state storage media, hard disk storage media, virtual storage media, cloud-based storage drives, storage servers, and/or the like.

(45) Referring now to FIG. 2, a method **200** of electronically collecting and linking standardized case data in a data warehouse is shown, according to an example embodiment. Method **200** can be carried out by the system of FIG. 1. More particularly, the method **200** can be carried out by the processing circuit **128** of the provider computing system **104** and through communication with the user computing devices **108** and/or the health agency computing systems **112**.

(46) Method **200** commences at step **204** at which the provider computing system **104** receives health agency case data from one or more of the multiple health agency computing systems **112**. The health agency case data may be associated with multiple cases, each case associated with a medical product and an adverse event. The health agency case data may include data pertaining to each of the cases including a medical product identifier (e.g., NDC product code, NDC package code, brand name, generic name, application number, substance name(s), drug authorization number, drug role, etc.) of the medical product associated with the case, an adverse event identifier (e.g., adverse event term, adverse event code, MedDRA version, etc.) of the adverse event associated with the case, a patient identifier (e.g., patient gender, patient age group, patient initials, etc.), a seriousness of the case (e.g., serious: results in death, serious: life threatening, non-serious, etc.), a case identifier (e.g., a case unique identifier (UID), a case ID, etc.), case version data, and/or one or more pieces of date/time data (e.g., date/time the case was first/initially received by the FDA, date/time the most recent case data was received by the health agency, etc.) associated

with the case. In some embodiments, the health agency case data may be received from the health agency computing systems **112** (e.g., the FDA electronic submissions gateway) in a source document (e.g., an E2B XML file, etc.). In some embodiments, the health agency case data may be received from a specific health agency computing system **112** at a specific interval of time. For example, the provider computing system **104** may receive health agency case data from the health agency computing system **112** associated with the FDA every 3 months (because the FAERS releases updated data quarterly). In another example, the provider computing system **104** may receive health agency case data from the health agency computing system **112** associated with the EMA every month. In this regard, step **204** may repeat at an interval for each of the health agency computing systems **112**.

(47) Once the provider computing system **104** has received the health agency case data, the method **200** proceeds to step **208** at which the provider computing system **104** cleans the case data. To clean the health agency case data, the provider computing system **104** may remove special characters (e.g., “*”, “_”, characters that are not American Standard Code for Information Interchange (ASCII) characters, etc.) from the case data, remove duplicate cases within the health agency case data (e.g., based on the case identifier of each case matching, based on the reporting country of each case matching, based on the gender of each case matching, based on the event date of each case matching, based on the adverse events of each matching, and/or based on the medical product of each case matching), and/or standardize the health agency case data. For example, the provider computing system **104** may standardize the medical product identifiers (e.g., the medical product name or brand name) of the health agency case data by separating terms with multiple words (e.g., “Drugx (substancex)”) into two separate medical product identifiers (e.g., “Drugx” and “substancex”). In another example, the provider computing system **104** may remove dosages, dosage forms, and route of administration (RoA) from the medical product identifier (e.g., “Drugx (300 MG)” to “Drugx” or “Drugx (tablet)” to “Drugx”). In another example, the provider computing system **104** may standardize the health agency case data by converting each field to a specific data type (e.g., patient age group to integers, drug name to a String, etc.)). In some embodiments to standardize the case data where multiple versions of a case are received by the provider computing system **104**, the provider computing may generate a version active date and a version end date and add them to the health agency case data. For example, the provider computing system **104** may receive health agency case data for a case including a first version with a new information receipt date and/or initial receipt date of Jan. 1, 2001 and a second version with a new information receipt date of Jan. 1, 2002. In response, the provider computing system **104** may store the version data associated with each including determining and adding a version active start date/time of Jan. 1, 2001 and/or a version active end date/time of Jan. 1, 2002 for the first version and a version active start date/time of Jan. 1, 2002 and no version active end date/time for the second version of the case. In this regard, the version active start date is the new info date of the present version of the case, and the version active end date is the new info date of the next version of the case (assuming there is one).

(48) Once the provider computing system **104** has cleaned the health agency case data, the method **200** proceeds to step **210** at which the provider computing system **104** receives medical product data from the medical product repository **134** associated with one or more medical products. The medical product data may be received from the user computing device **108** and include data associated with multiple medical products (e.g., DrugX, DrugY, etc.). Further, for each medical product associated with the medical product data, the medical product data may include data pertaining to the medical product and signals associated with the medical product including a primary data source, a threshold PRR value, a threshold x.sup.2 value, a threshold, EBGm value, a threshold EB05 value, a minimum number of cases, a customer or organization associated with the medical product, a name of the medical product, a medical product type, any substances included in the medical product, and one or more medical product identifiers (e.g., e.g., NDC product code,

NDC package code, brand name, generic name, a medical product application number, substance name(s), drug authorization number, drug role, etc.) associated with the medical product. FIG. 4 shows a signal product profile page 400 through which the user of the user computing device 108 can generate and provide medical product data associated with one or more medical products to the provider computing system 104.

(49) In some embodiments, at step 210, the provider computing system 104 may receive medical product data that is associated with a signal product profile (e.g., signal product profile data). The signal product profile may be associated with one or more medical products and include a name, one or more statistical value thresholds or minimums, a primary data source(s), an associated organization or customer, one or more associated substances, and one or more medical product identifiers, as shown and discussed regarding FIG. 4. In some embodiments, after receiving the signal product profile data, the provider computing system 104 may store the signal product profile in a signal product profile repository. In this regard, at or after step 210, the provider computing system 104 may retrieve or select the signal product profile from the signal product profile repository for subsequent use.

(50) Once the provider computing system 104 has received the medical product data, the method 200 proceeds to step 211 at which the provider computing system 104 receives adverse event identifiers associated with one or more adverse events. In some embodiments, the adverse event identifiers may be received from a medical dictionary repository internal or external to the provider computing system 104 (e.g., a MedDRA repository (not shown)). Further, the adverse event identifier may include data pertaining to the adverse event such as an adverse event term (e.g., MedDRA term), adverse event code (e.g., MedDRA code), and/or the class within the MedDRA hierarchy of the adverse event (e.g., System Organ Class (SOC), High-Level Group Term (HLGT), High Level Term (HLT), Preferred Term (PT), Lowest Level Term (LLT), etc.). In some embodiments, each adverse event may be associated with two adverse event identifiers (e.g., a MedDRA term and MedDRA code).

(51) In some embodiments, before or after step 211, the provider computing system 104 may receive data from one or more external repositories (not shown). For example, the provider computing system 104 may receive NDC data from an external NDC repository (e.g., the NDC directory associated with the FDA). The NDC data may include medical product data including multiple medical product identifiers (e.g., NDC product code, NDC package code, brand name, generic name, application number, substance name(s), drug authorization number, and/or drug role), a medical product marketing start date, and a medical product marketing end date. In another example, the provider computing system may receive substance data from an external substance repository (e.g., the Unique Ingredient Identifier (UNII) repository associated with the FDA). The substance data may include multiple substance identifiers (e.g., substance name, the chemical formula of the substance, UNII of the substance) and a list of marketed medical products within which the substance is used. In some embodiments, the provider computing system 104 may further receive Structured Product Labeling (SPL) data, RxNorm data, and/or PharmClass data from external data repositories. The external data (e.g., the NDC data, the substance data, the SPL data, the RxNorm data, and/or PharmClass data) may be used by the provider computing system 104 to merge the health agency case data with the medical product data received at step 210 and/or the adverse event identifiers received at step 211. For example, the provider computing system 104 may utilize the external data to standardize vocabularies and determine matches between the medical product data, the adverse event identifiers, and/or the health agency case data.

(52) Once the provider computing system 104 has received the adverse event identifiers, the method 200 proceeds to step 212 at which the provider computing system 104 combines the cleaned health agency case data with at least a portion of the medical product data and one or more of the multiple adverse event identifiers. To combine health agency case data with at least a portion of the medical product data, the provider computing system 104 may match at least a portion of the

medical product identifiers of the medical product data with one or more medical product identifiers of the cleaned health agency case data. For example, the medical product data may be associated with a first case and a second case. As a result, the medical product data may include a first medical product identifier (e.g., an NDC) for the first medical product, a second medical product identifier for the second medical product (e.g., an NDC), and a third medical product identifier for the first medical product (e.g., an application number). The provider computing system **104** may search or analyze the cleaned health agency case data for any cases that include the first medical product identifier, the second medical product identifier, or the third medical product identifier. Then, in response to determining the cleaned health agency case data includes a case with the first medical product identifier, the provider computing system **104** may combine at least a part of the matching cleaned health agency case data with at least a part of the matching medical product data. For instance, if the cleaned health agency data includes an NDC but does not include substance data and a brand name, the provider computing system **104** may add the substance data and the brand name of the medical product data to the cleaned health agency data and generate combined cleaned health agency data.

(53) Likewise, to combine health agency case data with one or more of the adverse event identifiers, the provider computing system **104** may match at least a portion of the adverse event identifiers with one or more adverse event identifiers of the cleaned health agency case data. For example, the adverse event identifier may be associated with a first adverse event. As a result, the adverse event identifiers may include a first adverse event identifier (e.g., a MedDRA term) for the first adverse event and a second adverse event identifier for the first adverse event (e.g., a MedDRA code). The provider computing system **104** may search or analyze the cleaned health agency case data for any cases that include the first adverse event identifier or the second adverse event identifier. Then, in response to determining the cleaned health agency case data includes a case with the first adverse event identifier, the provider computing system **104** may combine at least a part of the matching cleaned health agency case data with at least a part of the matching adverse event identifier(s). For instance, if the cleaned health agency data includes a MedDRA term but does not include a MedDRA code, the provider computing system **104** may add the MedDRA code of the adverse event identifier(s) to the cleaned health agency data and generate combined health agency data.

(54) In some embodiments, to combine the cleaned health agency case data with the medical product data and generate or determine combined health agency case data, the provider computing system **104** may further include a link to a medical product data object of the medical product data within the combined health agency case data. For example, the provider computing system **104** may determine the cleaned health agency case data includes case data associated with a first medical product, and that the medical product data includes medical product data associated with the first medical product. In response, the provider computing system **104** may combine the matching medical product data with the matching health agency case data and generate combined health agency case data including a link or other digital connection (of the medical product data) to a medical product data object associated with the medical product.

(55) In some embodiments, to combine the cleaned health agency case data with the adverse event identifiers and generate or determine combined health agency case data, the provider computing system **104** may further include a link to an adverse event identifier data object of the adverse event identifier within the combined health agency case data. For example, the provider computing system **104** may determine the cleaned health agency case data includes case data associated with a first adverse event, and that the adverse event identifier includes an identifier matching the first adverse event. In response, the provider computing system **104** may combine the matching adverse event identifier with the matching health agency case data and generate combined health agency case data including a link or other digital connection to an adverse event identifier object associated with the adverse event.

(56) In some embodiments, the provider computing system **104** may use the external data to combine the cleaned health agency case data with at least a portion of the medical product data and the adverse event identifiers. For instance, if the provider computing system **104** combines or codes all the cases within the case data with medical product data and adverse event identifiers besides two (e.g., a first case and a second case), the provider computing system **104** may use the external data to assist in combining the data. For example, the case data associated with the first case may have been combined or matched with the adverse event identifier but not a medical product. In response, the provider computing system **104** may utilize the external data (e.g., the NDC data, the substance data, the SPL data, the RxNorm data, and/or PharmClass data) to transform the medical product identifier of the case data to one that matches the medical product data. For instance, the NDC data may include an NDC product code that matches the NDC product code of the cleaned health agency case data and is not included within the medical product data. Then, the provider computing system **104** may determine a medical product identifier (e.g., brand name) of the cleaned health agency case data based on the NDC data, and match/combine the cleaned health agency case data with the medical product based on the determined medical product identifier.

(57) By cleaning the health agency case data received from the health agency case repository **184** (and other additional case data) and then combining the health agency case data with the medical product data from the medical product repository **134** and the adverse event identifiers of the adverse event identifier repository (not shown) such that the resulting case data is a standard format, standard data type, and deduplicated, the provider computing system **104** provides for higher quality and more available case data stored within the central case data warehouse **130** and a technical improvement to signal detection data management systems overall. For example, because the provider computing system **104** standardizes the health agency case data (and other additional case data) and combines the case data with medical product data and adverse event identifiers such that it is in a standard format, the provider computing system **104** is able to utilize multiple different data sources (including external sources) or repositories to collect case data for the central case data warehouse **130**, which provides for more case data available to the provider computing system **104** when determining potential signals than in typical signal detection data management systems, which typically only utilize a single data source (e.g., so all the received case data is structured the same). Further, because the provider computing system **104** cleans the case data by removing special characters and converting each field of the case data to a specific data type, the provider computing system **104** and the central case data warehouse **130** provide for a more reliable, trusted, and error-free data source, that can be used without having to handle and store invalid data. Because external case data can come from a variety of sources, the case data can typically include a large number of errors, invalid data, and be unreliable. In a typical signal detection data management system, these errors and invalid data may be stored within the case repository and utilized when detecting signals, which can provide or cause inaccurate and unreliable signal detection. In comparison, the provider computing system **104** cleans the case data by removing special characters, deduplicating the data, and converting each field of the case data to a specific data type which removes the errors and invalid data. By doing so, the central case data warehouse **130** does not store the invalid data saving on memory and processing power and produces more valid and standardized case data which provides for more accurate and reliable signal detection overall.

(58) Once the provider computing system **104** has combined the cleaned health agency case data with at least a portion of the medical product data and at least a portion of the adverse event identifiers and generated/determined combined health agency case data, the method **200** proceeds to step **216** at which the provider computing system **104** receives or selects trusted case data from the trusted case repository **146**. The trusted case data may be associated with multiple cases, each case associated with a medical product and an adverse event. The trusted case data may include data pertaining to each of the cases including a medical product identifier (e.g., NDC product code,

NDC package code, brand name, generic name, application number, substance name(s), drug authorization number, drug role, etc.) of the medical product associated with the case, an adverse event identifier (e.g., adverse event term, adverse event code, MedDRA version, etc.) of the adverse event associated with the case, patient non-identifying data (e.g., patient initials, patient age group, patient gender, etc.), adverse event information associated with the case (e.g., reporter country, reporter qualification, etc.), a seriousness of the case (e.g., serious: results in death, serious: life threatening, non-serious, etc.), a case identifier (e.g., a case unique identifier (UID), a case ID, etc.), case version data (e.g., version 1.0, version active start date, version active end date), and/or one or more pieces of date/time data (e.g., date/time the case was first/initially received by the PV circuit **144**, date/time the most recent case data was received by the PV circuit **144**, etc.) associated with the case. In some embodiments, the trusted case data may be received or selected from the trusted case repository **146** before the health agency case data (e.g., before step **204**). In some embodiments, the trusted case data may be received by the provider computing system **104** at a specific interval of time (e.g., weekly). In other embodiments, the trusted case data may be received by the provider computing system **104** as the cases enter a closed state (e.g., closed, submitted, etc.) as determined by the PV circuit **144**. For example, the PV circuit **144** may change the state of a specific case from Active to Closed and then provide the case and the trusted case data to the central case data warehouse **130** for storage (e.g., within the one or more PV repositories **132**).

(59) By utilizing the trusted case repository **146** and receiving trusted or PV case data, the provider computing system **104** and the system **100** provide for an improved signal detection system overall. For instance, typical signal detection systems may utilize a single source of case data (e.g., FAERS) to determine and detect potential signals, which can lead to a shortage in data as well as missing or not including cases that are determined to not require reporting to the health authority (e.g., the FDA). In comparison, the present system **100** is a signal detection system that directly receives trusted case data from the PV circuit **144** (e.g., from a PV safety application). By doing so, the system **100** and the provider computing system **104** has access to case data that is not reported to the health authorities but still may provide helpful insights and more accurate signals overall. Further, because the case data is received from the trusted case repository **146** and the PV circuit **144**, the case data is assumed to be of a high quality and accuracy (e.g., due to the rigors the case data must go through in the PV circuit **144** (e.g., validation, verification, medical review, etc.) and does not require cleaning while still being relatively error free. As a result, the provider computing system **104** saves on processing power by not cleaning the trusted case data, while still storing a high-quality and valid set of case data within the central case data warehouse **130** and then utilizing the trusted set of case data to determine potential signals.

(60) In some embodiments, the order in which the medical product data, the adverse event identifiers, the trusted case data, and the health agency case data are received may differ from what is shown (e.g., the adverse event identifiers may be received before the medical product data and the health agency case data, the trusted case data may be received before health agency case data, and the like). Furthermore, in some embodiments, medical product data, the adverse event identifiers, the trusted case data, and/or the health agency case data may be received in two or more steps. For example, the provider computing system **104** may receive a first set of health agency case data at step **204** (and proceed through steps **204-212**) and a second set of health agency case data at a later time (and again proceed through steps **204-212**). In this regard, the provider computing system **104** may receive the medical product data, the adverse event identifiers, the trusted case data, and/or the health agency case data as a stream of data in portions over time. When the provider computing system **104** receives multiple sets of case data, the provider computing system **104** may move through the order of the method **200** in the same way. If for example, the provider computing system **104** receives a set of trusted case data but does not receive a set of health agency case data, the provider computing system **104** may begin at step **216** and

match/combine the trusted case data with the case data included in the central case data warehouse **130** (e.g., within the one or more health agency repositories **131**, within the one or more PV repositories **132**, and/or within the one or more additional case repositories **133**) at step **220**. Likewise, if the provider computing system **104** receives a set of health agency case data but does not receive a set of trusted case data, the provider computing system **104** may begin at step **204** and match/combine the trusted case data with the case data included in the central case data warehouse **130** (e.g., within the one or more health agency repositories **131**, within the one or more PV repositories **132**, and/or within the one or more additional case repositories **133**) at step **220** (and skip step **216**). In this regard, the provider computing system **104** may link or match the case data incrementally (as it is received).

(61) Once the provider computing system **104** has received the trusted case data, the method **200** proceeds to step **220** at which the provider computing system matches at least a portion of the combined health agency case data with the trusted case data (e.g., determines the portions match). To match each case of the combined health agency case data with the trusted case data, the provider computing system **104** may determine whether each case of the trusted case data matches a case of the combined health agency data based on the case identifier being the same. For example, the provider computing system **104** may determine the trusted case data is associated with a first case and includes a first case identifier (e.g., case UID “101”). Then, the provider computing system may search the combined health agency data for a case including the same first case identifier and determine one or more matches. In some embodiments, at step **220**, the provider computing system **104** may match one or more of the cases of the trusted case data and the combined health agency case data (e.g., based on matching case identifiers). Then, after step **220**, the provider computing system **104** may link the case data and the combined health agency case data based on the matching cases.

(62) In some embodiments and in response to determining a match, the provider computing system **104** may generate a link or other digital connection and modify the trusted case data to include the link. The link may point to the matching case of the combined health agency case data and provide an indication that each case is the same. Likewise, the provider computing system **104** may generate a second link or other digital connection and modify the combined health agency case data to include the second link. The second link may point to the matching case of the trusted case data and provide an indication that each case is the same. In other embodiments, the provider computing system **104** may join/combine the trusted case data and the combined health agency case data into a single set of central case data (e.g., within a single table) into which each case is distinct. For example, the provider computing system **104** may generate a set of central case data including or associated with multiple cases. In some embodiments, the central case data may be stored in a table. As a result, each case may be delimited by a separate row or column and/or each case electronic data source or case data type (e.g., PV circuit **144**, a first health agency computing system **112**, a second health agency computing system **112**) is delimited by a separate row or column. In this regard, while the case data is combined or mixed to form the central case data, each type or source of case data (e.g., trusted case data, health agency case data, etc.) is still distinguished and/or separated, such that the provider computing system **104** can output each type of case data individually.

(63) In some embodiments, prior to step **220**, the provider computing system **104** may receive additional case data (e.g., external case data). For example, the provider computing system **104** may receive additional case data from a medical literature repository (e.g., PubMed®, Embase®, and the like), a social media case mining repository (i.e., a repository where potential or verified cases that are mined from social media (e.g., Facebook®, Twitter®, etc.) data are stored), and other external repositories through which case data can be retrieved/received from. Moreover, at step **220**, the provider computing system **104** may match and/or combine the trusted case data, the combined health agency case data, and the additional case data based on the case identifiers of

each. For instance, the provider computing system **104** may match a first case of the trusted case data, with a second case of the combined health agency case data and a third case of the additional case data based on each having the same case identifier (e.g., case UID). The provider computing system **104** may then combine/join or link all of the matching case data as described herein. In some embodiments, the provider computing system **104** may further assign a priority ranking to each electronic data source. For example, the provider computing system **104** may assign a priority of **1** to the trusted case data source, a ranking of **2** to the health agency case data source, and the like.

(64) While multiple types of case data are described herein, it should be understood that each type of case data (e.g., central case data, health agency case data, trusted case data, external social media case data, external medical literature case data, etc.) is associated with or includes data that is related to a case. While the different types of case data may be structured differently overall, each type of case data may include a case identifier, a medical product identifier, an adverse event identifier, and/or date data. If the case data received does not include one or more of a case identifier, a medical product identifier, an adverse event identifier, and/or date data, the provider computing system **104** may clean and combine the case data as discussed with regard to step **208** and **212** to standardize the case data and ensure all the case data stored within the central case data warehouse **130** is usable.

(65) Once the provider computing system **104** has matched and linked or combined the trusted case data and the combined health agency case data, the method **200** proceeds to step **224** at which the provider computing system **104** stores the combined health agency case data and the trusted case data within the central case data warehouse **130** (e.g., within the one or more health agency repositories **131** and within the one or more PV repositories **132**). In some embodiments, the provider computing system **104** may store the generated central case data within the central case data warehouse **130** (e.g., within the central case repository **195**) at step **224**. In one example, the central case data may be stored within a table and the table may be stored within the central case repository **195** of the central case data warehouse **130**.

(66) Once the provider computing system **104** has stored the case data (e.g., the central case data) within the central case data warehouse **130**, the method **200** proceeds to step **228**, at which the provider computing system **104** receives a request for case data. The request may identify one or more electronic sources (electronic data sources) (e.g., the trusted case repository **146**, FAERs, one or more external medical literature case repositories, EVDAS, etc.). In some embodiments, the request for case data may be generated by and received from the user computing device **108**.

(67) If at step **228** the request identifies only the health agency case repository **184** as the electronic data source, the method **200** proceeds to step **232**, at which the provider computing system **104** outputs the combined health agency case data (e.g., from the health agency repository **131**). In some embodiments, if the different types of case data were combined to form central case data, the provider computing system **104** may output the portion of the central case data delimited as from the health agency case repository **184** (e.g., the portion of the central case data within the health agency case repository **184** row or column) from the central case repository **195**. In some embodiments, the combined health agency case data may be output by the provider computing system **104** to the user computing device **108** (e.g., to enable display on a user interface as will be described further herein.). In other embodiments, the combined health agency case data may be output by the provider computing system to one or more of the health agency computing systems **112**. In some embodiments, the request may include an address (e.g., IP address, email address, Amazon S3® bucket address, file transfer protocol (FTP) address, etc.) to which the case data is to be output.

(68) If at step **228** the request identifies only the trusted case repository **146** as the electronic data source, the method **200** proceeds to step **236**, at which the provider computing system **104** outputs the trusted case data (e.g., of the one or more PV repositories **132**). In some embodiments, if the

case data was combined to form central case data, the provider computing system **104** may output the portion of the central case data delimited as from the trusted case repository **146** (e.g., the portion of the central case data within the trusted case repository **146** row or column) from the central case repository **195**. In some embodiments, the trusted case data may be output by the provider computing system **104** to the user computing device **108** (e.g., to enable display on a user interface as will be described further herein.) In other embodiments, the trusted case data may be output by the provider computing system to one or more of the health agency computing systems **112**. In some embodiments, the request may include an address (e.g., IP address, email address, Amazon S3® bucket address, file transfer protocol (FTP) address, etc.) to which the case data is to be output.

(69) If at step **228** the request identifies both the health agency case repository **184** and the trusted case repository **146** as the electronic data sources, the method **200** proceeds to step **240**, at which the provider computing system **104** outputs the trusted case data (e.g., from the PV repositories **132**) and a portion of the combined health agency case data (e.g., from the health agency repository **131**). As described herein, because the trusted case repository **146** is an internal repository to the provider computing system **104** and receives high-quality case data, the trusted case repository **146** is trusted or preferred. In this regard and when both electronic sources are selected, the provider computing system **104** may output the trusted case data and the portion of the combined health agency case data for which there is no matching trusted case data. By doing so, the provider computing system **104** outputs the highest relative quality of case data, while providing for maximum volume of case data. The provider computing system **104** may determine the combined health agency case data for which there is no matching trusted case data based on the links included in the health agency case data. In some embodiments, the portion of the combined health agency case data for which there is no match and the trusted case data may be output by the provider computing system **104** to the user computing device **108** (e.g., to enable display on a user interface as will be described further herein.) In other embodiments, the portion of the combined health agency case data for which there is no match and the trusted case data may be output by the provider computing system to one or more of the health agency computing systems **112**. In some embodiments, the request may include an address (e.g., IP address, email address, Amazon S3® bucket address, file transfer protocol (FTP) address, etc.) to which the case data is to be output.

(70) To output the trusted case data and the portion or segment of the combined health agency data, the provider computing system **104** may first select or query the central case warehouse **130** for all case data associated with the medical product (e.g., all of the combined health agency case data from step **232** and all of the trusted case data from step **236**). Then, the provider computing system **104** may determine the matching portion or segment of the combined health agency case data based on the generated links included in the selected trusted case data. Finally, the provider computing system **104** may remove the matching portion or segment of the combined health agency case data from all of the selected health agency case data. The resulting portion or segment may be the health agency case data for which there is no match.

(71) In some embodiments, if the case data was combined to form central case data, the provider computing system **104** may output the portion of the central case data delimited as from the trusted case repository **146** and the portion of the central case data delimited as from the health agency case repository **184** for which there is no match (e.g., for which there is no data in the trusted case repository row or column).

(72) In some embodiments, when more than one electronic data source is identified in the request, the provider computing system **104** may select portions of the central case data based on the priority of each electronic data source. For example, if the request identifies the health agency case repository **184**, the trusted case repository **146**, and an external medical literature case repository, the provider computing system **104** may output portions of each case type based on the priority of the electronic data source. If, for example, the trusted case repository **146** was assigned priority **1**,

the health agency case repository **184** was assigned priority **2**, and the external medical literature case repository was assigned priority **3**, the provider computing system **104** may output all of the trusted case data that matches the request, the combined health agency case data for which there is not a match with the trusted case data, and the medical literature case data for which there is not a match with the trusted case data or the combined health agency case data. In some embodiments, because the trusted case repository **146** is trusted or preferred, the trusted case repository **146** may always be assigned a priority of **1**, and the user computing device **108** may assign a priority to the rest of the electronic data sources. In other embodiments, the user computing device **108** may assign a priority to all of the electronic data sources. In some embodiments, if there are multiple versions of a case that match the request (e.g., version 1.0 from the trusted case repository **146**, version 2.0 from the trusted case repository **146**, and version 2.0 from the health agency case repository **184**), the provider computing system **104** may output the most recent version of the case from the highest priority source.

(73) By linking or merging the case data such that it is interconnected and then outputting the case data based on the electronic data source(s) of the request, the provider computing system **104** outputs the maximum amount of case data possible while preventing duplicate cases from being included within the output case data, thereby providing an improvement to case data warehousing and querying systems. For instance, by outputting the case data based on the priority of the type of the case data, the provider computing system **104** selects the maximum amount of case data that reflects the priority (e.g., as much case data as possible from the source identified as priority **1**, any case data that is not available from priority **1** from the source identified as priority **2**, and so on) while not including duplicates. In typical case data warehousing and querying systems, a single data source is utilized such that linking/combining of the case data is not required, which provides for a much smaller set of case data. In comparison, by including the maximum amount of case data while still removing/preventing duplicate data, the provider computing system **104** provides for more accurate signal detection and overall better statistical values by including multiple sources/types of case data. The additional case data provides for more insights and data points on which the provider computing system **104** can calculate the statistical scores and determine potential signals, thereby providing more accurate signal detection. Further, by preventing the output of duplicate case data by linking the case data and only outputting a single set of each case, the provider computing system **104** prevents duplicate bias which skews the signals and statistical values generated toward the duplicate data.

(74) Additionally, by linking or combining each type of the case data such that it is still distinguishable and can be individually output, the provider computing system **104** provides for a central repository and location of case data while providing flexibility and customizability on the case data sought. In this regard, the provider computing system **104** allows for the user computing device **108** to indicate (e.g., in the request) the sources from which case data is sought, and the provider computing system **104** outputs the corresponding case data while preventing duplicates from being output. By doing so, the provider computing system **104** provides additional insights into the signal and statistical values that are typically not available due to the use of a single source by separating the case data based on the source.

(75) Referring now to FIG. **3**, a method **300** of dynamically querying standardized case data from the data warehouse and determining one or more potential signals is shown, according to an example embodiment. While different overall, it should be understood that any steps or discussion of the method **300** may be applied or included within the method **200**, and vice versa, and that such combinations are included within the scope of the present disclosure. For example, the method **300** may include any of the steps **204-240**, after or before any steps included in the method **300**, and the method **200** may include any of the steps **304-328**, after or before any of the steps included in the method **200**. In this regard, method **200** demonstrates how the case data may be standardized and loaded into the central case data warehouse **130**, and the method **300** demonstrates how the case

data may be queried and output from the central case data warehouse **130**. Method **300** can be carried out by the system of FIG. **1**. More particularly, the method **300** can be carried out by the processing circuit **122** of the provider computing system **104** and through communication with the user computing device **108** and the health agency computing systems **112**.

(76) Method **300** commences at step **304** at which the provider computing system receives a request for case data. The timeframe may include a start date/time and an end date/time. The request may identify a timeframe and a medical product. In some embodiments, the request may further identify an electronic data source, an adverse event, and one or more filters (e.g., statistical value minimums or maximums, age group(s), gender(s), seriousness, etc.) as will be described further herein. In some embodiments, the request may be received from and generated by the user computing device **108**. In some embodiments, the request may include an electronic address to which the resulting case data is to be provided.

(77) Once the provider computing system **104** has received the request, the method **300** proceeds to step **306** at which the provider computing system **104** receives one or more statistical value minimums or thresholds. In some embodiments, the statistical value thresholds may be received within the medical product data (e.g., of step **210** of the method **200**) from the user computing device **108**. In other embodiments, the statistical value thresholds may be received as a part of a signal product profile (e.g., signal product profile data). The statistical value minimums may represent a minimum value for each of the statistical values when determining potential signals of the medical product. For instance, the statistical value minimums received in association with Drugx, may indicate a potential signal of Drugx must have a minimum of 3 cases and a minimum PRR of **3**. In other embodiments, the statistical value minimums may be received separately from the medical product data and be specific to all medical products. In some embodiments, the statistical value minimums may be specific to a selected adverse event.

(78) Once the provider computing system **104** has received the statistical value minimums, the method **300** proceeds to step **308** at which the provider computing system **104** selects case data from the central case warehouse **130** (e.g., from the one or more health agency repositories **131**, from the one or more PV repositories **132**, from the one or more additional case repositories **133**, etc.) based on the request. For example, the provider computing system **104** may query or select case data from the central case warehouse **130** based on the case data matching or including the medical product identified in the request (e.g., based on a medical product identifier of the case data matching a medical product identifier of the case data). In addition, the provider computing system **104** may query or select case data based on the case data being active within the timeframe (e.g., after the start date/time and before the end date/time of the case data). For instance, the request may request and/or identify case data associated with DrugX that was active between Jan. 1, 2001 and Jan. 1, 2002. In response, the provider computing system **104** may query or select case data that is associated with or includes DrugX and that includes a receipt or new info date/time (e.g., an active version start date/time) before Jan. 1, 2002 and an active version end date/time after Jan. 1, 2001. If two or more versions of the same case meet this criterion, the provider computing system **104** may select the most recent version from the central case warehouse **130** (e.g., from the one or more health agency repositories **131**, from the one or more PV repositories **132**, from the one or more additional case repositories **133**, etc.).

(79) In some embodiments, the request may identify a signal product profile (which will be described further herein); each signal product profile may represent or be associated with multiple medical products (e.g., DrugX (50 mg) and DrugX (30 mg)) or substances. In this regard, at step **308**, the provider computing system **104** may return case data that matches the signal product profile (e.g., either DrugX (50 mg) or DrugX (30 mg)).

(80) If the request further includes or identifies an adverse event and one or more filters, the provider computing system **104** may further query or select case data from the central case warehouse **130** (e.g., from the one or more health agency repositories **131**, from the one or more

PV repositories **132**, from the one or more additional case repositories **133**, etc.) based on the case data meeting/matching the adverse event and the one or more filters (in addition to the medical product and the timeframe). For example, if the request further identifies an adverse event of “stomach mass” and a filter of seriousness being “Results in Death”, the provider computing system **104** may select case data of cases in which the adverse event is a stomach mass (e.g., based on the adverse event identifiers matching) and the seriousness is results in death. If the request further includes or identifies one or more electronic data sources, the provider computing system **104** may select the case data as described with reference to the steps **228-240** of the method **200** from the central case warehouse **130** (e.g., based on the priority and the matching case data as determined by the provider computing system **104** at step **220**).

(81) As described herein, the central case data warehouse **130** may include one or more health agency repositories **131**, one or more central PV case repositories **132**, and one or more additional case repositories **133**. In this regard, the case data selected at step **308** may be selected, by the provider computing system (e.g., the processing circuit **128**), from any of the one or more health agency repositories **131**, the one or more additional case repositories **133**, and the one or more central PV case repositories **132** of the central case data warehouse **130**. For instance, the provider computing system **104** may query or select case data from the central health agency case repository **131** and one or more of the multiple central PV case repositories **132** based on the case data matching or including the medical product identified in the request. As described herein, each central PV case repository **132** may be associated with and include trusted case data associated with a specific medical product. In this regard, the provider computing system may query or select case data from a specific PV repository **132** based on the case data matching or including the medical product identified in the request.

(82) Once the provider computing system **104** has selected the case data from the central case data warehouse **130**, the method **300** proceeds to step **312** at which the provider computing system **104** determines one or more statistical values based on the selected case data. If the request does not specify an adverse event, the provider computing system **104** may determine one or more statistical values for each MedDRA PT adverse event within the case data. For instance, the provider computing system **104** may group the selected case data by PT and determine one or more statistical values including a case count, a PRR value, an $x_{sup.2}$ value, multiple EBGM values, an Interaction Signal Score (INTSS) value, one or more confidence scores, and/or the like for each group of cases/case data. In comparison, if the request specifies an adverse event, the provider computing system **104** may determine one or more statistical values for the case data associated with that adverse event.

(83) The PRR value is a statistical value that is used to summarize the extent to which a particular adverse event is reported for individuals taking a specific medical product, compared to the frequency at which the same adverse event is reported for patients taking some other medical product. A PRR value greater than 1 typically suggests that the adverse event is more commonly reported for individuals taking the medical product of interest, relative to the comparison medical product. Similarly, the $x_{sup.2}$ value is a statistical test and value that is produced and used to determine whether there is a statistically significant difference between the expected frequencies and the observed frequencies of adverse events occurring with the use of a medical product. Standard values of interest for PRR are ≥ 3 and ≥ 4 for $x_{sup.2}$, with ≥ 3 cases.

(84) The EB values include the Empirical Bayes Geometric Mean (EBGM) value, the EB05 value, and the EB95 value. The EB values are calculated using the Multi-Item Gamma Poisson Shrinker (MGPS) method, where a repository or a combination of repositories is analyzed and searched for the occurrence of unexpectedly frequent medical product-event combinations occurring. MGPS produces a score called EBGM, EB05, and EB95 for a medical product-adverse event combination and a score called INTSS for a medical product 1-medical product 2-adverse event combination. The EBGM value is the geometric mean of a posterior distribution. The 5th (EB05) and 95th

percentiles (EB95) of a posterior distribution create a two-sided 90% credibility interval.

(85) Once the provider computing system **104** has determined one or more statistical values based on the selected case data, the method **300** proceeds to step **316** at which the provider computing system **104** determines one or more potential signals based on the one or more statistical values and the one or more statistical value minimums. As described herein, for each group of case data (e.g., for each MedDRA PT), the provider computing system **104** may determine whether the statistical values indicate the medical product and adverse event are a potential signal. For example, the provider computing system **104** may compare the statistical values with the minimum statistical values, and assuming they are greater than or equal to each of the respective minimums, determine the adverse event and medical product pair are a potential signal. If the statistical values are less than the minimum statistical values, the provider computing system **104** may determine the adverse event and medical product pair are not a potential signal. If the request identified an adverse event, the provider computing system **104** may compare the statistical values with the minimum statistical values, and assuming they are greater than or equal to each of the respective minimums, determine the adverse event and medical product pair are a potential signal.

(86) In some embodiments, the provider computing system **104** may determine a potential signal in response to a single statistical value being greater than the corresponding minimum statistical value. In other embodiments, the provider computing system **104** may determine a potential signal in response to two or more statistical values being greater than the corresponding minimum statistical values. In some embodiments, the user via the user computing device **108** may set the number of statistical values that must be greater than the corresponding minimum statistical values to determine a potential signal (which may then be provided to the provider computing system **104**). In other embodiments, the user via the user computing device **108** may set a specific set of one or more statistical values (e.g., PRR and case count, EBGm and PRR, etc.) that must be greater than the corresponding minimum statistical values to determine a potential signal (which may then be provided to the provider computing system **104**).

(87) Once the provider computing system **104** has determined one or more potential signals based on the one or more statistical values and the one or more statistical value minimums, the method **300** proceeds to step **320** at which the provider computing system **104** outputs the case data, the one or more statistical values, and/or the one or more potential signals. In some embodiments, the provider computing system **104** outputs the case data, the one or more statistical values, and/or the one or more potential signals to the user computing device **108**. In some embodiments, the provider computing system **104** outputs each to the user computing device **108** enable display on a user interface as will be described further herein with regard to FIGS. 5A-7B. In some embodiments, the provider computing system **104** outputs the case data, the one or more statistical values, and/or the one or more potential signals to one or more of the health agency computing systems **112**.

(88) In some embodiments, once the provider computing system **104** has output the case data, the one or more statistical values, and/or the one or more potential signals, the provider computing system **104** may generate an electronic document including one or more of: the case data, the one or more statistical values, and/or the one or more potential signals. In some embodiments, the electronic document may be an aggregate or periodic report such as a Periodic Safety Update Report (PSUR) or a Periodic Benefit-Risk Evaluation Report (PBRER). In other embodiments, the electronic document may be an E2B XML file including one or more of: the case data, the one or more statistical values, and/or the one or more potential signals. In some embodiments, the provider computing system **104** generates the electronic document in response to receiving a verification or validation of the one or more potential signals. In some embodiments, the provider computing system **104** may receive at least a portion of the electronic document from the user computing device **108** and modify the electronic document to include the one or more of: the case data, the one or more statistical values, and/or the one or more potential signal. In some embodiments, the electronic document is an Excel file, a Comma Separated Value (CSV) file, a

PDF file, or an HTML file.

(89) Once the provider computing system **104** has generated the electronic document, the provider computing system **104** may output the electronic document. In some embodiments, the provider computing system **104** may output the electronic document to at least one of the user computing device **108** or one or more of the health agency computing systems **112**. In some embodiments, the provider computing system **104** may output the electronic document (e.g., as an E2B XML file) to one or more of the health agency computing systems **112** via an AS2 Gateway communication.

(90) In some embodiments, once the provider computing system **104** has output the case data, the one or more statistical values, and/or the one or more potential signals to enable display on the user interface, the provider computing system **104** may receive a request to track a specific potential signal from the user computing device **108**. In response, the provider computing system **104** may generate a tracked signal data object associated with the specific medical product and a specific adverse event and store the tracked signal data object in a tracked signal repository (not shown). In some embodiments, the provider computing system **104** may then use the tracked signal data object to store case data, statistical values, and user inputs associated with the specific tracked signal (e.g., comments, analysis, etc.). In this regard, the electronic document described herein may be populated with the data of the tracked signal data object for reporting the specific tracked signal.

(91) Referring now to FIGS. **4-8**, user interfaces shown and displayed to the user of the user computing device **108** during the methods **200** and/or **300** are shown, according to example embodiments. As described herein, the user interfaces of FIGS. **4-8** may be one or more of web interfaces generated by the provider computing system **104** and rendered by the user computing device **108** as part of a web application or graphical user interfaces downloaded and generated by the user computing device **108** as part of a software application (e.g., a mobile application, etc.). Further, the user interfaces shown on FIGS. **4-8** allow for communication between the user and the provider computing system **104** via the user computing device **108** (specifically via the I/O circuit **162**). Through interaction with the various user interfaces, the user may provide user input, feedback, and other data requested by the provider computing system **104**. In this regard, it should be understood that each interaction described herein by the user with the user interfaces of FIGS. **4-8** may be provided to the user computing device **108** and then transmitted to the provider computing system **104** and that each action described herein as occurring to the user and/or the user computing device **108** (e.g., navigating to a certain page, generating a popup, etc.) may be performed by the provider computing system **104**.

(92) Referring now to FIG. **4**, a medical product or signal product profile page **400**, which can be displayed on a display of the I/O circuit **162** of the one or more of the user computing devices **108**, is shown. In general, the signal product profile page **400** provides the respective user computing device **108** with an interface to initially set, view, and manage the settings for signal detection for a specific medical product (e.g., drug X) and provide any changes to the medical product data to the provider computing system **104**. For example, via the signal product profile page **400**, the user may provide initial medical product data associated with a medical product to the user computing **108**, which may provide the initial medical product data to the provider computing system **104** to store within the medical product repository **134**. In another example, via the signal product profile page **400**, the user of the user computing device **108** may alter the medical product data associated with the medical product, which may be provided by the user computing device **108** to the provider computing system **104** for storage in the medical product repository **134**. In this regard, the provider computing system **104** may provide medical product data associated with the medical product to the respective user computing device **108** to enable display of the signal product profile page **400** on the display of the I/O circuit **162**. As shown, the signal product profile page **400** includes a signal product profile details section **404**, a generate signals button **406**, a medical product(s) section **430**, a substance(s) section **462**, and an other identifier(s) section **456**.

(93) The signal product profile details section **404** provides the user of the respective user

computing device **108** with an interface to set, manage, and determine the signal details associated with the medical product and includes a profile name field **406**, an organization field **408**, a primary data source field **410**, multiple minimum statistical value minimum fields (e.g., a PRR minimum field **412**, an x.sup.2 minimum field **414**, an EBGM minimum field **416**, an EB05 minimum field **418**, and a minimum case count field **420**), an include generic products checkbox or field **422**, an include characterization concomitant checkbox or field **424**, and an include characterization interacting field **426**. It should be understood that each of the fields **406-420** may be included in or a part of the medical product data or signal product profile data described herein (e.g., with regard to step **210** or step **306**).

(94) The profile name field **406** is a selectable and/or editable text field through which the user of the respective user computing device **108** can edit the name of the signal product profile associated with the signal and the medical product which may then be sent by the respective user computing device **108** to the provider computing system **104** for storage. Similarly, the organization field **408** is a selectable and/or editable text field through which the user of the respective user computing device **108** can edit the organization or customer (e.g., Pharma X, Contract Research Organization X, etc.) associated with the signal product profile and the signal which may then be sent by the respective user computing device **108** to the provider computing system **104** for storage. In some embodiments, the organization field **408** may determine the permissions the user computing device **108** has (e.g., which medical products or medical product data objects the user computing device **108** can receive case data and medical product data in association with).

(95) Likewise, the primary data source field **410** is a selectable and/or editable text field through which the user of the respective user computing device **108** can edit the default data source associated with the signal product profile and signals thereof which may then be sent by the respective user computing device **108** to the provider computing system **104** for storage. In some embodiments, the primary data source field **410** may determine which data source is automatically selected (and included in the request for case data as described with reference to the methods **200** and **300**) when the user computing device **108** navigates to the signal detection page **500**, as will be described further herein.

(96) The multiple threshold statistical value minimum fields are each selectable and/or editable text fields through which the user of the respective user computing device **108** can edit the threshold statistical value of each of the specific statistical values associated with the signal product profile and signals thereof which may then be sent by the respective user computing device **108** to the provider computing system **104** for storage. For example, via the multiple threshold statistical value minimum fields the user can initially set or edit the threshold PRR value, the threshold x.sup.2 value, the threshold EBGM value, the threshold EB05 value, the threshold (or maximum) EB95 value, the minimum number of cases, and the like.

(97) The generate signals button **406** is a selectable or clickable button that, when selected, may cause the user computing device **108** to generate a request for case data (e.g., as described with regard to the method **300**) associated with the medical product and the medical product data of the signal product profile page **400**. Additionally, when the generate signals button **406** is selected the provider computing system may navigate the user computing device **108** to the signal detection page **500**, which will be described further herein.

(98) The medical product(s) section **430** provides the user of the respective user computing device **108** with an interface to set, manage, and determine the medical products (e.g., medical product data object(s) associated with the signal product profile and the medical product data of the signal product profile page **400**. As shown the medical product(s) section **430** includes one or more medical product or medical product data object representations **434**.

(99) Each medical product representation **434** may represent a specific medical product and/or medical product data object that is associated with the signal product profile of the signal product profile page **400**. In this regard, it should be understood that multiple medical products may be

associated with a single signal product profile. For example, the signal product profile may be associated with DrugX (30 MG) and DrugX (50 MG), which are considered two separate medical products. As shown, each medical product representation **434** includes a name field **436**, a medical product field **438**, a medical product brand or generic name field **440**, a medical product type field **442**, a medical product abbreviation field **444**, and a medical product organization **446**. It should be understood that each of the fields **436-446** may be included in or a part of the medical product data described herein.

(100) The medical product name field **436** is a selectable and/or editable text field through which the user of the respective user computing device **108** can edit the name of the medical product or medical product data objective profile associated with the medical product of the medical product representation **434** which may then be sent by the respective user computing device **108** to the provider computing system **104** for storage. Likewise, the medical product brand or generic name field **408** is a selectable and/or editable text field through which the user of the respective user computing device **108** can edit or set the brand or generic name associated with the medical product of the medical product representation **434** which may then be sent by the respective user computing device **108** to the provider computing system **104** for storage.

(101) Similarly, the medical product type field **442** is a selectable and/or editable text field or drop-down box with options through which the user of the respective user computing device **108** can edit and set the type of the medical product (e.g., Drug, Vitamin, Dietary Supplement, Medical Device, etc.) associated with the medical product representation **434** which may then be sent by the respective user computing device **108** to the provider computing system **104** for storage. Further, the medical product organization field **446** is a selectable and/or editable text field through which the user of the respective user computing device **108** can edit the organization or customer (e.g., Pharma X, Contract Research Organization X, etc.) associated with the medical product of the medical product representation **434** may then be sent to the provider computing system **104** for storage by the respective user computing device **108**.

(102) The substance(s) section **452** provides the user of the respective user computing device **108** with an interface to set, manage, and determine the substance(s) associated with the signal product profile and the medical product data of the signal product profile page **400**. While not shown in detail, the substance(s) section **452** may include one or more substance representations (not shown). Each substance representation may represent a specific substance that is associated with the signal product profile of the signal product profile page **400**. Each substance representation may include multiple substance fields which are editable. For example, each substance representation may include a substance name field, chemical formula field, a UNII field, and the like.

(103) The other identifiers section **456** provides the user of the respective user computing device **108** with an interface to set, manage, and determine other medical product identifiers (i.e., outside of those included in the details section **404**, the medical products section **430**, and the substance(s) section **452**) associated with the signal product profile and the medical product data of the signal product profile page **400**. As shown, the other identifiers section **456** includes one or more medical product identifier representations **458**.

(104) Each medical product identifier representation **434** may represent a specific medical product identifier that is associated with the signal product profile and/or the medical product(s) of the signal product profile page **400**. As shown, each medical product identifier representation **458** includes a medical product identifier name field **460**, a medical product identifier value field **462**, and a medical product identifier type field **464**. It should be understood that each of the fields **460-464** may be included in or a part of the medical product data and/or the medical product identifiers described herein.

(105) The medical product identifier type field **464** is a selectable and/or editable text field and/or drop-down box with options through which the user of the respective user computing device **108** can edit the type (e.g., Application Number, NDC-Product, NDC-Package, etc.) of the medical

product identifier associated with the medical product identifier representation **458** which may then be sent by the respective user computing device **108** to the provider computing system **104** for storage. Likewise, the medical product identifier value field **462** is a selectable and/or editable text field through which the user of the respective user computing device **108** can edit or set the value of the medical product identifier associated with the medical product identifier representation **458** which may then be sent by the respective user computing device **108** to the provider computing system **104** for storage

(106) Referring now to FIGS. 5A-5B, a signal detection page **500**, which can be displayed on a display of the I/O circuit **162** of one or more of the user computing devices **108**, is shown. In general, the signal product profile page **400** provides one or more of the user computing devices **108** with an interface to view and manage case data, statistical values, and potential signals associated with a specific medical product or signal product profile (e.g., the medical product or signal product profile of the signal product profile page **400**). In this regard, the signal detection page **500** may be associated with a specific medical product or signal product profile. To be navigated to the signal detection page **500**, the user of the user computing device **108** may select the generate signals button **406** of the signal product profile page **400**. In response to doing so, the user computing device **108** may generate a request for case data based on and including/identifying the medical product of the signal product profile page **400**, as described with reference to the method **300**. In this regard and in response, the provider computing system **104** may provide the resulting case data, statistical values, and potential signals to the respective user computing device **108** to enable display of the signal detection page **500** on the display of the I/O circuit **162**. As shown, the signal detection page **500** includes a refresh button **502**, an options section **504**, a statistical value chart or graph **522**, a heat map **530**, and a list of detected or potential signals **540**.

(107) The refresh button **502** is a selectable or clickable button that, when selected, may cause the user computing device **108** to generate a request for case data and provide the request to the provider computing system **104**. In this regard, by selecting the refresh button **502**, the user computing device **108** receives the newest updated case data, statistical values, and potential signals from the provider computing system **104** in real-time. In some embodiments, the user computing device **108** may generate the request to identify or include the data sources, the timeframe, and the filters of the options section **504**.

(108) Through refreshing the case data with a selection of the refresh button **502** (and/or the apply button **518**) by receiving a new request for case data and then outputting updated case data, the provider computing system **104** and the system **100** provide for an improved signal detection system. Typically, signal detection systems require manual labor-intensive queries to be setup by a user and then run over a long set of time (e.g., overnight, over the weekend, etc.) before new case data is received and ready for analysis. In this regard, the system **100** provides for a quicker, real-time, process and system for receiving updated case data through the use of the request for case data. For instance, by utilizing a simple request, and not a manual labor-intensive query, the system **100** simplifies the process for request and receiving refreshed/updated case data, and thereby uses less processing power and memory. For instance, instead of taking a long set of time to return updated case data, the system **100** utilizes the request which saves on processing power and memory and returns refreshed case data within a matter of minutes.

(109) The options section **504** provides the user of the respective user computing device **108** with an interface to set, manage, and determine the filters, electronic data sources, and the timeframe which are applied to the case data received from the provider computing system **104** and received and displayed on the signal detection page **500**. As shown the options section **504** includes multiple electronic data source checkboxes (e.g., the FAERs checkbox **506** and the trusted or PV case repository checkbox **507**), one or more timeframe or reporting period fields **508**, multiple filter fields (e.g., the PRR minimum field **510**, the x.sup.2 minimum field **512**, the EBGM minimum field **514**, the EB05 minimum field **516**), and an apply button **518**. In some embodiments, the

multiple electronic data source checkboxes and multiple filter fields may be prepopulated with values based on the medical product or signal product profile of the signal product profile page **400**. For instance, the multiple electronic data source checkboxes may be checked or unchecked based on the primary data source field **410** of the medical product field. For example, the FAERs checkbox **506** may be selected or checked and the trusted or PV case repository checkbox **507** may be unselected or not checked, in response to the primary data source field **410** identifying FAERs as the primary data source. In another example, the PRR minimum field **510** may be prepopulated with the PRR minimum value of the PRR minimum field **412** of the signal product profile page **400**. In some embodiments, the prepopulated values may then be used to generate the request for case data (e.g., included in the request for case data).

(110) The multiple electronic data source checkboxes or fields are each a selectable and editable checkbox through which the user of the respective user computing device **108** can set the one or more electronic data sources to be included in the request for case data described herein. For instance, by selecting the FAERs checkbox **506** and the trusted or PV case repository checkbox **507**, the user computing device **108** may include or identify each within the request for case data (as described with regard to the step **228** of the method **200**). Likewise, the multiple filter fields are each selectable and editable text fields through which the user of the respective user computing device **108** can set the filters to be included in the request for case data described herein.

(111) The timeframe fields **508** are selectable and editable date/time fields through which the user of the of the respective user computing device **108** can set the timeframe (e.g., the active start date and the active end date) to be included in the request for case data described herein. For instance, via the timeframe fields **508**, the user of the user computing device **108** may set the active start date to be Jan. 1, 2004 and the active end date to be Oct. 5, 2022 (as shown in FIG. 5A).

(112) In some embodiments, the apply or apply filters button **518** is a selectable button that, when selected, may cause the user computing device **108** to filter the received case data and generate the statistical value chart or graph **522**, the heat map **530**, and the list of detected or potential signals **540** using the filtered case data. In other embodiments, when the apply button **518** is selected, the user computing device **108** may generate a request for case data including or identifying the data source, the timeframe, and the filters of the fields of the options section **504** (e.g., similar to or the same as the refresh button **502**). In response, the provider computing system **104** may provide updated case data, statistical values, and potential signals to the user computing device **108** to enable display on the signal detection page **500** of the statistical value chart or graph **522**, the heat map **530**, and the list of detected or potential signals **540** including the updated data, values, and signals.

(113) The statistical value chart or graph **522** is a graph or chart that displays the received one or more statistical values in comparison. For example, as shown, the statistical value graph **522** is a bubble chart that includes PRR on the Y-axis and $x_{sup.2}$ on the X-Axis. In some embodiments, the user of the user computing device **108** may select which statistical value is to be displayed on the X-Axis and which statistical value is to be displayed on the Y-Axis. In this regard, each of the bubbles shown may be a group of case data which is grouped by adverse event term (e.g., MedDRA PT), as described herein with regard to the method **300**. Larger circles or bubbles may indicate a larger number of cases, as compared to smaller circles or bubbles. In some embodiments, the bubbles may be colored to provide an indication of the electronic data source from which they came (e.g., blue indicates FAERs, Yellow indicates the trusted or PV case repository **146**, red indicates both, etc.). In some embodiments, the statistical graph **522** is interactive such that the user can select or zoom in/out on the data included in the graph **522** to change the amount of data appearing on the graph **522**.

(114) In some embodiments, if the user selects or clicks on one of the bubbles of the graph, the heatmap **522** and the list of detected or potential signals **540** may display data associated with that bubble (e.g., with the group of cases associated with that bubble). In this regard, selecting case data

within the statistical value chart or graph **522**, the heat map **530**, and/or the list of detected or potential signals **540** may cause the user computing device **108** or the provider computing system **104** to filter the case data of the signal detection page **500** to the selected data.

(115) The MedDRA heatmap **530** is a graph or chart that displays the received case data in a heatmap based on the seriousness, the MedDRA terms used to group the case data, and volume (e.g., number of cases) of the case data. Further, the heatmap **530** may be interactive and display the case data based on the MedDRA hierarchy. For example, when the user first navigates to the signal detection page **500**, the heatmap **530** may display the applicable SOC terms (e.g., highest level terms) of the MedDRA hierarchy (e.g., SOC terms which match cases of the received case data) within a tile of the heatmap. The tile including the SOC terms may be colored based on the seriousness of the (majority of) cases therein (e.g., red for serious results in death, blue for serious “other medically important conditions, white for non-serious, etc.) and sized based on the volume of the cases therein (e.g., proportionally to one another). For instance, a tile including a SOC (e.g., Gastrointestinal disorders) that is associated with two cases that both resulted in death may be colored in red and twice the size of a tile that is associated with a single case.

(116) Additionally, the user of the user computing device **108** may then be able to select the tile to see the next hierarchy of classes. For instance, the tile including the SOC Gastrointestinal disorders may be selected to display tiles of the next class (e.g., HLGT) that are applicable to the received cases (e.g., Diverticular disorders, Gastrointestinal infections, Gastrointestinal vascular conditions, etc.). This process may be repeated until reaching the lowest level of terms within the MedDRA hierarchy. In some embodiments, the user computing device **108** may automatically navigate the heatmap **530** to the MedDRA hierarchy level associated with a MedDRA term selected on the graph **522**.

(117) The list of detected or potential signals **540** is an interactive list of the determined potential signals (as discussed with regard to step **312**) through which the user of the user computing device **108** can interact to manage and process the potential signals. As shown, the list of potential signals **540** includes a search bar or field **544** and multiple potential signal representations **548**. The search bar or field **544** is a selectable text field through which the user of the user computing device **108** can filter the multiple potential signal representations **548** that are shown within the list of potential signals **540**. For example, the user may enter the term “Gastric Disorder” into the search field **544**, and the user computing device **108** may filter the displayed potential signal representations **548** down to a single potential signal representation **548** associated with the adverse event Gastric Disorder. In some embodiments, the user computing device **108** may automatically display the potential signal representations **548** associated with a MedDRA term selected on the graph **522**.

(118) Each potential signal representation **548** may represent a specific determined potential signal that is associated with the medical product and adverse event groups of the signal detection page **500**. As shown, each potential signal representation **548** includes a signal or adverse event field **552**, a tracking button **554**, a state field **556**, a source field **558**, and multiple statistical value fields (e.g., a case count field **558**, a PRR field **560**, an x.sup.2 field **562**, an EB05 field **564**, an EBGM field **568**, and an EB95 field **570**).

(119) The signal or adverse event field **552** may be a text field that indicates and displays the adverse event term (e.g., MedDRA PT) of the potential signal associated with the potential signal representation **548**. Similarly, the state field **556** and the data source field **556** may each be text fields that indicate and display the state (e.g., new, tracked, validated, verified, submitted, etc.) and the electronic data source, respectfully, of the potential signal associated with the potential signal representation **548**.

(120) The tracking button **554** is a selectable button that, when selected, may navigate the user computing device **108** to a signal page **600** through which the user of the user computing device **108** can assess and/or submit (e.g., within an electronic document) the potential signal associated with the potential signal representation **548**. In some embodiments, the tracking button **554**, when

selected, may cause the user computing device **108** to provide an indication of such to the provider computing system **104**. In response, the provider computing system **104** may generate one or more alerts or other notifications when changes occur to the signal (e.g., when new case data associated with the potential signal is received, when the statistical values associated with the signal change, etc.).

(121) The multiple statistical value fields may each be text fields that indicate and display the statistical values of the potential signal associated with the potential signal representation **548**. For instance, the potential signal representation may include a PRR field **560** that displays the PRR value associated with the potential signal of the potential signal representation **548**. In some embodiments, statistical values which are below the respective minimum statistical values may be indicated as such on the potential signal representation **548**. For instance, the statistical value fields which are below the minimum statistical values may be highlighted, emphasized, colored, or otherwise indicated (e.g., include an asterisk) as such.

(122) While not shown, the signal detection page **500** may further include a case listing or case listing section. The case listing may be an interactive list of the received cases associated with the medical product and/or the potential signals. The case listing may include a search bar or field, a data source field, an adverse event field, a seriousness field, a date/time field (e.g., date of receipt, date of new info), and/or a version field.

(123) Referring now to FIG. **6**, a signal page **600**, which can be displayed on a display of the I/O circuit **162** of one or more of the user computing devices **108**, is shown. In general, the signal page **600** provides one or more of the user computing devices **108** with an interface to view and manage a specific potential signal. In this regard, the signal page **600** may be associated with a specific medical product or signal product profile and adverse event. To be navigated to the signal page **600**, the user of the user computing device **108** may select the track signal button **554** of the signal detection page **500**. In response to doing so, the user computing device **108** may generate a request for case data based on and identifying the medical product and adverse event associated with the signal page **600**, as described with reference to the method **300**. In this regard and in response, the provider computing system **104** may provide the resulting case data and statistical values to the respective user computing device **108** to enable display of the signal page **600** on the display of the I/O circuit **162**. In some embodiments, the provider computing system **104** may generate a signal data object, in response to the user selecting the track signal button **554** of the signal detection page **500**, and the signal data object may include the resulting case data and statistical values. As shown, the signal page **600** includes a state section **604**, a signal details section **608**, a signal sources section **620**, a case listing section **640**, and a workbench button **650**.

(124) The state section **604** provides the user of the user computing device **108** with an indication of the state that the signal associated with the signal page **600** is currently in. In some embodiments, the user of the user computing device **108** may provide an indication of verification and validation via the state section **604**. In this regard, the signal of the signal page **600** may progress through the various states of the state section **604** until reaching a closed state (e.g., submitted, closed, etc.). It should be understood that states outside of those shown in the state section **604** are possible (e.g., submitted).

(125) The signal details section **608** provides the user of the user computing device **108** with an indication of high-level details regarding the signal associated with the signal page **600**. As shown, the signal details section **608** includes a signal name field **610**, a first adverse event term field **612**, a second adverse event term field **616**, and a signal product profile field **614**.

(126) The signal name field **610** may be a selectable and/or editable text field through which the user of the respective user computing device **108** can edit the name of the signal associated with the signal page **600** which may then be sent by the respective user computing device **108** to the provider computing system **104** for storage. Similarly, the signal product profile field **614** may be a selectable and/or editable text field or drop-down box with options through which the user of the

respective user computing device **108** can edit and set the signal product profile associated with the signal of the signal page **600** which may then be sent by the respective user computing device **108** to the provider computing system **104** for storage. In some embodiments, the signal product profile is the signal product profile or medical product associated with the signal detection page **500** that was used to navigate to the signal page **600**.

(127) The first adverse event term field **612** and the second adverse event term field **616** are each editable text fields or drop-down box with options through which the user of the respective user computing device **108** can edit and set a first adverse event and/or second adverse event associated with the signal of the signal page **600** which may then be sent by the respective user computing device **108** to the provider computing system **104** for storage. As described herein, signals may look at results between a medical product-adverse event pair or a medical product **1**-medical product **2**-adverse event pair. In this regard, the details section **608** may include the first adverse event term field **612** and the second adverse event term field **616**. In signals which are only looking at a medical product-adverse event pair, the second adverse event term field **616** may be the same as the first adverse event term field **612** (as shown in FIG. 6).

(128) The signal sources section **620** provides the user of the user computing device **108** with a breakdown, by electronic data source, of the received case data and statistical values associated of the signal associated with the signal page **600**. As shown, the signal sources section **620** includes a signal sources table with multiple signal source rows or portions **624**.

(129) The signal source rows or portions **624** each represent an electronic data source and include/display multiple statistical values associated with the case data of the respective data source. For example, the signal sources section **620** includes a first signal source portion **624** associated with the PV or trusted case repository **146** (as discussed with regard to the step **236** of the method **200**), a second signal source portion **624** associated with the health agency case repository **184** (e.g., FAERS) and the PV repository in conjunction (e.g., as discussed with regard to the step **240** of the method **200**), and a third signal source portion **624** associated with the health agency case repository **184** (e.g., FAERS) (as discussed with regard to the step **238** of the method **200**). Further, each signal source portion **624** includes a case count field, a PRR field, an x.sup.2 field, an EB05 field, an EBGM field, and an EB95 field.

(130) By breaking down the case data and statistical values by each electronic data source, the signal page **600** provides for additional insights that are not available in typical signal detection systems. For instance, by breaking the case counts down by source (e.g., 10 cases from FAERS, 10 cases from the trusted case repository **146**, 15 cases from FAERS and the trusted case repository **146** combined), the user computing device **108** (and the provider computing system **104**) are able to distinguish trends that are not available in typical signal detection systems. For instance, because cases that have been provided to FAERS should have been reported by the PV circuit **144**, the user computing device **108** (and the provider computing system **104**) can analyze the source specific case counts to determine cases that were not reported by the PV circuit **144** to FAERS. In some embodiments, the provider computing system **104** may automatically analyze which cases have not been received or processed by the PV circuit **144** and provide an indication to the user computing device **108** of the specific cases. In another example, the user computing device **108** (and the provider computing system **104**) can analyze which sources contain the most unique cases (e.g., cases with no matches in the other case repositories) and the least unique cases to better determine the priority of the electronic data sources based on the source specific case counts.

(131) While not shown in detail, the case listing section **640** may be an interactive list of the received cases associated with the signal of the signal page **600**. The case listing section **640** may include a search bar or field, a data source field, an adverse event field, a seriousness field, a date/time field (e.g., date of receipt, date of new info), and/or a version field.

(132) The tracking button **554** is a selectable button that, when selected, may navigate the user computing device **108** to a signal page **600** through which the user of the user computing device

108 can assess and/or submit (e.g., within an electronic document) the potential signal associated with the potential signal representation **548**. In some embodiments, the tracking button **554**, when selected, may cause the user computing device **108** to provide an indication of such to the provider computing system **104**. In response, the provider computing system **104** may generate one or more alerts or other notifications when changes occur to the signal (e.g., when new case data associated with the potential signal is received, when the statistical values associated with the signal change, etc.).

(133) The workbench button **650** is a selectable button that, when selected, may navigate the user computing device **108** to a workbench page **700** through which the user of the user computing device **108** can assess and more finely analyze the signal of the signal page **600**. In some embodiments, the user computing device **108** or the provider computing system **104** may use the received case data of the signal page **600** when generating and navigating to the workbench page **700**.

(134) Referring now to FIGS. 7A-7B, the workbench page **700**, which can be displayed on a display of the I/O circuit **162** of one or more of the user computing devices **108**, is shown. In general, the workbench page **700** provides one or more of the user computing devices **108** with an interface to view and analyze the signal of the signal page **600**. To be navigated to the workbench page **700**, the user of the user computing device **108** may select the workbench button **650** of the signal page **600**. In response to doing so, the user computing device **108** may generate a request for case data based on and identifying the medical product and adverse event associated with the signal of the signal page **600**, as described with reference to the method **300**. In this regard and in response, the provider computing system **104** may provide the resulting case data and statistical values to the respective user computing device **108** to enable display of the workbench page **700** on the display of the I/O circuit **162**. In some embodiments, the user computing device **108** or the provider computing system **104** may use the received case data of the signal page **600** to enable display of the workbench page **700**. As shown, the workbench page **700** includes a filters or options section **704**, a signal source summary section **760**, and a signal analytics section or dashboard **770**.

(135) The filters or options section **704** provides the user of the respective user computing device **108** with an interface to set, manage, and determine the filters, electronic data sources, and the timeframe which are applied to the case data received from the provider computing system **104** and received and displayed in the signal analytics section or dashboard **770**. As shown the options section **704** includes multiple electronic data source checkboxes (e.g., the all sources checkbox **708**, the FAERs checkbox **709**, and the trusted or PV case repository checkbox **710**), one or more timeframe or reporting period fields **712**, multiple seriousness filter fields or checkboxes (e.g., the all seriousness's checkbox **714**, the results in death seriousness checkbox **716**, the life threatening seriousness checkbox **718**, the caused/prolonged hospitalization seriousness checkbox **720**, the disabling/incapacitating seriousness checkbox **722**, the congenital anomaly/birth defect seriousness checkbox **724**, the other medically important condition seriousness checkbox **726**, and the non-serious checkbox **728**), multiple age group filter fields or checkboxes (e.g., the all age group checkbox **730**, the Fetus age group checkbox **732**, the neonate age group checkbox **734**, the infant age group checkbox **736**, the child age group checkbox **748**, the adolescent age group checkbox **740**, the adult age group checkbox **742**, the elderly age group checkbox **744**, and the undefined age group checkbox **746**), the multiple gender filter fields or checkboxes (e.g., the all genders checkbox **748**, the female gender checkbox **750**, the male gender checkbox **752**, and the undefined gender checkbox **754**), the reset button **756**, and the apply filters button **758**.

(136) The multiple electronic data source checkboxes or fields are each a selectable and editable checkboxes through which the user of the respective user computing device **108** can set the one or more electronic data sources to be included in the request for case data described herein. For instance, by selecting the FAERs checkbox **709**, the user computing device **108** may include or identify each within the request for case data (as described with regard to the step **228** of the

method **200**).

(137) Likewise, the multiple filter fields (e.g., the multiple age group filter checkboxes, the multiple seriousness filter checkboxes, the multiple gender filter checkboxes, etc.) are each selectable and editable checkboxes through which the user of the respective user computing device **108** can set the filters to be included in the request for case data described herein. For instance, by selecting the Fetus age group checkbox **732**, the neonate age group checkbox **734**, and the all seriousness's checkbox **714**, the user computing device **108** may include or identify the case data is to be for cases that are within the neonate age group, the fetus age group, and all seriousness types.

(138) The timeframe fields **712** are selectable and editable date/time fields through which the user of the of the respective user computing device **108** can set the timeframe (e.g., the active start date and the active end date) to be included in the request for case data described herein. For instance, via the timeframe fields **712**, the user of the user computing device **108** may set the active start date to be Jan. 1, 2004 and the active end date to be Oct. 5, 2022 (as shown in FIG. 7A).

(139) In some embodiments, the apply or apply filters button **756** is a selectable button that, when selected, may cause the user computing device **108** to filter the received case data and generate the analytics dashboard **770** using the filtered case data. In other embodiments, when the apply filters button **756** is selected, the user computing device **108** may generate a request for case data including or identifying the data source, the timeframe, and the filters of the fields of the filters section **704**. In response, the provider computing system **104** may provide updated case data, statistical values to the user computing device **108** to enable display on the workbench page **700** of the analytics dashboard **770**.

(140) The signal source summary section **760** provides the user with a summary of the signal associated with the workbench page **700** and analyzes the statistical values associated with the signal by electronic data source. As shown, the signal source summary section **760** includes a signal source graph or chart **762** and a signal sources table with multiple signal source rows or portions **764**. In this regard, the analytics dashboard **770** provides an interface or dashboard to apply and view the case data with the one or more filters and the signal source summary section **760** represents the case data prior to the filters being applied.

(141) The signal source rows or portions **764** each represent an electronic data source and include/display multiple statistical values associated with the case data of the respective data source. For example, the signal source summary section **760** includes a first signal source portion **764** associated with the PV or trusted case repository **146** (as discussed with regard to the step **236** of the method **200**), a second signal source portion **764** associated with the health agency case repository **184** (e.g., FAERS) and the PV repository in conjunction (e.g., as discussed with regard to the step **240** of the method **200**), and a third signal source portion **764** associated with the health agency case repository **184** (e.g., FAERS) (as discussed with regard to the step **238** of the method **200**). Further, each signal source portion **764** includes a case count field, a PRR field, an x.sup.2 field, an EB05 field, an EBGM field, and an EB95 field.

(142) Similarly, the signal source graph or chart **762** is a chart that displays the one or more statistical values of each signal source portion **764** in comparison. For instance, in FIG. 7A, the signal source chart **762** is a pie chart that displays the case count of the first signal source portion **764**, the second signal source portion **764**, and the third signal source portion **764** in comparison with one another. In some embodiments, the signal source graph or chart **762** may be a different type of chart or graph (e.g., bar chart, bubble chart, etc.).

(143) The analytics dashboard or section **770** provides the user with the filtered cases of the signal associated with the workbench page **700**. As shown, the analytics dashboard or section **770** includes a filtered signal sources table with one or more filtered signal source rows or portions **772**, a filtered seriousness chart or graph **780**, a filtered age group chart or graph **784**, and a filtered gender chart or graph **788**.

(144) The filtered signal source rows or portions **772** each represent an electronic data source and

include/display multiple statistical values associated with the filtered case data of the respective data source based on the filters of the filter section **704**. For example, the filtered signal sources table is shown to include a first filtered signal source portion **772** associated with the health agency case repository **184** (e.g., FAERS). Similar to the signal source portion **764**, each filtered signal source portion **772** includes a case count field, a PRR field, an x.sup.2 field, an EB05 field, an EBGM field, and an EB95 field.

(145) The filtered seriousness chart or graph **780** is a chart that displays the one or more statistical values of the filtered case data in comparison based on seriousness. For instance, in FIG. 7B, the filtered seriousness chart **780** is a pie chart that displays the case count (or a percentage of the whole thereof) of the filtered cases based on seriousness (e.g., 25% of the cases are serious: results in death, 25% of the cases are serious: life threatening, and so on). In some embodiments, the filtered seriousness chart or graph **780** may be a different type of chart or graph (e.g., bar chart, bubble chart, etc.).

(146) Likewise, the filtered age group chart or graph **784** is a chart that displays the one or more statistical values of the filtered case data in comparison based on age group. For instance, in FIG. 7B, the filtered age group chart **784** is a pie chart that displays the case count (or a percentage of the whole thereof) of the filtered cases based on age group (e.g., 25% of the cases are within the neonatal age group, 25% of the cases are in the adult age group, and so on). In some embodiments, the filtered age group chart **784** may be a different type of chart or graph (e.g., bar chart, bubble chart, etc.).

(147) The filtered gender chart or graph **788** is a chart that displays the one or more statistical values of the filtered case data in comparison based on gender. For instance, in FIG. 7B, the filtered gender chart **788** is a pie chart that displays the case count (or a percentage of the whole thereof) of the filtered cases based on gender (e.g., 50% of the cases are males and 50% of the cases are females). In some embodiments, the filtered gender chart **788** may be a different type of chart or graph (e.g., bar chart, bubble chart, etc.).

(148) Referring now to FIG. 8, the PV repository management page **800**, which can be displayed on a display of the I/O circuit **162** of one or more of the user computing devices **108**, is shown. In general, the PV repository management page **800** provides one or more of the user computing devices **108** with an interface to view, manage, and request the transfer of the trusted case data of the trusted case repository **146** to the central case data warehouse **130** (e.g., to the one or more PV repositories **132**). In this regard, the provider computing system **104** may provide the medical product data associated with the customer to the user computing device **108** to enable display PV repository management page **800**. As shown, the PV repository management page **800** includes a trusted case data management section **804** and a case sync log section **820**.

(149) The trusted case data management section **804** provides the user of the respective user computing device **108** with an interface to manage the transfer of the trusted case data from the trusted case repository **146** to the central case data warehouse **130**. As shown the trusted case data management section **804** includes a PV repository representation **808**.

(150) Each PV repository representation **808** may represent a specific central PV case repository **132** and/or the medical product or customer with which the PV repository is associated. As shown, each PV repository representation **808** includes a name field **810**, an options button **812**, an enable send to signal checkbox **816**, and an API key field **818**.

(151) The name field **810** is a selectable and/or editable text field through which the user of the respective user computing device **108** can edit the name of the PV repository associated with the PV repository representation **808** which may then be sent by the respective user computing device **108** to the provider computing system **104** for storage.

(152) The options button **812** is a selectable button that, when selected, drops down multiple options including a send to signal option **814** and a send unsuccessful copies to signal option **816**. The send to signal (also referred to as send to central case data warehouse) option **814** is a

selectable option that, when selected, provides a request to the provider computing system **104** to copy all of the cases associated with the medical product or customer associated with the PV repository and the related trusted case data within the trusted case repository **146** to the central case data warehouse **130**. In this regard, in response to receiving the request, the provider computing system **104** (e.g., the PV circuit **144**) may select each of the resulting cases and related trusted case data from the trusted case repository **146** and provide a copy of each to the central case data warehouse **130** for storage in one of the central PV case repositories **132**. In some embodiments, the send to signal option **814** provides a request to the provider computing system **104** to copy all of the cases within one or more certain states (e.g., closed, superseded, voided, nullified, etc.) and associated with the medical product or customer associated with the PV repository and the related trusted case data within the trusted case repository **146** to the central case data warehouse **130**.

(153) Similarly, the send unsuccessful copies to signal (also referred to as send to central case data warehouse) option **816** is a selectable option that, when selected, provides a request to the provider computing system **104** to copy all of the cases that previously failed to copy (as indicated in the case sync log section **820**). In this regard, in response to receiving the request, the provider computing system **104** (e.g., the PV circuit **144**) may select each of the resulting cases and related trusted case data from the trusted case repository **146** and provide a copy of each to the central case data warehouse **130** for storage in one of the central PV case repositories **132**.

(154) The enable send to signal checkbox **816** is a selectable checkbox that, when checked, provides an indication that cases of the trusted case repository **146** are to be automatically copied to the central case data warehouse **130**, when moved to a closed state. In this regard, when the user checks the enable send to signal checkbox **816**, the user computing device **108** may send an indication of such. Then, when a case of the PV circuit **144** moves to a closed state, the provider computing system **104** (e.g., the PV circuit **144**) may send the closed case and related trusted case data from the trusted case repository **146** and provide a copy to the central case data warehouse **130** for storage in one of the central PV case repositories **132**.

(155) The API key **818** is a text field that indicates or includes an application programming interface (API) key associated with the central PV case repository **132** of the central case data warehouse **130** to which the trusted case data is provided.

(156) The case sync log section **820** provides the user of the respective user computing device **108** with an interface to manage and view the status of cases that were transferred from the trusted case repository **146** to the central case data warehouse **130**. As shown the case sync log section **820** includes multiple case transmission representations **824**.

(157) Each case transmission representation **824** may represent a specific attempt at copying a case from the trusted case repository **146** to the central case data warehouse **130**. As shown, each case transmission representation **824** includes a name field **828**, an associated customer field **830**, a sync status field **832**, a log message **834**, an associated case field **836**, a sync date/time field **838**, and a copy ID field **840**. In some embodiments, the transmission representation **824** may further include a medical product field (not shown).

(158) The name field **828** is a text field that includes the name of the case transmission associated with the case transmission representation **824**. Similarly, the associated customer field **830** is a text field that includes the customer with which the case is associated.

(159) The sync status field **832** is a text field that includes the status of the case transmission associated with the case transmission representation **824**. For example, the sync status field **832** may include the status “Success”, “Failure”, “Pending”, “Paused”, and the like. In this regard, the send unsuccessful copies to signal option **816** may apply to case transmissions with the status “Failure”.

(160) The log message **834** is a text field that includes a system (e.g., the provider computing system **104**) generated message associated with the sync status of the sync status field **832**. For instance, when a case transmission was successful the log message **834** may include the system

generated message “Case successfully copied”. In other example, the log message **834** may include a message explaining a case transmission with the status “Failure” (e.g., “Case could not copy due to case missing a narrative” “Case could not copy due to the case being reopened”, etc.).

(161) The associated case field **836** is a selectable text field that includes the case associated with the case transmission representation **824**. In some embodiments, the associated case field **836** is a selectable link that, when selected, navigates the user of the user computing device **108** to a case page (not shown) associated with the specific case.

(162) The sync date/time field **838** is a date/time field that includes the date/time the case transmission attempted to process, failed to process, successfully processed, and the like. Similarly, the copy ID field **840** is a text field that includes a unique ID associated with the transmission of the case such that the transmission can be identified.

(163) Referring now to FIGS. **9A-9C**, multiple example embodiments of the central case data warehouse **130** are shown. FIG. **9A** shows a central case data warehouse **130A** including multiple health agency repositories (also referred to as central health agency case repositories) **131**, multiple PV repositories (also referred to as central PV case repositories) **132**, and multiple additional case repositories (also referred to as central additional case repositories) **133**. As described herein, the central case data warehouse **130A** may include a central health agency case repository **131** for each of the health agency computing systems **112** from which health agency case data is received. For instance, central case data warehouse **130A** may include a first central health agency case repository **131** in which combined health agency case data associated with and received from the FDA (e.g., FAERS) is stored and a second central health agency case repository **131** in which combined health agency case data associated with and received from Health Canada is stored. In this regard, the central case data warehouse **130A** (or the health agency repository **131**), when requested or queried, may output the combined health agency case data of the respective central health agency case repository **131** for which combined health agency case data is sought or queried (e.g., in response to the request for case data identifying FAERS as an electronic data source, outputting combined health agency case data from the central health agency case repository **131** associated with FAERS).

(164) Additionally, the central case data warehouse **130A** may include a separate central PV case repository **132** for each medical product or signal product profile (also referred to as a medical product profile). For instance, the central case warehouse **130A** may include a first central PV case repository **132** in which trusted case data received from the trusted case repository **146** and associated with Drug X is stored and a second central PV case repository **132** in which trusted case data received from the trusted case repository **146** and associated with Drug Y is stored. In other embodiments, the central case warehouse **130** may include a separate central PV case repository **132** for each separate customer. For instance, the central case warehouse **130A** may include a first central PV case repository **132** associated with customer or Pharma X and a second central PV case repository **132** associated with customer or Pharma Y, thereby preventing separate customer data from becoming mistakenly intermingled. In this regard, the central case data warehouse **130A** (or the PV repository **132**), when requested or queried, may output the trusted case data of the respective central PV case repository **132** for which trusted case data is sought or queried (e.g., in response to the request for case data identifying drug X as a medical product, outputting trusted case data from the central PV case repository **132** associated with drug X).

(165) Moreover, the central case data warehouse **130A** may include a separate central additional case repository **133** for each external or additional source of case data. For instance, the central case warehouse **130A** may include a first central additional case repository **133** in which social media case data received from a social media case mining repository is stored and a second central additional case repository **133** in which medical literature case data received from a medical literature case repository is stored. In another example, the central case warehouse **130A** may include a first central additional case repository **133** in which social media case data received from

a first social media case mining repository is stored and a second central additional case repository **133** in which social media case data received from a second social media case mining repository is stored. In this regard, the central case data warehouse **130A** (or the additional case repository **133**), when requested or queried, may output the additional case data of the respective central additional case repository **133** for which additional case data is sought or queried (e.g., in response to the request for case data identifying the social media mining repository as an electronic data source, outputting additional case data from the central additional case repository **133** associated with the social media mining repository).

(166) FIG. **9B** shows a central case data warehouse **130B** including a single central health agency case repository **131**, a single central PV case repository **132**, and a central additional case repository **133**. As described herein, the central case data warehouse **130B** may include a single central health agency case repository **131** in which all of the health agency case data (after being cleaned and combined) received from the health agency computing systems **112** is stored. In this regard, the combined health agency case data stored therein may still be distinguishable or separable by health agency from which the combined health agency case data was received. For example, a first portion of the combined health agency case data stored within the single central health agency case repository **131** may be distinguishable as associated with or received from the FDA (e.g., FAERS) and a second portion of the combined health agency case data stored within the single central health agency case repository **131** may be distinguishable as associated with or received from the WHO (e.g., Vigibase). In this regard, the central case data warehouse **130A**, when requested or queried, may output the portion of the combined health agency case data of the single central health agency case repository **131** for which combined health agency case data is sought or queried (e.g., in response to the request for case data identifying FAERS as an electronic data source, outputting the portion of the combined health agency case data from the central health agency case repository **131** associated with FAERS).

(167) Additionally, the central case data warehouse **130B** may include a single central PV case repository **132** in which all of the trusted case data received from the trusted case repository **146** is stored. In this regard, the trusted case data stored therein may still be distinguishable or separable by medical product and/or customer for which the trusted case data is associated. For example, a first portion of the trusted case data stored within the single central PV case repository **132** may be distinguishable as associated with a first customer (e.g., Biopharma **1**) and a second portion of the trusted case data stored within the single central PV case repository **132** may be distinguishable as associated with a second customer (e.g., Biopharma **2**). In this regard, the central case data warehouse **130A** (or the PV repository **132**), when requested or queried, may output the portion of the trusted case data of the single central PV case repository **132** for which trusted case data is sought or queried (e.g., in response to the request for case data identifying drug X as a medical product, outputting the portion of the trusted case data from the central PV case repository **132** associated with drug X).

(168) Additionally, the central case data warehouse **130B** may include a single central additional case repository **133** in which all of the additional case data received by the provider computing system **104** is stored. In this regard, the additional case data stored therein may still be distinguishable or separable by source from which the additional case data was received. For example, a first portion of the additional case data stored within the single additional case repository **133** may be distinguishable as received from a first social media case repository and a second portion of the additional case data stored within the single additional case repository **133** may be distinguishable as received from a medical literature case repository. In this regard, the central case data warehouse **130A** (or the additional case repository **133**), when requested or queried, may output the portion of the additional case data of the single central additional case repository **133** for which additional case data is sought or queried (e.g., in response to the request for case data identifying the social media mining repository as an electronic data source, outputting

the portion of the additional case data from the central additional case repository **133** associated with the social media mining repository).

(169) FIG. **9C** shows the central case data warehouse **130C** including a single central case repository **195**. The single central case repository **195** may be a repository within which all of the received case data (e.g., the trusted case data from the trusted case repository **146**, the combined health agency case data received from the health agency computing systems **112**, and the additional case data received from one or more additional repositories) is stored. In this regard, the central case warehouse **130C** may combine the different types of case data and store them together within the single central case repository **195** while still maintaining or distinguishing between the types of the case data such that the source of the case data is still identifiable (e.g., each source of case data is included in a separate row or column of a table), and therefore separable.

(170) It should be understood that any of the example embodiments (**130A-130C**) and the components thereof may be combined and that such combinations are within the scope of this disclosure. For example, the central case data warehouse **130** may include a single central health agency case repository **131** as discussed with regard to FIG. **9A** and multiple central PV case repositories **132** as discussed with regard to FIG. **9B**, and vice versa. In another example, the central case data warehouse may include a single central health agency case repository **131**, multiple central PV case repositories **132**, and a single additional case repository **133**.

(171) The one or more health agency repositories (also referred to as the central health agency case repository) **131** are each a repository (e.g., a database, cloud storage, etc.) that is structured or configured to receive, store, and manage the cleaned and combined health agency case data received from the health agency computing system **112**. For example, the provider computing system **104** may receive health agency case data, clean the health agency case data, combine the health agency case data with medical product data and/or one or more adverse event identifiers, and store the combined health agency case data within the one or more central health agency case repositories **131** of the central case warehouse **130**. Each central health agency case repository **131** may be structured according to various database types, such as relational, hierarchical, network, flat, point-in time, and/or object relational. In some embodiments, each central health agency case repository **131** includes a plurality of nonvolatile/non-transitory storage media such as solid-state storage media, hard disk storage media, virtual storage media, cloud-based storage drives, storage servers, and/or the like.

(172) Similarly, the one or more PV repositories (also referred to as central PV case repositories) **132** are each a repository (e.g., a database, cloud storage, etc.) that is structured or configured to receive, store, and manage the trusted case data received from the trusted case repository **146** of the PV circuit **144**. Each central PV case repository **132** may be structured according to various database types, such as relational, hierarchical, network, flat, point-in time, and/or object relational. In some embodiments, each central PV case repository **132** includes a plurality of nonvolatile/non-transitory storage media such as solid-state storage media, hard disk storage media, virtual storage media, cloud-based storage drives, storage servers, and/or the like.

(173) Likewise, the central case repository **195** is a repository (e.g., a database, cloud storage, etc.) that is structured or configured to receive, store, and manage central case data generated by the provider computing system **104** (e.g., the processing circuit **122**, the central case data warehouse **130**, etc.). The central case repository **195** may be structured according to various database types, such as relational, hierarchical, network, flat, point-in time, and/or object relational. In some embodiments, the central case repository **195** includes a plurality of nonvolatile/non-transitory storage media such as solid-state storage media, hard disk storage media, virtual storage media, cloud-based storage drives, storage servers, and/or the like.

(174) The embodiments described herein have been described with reference to the drawings. The drawings illustrate certain details of specific embodiments that implement the systems, methods, and programs described herein. However, describing the embodiments with drawings should not be

construed as imposing on the disclosure any limitations that may be present in the drawings.

(175) It should be understood that no claim element herein is to be construed under the provision of 35 U.S.C § 112 (f), unless the element is expressly recited using the phrase “means for.”

(176) As used herein, the term “circuit” may include hardware structured to execute the functions described herein. In some embodiments, each respective “circuit” may include machine-readable media for configuring the hardware to execute the functions described herein. The circuit may be embodied as one or more circuitry components including, but not limited to, processing circuitry, network interfaces, peripheral devices, input devices, output devices, sensors, etc. In some embodiments, a circuit may take the form of one or more analog circuits, electronic circuits (e.g., integrated circuits (IC), discrete circuits, system on a chip (SOC) circuits), telecommunication circuits, hybrid circuits, and any other type of “circuit.” In this regard, the “circuit” may include any type of component for accomplishing or facilitating achievement of the operations described herein. For example, a circuit as described herein may include one or more transistors, logic gates (e.g., NAND, AND, NOR, OR, XOR, NOT, XNOR), resistors, multiplexors, registers, capacitors, inductors, diodes, wiring, and so on.

(177) The “circuit” may also include one or more processors communicably coupled to one or more memory or memory devices. In this regard, the one or more processors may execute instructions stored in the memory or may execute instructions otherwise accessible to the one or more processors. In some embodiments, the one or more processors may be embodied in various ways. The one or more processors may be constructed in a manner sufficient to perform at least the operations described herein. In some embodiments, the one or more processors may be shared by multiple circuits (e.g., circuit A and circuit B may comprise or otherwise share the same processor which, in some example embodiments, may execute instructions stored, or otherwise accessed, via different areas of memory). Alternatively or additionally, the one or more processors may be structured to perform or otherwise execute certain operations independent of one or more co-processors. In other embodiments, two or more processors may be coupled via a bus to enable independent, parallel, pipelined, or multi-threaded instruction execution. Each processor may be implemented as one or more general purpose processors, application specific integrated circuits (ASICs), field programmable gate arrays (FPGAs), digital signal processors (DSPs), or other suitable electronic data processing components structured to execute instructions provided by the memory. The one or more processors may take the form of a single core processor, a multi-core processor (e.g., dual core, quad core, etc.), microprocessor, etc. In some embodiments, the one or more processors may be external to the apparatus. For example, the one or more processors may be a remote processor (e.g., a cloud-based processor). Alternatively or additionally, the one or more processors may be internal and/or local to the apparatus. In this regard, a circuit or components thereof may be disposed locally (e.g., as part of a local server, a local computing system) or remotely (e.g., as part of a remote server such as a cloud-based server). To that end, a “circuit” as described herein may include components that are distributed across one or more locations. Further, the circuits of the processing circuit described herein may be distributed across one or more locations (e.g., each as part of one or more remote servers).

(178) An example system for implementing the overall system or portions of the embodiments might include a general purpose computing device in the form of computers, including a processing unit, a system memory, and a system bus that couples various system components including the system memory to the processing unit. Each memory device may include non-transient volatile storage media, non-volatile storage media, non-transitory storage media (e.g., one or more volatile and/or non-volatile memories), etc. In some embodiments, the non-volatile storage media may take the form of ROM, flash memory (e.g., flash memory such as NAND, 3D NAND, NOR, 3D NOR), EEPROM, MRAM, magnetic storage, hard disks, optical disks, etc. Combinations of the above are also included within the scope of machine-readable media. In this regard, machine-executable instructions comprise, for example, instructions and data which cause a general purpose computer,

special purpose computer, or special purpose processing machine to perform a certain function or group of functions. Each respective memory device may be operable to maintain or otherwise store data relating to the operations performed by one or more associated circuits, including processor instructions and related data (e.g., database components, object code components, script components), in accordance with the example embodiments described herein.

(179) It should also be noted that the term “input devices,” as described herein, may include any type of input device including, but not limited to, a keyboard, a keypad, a mouse, a joystick, or other input devices performing a similar function. Comparatively, the term “output device,” as described herein, may include any type of output device including, but not limited to, a computer monitor, printer, facsimile machine, or other output devices performing a similar function.

(180) It should be noted that the term “field,” as described herein may include any form of an input field through which the user interfaces shown and described may receive input from a user of a computing device. For instance, the term “field” may include a text field, a drop-down box and selectable options, a lookup box, a search bar, an icon, one or more checkboxes, one or more radio buttons, a button, a toggle, a date field, a slider, and the like. Further, each “field” may include and/or receive data that is associated with a data object as described herein.

(181) It should be noted that although the diagrams herein may show a specific order and composition of method steps, it is understood that the order of these steps may differ from what is depicted. For example, two or more steps may be performed concurrently or with partial concurrence. Also, some method steps that are performed as discrete steps may be combined, steps being performed as a combined step may be separated into discrete steps, the sequence of certain processes may be reversed or otherwise varied. The order or sequence of any element or apparatus may be varied or substituted according to alternative embodiments. Accordingly, all such modifications are intended to be included within the scope of the present disclosure as defined in the appended claims. Such variations will depend on the machine-readable media and hardware systems chosen and on designer choice. It is understood that all such variations are within the scope of the disclosure. Likewise, software and web implementations of the present disclosure could be accomplished with standard programming techniques with rule-based logic and other logic to accomplish the various database searching steps, correlation steps, comparison steps, and decision steps.

(182) The foregoing description of embodiments has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure to the precise form disclosed, and modifications and variations are possible in light of the above teachings or may be acquired from this disclosure. The embodiments were chosen and described in order to explain the principles of the disclosure and its practical application to enable one skilled in the art to utilize the various embodiments and with various modifications as are suited to the particular use contemplated. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions and embodiment of the embodiments without departing from the scope of the present disclosure as expressed in the appended claim.

Claims

1. A method for collecting case data in a central case data storage system, wherein the central case data storage system comprises a provider computing system including a trusted case repository and a central case data warehouse, the method comprising: receiving, by a network interface of the provider computing system, health agency case data associated with one or more health agency cases from a health agency case repository, wherein the health agency case data includes a first date associated with a first version of a health agency case of the one or more health agency cases, and wherein the health agency case data includes a second date associated with a second version of the health agency case; cleaning, by a processing circuit of the provider computing system, the health

agency case data, wherein cleaning the health agency case data includes: generating, by the provider computing system, a first version start date and a first version end date associated with the first version of the health agency case based on the health agency case data, generating, by the provider computing system, a second version start date associated with the second version of the health agency case based on the health agency case data, and modifying, by the provider computing system, the health agency case data to include the first version start date, the first version end date, and the second version start date; receiving, by the network interface, medical product data associated with one or more medical products from a user computing device; receiving, by the network interface, a plurality of adverse event identifiers from a medical dictionary repository; generating, by the processing circuit, combined health agency data by combining the cleaned health agency case data with the medical product data and an adverse event identifier of the plurality of adverse event identifiers, wherein the first version of the health agency case and the second version of the health agency case are maintained in the combined health agency case data; selecting, by the processing circuit, trusted case data associated with one or more Pharmacovigilance (PV) cases from the trusted case repository based on the trusted case data including a customer field identifying a first customer; determining, by the processing circuit, the combined health agency case data and the trusted case data at least partially match based on at least one of the one or more health agency cases matching at least one of the one or more PV cases; generating, by the processing circuit, one or more digital connections between the combined health agency case data and the trusted case data, wherein the one or more digital connections include a digital connection for each matching PV case and health agency case; storing, by the processing circuit, the combined health agency case data, the trusted case data, and the one or more digital connections in the central case data warehouse; receiving, by the network interface, a request identifying the health agency case repository and a timeframe from the user computing device, wherein the timeframe encompasses the first version start date, the first version end date, and the second version start date; selecting, by the processing circuit, case data including at least a portion of the combined health agency case data from the central case data warehouse based on the request, wherein the portion of the combined health agency case data includes the second version of the health agency case, and wherein the portion of the combined health agency case data does not include the first version of the health agency case; and transmitting, by the network interface, the selected case data to an address associated with the user computing device.

2. The method of claim 1, wherein the one or more digital connections are each a link, and wherein the method further comprises: adding, by the processing circuit, each link to the trusted case data selected from the trusted case repository.

3. The method of claim 2, wherein the central case data warehouse comprises a central health agency case repository and one or more central PV repositories, wherein the trusted case data comprising the one or more links is stored in the one or more central PV repositories of the central case data warehouse, and wherein the combined health agency case data is stored in the health agency repository of the central case data warehouse.

4. The method of claim 1, wherein the request is a first request, wherein the case data is first case data, and further comprising: receiving, by the network interface, a second request identifying the trusted case repository as an electronic data source; selecting, by the processing circuit, second case data including at least a portion of the trusted case data from the central case data warehouse based on the request; and outputting, by the network interface, the selected second case data.

5. The method of claim 1 wherein the request is a first request, wherein the case data is first case data, and further comprising, receiving, by the network interface, a second request identifying the health agency case repository as an electronic data source; selecting, by the processing circuit, second case data including at least a portion of the combined health agency case data from the central case data warehouse based on the request; and outputting, by the network interface, the selected second case data.

6. The method of claim 1, wherein the combined health agency case data includes a first case identifier, wherein the trusted case data selected from the trusted case repository includes a second case identifier, and wherein the method further comprises: determining, by the processing circuit, at least one of the one or more health agency cases match at least one of the one or more PV cases based on the first case identifier matching the second case identifier.

7. The method of claim 6, wherein the request is a first request, wherein the case data is first case data, wherein the combined health agency case data includes a first portion that is associated with the first case identifier, wherein the trusted case data selected from the trusted case repository includes a second portion that is associated with the second case identifier, wherein the one or more digital connections include a first digital connection between the first portion of the combined health agency case data and the second portion of the trusted case data, and wherein the method further comprises: receiving, by the network interface, a second request identifying the health agency case repository and the trusted case repository as electronic data sources; selecting, by the processing circuit, second case data including the first portion of the combined health agency case data and the second portion of the trusted case data from the central case data warehouse based on the request; and removing, by the processing circuit, the first portion of the combined health agency case data from the selected second case data based on the first digital connection; and outputting, by the network interface, the selected second case data.

8. The method of claim 1, wherein combining the cleaned health agency case data with the medical product data and the adverse event identifier of the plurality of adverse event identifiers comprises: determining, by the processing circuit, at least a portion of the cleaned health agency case data matches at least a portion of the medical product data based on a medical product identifier of the cleaned health agency case data being the same as a medical product identifier of the medical product data; combining, by the processing circuit, the matching portion of the cleaned health agency case data and the matching portion of the medical product data; determining, by the processing circuit, at least a portion of the combined health agency case data matches the adverse event identifier based on an adverse event identifier of the combined health agency case data being the same as the adverse event identifier of the plurality of adverse event identifiers; and combining, the matching portion of the combined health agency case data with the adverse event identifier.

9. The method of claim 1, further comprising: receiving, by the network interface, a source file including adverse event data associated with one or more adverse event and a medical product, wherein the adverse event data includes seriousness data indicating the adverse event resulted in death; generating, by the processing circuit, a case including at least a portion of the trusted case data, wherein the portion of the trusted case data includes the adverse event data; receiving, by the network interface, an indication of verification of the case from a user computing device; and storing, by the processing circuit, the portion of the trusted case data within the trusted case repository.

10. A method for collecting case data in a central case data storage system, wherein the central case data storage system comprises a provider computing system including a central case data warehouse, the method comprising: receiving, by a network interface of the provider computing system, health agency case data associated with one or more health agency cases from a health agency case repository, wherein the health agency case data includes a first date associated with a first version of a health agency case of the one or more health agency cases, and wherein the health agency case data includes a second date associated with a second version of the health agency case; cleaning, by a processing circuit of the provider computing system, the health agency case data, wherein cleaning the health agency case data includes: generating, by the provider computing system, a first version start date and a first version end date associated with the first version of the health agency case based on the health agency case data, generating, by the provider computing system, a second version start date associated with the second version of the health agency case based on the health agency case data, and modifying, by the provider computing system, the health

agency case data to include the first version start date, the first version end date, and the second version start date; receiving, by the network interface, medical product data associated with one or more medical products from a user computing device; receiving, by the network interface, a plurality of adverse event identifiers from a medical dictionary repository; generating, by the processing circuit, combined health agency data by combining the cleaned health agency case data with the medical product data and an adverse event identifier of the plurality of adverse event identifiers, wherein the first version of the health agency case and the second version of the health agency case are maintained in the combined health agency case data; selecting, by the processing circuit, trusted case data associated with one or more Pharmacovigilance (PV) cases from the central case data warehouse based on the trusted case data including a customer field identifying a first customer; determining, by the processing circuit, the combined health agency case data and the trusted case data at least partially match based on at least one of the one or more health agency cases matching at least one of the one or more PV cases; generating, by the processing circuit, one or more digital connections between the combined health agency case data and the trusted case data, wherein the digital connections include a digital connection for each matching PV case and health agency case; storing, by the processing circuit, the combined health agency case data, the trusted case data, and the one or more digital connections in the central case data warehouse; receiving, by the network interface, a request identifying the health agency case repository and a timeframe from the user computing device, wherein the timeframe encompasses the first version start date, the first version end date, and the second version start date; selecting, by the processing circuit, case data including at least a portion of the combined health agency case data from the central case data warehouse based on the request, wherein the portion of the combined health agency case data includes the second version of the health agency case, and wherein the portion of the combined health agency case data does not include the first version of the health agency case; and outputting transmitting, by the network interface, the selected case data to an address associated with the user computing device.

11. The method of claim 10, wherein the request is a first request, wherein the case data is first case data, and further comprising: receiving, by the network interface, a second request identifying a trusted case repository as an electronic data source; selecting, by the processing circuit, second case data including at least a portion of the trusted case data from the central case data warehouse based on the request; and outputting, by the network interface, the selected second case data.

12. The method of claim 10, wherein the request is a first request, wherein the case data is first case data, and further comprising: receiving, by the network interface, a second request identifying the health agency case repository as an electronic data source; selecting, by the processing circuit, second case data including at least a portion of the combined health agency case data from the central case data warehouse based on the request; and outputting, by the network interface, the selected second case data.

13. The method of claim 10, wherein the adverse event identifier is a first adverse event identifier, and further comprising: receiving, by the network interface, social media case data from a social media case mining repository; cleaning, by the processing circuit, the social media case data; combining, by the processing circuit, the cleaned social media case data with the medical product data and a second adverse event identifier of the plurality of adverse event identifiers; and storing, by the processing circuit, the combined social media case data in the central case data warehouse.

14. The method of claim 10, wherein the one or more digital connections are each a link, and wherein the method further comprises: adding, by the processing circuit, each link to the trusted case data selected from the central case data warehouse.

15. The method of claim 14, wherein the central case data warehouse comprises a central health agency case repository and one or more central PV repositories, wherein the trusted case data comprising the one or more links is stored in the one or more central PV repositories of the central case data warehouse, and wherein the combined health agency case data is stored in the health

agency repository of the central case data warehouse.

16. The method of claim 10, wherein combining the cleaned health agency case data with the medical product data and the adverse event identifier of the plurality of adverse event identifiers comprises: determining, by the processing circuit, at least a portion of the cleaned health agency case data matches at least a portion of the medical product data based on a medical product identifier of the cleaned health agency case data being the same as a medical product identifier of the medical product data; combining, by the processing circuit, the matching portion of the cleaned health agency case data and the matching portion of the medical product data; determining, by the processing circuit, at least a portion of the combined health agency case data matches the adverse event identifier based on an adverse event identifier of the combined health agency case data being the same as the adverse event identifier of the plurality of adverse event identifiers; and combining, the matching portion of the combined health agency case data with the adverse event identifier.

17. The method of claim 1, wherein the first version start date is the first date of the health agency case data, wherein the first version end date is the second date of the health agency case data, wherein the second version end date is the second date of the health agency case data.

18. The method of claim 10, wherein the first version start date is the first date of the health agency case data, wherein the first version end date is the second date of the health agency case data, wherein the second version end date is the second date of the health agency case data.

19. The method of claim 1, wherein the request includes the address, and wherein the address is at least one of: an internet protocol (IP) address, a file transfer protocol (FTP) address, or an email address, and wherein the case data is transmitted to the address.

20. The method of claim 10, wherein the request includes the address, and wherein the address is at least one of: an internet protocol (IP) address, a file transfer protocol (FTP) address, or an email address, and wherein the case data is transmitted to the address.
