

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401724
Kind Code	B1
Date of Patent	August 26, 2025
Inventor(s)	Delaney; Christopher Edward et al.

Systems and methods for establishing discrete connection to a network endpoint

Abstract

Systems and methods are provided for connecting a client to a desired network endpoint. Example systems and methods include receiving, at a server, a request identifying a network endpoint to be accessed, configuring a proxy instance, the proxy instance being configured to receive a connection from a client to forward that client connection to the identified network endpoint, and deleting the proxy instance upon occurrence of a session end criteria. In some embodiments, the request identifying a network endpoint to the server is received from the network endpoint. In some embodiments, the request identifying a network endpoint to the server is received from the client. In some embodiments, a platform as a service is used to configure the proxy instance. In some embodiments, the request identifying a network endpoint is made to the platform as a service rather than to the server, which is not included in the embodiment.

Inventors: Delaney; Christopher Edward (Front Royal, VA), Jurado; Chava Louis (Leesburg, VA), Jacobs; Carl Bailey (Fredericksburg, VA)

Applicant: Cyber IP Holdings, LLC (Herndon, VA)

Family ID: 1000007352208

Assignee: Cyber IP Holdings, LLC (Herndon, VA)

Appl. No.: 18/456617

Filed: August 28, 2023

Related U.S. Application Data

continuation parent-doc US 17744819 20220516 US 11778039 child-doc US 18456617
us-provisional-application US 63190262 20210519

Publication Classification

Int. Cl.: H04L67/141 (20220101); H04L67/2895 (20220101); H04L67/60 (20220101)

U.S. Cl.:

CPC H04L67/141 (20130101); H04L67/2895 (20130101); H04L67/60 (20220501);

Field of Classification Search

CPC: H04L (67/141); H04L (67/2895)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10601948	12/2019	Juravicius	N/A	H04L 67/02
2010/0250648	12/2009	Cao	709/219	H04L 67/1001
2022/0279046	12/2021	Perng	N/A	H04L 67/2866

Primary Examiner: Ndiaye; Cheikh T

Attorney, Agent or Firm: Jones Day

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/744,819, filed May 16, 2022, which claims priority to U.S. Provisional Application No. 63/190,262, filed May 19, 2021, and makes reference to U.S. Pat. Nos. 10,080,249, 10,616,938, 9,935,850, 10,476,761, and 10,897,409, by Delaney, et. al., all of which are incorporated herein by reference in their entirety.

BACKGROUND

(1) Networks facilitate communication between entities. Confidentiality, security, and privacy interests may make it desirable to obfuscate characteristics of those communications. For example, content of communications across a public network may be protected via encryption of those communications. It may also be desirable to shield characteristics of the communicating entities, including aspects such as the identity of the communicating entities and their locations (e.g., physical or network locations).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Aspects of the present disclosure are best understood from the following detailed description when read with the accompanying figures. It should be noted that, in accordance with the standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.

(2) FIG. 1 is a block diagram depicting an example topology configuration of a computer-implemented environment to establish a network connection between a client and a network endpoint without revealing the client's network location to the network endpoint.

- (3) FIG. 2 is a block diagram depicting an example set of operations to establish a network connection between a client and a network endpoint without revealing the client's network location to the network endpoint.
- (4) FIG. 3 is a block diagram depicting an example topology configuration of a computer-implemented environment to establish a network connection between a client and a network endpoint without revealing the network endpoint's network location to the client.
- (5) FIG. 4 is a block diagram depicting an example set of operations to establish a network connection between a client and a network endpoint without revealing the network endpoint's network location to the client.
- (6) FIG. 5 depicts an example topology configuration of a serverless computer-implemented environment to establish a network connection between a client and a network endpoint without revealing the client's network location to the network endpoint.
- (7) FIG. 6 is a block diagram depicting an example serverless set of operations to establish a network connection between a client and a network endpoint without revealing the client's network location to the network endpoint.
- (8) FIG. 7 is a flow diagram depicting a computer-implemented method configuration to establish a network connection between two parties comprising a client and a network endpoint without revealing one party's network location to the other party.
- (9) Corresponding numerals and symbols in the different figures generally refer to corresponding parts unless otherwise indicated. The figures are drawn to clearly illustrate the relevant aspects of the embodiments and are not necessarily drawn to scale.

DETAILED DESCRIPTION

- (10) The following disclosure provides many different embodiments, or examples, for implementing different features of the provided subject matter. Specific examples of components and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in some various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between some various embodiments and/or configurations discussed.
- (11) Some embodiments of the disclosure are described. Additional operations can be provided before, during, and/or after the stages described in these embodiments. Some of the stages that are described can be replaced or eliminated for different embodiments. Additional features can be added to the circuit. Some of the features described below can be replaced or eliminated for different embodiments. Although some embodiments are discussed with operations performed in a particular order, these operations may be performed in another logical order.
- (12) Systems and methods as described herein provide, in examples, mechanisms that enable network connections to be established among parties (e.g., two parties comprising a client and a network endpoint) while protecting confidentiality of aspects of those communications and parties, such as without one or both of the parties being aware of the actual network location of the other party. For two parties to establish a connection and communicate with one another over a network, both parties on each end of the connection typically have a network path to the other endpoint. This arrangement may present a privacy vulnerability because the connection could reveal the network location of each party to the other or to third parties observing the communication channel. When a client application connects to a network endpoint on a server over the internet, the client's network location on the internet may be visible to the network endpoint. From the network endpoint's perspective, if the network endpoint wants clients to be able to connect to it on its server over the

internet, the clients may know the network endpoint's network location on the internet to establish the connection. In both of these circumstances, there should be trust between the parties that the network location information will not be used for malicious purposes. Such trustworthiness is not an assured thing, especially as interest in internet security and privacy grows with increasing data breaches and data collection.

(13) Systems and methods as described herein, sometimes referred to as Displacer systems and methods, enable a network connection to be established between two parties, such as a client and an endpoint, without disclosing one or both parties' network location to the other party. In some embodiments, a system establishes a network connection between a client or user and a network endpoint on a server without the network endpoint being aware of a location of the client or user. In other embodiments, a network connection may be established between a client or user and a network endpoint on a server without the client or user knowing the actual network location of the network endpoint or its server. Additionally, any interactions between the client and network endpoint are shielded from third-party observers.

(14) In some embodiments, the proxy instance is utilized to facilitate the system and methods as described herein. In embodiments, such proxy instances may be implemented as a Portal Proxy instance, as described in U.S. Pat. Nos. 10,080,249 and 10,616,938, which are incorporated herein by reference in their entirety. In embodiments wherein the proxy instance is a Portal Proxy instance, a first reverse proxy connection is configured to receive a connection from the client to set up a discreet connection, where an invitation indicating a mechanism for accessing the first reverse proxy connection is provided to the client. Access credentials are transmitted to the client over the first reverse proxy connection, the access credentials including an address for accessing a second reverse proxy connection, the first reverse proxy connection being deleted following delivery of the access credentials. The second reverse proxy connection facilitates the discreet connection between the client and the network endpoint without any detectable direct contact with the service.

(15) In some embodiments, public IP addresses of Inbound Proxy nodes of a network (e.g. a Fognigma Network) are used instead of a real IP address of the network endpoint as a designated endpoint of the proxy instances, as described in U.S. Pat. Nos. 9,935,850, 10,476,761, and 10,897,409, which are incorporated herein by reference in their entirety. In such embodiments, a network specification is received from the network endpoint. Resources from one or more resource providers are provisioned. An on-demand computing network is configured according to the network specification, wherein a first provisioned resource is configured as a hub device and one or more second provisioned resources are provisioned as rim devices, where rim devices are configured to communicate with one another only via the hub device. The network endpoint is then implemented as a rim device, which can be contacted by the client only through the hub device. In this embodiment, the client can only see the IP address of the hub device and not the IP address of the network endpoint itself.

(16) FIG. 1 is a block diagram depicting an example topology configuration of a computer-implemented environment **100** to establish a network connection between a client **101** and a network endpoint **105** without revealing the client's network location to the network endpoint **105**. In some embodiments, the client **101** may be a network application or an internet user. The client **101** interacts with a server **102**. In some embodiments, the client **101** connects to the server **102** by navigating to a known URL address of the server **102**. The server **102** interacts with a platform as a service provider **103**. In some embodiments, the server requests the platform as a service provider to create a proxy instance **104** (e.g., a proxy instance that is only configured for connections between the client **101** and the network endpoint **105** or a limited set of network endpoints). In some embodiments, the platform as a service provider **103** is configured with Portal Proxy software and configures the proxy instance **104** as a Portal Proxy instance.

(17) The connection between the client **101** and the network endpoint **105** is facilitated by the

proxy instance **104**. In some configurations, the platform as a service provider **103** sends a URL of the proxy instance **104** to the server **102**, which then sends the URL of the proxy instance **104** to the client **101**. The client **101** then accesses the proxy instance, such as by using the URL of the proxy instance **104** to establish a connection to the proxy instance **104**. This connection between the client **101** and the proxy instance **104** may take a variety of forms, including a virtual private network (VPN) connection. In some implementations, the proxy instance **104** may be configured with an IP address whitelist that is populated with an address associated with the client **101**, thereby limiting connections to the proxy instance **104** to connections from the client **101**.

(18) In embodiments, this process prevents the network endpoint **105** from determining an actual network location of the client **101**. Instead, the network endpoint **105** is limited to determining a network location of the proxy instance **104** by observing the connection made to the network endpoint **105** by the client **101** through the proxy instance **104**.

(19) In some examples, the proxy instance **104** is a temporary entity to facilitate communication between the client **101** and the network endpoint **105** for a limited period of time. For example, the proxy instance **104** may be deleted upon the occurrence of a session end criteria. In some embodiments, the session end criteria occurs when the client **101** terminates a connection to the network endpoint **105** or to the proxy instance, whereupon detection of that connection termination, the proxy instance initiates termination of its instance (e.g., via a message to the platform as a service provider **103**). In another example, the session end criteria takes the form of an expiration of a pre-determined period of time or inactivity for more than a threshold period of time, such session end criteria may be detected by the proxy instance **104**, by the server **102**, or by the platform as a service provider **103** that spawned the proxy instance **104**. In some embodiments, when the client **101** is done with the connection to the network endpoint **105**, the client **101** directs the server **102** to delete the proxy instance **104** via a communication to the server **102**. The server **102** directs the platform as a service provider **103** to delete the proxy instance **104**, and the platform as a service provider **103** deletes the proxy instance **104**.

(20) In embodiments, the implementation of FIG. 1 can be accomplished without the client **101** needing to have accounts or credentials with any platform as a service provider **103**. Because the server **102** acts as an agent to the platform as a service provider **103**, more than one platform as a service provider may be used for different connections without requiring additional configuration on the client **101**.

(21) FIG. 2 is a block diagram depicting an example set of operations to establish a network connection between a client **201** and a network endpoint **205** without revealing the client's network location to the network endpoint **205**. In some embodiments, the client **201** may be a network application or a network user. In some embodiments, in communication 1 of FIG. 2, the client **201** initiates a connection with a server **202** by connecting to a known URL address of the server **202**. Upon connecting to the server **202**, the client **201** requests a proxy connection to the network endpoint **205** by communicating the known URL address of the network endpoint **205** to the server **202**.

(22) Upon receiving the URL of the network endpoint **205** from the client **201**, in communication 2 of FIG. 2, the server **202** makes a request to a platform as a service provider **203** to configure and launch a proxy instance **204**. The proxy instance **204** is configured to redirect connections made to the proxy instance **204** to the network endpoint **205** in communication 3 of FIG. 2. In some embodiments, the proxy instance **204** is an instance of the Portal Proxy software. In some embodiments, in communication 4 of FIG. 2, the platform as a service provider **203** communicates a URL of the proxy instance **204** to the server **202** upon launching the proxy instance **204**. In communication 5 of FIG. 2, the server **202** communicates the URL of the proxy instance **204** to the client **201**.

(23) Upon receiving the URL of the proxy instance **204** from the server **202**, the client **201** uses the URL to make a connection to the proxy instance **204** in communication 6 of FIG. 2. The

connection of the client **201** to the proxy instance **204** is then forwarded by the proxy instance **204** to the network endpoint **205** in communication 7 of FIG. 2.

(24) In some embodiments, the network endpoint **205** is unable to determine an actual network location of the client **201**. Instead, the network endpoint **205** can only determine a network location of the proxy instance **204** by observing the connection made to the network endpoint **205** by the client **201** through the proxy instance **204**.

(25) The proxy instance **204** is deleted upon the occurrence of a session end criteria. In some embodiments, the session end criteria occurs when the client **201** terminates a connection to the network endpoint **205**, an expiration of a pre-determined period of time, or inactivity for more than a threshold period of time. In some embodiments, in communication 8 of FIG. 2, when the client **201** is done with the connection to the network endpoint **205**, the client **201** directs the server **202** to delete the proxy instance **204**. In communication 9 of FIG. 2, the server **202** directs the platform as a service provider **203** to delete the proxy instance **204**. In communication 10 of FIG. 2 the platform as a service provider **203** deletes the proxy instance **204**.

(26) FIG. 3 is a block diagram depicting an example topology configuration of a computer-implemented environment **300** to establish a network connection between a client **301** and a network endpoint **305** without revealing the network endpoint's network location to the client **301**. In some embodiments, the client **301** may be a network application or an internet user. The client **301** interacts with a server **302**. In some embodiments, the network endpoint **305** connects to the server **302** by navigating to a known URL address of the server **302**. The server **302** interacts with a platform as a service provider **303**. In some embodiments, the server requests the platform as a service provider to create a pool of proxy instances **304** (e.g., a proxy instance that is only configured for connections between the client **301** and the network endpoint **305** or a limited set of network endpoints). In some embodiments, the platform as a service provider **303** is configured with Portal Proxy software and configures the pool of proxy instances **304** as Portal Proxy instances.

(27) The connection between the client **301** and the network endpoint **305** is facilitated by the individual proxy instance **306**, which is allocated to the client **301** by the server **302** when a client **301** navigates to a known URL for the network endpoint **305** in some embodiments. Upon allocating the individual proxy instance **306** to the client **301**, a new proxy instance is added to the pool of proxy instances **304** to maintain the pool of proxy instances **304** in some embodiments. In some embodiments, the platform as a service provider **303** sends a URL of the individual proxy instance **306** to the server **302**, which then sends the URL of the proxy instance **104** to the client **301**. The client **301** then accesses the individual proxy instance **306**, such as by using the URL of the individual proxy instance **306** to establish a connection to the individual proxy instance **306**. This connection between the client **301** and the individual proxy instance **306** may take a variety of forms, including a virtual private network (VPN) connection. In some implementations, the individual proxy instance **306** may be configured with an IP address whitelist that is populated with an address associated with the client **301**, thereby limiting connections to the individual proxy instance **306** to connections from the client **301**.

(28) In embodiments, this process prevents the client **301** from determining an actual network location of the network endpoint **305**. Instead, the client **301** is limiting to determining a network location of the individual proxy instance **306** by observing the connection made to the network endpoint **305** by the client **301** through the individual proxy instance **306**. In some examples, the individual proxy instance **306** is a temporary entity to facilitate communication between the client **301** and the network endpoint **305** for a limited period of time. For example, the individual proxy instance **306** may be deleted upon the occurrence of a session end criteria (e.g., session end criteria as described above with reference to FIG. 1. In embodiments, the pool of proxy instances **304** may not use the real IP address of the network endpoint **305** as their designated endpoint, but may instead be Inbound Proxy nodes of a Fognigma Network, as described in U.S. Pat. Nos. 9,935,850,

10,476,761, and 10,897,409. In embodiments, the actual network endpoint **305** server(s) may exist within a Fognigma Network and accessible only via an Inbound Proxy.

(29) FIG. **4** is a block diagram depicting an example set of operations to establish a network connection between a client **401** and a network endpoint **405** without revealing the network endpoint's network location to the client **401**. In some embodiments, in communication **1** of FIG. **4**, a network endpoint **405** initiates a connection with a server **402** by connecting to a known URL address of the server **402**. In communication **2** of FIG. **4**, the server **402** then makes a request to a platform as a service provider **403** to configure and launch a pool of proxy instances **404**.

(30) In embodiments, in communication **3** of FIG. **4**, the pool of proxy instances **404** are each configured to redirect inbound connections to the network endpoint **405**. In embodiments, credentials for configuring the pool of proxy instances **404** are provided by the network endpoint **405**. In some embodiments, the pool of proxy instances **404** are Portal Proxy instances.

(31) When a client **401** enters a known URL of the network endpoint **405**, the client is connected to the server **402** in communication **4** of FIG. **4**. Upon connecting to the server **402**, in communication **5** of FIG. **4**, the server **402** allocates an individual proxy instance **406** from the pool of proxy instances **404** for use by the client **401**. As the server **402** allocates the individual proxy instance **406** from the pool of proxy instances **404** for use by the client **401**, in communication **6** of FIG. **4**, the server **402** sends a request to the platform as a service provider **403** to configure and launch a new proxy instance to maintain the pool of proxy instances **404**. In communication **7** of FIG. **4**, the platform as a service provider then configures and launches a new proxy instance to maintain the pool of proxy instances **404**.

(32) In embodiments, in communication **8** of FIG. **4**, the server **402** issues an HTTP 302 (Resource Temporarily Moved) response code to the client **401**, containing a URL of the individual proxy instance **406** that was allocated to the client **401** by the server **402**. Upon receiving the URL of the individual proxy instance **406**, the client **401** makes a connection to the individual proxy instance **406** in communication **9** of FIG. **4**. The individual proxy instance **406** forwards the connection with the client **401** to the network endpoint **405** in communication **10** of FIG. **4**.

(33) In embodiments, this process prevents the client **401** from determining an actual network location of the network endpoint **405**. Instead, the client **401** is limited to determining a network location of the individual proxy instance **406** by observing the connection made to the network endpoint **405** by the client **401** through the individual proxy instance **406**.

(34) In some examples, the individual proxy instance **406** is a temporary entity to facilitate communication between the client **401** and the network endpoint **405** for a limited period of time. For example, the individual proxy instance **406** may be deleted upon the occurrence of a session end criteria. In some embodiments, the session end criteria occurs when the network endpoint **405** determines the session with the client **401** to be over. In some embodiments, the session with the client **401** may be deemed to be over when the client **401** terminates a connection to the network endpoint **405** or to the individual proxy instance **406**, whereupon detection of that connection termination, the individual proxy instance **406** initiates termination of its instance. In another example, the session end criteria takes the form of an expiration of a pre-determined period of time, or inactivity for more than a threshold period of time such session end criteria may be detected by the individual proxy instance **406** or by the server **402** that spawned the individual proxy instance **406**. In some embodiments, when the network endpoint **405** determines the session with the client **401** to be over the network endpoint **405** directs the server **402** to delete the individual proxy instance **406** via a communication to the server **102** in communication **11** of FIG. **4**. In communication **12** of FIG. **4**, the server **402** directs the platform as a service provider **403** to delete the individual proxy instance **406**. In communication **13** of FIG. **4**, the platform as a service provider **403** deletes the proxy instance **406**.

(35) FIG. **5** depicts an example topology configuration of a serverless computer-implemented environment **500** to establish a network connection between a client **501** and a network endpoint

505 without revealing the client's network location to the network endpoint **505**. In some embodiments, the client **501** may be a network application or a network user. In some embodiments, the client **501** requests a proxy connection to the network endpoint **505** by communicating a known URL address of the network endpoint **505** to a platform as a service provider **503**.

(36) Upon receiving the URL of the network endpoint **505** from the client **501**, the platform as a service provider **503** configures and launches a proxy instance **504** (e.g., a proxy instance that is only configured for connections between the client **501** and the network endpoint **505** or a limited set of network endpoints). The proxy instance **504** is configured to redirect connections made to the proxy instance **504** to the network endpoint **505**. In some embodiments, the proxy instance **504** is an instance of the Portal Proxy software. In some embodiments, the platform as a service provider **503** communicates a URL of the proxy instance **504** to the client **501** upon launching the proxy instance **504**.

(37) Upon receiving the URL of the proxy instance **504**, the client **501** uses the URL to make a connection to the proxy instance **504**. The connection of the client **501** to the proxy instance **504** is then forwarded by the proxy instance **504** to the network endpoint **505**. This connection between the client **501** and the proxy instance **504** may take a variety of forms, including a virtual private network (VPN) connection. In some implementations, the proxy instance **504** may be configured with an IP address whitelist that is populated with an address associated with the client **501**, thereby limiting connections to the proxy instance **504** to connections from the client **501**.

(38) In embodiments, this process prevents the network endpoint **505** from determining an actual network location of the client **501**. Instead, the network endpoint is limited to determining a network location of the proxy instance **504** by observing the connection made to the network endpoint **505** by the client **501** through the proxy instance **504**.

(39) In some examples, the proxy instance **504** is a temporary entity to facilitate communication between the client **501** and the network endpoint **505** for a limited period of time. For example, the proxy instance **504** may be deleted upon the occurrence of a session end criteria as described above. In embodiments, the implementation of FIG. 5 can be accomplished without the client **501** needing to have accounts or credentials with any platform as a service provider **503**. The proxy instance **504** may be configured with an IP address whitelist limiting connections to the proxy instance **504** to connections from the client **501**.

(40) FIG. 6 is a block diagram depicting an example serverless set of operations to establish a network connection between a client **601** and a network endpoint **605** without revealing the client's network location to the network endpoint **605**. In some embodiments, the client **601** may be a network application or a network user. In some embodiments, in communication 1 of FIG. 6, the client **601** makes a connection to a platform as a service provider **603** and requests the platform as a service provider **603** to configure and launch a proxy instance **604** (e.g., a proxy instance that is only configured for connections between the client **101** and the network endpoint **105** or a limited set of network endpoints).

(41) In some embodiments, a known URL of the network endpoint **605** is provided to the platform as a service provider **603** by the client **601**, which configures the proxy instance **604** to have a proxy destination of the known URL of the network endpoint **605** in communication 2 of FIG. 6. In some embodiments, the proxy instance **604** is a Portal Proxy instance.

(42) In some embodiments, upon launching the proxy instance **604**, the platform as a service provider reports successful launch of the proxy instance **604** to the client **601**, along with a URL of the proxy instance **604** in communication 3 of FIG. 6. Upon receiving the URL of the proxy instance **604**, the client **601** establishes a connection to the proxy instance **604** in communication 4 of FIG. 6. This connection between the client **601** and the proxy instance **604** may take a variety of forms, including a virtual private network (VPN) connection. In some implementations, the proxy instance **604** may be configured with an IP address whitelist that is populated with an address

associated with the client **601**, thereby limiting connections to the proxy instance **604** to connections from the client **601**. The connection between the client **601** and the proxy instance **604** is then forwarded by the proxy instance **604** to the network endpoint **605** in communication 5 of FIG. 6.

(43) The proxy instance **604** is deleted upon the occurrence of a session end criteria. In some embodiments, the session end criteria occurs when the network endpoint **605** determines the session with the client **601** to be over. In some embodiments, the session with the client **601** may be deemed to be over when the client **601** terminates a connection to the network endpoint **605**, an expiration of a pre-determined period of time, or inactivity for more than a threshold period of time. In some embodiments, when the network endpoint **605** determines the session with the client **601** to be over, in communication 6 of FIG. 6, the network endpoint **605** directs the platform as a service provider **603** to delete the individual proxy instance **604**. In communication 7 of FIG. 6, the platform as a service provider **603** deletes the proxy instance **604**.

(44) Under these circumstances, the network endpoint **605** is unable to determine an actual network location of the client **601**. Instead, the network endpoint **605** can only determine a network location of the proxy instance **604** by observing the connection made to the network endpoint **605** by the client **601** through the proxy instance **604**.

(45) The proxy instance **604** may be configured with an IP address whitelist limiting connections to the proxy instance **604** to connections from the client **601**.

(46) FIG. 7 is a flow diagram depicting a computer-implemented method configuration to establish a network connection between two parties comprising a client and a network endpoint without revealing one party's network location to the other party. At **701**, a request is made to a server identifying a network endpoint to be accessed. At **702**, a proxy instance is configured to receive a connection from a client and to forward that client connection to the identified network endpoint. At **703**, a connection is established between the client and the proxy instance. At **704**, the client connection is forwarded to the identified network destination. At **705**, the proxy instance is deleted upon occurrence of a session end criteria.

(47) Systems and methods as described herein may take a variety of forms. The foregoing outlines features of several embodiments so that those skilled in the art may better understand the aspects of the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

Claims

1. A computer-implemented method of connecting a client to a desired network endpoint, comprising: receiving, at a server, a request from a requestor identifying the desired network endpoint to be accessed; wherein the server acts as an agent for the requestor to a platform as a service provider such that the requestor and the platform as a service provider do not directly communicate; using the server to allocate one or more proxy instances to receive a connection from the client and to forward the connection to the network endpoint, the one or more proxy instances comprising: at least one proxy instance configured to receive the connection from the client to set up a discrete network connection between the client and the network endpoint, and at least one proxy instance configured to facilitate the discrete network connection without any detectable direct contact between the client and the network endpoint; and deleting the one or more proxy instances upon occurrence of a session end criteria.

2. The method of claim 1, wherein the requestor is the network endpoint, prompting the server to request the platform as a service provider to perform the configuring of the one or more proxy instances; and wherein the platform as a service provider performs the configuring of the one or more proxy instances.
3. The method of claim 2, wherein the one or more proxy instances comprises a pool of proxy instances.
4. The method of claim 3, wherein the server allocates one proxy instance from the pool of proxy instances to the client upon the client entering a URL corresponding to the network endpoint.
5. The method of claim 4, wherein the server requests the platform as a service provider to create a new proxy instance upon the server allocating the one proxy instance from the pool of proxy instances to the client; and wherein the platform as a service provider creates the new proxy instance per the server's request.
6. The method of claim 4, wherein the server issues an HTTP 302 (Resource Temporarily Moved) response code to the client containing a URL of the one proxy instance that was allocated to the client.
7. The method of claim 1, wherein the at least one proxy instance configured to receive the connection from the client to set up the discrete network connection comprises a first reverse proxy, and the at least one proxy instance configured to facilitate the discrete network connection without any detectable direct contact between the client and the network endpoint comprises a second reverse proxy; and wherein the one or more proxy instances are further implemented by: sending an invitation indicating a mechanism for connecting to the first reverse proxy to the client; sending access credentials to the client over the first reverse proxy connection including an address for connecting to the second reverse proxy; and deleting the first reverse proxy connection upon delivery of the access credentials.
8. The method of claim 1, wherein the session end criteria comprises the client terminating the discrete network connection to the network endpoint, an expiration of a pre-determined period of time, or inactivity for more than a threshold period of time.
9. The method of claim 1, wherein the requestor is the client.
10. The method of claim 9, wherein the one or more proxy instances are configured with an IP address whitelist limiting connections to the one or more proxy instances to connections from the client.
11. The method of claim 1, wherein the server forwards the request to the platform as a service provider to configure the one or more proxy instances.
12. The method of claim 11, wherein the server requests the platform as a service provider to delete the one or more proxy instances upon occurrence of the session end criteria; and wherein the platform as a service provider deletes the one or more proxy instances per the server's request.
13. The method of claim 11, wherein the server receives at least one URL to the one or more proxy instances from the platform as a service provider and transmits the at least one URL of the one or more proxy instances to the client, the client establishing the connection to the one or more proxy instances using the at least one URL of the one or more proxy instances.
14. The method of claim 13, wherein the network endpoint is the public IP address of an inbound proxy node comprising a hub device of an on-demand computing network configured to comprise one or more rim devices, which can only be contacted by the client through the hub device wherein the network endpoint is configured to be a rim device.
15. A computer-implemented system for connecting a client to a desired network endpoint, comprising: a server comprising: one or more data processors; and a non-transitory computer-readable medium encoded with instructions to command one or more data processors to: receive a request from a requestor identifying the desired network endpoint to be accessed; act as an agent for the requestor to a platform as a service provider such that the requestor and the platform as a service provider do not directly communicate; make a request to the platform as a service provider

to configure one or more proxy instances to receive a connection from the client and to forward the connection to the network endpoint, the one or more proxy instances comprising: at least one proxy instance configured to receive the connection from the client to set up a discrete network connection between the client and the network endpoint, and at least one proxy instance configured to facilitate the discrete network connection without any detectable direct contact between the client and the network endpoint; and delete the one or more proxy instances upon occurrence of a session end criteria.

16. The computer-implemented system of claim 15, wherein the requestor is the client.

17. The computer-implemented system of claim 15, wherein the requestor is the network endpoint, prompting the server to request the platform as a service provider to perform the configuring of the one or more proxy instances; and wherein the platform as a service provider performs the configuring of the one or more proxy instances.

18. The computer-implemented system of claim 17, wherein the one or more proxy instances comprises a pool of proxy instances.

19. The computer-implemented system of claim 18, wherein the server allocates one proxy instance from the pool of proxy instances to the client upon the client entering a URL corresponding to the network endpoint.

20. A computer-implemented system for connecting a client to a desired network endpoint, comprising: a processor-implemented platform as a service provider configured to implement instructions stored on a computer-readable medium that commands the platform as a service provider to execute steps comprising: receiving a request from the client identifying the desired network endpoint to be accessed; configuring one or more proxy instances to receive a connection from the client and to forward the connection to the network endpoint, the one or more proxy instances comprising: a first reverse proxy instance configured to receive the connection from the client to set up a discrete network connection between the client and the network endpoint, and a second reverse proxy instance configured to facilitate the discrete network connection without any detectable direct contact between the client and the network endpoint; wherein the client to network endpoint connection is implemented by: sending to the client a mechanism for connecting to the first reverse proxy; and sending access credentials to the client over the first reverse proxy connection for connecting to the second reverse proxy; and deleting the one or more proxy instances upon occurrence of a session end criteria.

21. A computer-implemented method of connecting a client to a desired network endpoint, comprising: receiving, at a server, a request from a requestor identifying the desired network endpoint to be accessed; wherein the server acts as an agent for the requestor to a platform as a service provider such that the requestor and the platform as a service provider do not directly communicate; using the server to allocate a pool of proxy instances that is configured to set up a discrete network connection between the client and the network endpoint, wherein at least one of the proxy instances is configured to receive a connection from the client and to forward the connection to the network endpoint; allocating the at least one proxy instance from the pool of proxy instances; facilitating the discrete network connection without any detectable direct contact between the client and the network endpoint using the at least one proxy instance; and deleting the at least one proxy instance upon occurrence of a session end criteria.

22. The method of claim 21, wherein each of the proxy instances of the pool of proxy instances are configured to receive the connection from the client and forward the connection to the network endpoint.

23. The method of claim 21, wherein the pool of proxy instances comprises a quantity of proxy instances, and wherein the server requests the platform as a service provider to create at least one new proxy instance to maintain the quantity of proxy instances upon the server allocating the at least one proxy instance to the client; and wherein the platform as a service provider creates the new proxy instance per the server's request.

