

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396856
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Collins; Simon et al.

Ceramic femoral resurfacing head prosthesis

Abstract

A ceramic femoral resurfacing head prosthesis (**110**) comprises a ceramic convex outer contact surface (**112**) engagable with an acetabulum of a patient or an acetabular cup prosthesis and a concave inner fixation surface (**114**) having an inner-land portion (**128**), the ceramic convex outer contact surface (**112**) and the concave inner fixation surface (**114**) extending to intersect each other at a rim (**116**). A ceramic stem (**120**) projects from the concave inner fixation surface (**114**), and is adapted to be received by a stem bore. The concave inner fixation surface (**114**) includes a skirt (**134**) which is cylindrical or substantially cylindrical, or frusto-conical or substantially frusto-conical, and at least one circumferentially elongate recess (**136**) at the skirt (**134**).

Inventors: Collins; Simon (Tetbury, GB), Taylor; Andrew Clive (Chichester, GB), Tuke; Michael Antony (Surrey, GB), Carrasco; Carolina Avila (Surrey, GB)

Applicant: MatOrtho Limited (Surrey, GB)

Family ID: 1000008782861

Assignee: MatOrtho Limited (Surrey, GB)

Appl. No.: 17/534412

Filed: November 23, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220079765 A1	Mar. 17, 2022

Foreign Application Priority Data

GB	1718082	Nov. 01, 2017
----	---------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **A61F2/36** (20060101); **A61F2/30** (20060101); **A61F2/46** (20060101)

U.S. Cl.:

CPC **A61F2/3603** (20130101); **A61F2/30771** (20130101); **A61F2/3609** (20130101);
A61F2/4609 (20130101); A61F2002/30327 (20130101); A61F2002/30593 (20130101);
A61F2002/30616 (20130101); A61F2002/30822 (20130101); A61F2002/30881
(20130101); A61F2002/3605 (20130101); A61F2002/3615 (20130101)

Field of Classification Search

CPC: A61F (2/3603); A61F (2002/30822); A61F (2002/3615); A61F (2002/4007)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4224699	12/1979	Weber	N/A	N/A
4312079	12/1981	Dorre et al.	N/A	N/A
4752296	12/1987	Buechel	623/23.14	A61F 2/40
6063124	12/1999	Amstutz	623/22.21	A61F 2/3603
6096084	12/1999	Townley	623/23.14	A61F 2/32
6524343	12/2002	Storer	623/22.46	A61F 2/3603
7255717	12/2006	Park	623/23.14	A61F 2/3603
7338498	12/2007	Long	606/102	A61F 2/3603
7517364	12/2008	Long	623/19.14	A61B 17/15
7527631	12/2008	Maroney	606/102	A61B 90/06
8177852	12/2011	Mcminn	623/22.44	A61F 2/3859
8361163	12/2012	Quaid	623/23.13	A61B 17/1668
11278414	12/2021	Collins	N/A	A61F 2/3603
11672668	12/2022	Iannotti	623/19.14	A61F 2/4003
11771561	12/2022	Running	623/19.13	A61F 2/30749
2002/0022889	12/2001	Chibrac	623/18.11	A61B 17/1684
2005/0065612	12/2004	Winslow	623/19.14	A61F 2/4014
2006/0085079	12/2005	Carroll	623/23.39	A61F 2/36
2006/0184251	12/2005	Zhang	623/23.56	A61F 2/30767
2007/0162149	12/2006	Kropf	N/A	N/A
2008/0033577	12/2007	Kohan	623/32	A61L 27/58
2009/0018666	12/2008	Grundei	623/22.21	A61F 2/3603
2009/0149965	12/2008	Quaid	623/22.4	A61B 17/1668
2009/0192620	12/2008	Ebbitt	623/18.11	A61F 2/4607
2009/0248170	12/2008	Tuke	623/23.11	A61F 2/3603

2009/0306788	12/2008	Timoteo	623/23.14	A61B 17/15
2010/0076570	12/2009	Band et al.	N/A	N/A
2010/0305713	12/2009	Grundei	623/23.12	A61F 2/3603
2010/0312353	12/2009	Howald	623/23.12	A61B 17/175
2012/0029650	12/2011	Bruce	623/22.4	A61F 2/3603
2013/0060347	12/2012	McMinn	623/23.23	A61F 2/3603
2015/0335437	12/2014	Bruun Lauritzen	623/23.12	A61F 2/34
2016/0045320	12/2015	Klinger et al.	N/A	N/A
2016/0113771	12/2015	McMinn	623/23.11	A61F 2/3603
2018/0325695	12/2017	Wozencroft	N/A	A61F 2/4607
2021/0045881	12/2020	Melozzi	N/A	A61F 2/3603

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2751537	12/1978	DE	N/A
1570816	12/2004	EP	N/A
1900344	12/2007	EP	N/A
2686503	12/1992	FR	N/A
2996443	12/2013	FR	N/A
2139097	12/1983	GB	N/A
396561	12/2003	GB	N/A
2434749	12/2006	GB	N/A
2531589	12/2015	GB	N/A
2012011866	12/2013	MX	N/A
2004032987	12/2003	WO	N/A
2008037978	12/2007	WO	N/A

OTHER PUBLICATIONS

Examination Report of IP Australia in related Australian Patent Appl. No. 2018361710, dated Oct. 27, 2023, 6 pages. cited by applicant

Examination Report of the European Patent Office in related European Patent Appl. No. 22183281.9, dated Jan. 4, 2024, 6 pages. cited by applicant

Extended European Search Report of the European Patent Office in related European Patent Appl. No. 22182910.4, dated Aug. 30, 2022, 7 pages. cited by applicant

Partial European Search Report of the European Patent Office in related European Patent Appl. No. 22183281.9, dated Jun. 13, 2023, 10 pages. cited by applicant

Extended European Search Report of the European Patent Office in related European Patent Appl. No. 22189014.8, dated Jun. 16, 2023, 6 pages. cited by applicant

Extended European Search Report of the European Patent Office in related European Patent Appl. No. 22183281.9, dated Aug. 30, 2023, 11 pages. cited by applicant

Search Report of the United Kingdom Intellectual Property Office in related application No. GB1718082.9 for claims 35-47, dated Dec. 14, 2017, 2 pages. cited by applicant

Search Report of the United Kingdom Intellectual Property Office in related application No. GB1718082.9 for claims 62-75, dated Dec. 14, 2017, 2 pages. cited by applicant

Search Report of the United Kingdom Intellectual Property Office in related application No. GB1718082.9 for claims 1-26, dated Dec. 15, 2017, 1 page. cited by applicant

Search Report of the United Kingdom Intellectual Property Office in related application No. GB1718082.9 for claims 27-34, dated Dec. 15, 2017, 1 page. cited by applicant

Search Report of the United Kingdom Intellectual Property Office in in related application No. GB1718082.9 for claims 48-61, dated Dec. 15, 2017, 1 page. cited by applicant

Examination Report of the United Kingdom Intellectual Property Office in related application No. GB1718082.9, dated Jun. 24, 2021, 8 pages. cited by applicant
Examination Report of the United Kingdom Intellectual Property Office in related application No. GB1718082.9, dated Jul. 20, 2021, 2 pages. cited by applicant
Combined Search and Examination Report of the United Kingdom Intellectual Property Office in related application No. GB1802167.5, dated Feb. 28, 2018, 4 pages. cited by applicant
Search Report of the United Kingdom Intellectual Property Office in in related application No. GB1905809.8 for claims 1-14, dated May 3, 2019, 1 page. cited by applicant
Examination Report of the United Kingdom Intellectual Property Office in related application No. GB1905809.8, dated Oct. 15, 2019, 4 pages. cited by applicant
Examination Report of the United Kingdom Intellectual Property Office in related application No. GB1905809.8, dated Dec. 2, 2019, 2 pages. cited by applicant
Examination Report of the United Kingdom Intellectual Property Office in related application No. GB1905809.8, dated Jan. 14, 2020, 1 page. cited by applicant
Search Report of the United Kingdom Intellectual Property Office in related application No. GB1906631.5 for claims 1-17, dated May 23, 2019, 2 pages. cited by applicant
Examination Report of the United Kingdom Intellectual Property Office in related application No. GB1906631.5, dated Apr. 20, 2020, 2 pages. cited by applicant
Search Report of the United Kingdom Intellectual Property Office in related application No. GB1912801.6 for claims 1-17, dated Jan. 29, 2020, 1 page. cited by applicant
Combined Search and Examination Report of the United Kingdom Intellectual Property Office in related application No. GB1912801.6, dated Jan. 30, 2020, 5 pages. cited by applicant
Examination Report of the United Kingdom Intellectual Property Office in related application No. GB1912801.6, dated Jul. 6, 2020, 4 pages. cited by applicant
Search Report of the United Kingdom Intellectual Property Office in related application No. GB1912801.6, dated Jun. 28, 2021, 3 pages. cited by applicant
International Search Report in related international application No. PCT/GB2018/053182, dated Feb. 12, 2019, 10 pages. cited by applicant
Communication pursuant to Article 94(3) EPC of the European Patent Office in related European Patent Appl. No. 22189014.8, dated Feb. 20, 2025, 3 pages. cited by applicant

Primary Examiner: Stewart; Alvin J

Attorney, Agent or Firm: Bochner PLLC

Background/Summary

(1) The present invention relates to a ceramic femoral resurfacing head prosthesis for use in hip resurfacing procedures. The invention further relates to a method of increasing a fixation-land area of a ceramic femoral resurfacing head and a femoral resurfacing head prosthesis system for selective engagement of a femoral resurfacing head prosthesis with a resected femur based on one or more characteristics of the resected femur.

(2) Femoral resurfacing has been developed as an alternative to conventional total hip replacement in a procedure for the treatment of arthritis of the hip, a condition which causes considerable pain and loss of movement. The hip is a ball and socket joint which allows the upper leg to move from side to side, back to front, and to rotate. The joint is made up of the head of the femur, the ball, which fits into the acetabulum, the socket. In a healthy hip, both the head of the femur and acetabulum are covered with cartilage which provides a smooth surface allowing the joint to move

freely.

(3) In general, femoral resurfacing involves the process of capping the head of the femur with a femoral resurfacing head prosthesis, attaching the prosthesis via bone cement, and fitting an acetabular cup to the acetabulum, generally using cementless fixation via a Titanium and/or Hydroxyapatite plasma coating. The femoral resurfacing head prosthesis and acetabular cup are conventionally formed from metal. A femoral resurfacing head prosthesis **10** in accordance with the state of the art is shown in FIGS. **1** to **5** and typically comprises a substantially spherical convex outer contact surface **12**, a concave inner fixation surface **14**, a rim **16** between the two surfaces defining an opening **18** and a stem **20** projecting from the concave inner fixation surface **14** and through the opening **18**.

(4) It has been found that a metal-on-metal resurfacing can result in the production of metal ions and subsequent diffusion or transport of the metal ions to the bloodstream or locality surrounding the hip replacement prosthesis. The presence of metal ions can result in allergic reaction or other adverse health effects for the patient.

(5) Additionally, there is a risk of partial or total detachment of the femoral resurfacing head prosthesis from the underlying bone cement, if the adhesion or bonding between them is insufficient. Therefore, an increase in the area of overlap between an inner surface of a femoral resurfacing head prosthesis to the femur is desired, in order to increase the adhesion and thus minimise said risk. Further, by maximising the bone volume within the head prosthesis, bone resorption that can occur from stress shielding may be minimised.

(6) The present invention seeks to provide a solution to these problems.

(7) According to a first aspect of the present invention, there is provided a ceramic femoral resurfacing head prosthesis comprising: a ceramic convex outer contact surface engagable with an acetabulum of a patient or an acetabular cup prosthesis; a concave inner fixation surface having an inner-land portion, the ceramic convex outer contact surface and the concave inner fixation surface extending to intersect each other at a rim; and a ceramic stem projecting from the concave inner fixation surface, the stem adapted to be received by a stem bore, wherein a free distal end of the stem is at, or spaced inwardly of, a plane defined by the said rim, wherein the concave inner fixation surface includes a skirt between the inner-land portion and the rim of the head prosthesis, the skirt being cylindrical or substantially cylindrical, or frusto-conical or substantially frusto-conical, and at least one circumferentially elongate recess at the skirt to prevent or inhibit pull-off removal of the head prosthesis.

(8) The use of ceramic is advantageous as the production of potentially hazardous metal ions is prevented or limited, given the reduction in the amount of metal used for the prosthesis. Additionally, ceramics are typically harder than most metals and therefore the wear of the prosthesis can be reduced compared to a typical arrangement, resulting in an increased longevity of the prosthesis. Hip resurfacing prostheses typically are not formed from ceramic as ceramics are generally brittle by nature and fracture can be unpredictable.

(9) A free distal end of the stem being at, or spaced inwardly of, the rim results in a shorter stem than in a typical or conventional metal resurfacing arrangement. A shorter stem results in a reduced moment acting about the base of the stem and/or at any given point along the stem. This therefore reduces the amount of stress acting at or adjacent to the base and therefore improves the stress characteristics at or adjacent the base. The improvement and/or relative lack of degradation of the stress characteristics at the base of the stem is key for the present invention given its formation from ceramic, rather than metal as is conventional, given that, in general, ceramic has a lower ductility than metal. The risk of mechanical failure of the stem, and thus of the entire prosthesis, is thus reduced. Additionally, as the stem does not project beyond the rim, the prosthesis adopts a shape which substantially saves material. The device is therefore more conveniently and cheaply produced through green machining and sintering, a method typically used for the production of ceramic components. Lastly, the shorter stem results in a shorter stem bore being required to be

drilled for implantation and therefore improves bone conservation.

(10) The concave inner fixation surface may have a plurality of anti-rotation elements spaced around a circumference thereof. The ceramic stem may include at least a two-part angular transition in a longitudinal direction of the stem to meet the inner fixation surface such that the inner-land portion of the inner fixation surface at or adjacent to the stem is increased. The at least two-part angular transition may define a curve in a longitudinal direction of the stem having a non-uniform radius.

(11) The at least two-part angular transition may include a first curved part having a radius in a range of 5 mm to 150 mm, a second curved part having a radius in a range of 10 mm to 100 mm, and a third curved part having a radius in a range of 0.5 mm to 2 mm. More preferably, the first curved part has a radius of or substantially of 50 mm, the second curved part has a radius of or substantially of 17.5 mm, and the third curved part has a radius of or substantially of 1.5 mm.

(12) The first and second curved parts and the second and third curved parts may be contiguous with each other. The at least two-part angular transition may include at least one flat in a longitudinal direction of the stem. The at least two-part angular transition may be or may include a catenary curve. The circumferentially elongate recess may be an endless channel.

(13) A rim of the ceramic femoral resurfacing head prosthesis defines an asymmetrical profile between the inner fixation surface and the outer contact surface with two or more different arcs having a radius in a range of 0.2 mm to 1.5 mm.

(14) According to a second aspect of the present invention, there is provided a femoral resurfacing head prosthesis comprising: a ceramic convex outer contact surface engagable with an acetabulum of a patient or an acetabular cup prosthesis; a concave inner fixation surface, the ceramic convex outer contact surface and the concave inner fixation surface extending to intersect each other at a rim; and a ceramic stem projecting from the concave inner fixation surface and adapted to be received by a stem bore, wherein a free distal end of the stem is at, or spaced inwardly of, a plane defined by the said rim, wherein the concave inner fixation surface has a plurality of anti-rotation elements spaced around a circumference thereof. Preferably, one or more of the plurality of anti-rotation elements have the form of a discontinuous indentation, discontinuous recess and/or discontinuous groove.

(15) According to a third aspect of the present invention, there is provided a ceramic femoral resurfacing head prosthesis comprising: a ceramic convex outer contact surface engagable with an acetabulum of a patient or an acetabular cup prosthesis; a concave inner fixation surface having an inner-land portion, the ceramic convex outer contact surface and the concave inner fixation surface extending to intersect each other at a rim; and a ceramic stem projecting from the concave inner fixation surface and adapted to be received by a stem bore, wherein a free distal end of the stem is at, or spaced inwardly of, a plane defined by the said rim, wherein the concave inner fixation surface includes a skirt between the inner-land portion and the rim of the head prosthesis, the skirt being cylindrical or substantially cylindrical, or frusto-conical or substantially frusto-conical, at least one circumferentially elongate recess at the skirt to prevent or inhibit pull-off removal of the head prosthesis, and a plurality of anti-rotation elements spaced around a circumference thereof.

(16) According to a fourth aspect of the present invention, there is provided a ceramic femoral resurfacing head prosthesis comprising: a ceramic convex outer contact surface engagable with an acetabulum of a patient or an acetabular cup prosthesis; a concave inner fixation surface, the ceramic convex outer contact surface and the concave inner fixation surface extending to intersect each other at a rim; and a ceramic stem projecting from the concave inner fixation surface and adapted to be received by a stem bore, wherein a free distal end of the stem is at, or spaced inwardly of, a plane defined by the said rim, wherein the ceramic stem includes at least a two-part angular transition in a longitudinal direction of the stem to meet the concave inner fixation surface such that an inner-land portion of the concave inner fixation surface at or adjacent to the ceramic stem is increased, the at least a two-part angular transition defining a curve in a longitudinal

direction of the stem having a non-uniform radius.

(17) According to a fifth aspect of the present invention, there is provided a ceramic femoral resurfacing head prosthesis comprising: a ceramic convex outer contact surface engagable with an acetabulum of a patient or an acetabular cup prosthesis; a concave inner fixation surface, the ceramic convex outer contact surface and the concave inner fixation surface extending to intersect each other at a rim; and a ceramic stem projecting from the concave inner fixation surface and adapted to be received by a stem bore, wherein a free distal end of the stem is at, or spaced inwardly of, a plane defined by the said rim, wherein the ceramic stem includes at least a two-part angular transition in a longitudinal direction of the stem to meet the concave inner fixation surface such that an inner-land portion of the concave inner fixation surface at or adjacent to the ceramic stem is increased, the two-part angular transition being or including a catenary curve.

(18) According to a sixth aspect of the present invention, there is provided a ceramic femoral resurfacing head prosthesis comprising: a ceramic convex outer contact surface engagable with an acetabulum of a patient or an acetabular cup prosthesis; a concave inner fixation surface; a ceramic stem projecting from the inner fixation surface, the stem adapted to be received by a stem bore; a base portion of the stem comprising at least a two-part angular transition in a longitudinal direction of the stem to meet the inner fixation surface, thereby increasing an inner-land portion of the inner fixation surface at or adjacent to the stem.

(19) The extension of the inner-land portion of the inner fixation surface increases an area of overlap between the inner fixation surface and the in use resected head of the femur, to which the ceramic femoral resurfacing head prosthesis is attached. This allows for an increase in an area of contact between in use bone cement or other bonding agent, typically applied between the prosthesis and the femur to adhere the prosthesis to the femur, and the inner fixation surface. An increase in the area of contact can increase the adhesion, and therefore the risk of failure of the resurfacing by detachment of the prosthesis from the femur is reduced. The longevity of the replacement may thus be increased.

(20) Preferably, the concave inner fixation surface has a plurality of anti-rotation elements spaced around a circumference thereof. The at least two-part angular transition may define a curve in a longitudinal direction of the stem having a non-uniform radius.

(21) The at least two-part angular transition may include a first curved part having a radius in a range of 5 mm to 150 mm, a second curved part having a radius in a range of 10 mm to 100 mm, and a third curved part having a radius in a range of 0.5 mm to 2 mm. The first curved part may have a radius of or substantially of 50 mm, the second curved part has a radius of or substantially of 17.5 mm, and the third curved part has a radius of or substantially of 1.5 mm. Preferably, the first and second curved parts and the second and third curved parts are contiguous with each other.

(22) The at least two-part angular transition may include at least one flat in a longitudinal direction of the stem. Preferably, the at least two-part angular transition is or includes a catenary curve.

(23) The concave inner fixation surface may include at least one circumferentially elongate recess for surgical bone cement interdigitation to prevent or inhibit pull-off removal of the head prosthesis. The circumferentially elongate recess may be an endless channel. The inner fixation surface may include a skirt between the inner-land portion and a rim of the head prosthesis, the circumferentially elongate recess being at the skirt.

(24) Preferably, the outer contact surface and the inner fixation surface extend to intersect each other at a or the rim, and a free distal end of the stem is at or spaced inwardly of a plane defined by the said rim. A or the rim may define an asymmetrical profile between the inner fixation surface and the outer contact surface with two or more different arcs having a radius in a range of 0.2 mm to 1.5 mm. A or the rim may include at least an outer radius to the convex outer contact surface equal to or greater than 0.5 mm.

(25) Preferably, the anti-rotation elements comprise one or more indentations on the inner fixation surface to receive a surgical bone cement. One or more of the anti-rotation elements may have the

form of a discontinuous semi-toroidal indentation on the inner fixation surface. The anti-rotation elements may be equi-angularly spaced apart on the inner fixation surface. Preferably, at least one anti-rotation element includes a multipart indentation having a plurality of anti-rotation zones. Each anti-rotation zone may be demarcated from the other anti-rotation zones by discontinuities in depth of the indentation at their respective boundary. Preferably, each anti-rotation element has a central anti-rotation zone, and a plurality of non-central anti-rotation zones adjacent to the central anti-rotation zones. Preferably, at least two non-central anti-rotation zones are separated from each other by the central anti-rotation zone. The central anti-rotation zone may comprise a majority of the volume of the indentation.

(26) According to a seventh aspect of the present invention, there is provided a method of increasing a fixation-land area of a ceramic femoral resurfacing head without or without substantially detrimentally affecting a stress characteristic at or adjacent to an associated stem, the method comprising the step of forming a stem of a ceramic femoral resurfacing head prosthesis in accordance with the first aspect of the invention with at least a two-part angular transition in a longitudinal direction thereof to meet an inner fixation surface.

(27) A two-part angular transition enables a first curved part to have a smaller or tighter radius of curvature, and a second curved part to have a greater radius of curvature, than the radius of curvature of the transition between the stem and the inner fixation surface for a typical or conventional femoral resurfacing head. A smaller radius of curvature allows for a sharper or more abrupt transition between the inner fixation surface and the longitudinal extent of the stem which enables an increase in the extent of the inner fixation surface. A second curved part having a greater bend radius reduces a stress concentration at the base of the stem. As such, the stress characteristic adjacent to the stem is not detrimentally affected, and the risk of mechanical failure of the stem is not increased compared to currently known transitions of metal resurfacing heads, given that the ceramic generally has a lower ductility compared to typical metal compositions.

(28) A radial extent of the at least two-part angular transition may be unbisectable. The at least two-part angular transition may be defined by two different curves. The at least two-part angular transition may be defined by a flat and a curve in a longitudinal direction of the stem.

(29) According to an eighth aspect of the present invention, there is provided a femoral resurfacing head prosthesis system for selective engagement of a femoral resurfacing head prosthesis with a resected femur based on one or more characteristics of the resected femur, the femoral resurfacing head prosthesis system comprising: a first group of ceramic femoral resurfacing head prostheses, each ceramic femoral resurfacing head prosthesis of the first group having a first convex outer contact surface with a predetermined geometry which is different to the others within the first group, the first convex outer contact surface being engageable with an acetabulum of a patient or an acetabular cup prosthesis; a first inner fixation surface adapted to be engaged with a femur of the patient; and a first stem projecting from the first inner fixation surface, the first stem having a first lateral extent adapted to be receivable by a stem bore, the first lateral extent being common to the first group; and at least a second group of ceramic femoral resurfacing head prostheses, each ceramic femoral resurfacing head prosthesis of the second group having a second convex outer contact surface with a predetermined geometry which is different to the others within the second group, the second convex outer contact surface being engagable with an acetabulum of a patient or an acetabular cup prosthesis; a second inner fixation surface adapted to be engaged with a femur of the patient; and a second stem projecting from the second inner fixation surface, the second stem having a second lateral extent adapted to be receivable by a stem bore, the second lateral extent being common to the second group and different to the first group; one said ceramic femoral resurfacing head prosthesis from the first or second groups being selectively engagable with the resected femur based on the one or more characteristics thereof.

(30) Providing a first and second group of ceramic femoral resurfacing head prostheses, each prosthesis within each group having a convex outer contact surface having a different pre-

determined geometry to every other prosthesis within the same respective group, allows for the geometry and/or dimensions of the convex outer contact surface to be more closely matched to the geometry and/or dimensions of the acetabulum of a patient, without necessitating patient-specific construction of each ceramic femoral resurfacing head prosthesis. Advantageously, the prostheses of each of the first group and the second group respectively may have a common second lateral extent, the common second lateral extent of the first group being different to the common second lateral extent of the second group, so that a surgeon or other medical practitioner may select a second lateral extent suitable to the patient's anatomy while reducing the variation of dimension of stem bore that the surgeon may be required to form.

(31) The first convex outer contact surface of each ceramic femoral resurfacing head prosthesis of the first group may have a different equatorial circumference to that of the other ceramic femoral resurfacing head prosthesis in the first group. The second convex outer contact surface of each ceramic femoral resurfacing head prosthesis of the second group may have a different equatorial circumference to that of the other ceramic femoral resurfacing head prosthesis in the second group. The ceramic femoral resurfacing head prostheses of the first and second groups each may have different equatorial circumferences. A length and/or diameter of the first and second stems may be different.

(32) Preferably, a rim of each ceramic femoral resurfacing head prosthesis of the first and second groups defines an asymmetrical profile between the inner fixation surface and the outer contact surface with two or more different arcs having a radius in a range of 0.2 mm to 1.5 mm. The outer contact surface and the inner fixation surface may extend to intersect each other at a rim, and a free distal end of the stem may be at or spaced inwardly of a plane defined by the said rim. The first and/or second inner fixation surfaces may include at least one circumferentially elongate recess to prevent or inhibit pull-off removal of the head prosthesis.

(33) According to a ninth aspect of the present invention, there is provided a ceramic femoral resurfacing head prosthesis comprising: a ceramic convex outer contact surface engagable with an acetabulum of a patient or an acetabular cup prosthesis; a concave inner fixation surface, the outer contact surface and the inner fixation surface extending to intersect each other at a rim; a ceramic stem projecting from the inner fixation surface and adapted to be received by a stem bore, wherein a free distal end of the stem is at, or spaced inwardly of, a plane defined by the said rim.

(34) The concave inner fixation surface may have a plurality of anti-rotation elements spaced around a circumference thereof. The ceramic stem may include at least a two-part angular transition in a longitudinal direction of the stem to meet the inner fixation surface such that an inner-land portion of the inner fixation surface at or adjacent to the stem is increased.

(35) The at least two-part angular transition may define a curve in a longitudinal direction of the stem having a non-uniform radius. The at least two-part angular transition may include a first curved part having a radius in a range of 5 mm to 150 mm, a second curved part having a radius in a range of 10 mm to 100 mm, and a third curved part having a radius in a range of 0.5 mm to 2 mm. The first curved part may have a radius of or substantially of 50 mm, the second curved part has a radius of or substantially of 17.5 mm, and the third curved part has a radius of or substantially of 1.5 mm. The first and second curved parts and the second and third curved parts may be contiguous with each other. The at least two-part angular transition may include at least one flat in a longitudinal direction of the stem. The at least two-part angular transition may or may include a catenary curve.

(36) The concave inner fixation surface may include at least one circumferentially elongate recess to prevent or inhibit pull-off removal of the head prosthesis. The circumferentially elongate recess may be an endless channel. The inner fixation surface may include a skirt between the inner-land portion and a rim of the head prosthesis, the circumferentially elongate recess being at the skirt. A rim of the ceramic femoral resurfacing head prosthesis may define an asymmetrical profile between the inner fixation surface and the outer contact surface with two or more different arcs having a

radius in a range of 0.2 mm to 1.5 mm.

(37) According to a tenth aspect of the present invention, there is provided a ceramic femoral resurfacing head prosthesis comprising: a ceramic convex outer contact surface engagable with an acetabulum of a patient or an acetabular cup prosthesis; a concave inner fixation surface, the outer contact surface and the inner fixation surface extending to intersect each other at a rim; a ceramic stem projecting from the inner fixation surface and adapted to be received by a stem bore, wherein the rim defines an asymmetrical profile between the inner and outer contact surfaces with two or more different arcs having a radius in a range of 0.2 mm to 1.5 mm.

(38) The rim having an asymmetrical profile with two or more different arcs allows for the width of the rim to be increased, by reducing a longitudinal extent of the ceramic femoral resurfacing head prosthesis, whilst simultaneously maximising the inner fixation surface and reducing the risk of damage to an external edge portion of the rim on implantation and/or in use. The width of the rim is increased as compared to a conventional femoral resurfacing head prosthesis by reducing the longitudinal extent of the ceramic femoral resurfacing head prosthesis while maintaining the dimensions of the outer contact surface.

(39) An asymmetric profile enables a radius of curvature of an external edge of the rim to be greater than the radius of curvature of the external edge of the rim of a conventional prosthesis. Furthermore, a radius of curvature of an internal edge of the rim, due to the asymmetry, may be the same or similar as the radius of curvature of a conventional prosthesis, for example. The similar internal edge curvature maximises the inner fixation surface by maintaining the abruptness or sharpness of the transition between the inner fixation surface and the rim, and the gradual, greater radius of curvature of the external edge reduces the risk of damage to the rim by reducing stress concentration adjacent to the external edge rim.

(40) The concave inner fixation surface may have a plurality of anti-rotation elements spaced around a circumference thereof. The rim may include at least an outer radius to the convex outer contact surface equal to or greater than 0.5 mm. A free distal end of the stem may be at, or spaced inwardly of, a plane defined by the said rim.

(41) Preferably, the ceramic stem includes an at least two-part angular transition in a longitudinal direction of the stem to meet the inner fixation surface such that an inner-land portion of the inner fixation surface at or adjacent to the stem is increased. The at least two-part angular transition may define a curve in a longitudinal direction of the stem having a non-uniform radius. The at least two-part angular transition may include a first curved part having a radius in a range of 5 mm to 150 mm, a second curved part having a radius in a range of 10 mm to 100 mm, and a third curved part having a radius in a range of 0.5 mm to 2 mm. The first curved part may have a radius of or substantially of 50 mm, the second curved part has a radius of or substantially of 17.5 mm, and the third curved part has a radius of or substantially of 1.5 mm. The first and second curved parts and the second and third curved parts may be contiguous with each other.

(42) The at least two-part angular transition may include at least one flat in a longitudinal direction of the stem. The at least two-part angular transition may be or include a catenary curve. The concave inner fixation surface may include at least one circumferentially elongate recess to prevent or inhibit pull-off removal of the head prosthesis. The circumferentially elongate recess may be an endless channel. The inner fixation surface may include a skirt between the inner-land portion and a rim of the head prosthesis, the circumferentially elongate recess being at the skirt.

(43) According to an eleventh aspect of the present invention, there is provided a ceramic femoral resurfacing head prosthesis comprising: a ceramic convex outer contact surface engagable with an acetabulum of a patient or an acetabular cup prosthesis; a concave inner fixation surface, the outer contact surface and the inner fixation surface extending to intersect each other at a rim; a ceramic stem projecting from the inner fixation surface and adapted to be received by a stem bore; and at least one circumferentially elongate recess at the concave inner fixation surface to promote surgical bone cement interdigitation and prevent or inhibit pull-off removal of the head prosthesis.

- (44) Pull-off of the head prosthesis after the hip resurfacing surgery had been completed would result in a failure of the prosthesis and thus pain and/or a reduction in mobility of the patient. Further surgery would be necessitated to correct the issue. Therefore, a circumferentially elongate recess increases or maintains a longevity of the resurfaced hip joint.
- (45) The concave inner fixation surface may have a plurality of anti-rotation elements spaced around a circumference thereof. The circumferentially elongate recess may be an endless channel. The inner fixation surface may include a skirt between the inner-land portion and a rim of the head prosthesis, the circumferentially elongate recess being at the skirt.
- (46) The rim may define an asymmetrical profile between the inner and outer contact surfaces with two or more different arcs having a radius in a range of 0.2 mm to 1.5 mm. The rim may include at least an outer radius to the convex outer contact surface equal to or greater than 0.5 mm. A free distal end of the stem may be at, or spaced inwardly of, a plane defined by the said rim.
- (47) The ceramic stem may include an at least two-part angular transition in a longitudinal direction of the stem to meet the inner fixation surface such that an inner-land portion of the inner fixation surface at or adjacent to the stem is increased. The at least two-part angular transition may define a curve in a longitudinal direction of the stem having a non-uniform radius. The at least two-part angular transition may include a first curved part having a radius in a range of 5 mm to 150 mm, a second curved part having a radius in a range of 10 mm to 100 mm, and a third curved part having a radius in a range of 0.5 mm to 2 mm. The first curved part may more preferably have a radius of or substantially of 50 mm, the second curved part has a radius of or substantially of 17.5 mm, and the third curved part has a radius of or substantially of 1.5 mm. The first and second curved parts and the second and third curved parts may be contiguous with each other. The at least two-part angular transition may include at least one flat in a longitudinal direction of the stem.
- (48) The at least two-part angular transition may be or may include a catenary curve.
-

Description

(1) The invention will now be more particularly described, by way of example only, with reference to the accompanying drawings, in which: a. FIG. 1 shows a radial cross-section of a femoral resurfacing head prosthesis in accordance with the state of the art; b. FIG. 2 shows a representation of the femoral resurfacing head prosthesis of FIG. 1 from a distal end of a stem; c. FIG. 3 is a perspective representation of the radial cross-section of FIG. 1 with stress distribution indicated, stress is here indicated by colour with green indicating low stress and red indicating high stress; d. FIG. 4 shows an enlarged view of FIG. 1, showing the interconnection of a stem and an inner fixation surface, stress is here indicated by colour with green indicating low stress and red indicating high stress; e. FIG. 5 shows an enlarged view of FIG. 1, showing a rim of the femoral resurfacing head prosthesis, with the value of the radius of curvature of the internal and external edges of the rim indicated; f. FIG. 6 shows a perspective representation of a first embodiment of a femoral resurfacing head prosthesis, in accordance with the first, fourth, fifth and sixth aspects of the present invention and specifically adapted for the method in accordance with the second aspect of the present invention; g. FIG. 7 shows a representation of the femoral resurfacing head prosthesis of FIG. 6 from a distal end of a stem; h. FIG. 8 shows a perspective representation of a radial cross-section of the femoral resurfacing head prosthesis, with stress distribution indicated; stress is here indicated by colour, with green indicating low stress and red indicating high stress; i. FIG. 9 shows the radial cross-section of the femoral resurfacing head prosthesis in FIG. 8, enlarged and showing the interconnection of a stem and an inner fixation surface, with stress concentration indicated by colour: green indicating low stress and red indicating high stress; j. FIG. 10 is a similar view of the femoral resurfacing head prosthesis shown in FIG. 9, but showing in broken line a prior-art uniform-radius transition between the stem and the inner fixation surface, as well as

in overlaid solid line a multi-part transition between the stem and the inner fixation surface according to the present invention; k. FIG. 11 shows an axial cross-section of the femoral resurfacing head prosthesis of the present invention overlying an axial cross-section of the prior-art resurfacing head, the different cross-sections being indicated by different colours with the femoral resurfacing head prosthesis of the present invention being shown in pink, and the prior-art device being shown in grey; l. FIG. 12 shows an enlargement of a portion of the rim of the femoral resurfacing head prosthesis, referenced by circle A in FIG. 11; m. FIG. 13 shows the enlarged portion of the rim, shown in FIG. 12, with the width of the rim of the present invention overlying a portion of the rim of the prior-art head; n. FIG. 14 shows the enlarged portion of the rim of the femoral resurfacing head prosthesis shown in FIGS. 12 and 13, with a comparison of inner and outer lateral rim-edge radii; o. FIGS. 15a, 15b and 15c show second, third and fourth embodiments of the ceramic femoral resurfacing head prosthesis each embodiment being adapted for a first group of the system in accordance with the third aspect of the present invention; and

(2) FIGS. 16a, 16b and 16c show fifth, sixth and seventh embodiments of the present invention in accordance with each embodiment being adapted for a second group of the system in accordance with the third aspect of the present invention.

(3) Referring to FIGS. 6 to 14 there is shown a ceramic femoral resurfacing head prosthesis **110** comprising a ceramic convex outer contact surface **112**, which is or is a substantially spherical surface and is generally a segment of a sphere slightly greater than a hemisphere, and a concave inner fixation surface **114**.

(4) Although the outer contact surface and the inner fixation surface are described as being convex and concave respectively, it is appreciated that one or both surfaces may in fact not be concave or convex and/or may be at least in part planar or multifaceted, as necessity dictates.

(5) The ceramic convex outer contact surface **112** and the concave inner fixation surface **114** are preferably contiguous and meet at a rim **116** which thereby forms a plane and a circular or substantially circular opening **118**. In this way, the rim may be planar or substantially planar.

(6) A ceramic stem **120** projects from the concave inner fixation surface **114**, preferably opposite or substantially opposite from the opening **118**. The ceramic stem **120** may have a base portion **122** proximal to and at or adjacent to the concave inner fixation surface **114**, a cylindrical or a substantially cylindrical shaped body portion **124** and a frustoconical or substantially frustoconical shaped distal free end **126**, or tip portion, distal to the concave inner fixation surface **114** and the base portion **122**, the body portion **124** separating the base portion **122** from the distal free end **126**.

(7) A longitudinal extent of the ceramic stem **120** is such that the distal free end **126** is at or spaced inwardly of the plane defined by the rim **116**. The ceramic stem **120** is therefore shorter than the stem **20** of the prior art femoral resurfacing head prosthesis; a direct comparison of the two stems can be seen in FIGS. 15a to 15c and 16a to 16c. Whilst the extent of the ceramic stem is so described, it is appreciated that the longitudinal extent of the stem may be such that the distal free end of the stem extends beyond the plane defined by the rim.

(8) The base portion **122** of the ceramic stem **120** merges, substantially merges or transitions into the concave inner fixation surface **114** and the concave inner fixation surface **114** preferably has an inner-land **128** which here may be at or adjacent to base portion **122** such that it may be considered to extend around a circumferential extent of, surround, encircle and/or be adjacent to the base portion **122**. The inner-land **128** is preferably planar or substantially planar and may be transverse, lateral or perpendicular or substantially perpendicular to a longitudinal extent of the ceramic stem **120**. Whilst described as encircling the base portion, it is appreciated that the inner-land may only extend around part of the circumferential extent the base portion.

(9) Adjacent to the inner-land **128**, an intermediary portion **130** of the concave inner fixation surface **114** may extend at an angle to the plane of the inner-land **128**, and preferably at an obtuse angle. This arrangement is such that the intermediary portion **130** and the inner-land **128** together substantially form the shape of an external surface of a frustocone with a base removed.

(10) A plurality of, and preferably three as shown, anti-rotation elements **132** may be equiangularly arranged around a circumferential extent of the concave inner fixation surface **114**, and more specifically the intermediary portion **130**. Each anti-rotation element **132** may here be formed as an indentation, recess or groove in the concave inner fixation surface **114** and a longitudinal extent of the indentation, recess or groove may be aligned with a circumferential extent of the intermediary portion **130**. The anti-rotation elements **132** are preferably spaced apart, i.e. discontinuous from one another, to prevent rotation around a circumferential extent of the concave inner fixation surface **114**. Here, preferably each anti-rotation element **132** may be elongate and may have at least one rounded edge. Each of the anti-rotation elements **132** may have the form of a discontinuous semi-toroidal indentation. This toroidal indentation is such that a radial profile of the anti-rotation element **132** may be a circular or semi-circular.

(11) Additionally, whilst described as being circumferentially aligned elongate indentations, recesses or grooves, it is appreciated that anti-rotation elements may take other forms, for example each anti-rotation element may be a circular recess or may be a projection. Furthermore, at least one of the anti-rotation elements may include a multipart indentation having a plurality of anti-rotation zones and each anti-rotation zone may be demarcated from the other anti-rotation zones by discontinuities in depth of the indentation at their respective boundary. Each anti-rotation element may have a central anti-rotation zone and a plurality of non-central anti-rotation zones adjacent to the central anti-rotation zone. Although described and shown as being positioned in the intermediary portion, it is appreciated that the anti-rotation elements may in fact be positioned elsewhere on concave inner fixation surface, for example on the inner-land area **128**. It is also appreciated that the ceramic femoral resurfacing head prosthesis may not necessarily include a or any anti-rotation elements.

(12) The concave inner fixation surface **114** may further comprise a skirt **134** positioned between the rim **116** and the inner-land **128**, and more specifically between the rim **116** and the intermediary portion **130**. The skirt **134** is preferably annular in shape and an axial extent of the annular shaped skirt **134** may extend parallel or substantially parallel to a longitudinal extent of the ceramic stem **120**. Whilst described as extending parallel to the ceramic stem **120**, it is appreciated that the axial extent of the skirt **134** may in fact extend at an angle and towards the stem and as such the skirt **134** may be considered to taper or narrow in diameter towards the rim **116**. Alternatively, the axial extent of the skirt **134** may in fact extend at an angle and away from the stem such that the skirt **134** may be considered to widen in diameter towards the rim **116**. The skirt **134** is preferably cylindrical or substantially cylindrical, or frusto-conical or substantially frusto-conical.

(13) The skirt **134** may preferably further comprise at least one circumferentially elongate recess **136** or groove in the concave inner fixation surface **114**, preferably extending around a circumferential extent of the concave inner fixation surface **114** and/or skirt **134**. The elongate recess **136** may be an endless channel, although it is appreciated that the recess may not be endless and may only extend around a portion of the extent of concave inner fixation surface. Additionally, there may be a plurality of circumferentially aligned and substantially coplanar elongate recesses **136** positioned in the skirt **134** which individually extend around a portion of the circumference of the skirt **134**.

(14) The merging and/or transition of the base portion **122** of the ceramic stem **120** with or to the inner-land **128** of the concave inner fixation surface **114** is preferably at least a two-part angular transition **138**. Each part of the at least two-part angular transition **138** preferably has a different radius or radius of curvature such that a radial extent of the at least two-part angular transition is unbisectable. The radius of curvature of each curved part is therefore different. The curved parts are not symmetrical about a plane which separates adjacent said curved parts. One or more of the curved parts may also not be symmetrical about a line which bisects the said curved part. The unbisectability of the radial extent of the at least two-part angular transition **138** is shown by sectioning line B1 in FIG. 9, which does not bisect the two-part angular transition **138**. By contrast

the bisectability of the radial extent of the single angular transition **38** of the prior art is shown by bisection line B2 in FIG. 4.

(15) Therefore, the at least two-part angular transition **138** preferably defines a curve in an axial or longitudinal direction or extent of the stem **120** having a non-uniform radius. Most preferably, as shown in FIG. 9, the at least two-part angular transition **138** is a three-part angular transition **140**. The two- or three-part transition **138**, **140** preferably extends uniformly around the circumferential extent of the base portion **122** of the ceramic stem **120**. This is such that the base portion **122** of the stem **120** may be considered to be hyperbolic frustocone or a frustocone having a nonuniform pitch, with the wider base of the frustocone being adjacent to the inner-land **128**. A direct comparison between the transition of the present invention and the transition **38** of the prior art can be seen in FIG. 10. The transition in accordance with the state of the art is also shown in FIGS. 3 and 4.

(16) The three-part angular transition **140** preferably firstly comprises a first curved part **142**. The first curved part **142** is an axial extent of the base portion **122** of the stem **120** being at or adjacent to the cylindrical body portion **124** having a constant, uniform or regular radius of curvature, referenced at R1 in FIG. 10. The curvature of R1 is preferably such that it curves away from an axial direction of the stem **120**. The radius of curvature R1 is preferably in the range of 5 mm to 150 mm and more preferably may be at, around or substantially 50 mm. Although being described as having a constant, uniform or regular radius of curvature, it is appreciated that the first curved part may be flat, and thus have an undefinable radius of curvature, in an axial or longitudinal extent of the stem, or may be irregularly or non-uniformly curved. In the instance of being flat, an axial cross-section of the first curved part may be considered to be straight. Whilst the radius of curvature of the first part is given as preferably having an upper limit, it is appreciated that the radius of curvature may in fact only preferably be greater than 5 mm.

(17) The three-part angular transition **140** further comprises a second curved part **144**. The second curved part **142** is on an axial extent of the base portion **122** of the stem **120** being adjacent to and contiguous with the first curved part **142** and is distal to the cylindrical body portion **124** as compared to the first curved part **142**, having a radius of curvature referenced R2 in FIG. 10. The radius of curvature of the second curved part **144** may preferably be in the range of 10 mm to 100 mm, may more preferably be in the range of 10 mm to 25 mm, may most preferably be in the range of 15 mm to 20 mm, and may be at, around or substantially 17.5 mm. Although, the second curved part **144** is described as being a curve having a radius of curvature of the above values, it is appreciated that the curve may in fact be a catenary curve thus having no singular radius of curvature. Alternatively, the second curved part may in fact be flat in an axial or longitudinal extent of the stem, and thus have an undefinable radius of curvature in an axial or longitudinal extent of the stem. In this instance, an axial cross-section of the second curved part may be considered to be straight. Lastly the second curved part may have parabolic character or have any irregular or non-uniform curvature. Whilst the radius of curvature of the second part is given as preferably having an upper limit, it is appreciated that the radius of curvature may in fact only preferably be greater than 10 mm.

(18) The three-part angular transition **140** lastly comprises a third curved part **146**, having a radius of curvature labelled R3. The third curved part **146** is on an axial extent of the base portion **122** of the stem **120** being inter-positioned between and at or adjacent to both of the inner-land **128** portion and second curved part **144**. The third curved part **146** may preferably have a constant, uniform or regular radius of curvature R3. The radius of curvature R3 of the third curved part **146** may preferably in the range of 0.5 mm to 2 mm, and more preferably may be at, around or substantially 1.5 mm. Although being described as having a constant, uniform or regular radius of curvature, it is appreciated that the third curved part may be flat, and thus have an undefinable radius of curvature in an axial or longitudinal extent of the stem or may be irregularly or non-uniformly curved. In the instance of the third curved part being flat, an axial cross-section of the third curved part may be

considered to be straight. Whilst the radius of curvature of the third part is given as preferably having an upper limit, it is appreciated that the radius of curvature may in fact only preferably be greater than 0.5 mm.

(19) Whilst the at least two-part angular transition **138** is described as having three angular transitions, with the first and second curved parts **142**, **144** being contiguous with each other and the second and third parts **144**, **146** being contiguous with each other, it is appreciated that it may in fact only have two angular transitions or may have more than three angular transitions. Whilst the above values for the radius of curvatures of the curved part are specified, it should be noted that the advantage provided by the at least two-part angular transition **138** is given by having at least two contiguous curved parts; a curved part adjacent to the stem and a curved part adjacent to the inner-land **128**, the curved part adjacent to the inner-land **128** having a tighter or smaller radius of curvature than the radius of curvature of the curved part adjacent to the stem. The above values of radius of curvature **R1**, **R2**, **R3** may vary and/or scale depending on the dimensions of the other features of the ceramic femoral resurfacing head prosthesis **110**, particularly a diameter of the ceramic outer contact surface **112**. Alternatively, the above values may not vary and/or scale depending on the dimensions of the ceramic of the other features of the ceramic femoral resurfacing head prosthesis **110**.

(20) It is appreciated that the transition may in fact not extend uniformly around the circumferential extent of the base and the number of curved parts or radius of curvature of each part of the transition may vary depending on its circumferential position. It is further noted that the ceramic femoral resurfacing head prosthesis **110** may in fact have a singular angular transition, for example, the curved part **38** in the state of the art having a radius of curvature of 2.5 mm and indicated by **R4** in FIG. **10**.

(21) The three-part angular transition **140** is so arranged to maximise the surface area of the inner-land **128**, by decreasing the lateral extent over which the transition **140** extends, whilst maintaining, improving, or restricting or limiting a degradation of in use stress characteristics, such as stress concentration, adjacent to the base **124** of the ceramic stem **120** as compared to the prior art. This is achieved by having a third curved part **146** with a smaller radius of curvature than the radius of curvature **R4** of the prior art, allowing the transition or merging between the stem **120** and the inner-land **128** to occur more proximal to the stem **120**. Any negative affect to the stress characteristics by this tighter radius of curvature is mitigated by having second and/or first curved parts **142**, **144** having a radius of curvature greater than the prior art and greater than the third curved part **146** which reduces stress concentration. This increase of inner-land **128** whilst maintenance of suitable stress characteristics is demonstrated by a comparison of FIGS. **4** and **9**. The lateral extent of the transition **140** between the stem **120** and the inner-land **128** is indicated in FIG. **10** by **X1** for the present invention and **X2** in the prior art. Given that **X1** is smaller than **X2**, the inner-land **128** can be shown to be extended and increased in area in the present invention as compared to the prior art.

(22) The rim **116** preferably has an asymmetrical profile, the asymmetric profile may be considered to be a lateral profile of the rim **116**. The asymmetrical profile of the rim **116**, and a comparison to the symmetrical rim **116** of the prior art, may be seen in FIGS. **12** to **14**.

(23) The rim **116** here has an inner, or internal, edge **148** and an outer, or external, edge **150**, both edges **148**, **150** preferably extending around a circumferential extent of the rim **116** and thus the ceramic femoral resurfacing head prosthesis **110**. The outer edge **150** may be proximal to the ceramic convex outer contact surface **112** and the inner edge **148** may be proximal to the concave inner fixation surface **114**. Both the inner edge **148**, and the outer edge **150** may be considered to be curved or substantially curved, the inner edge **148** having a radius of curvature labelled **R5** in FIG. **14** and similarly **R6** for the outer edge **150**. The radius of curvature of the inner edge **148** is preferably smaller than the radius of curvature of the outer edge **150**. The radius of curvature of the inner edge **148** may preferably be in a range of 0.2 mm and 1.5 mm and may more preferably be at,

around or substantially 0.5 mm. The radius of curvature of the outer edge **150** is preferably in the range of 0.5 mm and 2 mm, and more preferably being at, around or substantially 1 mm. Whilst the above values are specified, it should be appreciated that the radius of curvature may vary depending on the overall size of the ceramic femoral resurfacing head prosthesis **110** and that the importance of this part of the present invention is that the radius of curvature of the outer edge **150** is greater than the radius of curvature of the inner edge **148**. A substantially flat or planar portion may interspace the inner and outer edges **148**, **150**.

(24) The effect of the lateral profile of the rim **116** being asymmetrical is that the rim **116** may be thickened, when compared to the prior art, by the axial extent of the ceramic femoral resurfacing head prosthesis **110** being reduced, but the concave inner fixation surface **114** may still be maximised. The smaller inner radius of curvature R5 maximises the concave inner fixation surface **114** by reducing the axial extent of the transition between the inner surface **114** and the distal surface of the rim **116**. The larger outer radius of curvature R6 reduces stress concentration and therefore reduces the risk of fracture or failure of part of this component, when compared to a smaller or typical radius of curvature. The contrasting symmetrical profile, and therefore equal radius of curvature for both the inner and outer edge **48**, **58** of the rim **16** in the prior art can be seen in FIG. 5 where the radius of curvature of both edges is labelled as R7. This radius of curvature can also be seen in FIGS. 12 and 13 where the profiles of both rims **16**, **116** are shown overlain. The increase in width of the rim **116** of the present invention over the prior art is illustrated in FIG. 13 by a comparison of W1, a width of the rim of the present invention, with W2, a width of the rim of the prior art.

(25) Whilst the profile of the rim **116** of the ceramic femoral resurfacing head prosthesis **110** is here described as being asymmetrical, it is appreciated that it may in fact be symmetrical, for example similar to or the same as the profile of the rim **16** in the prior art.

(26) The ceramic femoral resurfacing head prosthesis **110** may preferably be wholly made from ceramic; however, it is appreciated that ceramic femoral resurfacing head prosthesis may only partly be made from ceramic and that selected components, such as the stem **120**, may not be made from ceramic. The ceramic selected for use in the ceramic femoral resurfacing head prosthesis **110** may preferably be inert to the human body and should have a high hardness to reduce wear. Ceramics suitable for use may in particular be zirconia toughened alumina but also alumina, zirconia, activated alumina, bioglass, silicon nitride, zirconia or any other ceramic.

(27) Whilst the rim **116** is here described as forming a plane it is appreciated that the rim **116** may not be substantially planar and may undulate, for example having the form of a wave or having a sinusoidal or substantially sinusoidal circumferential extent. In the event that the rim **116** is not planar, a plane defined by the rim **116** may be taken to be the extent of the rim **116** furthest from, closest to or at a mean distance of the rim from the inner-land portion **120**. Additionally or alternatively, whilst the plane defined by the rim **116** is shown as being perpendicular to the longitudinal extent of the ceramic stem **120**, it is appreciated that the rim may not be perpendicular to the longitudinal extent of the ceramic stem **120**. For example, the plane defined by the rim may be at an angle to the ceramic stem **120**, due to an asymmetrical longitudinal extent of the skirt **134**.

(28) Referring to FIGS. 15a to 15c, there are shown variations of the first embodiment of the ceramic femoral resurfacing head prosthesis **110** together forming a first group **152** of ceramic femoral resurfacing head prostheses **110**. Referring to FIGS. 16a to 16c, there are shown variations of the first embodiment of the ceramic femoral resurfacing head prosthesis **110** together forming a second group **154** of ceramic femoral resurfacing head prostheses **110**. Although only first and second groups **152**, **154** are described, it will be clear that more than two groups having the characteristics outlined hereinafter can be provided, where necessity dictates.

(29) Each prosthesis variation of the first embodiment may be at least in part distinguished by a differing equatorial diameter of the convex outer contact surface **112** for each ceramic femoral resurfacing head prosthesis **110**. The equatorial diameter of the convex outer contact surface **112** in

mm for each variation of first embodiment is given below each figure as a size. For example, “Size 40” refers to an equatorial diameter of substantially 40 mm. These variants on the present invention are the same as the preceding embodiment with the exception that the dimensions of the stem as compared to the ceramic convex outer contact surface **112** may differ. Elements which are similar or identical to those of the preceding embodiment are denoted by the same reference number with i to vi added to denote a variation, and further detailed description is omitted.

(30) Across the first group **152**, a lateral extent of the ceramic stem **120i** may be constant, common or uniform or substantially constant, common or uniform along at least a majority of a longitudinal extent of the stem. Given that the lateral extent of each stem **120i** may not be constant along an entire longitudinal extent thereof, due at least to the tapering at the distal free end portion **126i** and the at least two-part angular transition **138i** of the base portion **122i**, the said lateral extent which is constant across the group may be taken from a same or similar longitudinal reference point for each ceramic stem **120i** of a first group **152**.

(31) The longitudinal reference point may, for example, be within a longitudinal extent of the body portion **124i**, the body portion of each ceramic stem preferably having a constant or substantially constant lateral extent therealong. Alternatively, the longitudinal reference point may be taken to be at the base of the ceramic stem **120i** or between the inner-land **128i** and the body portion **124i**.

(32) The constant or substantially constant lateral extent of each ceramic stem **120i** within the first group **152** may at least be along part of the longitudinal extent of each ceramic stem **120i** and may preferably be constant or substantially constant along a majority of each ceramic stem **120i** of a group. Whilst a lateral extent of each ceramic stem **120i** is constant, a longitudinal extent of each stem **120i** may vary across the group **152**. This varying longitudinal extent may be achieved by varying only the longitudinal extent of the body portion **124i** of each stem **120i**, in this way a longitudinal and lateral extent of the base portion **122i** and the distal free end portion **126i** of each stem within the group **152** may be constant or common. Alternatively, the length of the ceramic stem may be varied by also or only varying the longitudinal extent of the base portion **122i**, including the at least two-part angular transition **138i**, and/or the distal free end portion **126i**. Given the non-constant lateral extent of the base portion **122i** or distal free end portion **126i**, by varying their longitudinal extent the lateral extent of the ceramic stem **120i** may vary at these portions and thus the lateral extent of each ceramic stem **120i** within a group may not be constant along the entirety of the longitudinal extent of the stem **120i**. In the event that a lateral cross-section of the ceramic stem **120i** is not circular, the major or largest lateral dimension of the lateral extent should be constant, common or uniform across a group, in the same or similar way as described above.

(33) The at least two-part angular transition **138i** may be the same for each ceramic stem **120i** of each ceramic femoral resurfacing head prosthesis **110i** within the first group **152**. Alternatively, the at least two-part angular transition **138i** may be different for each ceramic stem **120i** of each ceramic femoral resurfacing head prosthesis **110i** within the first group **152**. This difference may be due to differing radii of curvature for each or any of the curved parts of the two-part angular transition **138** across each femoral resurfacing head prosthesis **110i** of the first group **152**.

(34) Although the longitudinal extent of each ceramic stem **120i** is described as varying across a first group **152**, it is appreciated that the longitudinal extent of each ceramic stem **120i** may also remain constant, common or uniform or substantially constant, common or uniform.

(35) The lateral extent of the ceramic stem **120i** may be in the range of 5 mm to 7.5 mm, and more preferably may be at, around or substantially 6.6 mm. The lateral extent of the first group **152** may be given by $\varnothing X$ in FIGS. **15a** to **15c**. The dimensions of the remainder of the features of each of the femoral resurfacing head prosthesis may vary, especially the ceramic convex outer contact surface **112i**, the concave inner fixation surface **114i** and even a length of the stem. As such, each ceramic femoral resurfacing head prosthesis **110i** may have a different equatorial circumference to that of the other ceramic femoral resurfacing head prostheses **110i** of the first group **152**. Therefore, the ceramic stems of all of the ceramic femoral resurfacing head prostheses **110i** of a first group

152 may be individually selectively co-operable with a given, and the same, stem bore, also known as the femoral bore.

(36) In the same or similar way as above, within the second group **154**, the lateral extent of the ceramic stem **120iv** may be constant, common or uniform or substantially constant, common or uniform along at least part of the longitudinal extent of the ceramic stem. Within the second group **154**, the said constant lateral extent may be taken at the same or similar longitudinal reference point as above. In the same or similar way as above, the longitudinal extent of each of the ceramic stems **120iv** within the group **154** may vary or, alternatively, may not vary. Here the lateral extent of ceramic stem **120iv** may be in the range of 7 mm to 9 mm, and more preferably may be at, around or substantially 8.1 mm and therefore may be generally greater than the lateral extent of the ceramic stem **120i** of the first group **152**. The lateral extent of the second group **154** is given by $\varnothing Y$ in FIGS. **16a** to **16c**. The dimensions of the remainder of the features of each of the femoral resurfacing head prosthesis may vary, especially the convex outer contact surface. The dimensions of said features of the second group **154**, including the longitudinal extent of the stem **120iv**, may also vary with respect to the dimensions of the said features of the first group **152**. As such, each ceramic femoral resurfacing head prosthesis **110iv** may have a different equatorial circumference and/or a different longitudinal extent of the stem, to that of the other ceramic femoral resurfacing head prosthesis **110iv** of a second group **154** and of the first group **152**.

(37) The at least two-part angular transition **138i** of the ceramic stem **120i** of the first group **152** may be the same or similar to the at least two-part angular transition **138iv** of the ceramic stem **120iv** of the second group **154**. Alternatively, the at least two-part angular transition **138i** of the ceramic stem **120i** of the first group **152** may be different to the at least two-part angular transition **138iv** of the ceramic stem **120iv** of the second group **154**.

(38) However, the lateral extent of the ceramic stem **120iv** of the second group **154** is different to the ceramic stem **120i** of the first group **152**. Therefore, the ceramic stems of all of the ceramic femoral resurfacing head prostheses **110iv** of a second group **154** may be individually selectively co-operable with a given, and the same, stem or femoral bore, but may not be individually selectively co-operable with a stem or femoral bore suitable for use with the first group **152** and vice versa.

(39) Therefore, a range of prostheses having differing ceramic convex outer contact surfaces **112** and concave inner fixation surface **114**, but all being suitable for insertion into a stem bore or femoral bore of the same dimensions, and in particular the same lateral dimension, may be selectable.

(40) Whilst, as described, the only difference between the ceramic femoral resurfacing head prostheses **110** are the relative size of the lateral extent of the stem **120** compared to the other features, it is appreciated that within a group, for a given lateral extent of stem, there may be other variations. For example, there may be differing numbers of anti-rotation elements or no anti-rotation elements between the ceramic femoral resurfacing head prostheses of a group. Additionally, there may be more or different shaped or sized elongate recesses to promote adhesion to the head of the femur. Therefore, in use the surgeon may select from a group of femoral resurfacing head prostheses having a particular feature and having already prepared the stem bore during surgery.

(41) A surgical procedure may be performed to in use apply the ceramic femoral resurfacing head prosthesis **110** to a patient. This may take the form of making an incision in the patient, adjacent to the hip. The surgical approach may be most commonly made posterior to the hip, however lateral, anterior, anterior-lateral and medial approaches are also possible. The head portion of the femur and the acetabulum are then exposed and the head of the femur may be dislocated from the acetabulum.

(42) A ceramic femoral resurfacing head prosthesis **110** or femoral resurfacing head prosthesis group **152**, **154** may be selected based on the size of the femur head and the size of the acetabulum

or acetabular cup into which the femur is to be inserted. The head of the femur is then prepared and/or resected by shaping the femur so as to substantially correspond with the concave inner fixation surface **114** of the selected femoral resurfacing head prosthesis. This may involve removing an edge portion of the head of the femur using a chamfer-cutting tool.

(43) A stem bore may be drilled into a longitudinal extent of the femur, the diameter and length of the bore to be drilled corresponding to the dimensions of the stem **120** of the femoral resurfacing head prosthesis **110** or femoral resurfacing head prosthesis group **152**, **154** selected. If a group **152**, **154** of femoral resurfacing head prostheses **110** has been selected then a single femoral resurfacing head prosthesis **110** is selected from that group which corresponds most closely with the size of the acetabulum or acetabular cup into which the resurfaced femur head is to be inserted.

(44) Bone cement is then applied to the concave inner fixation surface **114** and/or the surface of the resected femur. The femoral resurfacing head prosthesis is then positioned over the resected femur and the ceramic stem **120** is inserted into the stem bore. The bone cement bonds or affixes the resected femur to the ceramic femoral head prosthesis. The optional anti-rotation elements **132** may be filled with cement and therefore prevent rotation of the femoral resurfacing head prosthesis. Similarly, the elongate recess **136** may also be filled with cement and thereby promote surgical bone cement interdigitation to prevent or inhibit pull-off removal of the head prosthesis **110**. The resurfaced ceramic femoral head may then be inserted or impacted into the acetabulum or acetabular cup.

(45) The acetabulum is then typically prepared to receive an in use acetabular cup by removing cartilage from and otherwise enlarging the acetabulum with a reamer. An in use acetabular cup, selected to correspond to the ceramic convex outer contact surface, is then inserted or impacted into the enlarged acetabulum and may be secured by using an adhesive such as bone cement.

(46) The area around the hip may then be cleaned to remove any excess bone or cement, and the incision may be sealed.

(47) It is appreciated that the above procedure may be performed in a reverse sequence and the above sequence of events is given for illustrative purposes only. For example, the procedure may clearly also be performed by first preparing the acetabulum or acetabular cup and then resurfacing the femoral head.

(48) It is therefore possible to provide a ceramic femoral head prosthesis which, through a two- or more-part angular transition of the stem to increase an inner-land for improved bone engagement and support, has at least comparable stress characteristics at or adjacent to a base of the stem compared to presently known non-ceramic femoral head prostheses.

(49) Furthermore, it is also possible to provide a ceramic femoral head prosthesis with a more robust rim to prevent or limit fracture, chipping or breakage, thereby significantly improving longevity.

(50) Additionally, it is possible to provide a ceramic femoral head prosthesis with an internal profile that improves engagement of the prosthesis with the femur through surgical bone cement interdigitation, thereby reducing a likelihood of the prosthesis unseating during patient use.

(51) These features may be present in the ceramic femoral head prosthesis either individually or in any combination.

(52) It is also possible to provide a system of two or more groups of selectable ceramic femoral head prostheses having different outer surface characteristics. By each group having a common ceramic stem dimension, profile or stem diameter, a number of tools required to fit the selected prosthesis may be reduced.

(53) The words ‘comprises/comprising’ and the words ‘having/including’ when used herein with reference to the present invention are used to specify the presence of stated features, integers, steps or components, but do not preclude the presence or addition of one or more other features, integers, steps, components or groups thereof.

(54) It is appreciated that certain features of the invention, which are, for clarity, described in the

context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the invention which are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable sub-combination.

(55) The embodiments described above are provided by way of examples only, and various other modifications will be apparent to persons skilled in the field without departing from the scope of the invention as defined herein.

Claims

1. A ceramic femoral resurfacing head prosthesis comprising: a ceramic convex outer contact surface adapted to engage with at least any one of an acetabulum of a patient and an acetabular cup prosthesis; a concave inner fixation surface, the outer contact surface and the inner fixation surface configured to extend to intersect each other at a rim; a bone-fixation surface comprising a ceramic stem configured to project from an inner-land portion of the inner fixation surface and adapted to be received by a stem bore; wherein the concave inner fixation surface comprises an intermediary portion which extends at an obtuse angle relative to the inner-land portion and a skirt between the intermediary portion and the rim; wherein a free distal end of the stem is any one of at and spaced inwardly of, a plane defined by the said rim, wherein the intermediary portion includes at least one circumferentially elongate recess configured to any one of prevent and inhibit pull-off removal of the head prosthesis; and wherein the stem is the sole projection of the inner fixation surface.
2. The ceramic femoral resurfacing head prosthesis as claimed in claim 1, wherein the concave inner fixation surface has a plurality of anti-rotation elements spaced around a circumference thereof.
3. The ceramic femoral resurfacing head prosthesis as claimed in claim 1, wherein the ceramic stem includes at least a two-part angular transition in a longitudinal direction of the stem to meet the inner fixation surface such that an inner-land portion of the inner fixation surface adjacent to the stem is increased.
4. The ceramic femoral resurfacing head prosthesis as claimed in claim 3, wherein the at least two-part angular transition defines a curve in a longitudinal direction of the stem having a non-uniform radius.
5. The ceramic femoral resurfacing head prosthesis as claimed in claim 4, wherein the at least two-part angular transition includes a first curved part having a radius in a range of 5 mm to 15 mm, a second curved part having a radius in a range of 2 mm to 5 mm, and a third curved part having a radius in a range of 0.5 mm to 2 mm.
6. The ceramic femoral resurfacing head prosthesis as claimed in claim 5, wherein the first curved part has a radius of or substantially of 10 mm, the second curved part has a radius of or substantially of 2.5 mm, and the third curved part has a radius of or substantially of 1.5 mm.
7. The ceramic femoral resurfacing head prosthesis as claimed in claim 5, wherein the first and second curved parts and the second and third curved parts are contiguous with each other.
8. The ceramic femoral resurfacing head prosthesis as claimed in claim 3, wherein the at least two-part angular transition includes at least one flat in a longitudinal direction of the stem.
9. The ceramic femoral resurfacing head prosthesis as claimed in claim 3, wherein the at least two-part angular transition is or includes a catenary curve.
10. The ceramic femoral resurfacing head prosthesis as claimed in claim 1, wherein lateral and longitudinal axes of the said elongate recess are curved.
11. The ceramic femoral surfacing head prosthesis as claimed in claim 1, wherein the circumferentially elongate recess is an endless channel.
12. The ceramic femoral surfacing head prosthesis as claimed in claim 1, wherein the inner fixation surface includes a skirt between the inner-land portion and the rim of the head prosthesis, the circumferentially elongate recess being at the skirt.

13. The ceramic femoral resurfacing head prosthesis as claimed in claim 1, wherein the rim of the ceramic femoral resurfacing head prosthesis defines an asymmetrical profile between the inner fixation surface and the outer contact surface with two or more different arcs having a radius in a range of 0.2 mm to 1.5 mm.

14. The ceramic femoral resurfacing head prosthesis as claimed in claim 1, wherein the concave inner fixation surface is ceramic.

15. The ceramic femoral resurfacing head prosthesis as claimed in claim 1, wherein the concave inner fixation surface is multi-faceted.

16. The ceramic femoral surfacing head prosthesis as claimed in claim 1, wherein the rim is any one of planar and substantially planar.
