

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398822
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Ejima; Takahiro et al.

Valve

Abstract

There is provided a valve capable of reducing valve leakage. The valve includes: a valve housing in which ports through which a fluid passes are formed; a valve body configured to be driven by a drive source; a valve seat on which a contact portion of the valve body is seated; and biasing members for biasing the valve body in a valve closing direction. The valve seat is formed of an elastic member.

Inventors:	Ejima; Takahiro (Tokyo, JP), Furukawa; Kenshiro (Tokyo, JP), Fukudome; Kohei (Tokyo, JP), Shirafuji; Keigo (Tokyo, JP)
Applicant:	EAGLE INDUSTRY CO., LTD. (Tokyo, JP)
Family ID:	1000008782663
Assignee:	EAGLE INDUSTRY CO., LTD. (N/A, JP)
Appl. No.:	18/267072
Filed (or PCT Filed):	December 06, 2021
PCT No.:	PCT/JP2021/044726
PCT Pub. No.:	WO2022/131053
PCT Pub. Date:	June 23, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240011574 A1	Jan. 11, 2024

Foreign Application Priority Data

JP	2020-209652	Dec. 17, 2020
----	-------------	---------------

Publication Classification

Int. Cl.: **F16K31/06** (20060101); **F16K1/46** (20060101); B60H1/00 (20060101); F04B27/18 (20060101); F25B41/345 (20210101)

U.S. Cl.:

CPC **F16K31/0655** (20130101); **F16K1/46** (20130101); B60H1/00485 (20130101); F04B27/1804 (20130101); F16K31/0613 (20130101); F25B41/345 (20210101)

Field of Classification Search

CPC: F16K (1/46); F16K (31/0655); F16K (1/34); F16K (31/0613); F16K (5/207); F16K (17/087); F16K (31/126); F04B (2027/1818); F04B (2027/1831); F04B (2027/1859); F04B (27/1804); F04B (2027/1822-1881); B60H (1/00485); F25B (41/345)

USPC: 137/625.65; 417/222.2; 251/359-363; 251/129.15

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
813555	12/1905	Hayden	N/A	F16K 1/34
821758	12/1905	Smith	N/A	F16K 1/46
877865	12/1907	Ricksecker	N/A	F16K 1/34
1170412	12/1915	Campbell	251/359	F16K 15/20
1449876	12/1922	Erastus	N/A	F01L 3/20
1614002	12/1926	Horton	N/A	A62C 36/605
1758471	12/1929	Julius	N/A	F16K 1/46
1797036	12/1930	Wolf	251/359	F16K 15/20
1800127	12/1930	Wilson	N/A	F16K 1/34
1847385	12/1931	Franklin	N/A	F16K 1/34
2196798	12/1939	Otto	N/A	F16K 1/36
2267515	12/1940	Wilcox	N/A	F16K 31/0627
2331503	12/1942	Ray	N/A	F16K 41/10
2543010	12/1950	Gardner	315/108	F16K 31/0655
2797061	12/1956	Buchanan	N/A	F16K 31/06
2887293	12/1958	Fred	N/A	F16K 31/60
2893685	12/1958	Camp	N/A	F16K 1/36
2898082	12/1958	Von Almen	N/A	F04B 53/1027
3049332	12/1961	Webster	N/A	F16K 1/02
3054422	12/1961	Napolitano	N/A	F16K 1/385
3070120	12/1961	Wendt	N/A	F16K 1/46
3185438	12/1964	Smirra	N/A	F16K 1/34
3204925	12/1964	Enrico	N/A	F16K 1/50

3230973	12/1965	Rudolf	N/A	F16K 1/46
3278156	12/1965	Callahan	N/A	F16K 41/10
3360304	12/1966	Adams	N/A	B61K 7/12
3394732	12/1967	Constantine	N/A	F16K 1/36
3426741	12/1968	Haagen	N/A	F01L 3/02
3483888	12/1968	Hugo	N/A	F16K 15/046
3623699	12/1970	Matousek	251/368	F16K 1/46
3627257	12/1970	Stamfil	N/A	F16K 31/0693
3679169	12/1971	Bedo	N/A	F16K 41/02
3854495	12/1973	Cowley	N/A	G05D 16/0663
4085921	12/1977	Ueda et al.	N/A	F16K 31/06
4149699	12/1978	Speckmann	N/A	F16K 41/00
4318532	12/1981	Winkler	N/A	F16K 1/34
4345739	12/1981	Wheatley	N/A	F16K 1/2263
4364615	12/1981	Euler	N/A	F16C 27/04
4417601	12/1982	Bennett	N/A	A62C 31/12
4448038	12/1983	Barbier	N/A	F25B 41/34
4474356	12/1983	Baumann	N/A	F16K 1/12
4579145	12/1985	Leiber	N/A	F16H 61/0251
4615358	12/1985	Hammond	N/A	F15B 13/0402
4617889	12/1985	Nishimiya	N/A	F02D 31/00
4632358	12/1985	Orth	N/A	F25B 41/347
4669272	12/1986	Kawai	417/270	F04B 49/225
4687419	12/1986	Suzuki	417/270	F04B 27/1804
4778150	12/1987	Pratt	N/A	F16K 41/043
4813647	12/1988	Yagi	251/129.05	F02M 3/075
4825909	12/1988	Martin	N/A	F15B 13/02
4848729	12/1988	Danzy	N/A	F16K 1/46
4895192	12/1989	Mortenson	N/A	F01M 11/04
4915355	12/1989	Fort	N/A	F16K 1/46
4917150	12/1989	Koch	N/A	F16K 31/0606
4921208	12/1989	LaMarca	N/A	F16K 31/0693
4922957	12/1989	Johnson	N/A	F16K 1/46
4923173	12/1989	Szymaszek	N/A	F16K 1/36

4936337	12/1989	DuHack	137/329.04	F16K 31/408
4979542	12/1989	Mesenich	N/A	F02M 47/027
4998559	12/1990	McAuliffe	N/A	F16H 61/0251
5011116	12/1990	Alberts	N/A	F16K 47/00
5060695	12/1990	McCabe	N/A	G05D 16/2024
5217047	12/1992	McCabe	N/A	F16H 16/0251
5232195	12/1992	Torrielli	N/A	H01F 7/1607
5246205	12/1992	Gillingham	N/A	F01N 3/0212
5263694	12/1992	Smith	N/A	B60G 15/068
5364066	12/1993	Dorste	N/A	F25B 41/35
5409036	12/1994	Ahmadian	137/625.65	H01F 7/14
5439027	12/1994	Layton	N/A	F16K 1/385
5702235	12/1996	Hirota	N/A	F04B 27/1804
5778932	12/1997	Alexander	N/A	G05D 16/2024
5797730	12/1997	Kawaguchi	417/295	F04B 49/225
5810030	12/1997	Uchiyama	251/129.07	F16K 31/0655
5897096	12/1998	Nakano	251/65	F16K 41/103
6010312	12/1999	Suitou	N/A	F04B 27/1804
6019118	12/1999	Voggenreiter et al.	N/A	F16K 51/02
6149398	12/1999	Fukanuma	184/6.17	F04B 27/1804
6155391	12/1999	Kashiwagi et al.	N/A	F16F 9/348
6161585	12/1999	Kolchinsky	N/A	F05D 16/2024
6257836	12/2000	Ota et al.	417/222.02	N/A
6280152	12/2000	Sugiura	417/269	F04B 27/0891
6315266	12/2000	Hirota	N/A	F16K 31/406
6321995	12/2000	Badovick	N/A	F25B 41/335
6361283	12/2001	Ota	N/A	F04B 27/1084
6443420	12/2001	Hettinger	N/A	F16K 31/02
6481976	12/2001	Kimura	N/A	F04B 27/1804

6517324	12/2002	Ota	62/228.5	F04B 27/1804
6626000	12/2002	Meyer	N/A	F25B 41/345
6772990	12/2003	Sasaki	62/228.3	F16K 31/0627
6776182	12/2003	Ishitoya	N/A	F16K 25/00
6811140	12/2003	Maini	N/A	F16K 1/46
6840504	12/2004	Hagiwara	N/A	F16K 1/36
6959718	12/2004	Kayahara	N/A	F16K 31/0655
7007917	12/2005	Choi	N/A	F16K 31/0655
7040595	12/2005	Hirota	N/A	F16K 31/02
7246787	12/2006	Kumar	251/282	F16K 31/0675
7481417	12/2008	Mayer	N/A	F16K 51/02
7533687	12/2008	Uemura	N/A	F16K 27/048
7562675	12/2008	Nomichi	137/625.48	F16K 1/443
7726949	12/2009	Taguchi	N/A	F04B 1/26
7758014	12/2009	Lancaster	N/A	F16K 1/04
7832653	12/2009	Yukimoto	N/A	F25B 41/39
7958908	12/2010	Cho et al.	N/A	F15B 13/044
7971797	12/2010	Habermann	N/A	F16K 31/002
8021124	12/2010	Umemura	N/A	F16K 27/048
8079827	12/2010	Iwa	N/A	F04B 27/1804
8128061	12/2011	Uemura	N/A	F04B 27/1804
8225818	12/2011	Stephens	N/A	F15B 13/0442
8328163	12/2011	Boesch	N/A	F16K 1/36
8387947	12/2012	Uemura	N/A	F04B 27/1804
8434518	12/2012	Okamoto	137/625.69	F16K 31/0655
8469337	12/2012	Hoeptner	N/A	F16K 1/36
8579257	12/2012	Taylor	N/A	F16K 1/46
8651826	12/2013	Futakuchi	N/A	F04B 27/1804
8684037	12/2013	Huynh	N/A	F15B 13/01
8757592	12/2013	Marica	N/A	F16K 31/00
8757988	12/2013	Fukudome	417/270	F04B 27/1804
9022346	12/2014	Najmolhoda	N/A	F16K 31/0613

9027598	12/2014	Schneider	N/A	F16K 31/0613
9132714	12/2014	Futakuchi	N/A	F04B 27/1804
9243733	12/2015	Lively	N/A	G05D 16/02
9297373	12/2015	Bagagli	N/A	F16K 15/026
9383021	12/2015	Kosmehl	N/A	F16K 1/36
9400027	12/2015	Imaizumi	N/A	F16F 1/32
9453518	12/2015	Schulz	N/A	F15B 13/043
9470337	12/2015	Roper	N/A	F16K 1/36
9581149	12/2016	Ota et al.	N/A	F04B 27/1804
9581150	12/2016	Ota et al.	N/A	F04B 18/04
9638082	12/2016	Fujita	N/A	F16K 25/00
9732874	12/2016	Saeki	N/A	F04B 27/1804
9874286	12/2017	Bagagli	N/A	F16K 15/12
10113539	12/2017	Sugamura	N/A	F04B 27/1804
10378657	12/2018	Lin	N/A	F16K 1/46
10519944	12/2018	Taguchi	N/A	F04B 27/1804
10557463	12/2019	Sugamura	N/A	F04B 27/1804
10690125	12/2019	Hayama	N/A	F04B 27/18
10784804	12/2019	Sasaki	N/A	H02P 25/022
10837431	12/2019	Tonegawa	N/A	F16K 31/0613
11085431	12/2020	Fukudome et al.	N/A	F16K 31/06
11092244	12/2020	Hu	N/A	F16K 1/36
11313475	12/2021	Lv	N/A	F25B 41/35
11415238	12/2021	Nakanishi	N/A	F16K 31/0655
11480166	12/2021	Hayama et al.	N/A	F04B 27/10
11519399	12/2021	Kurihara	N/A	F04B 53/1087
11536389	12/2021	Fukudome	N/A	F16K 31/0655
11542929	12/2022	Hayama	N/A	F04B 27/18
11542931	12/2022	Hayama	N/A	G05D 7/005
11555489	12/2022	Hayama	N/A	F04B 27/10
11603832	12/2022	Higashidozono	N/A	F16K 31/0624
12018663	12/2023	Kurihara	N/A	F16K 15/184

12025237	12/2023	Kurihara	N/A	F04B 27/1804
12031531	12/2023	Fukudome	N/A	F16K 31/0655
12196464	12/2024	Ejima	N/A	B60H 1/00485
12292130	12/2024	Ejima	N/A	F16K 27/048
2001/0003573	12/2000	Kimura et al.	417/222.2	N/A
2002/0134444	12/2001	Isobe	N/A	F16K 27/041
2003/0145615	12/2002	Sasaki	N/A	F16K 31/0637
2003/0197141	12/2002	Kajitani	N/A	F16L 47/00
2003/0202885	12/2002	Taguchi	N/A	F04B 49/00
2004/0045305	12/2003	Murase	N/A	F25B 49/022
2004/0165994	12/2003	Umemura	N/A	F04B 27/1804
2005/0076959	12/2004	Yamamoto	N/A	F16K 31/0624
2005/0151310	12/2004	Rodeffer	N/A	F16F 1/32
2005/0163624	12/2004	Taguchi	N/A	F04B 27/1804
2007/0214814	12/2006	Umemura et al.	N/A	N/A
2007/0264134	12/2006	Hirota	N/A	F04B 27/1804
2008/0138213	12/2007	Umemura et al.	417/222.2	N/A
2008/0175727	12/2007	Umemura et al.	N/A	F04B 49/22
2009/0108221	12/2008	Umemura et al.	251/129.15	N/A
2009/0114871	12/2008	Iwa	N/A	F04B 27/14
2009/0183786	12/2008	Iwa	137/487.5	N/A
2009/0256091	12/2008	Nordstrom	N/A	F16K 31/0613
2010/0051838	12/2009	Uemura	N/A	F04B 27/1804
2010/0252763	12/2009	Courth	N/A	F16K 31/0665
2010/0282991	12/2009	Okamoto	N/A	F16K 31/02
2011/0041941	12/2010	Sonsterod	N/A	F16K 15/14
2011/0061749	12/2010	Okamoto	137/492.5	F16K 31/0655
2011/0089352	12/2010	Morgan	N/A	F16K 11/0716
2011/0203888	12/2010	Sonsterod	N/A	F16F 9/32
2012/0056113	12/2011	Tano	N/A	F04B 27/1804
2012/0097881	12/2011	Aoyama	251/359	F16K 1/425
2012/0198992	12/2011	Futakuchi et al.	91/505	N/A
2012/0198993	12/2011	Fukudome	91/505	N/A

2012/0211686	12/2011	Okamoto	N/A	F16K 31/0655
2013/0291963	12/2012	Futakuchi et al.	137/487.5	N/A
2014/0099214	12/2013	Fukudome	417/222.2	N/A
2014/0109973	12/2013	Neumeister	N/A	C23C 16/4412
2014/0130916	12/2013	Saeki	N/A	F16K 31/0613
2014/0294632	12/2013	Kondo et al.	417/434	N/A
2014/0369862	12/2013	Ota et al.	N/A	F04B 27/1804
2015/0004010	12/2014	Saeki	N/A	F04B 27/1804
2015/0021131	12/2014	Wootten	N/A	F16F 9/348
2015/0027573	12/2014	Ochiai	N/A	F15B 14/0402
2015/0044067	12/2014	Ota et al.	N/A	F04B 27/1804
2015/0060708	12/2014	Glime, III	251/335.1	F16K 31/1225
2015/0068628	12/2014	Iwa	137/625.65	N/A
2015/0104334	12/2014	Ota et al.	N/A	F04B 27/1804
2015/0275874	12/2014	Ota	N/A	F04B 27/1804
2015/0276065	12/2014	Yoshida	N/A	F16K 3/246
2015/0345655	12/2014	Higashidozono	137/624.27	N/A
2016/0053755	12/2015	Taguchi	N/A	F04B 49/22
2016/0208954	12/2015	Ito et al.	N/A	F16K 39/02
2016/0290326	12/2015	Sugamura	N/A	F04B 27/1804
2017/0261113	12/2016	Sato	N/A	F16K 31/0675
2017/0284562	12/2016	Hayama	N/A	F16K 41/00
2018/0156345	12/2017	Kanda	N/A	F15B 13/0431
2018/0187793	12/2017	Futakuchi	N/A	F04B 39/08
2018/0238455	12/2017	Yazawa	N/A	F16K 31/508
2018/0291888	12/2017	Tonegawa et al.	N/A	F04B 49/22
2018/0372129	12/2017	Kato	N/A	F15B 13/0402
2019/0162175	12/2018	Higashidozono	N/A	F04B 27/18
2019/0293061	12/2018	Kume	N/A	F16K 11/048
2020/0011444	12/2019	Morita et al.	N/A	F16K 31/04
2020/0032781	12/2019	Higashidozono	N/A	F16K 31/0624
2020/0088178	12/2019	Fukudome et al.	N/A	F16K 31/06
2020/0173580	12/2019	Sandack	N/A	F16K 51/02

2020/0309105	12/2019	Hayama et al.	N/A	F04B 27/18
2020/0318624	12/2019	Hayama	N/A	F04B 27/18
2020/0325881	12/2019	Hayama et al.	N/A	F04B 27/18
2020/0332786	12/2019	Hayama	N/A	F04B 27/1804
2020/0362974	12/2019	Hayama et al.	N/A	F16K 11/24
2020/0370545	12/2019	Hayama et al.	N/A	F04B 27/18
2021/0372396	12/2020	Kurihara	N/A	G05D 7/0635
2021/0404570	12/2020	Hayama et al.	N/A	F16K 17/04
2022/0213878	12/2021	Fukudome et al.	N/A	F04B 27/18

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
104520155	12/2014	CN	B60T 8/36
107339442	12/2016	CN	F16K 1/02
209146387	12/2018	CN	F16K 31/42
110260001	12/2018	CN	F16K 15/016
110735965	12/2019	CN	F16K 1/00
111279076	12/2019	CN	F04B 27/18
111316028	12/2019	CN	F16K 31/06
111417780	12/2019	CN	F04B 27/18
2414893	12/1974	DE	F16K 15/00
2706439	12/1977	DE	F16K 11/04
10039066	12/2001	DE	F16K 31/06
102006033747	12/2007	DE	F16K 31/00
0229315	12/1986	EP	F02M 3/07
1519128	12/2004	EP	F25B 41/06
2180217	12/2009	EP	F16K 31/06
2594794	12/2012	EP	F04B 27/18
3056778	12/2015	EP	F16K 31/04
3258103	12/2016	EP	F04B 27/18
3296599	12/2017	EP	F16K 1/34
3366957	12/2017	EP	F16K 1/34
3726054	12/2019	EP	F04B 27/18
5682358	12/1980	JP	G03B 15/00
5740945	12/1981	JP	B21B 39/14
H04171361	12/1991	JP	F04B 49/00
5346276	12/1992	JP	F25B 41/96
626454	12/1993	JP	F04B 27/08
H0711313	12/1994	JP	F16K 1/34
H8159320	12/1995	JP	F16K 31/04
H09144931	12/1996	JP	F16K 31/06
H10220926	12/1997	JP	F25B 41/06
11287281	12/1998	JP	F16F 9/348
200020763	12/1999	JP	F16K 31/06
2000304152	12/1999	JP	F16D 48/02
2001012534	12/2000	JP	F16F 9/46
2001501290	12/2000	JP	F16K 31/06

2001153495	12/2000	JP	F16K 31/06
2001153498	12/2000	JP	F16K 31/06
2001165055	12/2000	JP	F04B 27/14
2001263527	12/2000	JP	F16K 31/06
2002216803	12/2001	JP	H01M 8/02
2003004160	12/2002	JP	F16K 31/04
2003301772	12/2002	JP	N/A
2003314745	12/2002	JP	F16K 51/02
2003322086	12/2002	JP	F04B 49/00
2004003468	12/2003	JP	F04B 27/14
2004101163	12/2003	JP	F25B 41/06
2005307817	12/2004	JP	F04B 27/14
2005351605	12/2004	JP	F16K 1/38
2006153204	12/2005	JP	F16K 31/04
2007247512	12/2006	JP	F04B 27/14
2008157031	12/2007	JP	F04B 27/14
2008190574	12/2007	JP	F16K 31/06
2009030752	12/2008	JP	F16K 31/06
2009115204	12/2008	JP	F16K 31/04
2009221965	12/2008	JP	F04B 27/14
2009257523	12/2008	JP	F16K 31/06
2009275550	12/2008	JP	F04B 49/00
2010019406	12/2009	JP	F16K 31/04
2011501798	12/2010	JP	F16K 15/14
2011525962	12/2010	JP	F16F 9/32
4822735	12/2010	JP	A43B 23/24
2012144986	12/2011	JP	F04B 27/14
2012211579	12/2011	JP	F04B 27/14
2013024135	12/2012	JP	F04B 27/14
5167121	12/2012	JP	F04B 27/14
2013100915	12/2012	JP	F15K 31/06
2013194918	12/2012	JP	F16K 1/36
2014080927	12/2013	JP	F04B 27/16
2014092207	12/2013	JP	F16K 31/06
2014095463	12/2013	JP	F16K 31/06
2015075054	12/2014	JP	F04B 27/14
20151168	12/2014	JP	F04B 27/14
2015137546	12/2014	JP	F04B 27/14
2015178795	12/2014	JP	F04B 27/14
5983539	12/2015	JP	F04B 27/18
2016196825	12/2015	JP	F04B 27/18
2016196876	12/2015	JP	F04B 27/18
2016205404	12/2015	JP	F04B 27/18
6135521	12/2016	JP	F04B 27/18
2017089832	12/2016	JP	F16K 31/06
2017180525	12/2016	JP	F16K 31/04
2017219060	12/2016	JP	F16K 37/00
2018015739	12/2017	JP	C02F 1/46
2018035840	12/2017	JP	N/A
2018115684	12/2017	JP	B60G 17/08

2018179087	12/2017	JP	F16K 31/06
2019002436	12/2018	JP	F16K 3/26
2019131725	12/2018	JP	N/A
2019138473	12/2018	JP	F16K 1/36
2019167982	12/2018	JP	F16K 1/38
2019183960	12/2018	JP	F16K 31/06
2020041606	12/2019	JP	F16K 1/44
2020060108	12/2019	JP	F04B 27/18
20-0400543	12/2004	KR	B60S 1/52
1020050107244	12/2004	KR	F16K 17/10
WO9218795	12/1991	WO	F16K 1/34
WO2006090760	12/2005	WO	F04B 27/18
WO2007119380	12/2006	WO	F04B 27/14
WO2009025298	12/2008	WO	F16K 31/06
WO2011114841	12/2010	WO	F04B 27/14
WO2011132438	12/2010	WO	F16K 31/06
WO2012077439	12/2011	WO	F04B 27/14
WO2014119594	12/2013	WO	F04B 27/14
WO2014148367	12/2013	WO	F16K 31/06
WO2018124156	12/2017	WO	F16K 31/06
WO2019131482	12/2018	WO	F04B 27/18
WO2020110925	12/2018	WO	F04B 27/18
WO2020013169	12/2019	WO	F04B 27/18
WO2020218284	12/2019	WO	F04B 27/18

OTHER PUBLICATIONS

Official Action issued in European related Application Serial No. 21853972.4, dated Jul. 24, 2024, 8 pages. cited by applicant

Official Action issued in European related Application Serial No. 21872539.8, dated Sep. 3, 2024, 5 pages. cited by applicant

Official Action issued in European related Application Serial No. 21875395.2, dated Sep. 13, 2024, 7. cited by applicant

Official Action issued in European related Application Serial No. 21853139.0, dated Mar. 22, 2024, 15 pages. cited by applicant

Official Action issued in European related Application Serial No. 21852577.2, dated Mar. 22, 2024, 9 pages. cited by applicant

Official Action issued in European related Application Serial No. 21853892.4, dated Mar. 22, 2024, 8 pages. cited by applicant

Official Action issued in European related Application Serial No. 21854468.2, dated Jul. 24, 2024, 7 pages. cited by applicant

Official Action issued in European related Application Social No. 01853073 2. dated Jul. 25, 2024, 7 pages. cited by applicant

Official Action issued in Korean related Application Serial No. 10-2023-7004906, dated Jun. 17, 2024, 10 pages with English Translation. cited by applicant

Official Action issued in Korean related Application Serial No. 10-2023-7004905, dated Jun. 17, 2024, 10 pages with English Translation. cited by applicant

Official Action issued in Korean related Application Serial No. 10-2023-7011145, dated Jun. 18, 2024, 6 pages with English Translation. cited by applicant

Official Action issued in Korean related Application Serial No. 10-2023-7004093, dated Jun. 17, 2024, 11 pages with English Translation. cited by applicant

Official Action issued in Korean related Application Serial No. 10-2023-7020969, dated Jun. 21, 2024, 8 pages with English Translation. cited by applicant

Official Action issued in related U.S. Appl. No. 18/019,230, dated Apr. 25, 2024, 11 pages. cited by applicant

Official Action issued in related U.S. Appl. No. 18/019,066, dated Apr. 24, 2024, 6 pages. cited by applicant

Official Action issued in related U.S. Appl. No. 18/029,065, dated Apr. 23, 2024, 14 pages. cited by applicant

Official Action issued in related U.S. Appl. No. 18/017,825, dated Apr. 15, 2024, 15 pages. cited by applicant

Official Action issued in related U.S. Appl. No. 18/017,824, dated Mar. 13, 2024, 19 pages. cited by applicant

Official Action issued in related U.S. Appl. No. 18/019,060, dated Apr. 26, 2024, 6 pages. cited by applicant

Official Action issued in related U.S. Appl. No. 18/029,065, dated Aug. 6, 2024, 10 pages. cited by applicant

Official Action issued in related U.S. Appl. No. 18/019,066, dated Sep. 5, 2024, 7 pages. cited by applicant

Official Action issued in related U.S. Appl. No. 18/019,060, dated Sep. 5, 2024, 7 pages. cited by applicant

Official Action issued in related U.S. Appl. No. 18/027,599, dated Jun. 13, 2024, 16 pages. cited by applicant

Notice of Allowance issued in related U.S. Appl. No. 18/022,465, dated Apr. 25, 2024, 7 pages. cited by applicant

International Search Report and Written Opinion and International Preliminary Report on Patentability issued in PCT/JP2022/012340, dated May 31, 2022, 24 pages. cited by applicant

International Search Report and Written Opinion and International Preliminary Report on Patentability issued in PCT/JP2021/027769, dated Sep. 7, 2021, 24 pages. cited by applicant

International Search Report and Written Opinion and International Preliminary Report on Patentability issued in PCT/JP2021/027762, dated Oct. 5, 2021, 20 pages. cited by applicant

International Search Report and Written Opinion and International Preliminary Report on Patentability issued in PCT/JP2021/027766, dated Sep. 7, 2021, 24 pages. cited by applicant

International Search Report and Written Opinion and International Preliminary Report on Patentability issued in PCT/JP2021/027770, dated Oct. 5, 2021, 20 pages. cited by applicant

International Search Report and Written Opinion and International Preliminary Report on Patentability issued in PCT/JP2021/027772, dated Sep. 21, 2021, 24 pages. cited by applicant

International Search Report and Written Opinion and International Preliminary Report on Patentability issued in PCT/JP2021/027767, dated Sep. 7, 2021, 22 pages. cited by applicant

International Search Report and Written Opinion and International Preliminary Report on Patentability issued in PCT/JP2021/030007, dated Nov. 2, 2021, 18 pages. cited by applicant

International Search Report and Written Opinion and International Preliminary Report on Patentability issued in PCT/JP2021/034996, dated Dec. 12, 2021, 18 pages. cited by applicant

International Search Report and Written Opinion and International Preliminary Report on Patentability issued in PCT/JP2021/034990, dated Oct. 19, 2021, 18 pages. cited by applicant

International Search Report and Written Opinion and International Preliminary Report on Patentability issued in PCT/JP2021/034995, dated Dec. 14, 2021, 16 pages. cited by applicant

International Search Report and Written Opinion and International Preliminary Report on Patentability issued in PCT/JP2021/044726, dated Dec. 28, 2021, 22 pages. cited by applicant

Search Report issued in European related Application Serial No. 21906416.9, dated Oct. 22, 2024, 8 pages. cited by applicant

Official Action issued in Japanese related Application Serial No. 2022-541458, dated Oct. 15, 2024, 6 pages with English Translation. cited by applicant
Official action issued in related U.S. Appl. No. 18/019,230, dated Oct. 15, 2024, 13 pages. cited by applicant
Official action issued in related U.S. Appl. No. 18/019,057, dated Sep. 27, 2024, 11 pages. cited by applicant

Primary Examiner: Price; Craig J

Attorney, Agent or Firm: HAYES SOLOWAY P.C.

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a valve that variably controls a working fluid, for example, to a valve that controls a discharge amount of a variable capacity compressor used for an air conditioning system of an automobile according to pressure.

BACKGROUND ART

(2) A variable capacity compressor used for an air conditioning system of an automobile, etc. includes a rotating shaft to be rotationally driven by an engine, a swash plate coupled to the rotating shaft in such a manner that a tilt angle is variable, compressing pistons coupled to the swash plate, etc., and by changing the tilt angle of the swash plate, changes a stroke amount of the pistons to control a discharge amount of fluid. This tilt angle of the swash plate can be continuously changed by appropriately controlling pressure in a control chamber while utilizing a suction pressure P_s of a suction chamber that suctions the fluid, a discharge pressure P_d of a discharge chamber that discharges the fluid pressurized by the pistons, and a control pressure P_c of the control chamber that houses the swash plate, by means of a capacity control valve as a valve that is driven to open and close by electromagnetic force of a solenoid as a drive source.

(3) At the time of continuously driving the variable capacity compressor, the capacity control valve performs normal control in which energization is controlled by a control computer, a valve body is moved in an axial direction by electromagnetic force generated in the solenoid, and a flow passage between a discharge port and a control port is opened and closed by a valve to adjust the control pressure P_c of the control chamber of the variable capacity compressor.

(4) In addition, there is a capacity control valve that controls a flow rate of the fluid flowing from the control port to a suction port. For example, in a capacity control valve disclosed in Patent Citation 1, in an open state of the valve in which the solenoid is energized, the fluid flows to the suction port through a through-flow passage communicating with the control port inside a housing. When the solenoid is de-energized from the open state, a valve body having a rod shape can be moved toward a valve seat by biasing force of a bellows to close the through-flow passage, the valve seat being formed in the valve housing. In such a manner, pressure in the control chamber of the variable capacity compressor is controlled using a pressure difference between the control pressure P_c and the suction pressure P_s lower than the control pressure P_c .

CITATION LIST

Patent Literature

(5) Patent Citation 1: WO 2020/218284 A (Pages 11 to 13, FIG. 4)

SUMMARY OF INVENTION

Technical Problem

(6) In the capacity control valve of Patent Citation 1, a contact portion having a tapered shape is

formed such that one end of the valve body is tapered, and comes into contact with and is seated on the valve seat formed on an inner peripheral surface of the valve housing, through a wide surface. However, operation in which the valve body returns toward the valve seat from an open state is due to biasing force of the bellows, and return force of the valve body that depends on biasing force of the bellows is small. For this reason, in a case where contaminations are caught between the contact portion of the valve body and the valve seat when the valve is closed, the contaminations are not completely crushed, and a gap occurs between the contact portion of the valve body and the valve seat and becomes a cause of valve leakage, which is a problem.

(7) The present invention is conceived in view of such a problem, and an object of the present invention is to provide a valve capable of reducing valve leakage.

Solution to Problem

(8) In order to solve the foregoing problem, a valve according to the present invention includes: a valve housing in which a port through which a fluid passes is formed; a valve body to be driven by a drive source; a valve seat on which a contact portion of the valve body is seated; and a biasing member configured to bias the valve body in a valve closing direction or the valve. At least one of the contact portion of the valve body and the valve seat is formed of an elastic member. According to the aforesaid feature of the present invention, when the valve is closed, even in a case where contaminations are caught between the contact portion of the valve body and the valve seat, the elastic member can be elastically deformed to suppress generation of a gap between the contact portion and the valve seat, so that valve leakage can be reduced.

(9) It may be preferable that the contact portion of the valve body or the valve seat that comes into contact with a contact surface of the elastic member is formed of an annular projection and the elastic member is formed to have a modulus of elasticity smaller than a modulus of elasticity of the annular projection. According to this preferable configuration, when the valve is closed, even in a case where contaminations are caught between the annular projection and the contact surface of the elastic member, the elastic member can be reliably and elastically deformed to suppress generation of a gap between the contact portion and the valve seat, so that valve leakage can be reduced.

(10) It may be preferable that the contact surface is a surface orthogonal to a driving direction of the valve body. According to this preferable configuration, when the valve is closed, since it is difficult for the annular projection to relatively move with respect to the contact surface of the elastic member, sealability is enhanced, and damage to the contact surface of the elastic member caused by the annular projection is suppressed, so that sealability can be maintained over a long period of time.

(11) It may be preferable that the valve body or the valve housing is provided with an annular recessed portion and the elastic member inserted into the annular recessed portion is crimped and fixed from at least one of radially inner and outer sides. According to this preferable configuration, the elastic member inserted into the annular recessed portion can be prevented from coming off.

(12) It may be preferable that the elastic member has a rectangular cross section. According to this preferable configuration, even when the annular projection comes into contact with the contact surface of the elastic member at any position, stable elasticity can be provided.

(13) It may be preferable that the valve body is separately configured to come into contact with and to separate from a rod forming the drive source and the rod is biased in a valve opening direction by a rod biasing member. According to this preferable configuration, since the rod is held so as to be able to come into contact with and to separate from the valve body in a state where the rod is biased in the valve opening direction, when the valve is closed, the valve body is not affected by an inertial force of the rod, so that an excessive load can be prevented from being applied to the contact portion or to the valve seat.

(14) It may be preferable that the biasing member is a compression spring. According to this preferable configuration, a structure on a drive source side of the valve is simplified, and the

contact portion of the valve body is seated on the valve seat while the structure is such that an axis of the valve body is easily offset, so that good sealability can be obtained.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a cross-sectional view illustrating a structure of a capacity control valve as a valve according to a first embodiment of the present invention.
- (2) FIG. 2 is an enlarged cross-sectional view illustrating a state where a CS valve is closed in the capacity control valve in the first embodiment.
- (3) FIG. 3 is an enlarged cross-sectional view illustrating a state where the CS valve is opened in the capacity control valve in the first embodiment.
- (4) FIG. 4 is an enlarged cross-sectional view illustrating a state where an elastic member is elastically deformed when the CS valve is closed in the first embodiment.
- (5) FIG. 5 is an enlarged cross-sectional view illustrating a structure of a capacity control valve as a valve according to a second embodiment of the present invention.
- (6) FIG. 6 is an enlarged cross-sectional view illustrating a structure of a capacity control valve as a valve according to a third embodiment of the present invention.
- (7) FIG. 7 is an enlarged cross-sectional view illustrating a state where a CS valve is closed in the capacity control valve in the third embodiment.
- (8) FIG. 8 is an enlarged cross-sectional view illustrating a state where the CS valve is opened in the capacity control valve in the third embodiment.
- (9) FIG. 9 is a view illustrating a modification example of the elastic member.

DESCRIPTION OF EMBODIMENTS

(10) Modes for implementing a valve according to the present invention will be described below based on embodiments. Incidentally, in the embodiments, a capacity control valve will be described as an example but the present invention is also applicable to other uses such as an expansion valve.

First Embodiment

- (11) A capacity control valve as a valve according to a first embodiment of the present invention will be described with reference to FIGS. 1 to 3. Hereinafter, left and right sides when viewed from the front side of FIG. 1 will be described as being left and right sides of the capacity control valve. Specifically, the left side of the drawing sheets on which a valve housing 10 is disposed and the right side of the drawing sheets on which a solenoid 80 is disposed will be described as being the left side of the capacity control valve and the right side of the capacity control valve, respectively.
- (12) The capacity control valve of the present invention is assembled into a variable capacity compressor (not illustrated) used for an air conditioning system of an automobile, etc., and variably controls pressure of a working fluid (hereinafter, simply referred to as a “fluid”) that is a refrigerant. Accordingly, the capacity control valve controls a discharge amount of the variable capacity compressor to adjust the air conditioning system to a target cooling capacity.
- (13) First, the variable capacity compressor will be described. The variable capacity compressor includes a casing including a discharge chamber, a suction chamber, a control chamber, and a plurality of cylinders. Incidentally, the variable capacity compressor is provided with a communication passage that provides direct communication between the discharge chamber and the control chamber. The communication passage is provided with a fixed orifice 9 that balances the pressures of the discharge chamber and the control chamber (refer to FIG. 1).
- (14) In addition, the variable capacity compressor includes a rotating shaft, a swash plate, and a plurality of pistons. The rotating shaft is rotationally driven by an engine (not illustrated) installed outside the casing. The swash plate is coupled to the rotating shaft so as to be tiltable with respect to the rotating shaft by a hinge mechanism in the control chamber. The plurality of pistons are

coupled to the swash plate and are reciprocatably fitted in the respective cylinders. A capacity control valve **V1** is driven to open and close by electromagnetic force, so that pressure in the control chamber of a variable capacity compressor is appropriately controlled using a suction pressure P_s of the suction chamber that suctions the fluid, a discharge pressure P_d of the discharge chamber that discharges the fluid pressurized by the pistons, and a control pressure P_c of the control chamber that houses the swash plate. Accordingly, a tilt angle of the swash plate changes continuously. Accordingly, a stroke amount of the pistons is changed, so that a discharge amount of the fluid from the variable capacity compressor is controlled.

(15) As illustrated in FIG. 1, the capacity control valve **V1** of the first embodiment assembled into the variable capacity compressor adjusts an electric current that energizes a coil **86** forming the solenoid **80** as a drive source, to perform opening and closing control of a CS valve **50** in the capacity control valve **V1**. Accordingly, the fluid flowing out from the control chamber to the suction chamber is adjusted to variably control the control pressure P_c in the control chamber. Incidentally, a discharge fluid of the discharge pressure P_d of the discharge chamber is constantly supplied to the control chamber via the fixed orifice **9**, and the CS valve **50** in the capacity control valve **V1** is closed, so that the control pressure P_c in the control chamber is increased.

(16) In the capacity control valve **V1** of the first embodiment, the CS valve **50** is formed of a CS valve body **51** as a valve body and a CS valve seat **40a** as a valve seat. The CS valve seat **40a** is formed on an elastic member **40** that is press-fitted and crimped and fixed to an annular recessed portion **10a** of the valve housing **10**. A contact portion **51a** formed at an axially right end of the CS valve body **51** comes into contact with and separates from the CS valve seat **40a** in an axial direction to open and close the CS valve **50**.

(17) Next, a structure of the capacity control valve **V1** will be described. As illustrated in FIG. 1, the capacity control valve **V1** mainly includes the valve housing **10** made of a metallic material; the CS valve body **51** disposed to be reciprocatable in the axial direction inside the valve housing **10**; and the solenoid **80** connected to the valve housing **10** to exert a driving force on the CS valve body **51**.

(18) As illustrated in FIGS. 1 to 3, the CS valve body **51** is made of a metallic material or a resin material, and includes a recessed portion **51b** at a central portion thereof, the recessed portion **51b** being open to the right in the axial direction. A rod **52** is disposed through the coil **86** of the solenoid **80**. An axially left end portion of the rod **52** is inserted into the recessed portion **51b** so as to be contactable and separable. In addition, a communication passage **51c** penetrating through the CS valve body **51** in the axial direction is formed in the CS valve body **51** at a position that is further offset in a radially outward direction than the recessed portion **51b**. The communication passage **51c** is formed with a constant cross section. Incidentally, a plurality of the communication passages **51c** may be provided.

(19) In addition, an annular projection **51d** protruding to the right in the axial direction is formed on the CS valve body **51** at a position that is further offset in the radially outward direction than the communication passage **51c**. A tip, namely, an axially right end of the annular projection **51d** serves as the contact portion **51a** that comes into contact with and separates from the CS valve seat **40a** in the axial direction. In addition, the contact portion **51a** that is the tip of the annular projection **51d** is formed with a cross-sectional shape in which radially inner and outer sides of the contact portion **51a** are round chamfered and a flat portion is provided between both round chamfers (refer to FIGS. 2 and 3). Incidentally, the contact portion **51a** may be formed with a substantially curved cross-sectional shape in which a flat portion is not provided between both round chamfers, or may be C-chamfered instead of being round chamfered. In addition, chamfering is not essential, and a chamfer may be formed only on one of the radially inner and outer sides or may be not formed.

(20) As illustrated in FIGS. 1 to 3, in the valve housing **10**, a P_s port **11** as a port penetrating through the valve housing **10** in a radial direction and communicating with the suction chamber of

the variable capacity compressor, and a Pc port **12** as a port communicating with the control chamber are formed. The Ps port **11** is formed on an axially right side of the CS valve seat **40a**, namely, in a valve closing direction to be described later. In addition, the Pc port **12** is formed on an axially left side of the CS valve seat **40a**, namely, in a valve opening direction to be described later. (21) A first valve chamber **13** to which the fluid is supplied from the Pc port **12**, and a second valve chamber **14** to which the fluid that has passed through the CS valve **50** from the first valve chamber **13** is supplied and which communicates with the Ps port **11** are provided inside the valve housing **10**. The first valve chamber **13** is formed by a recessed portion **10b** that is formed on the axially left side of the CS valve seat **40a** and that is open to the left in the axial direction, and an opening portion on an axially left side is closed in a sealed manner by a lid member **15**.

(22) In addition, a bellows **16** as a biasing member (also referred to as biasing means) for biasing the CS valve body **51** to the right in the axial direction, namely, in the valve closing direction, and a coil spring **17** as another biasing member are disposed in the first valve chamber **13**. An axially left end of the bellows **16** is fixed to the lid member **15** in a sealed manner, an axially right end of the bellows **16** is fixed to an axially left end surface of the CS valve body **51** in a sealed manner, and a space **S1** is formed inside the bellows **16**. Incidentally, the coil spring **17** is a compression spring, and is disposed in the space **S1** formed inside the bellows **16**.

(23) In addition, the space **S1** communicates with the second valve chamber **14** through the communication passage **51c**, and the fluid in the second valve chamber **14** flows into the space **S1**. Namely, in a closed state of the CS valve **50**, the bellows **16** partitions the space **S1** and the first valve chamber **13** off from each other in a sealed manner.

(24) In addition, a recessed portion **10c** of which a radially inner side of an axially right end is recessed to the left in the axial direction is formed in the valve housing **10**. A flange portion **82d** of a center post **82** is inserted into the recessed portion **10c** from the right in the axial direction, so that the center post **82** is connected and fixed to the valve housing **10** in a substantially sealed state. Incidentally, an opening end on a solenoid **80** side of the second valve chamber **14** is formed on a radially inner side of a bottom surface of the recessed portion **10c** of the valve housing **10**.

(25) Here, the elastic member **40** will be described. As illustrated in FIGS. **1** to **3**, the elastic member **40** is a ring having a rectangular cross section that is made of a material such as rubber or resin having a modulus of elasticity smaller than that of the annular projection **51d** of the CS valve body **51**.

(26) In addition, the elastic member **40** is press-fitted to the annular recessed portion **10a** from the left in the axial direction, the annular recessed portion **10a** being recessed to the right in the axial direction in a bottom portion of the recessed portion **10b** forming the first valve chamber **13** of the valve housing **10**, and is crimped and fixed by crimping pieces **10d** (refer to FIGS. **2** and **3**) on radially inner and outer sides formed on opening portion of the annular recessed portion **10a**. In addition, an exposed portion of an axially left end surface of the elastic member **40** which is formed between the crimping pieces **10d** on the radially inner and outer sides, namely, a contact surface **40s** serves as the CS valve seat **40a**. The contact portion **51a** at the tip of the annular projection **51d** of the CS valve body **51** can come into contact with and separate from the contact surface **40s**.

(27) In addition, the elastic member **40** and the annular recessed portion **10a** before and after being press-fitted have a rectangular cross section, and have substantially the same dimensions on the radially inner and outer sides and in a thickness direction. Incidentally, the elastic member **40** before being press-fitted may be formed slightly larger or smaller than the annular recessed portion **10a**.

(28) The contact surface **40s** of the elastic member **40** is a surface orthogonal to a driving direction of the CS valve body **51**, and a width of the contact surface **40s** in the radial direction is formed larger than a width of the annular projection **51d** in the radial direction. Accordingly, the contact portion **51a** at the tip of the annular projection **51d** can be reliably seated on the CS valve seat **40a**, and contact between the annular projection **51d** and the crimping pieces **10d** on the radially inner

and outer sides can be prevented.

(29) As illustrated in FIG. 1, the solenoid **80** mainly includes a casing **81** including an opening portion **81a** that is open to the left in the axial direction; the center post **82** having a substantially cylindrical shape that is inserted into the opening portion **81a** of the casing **81** from the left in the axial direction and that is fixed on a radially inner side of the casing **81**; the rod **52** which is inserted into the center post **82** to be reciprocable in the axial direction and of which the axially left end portion is disposed on the axially left side of the CS valve seat **40a**; the CS valve body **51** press-fitted and fixed to the axially left end portion of the rod **52**; a movable iron core **84** to which an axially right end portion of the rod **52** is inserted and fixed; a coil spring **85** as a rod biasing member (also referred to as rod biasing means) provided on an axially right side of the movable iron core **84** to bias the rod **52** inserted and fixed to the movable iron core **84**, to the left in the axial direction, namely, in the valve opening direction; and the coil **86** for excitation wound on an outer side of the center post **82** with a bobbin interposed therebetween. Incidentally, the coil spring **85** is a compression spring.

(30) A recessed portion **81b** of which a radially inner side of an axially left end is recessed to the right in the axial direction is formed in the casing **81**, and an axially right end portion of the valve housing **10** is inserted and fixed to the recessed portion **81b** in a substantially sealed manner.

(31) The center post **82** is made of a rigid body that is a magnetic material such as iron or silicon steel, and includes a cylindrical portion **82b** which extends in the axial direction and in which an insertion hole **82c** into which the rod **52** is inserted is formed, and the flange portion **82d** having an annular shape and extending from an outer peripheral surface of an axially left end portion of the cylindrical portion **82b** in the radially outward direction.

(32) In addition, the center post **82** is inserted and fixed to the recessed portion **10c** of the valve housing **10** inserted and fixed to the recessed portion **81b** of the casing **81**, in a substantially sealed manner in a state where an axially right end surface of the flange portion **82d** is brought into contact with a bottom surface of the recessed portion **81b** of the casing **81** from the left in the axial direction. Namely, the center post **82** is fixed by sandwiching the flange portion **82d** between the bottom surface of the recessed portion **81b** of the casing **81** and the bottom surface of the recessed portion **10c** of the valve housing **10** from both sides in the axial direction.

(33) Next, an opening and closing operation of the capacity control valve **V1** will be described.

(34) First, a non-energized state of the capacity control valve **V1** will be described. As illustrated in FIGS. 1 and 2, in a non-energized state of the capacity control valve **V1**, the CS valve body **51** is pressed to the right in the axial direction, namely, in the valve closing direction by biasing forces of the bellows **16** and of the coil spring **17**, so that the contact portion **51a** at the tip of the annular projection **51d** of the CS valve body **51** is seated on the CS valve seat **40a** formed on the axially left end surface of the elastic member **40**, and the CS valve **50** is closed.

(35) At this time, when an effective pressure-receiving area of the bellows **16** is A, an effective pressure-receiving area of the CS valve body **51** is B, and an axially rightward direction is defined as being positive, a biasing force $F_{\text{sub.be1}}$ of the bellows **16**, a biasing force $F_{\text{sub.sp1}}$ of the coil spring **17**, a force $F_{\text{sub.P1}}$ due to the control pressure $P_c = (P_1 \times (A - B))$, a force $F_{\text{sub.P2}}$ due to the suction pressure $P_s = -(P_2 \times (A - B))$, and a biasing force $F_{\text{sub.sp2}}$ of the coil spring **85** act on the CS valve body **51**. Namely, when the axially rightward direction is defined as being positive, a force $F_{\text{sub.rod}} = F_{\text{sub.be1}} + F_{\text{sub.sp1}} + F_{\text{sub.P1}} - F_{\text{sub.P2}} - F_{\text{sub.sp2}}$ acts on the CS valve body **51**.

(36) Specifically, the fluid in the space **S1** acts on the axially left end surface of the CS valve body **51**, and the fluid in the second valve chamber **14** acts on an axially right end surface of the CS valve body **51**. Since the second valve chamber **14** and the space **S1** communicate with each other through the communication passage **51c** formed in the CS valve body **51**, the fluid in the second valve chamber **14** located closer to a valve closing direction side than the CS valve body **51**, namely, the fluid of the suction pressure P_s supplied from the P_s port **11** flows into the space **S1**.

(37) In addition, since the communication passage **51c** is a narrowed through-hole, when a slight

pressure difference occurs instantaneously between pressure in the space **S1** and pressure in the second valve chamber **14**, the fluid in the space **S1** is unlikely to instantaneously move toward the second valve chamber **14** and is held in the space **S1**, and a closed state of the CS valve **50** is easily maintained.

(38) In such a manner, the fluid flowing into the space **S1** and into the second valve chamber **14** is the fluid of the same suction pressure P_s supplied from the P_s port **11**. In addition, in the present embodiment, since the effective pressure-receiving area A of the bellows **16** and the effective pressure-receiving area B of the CS valve body **51** are equal (i.e., $A=B$), both the forces $F_{sub.P1}$ and $(F_{sub.P2})$ acting on the CS valve body **51** due to the control pressure P_c and to the suction pressure P_s are substantially zero. Namely, when the rightward direction is defined as being positive, a force $F_{sub.rod}=F_{sub.be1}+F_{sub.sp1}-F_{sub.sp2}$ substantially acts on the CS valve body **51**.

(39) Next, an energized state of the capacity control valve **V1** will be described. As illustrated in FIG. 3, in an energized state of the capacity control valve **V1**, namely, during normal control or during so-called duty control, when an electromagnetic force $F_{sub.sol}$ generated by the application of an electric current to the solenoid **80** is larger than the force $F_{sub.rod}$ (i.e., $F_{sub.sol}>F_{sub.rod}$), the movable iron core **84** is pulled to a center post **82** side, namely, to the axially left side, and the rod **52** fixed to the movable iron core **84** and the CS valve body **51** held so as to be able to come into contact with and to separate from the rod **52** move together to the left in the axial direction, namely, in the valve opening direction. Accordingly, the contact portion **51a** of the CS valve body **51** separates from the CS valve seat **40a** formed on the contact surface **40s** of the elastic member **40**, and the CS valve **50** is opened. In addition, when the solenoid **80** is driven, the movable iron core **84** comes into contact with an axially right side of the center post **82**, so that further separation of the CS valve body **51** from the CS valve seat **40a** is restricted.

(40) In such a manner, the capacity control valve **V1** can control pressure in the control chamber of the variable capacity compressor using a pressure difference between the control pressure P_c and the suction pressure P_s lower than the control pressure P_c due to a valve opening degree of the CS valve **50** that is adjusted by balance between electromagnetic force of the solenoid **80** and the biasing forces of the bellows **16**, of the coil spring **17**, and of the coil spring **85**.

(41) As described above, in the capacity control valve **V1** of the first embodiment, even in a case where contaminations are caught between the contact portion **51a** at the tip of the annular projection **51d** of the CS valve body **51** and the CS valve seat **40a** formed on the contact surface **40s** of the elastic member **40** when the valve is closed, the elastic member **40** can be elastically deformed to suppress generation of a gap between the contact portion **51a** of the CS valve body **51** and the CS valve seat **40a**, so that valve leakage can be reduced.

(42) In addition, since the elastic member **40** is formed to have a modulus of elasticity, namely, a Young's modulus smaller than that of the annular projection **51d** of the CS valve body **51**, when the valve is closed, even in a case where contaminations are caught between the contact portion **51a** of the CS valve body **51** and the CS valve seat **40a** formed on the contact surface **40s** of the elastic member **40**, the elastic member **40** can be reliably and elastically deformed to suppress generation of a gap between the contact portion **51a** of the CS valve body **51** and the CS valve seat **40a**. Further, regardless of whether or not contaminations are caught, when the valve is closed, since the contact portion **51a** at the tip of the annular projection **51d** elastically deforms the elastic member **40** and is slightly buried (refer to FIG. 4), it is difficult for the CS valve body **51** to relatively move with respect to the contact surface **40s** of the elastic member **40** in a valve closed state of the CS valve **50**, so that sealability is enhanced.

(43) Since the contact surface **40s** of the elastic member **40** on which the CS valve seat **40a** is formed is a surface orthogonal to the driving direction of the CS valve body **51**, when the valve is closed, it is difficult for the annular projection **51d** to further relatively move with respect to the contact surface **40s** of the elastic member **40**, so that sealability is enhanced. In addition, when the

valve is closed, since the relative movement of the annular projection **51d** with respect to the contact surface **40s** of the elastic member **40** is suppressed, damage to the contact surface **40s** of the elastic member **40** caused by the annular projection **51d** is suppressed, so that sealability can be maintained over a long period of time. Incidentally, in the capacity control valve **V1** of the present embodiment, since the CS valve body **51** and the rod **52** are held so as to be able to come into contact with and to separate from each other, and the CS valve body **51** is supported by the bellows **16** fixed to the valve housing **10** via the lid member **15** on the axially left side of the CS valve seat **40a**, the structure is such that the CS valve body **51** easily moves when the valve is closed, but as described above, the relative movement of the annular projection **51d** with respect to the contact surface **40s** of the elastic member **40** is suppressed, sealability or durability is guaranteed.

(44) Further, since corners on the radially inner and outer sides of the tip portion of the annular projection **51d** are round chamfered, and the tip portion is formed with a substantially curved cross-sectional shape, damage to the contact surface **40s** of the elastic member **40** caused by the annular projection **51d** is further suppressed.

(45) When materials of the contact portion of the valve body and of the valve seat are a combination of metals as in the related art, since not only a gap is likely to be generated due to contaminations being caught, but also a gap is likely to be generated by an offset between the contact portion of the valve body and the valve seat in a closed state of the valve, valve leakage is likely to occur, but as described above, in the first embodiment, since the CS valve seat **40a** is formed on the contact surface **40s** of the elastic member **40**, this problem can be solved.

(46) In addition, since the valve housing **10** is provided with the annular recessed portion **10a**, and the elastic member **40** press-fitted to the annular recessed portion **10a** is crimped and fixed by the crimping pieces **10d** on the radially inner and outer sides, the elastic member **40** inserted into the annular recessed portion **10a** can be prevented from coming off. Incidentally, since the elastic member **40** is press-fitted to the annular recessed portion **10a** or is crimped and fixed by the crimping pieces **10d** on the radially inner and outer sides, the elastic member **40** may be deformed in the radial direction to cause the contact surface **40s** to slightly bulge to the left in the axial direction, so that when the valve is closed, the contact portion **51a** at the tip of the annular projection **51d** is easily buried in the contact surface **40s** of the elastic member **40**.

(47) In addition, since the elastic member **40** has a rectangular cross section, even when the annular projection **51d** comes into contact with the contact surface **40s** of the elastic member **40** at any position, stable elasticity can be provided.

(48) In addition, the CS valve body **51** is configured separately from the rod **52** forming the solenoid **80**, and the rod **52** is biased in the valve opening direction by the coil spring **85**, so that the CS valve body **51** and the rod **52** are held so as to be able to come into contact with and to separate from each other. When the valve is closed, the contact portion **51a** of the CS valve body **51** is seated on the CS valve seat **40a** formed on the contact surface **40s** of the elastic member **40**, and at the same time, the CS valve body **51** is not affected by an inertial force of the rod **52** acting to the right in the axial direction. For this reason, an excessive load is not applied to the annular projection **51d** or to the elastic member **40**. Namely, when the valve is closed, since only the biasing forces of the bellows **16** and of the coil spring **17** act on the annular projection **51d** or on the elastic member **40**, an excessive load is not applied to the annular projection **51d** or to the elastic member **40**, so that damage thereto can be prevented.

(49) In addition, since the coil spring **17** disposed inside the bellows **16** is a compression spring, a structure on the solenoid **80** side of the capacity control valve **V1** is simplified, and the contact portion **51a** at the tip of the annular projection **51d** of the CS valve body **51** is seated on the CS valve seat **40a** while the structure is such that an axis of the CS valve body **51** is easily offset, so that good sealability can be obtained.

(50) Incidentally, the crimping piece **10d** may be provided on at least one of the radially inner and outer sides of the valve housing **10**.

Second Embodiment

(51) A capacity control valve as a valve according to a second embodiment of the present invention will be described with reference to FIG. 5. Incidentally, a description of configurations that are the same as the configurations of and are duplicated in the first embodiment will be omitted.

(52) As illustrated in FIG. 5, in a capacity control valve V2 in the second embodiment, a valve housing is configured such that a first valve housing **210** and a second valve housing **211** are integrally connected and fixed to each other in a substantially sealed state by externally fitting an axially left end portion of the second valve housing **211** to an axially right end portion of the first valve housing **210** from the right in the axial direction. The Pc port **12** communicating with the control chamber of the variable capacity compressor is formed in the first valve housing **210**. In addition, the Ps port **11** communicating with the suction chamber of the variable capacity compressor is formed in the second valve housing **211**.

(53) An annular recessed portion **211a** recessed to the right in the axial direction is formed in the axially left end portion of the second valve housing **211**, and an elastic member **240** is press-fitted to the annular recessed portion **211a** from the left in the axial direction, and is crimped and fixed by a crimping piece **211d** on a radially inner side formed on an opening portion of the annular recessed portion **211a**. Further, when the first valve housing **210** and the second valve housing **211** are connected and fixed to each other, an annular protrusion **210a** having a rectangular cross section that is formed on the axially right end portion of the first valve housing **210** is pressed against a radially outer side of an axially left end surface of the elastic member **240**, so that the elastic member **240** is sandwiched and held between the first valve housing **210** and the second valve housing **211**.

(54) In addition, a CS valve seat **240a** as a valve seat is formed on the axially left end surface of the elastic member **240**, the CS valve seat **240a** being formed of an exposed portion of the axially left end surface formed between the annular protrusion **210a** of the first valve housing **210** and the crimping piece **211d** of the second valve housing **211**, namely, of a contact surface **240s**.

(55) According to this configuration, in the capacity control valve V2 of the second embodiment, since the elastic member **240** is sandwiched and held between the first valve housing **210** and the second valve housing **211** that are integrally connected and fixed to each other, the elastic member **240** inserted into the annular recessed portion **211a** can be prevented from coming off.

(56) In addition, compared to when the crimping pieces **10d** are formed on the radially inner and outer sides inside the valve housing **10** as in the first embodiment, in the second embodiment, the valve housing is divided, so that processing of the first valve housing **210** and the second valve housing **211** for holding the elastic member **240** is facilitated.

(57) Incidentally, in the second embodiment, since the elastic member **240** can be held by the annular protrusion **210a** of the first valve housing **210**, the crimping piece **211d** of the second valve housing **211** may not be formed. Accordingly, only a recess of the annular recessed portion **211a** may be formed in the second valve housing **211**, and the second valve housing **211** is more easily processed.

Third Embodiment

(58) A capacity control valve as a valve according to a third embodiment of the present invention will be described with reference to FIGS. 6 to 8. Incidentally, a description of configurations that are the same as the configurations of and are duplicated in the first embodiment will be omitted.

(59) As illustrated in FIG. 6, in a capacity control valve V3 of the third embodiment, the CS valve **50** is formed of a CS valve body **351** as a valve body and a CS valve seat **310a** as a valve seat at a tip of an annular projection **310d** of a valve housing **310**, and a contact portion **340a** formed on a contact surface **340s** of an elastic member **340** that is press-fitted and crimped and fixed to an annular recessed portion **351a** formed at an axially right end of the CS valve body **351** comes into contact with and separates from the CS valve seat **310a** in the axial direction, to open and close the CS valve **50**.

(60) As illustrated in FIGS. 6 to 8, the CS valve body 351 is made of a metallic material, and the annular recessed portion 351a recessed to the left in the axial direction is formed in the CS valve body 351 at a position that is much further offset in the radially outward direction than a communication passage 351c.

(61) The elastic member 340 is press-fitted to the annular recessed portion 351a of the CS valve body 351 from the right in the axial direction, and is crimped and fixed by crimping pieces 351d (refer to FIGS. 7 and 8) on radially inner and outer sides formed on an opening portion of the annular recessed portion 351a. In addition, the contact portion 340a of the CS valve body 351 is formed on an axially right end surface of the elastic member 340, the contact portion 340a being formed of an exposed portion of the axially right end surface formed between the crimping pieces 351d on the radially inner and outer sides, namely, of the contact surface 340s. The contact portion 340a can come into contact with and separate from the CS valve seat 310a at the tip of the annular projection 310d of the valve housing 310.

(62) As illustrated in FIGS. 6 to 8, the annular projection 310d that is formed on a bottom portion of a recessed portion 310b forming the first valve chamber 13 and that protrudes to the left in the axial direction is formed on the valve housing 310. The CS valve seat 310a from which the contact portion 340a of the CS valve body 351 comes into contact with and separates in the axial direction is formed at the tip, namely, an axially left end of the annular projection 310d.

(63) According to this configuration, in the capacity control valve V3 of the third embodiment, since the elastic member 340 is provided on the CS valve body 351 that is a member to be assembled to the valve housing 310, processing of the CS valve body 351 for holding the elastic member 340 is facilitated.

(64) Incidentally, the crimping piece 351d may be provided on at least one of the radially inner and outer sides of the CS valve body 351.

(65) The embodiments of the present invention have been described above with reference to the drawings, but the specific configurations are not limited to the embodiments, and changes or additions that are made without departing from the scope of the present invention are also included in the present invention.

(66) For example, in the embodiments, a mode in which one of the CS valve seat and the contact portion of the CS valve body facing the annular projection in the axial direction is formed of an elastic member has been described, but the present invention is not limited to the configuration, and both the contact portion of the CS valve body and the CS valve seat may be formed of elastic members. In this case, only the annular projection may be formed of an elastic member. In addition, it is preferable that the elastic member on which the contact surface is formed has a modulus of elasticity smaller than that of the elastic member forming the annular projection. Incidentally, both the contact portion of the CS valve body and the CS valve seat may be formed of elastic members having the same modulus of elasticity.

(67) In addition, the contact surface of the elastic member may not be a surface orthogonal to the driving direction of the CS valve body, and may be formed as, for example, a tilted surface or a curved surface.

(68) In addition, in the embodiments, the valve housing and the CS valve body have been described as being made of a metallic material or a resin material, but it is preferable that a member by which the elastic member is held through crimping and fixing is made of a metallic material. In addition, for example, when a member by which the elastic member is held is made of a resin material, instead of the crimping piece, a portion that becomes a pressing piece that prevents the elastic member from coming off may be fleshed out.

(69) In addition, in the embodiments, the elastic member has been described as being press-fitted to the annular recessed portion, but the elastic member may be simply inserted into the annular recessed portion. In addition, the elastic member is not limited to being disposed inside the annular recessed portion, and for example, may be fixed to the valve housing or to the CS valve body by

another member such as an adhesive agent or a bolt.

(70) In addition, the elastic member is not limited to having a rectangular cross section, and the cross-sectional shape may be, for example, a circular shape, a triangular shape, a T shape, a V shape, an X shape, etc. For example, as illustrated in FIG. 9, when an elastic member **40'** is formed with a T-shaped cross section, the elastic member **40'** may be crimped and fixed by pressing step portions provided in the elastic member **40'** press-fitted to the annular recessed portion **10a**, using the crimping pieces **10d** on the radially inner and outer side.

(71) In addition, in the embodiments, the CS valve body has been described as being configured as a member separate from the rod disposed through the coil of the solenoid, and as being able to come into contact with and to separate from the rod, but the present invention is not limited to the configuration, and the CS valve body and the rod that are separate members may be integrally connected and fixed to each other. In addition, the CS valve body and the rod may be integrally formed. In this case, the coil spring that biases the rod in the valve opening direction may not be provided.

(72) In addition, since the coil spring is disposed inside the bellows, the bellows itself may not have a biasing force.

(73) In addition, the coil spring may not be disposed inside the bellows.

(74) In addition, in the embodiments, a mode in which the effective pressure-receiving area A of the bellows and the effective pressure-receiving area B of the CS valve body are the same (i.e., $A=B$) has been described, but the present invention is not limited to this mode, and the effective pressure-receiving area A may be set slightly larger than the effective pressure-receiving area B (i.e., $A>B$) such that a closed state of the CS valve can be reliably maintained, or the effective pressure-receiving area B may be set slightly larger than the effective pressure-receiving area A (i.e., $A<B$) such that the CS valve is easily opened. Namely, an influence of pressure of the fluid acting on both sides the CS valve body in a movement direction may be reduced.

(75) In addition, the capacity control valve of the embodiments has been described as a CS valve, but the present invention is not limited to the configuration, and the capacity control valve may be a DC valve that opens and closes a flow passage between the Pd port and the Pc port.

(76) In addition, the drive source may be a member other than the solenoid.

REFERENCE SIGNS LIST

(77) **9** Fixed orifice **10** Valve housing **10a** Annular recessed portion **10d** Crimping piece **11** Ps port (port) **12** Pc port (port) **13** First valve chamber **14** Second valve chamber **15** Lid member **16** Bellows (biasing member) **17** Coil spring (biasing member) **40** Elastic member **40a** CS valve seat (valve seat) **40s** Contact surface **50** CS valve **51** CS valve body (valve body) **51a** Contact portion **51d** Annular projection **52** Rod **80** Solenoid (drive source) **85** Coil spring (rod biasing member) **210** First valve housing (valve housing) **210a** Annular protrusion **211** Second valve housing (valve housing) **211a** Annular recessed portion **211d** Crimping piece **240** Elastic member **240a** CS valve seat (valve seat) **240s** Contact surface **310** Valve housing **310a** CS valve seat (valve seat) **310d** Annular projection **340** Elastic member **340a** Contact portion **340s** Contact surface **351** CS valve body (valve body) **351a** Annular recessed portion **351d** Crimping piece **S1** Space **V1, V2, V3** Capacity control valve (valve)

Claims

1. A valve, comprising: a valve housing in which a port through which a fluid passes is formed; a valve body configured to be driven by a drive source; a valve seat on which a contact portion of the valve body is seated; a biasing member configured to bias the valve body in a valve closing direction of the valve; and a bellows having a first end portion fixed to the valve body and a second end portion fixed to the valve housing, the first end portion and the second end portion being opposed to each other in an axial direction, wherein the valve seat is formed of an elastic member

which is press-fitted into an annular recessed portion formed in the valve housing, the annular recessed portion is defined by an annular bottom surface, and an inner annular side wall surface and an outer annular side wall surface which are opposed to each other in a radial direction, the contact portion of the valve body is formed of an annular projection which is protruded toward the valve seat from a central part of an axially end surface of the valve body on a valve seat side and which has a contact surface formed by a flat tip surface orthogonal to the axial direction, and the valve body is provided with a through-hole which communicates with a radially inner side space of the contact portion and an inner space of the bellows.

2. The valve according to claim 1, the elastic member is formed to have a modulus of elasticity smaller than a modulus of elasticity of the annular projection.

3. The valve according to claim 2, wherein an inner diameter side end of the elastic member is crimped and fixed.

4. The valve according to claim 2, wherein the elastic member has a rectangular cross section.

5. The valve according to claim 2, wherein the valve body is separately configured to come into contact with and to separate from a rod forming the drive source, and the rod is biased in a valve opening direction by a rod biasing member.

6. The valve according to claim 2, wherein the biasing member is a compression spring.

7. The valve according to claim 1, wherein an inner diameter side end of the elastic member is crimped and fixed.

8. The valve according to claim 7, wherein the elastic member has a rectangular cross section.

9. The valve according to claim 7, wherein the valve body is separately configured to come into contact with and to separate from a rod forming the drive source, and the rod is biased in a valve opening direction by a rod biasing member.

10. The valve according to claim 7, wherein the biasing member is a compression spring.

11. The valve according to claim 1, wherein the elastic member has a rectangular cross section.

12. The valve according to claim 11, wherein the valve body is separately configured to come into contact with and to separate from a rod forming the drive source, and the rod is biased in a valve opening direction by a rod biasing member.

13. The valve according to claim 11, wherein the biasing member is a compression spring.

14. The valve according to claim 1, wherein the valve body is separately configured to come into contact with and to separate from a rod forming the drive source, and the rod is biased in a valve opening direction by a rod biasing member.

15. The valve according to claim 1, wherein the biasing member is a compression spring.
