

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399456
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Obuchi; Yusuke et al.

Sheet finisher

Abstract

A finisher for binding a sheet bundle includes a conveying portion for conveying sheets, a stacking portion for stacking the sheets, a manual setting portion to which the sheet bundle is inserted by an operator, a stapler having a head at a front portion thereof for binding the sheet bundle by a staple and a cartridge at a rear portion for housing the staple, a stapler moving unit for moving the stapler to a first stapling position for binding a corer portion of the sheet bundle, a second stapling position for binding the sheet bundle inserted into the manual setting portion and a staple loading position for removing the cartridge and replenishing a new cartridge, and a moving unit for rotating the stapler to a posture such that the rear portion rather than the front portion of the stapler is located at a front side in the depth direction.

Inventors: Obuchi; Yusuke (Tokyo, JP), Abe; Hideto (Tokyo, JP), Takahashi; Masaya (Yamanashi-ken, JP), Nishizawa; Seiji (Yamanashi-ken, JP)

Applicant: Obuchi; Yusuke (Tokyo, JP); Abe; Hideto (Tokyo, JP); Takahashi; Masaya (Yamanashi-ken, JP); Nishizawa; Seiji (Yamanashi-ken, JP)

Family ID: 1000008781985

Assignee: CANON FINETECH NISCA INC. (Misato, JP)

Appl. No.: 18/614125

Filed: March 22, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240231267 A1	Jul. 11, 2024

Foreign Application Priority Data

JP	2013-145854	Jul. 11, 2013
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc US 18074820 20221205 US 11947301 child-doc US 18614125
continuation parent-doc US 17470282 20210909 US 11520268 20221206 child-doc US 18074820
continuation parent-doc US 16900113 20200612 US 11150588 20211019 child-doc US 17470282
continuation parent-doc US 16773365 20200127 US 10705471 20200707 child-doc US 16900113
continuation parent-doc US 16576173 20190919 US 10579005 20200303 child-doc US 16773365
continuation parent-doc US 16031601 20180710 US 10496023 20191203 child-doc US 16576173
continuation parent-doc US 15440850 20170223 US 10048636 20180814 child-doc US 16031601
continuation parent-doc US 14325882 20140708 US 9586783 20170307 child-doc US 15440850

Publication Classification

Int. Cl.: **B65H37/04** (20060101); **B27F7/00** (20060101); **B27F7/17** (20060101); **B42B4/00** (20060101); **B42C1/12** (20060101); **B65H9/04** (20060101); **B65H31/02** (20060101); **B65H43/00** (20060101); **G03G15/00** (20060101); G03G21/16 (20060101)

U.S. Cl.:

CPC **G03G15/6544** (20130101); **B27F7/006** (20130101); **B27F7/17** (20130101); **B42B4/00** (20130101); **B42C1/12** (20130101); **B65H9/04** (20130101); **B65H31/02** (20130101); **B65H37/04** (20130101); **B65H43/00** (20130101); B65H2301/51611 (20130101); B65H2301/51616 (20130101); B65H2801/27 (20130101); G03G21/1633 (20130101); G03G2215/00544 (20130101); G03G2221/1672 (20130101)

Field of Classification Search

CPC: B65H (37/04); B65H (2801/27); G03G (21/1633); G03G (2221/1672); G03G (2215/00544)

USPC: 270/58.07; 270/58.08; 270/58.11

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7063248	12/2005	Noh et al.	N/A	N/A
8146908	12/2011	Terao	270/58.08	B42C 1/12
8342499	12/2012	Shiraishi	270/58.08	B65H 31/3027

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2005523855	12/2004	JP	N/A
2009012892	12/2008	JP	N/A
2021138547	12/2020	JP	N/A
03038530	12/2002	WO	N/A

OTHER PUBLICATIONS

Japan Patent Office, Decision of Refusal for Japanese Application No. 2022-205619 mailed on Apr. 16, 2024; 4 pp. cited by applicant

Japan Patent Office, Notice of Reasons for Refusal for Japanese Application No. 2022-205619 mailed on Nov. 27, 2023; 6 pp. cited by applicant

Primary Examiner: Nicholson, III; Leslie A

Attorney, Agent or Firm: HAUPTMAN HAM, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This is a continuation application of Ser. No. 18/074,820 filed on Dec. 5, 2022, which is a continuation application of Ser. No. 17/470,282 filed on Sep. 9, 2021, which is a continuation application of Ser. No. 16/900,113 filed on Jun. 12, 2020, which is a continuation application of Ser. No. 16/773,365 filed on Jan. 27, 2020, which is a continuation application of Ser. No. 16/576,173 filed on Sep. 19, 2019, which is a continuation application of Ser. No. 16/031,601 filed on Jul. 10, 2018, which is a continuation application of Ser. No. 15/440,850 filed on Feb. 23, 2017, which is a continuation application of Ser. No. 14/325,882 filed on Jul. 8, 2014, which claims priority of Japanese Patent Application No. 2013-145854 filed on Jul. 11, 2013, the disclosure of which is incorporated herein.

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The present invention relates to a sheet finisher for binding sheets.

2. Description of Related Arts

(2) In general, there has been known a post-processing apparatus (finisher) which performs a binding process on sheets with images formed thereon by an image forming apparatus after collating and stacking the sheets on a processing tray. For performing a binding process, there have been known a stapling unit to perform a binding process using a staple, a press binding unit to bond overlapped sheets with pressing deformation, and a unit to bind a sheet bundle as forming an opening and a folding piece thereat.

(3) A binding apparatus using a staple is known as an apparatus which reliably bonds a relatively thick sheet bundle as preventing the sheet bundle from being easily separated. Despite of a drawback of being easily separated, a press binding apparatus is used as a binding apparatus being environment-friendly with paper recycling and the like due to non-use of binding part such as a steel-made staple. Further, with such a binding apparatus, it has been known that the apparatus can be structured as being downsized, compactified, quiet, and power-saved.

(4) Japanese Patent Application Laid-open No. 2011-190021 (FIGS. 1 and 3) discloses an apparatus which is continuously connected to a sheet discharging port of an image forming apparatus. Here, image-formed sheets are introduced to and stacked on a processing tray from an introducing path and a binding process is performed thereon, and then, the sheets are stored in a stack tray at the downstream side. Further, the sheet bundle fed and stacked to the processing tray from a sheet discharging path is positioned by being regulated with a tailing end in the sheet discharging direction abutted. In the above state, the sheet bundle is arranged on the processing tray to be capable of selecting a method from a method to perform a binding process (multi-binding) on a plurality of positions at the sheet tailing end with a stapling unit, a method to perform a binding process (corner binding) on a single corner position of the sheet bundle, and a binding method to perform a binding process without using a staple.

(5) The staple-binding method is disclosed as a stapling unit and the non-staple binding unit is disclosed as a press binding unit. The stapling unit is supported by a guide rail to be movable along the end face of the sheet bundle positioned on the processing tray to perform multi-binding at a predetermined interval or corner binding at a single corner position. Further, the non-staple binding unit is structured to bond sheets mutually with pressing deformation using a binder mechanism having an upper-lower pair of corrugation-shaped pressurizing faces.

(6) Further, Japanese Patent Application Laid-open No. 2012-025499 (FIG. 2) discloses a similar apparatus as disclosed above. Here, there is disclosed an apparatus in which sheets fed from an image forming apparatus are discharged to a stack tray at the downstream side, after a post-processing is performed thereon as selecting a binding process using a staple or a binding process with a non-staple binding unit in a state that the sheets are stacked on a processing tray.

(7) Further, Japanese Patent Application Laid-open No. 2005-096392 (FIG. 3) discloses an apparatus including a stage arranged at a body casing, the stage having a slit-shaped groove to which a sheet bundle is inserted. Here, after sheets fed from an image forming apparatus are collated and stacked on a stack tray, an operator inserts the sheet bundle to the stage so that a binding process is performed thereon with a stapling unit arranged inside the body casing.

SUMMARY OF THE INVENTION

(8) As described above, there has been widely known a post-processing apparatus for performing a binding process after collating and stacking image-formed sheets fed from an image forming apparatus and storing the sheets on a stack tray. Further, there has been known an apparatus which performs a post-process as selecting a binding process using a staple or a binding process with a non-staple binding unit on a sheet bundle stacked on a processing tray.

(9) Further, Japanese Patent Application Laid-open No. 2005-096392 and the like propose an apparatus which includes a slit-shaped manual setting base arranged at an external body casing. Here, an operator sets a sheet bundle discharged to a stack tray to the manual setting base and a binding process is performed thereon. For arranging the manual setting base at the external casing, there has been known a structure to set a sheet bundle at the external casing in a state of being raised in the vertical direction. Here, there has not been known that a binding processing unit is commonly used for a binding device to bind a sheet bundle stacked on the processing tray and processor to bind a sheet bundle set at the external casing.

(10) An object of the present invention is to provide a sheet bundle binding processing apparatus capable of selecting from staple binding, non-staple binding, and a manual binding to be performed on a sheet bundle.

(11) A sheet processing apparatus comprises a conveying portion which conveys sheets; a conveying path which is a path for sheets conveyed by the conveying portion; a stack portion on which sheets discharged from a discharging port of the conveying path by the conveying portion in a conveying direction are stacked; a first binding portion which has a first binding member and which moves in a crossing direction crossing to the conveying direction so that the first binding portion moves from a first side of the sheet processing apparatus to a second side of the sheet processing apparatus and moves from the second side to the first side; a first regulating portion which regulates a position of a sheet bundle, stacked on the stack portion, in the crossing direction by contacting an end of the first side of the sheet bundle in the crossing direction and moves in the crossing direction; a second regulating portion which regulates a position of a sheet bundle, stacked on the stack portion, in the crossing direction by contacting an end of the second side of the sheet bundle in the crossing direction and moves in the crossing direction; a third regulating portion which regulates a position of a sheet bundle, stacked on the stack portion, in the conveying direction by contacting an upstream end of the sheet bundle in the conveying direction; and a second binding portion which has a second binding member and which binds a corner portion of a sheet bundle without a staple, the corner portion including an end where the first regulating portion has contacted and an end where the third regulating portion has contacted, the corner portion being

on the first side of the sheet bundle.

(12) The first binding portion binds a corner portion of a sheet bundle by a staple, the corner portion including an end where the first regulating portion has contacted and an end where the third regulating portion has contacted, the corner portion being on the first side of the sheet bundle. The second binding member is located at a downstream side relative to the first binding member in the conveying direction. The upstream end of the sheet bundle when the upstream end of the sheet bundle is bound by the second binding portion is located at a downstream side relative to the upstream end of the sheet bundle when the upstream end of the sheet bundle is bound by the first binding portion.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an explanatory view of a whole configuration of an image forming system according to the present invention;
- (2) FIG. 2 is an explanatory perspective view illustrating a whole configuration of a post-processing apparatus in the image forming system of FIG. 1;
- (3) FIG. 3 is a side sectional view (at an apparatus front side) of the apparatus of FIG. 2;
- (4) FIGS. 4A and 4B are explanatory views of a sheet introducing mechanism of the apparatus of FIG. 2, while FIG. 4A illustrates a state that a paddle rotor is at a waiting position and FIG. 4B illustrates a state that the paddle rotor is at an engaging position;
- (5) FIG. 5 is an explanatory view illustrating an arrangement relation among respective areas and alignment positions in the apparatus of FIG. 2;
- (6) FIG. 6 is a structural explanatory view of the side aligning device in the apparatus of FIG. 2;
- (7) FIG. 7 is an explanatory view of a moving mechanism of a stapling unit;
- (8) FIG. 8 is an explanatory view illustrating binding positions of the stapling unit;
- (9) FIG. 9 is an explanatory view of multi-binding and left corner binding of the stapling unit;
- (10) FIGS. 10A to 10C illustrate states of the stapling unit at binding positions, while FIG. 10A illustrates a state at a right corner binding position, FIG. 10B illustrates a state at a staple loading position, and FIG. 10C illustrates a state at a manual binding position;
- (11) FIGS. 11A to 11D are explanatory views of a sheet bundle discharging mechanism in the apparatus of FIG. 2, while FIG. 11A illustrates a waiting state, FIG. 11B illustrates a transitional conveying state, FIG. 11C illustrates a structure of a second conveying member, and FIG. 11D illustrates a state of discharging to a stack tray;
- (12) FIGS. 12A to 12G illustrate a binding processing method of a sheet bundle;
- (13) FIG. 13A is a structural explanatory view of the stapling unit and FIG. 13B is a structural explanatory view of a press binding unit;
- (14) FIG. 14 is a structural explanatory view of the stack tray in the apparatus of FIG. 2;
- (15) FIGS. 15A to 15F are explanatory views of the kicker device in the apparatus of FIG. 2;
- (16) FIG. 16 is an explanatory view of a control configuration of the apparatus of FIG. 1;
- (17) FIG. 17 illustrates operational flows of a staple-binding processing mode;
- (18) FIG. 18 illustrates operational flows of an eco-binding mode;
- (19) FIG. 19 illustrates operational flows of a printout mode;
- (20) FIG. 20 illustrates operational flows of a sorting mode;
- (21) FIG. 21 illustrates common operational flows of introducing sheets onto a processing tray; and
- (22) FIG. 22 illustrates operational flows of a manual staple-binding process.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

- (23) In the following, the present invention will be described in detail based on preferred embodiments illustrated in the drawings. The present invention relates to a sheet bundle binding

processing mechanism which performs a binding process on a collated and stacked sheet bundle with images formed thereon in a later-mentioned image forming system. The image forming system illustrated in FIG. 1 includes an image forming unit A, an image reading unit C, and a post-processing unit B. A document image is read by the image reading unit C. Based on the image data, the image forming unit A forms an image on a sheet. Then, the post-processing unit B (i.e., sheet bundle binding processing apparatus, as the case may be) performs a binding process with the image-formed sheets collated and stacked and stores the sheets on a stack tray **25** at the downstream side.

(24) The post-processing unit B which will be described later is built in as a unit at a sheet discharge space (stack tray space) **15** which is formed in a housing of the image forming unit A. The post-processing unit B has an inner finisher structure having a post-processing mechanism which performs a binding process after the image-formed sheets conveyed to a sheet discharging port **16** are collated and stacked on a processing tray and subsequently stores the sheets on the stack tray **25**. Not limited to the above, the present invention may have a stand-alone structure that the image forming unit A, the image reading unit C, and the post-processing unit B are independently arranged and the respective units are connected by network cables to be systematized.

(25) Sheet-Bundle Binding Processing Apparatus (Post-Processing Unit)

(26) As illustrated in FIGS. 2 and 3 being a perspective view and a sectional view of the post-processing unit B, the post-processing unit B includes an apparatus housing **20**, a sheet introducing path **22** which is arranged in the apparatus housing **20**, a processing tray **24** which is arranged at the downstream side of a path sheet discharging port **23**, and a stack tray **25** which is arranged at the downstream side further therefrom.

(27) Apparatus Housing

(28) The apparatus housing **20** includes an apparatus frame **20a** and an external casing **20b**. The apparatus frame **20a** has a frame structure to support later-mentioned mechanisms (a path mechanism, a tray mechanism, a conveying mechanism, and the like). In the drawings, a binding mechanism, the conveying mechanism, a tray mechanism, and a driving mechanism are arranged at a right-left pair of side frames (not illustrated) which are mutually opposed to form a monocoque structure as being integrated with the external casing **20b**. The external casing **20b** has the monocoque structure obtained by integrating, with mold processing using resin or the like, right-left side frames **20c**, **20d** and a stay frame (later-mentioned bottom frame **20e**) which connects the side frames **20c**, **20d**. Here, a part (at the apparatus front side) thereof is exposed to be operable from the outside.

(29) That is, the frames are stored in the sheet discharge space **15** of the later-mentioned image forming unit A with an outer circumference thereof covered by the external casing **20b**. In the above state, a front side of the external casing **20b** is exposed to be operable from the outside. A later-mentioned cartridge mount opening **28** for staples, a manual setting portion (insertion portion) **29**, and a manual operation button **30** (in the drawing, a switch having a built-in lamp) are arranged at the front side of the external casing **20b**.

(30) The external casing **20b** has a length L_x in a sheet discharging direction and a length L_y in a direction perpendicular to the sheet discharging direction which are set based on the maximum sheet size as being smaller than the sheet discharge space **15** of the later-mentioned image forming unit A.

(31) Sheet Introducing Path (Sheet Discharging Path)

(32) As illustrated in FIG. 3, the sheet introducing path **22** (hereinafter, called a sheet discharging path) having an introducing port **21** and a discharging port **23** is arranged at the abovementioned apparatus housing **20**. In FIG. 3, the sheet discharging path **22** is structured as receiving a sheet in the horizontal direction and discharging the sheet from the discharging port **23** after conveying approximately in the horizontal direction. The sheet discharging path **22** includes an appropriate paper guide (plate) **22a** and incorporates a feeder mechanism which conveys a sheet. The feeder

mechanism is structured with pairs of conveying rollers arranged at predetermined intervals in accordance with a path length. In FIG. 3, a pair of introducing rollers **31** is arranged in the vicinity of the introducing port **21** and a pair of discharging rollers **32** is arranged in the vicinity of the discharging port **23**. A sheet sensor **Se1** to detect a sheet leading end and/or a sheet tailing end is arranged at the sheet discharging path **22**.

(33) The sheet discharging path **22** includes a linear path arranged approximately in the horizontal direction as traversing the apparatus housing **20**. Here, a sheet is prevented from receiving stress which is caused by a curved path. Accordingly, the sheet discharging path **22** is formed as having linearity which is allowed by apparatus layout. The pair of introducing rollers **31** and the pair of discharging rollers **32** are connected to the same driving motor **M1** (hereinafter, called a conveying motor) and convey a sheet at the same circumferential speed.

(34) Processing Tray

(35) As illustrated in FIG. 3, the processing tray **24** is arranged at the downstream side of the sheet discharging port **23** of the sheet discharging path **22** as forming a step d therefrom. For upward stacking of sheets fed from the sheet discharging port **23** into a bundle shape, the processing tray **24** includes a sheet placement face **24a** which supports at least a part of the sheets. FIG. 3 illustrates a structure (bridge-support structure) in which a sheet leading end side is supported by the later-mentioned stack tray **25** and a sheet tailing end side is supported by the processing tray **24**. Thus, the processing tray **24** is downsized.

(36) At the processing tray **24**, there are arranged a stapling unit **26** being a first binding device to staple-bind a sheet bundle using a staple, a press binding unit **27** being a second binding device to perform a non-staple binding process without using a staple by pressing a sheet bundle so that a section thereof is in a corrugated state, a sheet introducing device **35** to introduce sheets, a sheet end regulating device **40** to stack introduced sheets into a bundle shape, an aligning device **45**, and a sheet bundle discharging mechanism **60**. According to the above, on the processing tray **24**, sheets fed from the sheet discharging port **23** are stacked into a bundle shape, and a binding process is performed by a binding device being either the stapling unit **26** or the press binding unit **27** after the sheets are aligned into a predetermined posture. Subsequently, the processed sheet bundle is discharged to the stack tray **25** at the downstream side. Since the press binding unit **27** operates without using a staple as being advantageous in resource saving, the binding process with the press binding unit **27** is hereinafter called eco-binding.

(37) Sheet Introducing Mechanism (Sheet Introducing Device)

(38) Since the processing tray **24** is arranged as forming the step d from the sheet discharging port **23**, it is required to arrange the sheet introducing device **35** which smoothly conveys a sheet onto the processing tray **24** with a correct posture. In the drawings, the sheet introducing device **35** (friction rotor) is structured with a lifting-lowering paddle rotor **36**. When a sheet tailing end is discharged from the sheet discharging port **23** onto the processing tray **24**, the paddle rotor **36** conveys the sheet in a direction (rightward in FIG. 3) opposite to the sheet discharging direction, so that the sheet is abutted to later-mentioned sheet end regulating device **40** to be aligned (positioned).

(39) A lifting-lowering arm **37** which is axially-supported swingably by a support shaft **37x** at the apparatus frame **20a** is arranged at the discharging port **23**. The paddle rotor **36** is axially-supported rotatably at a top end part of the lifting-lowering arm **37**. A pulley (not illustrated) is arranged at the support shaft **37x** and the abovementioned conveying motor **M1** is connected to the pulley.

(40) In addition, a lifting-lowering motor (hereinafter, called a paddle lifting-lowering motor) **M3** is connected to the lifting-lowering arm **37** via a spring clutch (torque limiter) and is structured so that the lifting-lowering arm **37** is lifted and lowered with rotation of the lifting-lowering motor **M3** between a waiting position **Wp** at the upper side and an operating position (sheet engaging position) **Ap** at the lower side. That is, the spring clutch lifts the lifting-lowering arm **37** from the operation position **Ap** to the waiting position **Wp** with rotation of the paddle lifting-lowering motor

M3 in one direction and keeps the lifting-lowering arm 37 waiting at the waiting position Wp after abutting to a stopper (not illustrated). On the contrary, the spring clutch is released with rotating of the paddle lifting-lowering motor M3 in the opposite direction, so that the lifting-lowering arm 37 is lowered under own weight thereof from the waiting position Wp to the operating position Ap at the lower side to be engaged with the upmost sheet.

(41) In the illustrated apparatus, a pair of the paddle rotors 36 are arranged in a bilaterally symmetric manner with respect to a sheet center Sx (center reference) as being apart by a predetermined distance, as illustrated in FIG. 5. Alternatively, three paddle rotors in total may be arranged at the sheet center and both sides thereof, or one paddle rotor may be arranged at the sheet center.

(42) The paddle rotor 36 is structured with a flexible rotor formed of a rubber-made plate-shaped member, plastic-made blade member, or the like. Instead of the paddle rotor 36, it is possible that the sheet introducing device 35 is structured with a friction rotating member such as a roller body and a belt body. In the above description, the illustrated apparatus includes the mechanism with which the paddle rotor 36 is lowered from the waiting position Wp at the upper side to the operating position Ap at the lower side after a sheet tailing end is discharged from the discharging port 23. However, instead of the above, it is possible to adopt a lifting-lowering mechanism described below.

(43) With a lifting-lowering mechanism being different from the illustrated mechanism, for example, when a sheet leading end is discharged from the discharging port 23, a friction rotor is lowered from a waiting position to an operating position and rotated concurrently in the sheet discharging direction. Then, at the timing when a sheet tailing end is discharged from the discharging port 23, the friction rotor is reversely rotated in a direction opposite to the sheet discharging direction. According to the above, it is possible that the sheet discharging from the discharging port 23 is conveyed to a predetermined position of the processing tray 24 at high speed without being skewed.

(44) Raking Rotor

(45) A raking rotor 33 is arranged so that a sheet tailing end (a leading end in the sheet discharging direction) of a curled sheet or a skewed sheet is reliably guided to a regulating device 40 at the downstream side when a sheet is conveyed to a predetermined position of the processing tray 24 by the paddle rotor 36. The raking rotor 33 is arranged below the pair of sheet discharging rollers 32 and guides a sheet fed by the paddle rotor 36 to the regulating device 40. The raking rotor 33 is structured with a ring-shaped belt member 34 (FIG. 4) and conveys the upmost sheet on the processing tray 24 to the regulating device 40 as being abutted thereto.

(46) The illustrated apparatus includes a raking rotor (raking-conveying device) 33 which applies a conveying force, to a regulating member side, on the upmost sheet of the sheets stacked at the upstream side of the later-mentioned sheet end regulating stopper 40 below the pair of sheet discharging rollers 32. In the drawings, a ring-shaped belt member (hereinafter, called a raking belt) 34 is arranged above the top end part of the processing tray 24. The raking belt 34 is engaged with the upmost sheet on the sheet placement face 24a and rotated in a direction to convey the sheet toward the regulating member side.

(47) The raking belt 34 is structured with a belt member (roulette belt, or the like) having a high frictional force made of soft material such as rubber material. The raking belt 34 is nipped and supported between an idle shaft 34y and a rotating shaft 34x which is connected to a drive motor (in the drawing, the conveying motor M1 is commonly used). A rotational force in the counterclockwise direction in FIG. 3 is applied to the raking belt 34 from the rotating shaft 34x. Along with the above, the raking belt 34 presses a sheet introduced along the upmost sheet stacked on the processing tray 24 and causes a leading end of the sheet to be abutted to the regulating stopper 40 at the downstream side.

(48) The raking belt 34 is configured to be moved upward and downward above the upmost sheet

on the processing tray **24** by a belt shifting motor (hereinafter, called a roulette lifting-lowering motor) **M5**. Here, a lifting-lowering mechanism therefor is skipped. At the timing when a sheet leading end enters between a belt face and the upmost sheet, the raking belt **34** is lowered and engaged with the introduced sheet. When a sheet bundle is conveyed from the processing tray **24** to the stack tray **25** at the downstream side by a sheet bundle conveying device **60** as described later, the roulette motor **M5** is controlled so that the raking belt **34** is separated from the upmost sheet and kept waiting at the upper side.

(49) Sheet Aligning Mechanism

(50) A sheet aligning mechanism **45** which performs positioning of an introduced sheet at a predetermined position (processing position) is arranged at the processing tray **24**. The sheet aligning mechanism **45** in the drawings includes the sheet end regulating device **40** which positionally regulates an end face (a leading end face or a tailing end face) in the sheet discharging direction of the sheet fed from the discharging port **23** and a side aligning device **45** which performs biasing and aligning in a direction (sheet side direction) perpendicular to the sheet discharging direction. In the following, description will be performed in the order thereof.

(51) Sheet End Regulating Device

(52) The illustrated sheet end regulating device **40** includes a tailing end regulating member **41** which performs regulation with abutting against a sheet tailing end in the sheet discharging direction. The tailing end regulating member **41** includes a regulating face **41a** which performs regulation with abutting the tailing end in the sheet discharging direction of the sheet introduced along the sheet placement face **24a** of the processing tray **24**. The tailing end regulating member **41** causes the tailing end of the sheet fed by the abovementioned raking rotor **33** to be abutted and stopped.

(53) When multi-binding is performed with the later-mentioned stapling unit **26**, the stapling unit **26** is moved along a sheet tailing end (in a direction perpendicular to the sheet discharging direction). To prevent obstruction against movement of the stapling unit **26**, the tailing end regulating member **41** is configured to adopt any one of the structures of: (1) adopting a mechanism with which the tailing end regulating member proceeds to and retracts from a movement path (motion trajectory) of the binding unit, (2) adopting a mechanism with which the tailing end regulating member is moved integrally with the binding unit, and (3) forming the tailing end regulating member, for example, as a channel-shaped folded piece arranged at the inside of a binding space which is formed by a head and an anvil of the binding unit.

(54) The illustrated tailing end regulating member **41** includes a plate-shaped folded member whose section has a U-shape (channel shape) arranged in the binding space of the stapling unit **26**. Here, a first member **41A** is arranged at the sheet center based on the minimum sheet size, and second and third members **41B**, **41C** are arranged bilaterally as being mutually distanced (see FIG. 5). According to the above, the stapling unit **26** is allowed to be moved in a sheet width direction.

(55) As illustrated in FIGS. 5 and 7, a plurality of the tailing end regulating members **41** formed of channel-shaped folded pieces is fixed to the processing tray **24** as top end parts thereof being fixed to a back face wall of the processing tray **24** with screws. The regulating face **41a** is formed at each of the tailing end regulating member **41** and an inclined face **41b** which guides a sheet end to the regulating face **41a** is continuously formed at a top end part of the folding thereof.

(56) Side Aligning Device

(57) The processing tray **24** is provided with an aligning device **45** which performs positioning of a sheet abutted to the abovementioned tailing end regulating member **41** in a direction perpendicular to the sheet discharging direction (sheet width direction).

(58) The aligning device **45** is structured differently based on whether sheets having different sizes are aligned on the processing tray **24** in center reference or side reference. In the apparatus illustrated in FIG. 5, sheets of different sizes are discharged from the discharging port **23** in the center reference and the sheets are aligned on the processing tray **24** in the center reference. A

binding process is performed by the stapling unit **26** on a sheet bundle which is aligned into a bundle shape in center reference, in accordance with the binding process, at binding positions **Ma1**, **Ma2** in an aligned posture for multi-binding and at binding positions **Cp1**, **Cp2** with the sheet bundle offset by a predetermined amount in the width direction for a lateral corner binding.

(59) As illustrated in FIG. **6**, the aligning device **45** includes a right side aligning member **46F** (at the apparatus front side) and a left side aligning member **46R** (at the apparatus rear side). Slit grooves **24x** penetrating the sheet placement face **24a** are formed at the processing tray **24**. The right side aligning member **46F** and the left side aligning member **46R** are fitted to the slit grooves **24x** and attached to the processing tray **24** as protruding thereabove. Each of the side aligning plates **46F**, **46R** is integrally formed with a rack **47** and is slidably supported by a plurality of guide rollers **49** (or rail members) at the back face side of the processing tray **24**. Aligning motors **M6**, **M7** are connected to the right-left racks **47** respectively via a pinion **48**. The right-left aligning motors **M6**, **M7** are structured with stepping motors. Positions of the right-left aligning plates **46F**, **46R** are detected by position sensors (not illustrated). Based on the detected values, the side aligning plates **46F**, **46R** can be moved respectively in either right or left direction by specified movement amounts.

(60) The side aligning plates **46F**, **46R** slidable on the sheet placement face **24a** have regulating faces **46x** which abut to side edges of a sheet. Here, the regulating faces **46x** can reciprocate by a predetermined stroke mutually in a closing direction or a separating direction. The stroke is determined from difference between the maximum sheet size and the minimum sheet size and the offset amount of positional movement (offset conveyance) of an aligned sheet bundle rightward or leftward. That is, the movement stroke of the right-left side aligning plates **46F**, **46R** is determined from a movement amount for aligning sheets having different sizes and the offset amount of the aligned sheet bundle. Here, not limited to the illustrated rack-pinion mechanism, it is also possible to adopt a structure that the side aligning plates **46F**, **46R** are fixed to a timing belt and the timing belt is connected to a motor via a pulley to reciprocate laterally.

(61) According to the above structure, binding process controller **75** causes the right-left side aligning members **46F**, **46R** at predetermined waiting positions (distanced by a sheet width+ α therebetween) based on sheet size information which is provided from the image forming unit **A** or the like. In the above state, a sheet is introduced onto the processing tray **24**. At the timing when a sheet end is abutted to the sheet end regulating member **41**, aligning operation is started. In the aligning operation, the right-left aligning motors **M6**, **M7** are rotated in opposite directions (closing directions) by the same amount. Accordingly, sheets introduced onto the processing tray **24** are stacked in a bundle shape as being positioned in reference to the sheet center. According to repetition of the introducing operation and the aligning operation, sheets are collated and stacked on the processing tray **24** in a bundle shape. Here, sheets of different sizes are positioned in center reference.

(62) It is possible to perform a binding process at a plurality of positions at a predetermined interval (i.e., multi-binding process) on the sheets stacked on the processing tray **24** in center reference as described above in the above posture at a tailing end (or a leading end) of the sheets. In a case of performing a binding process on a sheet corner, one of the right-left side aligning members **46F**, **46R** is moved to and stopped at a position where a sheet side end is matched with a specified binding position. Then, the side aligning member at the opposite side is moved in the closing direction. A movement amount in the closing direction is calculated in accordance with a sheet size. Accordingly, a sheet introduced onto the processing tray **24** is aligned so that a right side end is matched with a binding position in a case of right corner binding and a left side end is matched with a binding position in a case of left corner binding.

(63) When a sheet bundle aligned at a predetermined position on the processing tray **24** as described above is offset-moved for a later-mentioned eco-binding process, (1) drive control that the aligning member at the rear side in the movement direction is moved in a direction

perpendicular to the sheet conveying direction by a previously set amount in a state that the aligning member at the front side in the movement direction is retracted to a position being apart from an offset assumed position, or (2) drive control that the right-left aligning members are moved in a direction perpendicular to the sheet conveying direction by the same amount.

(64) Here, position sensors (not illustrated) such as a position sensor and an encode sensor are arranged at the right-left side aligning members **46F**, **46R** and the aligning motors **M6**, **M7** therefor to detect positions of the side aligning members **46F**, **46R**. Owing to that the aligning motors **M6**, **M7** are structured with stepping motors, home positions of the side aligning members **46F**, **46R** are detected by position sensors (not illustrated), and the motors are PWM-controlled, the right-left side aligning members **46F**, **46R** can be controlled with a relatively simple control configuration.

(65) Sheet Bundle Discharging Mechanism

(66) Next, the sheet bundle discharging mechanism (sheet bundle discharging device **60**) illustrated in FIG. **11** will be described. The sheet bundle discharging mechanism which discharges a sheet bundle bound by the stapling unit **26** or the press binding unit **27** to the stack tray **25** at the downstream side is arranged at the abovementioned processing tray **24**. At the processing tray **24** described based on FIG. **5**, the first sheet tailing end regulating member **41A** is arranged at the sheet center **Sx** and the second and third sheet tailing end regulating members **41B**, **41C** are arranged bilaterally as being mutually distanced. A sheet bundle stopped by the regulating members **41** is to be discharged to the stack tray **25** at the downstream side after a binding process is performed thereon by the stapling unit **26** or the press binding unit **27**.

(67) The sheet bundle discharging device **60** is arranged along the sheet placement face **24a** of the processing tray **24**. The illustrated sheet bundle discharging device **60** includes a first conveying member **60A** and a second conveying member **60B**. Here, conveyance in a first zone **L1** on the processing tray **24** is performed by the first conveying member **60A** and conveyance in a second zone **L2** is performed by the second conveying member **60B**, so that relay conveyance is performed. Since a sheet bundle is conveyed serially by the first and second conveying members **60A**, **60B**, mechanisms of the first and second conveying members **60A**, **60B** can be differently arranged. Here, it is required that the member which conveys a sheet bundle from a starting point being approximately the same as the sheet tailing end regulating device **40** is formed of a less swaying member (elongated supporting member) and a member which causes the sheet bundle to drop at an end point of conveyance is downsized (for travelling on a loop trajectory).

(68) The first conveying member **60A** is structured with a first discharging member **61** formed of a folded piece whose section has a channel shape. The first discharging member **61** includes a stopper face **61a** which stops a tailing end face of a sheet bundle, and a sheet face pressing member **62** (an elastic film member; Mylar piece) which presses an upper face of the sheet bundle stopped by the stopper face **61a**. As illustrated in the drawing, the first conveying member **60A** is formed of a folded piece whose section has a channel shape. Accordingly, fixed to a later-mentioned carrier member **65a** (belt), the first conveying member **60A** moves (feeds) the tailing end of the sheet bundle in the conveying direction as travelling integrally with the belt with less swaying. The first conveying member **60A** reciprocates with a stroke **Str1** on an approximately linear trajectory without travelling on a loop trajectory curved as described later.

(69) The second conveying member **60B** is structured with a second discharging member **63** which has a pawl shape. The second discharging member **63** includes a stopper face **63a** which stops a tailing end face of a sheet bundle, and a sheet face pressing member **64** which presses an upper face of the sheet bundle. The sheet face pressing member **64** having a sheet face pressing face **64a** is swingably axis-supported by the second discharging member **63**. An urging spring **64b** is arranged to cause the sheet face pressing face to press the upper face of the sheet bundle.

(70) The sheet face pressing face **64a** is formed as an oblique face oblique to a travelling direction as illustrated and is engaged with the tailing end of the sheet with a setting angle of γ when moved in the arrow direction in FIG. **11B**. At that time, the sheet face pressing face **64a** is deformed

upward (counterclockwise in FIG. 11C) in the arrow direction against the urging spring **64b**. Then, the sheet face pressing face **64a** presses the upper face of the sheet bundle toward the sheet placement face **24a** side by the action of the urging spring **64b**.

(71) According to the above structure, the first discharging member **61** reciprocate with the first carrier member **65a** and the second discharging member **63** reciprocate with a second carrier member **65b** between a base end part and an exit end part of the sheet placement face **24a**. Driving pulleys **66a**, **66b** and a driven pulley **66c** are arranged at the sheet placement face **24a** as being mutually distanced by the conveyance stroke. Idling pulleys **66d**, **66e** are arranged as illustrated in FIG. 10A.

(72) The first carrier member **65a** (toothed belt in the drawings) is routed between the driving pulley **66a** and the driven pulley **66c**. The second carrier member **65b** (toothed belt) is routed between the driving pulley **66b** and the driven pulley **66c** via the idling pulleys **66d**, **66e**. A drive motor M4 is connected to the driving pulleys **66a**, **66b**. Here, the first driving pulley **65a** is formed to have a small diameter and the second driving pulley **65b** is formed to have a large diameter so that rotating of the drive motor M4 is transmitted to the first carrier member **65a** at a low speed and to the second carrier member **65b** at a high speed.

(73) That is, the first conveying member **60A** and the second conveying member **60B** are connected, to travel respectively at a low speed and a high speed, commonly to the drive motor M4 via a decelerating mechanism (belt pulleys, gear coupling, or the like). In addition, a cam mechanism is incorporated in the second driving pulley **66b** to delay the drive transmission. This is, as described later, because of difference between the movement stroke Str1 of the first conveying member **60A** and the movement stroke Str2 of the second conveying member **60B** and positional adjustment of waiting positions of the respective members.

(74) According to the above structure, the first conveying member **60A** reciprocates on a linear trajectory with the first stroke Str1 from the tailing end regulation position of the processing tray **24**. Here, the first zone Tr1 is set within the first stroke Str1. The second conveying member **60B** reciprocates on a semi-loop trajectory with the second stroke Str2 from the first zone Tr1 to the exit end of the processing tray **24**. Here, the second zone Tr2 is set within the second stroke Str2.

(75) The first conveying member **60A** is moved from the sheet tailing end regulation position to the downstream side (from FIG. 11A to FIG. 11B) at a speed V1 with rotation in one direction of the drive motor M4 to convey the sheet bundle as pushing the tailing end thereof with the stopper face **61a**. Being delayed by a predetermined time from the first conveying member **60A**, the second conveying member **60B** projects above the sheet placement face **24a** from the waiting position (FIG. 11A) at the back face side of the processing tray **24** and is moved at a speed V2 as following the first conveying member **60A** in the same direction. Here, since the speed V2 is set to be higher than the speed V1, the sheet bundle on the processing tray **24** is relayed from the first conveying member **60A** to the second conveying member **60B**.

(76) FIG. 11B illustrates a state of the relay conveyance. The second conveying member **60B** travelling at the speed V2 catches up with the sheet bundle travelling at the speed V1. That is, after passing through the first zone Tr1, the second conveying member **60B** catches up with the first conveying member **60A** and performs conveyance to the downstream side in the second zone Tr2 as being engaged with the tailing end face of the sheet bundle.

(77) When the second conveying member **60B** is abutted, at the relay point at a high speed, to the sheet bundle travelling at the speed V1, the sheet bundle is discharged toward the stack tray **25** while the tailing end of the sheet bundle is held as being nipped between the sheet face pressing member **64** and the carrier member (belt) **65a** (**65b**) with the upper face of the sheet bundle pressed by sheet face pressing face **64a**.

(78) Method of Binding Process (Binding Position)

(79) As described above, sheets conveyed to the introducing port **21** of the sheet discharging path **22** are collated and stacked on the processing tray **24** and positioned (aligned) by the sheet end

regulating member **40** and the side aligning members **46F**, **46R** at the previously-set location and in the previously-set posture. Thereafter, a binding process is performed on the sheet bundle and the sheet bundle is discharged to the stack tray **25** at the downstream side. In the following, a method of the binding process is described.

(80) Multi-binding positions **Ma1**, **Ma2** where sheets are staple-bound at a plurality of positions, corner binding positions **Cp1**, **Cp2** where sheets are bound at a corner, a manual binding position **Mp** where a binding process is performed on manually-set sheets, and an eco-binding position **Ep** where sheets are bound at a corner by the press binding unit **27** without using a staple are defined for performing a binding process with the stapling unit **26** or the press binding unit **27** on a sheet bundle aligned into a bundle shape in center reference by the side aligning members **46F**, **46R**. In the following, positional relation among the respective binding positions will be described.

(81) Multi-Binding

(82) As illustrated in FIG. 5, in the multi-binding process, a sheet bundle positioned on the processing tray **24** by the sheet end regulating member **41** and the side aligning members **46F**, **46R** (hereinafter, called an aligned sheet bundle) is bound at an end edge (a tailing end edge in the drawings). The multi-binding positions **Ma1**, **Ma2** where a binding process is performed on two distanced positions is defined in a sheet introducing area **Ar** on the processing tray **24** as illustrated in FIG. 9. The later-mentioned stapling unit **26** is moved from a home position to the binding position **Ma1** and the binding position **Ma2** in the order thereof and performs a binding process respectively at the binding positions **Ma1**, **Ma2**. Here, not limited to two positions, the binding process may be performed at three or more positions as the multi-binding positions **Ma**. FIG. 12A illustrates a multi-bound state.

(83) Corner Binding

(84) The corner binding process defines binding positions as two bilateral positions being a right corner binding position **Cp1** where a binding process is performed on a right corner on an aligned sheet bundle stacked on the processing tray **24** and a left corner binding position **Cp2** where a binding process is performed on a left corner of an aligned sheet bundle. Here, the binding process is performed with a staple being oblique by a predetermined angle (approximately between 30 to 60 degrees). The later-mentioned stapling unit **26** is mounted on the apparatus frame with the entire unit being oblique by the predetermined angle thereat. FIGS. 12B and 12C illustrate corner-bound states.

(85) FIGS. 12B and 12C illustrate cases that the binding process is performed on either the right or left of a sheet bundle by selection while a staple is set oblique by the predetermined angle. Not limited to the above, even in a case that binding is performed on only one of the right and left corners, it is also possible to adopt a structure that the binding is performed with a staple being parallel to a sheet end edge without being oblique.

(86) Manual Binding

(87) In the illustrated apparatus, it is possible to perform a binding process with the stapling unit **26** on sheets which are inserted to a predetermined insertion portion from the outside of the apparatus. Here, a manual setting face **29a** for setting a sheet bundle from the outside into a manual-feeding area **Fr** which is adjacent to the sheet placement face **24a** via the side frame **20c** is arranged at the external casing **20b**. The sheet placement face **24a** and the manual setting face **29a** are arranged in parallel approximately at the same height so as to be capable of supporting sheets approximately at horizontal posture.

(88) As illustrated in FIG. 5, the manual binding position **Mp** is arranged at the manual setting face **29a** on the same straight line as the multi-binding positions **Ma1**, **Ma2**. Here, owing to that the stapling unit **26** is moved from the sheet introducing area **Ar** of the processing tray **24** to the manual feeding area **Fr**, a binding process is performed on a sheet bundle at the manual binding position **Mp**. Thus, the manual setting face **29a** structures the insertion portion to which a sheet bundle for manual binding is inserted.

(89) Eco-Binding Position

(90) The eco-binding position E_p is defined so that a binding process is performed on a side edge part (corner part) of sheets as illustrated in FIG. 5. The illustrated eco-binding position E_p is defined at a position where the binding process is performed on one position at the side edge part in the sheet discharging direction of a sheet bundle. Then, the binding process is performed as being oblique to sheets by a predetermined angle. The eco-binding position E_p is defined in the eco-binding area R_r which is distanced to the apparatus rear side from the sheet introducing area A_r of the processing tray 24.

(91) Mutual Relation Among Respective Binding Positions

(92) The multi-binding positions Ma_1 , Ma_2 are defined in the sheet introducing area A_r (at the inside thereof) where sheets are introduced to the processing tray 24 from the sheet discharging port 23. Each of the corner binding positions Cp_1 , Cp_2 is defined outside the sheet introducing area A_r at a reference position which is apart rightward or leftward (side alignment reference) by a predetermined distance from the sheet discharging reference S_x (center reference). As illustrated in FIG. 6, at the outer side from a side edge of a maximum size of sheets to be bound, the right corner binding position Cp_1 is defined at a position deviated rightward from a sheet side edge by a predetermined amount (δ_1) and the left corner binding position Cp_2 is defined at a position deviated leftward from a sheet side edge by a predetermined amount (δ_2). The deviation amounts are set to be the same ($\delta_1 = \delta_2$).

(93) The manual binding position M_p is defined approximately on the same straight line as the multi-binding positions Ma_1 , Ma_2 . Further, the corner binding positions Cp_1 , Cp_2 are defined at positions each having an oblique angle (e.g., 45 degrees) to be bilaterally symmetric about the sheet discharging reference S_x .

(94) The manual binding position M_p is defined in the manual-feeding area F_r in the apparatus front side and outside the sheet introducing area A_r . The eco-binding position E_p is defined in the eco-binding area R_r at the apparatus rear side R_e and outside the sheet introducing area A_r .

(95) Further, the manual binding position M_p is defined at a position which is offset by a predetermined amount (Of_1) from the right corner binding position Cp_1 of the processing tray 24. The eco-binding position E_p is defined at a position which is offset by a predetermined amount (Of_2) from the left corner binding position Cp_2 of the processing tray 24. Thus, the multi-binding positions Ma_1 , Ma_2 are defined based on the sheet discharging reference (center reference) of the processing tray 24 to which sheets are introduced, and the corner binding positions Cp_1 , Cp_2 are defined based on the maximum sheet size. Further, the manual binding position M_p is defined at the position which is offset by the predetermined amount (Of_1) from the right corner binding position Cp_1 to the apparatus front side. Similarly, the eco-binding position E_p is defined at the position which is offset by the predetermined amount (Of_2) from the left corner binding position Cp_2 to the apparatus rear side. According to the above, arrangement can be performed in an orderly manner without causing interference of sheet movement.

(96) Next, the sheet movement for the respective binding processes is described. In the multi-binding process, sheets are introduced to the processing tray 24 in center reference (or side reference) and aligned in the above state, and then, the binding process is performed thereon. After the binding process is performed, the sheets are discharged to the downstream side in the above posture. In the corner binding process, sheets are aligned at the alignment position at a specified side and the binding process is performed thereon. After the binding process is performed, the sheets are discharged to the downstream side in the above posture. In the eco-binding process, sheets introduced onto the processing tray 24 are offset by the predetermined amount Of_2 to the apparatus rear side after being stacked into a bundle shape. The binding process is performed thereon after the offset movement. After the binding process, the sheets are offset by a predetermined amount (for example, being the same as or smaller than the offset Of_2) to the sheet center side and discharged to the downstream side thereafter.

(97) Further, in the manual binding, an operator sets sheets on the manual setting face **29a** as being offset by the predetermined amount **Of1** from the alignment reference which is positioned at the front side from the processing tray **24**. According to the above, a plurality of the binding processes are performed while sheet setting positions therefor are defined in the direction perpendicular to the sheet conveying direction. Therefore, sheet jamming can be suppressed while keeping high processing speed.

(98) In the eco-binding process, the later-mentioned binding process controller **75** defines the eco-binding position **Ep** with sheets offset by a predetermined amount **Of3** in the sheet discharging direction from the tailing end reference position. This is to avoid interference between the stapling unit **26** for the left corner binding and an eco-binding unit (press binding unit **27** described later). Here, if the press binding unit **27** is mounted on the apparatus frame **20a** movably between the binding position and a retracting position retracting therefrom similarly to the stapling unit **26**, sheets are not required to be offset by the amount **Of3** in the sheet discharging direction.

(99) Here, the apparatus front side **Fr** denotes a front side of the external casing **20b** set by apparatus designing where various kinds of operation are performed by an operator. Normally, a control panel, a mount cover (door) for a sheet cassette, and an open-close cover through which staples are replenished for a stapling unit are arranged at the apparatus front side. Further, the apparatus rear side **Re** denotes a side of the apparatus facing to a wall face of a building, for example, when the apparatus is installed (installation conditions; the back face is designed to face a wall).

(100) Thus, in the illustrated apparatus, the manual binding position **Mp** is defined at the apparatus front side **Fr** and the eco-binding position **Ep** is defined at the apparatus rear side **Re** outside the sheet introducing area **Ar** with reference thereto. A distance **Ofx** between the manual binding position **Mp** and the reference of the sheet introducing area **Ar** (sheet introducing reference **Sx**) is set larger than a distance **Ofy** between the eco-binding position **Ep** and the sheet introducing reference **Sx** (i.e., $Ofx > Ofy$).

(101) Thus, the manual binding position **Mp** is defined to be apart from the sheet introducing reference **Sx** of the processing tray **24** and the eco-binding position **Ep** is defined to be close to the sheet introducing reference **Sx**. This is because operation of setting a sheet bundle to the manual binding position **Mp** from the outside is facilitated to be convenient owing to that the manual binding position **Mp** is apart from the processing tray **24**. Further, the eco-binding position **Ep** is defined to be close to the sheet introducing reference **Sx**. This is because the movement amount when sheets (aligned sheet bundle) introduced onto the processing tray **24** are offset-moved to the eco-binding position **Ep** can be small for speedy performance of the binding process (i.e., improvement of productivity).

(102) Moving Mechanism for Stapling Unit

(103) The stapling unit **26** includes a unit frame **26a** (first unit frame), a staple cartridge **39**, a stapling head **26b**, and an anvil member **26c**. Structures thereof will be described later. The stapling unit **26** is supported by the apparatus frame **20a** to reciprocate by a predetermined stroke along a sheet end face of the processing tray **24**. The supporting structure will be described in the following.

(104) FIG. 7 illustrates a front structure that the stapling unit **26** is attached to the apparatus frame **20a** and FIG. 8 illustrates a plane structure thereof. FIGS. 9 and 10 illustrate partial explanatory views of a guide rail mechanism which guides the stapling unit **26**.

(105) As illustrated in FIG. 7, a chassis frame (hereinafter, called a bottom frame) **20e** is attached to the right-left side frames **20c**, **20d** structuring the apparatus frame **20a**. The stapling unit **26** is mounted on the bottom frame **20e** to be movable by the predetermined stroke. A travel guide rail (hereinafter, simply called a guide rail) **42** and a slide cam **43** are arranged at the bottom frame **20e**. A travel rail face **42x** is formed at the guide rail **42** and a travel cam face **43x** is formed at the slide cam **43**. The travel rail face **42x** and the travel cam face **43x** in mutual cooperation support the

stapling unit **26** to be capable of reciprocating by the predetermined stroke and control the angular posture thereof.

(106) The travel rail face **42x** and the travel cam face **43x** are formed so that the travel guide rail **42** and the slide cam **43** allows the stapling unit **26** to reciprocate within a movement range SL (the sheet introducing area Ar, the manual-feeding area Fr, and the eco-binding area Rr) (see FIG. 8). The travel guide rail **42** is structured with a rail member having the stroke SL along the tailing end regulating member **41** of the processing tray **24**. In the drawing, the travel guide rail **42** is structured as an opening groove formed at the bottom frame **20e**. The travel rail face **42x** is formed at the edge of the opening and is arranged on the same straight line as the tailing end regulating member **41** of the processing tray **24** as being in parallel thereto. The slide cam **43** is arranged as being distanced from the travel rail face **42x**. In the drawing, the slide cam **43** is structured with a groove cam which is formed at the bottom frame **20e**. The travel cam face **43x** is formed at the groove cam.

(107) A drive belt **44** connected to a drive motor M11 is fixed to the stapling unit **26**. The drive belt **44** is wound around a pair of pulleys axially supported by the apparatus frame **20a**. The drive motor M11 is connected to one of the pulleys. Thus, the stapling unit **26** reciprocates by the stroke SL with forward and reverse rotation of the drive motor M11.

(108) The travel rail face **42x** and the travel cam face **43x** are arranged to include a parallel distance sections **43a**, **43b** (having a span G1) where the faces are in parallel, a narrow slant distance sections **43c**, **43d** (having a span G2), and a narrower slant distance section **43e** (having a span G3). Here, the spans satisfies the relation of " $G1 > G2 > G3$ ". The span G1 causes the stapling unit **26** to be in a posture as being in parallel to a sheet tailing end edge. The span G2 causes the stapling unit **26** to be in a slant posture rightward or leftward. The span G3 causes the stapling unit **26** to be in a posture slant at a larger angle. Thus, the angle of the stapling unit **26** is varied.

(109) Not limited to the opening groove structure, the travel guide rail **42** may adopt a variety of structures such as a guide rod, a projection rib, and others. Further, not limited to the groove cam, the slide cam **43** may adopt a variety of shapes as long as having a cam face to guide the stapling unit **26** in a predetermined stroke direction, such as a projection stripe rib member.

(110) The stapling unit **26** is engaged with the travel guide rail **42** and the slide cam **43** as follows. As illustrated in FIG. 7, the stapling unit **26** is provided with a first rolling roller (rail fitting member) **50** that is engaged with the travel rail face **42x** and a second rolling roller (cam follower member) **51** that is engaged with the travel cam face **43x**. Further, the stapling unit **26** is provided with a sliding roller **52** that is engaged with a support face of the bottom frame **20e**. The illustrated stapling unit **26** includes two ball-shaped sliding rollers **52a**, **52b** at two positions thereof. Further, a guide roller **53** that is engaged with a bottom face of the bottom frame **20e** is formed at the stapling unit **26** to prevent the stapling unit **26** floating from the bottom frame **20e**.

(111) According to the above structure, the stapling unit **26** is supported by the bottom frame **20e** movably via the sliding rollers **52a**, **52b** and the guide roller **53**. Further, the first rolling roller **50** and the second rolling roller **51** are rotated and moved along the travel rail face **42x** and the travel cam face **43x** respectively as following the travel rail face **42x** and the travel cam face **43x** respectively.

(112) The travel rail face **42x** and the travel cam face **43x** are arranged so that the parallel distance sections (having the span G1) are arranged at the position **43a** corresponding to the abovementioned multi-binding positions Ma1, Ma2 and the position **43b** corresponding to the manual binding position Mp. With the span G1, the stapling unit **26** is maintained in a posture as being perpendicular to a sheet end edge without being slant, as illustrated in FIGS. 9 and 10C. Accordingly, at the multi-binding positions Ma1, Ma2 and the manual binding position Mp, a sheet bundle is bound with a staple being in parallel to a sheet end edge.

(113) Further, the travel rail face **42x** and the travel cam face **43x** are arranged so that the slant distance sections (having the span G2) are arranged at the position **43c** corresponding to the right

corner binding position Cp1 and the position 43d corresponding to the left corner binding position Cp2. The stapling unit 26 is maintained in a rightward-angled posture (for example, rightward-angled by 45 degrees) or in a leftward-angled posture (for example, leftward-angled by 45 degrees), as illustrated in FIGS. 9 and 10A.

(114) Further, the travel rail face 42x and the travel cam face 43x are arranged so that the slant distance section (having the span G3) is arranged at the position 43e corresponding to a position for staple loading. The span G3 is formed to be shorter than the span G2. In this state, the stapling unit 26 is maintained in a rightward-angled posture (for example, rightward-angled by 60 degrees) as illustrated in FIG. 10B. The reason why the angular posture of the stapling unit 26 is varied at the staple loading position is that the posture is matched with an angular direction in which the staple cartridge 39 is mounted thereon. Here, the angle is set in relation with the open-close cover arranged at the external casing 20b.

(115) For varying the angular posture of the stapling unit 26 using the travel rail face 42x and the travel cam face 43x, it is preferable from a viewpoint of layout compactification to arrange a second travel cam face or a stopper cam face for angle varying in cooperation with the travel cam face 43x.

(116) Next, the stopper cam face will be described with reference to FIG. 8. As illustrated in FIG. 8, stopper faces 43y, 43z to be engaged with a part of the stapling unit 26 (in the drawing, the sliding roller 52a) are arranged at the side frame 20e to vary a posture of the stapling unit between the right corner binding position Cp1 and the manual binding position Mp at the apparatus front side. The stapling unit 26 inclined at the staple loading position is required to be corrected in inclination at the manual binding position Mp. When the angle is varied only by the travel rail face 42x and the travel cam face 43x, the movement distance becomes long.

(117) When the stapling unit 26 is moved toward the manual binding position Mp in a state of being locked by the stopper face 43y, the inclination of the stapling unit 26 is corrected. Further, when the stapling unit 26 is returned to the opposite direction from the manual binding position Mp, the stapling unit 26 is (forcedly) inclined to face toward the corner binding position Cp1 by the stopper face 43z.

(118) Stapling Unit

(119) The stapling unit 26 has been widely known as means to perform a binding process using a staple. An example thereof will be described with reference to FIG. 13A. The stapling unit 26 is structured as a unit separated from the sheet bundle binding processing apparatus (post-processing apparatus B). The stapling unit 26 includes a box-shaped unit frame 26a, a drive cam 26d swingably axis-supported by the unit frame 26a, and a drive motor M8 mounted on the unit frame 26a to rotate the drive cam 26d.

(120) The stapling head 26b and the anvil member 26c are arranged at a binding position as being mutually opposed. The stapling head 26b is vertically moved between a waiting position at the upper side and a stapling position at the lower side (the anvil member 26c) with the drive cam 26d and an urging spring (not illustrated). Further, the staple cartridge 39 is mounted on the unit frame 26a in a detachably attachable manner.

(121) Linear blank staples are stored in the staple cartridge 39 and fed to the head portion 26b by a staple feeding mechanism. A former member to fold a linear staple into a U-shape and a driver to cause the folded staple to bite into a sheet bundle are built in the head portion 26b. With such a structure, the drive cam 26d is rotated by the drive motor M8 and energy is stored in the urging spring. When the rotational angle reaches a predetermined angle, the head portion 26b is vigorously lowered toward the anvil member 26c. Owing to this action, a staple is caused to bite into a sheet bundle with the driver after being folded into a U-shape. Then, leading ends of the staple are folded by the anvil member 26c, so that staple-binding is completed.

(122) The staple feeding mechanism is built in between the staple cartridge 39 and the stapling head 26b. A sensor (empty sensor) to detect staple absence is arranged at the staple feeding

mechanism. Further, a cartridge sensor (not illustrated) to detect whether or not the staple cartridge **39** is inserted is arranged at the unit frame **26a**.

(123) The staple cartridge **39** adopts a structure that belt-shaped connected staples are stacked as being layered or are stored in a roll-shape in a box-shaped cartridge.

(124) Further, a circuit to control the abovementioned sensors and a circuit board to control the drive motor **M8** are arranged at the unit frame **26a** and transmit an alarm signal when the staple cartridge **39** is not mounted or the staple cartridge **39** is empty. Further, the stapling control circuit controls the drive motor **M8** to perform the stapling operation with a staple signal and transmits an operation completion signal when the stapling head **26b** is moved to an anvil position from the waiting position and returned to the waiting position.

(125) Press Binding Unit

(126) A structure of the press binding unit **27** will be described based on FIG. **13B**. As a press binding mechanism, there have been known a fold-binding mechanism (see Japanese Patent Application Laid-open No. 2011-256008) to perform binding by forming cutout openings at a binding portion of a plurality of sheets and mating as folding a side of each sheet and a press binding mechanism to perform binding by pressure-bonding a sheet bundle with corrugated faces formed on pressurizing faces **27b**, **27c** which are capable of being mutually pressure-contacted and separated.

(127) FIG. **13B** illustrates the press binding unit **27**. A movable frame member **27d** is axis-supported by a base frame member **27a** and both the frames are swung about a support shaft **27x** as being capable of being mutually pressure-contacted and separated. A follower roller **27f** is arranged at the movable frame member **27b** and is engaged with a drive cam **27e** arranged at the base frame **27a**.

(128) A drive motor **M9** arranged at the base frame member **27a** is connected to the drive cam **27e** via a deceleration mechanism. Rotation of the drive motor **M9** causes the drive cam **27e** to be rotated and the movable frame member **27d** is swung by a cam face (eccentric cam in FIG. **13B**) thereof.

(129) The lower pressurizing face **27c** and the upper pressurizing face **27b** are arranged respectively at the based frame member **27a** and the movable frame member **27d** as being mutually opposed. An urging spring (not illustrated) is arranged between the base frame member **27a** and the movable frame member **27d** to urge both the pressurizing faces **27a**, **27d** in a direction to be separated.

(130) As illustrated in an enlarged view of FIG. **13B**, convex stripes are formed on one of the upper pressurizing face **27b** and the lower pressurizing face **27c** and concave grooves to be matched therewith are formed on the other thereof. The convex stripes and the concave grooves are formed respectively into rib-shapes as having predetermined length. A sheet bundle nipped between the upper pressuring face **27b** and the lower pressurizing face **27c** is intimately contacted as being deformed into a corrugation shape. A position sensor (not illustrated) is arranged at the base frame member (unit frame) **27a** and detects whether or not the upper and lower pressurizing faces **27b**, **27c** are at the pressurization positions or separated positions. Further, the press binding unit **27** may be selectively arranged to be fixed to the apparatus frame or arranged to be movable.

(131) Stack Tray

(132) A structure of the stack tray **25** will be described based on FIG. **14**. The stack tray **25** is arranged at the downstream side of the processing tray **24**. A sheet bundle stacked on the processing tray **24** is stacked and stored onto the stack tray **25**. A tray lifting-lowering mechanism is arranged so that the stack tray **25** is sequentially lowered in accordance with a stacked amount thereon. Height of a stack face **25a** of the stack tray **25** is controlled so that the upmost sheet thereon is to be approximately flush with the sheet placement face **24a** of the processing tray **24**. Further, stacked sheets are inclined by an angle with a tailing end edge in the sheet discharging direction abutted to a tray aligning face **20f** by gravity.

(133) Specifically, a lifting-lowering rail **54** is vertically anchored in the stacking direction to the apparatus frame **20a**. A tray base body **25x** is fitted to the lifting-lowering rail **54** as being capable of being lifted and lowered using a slide roller **55** or the like in a slidable manner. A rack **25r** is formed in the lifting-lowering direction integrally with the tray base body **25x**. A drive pinion **56** axis-supported by the apparatus frame **20a** is engaged with the rack **25r**. Then, a lifting-lowering motor **M10** is connected to the drive pinion **56** via a worm gear **56** and a worm wheel **58**.

(134) Accordingly, when the lifting-lowering motor **M10** is rotated forwardly and reversely, the rack **25r** connected to the drive pinion **56** is moved to the upper side and lower side of the apparatus frame **20a**. With the above structure, the tray base body **25x** is lifted and lowered in a cantilevered state. Besides such a rack-pinion mechanism, the tray lifting-lowering mechanism may adopt a pulley-mounted belt mechanism or the like.

(135) The stack tray **25** is integrally attached to the tray base body **25x**. Sheets are stacked and stored on the stack face **25a** thereof. The tray alignment face **20f** to support sheet tailing end edges is vertically formed in the sheet stacking direction. In FIG. **14**, the tray alignment face **20f** is formed with the apparatus casing.

(136) Further, the stack tray **25** integrally attached to the tray base body **25x** is arranged as being inclined in an angled direction as illustrated in FIG. **14**. The angle (for example, 20 to 60 degrees) is set so that sheet tailing ends are abutted to the tray alignment face **20f** by gravity.

(137) Sheet Holding Mechanism

(138) A sheet holding mechanism **53** to press the upmost stacked sheet is arranged at the stack tray **25**. The illustrated sheet holding mechanism includes an elastic pressing member **53a** to press the upmost sheet, an axis-supporting member **53b** to cause the elastic pressing member **53a** to be rotatably axis-supported by the apparatus frame **20a**, a drive motor **M2** to rotate the axis-supporting member **53b** by a predetermined angle, and a transmitting mechanism thereof. The drive motor **M2** is drive-connected to the drive motor of the sheet bundle discharging mechanism **60** as a drive source. When a sheet bundle is introduced (discharged) to the stack tray **25**, the elastic pressing member **53a** is retracted to the outside of the stack tray **25**. After a tailing end of the sheet bundle is stored on the upmost sheet on the stack tray **25**, the elastic pressing member **53a** is rotated counterclockwise from the waiting position and presses the upmost sheet as being engaged therewith.

(139) Then, owing to an initial rotational operation of the drive motor **M2** to discharge a sheet bundle on the processing tray **24** toward the stack tray **25**, the elastic pressing member **53a** is retracted from a sheet face of the upmost sheet on the stack tray **25** to the retracting position.

(140) Level Sensor

(141) A level sensor to detect a sheet height of the upmost sheet is arranged at the stack tray **25**. The lifting motor is rotated based on a detection signal of the level sensor, so that the tray sheet placement face **25a** is lifted. A variety of mechanisms are known as the level sensor mechanism. In the drawing, the level sensor mechanism adopts a detection method to detect whether or not a sheet exists at the height position by emitting detection light from the tray alignment face **20f** of the apparatus frame **20a** to the tray upper side and detecting reflection light thereof.

(142) Stack Sheet Amount Sensor

(143) Similarly to the level sensor, a sensor to detect detaching of sheets from the stack tray **25** is arranged at the stack tray **25**. It is possible to detect whether or not sheets exist on the stack face, for example, by arranging a sensor lever which is rotated integrally with the elastic pressing member **53a** of the sheet holding mechanism **53** and detecting the sensor lever with a sensor element. Here, detailed description on the structure thereof is skipped. When the height position of the sensor lever becomes different (varied) between before and after discharging of a sheet bundle, the later-mentioned binding process controller **75** stops the sheet discharging operation or lifts the stack tray **25** to a predetermined position, for example. Such an operation is performed in an abnormal case, for example, in a case that a user carelessly removes sheets from the stack tray **25**.

during apparatus operation. Further, a lower limit position is defined for the stack tray 25 not to be lowered abnormally. A limit sensor Se3 to detect the stack tray 25 is arranged at the lower limit position.

(144) Image Forming System

(145) As illustrated in FIG. 1, the image forming unit A includes a sheet feeding portion 1, an image forming portion 2, a sheet discharging portion 3, and a signal processing portion (not illustrated) as being built in an apparatus housing 4. The sheet feeding portion 1 includes a cassette 5 in which sheets are stored. In FIG. 1, the sheet feeding portion 1 includes a plurality of the cassettes 5a, 5b, 5c to be capable of storing sheets having different sizes. Each of the cassettes 5a, 5b, 5c incorporates a sheet feeding roller 6 to feed a sheet and a separating device (a separating pawl, a separating roller, or the like) to separates sheets one by one.

(146) Further, a sheet feeding path 7 is arranged at the sheet feeding portion 1 for feeding a sheet from each cassette 5 to the image forming portion 2. A pair of resist rollers 8 are arranged at an end of the sheet feeding path 7, so that a sheet fed from each cassette 5 is aligned at a leading end thereof and caused to wait to be fed in accordance with image forming timing of the image forming portion 2.

(147) Thus, the sheet feeding portion 1 includes a plurality of cassettes in accordance with apparatus specifications and feeds a sheet of a size selected by a controller to the image forming portion 2 at the downstream side. Each cassette 5 is mounted on the apparatus housing 4 in a detachably attachable manner to be capable of replenishing sheets.

(148) The image forming portion 2 may adopt one of various image forming mechanisms to form an image on a sheet. FIG. 1 illustrates an electrostatic image forming mechanism. As illustrated in FIG. 1, a plurality of drums 9a to 9d each including a photo conductor in accordance with color elements are arranged at the apparatus housing 4. A light emitter (laser head or the like) 10 and a developer 11 are arranged at each of the drums 9a to 9d. A latent image (electrostatic image) is formed by the light emitter 10 at each of the drums 9a to 9d and toner ink is caused to adhere thereto by the developer 11. The ink images adhering on the respective drums 9a to 9d are superimposed to be an image as being transferred on a transfer belt 12 with respect to the respective color elements.

(149) The transferred image formed on the transfer belt 12 is transferred by a charger 13 onto a sheet fed from the sheet feeding portion 1 and fixed by a fixing device (heating roller) 14, and then, is fed to the sheet discharging portion 3.

(150) The sheet discharging portion 3 includes the sheet discharging port 16 to discharge a sheet to the sheet discharging space 15 formed in the apparatus housing 4 and a sheet discharging path 17 to guide the sheet from the image forming portion 2 to the sheet discharging port 16. A later-mentioned duplex path 18 is continuously arranged at the sheet discharging portion 3, so that a sheet having an image formed on the front face thereof is re-fed to the image forming portion 2 after being face-reversed.

(151) The sheet having an image formed on the front face thereof by the image forming portion 2 is face-reversed and re-fed to the image forming portion 2 through the duplex path 18. The sheet is discharged from the sheet discharging port 16 after an image is formed on the back face by the image forming portion 2. The duplex path 18 includes a switchback path to re-feed a sheet fed from the image forming portion 2 in the apparatus as inverting the conveying direction thereof and a U-turn path 18a to face-reverse the sheet re-fed into the apparatus. In the illustrated apparatus, the switchback path is formed on the sheet discharging path of the later-mentioned post-processing unit B.

(152) Image Reading Unit

(153) The image reading unit C includes a platen 19a and a reading carriage 19b which reciprocates along the platen 19a. The platen 19a is formed of transparent glass and includes a still image reading face to scan a still image with movement of the reading carriage 19b and a travel

image reading face to read a document image travelling at a predetermined speed.

(154) The reading carriage **19b** includes a light source lamp, a reflection mirror to polarize reflection light from a document, and a photoelectric conversion element (not illustrated). The photoelectric conversion element includes line sensors arranged in the document width direction (main scanning direction) on the platen **19a**. The reading carriage **19b** reciprocates in a sub scanning direction being perpendicular thereto, so that a document image is to be read in line order. Further, an automatic document feeding unit D to cause a document to travel at a predetermined speed is arranged above the travel image reading face of the platen **19a**. The automatic document feeding unit D includes a feeding mechanism to feed document sheets set on a sheet feeding tray to the platen **19a** one by one and to store each document sheet in a sheet discharging tray after each image is read.

(155) Description of Control Configuration

(156) A control configuration of the abovementioned image forming system will be described with reference to a block diagram in FIG. **16**. The image forming system illustrated in FIG. **16** includes a controller (hereinafter, called a main body controller) **70** for the image forming unit A and a binding process controller **75** being controller for the post-processing unit B (sheet bundle binding processing apparatus, as the case may be). The main body controller **70** includes a print controller **71**, sheet feeding controller **72**, and an input portion (control panel) **73**.

(157) Setting of an image forming mode and a post-processing mode is performed with the input portion (control panel) **73**. The image forming mode requires setting as of mode setting such color/monochrome printing and double-face/single face printing, and image forming conditions such as a sheet size, sheet quality, the number of copies, and enlarged/reduced printing. The post-processing mode is required to be set, for example, into a printout mode, a staple-binding processing mode, an eco-binding processing mode, or a jog sorting mode. Further, the illustrated apparatus includes a manual binding mode. In this mode, operation of a sheet bundle binding process is performed offline as being separate from the main body controller **70** for the image forming unit A.

(158) The main body controller **70** transfers, to the binding process controller **75**, selection of the post-processing mode and data such as the number of sheets, the number of copies, and thickness of sheets on which images are formed. Further, the main body controller **70** transfers a job completion signal to the binding process controller **75** each time when image forming is completed.

(159) The post-processing mode will be described in the following. In the printout mode, a sheet from the sheet discharging port **23** is stored at the stack tray **25** via the processing tray **24** without a binding process performed. In this case, sheets are overlapped and stacked on the processing tray **24** and a stacked sheet bundle is discharged to the stack tray **25** with a jog completion signal from the main body controller **70**.

(160) In the staple-binding processing mode (second sheet discharging mode), sheets from the sheet discharging port **23** are stacked and collated on the processing tray **24** and the sheet bundle is stored on the stack tray **25** after the binding process is performed thereon. In this case, sheets on which images are to be formed are specified by an operator basically to have the same thickness and size. In the staple-binding processing mode, any of the multi-binding, right corner binding, and left corner binding is selected and specified. The binding positions thereof are as described above.

(161) In the jog sorting mode, sheets are divided into a group whose sheets having images formed at the image forming unit A are offset and stacked on the processing tray **24** and a group whose sheets are stacked thereon without being offset. An offset sheet bundle and a non-offset sheet bundle are alternately stacked on the stack tray **25**. In the illustrated apparatus, an offset area (see FIG. **5**) is arranged. Then, sheets discharged from the sheet discharging port **23** onto the processing tray **24** in center reference S_x are divided into a group whose sheets are stacked as maintaining the above posture and a group whose sheets are stacked as being offset to the apparatus front side Fr by a predetermined amount.

(162) The reason why the offset area is arranged at the apparatus front side Fr is to maintain an operational area at the apparatus front side Fr for the manual binding process, a replacing process of a staple cartridge, and the like. The offset area is set to have dimensions (in the order of several centimeters) to divide sheet bundles.

(163) Manual Binding Mode

(164) The manual setting portion **29** where an operator sets a sheet bundle on which the binding process is to be performed is arranged at the apparatus front side Fr of the external casing **20b**. A sensor to detect a set sheet bundle is arranged at the manual setting face **29a** of the manual setting portion **29**. With a signal from the sensor, the later-mentioned binding process controller **75** moves the stapling unit **26** to the manual binding position. Subsequently, when an operation switch **30** is depressed by an operator, the binding process is performed.

(165) Thus, in the manual binding mode, the binding process controller **75** and the main body controller **70** perform controlling offline. Here, in a case that the manual binding mode and the staple-binding mode are to be performed concurrently, either mode is set to have priority.

(166) Binding Process Controller

(167) The binding process controller **75** causes the post-processing unit B to operate in accordance with the post-processing mode set by the image forming controller **70**. The illustrated binding process controller **75** is structured with a control CPU as including a ROM **76** and a RAM **77**. The later-mentioned post-processing operation is performed with control programs stored in the ROM **76** and control data stored in the RAM **77**. Here, drive circuits for all the above mentioned drive motors are connected to the control CPU **75**, so that start, stop, and forward-reverse rotation of the motors are controlled thereby.

(168) Description of Post-Processing Operation

(169) In the following, operational states of the respective binding processes will be described with reference to FIGS. **17** to **20**. For convenience of description, “a paddle” denotes sheet introducing a device (paddle rotor **36** or the like), “a roulette” denotes a raking rotor **33**, “an aligning plate” denotes a side aligning member **45**, “assists” denote the first and second conveying members **60A**, **60B**, “a button” denotes an operation switch of a stapling device, and “an LED” denotes an indication lamp indicating that a stapling operation is running.

(170) Stapling Mode

(171) In FIG. **17**, an image is formed on a final sheet for image forming and the final sheet is discharged from an image forming unit main body at the upper side (St01). At that time, a job end signal is transmitted from the image forming unit and the binding process controller **75** causes the paddle **36** to position and wait at a predetermined position (waiting of paddle vanes) (St02). At the same time, the right-left aligning plates **46R**, **46F** are moved to waiting positions (St03). A sheet fed from the sheet discharging port **16** of the image forming unit A is introduced from the introducing port **21** of the sheet introducing path (sheet discharging path) **22**. Then, discharging of the sheet tailing end by the sheet discharging roller **32** is detected by the sheet sensor Se1 (St04).

(172) The binding process controller **75** lowers the paddle **36** waiting on the processing tray **24** at the time when the sheet tailing end is separated from the sheet discharging roller **32** (St05). This operation is performed by activating the lifting-lowering motor M5. Concurrently with the paddle lowering operation, the binding process controller **75** lifts the roulette **33** to be retracted above the upmost sheet on the processing tray **24** (St08).

(173) With the above operation, the sheet fed from the image forming unit A is fed to the sheet introducing path **22**, and after the sheet tailing end passes through the sheet discharging roller **32**, the sheet is reversely conveyed by rotating the paddle **36** in the direction opposite to the sheet discharging direction in a state that the roulette **33** is retracted above the processing tray **24**. Thus, the sheet fed to the sheet introducing path **22** is stored on the processing tray **24** below the sheet discharging port **23** with the conveying direction thereof reversed at the sheet discharging port **23**.

(174) Next, the binding process controller **75** lifts the paddle **36** to be retracted from the sheet when

a predetermined time passes after the sheet is reversely conveyed from the sheet discharging port **23** in the direction opposite to the sheet discharging direction (St**06**). Concurrently with the above, the roulette **33** rotating in the direction opposite to the sheet discharging direction is lowered from the waiting position and engaged with the sheet introduced onto the processing tray **24** (St**09**).

(175) According to the above operation, the sheet is fed from the sheet discharging port **23** by the sheet discharging roller **32** and introduced onto the processing tray **24** as being reversely conveyed from the sheet discharging port **23** by the paddle **36** in the direction opposite to the sheet discharging direction. Then, the sheet is fed toward a predetermined position (toward the tailing end regulating member **41**) of the processing tray **24** by the roulette **33**. In the above sheet discharging operation, sheets having different sizes are discharged from the sheet discharging port **23** in center reference Sx. It is also possible to perform discharging from the sheet discharging port **23** in side reference. Here, for convenience, description is performed on a case of discharging in center reference Sx.

(176) Next, the binding process controller **75** moves the paddle **36** to a home position (HP) at the time when the trailing end of the sheet introduced onto the processing tray **24** is assumed to be abutted to the tailing end regulating stopper (tailing end regulating member) **41** with reference to a detection signal of the sheet discharging sensor Se2 (St**07**). Similarly, the roulette **33** is moved to a home position HP (St**10**).

(177) Next, the binding process controller **75** causes the aligning device **45** to bias and align the sheet in a state that the tailing end thereof is abutted to the tailing end regulating member **41**. The aligning operation differentiates sheet alignment positions between a case that the multi-binding mode is specified and a case that the corner binding mode is specified. When the multi-binding mode is specified, the binding process controller **75** causes the right-left side aligning members **46F**, **46R** to reciprocate (center alignment) between alignment positions where the sheet introduced onto the processing tray **24** is matched with a size width in discharging sheet reference (center reference Sx in the drawing) and waiting positions separated outward therefrom. That is, the binding process controller **75** biases and aligns the sheet by causing the side aligning members **46F**, **46R** to move from the waiting positions being wider than the size width to the alignment positions being matched with the size width based on size information sent from the image forming unit A (St**11** to St**13**).

(178) When the corner binding mode is specified, the binding process controller **75** causes one of the right-left aligning members **46F**, **46R** at a binding position side to move to and stop at the binding position based on size information and to move the other thereof to move to an alignment position from a waiting position retracting therefrom based on the size width of the sheet introduced to the processing tray **24**. The alignment position (of the aligning member at the movable side) is set to have a distance against the alignment position (of the aligning member at the binding position side) to be matched with the size width (corner binding position alignment). That is, in the corner binding process, one of the side aligning members **46F**, **46R** is moved and kept stopped at the specified binding position being right or left, and then, the other thereof is moved by an amount being matched to the size width after the sheet is introduced to the processing tray **24** to perform aligning (in side reference) (St**14** to St**16**).

(179) Next, the binding process controller **75** performs the binding operation (St**17**). In the multi-binding, the stapling unit **26** previously staying at the binding position is activated to perform the binding process thereat, and then, the binding process is performed at the second binding position after the stapling unit **26** is moved by a predetermined distance along the sheet tailing end edge (St**18** to St**20**). In the corner binding, the stapling unit **26** previously staying at the binding position is activated and the binding process is performed thereat.

(180) Next, when an operation completion signal is received from the stapling unit **26**, the binding process controller **75** causes the sheet bundle discharging device **60** to operate to discharge the sheet bundle from the processing tray **24** toward the stack tray **25** at the downstream side (St**21**).

When the sheet bundle discharging operation is completed, the binding process controller **75** moves the sheet bundle discharging device **60** to return to the initial position (St22). Concurrently with the above, the aligning device **46** is moved to return to the initial position (the waiting position to introduce a sheet to the processing tray **24**) (St23).

(181) Further, the binding process controller **75** causes the drive motor (in the drawing, the drive motor M2 commonly used for the paddle rotor **36**) to rotate the bundle holding device (elastic holding member) **53** arranged on the stack tray **25** (St24), so that the upmost sheet of the sheet bundle introduced to the stack tray **25** is pressed and held (St25).

(182) Eco-Binding Mode

(183) In the eco-binding operation, the binding process controller **75** performs the operation from step St1 to step St10 in which the sheet introduced onto the processing tray **24** is positioned as being abutted to the tailing end regulating member **41** as being similar to the abovementioned operation. Here, description of the above is skipped with the same reference provided.

(184) When the eco-binding process is specified, the binding process controller **75** causes the left side aligning member **46R** located at the binding unit side to move to an alignment position (eco-alignment position Ap2) being close to the eco-binding position Ep and to wait in a state of staying thereat (St26). Concurrently with this operation, the binding process controller **75** causes a sheet bundle guide to move from a retracting position above the processing tray **24** to an operating position on the processing tray **24** (St27). In the drawing, the shifting of the sheet bundle guide is performed so that the height position of a guide face is moved from the retracting position being a high position to the operating position being a low position as being synchronized with movement of the stapling unit **26**. That is, the binding process controller **75** causes the stapling unit **26** to move from a predetermined position (home position) to a position to be engaged with the sheet bundle guide. In this application, the stapling unit **26** is arranged to be engaged with the sheet bundle guide when located at a position Gp in FIG. 5 between Ma2 (the left multi-binding position Ma2) and Cp2 (the left corner binding position Cp2).

(185) Subsequently, the binding process controller **75** causes the right side aligning member **46F** at the opposite side to move to a waiting position distanced from a side edge of the sheet introduced onto the processing tray **24** (St28). Then, the right side aligning member **46F** is moved to an alignment position as driving the aligning motor (St29). The alignment position is set to a position so that a distance against the left side aligning member **46R** staying at the eco-alignment position is matched with the sheet width size.

(186) Thus, the present invention has a feature that a sheet introduced onto the processing tray **24** is aligned for eco-binding to the eco-alignment position Ap2 being apart from the binding position without being aligned at the binding position. When the sheet from the sheet discharging port **23** is set in sheet discharging reference (for example, center reference), the eco-alignment position Ap2 becomes the same as the alignment position in the multi-binding process. When the eco-alignment position Ap2 is set at a position being close to the eco-binding position Ep, the sheet is prevented from being interfered with the press binding unit **27** as preventing sheet jamming when being aligned. Further, after the alignment, it is possible to shorten a distance of moving the sheet bundle to the eco-binding position Ep. Accordingly, it is preferable that the eco-alignment position Ap2 is set to a close position to the extent possible within a range in which the sheet is not interfered with the press binding unit **27**.

(187) Next, the binding process controller **75** causes the side aligning member **46** to offset-move the sheet bundle aligned at the eco-alignment position Ap2 to the eco-binding position Ep (St30). Then, the side aligning member **46F** at the apparatus front side is retracted to be apart from the sheet by a predetermined amount (St31). Then, the aligning device **45** drives the sheet bundle conveying device **60** so that the sheet bundle is moved downward in the sheet discharging direction by a predetermined amount (St32). Concurrently with the above, the stapling unit **26** is moved to the initial position and the sheet bundle guide (not illustrated) is kept waiting at the retracting

position above the processing tray **24** (St33). Next, the binding process controller **75** causes the right side aligning member **46F** to move to the home position (St34).

(188) The binding process controller **75** transmits a command signal to the press binding unit **27** to cause the binding process operation to be performed (St35). Then, the binding process controller **75** operates a kicker device structured with the side aligning member **46R** (at the apparatus rear side) at the eco-binding position side. As the operation of the kicker device, first, the side aligning member **46R** is moved to a back-swing position (by an overrun amount in FIG. **15**) being separated from a position for engaging with the sheet side edge. The back-swing amount is determined in consideration of a rising time (self-exciting time) of the aligning motor **M6**. That is, the overrun amount is determined in consideration of a rising time in which the motor provides a predetermined output torque as providing running time to the aligning member **46R** (kicker device).

(189) When a process end signal is received from the press binding unit **27**, the binding process controller **75** causes the left side aligning member **46R** to move toward the sheet center by a predetermined amount by driving the aligning motor for the left side alignment member. According to this operation, the sheet bundle pressure-nipped by the press binding unit **27** is taken off and offset to the sheet center side by being kicked to the sheet center side from a state of being intimately contacted to the corrugation-shaped pressurizing faces (St37).

(190) The kicker mechanism will be described in the following.

(191) (1) The kick direction (the direction in which a conveyance force is applied to sheets, hereinafter being the same) of the left side aligning member **46R** (kicker device) is preferably the same as the strip direction (rib direction) of the pressurizing faces or a direction being slightly inclined (for example, approximately by 0 to 30 degrees) to either side with reference thereto. When a conveyance force is applied in a direction of arrow **z** in FIG. **15** (a direction perpendicular to the rib), the sheet bundle is likely to be unbound with the binding released. When a conveyance force is applied in a direction of arrow **w** in FIG. **15**, the sheet bundle is likely to be taken off from the pressurizing faces while the sheet bundle is kept bound. The angular direction is determined by experiment. In experiments of the inventors, it is preferable that the direction is set in a range between -30 degrees to 30 degrees with the reference of the rib direction.

(192) (2) The kicker device adopts a mechanism to push (feed) an end edge of a binding-processed sheet bundle toward the sheet center side. For example, as illustrated, the kicker device is structured with the left side aligning member **46R** (the right side aligning member **46F** in a case of right corner binding) to bias and align sheets on the processing tray **24** (in a direction perpendicular to the sheet discharging direction). Thus, it is preferable to adopt a conveying mechanism to apply a force to the entire sheet bundle in a direction for taking-off when the bound sheet bundle is to be taken off from the pressurizing faces. For example, when a sheet bundle is discharged by a nipping roller in the kick direction from the upper face of the sheet bundle, there occurs a problem that only a sheet contacting the nipping roller is taken off and the binding is released.

(193) (3) It is possible for the kicker device to adopt a floating mechanism to float a bottom face of a sheet bundle from the pressurizing faces of the binder mechanism concurrently with applying a kick force in a direction to separate the bound sheet bundle (in a direction intersecting the sheet discharging direction). A structure thereof is not illustrated here. For example, there are arranged a curved bottom piece to be engaged with the sheet bundle bottom face and an inclined cam face to protrude the curved bottom piece above the sheet placement face at the binding position (arranged at a back face of the processing tray or the like). In addition, a regulating face to be engaged with an end face of the sheet bundle on the sheet placement face is arranged at the side aligning member.

(194) When the side aligning member **46R** (kicker device) is located outside the sheet placement face (back-swing area), the curved bottom piece supports sheets at the same plane with the sheet placement face without receiving action of the inclined cam face. Subsequently, when the side aligning member is kick-moved toward the binding position, the curved bottom piece pushes up the sheet bundle. At the same time, the regulating face provides action to push out an end face of the

sheet bundle toward the sheet leading end. That is, an operational member (bottom face supporting member) to push up the bound sheet bundle from the pressurizing face and an operational member (side face regulating member) to push out the sheet bundle end edge toward the sheet center are arranged as operating when the side aligning member **46R** is caused to perform kick operation toward the binding position. As a result, the sheet bundle can be taken off from the pressurizing faces more reliably.

(195) Printout Sheet Discharging

(196) Description will be performed based on FIG. **19**. When a sheet is discharged from the image forming unit A (**St40**), the sheet sensor detects a leading end thereof and the paddle rotor **36** is moved to the waiting position (**St41**). Concurrently with the above, the side aligning members **46F**, **46R** are moved to the waiting positions (**St42**). Next, when the sheet tailing end passes through the sheet discharging roller **32** (**St43**), the binding process controller **75** lowers the paddle rotor **36** to the operating position (**St44**). Along with the above, the roulette rotor **33** is lifted to be retracted (**St45**).

(197) When a predetermined time passes after the sheet tailing end passes through the sheet discharging roller **32**, the binding process controller **75** lifts and moves the paddle rotor **36** to the retracting position (**St46**). Along with the above, the roulette rotor **33** is lowered to the operating position and feeds the sheet toward the tailing end regulating member **41** (**St47**). The binding process controller **75** moves the paddle rotor **36** to the home position at the time when the sheet tailing end is assumed to reach the tailing end regulating member **41** (**St48**). Further, the roulette rotor **33** is lifted to the home position (**St49**).

(198) Then, the binding process controller **75** causes the side aligning member **45** to move to the alignment position and perform the aligning operation. In the aligning operation, sheets having different sizes are stacked in center reference and fed to the stack tray **25** with the subsequent sheet discharging operation. In the printout sheet discharging operation, a later-mentioned non-standard size sheet discharging operation is performed when a large size sheet is introduced onto the tray.

(199) According to the binding process controller **75**, sheets are aligned and stacked on the processing tray **24** and the sheet bundle is discharged to the stack tray **25** at the downstream side. In the operation, the first conveying member **60A** of the sheet bundle discharging mechanism **60** is moved in the sheet discharging direction (**St50**). Next, the tray sheet holding member **53** is moved to the waiting position (**St51**). Then, the upmost sheet is pressed by rotating the tray sheet holding member **53** by a predetermined angle at the timing when the sheet bundle is introduced onto the stack tray **25** (**St52**). Subsequently, the binding process controller **75** causes the side aligning member **45** to return to the sheet introducing position (**St53**).

(200) Sort (Jog) Mode

(201) In a jog mode, approximately the same steps are performed as in the printout mode. Here, description thereof is skipped with the same reference provided to the same step. In the following, different steps will be described. Sheets introduced onto the processing tray **24** are stacked at different positions as being divided into a group whose sheets are aligned in center reference **Sx** and a group whose sheets are aligned in right side reference (**St54**). Then, the sheets are conveyed to the stack tray **25** at the downstream side as maintaining posture thereof. Here, the processing tray **24** is arranged at a position deviated to the apparatus front side and some sheets are aligned in right side reference. Then, sheets in center reference and sheets in right side reference biased toward an operator are stacked on the sheet placement face **24a**. Accordingly, sheet bundles are easy to be removed from the stack tray **25**.

(202) Common Operation in Respective Modes

(203) In the following, operation for introducing a sheet onto the processing tray **24** commonly performed in the abovementioned respective post-processing modes will be described with reference to FIG. **21**. When a sheet is discharged from the image forming unit A (**St60**), the binding process controller **75** causes, with a leading end detection signal from the sheet sensor **Se1**, the

paddle rotor **36** to be positioned at the waiting position (St**61**) and the predetermined aligning member **45** to be moved to the waiting position (St**62**). In this operation, the aligning member **45** is positioned at the waiting position to have a width size being slightly larger than the sheet size based on the sheet size signal sent from the image forming unit A.

(204) Next, at the timing when the sheet tailing end passes through the sheet discharging roller **32** (St**63**), the binding process controller **75** causes the paddle rotor **36** to be lowered from the waiting position at the upper side to the operating position at the lower side (St**64**). Along with the above, the roulette rotor **34** is lowered from the waiting position above the sheet placement face **24a** to the operating position on the sheet placement face **24a** (St**68**). At that time, both of the paddle rotor **36** and the roulette rotor **34** are rotated in the direction opposite to the sheet discharging direction.

(205) When a predetermined time (assumed time for the sheet tailing end to reach the position of the roulette rotor **34**) passes, the binding process controller **75** causes the paddle rotor **36** to be lifted from the operating position to the waiting position (St**65**). When a predetermined time (assumed time for the sheet leading end to reach the tailing end regulating member), the binding process controller **75** causes the roulette rotor **36** to be lifted by a small (St**69**). The lifting amount of the paddle rotor is amount previously set by experiment to reduce a pressing force against a sheet.

(206) Next, the binding process controller **75** causes the side aligning member **45** to move to the alignment position (St**70**). The alignment position is set to a different position in each binding processing mode, so that sheets are stacked at the abovementioned reference position in each mode, as described above.

(207) (1) For multi-binding in the staple-binding processing mode, sheets introduced onto the processing tray **24** are aligned in center reference. For right corner binding, sheets introduced onto the processing tray **24** are aligned in right side reference Ap1. For left corner binding, sheets introduced onto the processing tray **24** are aligned in left side reference Ap2. In any case of the above, the stapling unit **26** is prepared for the subsequent binding process operation as waiting at the binding position.

(208) (2) In the eco-binding processing mode, the binding process controller **75** causes sheets to be aligned at the eco-binding alignment position Ap3 defined at a position biased toward the sheet center from the eco-binding position or to be aligned in center reference.

(209) (3) In the printout mode, the binding process controller **75** causes sheets to be aligned in center reference.

(210) (4) In the jog processing mode, the binding process controller **75** causes the group being aligned in center reference and the group being aligned in right side reference to be alternately aligned in a repeated manner and to be discharged to the stack tray **25** as maintaining posture thereof.

(211) Next, after the abovementioned aligning operation is completed, the binding process controller **75** causes the side aligning member **45** to move to the initial position (St**71**), and then, the roulette rotor **34** to be lowered in a direction to press sheets (St**72**). Along with the above, the binding process controller **75** causes the paddle rotor **36** to be lifted to the waiting position as the home position and to stay thereat (St**73**).

(212) Manual Binding Operation

(213) The manual binding operation will be described with reference to a flowchart in FIG. **22**. A sheet presence-absence sensor Sm is arranged at the manual feeding portion. When the sheet presence-absence sensor Sm detects sheets, the binding process controller **75** causes the staple binding operation to be performed.

(214) The binding process controller **75** determines whether or not the stapling unit **26** is performing the binding process operation while the sensor Sm indicates an ON signal (St**80**). In a case of determining that the binding process operation can be interrupted, the stapling unit **26** is moved to the manual binding position Mp (is kept staying when the stapling unit **26** is at the binding

position) (St81). Then, an LED lamp is turned on to indicate that manual operation is running (St82).

(215) Next, after confirming that the sensor Sm is ON (St83), the binding process controller 75 determines whether or not the operation button 30 is operated (St84). When the sensor Sm is ON or when a predetermined time passes (St85) after the LED lamp is turned on (in the drawing, the time is set to two seconds) even if the sensor Sm is OFF, the LED lamp is turned on again (St86). Then, after confirming that the sensor Sm is ON (St87), the binding process controller 75 further determines whether or not a predetermined time passes after the LED lamp is turned on. Then, the stapling operation is performed (St88).

(216) Subsequently, when the sensor Sm is in an ON state after the stapling operation is performed, the binding process controller 75 performs the stapling operation again as returning to a predetermined step. According to the above, the binding process can be performed on a plurality of positions of a sheet bundle. When the sensor Sm detects a sheet-absence state and the sheet absence state continues even after a predetermined time, the stapling unit 26 is returned to the home position as assuming that the sheets are removed for the setting face. Here, if the home position of the stapling unit 26 is set at the manual binding position, the stapling unit 26 stays thereat (St93).

(217) In the present invention, during preparation or operation of the printout process, the jog sorting process, or the non-staple binding process on the processing tray, the manual stapling operation is performed based on ON/OFF of signals the abovementioned sensor Sm. Further, during operation of the multi-binding operation or the corner binding operation on the processing tray, the manual operation can be performed when sheet stacking is in operation and a jog completion signal is not transmitted from the image forming unit A. Even if a jog completion signal is transmitted, the manual stapling operation is performed when an interruption process is instructed.

(218) Thus, it is preferable for apparatus designing to adopt means that determines which has a priority between the manual stapling operation and stapling operation on the processing tray or that has an operator perform selection with a priority selection key.

Claims

1. A finisher for binding a sheet bundle, comprising: a conveying portion configured to convey a sheet; a tray configured to stack the sheet conveyed by the conveying portion one by one for forming the sheet bundle; an insertion portion to which the sheet bundle is configured to be inserted by an operator, the insertion portion being arranged on a front side of the finisher relative to the tray in a front-rear direction of the finisher; a stapler, configured to bind the sheet bundle by a staple, having a head at a front portion of the stapler for binding the sheet bundle, and a cartridge at a rear portion of the stapler for containing the staple; a stapler moving mechanism configured to move the stapler to a first stapling position for binding a corner portion of the sheet bundle at a rear side in the front-rear direction formed on the tray, a second stapling position for binding the sheet bundle inserted into the insertion portion located at the front side relative to the first stapling position in the front-rear direction, and a staple loading position for removing the cartridge and replenishing a new cartridge at a front position relative to the first stapling position in the front-rear direction; and a stapler turning mechanism configured to turn the stapler to a posture such that the rear portion rather than the front portion of the stapler is located at the front side in the front-rear direction in order that the cartridge can be easily removed in a direction from the front portion to the rear portion when replacing the cartridge.

2. The finisher according to claim 1, wherein the rear portion of the stapler at the staple loading position is located at an upstream side more than the front portion of the stapler in a conveying direction of the sheet where the conveying portion conveys the sheet to the tray.

3. A finisher for binding a sheet bundle, comprising: a conveying portion configured to convey a

sheet; a tray configured to stack the sheet conveyed by the conveying portion one by one for forming the sheet bundle; an insertion portion configured to be inserted the sheet bundle, the insertion portion being located at a front side of the finisher relative to the tray in a front-rear direction of the finisher; a stapler configured to bind the sheet bundle stacked on the tray and the sheet bundle inserted into the insertion portion, by a staple; a reciprocating mechanism configured to reciprocate the stapler along the front-rear direction of the finisher; and a turning mechanism configured to turn the stapler to a posture such that a downstream side in a predetermined direction of a cartridge of the staple for the stapler rather than an upstream side of the cartridge in the predetermined direction is located at the front side of the finisher in order that the cartridge of the staple can be easily removed along the predetermined direction when replacing the cartridge.

4. An image forming system, comprising: an image forming apparatus which forms an image on a sheet; and the finisher according to claim 3 for binding the sheets with images by the image forming apparatus.
