

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399537
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Jeong; Daeung et al.

Electronic device for detecting moisture

Abstract

An electronic device is provided. The electronic device includes a housing including a first surface, a second surface and a conductive frame disposed between the first surface and the second surface and including a through-hole, a first electrode is movable within the through-hole, a part of the first electrode protruding to outside of the conductive frame, a second electrode disposed on the second surface, and at least one processor. The at least one processor is configured to identify whether the first electrode is electrically disconnected to the conductive frame, obtain an information about the user' body through the first electrode and the second electrode, and refrain from obtaining the information based on identifying the first electrode is electrically connected to the conductive frame.

Inventors: Jeong; Daeung (Suwon-si, KR), Lee; Suho (Suwon-si, KR), Cho; Shinhee (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008781609

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 17/884990

Filed: August 10, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230161384 A1	May. 25, 2023

Foreign Application Priority Data

KR	10-2021-0161385	Nov. 22, 2021
KR	10-2021-0176613	Dec. 10, 2021

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/011583 20220804 PENDING child-doc US 17884990

Publication Classification

Int. Cl.: G06F1/16 (20060101); G06F3/01 (20060101); G06F3/041 (20060101)

U.S. Cl.:

CPC G06F1/1656 (20130101); G06F1/163 (20130101); G06F3/016 (20130101); G06F3/04164 (20190501);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8698769	12/2013	Coulson et al.	N/A	N/A
9298327	12/2015	Wenzel	N/A	N/A
9823286	12/2016	Connell et al.	N/A	N/A
10610157	12/2019	Pandya	N/A	G04G 21/08
10627783	12/2019	Rothkopf	N/A	G06F 3/016
11073950	12/2020	Lee et al.	N/A	N/A
11150766	12/2020	Hong et al.	N/A	N/A
11857298	12/2023	Allec	N/A	G06F 1/163
2019/0101870	12/2018	Pandya	N/A	A61B 5/339
2019/0133487	12/2018	Jung et al.	N/A	N/A
2019/0320981	12/2018	Kodama et al.	N/A	N/A
2021/0257086	12/2020	Kang et al.	N/A	N/A
2021/0275102	12/2020	Cho et al.	N/A	N/A
2022/0117533	12/2021	Mattila et al.	N/A	N/A
2023/0161384	12/2022	Jeong	361/679.26	A61B 5/28
2023/0221816	12/2022	Rosenberg et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110367952	12/2018	CN	N/A
112731833	12/2020	CN	N/A
112762701	12/2020	CN	N/A
5651036	12/2014	JP	N/A
6784822	12/2019	JP	N/A

2022527239	12/2021	JP	N/A
10-2016-0064842	12/2015	KR	N/A
10-2016-0094219	12/2015	KR	N/A
10-2017-0041511	12/2016	KR	N/A
10-1828068	12/2017	KR	N/A
10-2020-0045124	12/2019	KR	N/A
10-2137092	12/2019	KR	N/A
10-2250772	12/2020	KR	N/A
10-2264330	12/2020	KR	N/A
10-2021-0112630	12/2020	KR	N/A
10-2404321	12/2021	KR	N/A
10-2022-0133010	12/2021	KR	N/A
10-2022-0152700	12/2021	KR	N/A
2018/105447	12/2017	WO	N/A

OTHER PUBLICATIONS

International Search Report dated Nov. 18, 2022, issued in an International Patent Application No. PCT/KR2022/011583. cited by applicant

European Search Report dated Dec. 19, 2024, issued in European Application No. 22895796.5. cited by applicant

Primary Examiner: Hayman; Imani N

Assistant Examiner: Morrison; Rashen E

Attorney, Agent or Firm: Jefferson IP Law, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a continuation application, claiming priority under § 365(c), of an International application No. PCT/KR2022/011583, filed on Aug. 4, 2022, which is based on and claims the benefit of a Korean patent application number 10-2021-0161385, filed on Nov. 22, 2021, in the Korean Intellectual Property Office, and of a Korean patent application number 10-2021-0176613, filed on Dec. 10, 2021, in the Korean Intellectual Property Office, the disclosure of each of which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

(1) Various embodiments relate to an electronic device for detecting moisture.

BACKGROUND ART

(2) As users' interest in health increases, an electronic device may obtain information on the user's body. The user may easily find a way to improve one's own physical condition by continuously monitoring one's physical condition through information provided from the electronic device.

(3) As the user continuously wears the electronic device, the electronic device may be exposed to various situations that may cause a malfunction of the electronic device. For example, the electronic device may malfunction because a sensor fails to obtain accurate information from the user due to moisture or foreign substances penetrating into the inside.

(4) The above information is presented as background information only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to

whether any of the above might be applicable as prior art with regard to the disclosure.

DISCLOSURE

Technical Problem

(5) An electronic device may include various types of sensors to obtain information on the user's body. For example, the electronic device may include a sensor including an electrode to obtain information on the user's physical condition. For example, when the electrode and other components of the electronic device are unintentionally electrically connected to each other due to moisture penetrating into the electronic device, the sensor may not obtain accurate information from a user and thus may malfunction. In order to prevent a malfunction of the sensor, the electronic device may include a sensor for detecting moisture, but the electronic device may not quickly respond to the malfunction of the sensor as it takes time to process data received from the sensor, and thus data detected from the sensor may not be trusted. The electronic device may detect moisture penetrating into the electronic device without including the sensor.

(6) Various embodiments relate to the electronic device for detecting moisture.

(7) The technical problems to be achieved in this document are not limited to those described above, and other technical problems not mentioned herein will be clearly understood by those having ordinary knowledge in the art to which the present disclosure belongs, from the following description.

Technical Solution

(8) According to an embodiment, an electronic device may comprise a housing including a first surface, a second surface facing the first surface and facing a part of a user's body when the electronic device is worn to the user, and a conductive frame disposed between the first surface and the second surface and including a through-hole, a first electrode spaced apart from an inner surface of the through-hole, and movable within the through-hole, a part of the first electrode protruding to outside of the conductive frame, a second electrode disposed on the second surface, and contact with the part of the user's body when the electronic device is worn to the user, and a processor; wherein the processor may be configured to identify whether the first electrode is electrically disconnected to the conductive frame in response to identifying a designated event; obtain an information about the user' body through the first electrode and the second electrode, based on identifying the first electrode is electrically disconnected to the conductive frame; and refrain from obtaining the information based on identifying the first electrode is electrically connected to the conductive frame.

(9) According to an embodiment, an electronic device may an electronic device may comprise a housing including a first surface, a second surface facing the first surface and facing a part of a user's body when the electronic device is worn to the user, and a conductive frame disposed between the first surface and the second surface and including a first through-hole and a second through-hole, a display disposed on the first surface, a first electrode spaced apart from an inner surface of the first through-hole, and movable within the first through-hole, and a part of the first electrode protruding to outside of the conductive frame, a second electrode disposed on the second surface, and contact with the part of the user's body when the electronic device is worn to the user, a third electrode spaced apart from an inner surface of the second through-hole, and movable within the second through-hole, and a part of the third electrode protruding to outside of the conductive frame, a fourth electrode disposed on the second surface spaced apart from the second electrode, and contact with the part of the user's body when the electronic device is worn to the user, and processor, wherein, the processor may be configured to identify whether the first electrode or the third electrode is electrically disconnected to the conductive frame, in response to identifying a designated event, obtain an information about the user' body through the first electrode, the second electrode, the third electrode, and the fourth electrode, based on identifying the first electrode is electrically disconnected to the conductive frame and identifying the third electrode is electrically disconnected to the conductive frame, and refrain from obtaining the

information, based on identifying the first electrode is electrically connected to the conductive frame or the third electrode is electrically connected to the conductive frame.

Advantageous Effects

(10) According to an embodiment, the electronic device can easily detect whether moisture has penetrated into the electronic device without including a separate additional sensor, by determining whether a conductive frame and a first electrode are electrically disconnected. According to an embodiment, the electronic device can smoothly obtain information on the user's body through electrodes by easily detecting whether moisture has penetrated.

(11) The effects that can be obtained from the present disclosure are not limited to those described above, and any other effects not mentioned herein will be clearly understood by those having ordinary knowledge in the art to which the present disclosure belongs, from the following description.

Description

DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a block diagram of an electronic device in a network environment according to various embodiments.

(3) FIGS. 2A and 2B are perspective views of an electronic device according to an embodiment.

(4) FIG. 3 is an exploded perspective view of an electronic device according to an embodiment.

(5) FIG. 4A is a perspective view of a second surface of an electronic device according to an embodiment.

(6) FIG. 4B is a cross-section view illustrating an example in which an electronic device is cut along A-A' of FIG. 4A according to an embodiment.

(7) FIG. 5A is a block diagram of an electronic device according to an embodiment.

(8) FIG. 5B is a diagram illustrating an example of providing a notification of whether an electronic device is submerged, according to an embodiment.

(9) FIG. 6 is a block diagram of an electronic device according to an embodiment.

(10) FIG. 7 illustrates an example of an operation of a processor of an electronic device, according to an embodiment.

(11) FIG. 8 illustrates an example of an operation of a processor of an electronic device, according to an embodiment.

(12) Throughout the drawings, it should be noted that like reference numbers are used to depict the same or similar elements, features, and structures.

MODE FOR INVENTION

(13) The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit of the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.

(14) The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration

purpose only and not for the purpose of limiting the disclosure as defined by the appended claims and their equivalents.

(15) It is to be understood that the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a component surface” includes reference to one or more of such surfaces.

(16) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to various embodiments.

(17) Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(18) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation.

According to one embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(19) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised

learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(20) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(21) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(22) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(23) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(24) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(25) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(26) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(27) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(28) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(29) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a

vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(30) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(31) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(32) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(33) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™ wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(34) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(35) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g.,

the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(36) According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(37) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(38) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(39) FIGS. 2A and 2B are perspective views of an electronic device according to an embodiment.

(40) Referring to FIGS. 2A and 2B, an electronic device **200** (e.g., the electronic device **101** of FIG. 1) according to an embodiment may include a housing **210** including a first surface (or front surface) **210A**, a second surface (or rear surface) **210B**, and a side surface **210C** surrounding the space between the first surface **210A** and the second surface **210B** and binding members **250** and

260 connected to at least a part of the housing **210** and configured to detachably attach the electronic device **200** to a part of the user's body (e.g., wrist, ankle, etc.). In another embodiment (not illustrated), the housing may also refer to a structure that forms at least a part of the first surface **210A**, the second surface **210B**, and the side surface **210C** of FIG. 2A. According to an embodiment, at least a part of the first surface **210A** may be implemented by a substantially transparent front plate **201** (e.g., glass plate or polymer plate including various coating layers). The second surface **210B** may be implemented by a substantially opaque rear plate **207**. The rear plate **207** may be made of, for example, coated or colored glass, ceramic, polymer, metal (e.g., aluminum, stainless steel (STS), or magnesium), or a combination of at least two of the materials. The side surface **210C** may be coupled to the front plate **201** and the rear plate **207**, and may be implemented by a side bezel structure (or "side member") **206** including metal and/or polymer. In some embodiments, the rear plate **207** and the side bezel structure **206** may be integrally formed and may include the same material (e.g., metal material such as aluminum). The binding members **250** and **260** may be made of various materials and may be made in various shapes. The binding members **250** and **260** may be made of woven fabric, leather, rubber, urethane, metal, ceramic, or a combination of at least two of the materials.

(41) According to an embodiment, the electronic device **200** may include at least one of a display **220** (see FIG. 3), an audio module **205** and **208**, a sensor module **211**, a key input device **202**, **203** and **204**, and a connector hole **209**. In some embodiments, the electronic device **200** may omit at least one of the components (e.g., the key input devices **202**, **203** and **204**, the connector hole **209**, or the sensor module **211**) or may further include another component.

(42) The display **220** may be exposed, for example, through a substantial portion of the front plate **201**. The shape of the display **220** may correspond to the shape of the front plate **20**, such as circular (shown in FIG. 2A), oval, or polygonal. The display **220** may be coupled to or adjacent to a touch sensing circuit, a pressure sensor capable of measuring the strength (pressure) of touches, and/or a fingerprint sensor.

(43) The audio modules **205** and **208** may include a microphone hole **205** and a speaker hole **208**, a microphone for obtaining external sound may be disposed inside the microphone hole **205**, and in some embodiments, a plurality of microphones may be disposed to detect the direction of the sound. The speaker hole **208** may be used with an external speaker and a receiver for phone calls. In some embodiments, the speaker hole **208** and the microphone hole **205** may be implemented as a single hole, or a speaker (e.g., piezo speaker) may be included without the speaker hole **208**.

(44) The sensor module **211** may generate electrical signal(s) or data value(s) corresponding to internal operating state(s) of the electronic device **200** or external environmental state(s). The sensor module **211** may include, for example, a biometric sensor module **211** (e.g., heart-rate monitor (HRM) sensor) disposed on the second surface **210B** of the housing **210**. The electronic device **200** may further include at least one sensor module not shown, such as a gesture sensor, a gyro sensor, a pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a color sensor, an infrared sensor, a biometric sensor, a humidity sensor, and/or an illumination sensor.

(45) The sensor module **211** may include electrode regions **213** and **214** forming a part of the surface of the electronic device **200** and a bio-signal detection circuit (not shown) electrically connected to the electrode regions **213** and **214**. For example, the electrode regions **213** and **214** may include the first electrode region **213** and the second electrode region **214** disposed on the second surface **210B** of the housing **210**. The sensor module **211** may be configured such that the electrode regions **213** and **214** obtain electrical signal(s) from a part of the user's body, and the bio-signal detection circuit may detect biometric information of the user based on the electrical signal(s).

(46) The key input devices **202**, **203**, and **204** may include a wheel key **202** disposed on the first surface **210A** of the housing **210** and rotatable in at least one direction, and/or side key buttons **203** and **204** disposed on the side surface **210C** of the housing **210**. The wheel key may have a shape

corresponding to the shape of the front plate **201**. In another embodiment, the electronic device **200** may not include some or all of the above-described key input devices **202**, **203**, and **204**, and the not included key input devices **202**, **203**, and **204** may be implemented in other forms such as soft keys on the display **220**. The connector hole **209** may accommodate a connector (e.g., USB connector) for transmitting and receiving power and/or data to and from external electronic devices and may include another connector hole (not illustrated) capable of accommodating a connector for transmitting and receiving audio signals to and from an external electronic device. The electronic device **200** may further include, for example, a connector cover (not illustrated) that covers at least a part of the connector hole **209** and blocks the inflow of external foreign material into the connector hole.

(47) The binding members **250** and **260** may be attached to at least a part of the housing **210** and may be user-detachable from the housing **210** using locking members **251**, **261**. The binding members **250** and **260** may include one or more of a fixing member **252**, a fixing member fastening hole **253**, a band guide member **254**, and a band fixing ring **255**.

(48) The fixing member **252** may be configured to fix the housing **210** and the binding members **250** and **260** to a part of the user's body (e.g., wrist, ankle, etc.). The fixing member fastening hole **253** may correspond to the fixing member **252** to fix the housing **210** and the binding members **250** and **260** to the part of the user's body. The band guide member **254** may be configured to limit movement range of the fixing member **252** when the fixing member **252** is fastened to the fixing member fastening hole **253**, so that the binding members **250** and **260** are attached to be in close contact with the part of the user's body. The band fixing ring **255** may limit the range of movement of the binding members **250** and **260** when the fixing member **252** and the fixing member fastening hole **253** are fastened.

(49) FIG. 3 is an exploded perspective view of an electronic device according to an embodiment.

(50) Referring to FIG. 3, an electronic device **300** (e.g., the electronic device **101** of FIG. 1, the electronic device **200** of FIG. 2A and/or FIG. 2B) may include a side bezel structure **310**, a wheel key **320**, a front plate **201**, a display **220**, a first antenna **350**, a second antenna **355**, a support member **360** (e.g., a bracket), a battery **370**, a printed circuit board **380**, a sealing member **390**, and binding members **395** and **397**. At least one of the components of the electronic device **300** may be the same as or similar to at least one of the components of the electronic device **200** of FIGS. 1, 2A, and/or 2B, and repeated description thereof will be omitted. The support member **360** may be disposed inside the electronic device **300** to be connected to the side bezel structure **310** or may be integrated with the side bezel structure **310**. The support member **360** may be made of, for example, metal material and/or non-metal (e.g., polymer) material. The display **220** may be coupled to one surface of the support member **360**, and the printed circuit board **380** may be coupled to the other surface of the support member **360**. A processor, a memory, and/or an interface may be mounted on the printed circuit board **380**. The processor may include, for example, one or more of a central processing unit, an application processor, a graphic processing unit (GPU), an application processor sensor processor, or a communication processor.

(51) The memory may include, for example, a volatile memory or a nonvolatile memory. The interface may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, an SD card interface, and/or an audio interface. The interface may electrically or physically connect the electronic device **300** to an external electronic device, for example, and may include a USB connector, an SD card/MMC connector, or an audio connector.

(52) The battery **370** is a device for supplying power to at least one component of the electronic device **300**, and may include, for example, a non-rechargeable primary battery, a rechargeable secondary battery, or a fuel battery. At least a part of the battery **370** may be disposed on substantially the same plane as, for example, the printed circuit board **380**. The battery **370** may be integrally disposed inside the electronic device **200** or may be detachably coupled to the electronic device **200**.

(53) The first antenna **350** may be disposed between the display **220** and the support member **360**. The first antenna **350** may include, for example, a near field communication (NFC) antenna, a wireless charging antenna, and/or a magnetic secure transmission (MST) antenna. The first antenna **350** may, for example, perform short-range communication with an external device, wirelessly transmit and receive power required for charging, and transmit short-range communication signal or an electromagnetic signal including payment data. In another embodiment, an antenna structure may be formed by at least a portion of the side bezel structure **310** and/or a part of the support member **360** or a combination thereof.

(54) The second antenna **355** may be disposed between the printed circuit board **380** and the rear plate **393**. The second antenna **355** may include, for example, a near field communication (NFC) antenna, a wireless charging antenna, and/or a magnetic secure transmission (MST) antenna. For example, the second antenna **355** may perform short-range communication with an external device, wirelessly transmit and receive power required for charging, and may transmit a short-range communication signal or an electromagnetic signal including payment data. In another embodiment, an antenna structure may be formed by at least a portion of the side bezel structure **310** and/or a part of the rear plate **393** or a combination thereof.

(55) The sealing member **390** may be positioned between the side bezel structure **310** and the rear plate **393**. The sealing member **390** may be configured to block moisture and foreign material flowing into the space surrounded by the side bezel structure **310** and the rear plate **393** from the outside.

(56) FIG. 4A is a perspective view of a second surface of an electronic device according to an embodiment, and FIG. 4B is a cross-section view illustrating an example in which an electronic device is cut along A-A' of FIG. 4A according to an embodiment.

(57) Referring to FIGS. 4A and 4B, an electronic device **400** (e.g., electronic device **101** of FIG. 1, electronic device **200** of FIG. 2A and/or 2B, or electronic device **300** of FIG. 3) may include a housing **410** (e.g., housing **210** in FIG. 2A), a binding member **420** (e.g., binding members **250** and **260** of FIG. 2A and/or 2B), a display **430** (e.g., display **220** of FIG. 3), a plurality of electrodes **440**, an electronic component **450**, a non-conductive member **460**, and a sealing member **470**.

According to an embodiment, when worn by a user, the electronic device **400** may contact a part of the user's body (e.g., a wrist or an ankle).

(58) The housing **410** may form the overall appearance of the electronic device **400**. According to an embodiment, the housing **410** may include a first surface **410a** and a second surface **410b** facing the first surface **410a**. The first surface **410a** and the second surface **410b** may be substantially the same as the first surface **210A** of FIG. 2A and the second surface **210B** of FIG. 2B, respectively. According to an embodiment, when the electronic device **400** is worn by a user, the second surface **410b** may face a part of the user's body.

(59) According to an embodiment, the housing **410** may include an inner space **411** and a conductive frame **412**. The inner space **411** may accommodate various components of the electronic device **400**. For example, the inner space **411** may accommodate an electronic component **450** capable of performing various functions of the electronic device **400**. The inner space **411** may be an empty space formed inside the housing **410**. For example, the inner space **411** may refer to a space surrounded by the first surface **410a**, the second surface **410b**, and a side surface **410c** extending from an edge of the first surface **410a** and the second surface **410b** and connecting the first surface **410a** and the second surface **410b**. The conductive frame **412** may form at least a part of the side surface **410c** of the housing **410**. According to an embodiment, the conductive frame **412** may be disposed between the first surface **410a** and the second surface **410b** of the housing **410**, and may connect the first surface **410a** and the second surface **410b**. The conductive frame **412** may form the inner space **411** together with the first surface **410a** and the second surface **410b**, and may protect various components of the electronic device **400** accommodated in the inner space **411**. For example, the conductive frame **412** may form at least a

part of a side member (e.g., side member **206** of FIG. 2A). According to an embodiment, at least a part of the conductive frame **412** may be made of a metal material (e.g., aluminum, stainless steel (STS), or magnesium). For example, the conductive frame **412** may be entirely made of a metal material, or may be made of a combination of a metal and a non-conductive material (e.g., glass, ceramic, or polymer).

(60) According to an embodiment, the conductive frame **412** may include a first through hole **413** and a second through hole **414** connecting the inner space **411** of the housing **410** to the outside of the electronic device **400**. According to an embodiment, the first through hole **413** and the second through hole **414** may be extended to form, from the inner space **411** of the housing **410**, to the outside of the conductive frame **412**, in a direction substantially perpendicular to a direction toward the first surface **410a**.

(61) When the electronic device **400** is worn by a user, the binding member **420** may support the electronic device **400** so as not to deviate from the wearing position by contacting a part B1 of the user's body. The binding member **420** may be substantially the same as the binding members **260** and **270** of FIGS. 2A and/or 2B. The binding member **420** may be defined as a strap for fixing the electronic device **400** to the user's body. According to an embodiment, the binding member **420** may be rotatably coupled to the housing **410**. For example, the binding member **420** may be hinged to a part of the conductive frame **412** to be rotatable with respect to the conductive frame **412**. According to an embodiment, at least a part of the binding member **420** may be made of a metal material. For example, the binding member **420** may be entirely made of a metal (e.g., aluminum, stainless steel (STS), or magnesium), or a material including a combination of the metal and a non-conductive material (e.g., silicon, fiber, glass, ceramic, or polymer). As another example, the binding member **420** may be entirely made of a non-conductive material.

(62) The display **430** may output visual information. The user may check information on the state of the electronic device **400** or information on the state of the user through the visual information output by the display **430**. According to an embodiment, the display **430** may include a touch sensor configured to detect a user's touch or a pressure sensor that detects a magnitude of a force generated by the user's touch. When the display **430** includes the touch sensor or the pressure sensor, the display **430** may receive a user's touch input. For example, the touch sensor may be printed on a layer in the panel of the display **430** to be integrally formed with the display panel. For another example, the touch sensor may be formed of a film including a touch electrode and attached to one of the layers forming the display panel.

(63) The plurality of electrodes **440** may receive an electrical signal for obtaining information on the user's body. For example, the plurality of electrodes **440** may receive an electrical signal for obtaining at least one of information on the user's electrocardiogram (ECG), information on the user's bioelectrical impedance, information on the user's electromyogram (EMG), and information on the skin electrodermal activity (EDA). The information on skin electrodermal activity (EDA) may include, for example, at least one of a galvanic skin response (GSR), an electrothermal response (EDR), a psychogalvanic reflex (PGR), a skin conduction response (SCR), and a symmetric skin response (SSRS). According to an embodiment, the plurality of electrodes **440** may include a first electrode **441**, a second electrode **442**, a third electrode **443**, and/or a fourth electrode **444** spaced apart from each other. Each of the first electrode **441** and the third electrode **443** may be inserted into the first through hole **413** and the second through hole **414** of the conductive frame **412**, and the second electrode **442** and the fourth electrode **444** may be disposed on the second surface **410b** of the housing **410**. For example, the first electrode **441** and the third electrode **443** may extend to the outside of the electronic device **400** in a direction substantially perpendicular to a direction in which the first surface **410a** faces from the inner space **411** of the housing **410**, respectively. For another example, the second electrode **442** and the fourth electrode **444** may be disposed to face each other on the second surface **410b** of the housing **410**.

(64) According to an embodiment, the first electrode **441** and the third electrode **443** may function

as a key button by forming at least a part of the key buttons **203** and **204** of FIG. 2A. When the first electrode **441** or the third electrode **443** is pressed by a user, the electronic device **400** may perform a designated function in response to the pressure of the first electrode **441** or the third electrode **443**. For example, the electronic device **400** may perform an on/off function of power of the electronic device **400** or a wake-up/sleep function in response to pressure of the first electrode **441** or the third electrode **443**. According to an embodiment, the first electrode **441** and the third electrode **443** may be related with different functions of the electronic device **400**. According to an embodiment, one of the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444** may be omitted according to a function provided through the electronic device **400**. For example, the electronic device **400** may omit one of the first electrode **441** and the third electrode **443** or omit one of the second electrode **442** and the fourth electrode **444**, according to design necessity. When the third electrode **443** is unnecessary in the electronic device **400**, the third electrode **443** may be configured to operate as a key button but not as an electrode.

(65) According to an embodiment, a part of the first electrode **441** and the third electrode **443** may protrude to the outside of the conductive frame **412** and may move in the first through hole **413** and the second through hole **414**, respectively. As the first electrode **441** and the third electrode **443** move in the first through hole **413** and the second through hole **414**, respectively, the first electrode **441** and the third electrode **443** may provide a click feeling to the user of the electronic device **400**. According to an embodiment, the first electrode **441** and the third electrode **443** may be spaced apart from the inner surfaces of the first through hole **413** and the second through hole **414** to be movable in the first through hole **413** and the second through hole **414**, respectively. For example, each of the first electrode **441** and the third electrode **443** may be spaced apart from the first through hole **413** and the second through hole **414** in a direction substantially perpendicular to the extending direction of the first electrode **441** and the third electrode **443**. For example, the shape of the side surface of the first electrode **441** may correspond to the inner surface of the first through hole **413**. The side surface of the first electrode **441** and the inner surface of the first through hole **413** may be spaced apart from each other.

(66) According to an embodiment, the plurality of electrodes **440** may be electrically separated in a state before contacting parts B1 and B2 of the user's body. When the plurality of electrodes **440** contact parts B1 and B2 of the user's body, an electrical closed circuit may be formed by the plurality of electrodes **440** and the parts B1 and B2 of the user's body. As the electrical closed circuit is formed, the plurality of electrodes **440** may receive an electrical signal generated in the user's body or emit a current to a part B1 and B2 of the user through a part thereof and receive a current returning from the part B1 and B2 of the user through the other part.

(67) According to an embodiment, the plurality of electrodes **440** may receive an electrical signal generated in the user's body to obtain information on the user's electrocardiogram by contacting different parts B1 and B2 of the user's body. For example, when the electronic device **400** is worn on the user's left hand, the second electrode **442** disposed on the second surface **410b** may contact the left hand that is a part B1 of the user's body, and the first electrode **441** may contact the right hand that is the other part B2 of the user's body. When the first electrode **441** and the second electrode **442** contact different parts B1 and B2 of the user's body, an electrical closed circuit pass through the user's heart may be formed by the first electrode **441**, the second electrode **442**, and the different parts B1 and B2 of the body. The first electrode **441** and the second electrode **442** may obtain information on the user's electrocardiogram by receiving an active potential generated in the myocardium by the user's heartbeat via the electrical closed circuit pass through the user's heart.

(68) According to an embodiment, the plurality of electrodes **440** may emit a current via parts B1 and B2 of the user's body and receive a current returning again in order to obtain information on the user's bio-electric resistance by contacting different each parts B1 and B2 of the user's body. For example, when the electronic device **400** is worn on the user's left hand, as the second electrode **442** and the fourth electrode **444** disposed on the second surface **410b** contact with different

regions of the left hand, which is a part B1 of the user's body and the first electrode **441** and the third electrode **443** contact different fingers of the right hand, which is the other part B2 of the user's body, the electrical closed circuit may be formed in the first electrode **441**, the second electrode **442**, the third electrode **443**, the fourth electrode **444**, and different parts B1 and B2 of the body. When the electrical closed circuit is formed, as an alternating current is applied from a part of the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444** to different parts B1 and B2 of the user's body and the current is received to another part of the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444**, the electronic device **400** may obtain information on the user's bio-electrical resistance.

(69) Referring to FIG. **4B**, the electronic component **450** may include components disposed in the housing **410** and performing an operation of the electronic device **400**. According to an embodiment, the electronic component **450** may include at least one sensor (e.g., the sensor module **220** of FIG. **2B**), wherein at least one sensor may be configured to be electrically connected to a processor (e.g., the processor **120** in FIG. **1**) that perform the overall operation of the electronic device **400**, and the plurality of electrodes **440**, and detect information on the user's body through an electrical signal received from the plurality of electrodes **440**. According to an embodiment, the processor may be operatively coupled to the conductive frame **412**, the display **430**, and a plurality of electrodes **440**. According to an embodiment, the at least one sensor may be, for example, at least one of an electrocardiogram (ECG) sensor, a bioelectrical impedance analysis (BIA) sensor, an electromyogram (EMG) sensor, and an electrodermal activity (EDA) sensor.

(70) According to an embodiment, the electronic component **450** may include a contact part **451** forming an electrical contact with the first electrode **441**. The contact part **451** may not form an electrical contact with the first electrode **441** in a state where the first electrode **441** is not pressed by a user. When the first electrode **441** is pressed by a user, the contact part **451** may form an electrical contact with the first electrode **441** by contacting the first electrode **441**. As the contact part **451** and the first electrode **441** form an electrical contact, the electrical signal may be transmitted from the contact unit **451** to the processor, and the processor may perform a designated function of the electronic device **400** based on receiving the electrical signal. For example, the contact unit **451** may refer to a spring contact connector, but is not limited thereto and may be changed into various components capable of forming an electrical contact with the first electrode **441**.

(71) The non-conductive member **460** may electrically separate the conductive frame **412** from the first electrode **441**. The non-conductive member **460** may be made of an electrically non-conductive material such as plastic. According to an embodiment, the non-conductive member **460** may include a first non-conductive member **461** and a second non-conductive member **462** that coupled to the conductive frame **412** in order to contact the inner surface of the first through hole **413**, and the first electrode **441** and spaced apart from each other. For example, the first non-conductive member **461** may surround one area of the first electrode **441** close to the inner space **411** and may be fixed to the inner surface of the first through hole **413**. For another example, the second non-conductive member **462** may be coupled to one end of the first electrode **441** facing the outside of the electronic device **400** and may move together with the first electrode **441**. According to an embodiment, an air gap g may be formed between the first non-conductive member **461** and the second non-conductive member **462** so that the first non-conductive member **461** and the second non-conductive member **462** are spaced apart from each other in a state before the first electrode **441** is pressed by the user. The second non-conductive member **462** may move together with the first electrode **441**, according to a user's pressure, to contact the first non-conductive member **461**. The first non-conductive member **461** and the second non-conductive member **462** may function as a stopper for limiting a moving distance of the first electrode **441** by contacting according to movement of the first electrode **441**.

(72) The sealing member **470** may prevent foreign substances from penetrating into the inner space

411 from the outside of the electronic device **400** by sealing the first through hole **413**. For example, the first sealing member **471** may surround one area of the first electrode **441** positioned within the first through hole **413** inside the first non-conductive member **461**. The first sealing member **471** may contact the first non-conductive member **461** and the first electrode **441** by surrounding one region of the first electrode **441**, thereby sealing the first through hole **413**. For example, the sealing member **470** may refer an o-ring, but is not limited thereto.

(73) According to an embodiment, in order to obtain information on the user's body, the processor may be configured to identify whether the user's body is in contact with the plurality of electrodes **440**. For example, the processor may identify whether a user's body contacts the first electrode **441** and the second electrode **442** based on identifying impedance values between the first electrode **441** and the second electrode **442**. Since the user's body may serve as a conductor, when the part **B2** of the user's body contacts the first electrode **441**, an impedance value between the first electrode **441** and the second electrode **442** may be lower than when the part **B2** of the user's body is not in contact with the first electrode **441**. The processor may identify the impedance value between the first electrode **441** and the second electrode **442**, and when the identified impedance value is equal to or less than a reference value, it may determine that a user's body contacts the first electrode **441** and the second electrode **442**. According to an embodiment, while obtaining information on the user's body, the processor may be configured to continuously monitor an impedance value between the plurality of electrodes **440** in order to identify whether the user's body is in contact with the plurality of electrodes **440**.

(74) According to an embodiment, the processor may identify whether the first electrode **441** is electrically disconnected from the conductive frame **412** in response to identifying the designated event. The designated event may mean receiving an input signal of a user requesting information on the user's body or detecting that the designated mode of the electronic device **400** is changed to another designated mode. According to an embodiment, the processor may identify whether the first electrode **441** and the conductive frame **412** are electrically disconnected based on identifying whether an impedance value between the first electrode **441** and the conductive frame **412** is equal to or less than a reference value. For example, moisture may penetrate into the first through hole **413** along a fine gap between the conductive frame **412** and the second conductive member **462** and may be positioned in the air gap **g** between the first non-conductive member **461** and the second non-conductive member **462**. The moisture moved into the air gap **g** may contact the first electrode **441** and the conductive frame **412** to electrically connect the first electrode **441** and the conductive frame **412**. When the first electrode **441** and the conductive frame **412** are electrically connected to each other, an impedance value between the first electrode **441** and the conductive frame **412** may be measured to be lower than that when the first electrode **441** and the conductive frame **412** are electrically disconnected. According to an embodiment, the processor of the electronic device **400** may identify whether the first electrode **441** and the conductive frame **412** are electrically disconnected by identifying that the impedance value between the first electrode **441** and the conductive frame **412** is equal to or less than a reference value.

(75) According to an embodiment, the processor may be configured to obtain information on the user's body through the first electrode **441** and the second electrode **442** based on identifying that the first electrode **441** is electrically disconnected from the conductive frame **412**, and refrain from obtaining information on the user's body based on identifying that the first electrode **441** is electrically connected to the conductive frame **412**. For example, when the first electrode **441** and the conductive frame **412** are connected by moisture, the first electrode **441** may form an indirect electrical connection to a part **B1** of the body via the conductive frame **412** and/or the binding member **420** in contact with part **B1** of the body. When the first electrode **441** forms an indirect electrical connection with the part **B1** of the body, an impedance value between the first electrode **441** and the second electrode **442** may be less than or equal to a reference value in a state where the second electrode **442** contacts the part **B1** of the user's body. When an impedance value equal to or

lower than the reference value is identified, the processor may initiate an operation of obtaining information on the user's body and may malfunction, since normal contact with different parts of the body (B1, B2) and abnormal contact with part of the body (B1) are not distinguished by impedance values. For example, in the case of obtaining information on the user's electrocardiogram, since only a part B1 of the user's body comes into contact with the first electrode 441 and the second electrode 442 when the conductive frame 412 and the first electrode 441 are electrically connected, the electrical closed circuit formed by the first electrode 441 and the second electrode 442 does not pass through the user's heart, and the processor may not accurately obtain information on the user's electrocardiogram. Since the processor does not obtain information on the electrocardiogram, the processor may repeatedly perform an operation of determining whether the body is in contact again to cause a malfunction.

(76) According to the above-described embodiment, the electronic device 400 may identify whether the processor electrically disconnects the first electrode 441 and the conductive frame 412, and the electronic device 400 may prevent a malfunction of the processor by stopping obtaining information on the user's body when the electrical connection between the first electrode 441 and the conductive frame 412 is identified.

(77) Meanwhile, although the structure of FIG. 4B has been described with respect to the first through hole 413 and the first electrode 441, the description of FIG. 4B may be equally applied to the second through hole 414 and the third electrode 443. For example, the non-conductive member 460 may include a third non-conductive member (not illustrated) and a fourth non-conductive member (not illustrated) that coupled to the conductive frame 412 to contact the inner surface of the second through hole 414, and the third electrode 443 and spaced apart from each other. For another example, the sealing member 470 may further include a second sealing member (not illustrated) that seals the second through hole 414 by surrounding the third electrode 443.

(78) FIG. 5A is a block diagram of an electronic device according to an embodiment, and FIG. 5B is a diagram illustrating an example of providing a notification of whether an electronic device is submerged, according to an embodiment.

(79) According to an embodiment, referring to FIGS. 5A and 5B, the electronic device 400 may include a conductive frame 412, a display 430, a first electrode 441, a second electrode 442, a sensor 510, an impedance measurement circuit 520, at least one switch 530, an actuator 540, and a processor 550. The conductive frame 412 of FIGS. 5A and 5B, the display 430, the first electrode 441, and the second electrode 442 may be substantially the same as the conductive frame 412 of FIGS. 4A and/or 4B, the display 430, the first electrode 441, and the second electrode 442, respectively, and thus repeated descriptions thereof will be omitted.

(80) The sensor 510 may be configured to obtain information on a user's body by receiving an electrical signal received from the first electrode 441 and the second electrode 442. The sensor 510 may obtain information on the user's body and transmit the obtained information to the processor 550. For example, the sensor 510 may be at least one of an electrocardiogram (ECG) sensor, a bioelectrical impedance analysis (BIA) sensor, an electroencephalogram (EEG) sensor, and a galvanic skin response (GSR) sensor.

(81) The impedance measurement circuit 520 may obtain impedance values between the conductive frame 412, the first electrode 441, and the second electrode 442. For example, the impedance measurement circuit 520 may be electrically connected to the conductive frame 412 and the first electrode 441, thereby measuring an impedance value between the conductive frame 412 and the first electrode 441. For another example, the impedance measurement circuit 520 may be electrically connected to the first electrode 441 and the second electrode 442, thereby measuring an impedance value between the first electrode 441 and the second electrode 442.

(82) The at least one switch 530 may selectively connect at least one of the conductive frame 412, the first electrode 441, and the second electrode 442 to the impedance measurement circuit 520. According to an embodiment, the at least one switch 530 may switch to a first state A connecting

the conductive frame **412** and the first electrode **441** to the impedance measurement circuit **520** and a second state B connecting the first electrode **441** and the second electrode **442**.

(83) The actuator **540** may discharge moisture penetrating into the first through hole (e.g., the first through hole **413** of FIGS. **4A** and/or **4B**) or the second through hole (e.g., the second through hole **414** of FIG. **4A**) to the outside of the electronic device **400**. According to an embodiment, the actuator **540** may be disposed in the housing (e.g., the housing **410** of FIG. **4A** and/or FIG. **4B**) to vibrate the electronic device **400** or a designated component (e.g., the sound output module **155** of FIG. **1**) in the electronic device **400**, thereby discharging moisture to the outside of the electronic device **400**.

(84) The processor **550** may be operatively coupled to the display **430**, the sensor **510**, the impedance measurement circuit **520**, at least one switch **530**, and the actuator **540**. The processor **550** may identify whether the first electrode **441** is electrically disconnected from the conductive frame **412** in response to identifying the designated event. According to an embodiment, the designated event may include receiving an input signal of a user requesting information on a user's body. For example, when the user wants to obtain information on the body, the user may execute software (e.g., an application) used to provide information on the body by touching the display **430** or pressing the first electrode **441**. When execution (e.g., application execution) of software used to provide information on the body is detected, the processor **550** may perform an operation for identifying whether the first electrode **441** is electrically disconnected from the conductive frame **412**. According to another embodiment, the designated event may include identifying that the mode of the electronic device **400** is changed from the first designated mode to the second designated mode. The first designated mode may mean a swimming mode of the electronic device **400**, and the second designated mode may mean another operation mode of the electronic device **400** other than the swimming mode. The swimming mode of the electronic device **400** may mean an operating state of the electronic device **400** when a user swims while wearing the electronic device **400**. For example, when the electronic device **400** enters the swimming mode, the processor **550** may control the display **430** so that a touch input through the display **430** is not received. According to another embodiment, the designated event may include identifying whether moisture has penetrated into the electronic device **400** through a moisture detecting sensor (e.g., an atmospheric pressure sensor).

(85) According to an embodiment, the processor **550** may electrically connect the impedance measurement circuit **520** to the first electrode **441**, and the conductive frame **512** through the at least one switch **530** by switching the at least one switch **530** to the first state A, in response to identifying the designated event. The processor **550** may identify whether the first electrode **441** is electrically disconnected from the conductive frame **412** based on the impedance value between the first electrode **441** and the conductive frame **512** obtained through the impedance measurement circuit **520**. For example, the processor **550** may identify that the first electrode **441** is electrically connected to the conductive frame **412** based on identifying that the impedance value between the first electrode **441** and the conductive frame **412** is equal to or less than a reference value. For another example, the processor **550** may identify that the first electrode **441** is electrically disconnected from the conductive frame **412** based on identifying that the impedance value between the first electrode **441** and the conductive frame **412** is greater than the reference value.

(86) According to an embodiment, the processor **550** may be configured to obtain information on a user's body through the first electrode **441** and the second electrode **442**, based on identifying that the first electrode **441** is electrically disconnected from the conductive frame **412**. For example, the processor **550** may electrically connect the first electrode **441** and the second electrode **442** to the impedance measurement circuit **520** through the at least one switch **530** by switching the at least one switch **530** from the first state A to the second state B based on identifying that the first electrode **441** is electrically disconnected from the conductive frame **412**. As the at least one switch **530** is switched from the first state A to the second state B, the impedance measurement circuit **520**

and the conductive frame **412** may be electrically disconnected. According to an embodiment, the sensor **510** may obtain information on a user's bio-signal (e.g., an electrocardiogram) based on the electrical signals received by the first electrode **441** contacting a part of the body (e.g., part **B1** of the body in FIG. **4A**) and the second electrode **442** contacting another part of the body (e.g., part **B2** of the body in FIG. **4A**). The processor **550** may receive information on the user's bio-signal (e.g., ECG) acquired by the sensor **510** and notify the user of information on the user's bio-signal (e.g., ECG) through the display **430**.

(87) According to an embodiment, the processor **550** may identify whether the user's body contacts the first electrode **441** and the second electrode **442** based on identifying whether the impedance value between the first electrode **441** and the second electrode **442** is equal to or less than a reference value through the impedance measurement circuit **520**. For example, when it is identified that the impedance value between the first electrode **441** and the second electrode **442** is less than or equal to the reference value, the processor **550** may obtain information on the user's body through the sensor **510**. The processor **550** may notify the user of information on the user's body by outputting information on the user's body obtained through the sensor **510** to the display **430**. For another example, the processor **550** may provide a notification to the user to check the physical contact state based on identifying that the impedance value between the first electrode **441** and the second electrode **442** exceeds the reference value. The processor **550** may provide a visual notification for guiding contact with the body through the display **430**, a tactile notification that induces physical contact by vibrating the electronic device **400** through the actuator **540**, or an audible notification that induces physical contact through the sound output module (e.g., the sound output module **155** of FIG. **1**).

(88) According to an embodiment, the processor **550** may be configured to refrain from obtaining information on the user's body based on identifying that the first electrode **441** is electrically connected to the conductive frame **412**. When identifying that the first electrode **441** is electrically connected to the conductive frame **412**, the processor **550** may provide a notification that the electronic device **400** is submerged. For example, the processor **550** may provide a visual notification to the user that moisture has penetrated into the electronic device **400** through the display **430**. For another example, the processor **550** may provide a visual guide so that the user may remove moisture in the electronic device **400** through the display **430**. The visual guide provided through the display **430** may indicate an operation in which a user may remove moisture by shaking the electronic device **400** or may refer to a picture or a video indicating a method of drying the electronic device **400**. For another example, the processor **550** may remove moisture in the electronic device **400** by operating the actuator **540** to vibrate the electronic device **400**.

(89) As described above, according to an embodiment, the electronic device **400** may identify whether the electronic device **400** is submerged by identifying whether the first electrode **441** is electrically disconnected from the conductive frame **412** without including an additional sensor. For example, the electronic device **400** may include an impedance measurement circuit **520** to identify whether the user's body maintains contact with the first electrode **441** and the second electrode **442**. The electronic device **400** according to an embodiment may easily detect whether the electronic device **400** is submerged by connecting the conductive frame **412** and the first electrode **441** to the impedance measurement circuit **520** for checking the body contact state, and thus may not include a separate sensor for detecting submerging. As it is unnecessary to include a separate additional sensor, the electronic device **400** according to an embodiment may include a relatively simple circuit structure.

(90) FIG. **6** is a block diagram of an electronic device according to an embodiment.

(91) Referring to FIG. **6**, the electronic device **400** according to an embodiment may include a conductive frame **412**, a display **430**, a first electrode **441**, a second electrode **442**, a third electrode **443**, a fourth electrode **444**, a sensor **510**, an impedance measurement circuit **520**, at least one switch **530**, an actuator **540**, and a processor **550**.

(92) The conductive frame **412** of FIG. **6**, the display **430**, the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444** may be substantially the same as the conductive frame **412** of FIGS. **4A** and/or **4B**, display **430**, the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444**, respectively, and the sensor **510** of FIG. **6**, the impedance measurement circuit **520**, at least one switch **530**, the actuator **540**, and the processor **550** may be substantially the same as the sensor **510** of FIGS. **5A**, the impedance measurement circuit **520**, at least one switch **530**, the actuator **540**, and the processor **550**, respectively, and thus, repeated descriptions thereof will be omitted.

(93) According to an embodiment, the sensor **510** may be configured to obtain information on a user's body by receiving electrical signals received from the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444**.

(94) The impedance measurement circuit **520** may obtain impedance values between the conductive frame **412**, the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444**. For example, the impedance measurement circuit **520** may be electrically connected to the conductive frame **412** and the first electrode **441**, thereby measuring an impedance value between the conductive frame **412** and the first electrode **441**. For another example, the impedance measurement circuit **520** may be electrically connected to the conductive frame **412** and the third electrode **442**, thereby measuring an impedance value between the conductive frame **412** and the third electrode **442**. For another example, the impedance measurement circuit **520** may be electrically connected to the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444** through at least one switch **530**, thereby measuring impedance values between the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444**.

(95) According to an embodiment, the at least one switch **530** may selectively connect at least one of the conductive frame **412**, the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444** to the impedance measurement circuit **520**. According to an embodiment, the at least one switch **530** may switch to a first state A connecting the conductive frame **412** and the first electrode **441** to the impedance measurement circuit **520**, a second state B connecting the conductive frame **412** and the third electrode **443** to the impedance measurement circuit **520**, and a third state C that connects the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444** to the impedance measurement circuit **520**.

(96) According to an embodiment, the processor **550** may identify whether the first electrode **441** or the third electrode **443** is electrically disconnected from the conductive frame **412** in response to identifying a designated event. For example, in response to identifying the designated event, the processor **550** may electrically connect the impedance measurement circuit **520** to the first electrode **441**, and the conductive frame **512** through at least one switch **530** by switching the at least one switch **530** to the first state A. The processor **550** may identify whether the first electrode **441** is electrically disconnected from the conductive frame **412** based on the impedance value between the first electrode **441** and the conductive frame **512** obtained through the impedance measurement circuit **520**. For another example, in response to identifying the designated event, the processor **550** may electrically connect the impedance measurement circuit **520** to the third electrode **443**, and the conductive frame **412** through the at least one switch **530** by switching the at least one switch **530** to the second state B. The processor **550** may identify whether the third electrode **443** is electrically disconnected from the conductive frame **412** based on the impedance value between the third electrode **443** and the conductive frame **512** obtained through the impedance measurement circuit **520**. According to an embodiment, the order in which the first electrode **441** and the conductive frame **412** are connected to the impedance measurement circuit **520** and the third electrode **443** and the conductive frame **412** are connected may be arbitrarily changed.

(97) According to an embodiment, the processor **550** may be configured to obtain information on a

user's body through the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444**, based on identifying that the first electrode **441** is electrically disconnected from the conductive frame **412** and the third electrode **443** is electrically disconnected from the conductive frame **412**. For example, by switching at least one switch **530** from the first state A or the second state B to the third state C, the processor **550** may electrically connect the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444** to the impedance measurement circuit **520**. As the at least one switch **530** is switched to the third state C, the impedance measurement circuit **520** and the conductive frame **412** may be electrically disconnected. According to an embodiment, the sensor **510** may obtain information on the user's bio-electric resistance based on the electrical signals received to the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444**. The processor **550** may receive information on the user's bio-electrical resistance from the sensor **510** and notify the user of information on the user's bio-electrical resistance through the display **430**.

(98) According to an embodiment, the processor **550** may be configured to refrain from obtaining information on a user's body based on identifying that the first electrode **441** is electrically connected to the conductive frame **412**, or that the third electrode **443** is electrically connected to the conductive frame **412**. For example, the processor **550** may identify that the first electrode **441** or the third electrode **443** is electrically connected to the conductive frame **412**. Based on identifying that an impedance value between the first electrode **441** and the conductive frame **412** or an impedance value between the third electrode **443** and the conductive frame **412** is less than or equal to a reference value. When identifying that the first electrode **441** or the third electrode **443** is electrically connected to the conductive frame **412**, the processor **550** may provide a notification to the user that the electronic device **400** is submerged. For example, the processor **550** may provide a visual notification to the user that moisture has penetrated into the electronic device **400** through the display **430**. For example, the processor **550** may provide a visual notification to the user that moisture has penetrated into the electronic device **400** through the display **430**. For another example, the processor **550** may remove moisture in the electronic device **400** by operating the actuator **540** to vibrate the electronic device **400**.

(99) As described above, according to an embodiment, the electronic device **400** may identify whether the electronic device **400** is submerged by identifying whether the first electrode **441** or the third electrode **443** is electrically disconnected from the conductive frame **412** without including an additional sensor. For example, the electronic device **400** may include an impedance measurement circuit **520** to identify whether a user's body maintains contact with the first electrode **441**, the second electrode **442**, the third electrode **443**, and the fourth electrode **444**. The electronic device **400** according to an embodiment may not include a separate sensor for detecting submerging, since it is possible to easily detect whether the electronic device **400** is submerged by connecting the conductive frame **412** to the first electrode **441** or third electrode **443** to the impedance measurement circuit **520** to check the physical contact condition. As a separate additional sensor is not required, the electronic device **400** according to an embodiment may include a relatively simple circuit structure.

(100) FIG. 7 illustrates an example of an operation of a processor of an electronic device, according to an embodiment.

(101) The operation illustrated in FIG. 7 may be performed by the electronic device **400** illustrated in FIGS. 4A, 4B, 5A, and/or 5B.

(102) Referring to FIG. 7, in operation **710**, an electronic device (e.g., a processor **550** of the electronic device **400** of FIG. 4A) may identify a designated event. According to an embodiment, the designated event may include receiving an input signal of a user requesting information on a user's body or changing a designated mode of the electronic device. For example, the designated event may include detecting execution of software (e.g., execution of an application) used to provide information on the body. As another example, the designated event may include identifying

that the mode of the electronic device is changed from the first designated mode to the second designated mode. According to an embodiment, the first designated mode may mean a swimming mode of the electronic device, and the second designated mode may mean an operation mode of the electronic device other than the swimming mode.

(103) In operation **720**, the processor may identify whether the first electrode (e.g., the first electrode **441** of FIG. **4A**) is electrically disconnected from the conductive frame (e.g., the conductive frame **412** of FIG. **4A**) based on responding to the designated event. According to an embodiment, the processor may identify whether the first electrode is electrically disconnected from the conductive frame based on an impedance value between the first electrode and the conductive frame obtained through an impedance measurement circuit (e.g., the impedance measurement circuit **520** of FIG. **5A**). For example, the processor may identify that the first electrode is electrically connected to the conductive frame when the impedance value between the first electrode and the conductive frame is less than or equal to the reference value. For another example, the processor may identify that the first electrode is electrically disconnected from the conductive frame when the impedance value between the first electrode and the conductive frame exceeds the reference value.

(104) In operation **730**, the processor may obtain information on a user's body through the first electrode and the second electrode (e.g., the second electrode **442** of FIG. **4A**) based on identifying that the first electrode is electrically disconnected from the conductive frame. According to an embodiment, the processor may disconnect the conductive frame and the impedance measurement circuit through at least one switch (e.g., at least one switch **530** of FIG. **5A**), and may electrically connect the impedance measurement circuit to the first electrode and the second electrode. According to an embodiment, the first electrode and the second electrode may receive an electrical signal generated in the user's body in order to obtain information on the user's bio signal by contacting different parts of the user's body (e.g., different parts of the body (**B1**, **B2**) in FIG. **4A**). According to an embodiment, the first electrode and the second electrode may receive an electrical signal related to a user's bio-signal (e.g., ECG) by forming an electrical closed circuit pass through the user's heart with a part of the user's body.

(105) In operation **740**, the processor may refrain from obtaining information on the user's body based on identifying that the first electrode is electrically connected to the conductive frame. According to an embodiment, the processor may provide a user with a notification of whether the electronic device is submerged through a display (e.g., the display **430** of FIG. **4A**). According to another embodiment, the processor may remove moisture penetrating into the electronic device by vibrating the electronic device through an actuator (e.g., the actuator **540** in FIG. **5A**).

(106) As described above, according to an embodiment, the electronic device **400** may identify whether the electronic device **400** is submerged by identifying whether the first electrode **441** or the third electrode **443** is electrically disconnected from the conductive frame **412** without including an additional sensor.

(107) FIG. **8** illustrates an example of an operation of a processor of an electronic device, according to an embodiment.

(108) The operation illustrated in FIG. **8** may be performed by the electronic device **400** illustrated in FIGS. **4A**, **4B**, **5A**, and/or **5B**.

(109) Referring to FIG. **8**, operation **810** may be substantially the same as operation **710** of FIG. **7**, and thus a repeated description thereof will be omitted.

(110) In operation **820**, in response to identifying a designated event, the processor (e.g., the processor **550** of FIG. **5A**) may identify whether a first electrode (e.g., the first electrode **441** of FIG. **4A**) or a third electrode (e.g., the third electrode **443** of FIG. **4A**) is electrically disconnected from a conductive frame (e.g., the conductive frame **412** of FIG. **4A**). According to an embodiment, the processor may identify whether the first electrode or the third electrode is electrically disconnected from the conductive frame, based on whether the impedance value

between the first electrode and the conductive frame or between the third electrode and the conductive frame exceeds the reference value. For example, when an impedance value between the first electrode and the conductive frame or an impedance value between the third electrode and the conductive frame is less than or equal to a reference value, the processor may identify that the first electrode or the third electrode is electrically connected to the conductive frame.

(111) In operation **830**, the processor may obtain information on the user's body through the first electrode, the second electrode, the third electrode, and the fourth electrode based on identifying that the first electrode is electrically disconnected from the conductive frame and the third electrode is electrically disconnected from the conductive frame. According to an embodiment, the first electrode, the second electrode, the third electrode, and the fourth electrode may receive an electrical signal generated in the user's body in order to obtain information on the user's bio signal by contacting different parts of the user's body (e.g., different parts of the body **B1** and **B2** in FIG. **4A**). For example, the second electrode and the fourth electrode may contact different areas of the left hand, which are part of the user's body (e.g., part **B1** of the body illustrated in FIG. **4A**), and the first electrode and the third electrode may contact different fingers of the right hand, which are another part of the user's body (e.g., the other part **B2** of the body of FIG. **4A**). The first electrode, the second electrode, the third electrode, and the fourth electrode contacting different parts of the user's body may form an electrical closed circuit together with different parts of the user's body. According to an embodiment, the processor may obtain information on the user's bio electrical resistance based on an electrical signal received by the first electrode, the second electrode, the third electrode, and the fourth electrode.

(112) In operation **840**, according to an embodiment, the processor may be configured to refrain from obtaining information on the user's body, based on identifying that the first electrode is electrically connected to the conductive frame or that the third electrode is electrically connected to the conductive frame. According to an embodiment, when identifying that the first electrode or the third electrode is electrically connected to the conductive frame, the processor may provide a user with a notification that the electronic device is submerged. For example, the processor may provide a visual notification to the user that moisture has penetrated into the electronic device (e.g., the electronic device **400** of FIG. **4A**) through the display (e.g., the display **430** of FIG. **4A**). For another example, the processor may remove moisture in the electronic device by operating the actuator (e.g., the actuator **540** of FIG. **5A**) to vibrate the electronic device.

(113) As described above, according to an embodiment, the electronic device may identify whether the electronic device is submerged by identifying whether the first electrode or the third electrode is electrically disconnected from the conductive frame without including an additional sensor.

(114) According to an embodiment, an electronic device may comprise a housing (e.g. the housing **410** in FIG. **4A**) including a first surface (e.g., the first face **410a** of FIG. **4A**), a second surface (e.g., the second face **410b** of FIG. **4A**), facing the first surface and facing a part of the user's body when the electronic device (e.g., the electronic device **400** of FIG. **4A**) is worn to the user, and a conductive frame (e.g., the conductive frame **412** of FIG. **4A**) disposed between the first surface and the second surface and including a through-hole (e.g., the first through hole **413** of FIG. **4A**), a first electrode (e.g., the first electrode **441** of FIG. **4A**) spaced apart from an inner surface of the through-hole, and movable within the through-hole, a part of the first electrode protruding to outside of the conductive frame, a second electrode (e.g., the second electrode **442** of FIG. **4A**) disposed on the second surface, and contact with the part of the user's body when the electronic device is worn to the user, and a processor (e.g., the processor **550** of FIG. **5A**); wherein the processor may be configured to, in response to identifying a designated event, identify whether the first electrode is electrically disconnected to the conductive frame; obtain an information about the user' body through the first electrode and the second electrode, based on identifying the first electrode is electrically disconnected to the conductive frame; and refrain from obtaining the information based on identifying the first electrode is electrically connected to the conductive

frame.

(115) According to an embodiment, the processor may be configured to identify that the first electrode is electrically connected to the conductive frame, based on identifying that an impedance value between the first electrode and the conductive frame is less than or equal to a reference value, and identify that the first electrode is electrically disconnected to the conductive frame, based on identifying that the impedance value exceeds the reference value.

(116) According to an embodiment, the electronic device may further comprise an impedance measurement circuit (e.g., the impedance measurement circuit **520** of FIG. 5A) within the housing, and at least one switch (e.g., at least one switch **530** of FIG. 5A) within the housing, wherein, the processor may be configured to, in response to identifying the designated event, identify whether the first electrode is electrically disconnected to the conductive frame based on an impedance value between the first electrode and the conductive frame, by electrically connecting the impedance measurement circuit with the first electrode and the conductive frame via at least one switch, based on identifying the first electrode is electrically disconnected to the conductive frame, disconnect the conductive frame from the impedance circuit via at least one switch, and connect the impedance circuit with the first electrode and the second electrode via at least one switch.

(117) According to an embodiment, the processor may obtain the information through the first electrode in contact with another part of the user's body and the second electrode in contact with the part of the user's body, based on identifying the first electrode is electrically connected to the conductive frame.

(118) According to an embodiment, the designated event may include detecting the execution of software used for providing the information.

(119) According to an embodiment, the designated event may include identifying the mode of the electronic device is changed from a first designated mode to a second designated mode.

(120) According to an embodiment, the processor may be configured to provide a notification about whether the electronic device has submerged to the user, based on identifying the first electrode is electrically connected to the conductive frame.

(121) According to an embodiment, the electronic device may further comprise an actuator disposed within the housing, wherein, the processor may be configured to vibrate the electronic device through the actuator (e.g., the actuator **540** of FIG. 5A) based on identifying the first electrode is electrically connected to the conductive frame.

(122) According to an embodiment, the first electrode may extend from the inside of the housing along a direction perpendicular to a direction the first surface faces.

(123) According to an embodiment, the electronic device may further comprise a sealing member (e.g., the sealing member **470** of FIG. 4A) sealing the through-hole by surrounding the first electrode.

(124) According to an embodiment, the electronic device may further include a first non-conductive member (e.g., the first non-conductive member **461** in FIG. 4A) and a second non-conductive member (e.g., the second non-conductive member **462** in FIG. 4A) spaced apart from each other and coupled to the conductive frame to be in contact an inner surface of the through-hole and the first electrode.

(125) According to an embodiment, an electronic device may comprise a housing (e.g., housing **410** in FIG. 4A) including a first surface (e.g., the first surface **410a** of FIG. 4A), a second surface (e.g., the second surface **410b** of FIG. 4A) facing the first surface and facing a part of the user's body when the electronic device (e.g., the electronic device **400** of FIG. 4A) is worn to the user, and a conductive frame disposed between the first surface and the second surface and including a first through-hole (e.g., the first through hole **413** of FIG. 4A), and a second through-hole (e.g., the second through hole **414** of FIG. 4A), a display (e.g., the display **420** of FIG. 4A) disposed on the first surface, a first electrode (e.g., the first electrode **441** of FIG. 4A) spaced apart from an inner surface of the first through-hole, and movable within the first through-hole and a part of the first

electrode protruding to outside of the conductive frame, a second electrode (e.g., the second electrode **442** of FIG. 4A) disposed on the second surface, and contact with the part of the user's body when the electronic device is worn to the user, a third electrode (e.g., the third electrode **443** of FIG. 4A) spaced apart from an inner surface of the second through-hole, and movable within the second through-hole, and a part of the third electrode protruding to outside of the conductive frame, a fourth electrode (e.g., the fourth electrode **444** of FIG. 4A) disposed on the second surface spaced apart from the second electrode, and contact with the part of the user's body when the electronic device is worn to the user, and processor; wherein, the processor may be configured to, in response to identifying a designated event, identify whether the first electrode or the third electrode is electrically disconnected to the conductive frame; obtain an information about the user's body through the first electrode, the second electrode, the third electrode, and the fourth electrode, based on identifying the first electrode is electrically disconnected to the conductive frame and identifying the third electrode is electrically disconnected to the conductive frame; and refrain from obtaining the information, based on identifying the first electrode is electrically connected to the conductive frame or the third electrode is electrically connected to the conductive frame.

(126) According to an embodiment, the processor may be configured to identify that the first electrode or the third electrode is electrically connected to the conductive frame, based on identifying that an impedance value between the first electrode and the conductive frame or the third electrode and the conductive frame is less than or equal to a reference value, and identify that the first electrode or the third electrode is electrically disconnected to the conductive frame, based on identifying that the impedance value exceeds the reference value.

(127) According to an embodiment, the designated event may include detecting the execution of software used for providing the information.

(128) According to an embodiment, the designated event may include identifying the mode of the electronic device is changed from a first designated mode to a second designated mode.

(129) According to an embodiment, the processor may be configured to obtain the information through the first electrode, the second electrode, the third electrode, and the fourth electrode in contact with the different parts of the user's body, based on identifying the first electrode is electrically disconnected to the conductive frame and identifying the third electrode is electrically disconnected to the conductive frame.

(130) According to an embodiment, the processor may be configured to provide a notification through the display to the user that the electronic device has been submerged, based on identifying the first electrode is electrically connected to the conductive frame or the third electrode is electrically connected to the conductive frame.

(131) According to an embodiment, the electronic device may further include an actuator (e.g., the actuator **540** of FIG. 5A) disposed within the housing, wherein the processor may be configured to vibrate the electronic device through the actuator, based on identifying the first electrode or the third electrode is electrically connected to the conductive frame.

(132) According to an embodiment, the electronic device may further include a first sealing member (e.g., the first sealing member **471** of FIG. 4A) sealing the first through-hole by surrounding the first electrode, and a second sealing member sealing the second through-hole by surrounding the third electrode.

(133) According to an embodiment, the electronic device may further include a first non-conductive member (e.g., the first non-conductive member **461** of FIG. 4A) and a second non-conductive member spaced apart from each other and coupled to the conductive frame to be in contact an inner surface of the first through-hole and the first electrode, and a third non-conductive member (e.g., the second non-conductive member **462** of FIG. 4A) and a fourth non-conductive member spaced apart from each other and coupled to the conductive frame to be in contact an inner surface of the second through-hole and the third electrode.

(134) The electronic device according to various embodiments may be one of various types of

electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(135) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(136) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(137) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., an internal memory **136** or an external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(138) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., a compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(139) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the

multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added. (140) While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the appended claims and their equivalents.

Claims

1. An electronic device comprising: a housing including: a front surface, a rear surface, and a side surface including a conductive frame, the side surface positioned between the front surface and the rear surface; a first electrode spaced apart from the conductive frame and protruding to outside of the side surface; a second electrode disposed on the rear surface, and in contact with a part of a body of a user when the electronic device is worn on the user; impedance measurement circuitry; memory, in the housing, comprising one or more storage media storing instructions; and at least one processor in the housing, the at least one processor comprising processing circuitry, wherein the instructions that, when executed by the at least one processor individually or collectively, cause the electronic device to: obtain, through the first electrode, an electric signal, identify, using the impedance measurement circuitry, whether the first electrode is electrically disconnected from the conductive frame based on the electric signal, in response to identifying that the first electrode is electrically disconnected from the conductive frame, obtain biometric data about the body through the first electrode and the second electrode, and in response to identifying that the first electrode is electrically connected to the conductive frame, refrain from obtaining the biometric data about the body.
2. The electronic device of claim 1, wherein the instructions that, when executed by the at least one processor individually or collectively, further cause the electronic device to: identify an impedance value using the impedance measurement circuitry, identify that the first electrode is electrically connected to the conductive frame, based on identifying that the impedance value between the first electrode and the conductive frame is less than a reference value, and identify that the first electrode is electrically disconnected from the conductive frame, based on identifying that the impedance value exceeds the reference value.
3. The electronic device of claim 1, further comprising: at least one switch within the housing, wherein the impedance measurement circuitry is disposed in the housing; and wherein the instructions that, when executed by the at least one processor individually or collectively, further cause the electronic device to: identify whether the first electrode is electrically disconnected from the conductive frame based on an impedance value between the first electrode and the conductive frame, by electrically connecting the impedance measurement circuitry with the first electrode and the conductive frame via the at least one switch, and based on identifying the first electrode is electrically disconnected from the conductive frame, disconnect the conductive frame from the impedance measurement circuitry via the at least one switch, and connect the impedance measurement circuitry with the first electrode and the second electrode via the at least one switch.
4. The electronic device of claim 1, wherein the instructions that, when executed by the at least one

- processor individually or collectively, further cause the electronic device to obtain the biometric data through the first electrode in contact with another part of the body and the second electrode in contact with the part of the body, based on identifying that the first electrode is electrically connected to the conductive frame.
5. The electronic device of claim 1, wherein the instructions that, when executed by the at least one processor individually or collectively, further cause the electronic device to: identify an input requesting for obtaining the biometric data, and in response to identifying the input: in case of identifying that the first electrode is electrically connected to the conductive frame, refrain from obtaining the biometric data, and in case of identifying that the first electrode is electrically disconnected from the conductive frame, obtain the biometric data.
6. The electronic device of claim 1, wherein the instructions that, when executed by the at least one processor individually or collectively, further cause the electronic device to: provide a notification indicating that the electronic device has submerged, based on identifying that the first electrode is electrically connected to the conductive frame.
7. The electronic device of claim 1, further comprising: an actuator disposed within the housing, wherein the instructions that, when executed by the at least one processor individually or collectively, further cause the electronic device to: vibrate the electronic device through the actuator based on identifying that the first electrode is electrically connected to the conductive frame.
8. The electronic device of claim 1, wherein the first electrode is protruded from an inside of the housing through a through-hole within the conductive frame.
9. The electronic device of claim 1, further comprising a first non-conductive member and a second non-conductive member spaced apart from each other and coupled to the conductive frame to be in contact with an inner surface of a through-hole and the first electrode.
10. The electronic device of claim 1, further comprising: a third electrode, the third electrode electrically spaced apart from both the conductive frame and the first electrode; and a fourth electrode disposed on the rear surface to be contacted with another portion of the body when the electronic device is worn by the user, the fourth electrode electrically spaced apart from the conductive frame, wherein the instructions that, when executed by the at least one processor individually or collectively, cause the electronic device to: in response to identifying a designated event, identify whether the first electrode or the third electrode is electrically disconnected from the conductive frame, in response to identifying that the first electrode is electrically disconnected from the conductive frame and identifying that the third electrode is electrically disconnected from the conductive frame, obtain biometric data about the user through the first electrode, the second electrode, the third electrode, and the fourth electrode, and in response to identifying that the first electrode is electrically connected to the conductive frame or the third electrode is electrically connected to the conductive frame, refrain from obtaining the biometric data about the user.
11. The electronic device of claim 1, wherein the conductive frame is configured to function as an antenna radiator.
12. The electronic device of claim 1, wherein the instructions that, when executed by the at least one processor individually or collectively, cause the electronic device to: identify an impedance value using another electric signal obtained through the second electrode and the first electrode, identify whether the body is in contact with both the second electrode and the first electrode based on the impedance value, and obtain biometric data about the user, using the another electric signal, based on identifying that the body is in contact with both the second electrode and the first electrode.
13. The electronic device of claim 5, wherein the instructions that, when executed by the at least one processor individually or collectively, further cause the electronic device to: in response to identifying the input: obtain, through the first electrode, the electric signal.
14. The electronic device of claim 5, wherein the instructions that, when executed by the at least

one processor individually or collectively, cause the electronic device to: identify detecting execution of software used for providing the biometric data as the input requesting for obtaining the biometric data.

15. The electronic device of claim 5, wherein the instructions that, when executed by the at least one processor individually or collectively, cause the electronic device to: identify changing a mode of the electronic device from a first designated mode to a second designated mode as the input requesting for obtaining the biometric data.

16. The electronic device of claim 8, further comprising a sealing member sealing the through-hole by surrounding the first electrode.

17. The electronic device of claim 10, wherein the instructions that, when executed by the at least one processor individually or collectively, further cause the electronic device to: identify that the first electrode or the third electrode is electrically connected to the conductive frame, based on identifying that an impedance value between the first electrode and the conductive frame or the third electrode and the conductive frame is less than a reference value, and identify that the first electrode or the third electrode is electrically disconnected from the conductive frame, based on identifying that the impedance values between the first electrode and the conductive frame and between the third electrode and the conductive frame exceed the reference value.

18. The electronic device of claim 17, wherein the instructions that, when executed by the at least one processor individually or collectively, further cause the electronic device to: obtain the biometric data through the first electrode, the second electrode, the third electrode, and the fourth electrode in contact with different portions of the body, based on identifying that the first electrode is electrically disconnected from the conductive frame and identifying the third electrode is electrically disconnected from the conductive frame.

19. The electronic device of claim 17, wherein the first electrode is protruded from an inside of the housing through a through-hole within the conductive frame, wherein the third electrode is protruded from an inside of the housing through another through-hole within the conductive frame, and wherein the electronic device comprises: a first sealing member sealing the through-hole by surrounding the first electrode; and a second sealing member sealing the another through-hole by surrounding the third electrode.

20. The electronic device of claim 19, further comprising: a first non-conductive member and a second non-conductive member spaced apart from each other and coupled to the conductive frame to be in contact with an inner surface of the through-hole and the first electrode; and a third non-conductive member and a fourth non-conductive member spaced apart from each other and coupled to the conductive frame to be in contact with an inner surface of the another through-hole and the third electrode.
