

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12399543

Kind Code

B2

Date of Patent

August 26, 2025

Inventor(s)

Watanabe; Ryota et al.

Information processing apparatus for performing thermal control based on a specific combination of keys based on accepted operation signal

Abstract

An information processing apparatus includes: a controller that outputs notification information based on input information; and a processor that executes system processing based on an operating system (OS) and operation of thermal control processing by control of a Basic Input Output System (BIOS) using the notification information output from the controller. The controller accepts an operation signal indicative of an operated key according to a user's operation on a keyboard; determines whether the operated key is of a specific combination of keys based on the accepted operation signal; upon making a determination that the operated key is of the specific combination of keys, outputs, to the processor, a result of the determination as the notification information; and without another key being pressed after the result of the determination is output from the controller, the processor executes the thermal control processing based on the result of the determination.

Inventors: Watanabe; Ryota (Kanagawa, JP), Kamimura; Takuroh (Kanagawa, JP), Nakamura; Atsunobu (Kanagawa, JP), Seto; Yuichiro (Kanagawa, JP), Morishige; Yusaku (Kanagawa, JP), Ma; Ke (Kanagawa, JP)

Applicant: Lenovo Switzerland International GmbH (Zug, CH)

Family ID: 1000008782092

Assignee: Lenovo Switzerland International GmbH (Zug, CH)

Appl. No.: 18/498590

Filed: October 31, 2023

Prior Publication Data

Document Identifier

Publication Date

US 20240061481 A1

Feb. 22, 2024

Foreign Application Priority Data

JP 2020-192408 Nov. 19, 2020

Related U.S. Application Data

continuation parent-doc US 17183464 20210224 US 11853136 child-doc US 18498590

Publication Classification

Int. Cl.: G06F1/20 (20060101); G05B19/042 (20060101)

U.S. Cl.:

CPC G06F1/206 (20130101); G05B19/042 (20130101); G05B2219/23345 (20130101)

Field of Classification Search

CPC: G06F (1/206)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5862351	12/1998	He	710/104	G06F 9/4403
6134667	12/1999	Suzuki	361/679.48	G06F 1/206
2003/0058215	12/2002	Yamaji	345/156	G06F 3/0489
2003/0063071	12/2002	Wyatt	345/172	G06F 13/102
2003/0220721	12/2002	Cohen	700/301	G06F 1/3203
2005/0289372	12/2004	Park	713/300	G06F 1/3203
2009/0256546	12/2008	Wu	323/318	G06F 1/08
2009/0259348	12/2008	Syu	700/300	G06F 1/206
2009/0278679	12/2008	Dailey	340/500	G06F 9/542
2014/0298003	12/2013	Ali	713/2	G06F 9/4416
2020/0133358	12/2019	Mishra	N/A	G06V 10/774

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H08328698	12/1995	JP	N/A
2001005661	12/2000	JP	N/A

Primary Examiner: Suryawanshi; Suresh

Attorney, Agent or Firm: Osha Bergman Watanabe & Burton LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a continuation application of U.S. patent application Ser. No. 17/183,464, filed on Feb. 24, 2021, which claims priority to Japanese Patent Application No. 2020-192408, filed on Nov. 19, 2020. The contents of these applications are hereby incorporated herein by reference in their entirety.

TECHNICAL FIELD

(1) The present invention relates to an information processing apparatus and a control method.

BACKGROUND

(2) Information processing apparatuses such as personal computers generate heat according to the operation of electronic devices such as a CPU (Central Processing Unit) and raise the temperature thereof. Among the information processing apparatuses, there is an information processing apparatus configured to perform thermal control in order to suppress the rise in device temperature.

(3) In such an information processing apparatus, a temperature sensor and a cooling fan are provided for thermal control to measure the temperature of a major electronic device so as to control the settings such as the rotational speed of the fan based on the detection result of the temperature sensor (for example, see Japanese Unexamined Patent Application Publication No. 2007-226617). In order to perform the thermal control of the device, settings related to performance such as the upper limit power and the upper limit of the operating frequency of the CPU are also controlled.

(4) For example, in the above-described thermal control, there is an information processing apparatus capable of switching, with a user's operation, between such an operating mode as to give priority to performance, in which the upper limit of CPU power is set as high as possible to maximize the use of a cooling fan in order to suppress a temperature rise, and such an operating mode as to give priority to quietness, in which the upper limit of CPU power is set low to suppress a temperature rise in order to suppress the use of the cooling fan as little as possible. There is also an information processing apparatus which detects a placement state to perform thermal control according to the placement state, because the upper limit of allowable temperature varies depending on the placement state when the information processing apparatus is used, such as being used on a desk or being used on a lap.

(5) However, a driver running on an OS (Operating System) has been conventionally used to detect/determine the user's operation or the placement state in order to perform thermal control. Therefore, the thermal control function may not be able to be applied to such an OS as not to support the function of the driver, so its versatility is low.

SUMMARY

(6) One or more embodiments of the present embodiments provide an information processing apparatus and a control method which enable highly versatile thermal control independent of the type of OS.

(7) According to one or more embodiments, an information processing apparatus according to the first aspect of the present invention includes: a controller which outputs notification information according to input information; and a processor which functions as a system processing unit to execute system processing based on an OS (Operating System), and a BIOS processing unit to execute control related to the performance of the system processing by control of a BIOS (Basic Input Output System) based on the notification information output from the controller.

(8) The above information processing apparatus may be such that the controller includes: an acceptance unit which accepts, as the input information, a detection signal output from a sensor according to the movement of the information processing apparatus; and a determination unit which determines a placement state of the information processing apparatus based on the detection signal accepted by the acceptance unit, and outputs, to the BIOS processing unit, determination result information based on the determination result as the notification information, and the BIOS processing unit executes the control related to the performance of the system processing based on

the determination result information output from the controller.

(9) The above information processing apparatus may be such that the BIOS processing unit outputs, to the system processing unit, first setting information for setting an operating mode of the processor preset according to the placement state of the information processing apparatus as the control related to the performance of the system processing, and the system processing unit controls the processor based on the first setting information output from the BIOS processing unit.

(10) The above information processing apparatus may also be configured to further include a heat dissipation unit which replaces air inside a chassis of the information processing apparatus with outside air by the rotation of a fan, wherein the BIOS processing unit outputs, to the controller, second setting information for setting an operating mode related to fan rotation control of the heat dissipation unit preset according to the placement state of the information processing apparatus as the control related to the performance of the system processing, and the controller controls the rotation of the fan of the heat dissipation unit based on the second setting information output from the BIOS processing unit.

(11) The above information processing apparatus may also be such that the controller includes: an acceptance unit which accepts, as the input information, an operation signal indicative of an operated key according to a user's operation on a keyboard; and a determination unit which determines whether the operated key is a specific combination of keys or not based on the operation signal accepted by the acceptance unit, and when determining that the operated key is the specific combination of keys, outputs, to the BIOS processing unit, determination result information based on the determination result as the notification information, and the BIOS processing unit executes the control related to the performance of the system processing based on the determination result information output from the controller.

(12) The above information processing apparatus may further be such that the BIOS processing unit outputs, to the system processing unit, first setting information for setting an operating mode of the processor preset according to the specific combination of keys as the control related to the performance of the system processing, and the system processing unit controls the processor based on the first setting information output from the BIOS processing unit.

(13) The above information processing apparatus may further be configured to further include a heat dissipation unit which replaces air inside a chassis of the information processing apparatus with outside air by the rotation of a fan, wherein the BIOS processing unit outputs, to the controller, second setting information for setting an operating mode related to fan rotation control of the heat dissipation unit preset according to the specific combination of keys as the control related to the performance of the system processing, and the controller controls the rotation of the fan of the heat dissipation unit based on the second setting information output from the BIOS processing unit.

(14) In the above information processing apparatus, the first setting information may include information related to an upper limit of power consumption of the processor.

(15) In the above information processing apparatus, the first setting information may include information related to an upper limit of an operating frequency of the processor.

(16) A control method for an information processing apparatus according to the second aspect of the present invention includes: causing a system processing unit to execute system processing based on an OS (Operating System); causing a controller to output notification information according to input information; and causing a BIOS processing unit to execute control related to the performance of the system processing by control of a BIOS (Basic Input Output System) based on the notification information output from the controller.

(17) The above-described aspects of the present invention enable highly versatile thermal control independent of the type of OS.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view illustrating the appearance of an information processing apparatus according to a first embodiment.
- (2) FIG. 2 is a plan view schematically illustrating the inside of a second chassis of the information processing apparatus according to the first embodiment.
- (3) FIG. 3 is a block diagram illustrating an example of the hardware configuration of the information processing apparatus according to the first embodiment.
- (4) FIG. 4 is a block diagram illustrating an example of the functional configuration of the information processing apparatus according to the first embodiment.
- (5) FIG. 5 is a diagram illustrating an example of a fan table according to the first embodiment.
- (6) FIG. 6 is a diagram illustrating a CPU table according to the first embodiment.
- (7) FIG. 7 is a flowchart illustrating an example of thermal control processing according to the first embodiment.
- (8) FIGS. 8A and 8B are explanatory diagrams of the effect of thermal control according to the first embodiment.
- (9) FIG. 9 is a diagram illustrating an example of correspondences between keyboard operations and thermal control according to a second embodiment.
- (10) FIG. 10 is a block diagram illustrating an example of the functional configuration of an information processing apparatus according to the second embodiment.
- (11) FIG. 11 is a diagram illustrating an example of a fan table according to the second embodiment.
- (12) FIG. 12 is a diagram illustrating an example of a CPU table according to the second embodiment.
- (13) FIG. 13 is a flowchart illustrating an example of thermal control processing according to the second embodiment.

DETAILED DESCRIPTION

(14) Embodiments of the present invention will be described in detail below with reference to the accompanying drawings.

First Embodiment

(15) First, an overview of an information processing apparatus according to a first embodiment will be described.

(16) FIG. 1 is a perspective view illustrating the appearance of an information processing apparatus according to the present embodiment. An illustrated information processing apparatus **10** is a clamshell laptop PC (Personal Computer). The information processing apparatus **10** includes a first chassis **101**, a second chassis **102**, and a hinge mechanism **103**. The first chassis **101** and the second chassis **102** are chassis having a substantially rectangular plate shape (for example, a flat plate shape). One of the sides of the first chassis **101** and one of the sides of the second chassis **102** are joined (coupled) through the hinge mechanism **103** in such a manner that the first chassis **101** and the second chassis **102** are rotatable relative to each other around the axis of rotation of the hinge mechanism **103**. A state where an open angle θ between the first chassis **101** and the second chassis **102** around the axis of rotation is substantially 0° is a state where the first chassis **101** and the second chassis **102** are closed in such a manner as to overlap each other (called a “closed state”). Surfaces of the first chassis **101** and the second chassis **102** on the sides to face each other in the closed state are called “inner surfaces,” and surfaces on the other sides of the inner surfaces are called “outer surfaces,” respectively. The open angle θ can also be called an angle between the inner surface of the first chassis **101** and the inner surface of the second chassis **102**. As opposed to the closed state, a state where the first chassis **101** and the second chassis **102** are open is called an

“open state.” The open state is a state where the first chassis **101** and the second chassis **102** are rotated relative to each other until the open angle θ exceeds a preset threshold value (for example, 10°).

(17) A display unit **14** is provided on the inner surface of the first chassis **101**. Further, an input unit **32** is provided on the inner surface of the second chassis **102**. In the illustrated example, the input unit **32** is a physical keyboard. Note that the input unit **32** may include a touch pad or include a software keyboard. In the case of the software keyboard, a display unit is also provided on the inner surface of the second chassis **102**.

(18) In the closed state, the display unit **14** is not visible and any operation on the input unit **32** is disabled. On the other hand, in the open state, the display unit **14** is visible and any operation on the keyboard is enabled (that is, the information processing apparatus **10** is available). In a general usage form when a user uses the information processing apparatus **10**, the open state often falls within a range of $90^\circ \leq \text{open angle } \theta \leq 180^\circ$ as an example.

(19) FIG. 2 is a plan view schematically illustrating the inside of the second chassis **102** of the information processing apparatus **10**. In the following description, the second chassis **102** is also simply called a chassis BD. Here, the description will be made by taking, as an example, the information processing apparatus **10** equipped with a cooling fan **35**.

(20) A motherboard MB, a storage medium **23**, an audio system **24**, a battery **34**, and the cooling fan **35** are arranged inside the chassis BD. On the motherboard MB, for example, a CPU (Central Processing Unit) **11**, a video subsystem **13**, a chipset **21**, a BIOS (Basic Input Output System) memory **22**, an embedded controller **31**, and a power supply circuit **33** are mounted.

(21) The cooling fan **35** (an example of a heat dissipation unit) replaces air inside the chassis BD with outside air. For example, when the cooling fan **35** is operated to rotate the fan (impeller), the outside air enters the inside of the chassis BD through an air inlet **81** of the chassis BD, and the air is heat-exchanged through a heatsink (not illustrated) and exhausted outside of the chassis BD from an air outlet **83**. The heatsink is thermally coupled to the CPU **11** through a heat pipe (not illustrated) or the like. Inside the chassis BD, electronic devices required to manage temperature and temperature sensors **36** are arranged at plural predetermined positions, respectively. For example, an illustrated temperature sensor **36a** is placed to detect the temperature of the CPU **11**. Each of unillustrated other temperature sensors **36** is also placed to detect temperature at each position.

(22) The CPU **11** may be a CPU and a GPU, or either one of them. The CPU **11** may also be such a type as to form the CPU and the GPU on the same core. Further, the CPU **11** may be such a type as to form the CPU and the GPU on different cores and to share the load therebetween. Further, the number of CPUs **11** may be plural.

(23) As an example, the CPU **11** supports any of technologies, such as speed step, speed shift, or throttling, to adjust the operating voltage value and the operating frequency value depending on the operating mode. In the operating mode, the settings of parameters to control the operation of the CPU **11**, such as the upper limit of the power consumption of the CPU **11** and the upper limit of the operating frequency of the CPU **11**, are included. As the setting of the upper limit of the power consumption of the CPU **11**, for example, the setting of PL (Power Limit) defined for Intel CPU may be used. Further, as the setting of the upper limit of the operating frequency of the CPU **11**, the setting of TCC (Thermal Control Circuit) defined for Intel CPU may be used. In the following, the parameter to set the upper limit of the power consumption of the CPU **11** is abbreviated as “PL” and the parameter to set the upper limit of the operating frequency of the CPU **11** is abbreviated as “TCC,” but these abbreviations are not intended to limit the CPU **11** to an Intel CPU.

(24) For example, the CPU **11** adjusts the operating frequency and operating voltage of the CPU **11** according to the setting of “PL” not to exceed the upper limit of the set power consumption. For example, the CPU **11** instructs the embedded controller **31** to adjust the supply voltage from the power supply circuit **33** to the CPU **11**. Further, the CPU **11** sets an upper-limit operating frequency

according to the setting of “TCC” to adjust the operating frequency at which the CPU **11** actually operates. Thus, the power consumption and the amount of heat generation of the CPU **11** can be controlled. Note that the parameters to control the operation of the CPU **11** are not limited to the upper limit of the power consumption of the CPU **11** and the upper limit of the operating frequency of the CPU **11**, and any other parameter may also be included.

(25) Referring next to FIG. **3**, the main hardware configuration of the information processing apparatus **10** will be described. FIG. **3** is a block diagram illustrating an example of the hardware configuration of the information processing apparatus **10**.

(26) The information processing apparatus **10** includes the CPU **11**, a main memory **12**, the video subsystem **13**, the display unit **14**, the chipset **21**, the BIOS memory **22**, the storage medium **23**, the audio system **24**, a WLAN card **25**, a USB connector **26**, the embedded controller **31**, the input unit **32**, the power supply circuit **33**, the battery **34**, the cooling fan **35**, the temperature sensors **36**, and an acceleration sensor **37**.

(27) The CPU **11** executes various arithmetic processing by program control to control the entire information processing apparatus **10**. For example, the CPU **11** executes processing based on an OS (Operating System) or a BIOS program. The main memory **12** is a writable memory used as reading areas of execution programs of the CPU **11** or working areas to which processing data of the execution programs are written. The main memory **12** is configured, for example, to include plural DRAM (Dynamic Random Access Memory) chips. The execution programs include the OS, various drivers for hardware-operating peripheral devices, various services/utilities, application programs, and the like.

(28) The video subsystem **13** is a subsystem to implement functions related to image display. The video subsystem **13** includes a video controller. This video controller processes a drawing command from the CPU **11**, and writes processed drawing information to a video memory and reads this drawing information from the video memory to output the drawing information to the display unit **14** as drawing data (display data).

(29) The display unit **14** is, for example, a liquid crystal display or an organic EL display to display a display screen based on the drawing data (display data) output from the video subsystem **13**.

(30) The chipset **21** includes controllers, such as a USB (Universal Serial Bus), a serial ATA (AT Attachment), an SPI (Serial Peripheral Interface) bus, a PCI (Peripheral Component Interconnect) bus, a PCI-Express bus, and an LPC (Low Pin Count) bus, and plural devices are connected to the chipset **21**. For example, the plural devices include the BIOS memory **22**, the storage medium **23**, the audio system **24**, the WLAN card **25**, the USB connector **26**, and the embedded controller **31** to be described below.

(31) The BIOS memory **22** is configured, for example, by an electrically rewritable nonvolatile memory such as an EEPROM (Electrically Erasable Programmable Read Only Memory) or a flash ROM. The BIOS memory **22** stores a BIOS, system firmware used to control the embedded controller **31**, and the like.

(32) The storage medium **23** is configured to include an HDD (Hard Disk Drive), an SSD (Solid State Drive), or the like. For example, the storage medium **23** stores the OS, various drivers, various services/utilities, application programs, and various data.

(33) A microphone and a speaker, not illustrated, are connected to the audio system **24**, which records, plays back, and outputs sound data. As an example, the microphone and the speaker are incorporated in the information processing apparatus **10**.

(34) The WLAN (Wireless Local Area Network) card **25** is connected to a network by a wireless LAN to perform data communication. For example, when receiving data from the network, the WLAN card **25** generates an event trigger indicating that the data is received.

(35) The USB connector **26** is a connector to connect peripheral devices using the USB.

(36) The input unit **32** includes, for example, an input device such as a keyboard and a pointing device such as a touch pad. For example, as illustrated in FIG. **1**, the input unit **32** is placed on the

inner surface of the second chassis **102** as the keyboard. The input unit **32** outputs, to the embedded controller **31**, input information input with a user's operation (for example, an operation signal indicative of a key operated on the keyboard).

(37) The power supply circuit **33** is configured, for example, to include a DC/DC converter, a charge/discharge unit, an AC/DC adapter, and the like. For example, the power supply circuit **33** converts AC voltage supplied from an external power supply through an AC adapter (not illustrated) or DC voltage supplied from the battery **34** into plural voltages required to operate the information processing apparatus **10**. Further, the power supply circuit **33** supplies power to each unit of the information processing apparatus **10** under the control of the embedded controller **31**.

(38) The battery **34** is, for example, a lithium battery, which is charged through the power supply circuit **33** when power is supplied from the external power supply to the information processing apparatus **10**, and outputs the charged power through the power supply circuit **33** as operating power of the information processing apparatus **10** when power is not supplied from the external power supply to the information processing apparatus **10**.

(39) The acceleration sensor **37** is, for example, a three-axis acceleration sensor to detect acceleration according to the movement of the information processing apparatus **10**. Note that the acceleration sensor **37** is not limited to the three-axis acceleration sensor, and it may be a two-axis acceleration sensor. For example, the acceleration sensor **37** is placed in either one or both of the first chassis **101** and the second chassis **102** illustrated in FIG. **1**. The information processing apparatus **10** uses the detection result of the acceleration sensor **37** to determine a placement state of the information processing apparatus **10**. The placement state is a state of being placed on a desk, a state of being placed on a lap, or the like. For example, the information processing apparatus **10** uses the detection result of the acceleration sensor **37** to determine the placement state to be the state of being placed on the desk or the state of being placed on the lap based on the posture (orientation) or the amount of shaking of the information processing apparatus **10**.

(40) Note that the information processing apparatus **10** may use the detection results of two acceleration sensors **37** (**37A**, **37B**) to detect the open angle θ between the first chassis **101** and the second chassis **102**. For example, the information processing apparatus **10** may be so constructed that the acceleration sensor **37A** is arranged inside the first chassis **101** and the acceleration sensor **37B** is arranged inside the second chassis **102** to detect the open angle θ based on the acceleration detection results according to the respective movements of the first chassis **101** and the second chassis **102**.

(41) The embedded controller **31** is a one-chip microcomputer which monitors and controls various devices (peripheral devices, sensors, and the like) regardless of the system state of the information processing apparatus **10**. The embedded controller **31** includes a CPU, a ROM, a RAM, multi-channel A/D input terminal and D/A output terminal, a timer, and digital input/output terminals, which are not illustrated. To the digital input/output terminals of the embedded controller **31**, for example, the input unit **32**, the power supply circuit **33**, the cooling fan **35**, the temperature sensors **36**, the acceleration sensor **37**, and the like are connected, and the embedded controller **31** controls the operation of them.

(42) For example, the embedded controller **31** acquires the detection results of the temperature sensors **36** to control the cooling fan **35** based on the detection results. Further, the embedded controller **31** acquires the detection result of the acceleration sensor **37** to determine the placement state of the information processing apparatus **10** based on the detection result. For example, based on the detection result of the acceleration sensor **37**, the embedded controller **31** determines whether the information processing apparatus **10** is in the state of being placed on the desk or the state of being placed on the lap. Here, the "state of being placed on the desk" collectively means a state where the information processing apparatus **10** is supported by a stationary object, which is not limited to the state on the desk alone. The same applies to the state on a floor or the state on a shelf. Further, the "state of being placed on the lap" collectively means a state where the

information processing apparatus **10** is supported by part of a person's body, which is not limited to the state on the lap alone. The same applies to the state on an arm or the like. For example, the information processing apparatus **10** switches the thermal control to suppress a temperature rise in the information processing apparatus **10** based on the placement state (On Desk/On Lap) determined by the embedded controller **31**.

(43) The thermal control is to control the operation of the CPU **11** or the rotation of the cooling fan **35** in order to suppress the temperature rise in the information processing apparatus **10**, which is control related to the performance of system processing executed by the CPU **11**. Specifically, the thermal control includes control of an operating mode related to the performance of the CPU **11** (hereinafter simply called an “operating mode of the CPU **11**”). For example, the operating mode of the CPU **11** includes the setting of “PL,” the setting of “TCC,” and the like. The information processing apparatus **10** switches the operating mode of the CPU **11** depending on the placement state (On Desk/On Lap) of the information processing apparatus **10**.

(44) Further, the thermal control includes, as the control of the cooling fan **35**, the control of the start of rotation, the stop of rotation, the rotational speed, and the like. For example, the information processing apparatus **10** controls the rotation of the cooling fan **35** based on the detection results of the temperature sensors **36** provided inside the chassis BD. On this occasion, the control of the rotation of the cooling fan **35** is changed depending on the placement state (On Desk/On Lap) of the information processing apparatus **10**.

(45) Referring next to FIG. **4**, a functional configuration related to the thermal control executed by the information processing apparatus **10** will be described.

(46) FIG. **4** is a block diagram illustrating an example of the functional configuration of the information processing apparatus **10** according to the present embodiment. As the functional configuration related to the thermal control, the information processing apparatus **10** includes an OS processing unit **111** (an example of a system processing unit), a BIOS processing unit **115**, and an EC processing unit **310**. The OS processing unit **111** is a functional component implemented by the CPU **11** executing the OS and a program (a driver, an application, or the like) running on the OS. The BIOS processing unit **115** is a functional component implemented by the CPU **111** executing the BIOS program. The EC processing unit **310** is a functional component implemented by the embedded controller **31** executing a program to control the embedded controller **31**.

(47) The EC processing unit **310** controls the output of notification information according to various kinds of input information and the rotation of the cooling fan **35**. For example, the EC processing unit **310** includes an acceptance unit **311**, a determination unit **312**, a fan control unit **313**, and a fan table **314**. The acceptance unit **311** accepts, as input information, a detection signal according to the movement of the information processing apparatus **10** output from the acceleration sensor **37**. The determination unit **312** determines the placement state (On Desk/On Lap) of the information processing apparatus **10** based on the detection signal accepted by the acceptance unit **311**. For example, when the amount of movement of the information processing apparatus **10** is less than a predetermined threshold value, the determination unit **312** determines the state where the information processing apparatus **10** is being placed on the desk. On the other hand, when the amount of movement of the information processing apparatus **10** is equal to or more than the predetermined threshold value, the determination unit **312** determines the state where the information processing apparatus **10** is being placed on the lap. Then, the determination unit **312** outputs determination result information (information indicative of the placement state (On Desk/On Lap)) based on the determination result of the placement state to the BIOS processing unit **115** as the notification information mentioned above. Note that the determination unit **312** may output the determination result information (information indicative of the placement state (On Desk/On Lap)) to the BIOS processing unit **115** as the above-mentioned notification information only when the determination result of the placement state is changed.

(48) The fan control unit **313** controls the rotation of the cooling fan **35**. For example, the fan

control unit **313** refers to the fan table **314** to control the start and stop of the rotation of the cooling fan **35**, the rotational speed of the cooling fan **35**, and the like. The fan table **314** is a data table in which fan rotation control setting data used for thermal control is stored. For example, the fan table **314** is stored in a memory inside the embedded controller **31**.

(49) FIG. 5 is a diagram illustrating an example of the fan table **314** according to the present embodiment. In the fan table **314**, the temperature sensors **36** are associated with set temperatures used to control the rotation of the cooling fan **35**. For example, data on set temperatures changed among four-stage speed steps of the cooling fan **35**, i.e., stop of the operating state, low-speed rotation, medium-speed rotation, and high-speed rotation, are stored for each of the temperature sensors **36** (**36a** to **36e**) placed at the plural predetermined positions inside the chassis BD of the information processing apparatus **10**. The set temperatures are composed of enabled temperatures LTe, MTe, HTe and disabled temperatures LTd, MTd, HTd for each operating state, and each piece of data is set to form hysteresis characteristics between a case where the rotational speed changes in an increasing direction and a case where the rotational speed changes in a decreasing direction.

(50) The enabled temperatures LTe, MTe, HTe of the low-speed rotation, the medium-speed rotation, and the high-speed rotation are temperatures each of which moves to the speed step concerned from a one-step slower speed step when the measured temperature of each temperature sensor tends to rise. The disabled temperatures LTd, MTd, HTd of the low-speed rotation, the medium-speed rotation, and the high-speed rotation are temperatures each of which moves to a one-step slower speed step from the speed step concerned when the measured temperature of each temperature sensor tends to drop. Here, a speed step slower than the above-mentioned low-speed rotation is a stopped state.

(51) Although the temperature sensors **36a** to **36e** are illustrated here as examples of plural temperature sensors **36**, the number of temperature sensors **36** can be set to any number. The set temperature set for each of the temperature sensors **36a** to **36e** is set to operate the cooling fan **35** at a rotational speed as low as possible so that the surface temperature in a predetermined place of the chassis BD does not exceed a predetermined value, or to operate the cooling fan **35** at an appropriate rotational speed so that the temperature of each electronic device does not exceed a critical temperature.

(52) For example, the fan control unit **313** starts the rotation of the cooling fan **35** when the measured temperature of any one of the temperature sensors **36a** to **36e** reaches the enabled temperature LTe, and increases the rotational speed of the cooling fan **35** by one step when the measured temperature reaches the enabled temperature MTe or HTe. Further, the fan control unit **313** decreases the rotational speed of the cooling fan **35** by one step when the measured temperatures of all of the temperature sensors **36a** to **36e** drop up to less than the disabled temperature MTd or HTd, and stops the rotation of the cooling fan **35** when the measured temperatures become less than the disabled temperature LTd.

(53) Thus, the fan control unit **313** controls the rotation of the cooling fan **35** based on the measured temperatures of the temperature sensors **36** and the fan table **314**. However, the fricative sound of air passing through the air outlet **83** becomes larger as the rotational speed of the cooling fan **35** increases. For example, when the temperature of the CPU **11** rises, the rotational speed of the cooling fan **35** increases along therewith. In this case, noise may be generated.

(54) As illustrated in FIG. 5, the fan table **314** includes plural kinds of tables. The plural tables are included in the fan table **314** in a manner to be selectable, such as table FTA_A1 (On Desk) for an on desk mode applied when the information processing apparatus **10** is being placed on a desk and table FTA_A2 (On Lap) for an on lap mode applied when the information processing apparatus **10** is being placed on a lap. For example, since the upper limit of an allowable temperature in the case of use on the lap is lower than that in the case of use on the desk, FTA_A2 (On Lap) is set to operate the cooling fan **35** at a temperature lower than that in FTA_A1 (On Desk) so as to increase the rotational speed according to the temperature rise at a stage earlier than that in FTA_A1 (On

Desk). Which of the tables is referred to perform rotation control of the cooling fan **35** is determined by an instruction from the BIOS processing unit **115**.

(55) Returning to FIG. **4**, the BIOS processing unit **115** includes a thermal control unit **116** and a CPU table **117**. The thermal control unit **116** executes control related to the performance of system processing as thermal control based on determination result information (information indicative of either On Desk or On Lap) output from the EC processing unit **310**.

(56) For example, the thermal control unit **116** outputs, to the OS processing unit **111**, system setting information (an example of first setting information) for setting an operating mode of the CPU **11** preset according to the placement state (On Desk/On Lap) of the information processing apparatus **10** as the control related to the performance of the system processing. Specifically, when the determination result information output from the EC processing unit **310** is information indicative of On Desk, the thermal control unit **116** refers to the CPU table **117** to output, to the OS processing unit **111**, system setting information for setting the operating mode of the CPU **11** to the on desk mode. On the other hand, when the determination result information output from the EC processing unit **310** is information indicative of On Lap, the thermal control unit **116** refers to the CPU table **117** to output, to the OS processing unit **111**, system setting information for setting the operating mode of the CPU **11** to the on lap mode.

(57) FIG. **6** is a diagram illustrating an example of the CPU table **117** according to the present embodiment. In the CPU table **117**, the settings for each operating mode of the CPU **11** are stored. In the illustrated example, the on desk mode (On Desk) and the on lap mode (ON Lap) are set as operating modes of the CPU **11**. In the on desk mode (On Desk), a mode No. "A1" of the on desk mode is associated with the settings of "PL" and "TCC" of the CPU **11** in the on desk mode. In the on lap mode (ON Lap), a mode No. "A2" of the on lap mode is associated with the settings of "PL" and "TCC" of the CPU **11** in the on lap mode. For example, "PL" is so set that the upper-limit value of the power consumption of the CPU **11** is smaller in the on lap mode than that in the on desk mode. Further, "TCC" is so set that the upper-limit value of the operating frequency of the CPU **11** is smaller in the on lap mode than that in the on desk mode. Note that any operating mode other than the on desk mode and the on lap mode may also be set in the CPU table **117**.

(58) For example, upon setting the operating mode to the on desk mode, the thermal control unit **116** refers to the CPU table **117** to output, to the OS processing unit **111**, the mode No. "A1" and information including the set values of "PL" and "TCC" of the CPU **11** in the on desk mode as system setting information. On the other hand, upon setting the operating mode to the on lap mode, the thermal control unit **116** refers to the CPU table **117** to output, to the OS processing unit **111**, the mode No. "A2" and information including the set values of "PL" and "TCC" of the CPU **11** in the on lap mode as system setting information.

(59) Further, the thermal control unit **116** outputs, to the EC processing unit **310**, fan setting information (an example of second setting information) for setting the fan table **314** referred to by the EC processing unit **310** to control the rotation of the cooling fan **35** according to the placement state (On Desk/On Lap) of the information processing apparatus **10** as the control related to the performance of the system processing.

(60) Specifically, when the determination result information output from the EC processing unit **310** is information indicative of On Desk, the thermal control unit **116** outputs, to the EC processing unit **310**, fan setting information to be set to the table FTA_A1 (On Desk) of the on desk mode applied when the information processing apparatus **10** is being placed on the desk in the fan table **314** illustrated in FIG. **5**. The fan control unit **313** of the EC processing unit **310** refers to the table FTA_A1 (On Desk) to control the rotation of the cooling fan **35** based on this fan setting information.

(61) On the other hand, when the determination result information output from the EC processing unit **310** is information indicative of On Lap, the thermal control unit **116** outputs, to the EC processing unit **310**, fan setting information to be set to the table FTA_A2 (On Lap) of the on lap

mode applied when the information processing apparatus **10** is being placed on the lap in the fan table **314** illustrated in FIG. **5**. The fan control unit **313** of the EC processing unit **310** refers to the table FTA_A2 (On Lap) to control the rotation of the cooling fan **35** based on this fan setting information.

(62) Thus, in the information processing apparatus **10**, the cooling fan **35** is operated in the on lap mode at a temperature lower than in the on desk mode to increase the rotational speed according to the temperature rise at an earlier stage in order to suppress the temperature rise.

(63) The OS processing unit **111** executes processing by such an OS as not to be equipped with a DPTF (Dynamic Platform and Thermal Framework) driver running on Windows (registered trademark), i.e., processing by any OS other than Windows (registered trademark). Note that the DPTF driver is just an example that supports the on desk mode, the on lap mode, and the like, and the same applies to any other driver (for example, DTT (Dynamic Tuning Technology)) as long as the driver supports these modes. In the following, description will be made by taking the DPTF driver as an example. As the OS other than Windows (registered trademark), Linux (registered trademark) can be exemplified as an example. The OS processing unit **111** controls the operation of the CPU **11** based on the system setting information output from the BIOS processing unit **115**. For example, when acquiring system setting information to be set to the on desk mode from the BIOS processing unit **115**, the OS processing unit **111** controls the operation of the CPU **11** based on the set values of “PL” and “TCC” of the CPU **11** in the on desk mode included in the system setting information. On the other hand, when acquiring system setting information to be set to the on lap mode from the BIOS processing unit **115**, the OS processing unit **111** controls the operation of the CPU **11** based on the set values of “PL” and “TCC” of the CPU **11** in the on lap mode included in the system setting information.

(64) Thus, in the information processing apparatus **10**, control is so performed that the upper limit of the power consumption of the CPU **11** and the operating frequency of the CPU **11** are set lower in the on lap mode than in the on desk mode to suppress the temperature rise.

(65) Note that the thermal control of the present embodiment can also be applied to a case of using Windows (registered trademark) as the OS. An OS processing unit **112** (another example of the system processing unit) illustrated in FIG. **4** indicates an example of a functional component to execute processing by Windows (registered trademark) equipped with the DPTF driver. The information processing apparatus **10** may include this OS processing unit **112** instead of or in addition to the OS processing unit **111**. Like the OS processing unit **111**, the OS processing unit **112** controls the operation of the CPU **11** based on the system setting information output from the BIOS processing unit **115**. However, as for the settings of the CPU **11** (PL, TCC, and the like) used to control the operation of the CPU **11**, the OS processing unit **112** uses those set by the DPTF driver. For example, the OS processing unit **112** controls the operation of the CPU **11** based on the system setting information output from the BIOS processing unit **115**. In the DPTF driver, for example, a thermal control data table including at least the settings (PL, TCC, and the like) of the CPU **11** for the on desk mode and the settings (PL, TCC, and the like) of the CPU **11** for the on lap mode is stored. For example, when acquiring system setting information to be set to the on desk mode from the BIOS processing unit **115**, the OS processing unit **112** uses the DPTF driver to refer to the thermal control data table corresponding to the mode No. “A1” indicative of the on desk mode included in the system setting information in order to control the operation of the CPU **11**. On the other hand, when acquiring system setting information to be set to the on lap mode from the BIOS processing unit **115**, the OS processing unit **112** uses the DPTF driver to refer to the thermal control data table corresponding to the mode No. “A2” indicative of the on lap mode included in the system setting information in order to control the operation of the CPU **11**.

(66) Referring next to FIG. **7**, the operation of thermal control processing executed by respective components of the information processing apparatus **10** will be described. FIG. **7** is a flowchart illustrating an example of thermal control processing according to the present embodiment. (Step

S101) When acquiring a detection signal according to the movement of the information processing apparatus **10** output from the acceleration sensor **37** (G sensor), the EC processing unit **310** proceeds to processing in step **S103**. (Step **S103**) Based on the detection signal acquired in step **S101** from the acceleration sensor **37**, the EC processing unit **310** determines the placement state (On Desk/On Lap) of the information processing apparatus **10**. Then, the EC processing unit **310** proceeds to processing in step **S105**. (Step **S105**) Based on the determination result of the placement state in step **S103**, the EC processing unit **310** determines whether there is a change in placement state or not. When determining that there is no change in placement state (NO), the EC processing unit **310** returns to the processing in step **S101** to acquire a detection signal output from the acceleration sensor **37** (G sensor). On the other hand, when determining that there is a change in placement state (YES), the EC processing unit **310** proceeds to processing in step **S107**. (Step **S107**) Based on the determination result of the placement state, the EC processing unit **310** notifies the BIOS processing unit **115** of determination result information indicative of the placement state (On Desk/On Lap). For example, when determining that the placement state is a state where the information processing apparatus **10** is being placed on the desk, the EC processing unit **310** outputs, to the BIOS processing unit **115**, determination result information indicating that the placement state is On Desk, while when determining that the placement state is a state where the information processing apparatus **10** is being placed on the lap, the EC processing unit **310** outputs, to the BIOS processing unit **115**, determination result information indicating that the placement state is On Lap. Then, the procedure proceeds to processing in step **S109**. (Step **S109**) When acquiring in step **S107** the determination result information output from the EC processing unit **310**, the BIOS processing unit **115** refers to the CPU table **117** illustrated in FIG. **6** based on this determination result information to notify the OS processing unit **111** of system setting information to be set to an operating mode corresponding to the placement state (On Desk/On Lap). For example, when the determination result information output from the EC processing unit **310** is information indicative of On Desk, the BIOS processing unit **115** refers to the CPU table **117** to output, to the OS processing unit **111**, system setting information for setting the operating mode of the CPU **111** to the on desk mode. On the other hand, when the determination result information output from the EC processing unit **310** is information indicative of On Lap, the BIOS processing unit **115** refers to the CPU table **117** to output, to the OS processing unit **111**, system setting information for setting the operating mode of the CPU **111** to the on lap mode. Then, the BIOS processing unit **115** proceeds to processing in step **S111**. (Step **S111**) When acquiring in step **S107** the determination result information output from the EC processing unit **310**, the BIOS processing unit **115** notifies the EC processing unit **310** of fan setting information for setting the fan table **314**, to be referred to by the EC processing unit **310** to control the rotation of the cooling fan **35** based on this determination result information, to a table corresponding to the placement state (On Desk/On Lap). For example, when the determination result information output from the EC processing unit **310** is information indicative of On Desk, the BIOS processing unit **115** outputs, to the EC processing unit **310**, fan setting information to be set to the table FTA_A1 (On Desk) of the on desk mode in the fan table **314** illustrated in FIG. **5**. On the other hand, when the determination result information output from the EC processing unit **310** is information indicative of On Lap, the BIOS processing unit **115** outputs, to the EC processing unit **310**, fan setting information to be set to the table FTA_A2 of the on lap mode in the fan table **314** illustrated in FIG. **5**.

(67) Note that the order of step **S109** and step **S111** may be changed, or these steps may be performed at the same time. (Step **S113**) When acquiring in step **S109** the system setting information output from the BIOS processing unit **115**, the OS processing unit **111** controls the operation of the CPU **11** based on this system setting information. For example, when acquiring system setting information to be set to the on desk mode from the BIOS processing unit **115**, the OS processing unit **111** controls the operation of the CPU **11** based on the set values of “PL” and “TCC” of the CPU **11** in the on desk mode included in the system setting information. On the other

hand, when acquiring system setting information to be set to the on lap mode from the BIOS processing unit **115**, the OS processing unit **111** controls the operation of the CPU **11** based on the set values of “PL” and “TCC” of the CPU **11** in the on lap mode included in the system setting information.

(68) Note that when the OS of the information processing apparatus **10** is Windows (registered trademark) equipped with the DPTF driver, the OS processing unit **112** controls the operation of the CPU **11** in step **S113** based on the system setting information output from the BIOS processing unit **115**. For example, when acquiring system setting information to be set to the on desk mode from the BIOS processing unit **115**, the OS processing unit **112** controls the operation of the CPU **11** based on the settings (PL, TCC, and the like) of the CPU **11** for the on desk mode set by the DPTF driver. On the other hand, when acquiring system setting information to be set to the on lap mode from the BIOS processing unit **115**, the OS processing unit **112** controls the operation of the CPU **11** based on the settings (PL, TCC, and the like) of the CPU **11** for the on lap mode set by the DPTF driver. (Step **S115**) When acquiring in step **S111** fan setting information output from the BIOS processing unit **115**, the EC processing unit **310** refers to a table based on the fan setting information in the fan table **314** to control the cooling fan **35**. For example, when acquiring fan setting information to be set to the table **FTA_A1** (On Desk) of the on desk mode, the EC processing unit **310** refers to the table **FTA_A1** (On Desk) to control the rotation of the cooling fan **35**. On the other hand, when acquiring fan setting information to be set to the table **FTA_A2** (On Lap) of the on lap mode, the EC processing unit **310** refers to the table **FTA_A2** (On Lap) to control the rotation of the cooling fan **35**.

(69) FIGS. **8A** and **8B** are explanatory diagrams of the effect of thermal control according to the present embodiment. FIG. **8A** illustrates the setting of the upper limit (PL) of the power consumption of the CPU **11** and the temperature (Temp) of the information processing apparatus **10** when the thermal control is not switched between On Desk and On Lap. In the UL safety standards, temperature (Temp(Lap)) allowed in a case where the placement state in use is on the lap (that is, in contact with a person) is defined as temperature lower than temperature (Temp(Desk)) allowed in a case where the placement state in use is on the desk (that is, not in contact with a person). When the thermal control is not switched between on the desk and on the lap, since the temperature needs to be set not to exceed the temperature (Temp(Lap)) allowed in the case of being on the lap (in the case of being in contact with a person) in both cases of being on the desk and on the lap, the upper limit (PL) of the power consumption of the CPU **11** is fixed to the low setting in the on lap mode.

(70) On the other hand, FIG. **8B** illustrates the setting of the upper limit (PL) of the power consumption of the CPU **11** and the temperature (Temp) of the information processing apparatus **10** when the thermal control is switched between On Desk and On Lap. In this case, since allowable temperature in the on desk mode is higher than that in the on lap mode, the upper limit (PL) of the power consumption of the CPU **11** in the on desk mode can be set higher than that in the on lap mode. Thus, since the information processing apparatus **10** can increase the performance of the CPU **11** when being used on the desk by switching the thermal control between on the desk and on the lap while complying with the UL safety standards in both cases of being used on the lap and on the desk, user convenience is improved.

(71) As described above, the information processing apparatus **10** according to the present embodiment includes the embedded controller **31** (an example of a controller) which outputs notification information according to input information. The information processing apparatus **10** also includes the OS processing unit **111** or the OS processing unit **112** (the example of the system processing unit) which executes system processing based on the OS, and the CPU **11** (an example of a processor) functioning as the BIOS processing unit **115** which executes, by BIOS control, control related to the performance of the OS processing unit **111** or the OS processing unit **112** based on notification information output from the embedded controller **31**.

(72) Thus, the information processing apparatus **10** enables highly versatile thermal control

independent of the type of OS by the BIOS performing control related to performance based on the notification from the embedded controller **31**.

(73) For example, the embedded controller **31** (EC processing unit **310**) accepts, as the input information, a detection signal according to the movement of the information processing apparatus **10** from the acceleration sensor **37** which outputs the detection signal, and determines the placement state of the information processing apparatus **10** (for example, whether the information processing apparatus **10** is being placed on the desk or on the lap) based on the accepted detection signal. Then, the EC processing unit **310** outputs determination result information based on the determination result to the CPU **11** (BIOS processing unit **115**) as the notification information. Based on the determination result information output from the EC processing unit **310**, the BIOS processing unit **115** executes control related to the performance of the system processing.

(74) Thus, since the embedded controller **31** determines the placement state of the information processing apparatus **10** based on the detection signal of the acceleration sensor **37**, and the BIOS performs control related to performance based on the determination result, the information processing apparatus **10** enables highly versatile thermal control independent of the type of OS.

(75) Specifically, the BIOS processing unit **115** outputs, to the OS processing unit **111** or the OS processing unit **112**, system setting information (the example of the first setting information) for setting an operating mode (on desk mode/on lap mode) of the CPU **11** preset according to the placement state (On Desk/On Lap) of the information processing apparatus **10** as the control related to the performance of the system processing. Based on the system setting information (on desk mode/on lap mode) output from the BIOS processing unit **115**, the OS processing unit **111** or the OS processing unit **112** controls the upper limit of the power consumption or the upper limit of the operating frequency of the CPU **11**.

(76) Thus, since the information processing apparatus **10** controls the upper limit of the power consumption or the upper limit of the operating frequency of the CPU **11** according to the placement state (On Desk/On Lap) of the information processing apparatus **10**, the performance of the CPU **11** can be improved when being used on the desk while complying with the UL safety standards in both cases of being used on the lap and being used on the desk, thereby improving user convenience.

(77) The information processing apparatus **10** further includes the cooling fan **35** (the example of the heat dissipation unit) which replaces air inside the chassis of the information processing apparatus **10** with outside air by the rotation of the fan. The BIOS processing unit **115** outputs, to the EC processing unit **310**, fan setting information (the example of the second setting information) for setting an operating mode (on desk mode/on lap mode) related to control of the rotation of the cooling fan **35** preset according to the placement state (On Desk/On Lap) of the information processing apparatus **10** as the control related to the performance of the system processing. Based on the fan setting information (on desk mode/on lap mode) output from the BIOS processing unit **115**, the EC processing unit **310** controls the rotation of the cooling fan **35**.

(78) Thus, since the information processing apparatus **10** controls the rotation of the cooling fan **35** according to the placement state (On Desk/On Lap) of the information processing apparatus **10**, the performance of the CPU **11** can be improved when being used on the desk while complying the UL safety standards in both cases of being used on the lap or being used on the desk, thereby improving user convenience.

(79) In the present embodiment, the example of determining the state of being placed on the desk or the state of being placed on the lap as the placement state of the information processing apparatus **10** is described, but the definition of the placement state is not limited to these states. For example, a state where the information processing apparatus **10** is in contact with a person or a state where the information processing apparatus **10** is not in contact with a person may also be defined as the placement state. In this case, the state of being in contact with a person corresponds to the state of being placed on the lap, and the state of not being in contact with a person

corresponds to the state of being placed on the desk. Further, for example, a vibrational state in which there is vibration in the information processing apparatus **10** or a stationary state in which there is no vibration in the information processing apparatus **10** may be defined as the placement state. In this case, the vibrational state corresponds to the state of being placed on the lap, and the stationary state corresponds to the state of being placed on the desk. Thus, the placement state can be defined by various criteria based on the detection signal output from the acceleration sensor **37**. (80) Further, in the present embodiment, the example of using the acceleration sensor **37** to determine the placement state of the information processing apparatus **10** is described, but a gyro sensor, an inclination sensor, a geomagnetic sensor, or the like may also be used instead of or in addition to the acceleration sensor **37**.

Second Embodiment

(81) Next, a second embodiment of the present invention will be described.

(82) In the first embodiment, the example of switching the thermal control based on the placement state of the information processing apparatus **10** is described. In this embodiment, an example of switching the thermal control according to a user's operation on the keyboard will be described. Since the basic structure/configuration of an information processing apparatus **10A** according to the present embodiment is the same as the example of the information processing apparatus **10** illustrated in FIG. **1**, FIG. **2**, and FIG. **3**, the description thereof will be omitted. In the present embodiment, functions and processing different from those in the first embodiment will be described.

(83) First, examples of user's operations on the keyboard to perform thermal control will be described.

(84) FIG. **9** is a diagram illustrating an example of correspondences between keyboard operations and thermal control according to the present embodiment. In the illustrated example, a hot key that is a combination of "Fn" key and "L" key corresponds to a quiet mode (Quiet). A hot key that is a combination of "Fn" key and "M" key corresponds to a balance mode (Balance). A hot key that is a combination of "Fn" key and "H" key corresponds to a performance mode (Performance). The quiet mode, the balance mode, and the performance mode are operating modes related to the performance of the CPU **11**.

(85) The quiet mode is an operating mode to lower performance step before increasing the rotational speed of the cooling fan **35** when the temperature rises in order to give higher priority to quietness than the performance of the system processing by the CPU **11**.

(86) Here, suppressing the rotational speed of the cooling fan **35** means, by reducing the amount of heat generation of the CPU **11**, any one or some of not rotating the cooling fan **35** being stopped, stopping the cooling fan **35** being rotated, rotating the cooling fan **35** being rotated at a high rotational speed by suppressing the rotational speed to such an extent that noise generated by the rotation of the cooling fan **35** is not an issue.

(87) The performance mode is an operating mode to first increase the rotational speed of the cooling fan **35** up to a settable upper-limit speed when the temperature rises in order to give higher priority to performance than quietness. As mentioned above, when the detected temperature further rises even after the rotational speed of the cooling fan **35** is controlled, the performance step decreases.

(88) The balance mode is an operating mode adjusted to take advantage of both of quietness in the quiet mode and performance in the performance mode, which performs control between the quiet mode and the performance mode.

(89) When "Fn" key and "L" key of the input unit **32** (keyboard) are pressed at the same time with a user's operation, the information processing apparatus **10A** is set to the quiet mode. When "Fn" key and "M" key of the input unit **32** (keyboard) are pressed at the same time with a user's operation, the information processing apparatus **10A** is set to the balance mode. Further, when "Fn" key and "H" key of the input unit **32** (keyboard) are pressed at the same time with a user's

operation, the information processing apparatus **10A** is set to the performance mode.

(90) Note that each of the hot keys that are the combinations of keys described above is just an example, and each hot key is not limited to the combination of keys.

(91) FIG. **10** is a block diagram illustrating an example of the functional configuration of the information processing apparatus **10A** according to the present embodiment. The information processing apparatus **10A** includes, as a functional configuration related to thermal control, the OS processing unit **111** (the example of the system processing unit), a BIOS processing unit **115A**, and an EC processing unit **310A**. The functional configuration of the information processing apparatus **10A** differs from that of the information processing apparatus **10** illustrated in FIG. **4** in that thermal control is switched based on an operation signal output from the input unit **32**. For example, the operation signal is an operation signal generated with a hot key operation by the user as described above.

(92) The EC processing unit **310A** outputs notification information according to various kinds of input information, and controls the rotation of the cooling fan **35**. The EC processing unit **310A** includes the acceptance unit **311**, the determination unit **312**, the fan control unit **313**, and a fan table **314A**. The acceptance unit **311** accepts an operation signal output from the input unit **32** as input information. For example, the acceptance unit **311** accepts, as input information, an operation signal indicative of an operated key according to a user's operation on the input unit **32** (keyboard).

(93) Based on the operation signal accepted by the acceptance unit **311**, the determination unit **312** determines whether the operated key is a hot key that is a specific combination of keys or not. When the operated key is a hot key that is a specific combination of keys, the determination unit **312** outputs, to the BIOS processing unit **115A**, determination result information based on the determination result as notification information. For example, when determining a hot key that is a combination of “Fn” key and “L” key, the determination unit **312** outputs, to the BIOS processing unit **115A**, determination result information indicative of the quiet mode as notification information. When determining a hot key that is a combination of “Fn” key and “M” key, the determination unit **312** outputs, to the BIOS processing unit **115A**, determination result information indicative of the balance mode as notification information. Further, when determining a hot key that is a combination of “Fn” key and “H” key, the determination unit **312** outputs, to the BIOS processing unit **115A**, determination result information indicative of the performance mode as notification information.

(94) The fan control unit **313** controls the rotation of the cooling fan **35**. In the present embodiment, the fan control unit **313** refers to the fan table **314A** to control the start of the rotation of the cooling fan **35**, the stop of the rotation, the rotational speed, or the like.

(95) FIG. **11** is a diagram illustrating an example of the fan table **314A** according to the present embodiment. In the fan table **314A**, the temperature sensors **36** are associated with set temperatures used to control the rotation of the cooling fan **35**. Like in the fan table **314** illustrated in FIG. **5**, the illustrated fan table **314A**, data on set temperatures changed in the operating state of the cooling fan **35** among four-stage speed steps, i.e., stop of the operating state, low-speed rotation, medium-speed rotation, and high-speed rotation, are stored for each of the temperature sensors **36** (**36a** to **36e**) placed in the predetermined plural positions inside the chassis **BD** of the information processing apparatus **10**. In this fan table **314A** illustrated in FIG. **11**, tables are prepared in a selectable manner, such as table **FTA_B1** (Quiet) applied in the quiet mode, table **FTA_B2** (Balance) applied in the balance mode, and table **FTA_B3** (Performance) applied in the performance mode.

(96) For example, the cooling fan **35** needs to be controlled by suppressing the noise of the cooling fan **35** in the quiet mode more than the performance mode. Therefore, for example, the table **FTA_B1** (Quiet) is so set that the timing to start the rotation of the cooling fan **35** becomes later and the upper limit of the rotational speed of the cooling fan **35** becomes lower than the table **FTA_B3** (Performance). On the other hand, the table **FTA_B3** (Performance) is set to increase the

rotational speed according to the temperature rise at a stage earlier than the table FTA_B1 (Quiet). Further, the table FTA_B2 (Balance) is set between the table FTA_B1 (Quiet) and the table FTA_B3 (Performance). Which of the tables is referred to control the rotation of the cooling fan **35** is determined by an instruction from the BIOS processing unit **115A**.

(97) Returning to FIG. **10**, the BIOS processing unit **115A** includes the thermal control unit **116** and a CPU table **117A**. The thermal control unit **116** executes control related to the performance of the system processing based on the determination result information (information indicative of any one of the quiet mode, the balance mode, and the performance mode) output from the EC processing unit **310A**. For example, the thermal control unit **116** outputs, to the OS processing unit **111**, system setting information (the example of the first setting information) for setting the operating mode of the CPU **11** preset according to the hot key that is a combination of keys as the control related to the performance of system processing.

(98) Specifically, when the determination result information output from the EC processing unit **310A** is information indicative of the quiet mode, the thermal control unit **116** refers to the CPU table **117A** to output, to the OS processing unit **111**, system setting information for setting the operating mode of the CPU **111** to the quiet mode. When the determination result information output from the EC processing unit **310A** is information indicative of the balance mode, the thermal control unit **116** refers to the CPU table **117A** to output, to the OS processing unit **111**, system setting information for setting the operating mode of the CPU **111** to the balance mode. Further, when the determination result information output from the EC processing unit **310A** is information indicative of the performance mode, the thermal control unit **116** refers to the CPU table **117A** to output, to the OS processing unit **111**, system setting information for setting the operating mode of the CPU **111** to the performance mode.

(99) FIG. **12** is a diagram illustrating an example of the CPU table **117A** according to the present embodiment. In the CPU table **117A**, settings for each of the operating modes of the CPU **11** are stored. In the illustrated example, the quiet mode (Quiet), the balance mode (Balance), and the performance mode (Performance) are set as the operating modes of the CPU **11**. In the quiet mode (Quiet), a mode No. "B1" of the quiet mode is associated with the settings of "PL" and "TCC" of the CPU **11** in the quiet mode. In the balance mode (Balance), a mode No. "B2" of the balance mode is associated with the settings of "PL" and "TCC" of the CPU **11** in the balance mode. In the performance mode (Performance), a mode No. "B3" of the performance mode is associated with the settings of "PL" and "TCC" of the CPU **11** in the performance mode.

(100) For example, "PL" is so set that the upper-limit value of the power consumption of the CPU **11** is smaller in the quiet mode than in the performance mode. "PL" in the balance mode is set between those in the performance mode and the quiet mode. Further, "TCC" is so set that the upper-limit value of the operating frequency of the CPU **11** is smaller in the quiet mode than in the performance mode. "TCC" in the balance mode is set between those in the performance mode and the quiet mode. Note that any operating mode other than the quiet mode, the balance mode, and the performance mode may also be set in the CPU table **117A**.

(101) For example, upon setting the operating mode to the quiet mode, the thermal control unit **116** refers to the CPU table **117A** to output, to the OS processing unit **111**, information including the mode No. "B1" and set values of "PL" and "TCC" of the CPU **11** in the quiet mode as system setting information. Upon setting the operating mode to the balance mode, the thermal control unit **116** refers to the CPU table **117A** to output, to the OS processing unit **111**, information including the mode No. "B2" and set values of "PL" and "TCC" of the CPU **11** in the balance mode as system setting information. Further, upon setting the operating mode to the performance mode, the thermal control unit **116** refers to the CPU table **117A** to output, to the OS processing unit **111**, information including the mode No. "B3" and set values of "PL" and "TCC" of the CPU **11** in the performance mode as system setting information.

(102) Further, the thermal control unit **116** outputs, to the EC processing unit **310A**, fan setting

information (the example of the second setting information) for setting the fan table **314A** referred to by the EC processing unit **310A** to control the rotation of the cooling fan **35** according to whether the operating mode is the quiet mode, the balance mode, or the performance mode as the control related to the performance of the system processing.

(103) Specifically, when the determination result information output from the EC processing unit **310A** is information indicative of the quiet mode, the thermal control unit **116** outputs, to the EC processing unit **310A**, fan setting information to be set to the table FTA_B1 (Quiet) of the quiet mode in the fan table **314A** illustrated in FIG. **11**. The fan control unit **313** of the EC processing unit **310A** refers to the table FTA_B1 (Quiet) to control the rotation of the cooling fan **35** based on this fan setting information.

(104) When the determination result information output from the EC processing unit **310A** is information indicative of the balance mode, the thermal control unit **116** outputs, to the EC processing unit **310A**, fan setting information to be set to the table FTA_B2 (Balance) of the balance mode in the fan table **314A** illustrated in FIG. **11**. The fan control unit **313** of the EC processing unit **310A** refers to the table FTA_B2 (Balance) to control the rotation of the cooling fan **35** based on this fan setting information.

(105) Further, when the determination result information output from the EC processing unit **310A** is information indicative of the performance mode, the thermal control unit **116** outputs, to the EC processing unit **310A**, fan setting information to be set to the table FTA_B3 (Performance) of the performance mode in the fan table **314A** illustrated in FIG. **11**. The fan control unit **313** of the EC processing unit **310A** refers to the table FTA_B3 (Performance) to control the rotation of the cooling fan **35** based on this fan setting information.

(106) The OS processing unit **111** executes processing by such an OS as not to be equipped with the DPTF driver running on Windows (registered trademark), i.e., processing by any other OS such as Linux (registered trademark). In the present embodiment, the DPTF driver is just an example that supports the quiet mode, the balance mode, the performance mode, and the like, and the same applies to any other driver (for example, DTT) as long as the driver supports these modes. In the following, description will be made by taking the DPTF driver as an example. The OS processing unit **111** controls the operation of the CPU **11** based on the system setting information output from the BIOS processing unit **115A**. For example, when acquiring the system setting information to be set to the quiet mode from the BIOS processing unit **115A**, the OS processing unit **111** controls the operation of the CPU **11** based on the set values of “PL” and “TCC” of the CPU **11** in the quiet mode included in the system setting information. When acquiring system setting information to be set to the balance mode from the BIOS processing unit **115A**, the OS processing unit **111** controls the operation of the CPU **11** based on the set values of “PL” and “TCC” of the CPU **11** in the balance mode included in the system setting information. Further, when acquiring system setting information to be set to the performance mode from the BIOS processing unit **115A**, the OS processing unit **111** controls the operation of the CPU **11** based on the set values of “PL” and “TCC” of the CPU **11** in the performance mode included in the system setting information.

(107) Note that the thermal control of the present embodiment can also be applied to a case of using Windows (registered trademark) equipped with the DPTF driver as the OS. The OS processing unit **112** (the other example of the system processing unit) illustrated in FIG. **10** indicates an example of a functional component to execute processing by Windows (registered trademark) equipped with the DPTF driver. The information processing apparatus **10A** may include this OS processing unit **112** instead of or in addition to the OS processing unit **111**. Like the OS processing unit **111**, the OS processing unit **112** controls the operation of the CPU **11** based on the system setting information output from the BIOS processing unit **115A**. However, as for the settings of the CPU **11** (PL, TCC, and the like) used to control the operation of the CPU **11**, the OS processing unit **112** uses those set by the DPTF driver. For example, the OS processing unit **112** controls the operation of the CPU **11** based on the system setting information output from the BIOS

processing unit **115A**. In the DPTF driver, for example, a thermal control data table including at least the settings (PL, TCC, and the like) of the CPU **11** for the quiet mode, the balance mode, and the performance mode, respectively, is stored. When acquiring system setting information to be set to the quiet mode from the BIOS processing unit **115A**, the OS processing unit **112** uses the DPTF driver to refer to the thermal control data table corresponding to the mode No. “B1” indicative of the quiet mode included in the system setting information in order to control the operation of the CPU **11**. When acquiring system setting information to be set to the balance mode from the BIOS processing unit **115A**, the OS processing unit **112** uses the DPTF driver to refer to the thermal control data table corresponding to the mode No. “B2” indicative of the balance mode included in the system setting information in order to control the operation of the CPU **11**. Further, when acquiring system setting information to be set to the performance mode from the BIOS processing unit **115A**, the OS processing unit **112** uses the DPTF driver to refer to the thermal control data table corresponding to the mode No. “B3” indicative of the performance mode included in the system setting information in order to control the operation of the CPU **11**.

(108) Referring next to FIG. **13**, the operation of thermal control processing executed by respective components of the information processing apparatus **10A** will be described. FIG. **13** is a flowchart illustrating an example of thermal control processing according to the present embodiment. (Step **S201**) When acquiring an operation signal output from the input unit **32** (keyboard), the EC processing unit **310A** proceeds to processing in step **S203**. (Step **S203**) Based on the operation signal acquired in step **S201** from the input unit **32**, the EC processing unit **310A** determines the kind of key operated through the input unit **32** (keyboard). Then, the EC processing unit **310A** proceeds to processing in step **S205**. (Step **S205**) Based on the determination result on the kind of key in step **S203**, the EC processing unit **310A** determines whether the operated key is a specific hot key or not. The specific hot key indicates a hot key corresponding to each of the quiet mode, the balance mode, and the performance mode, respectively. When determining that the operated key is not the specific hot key (NO), the EC processing unit **310A** returns to the processing in step **S201** to acquire an operation signal output from the input unit **32** (keyboard). On the other hand, when determining that the operated key is the specific hot key (YES), the EC processing unit **310A** proceeds to processing in step **S207**. (Step **S207**) The EC processing unit **310A** notifies the BIOS processing unit **115A** of determination result information indicative of the operating mode (quiet mode/balance mode/performance mode) corresponding to the specific hot key. For example, when the operated key is the hot key as the combination of “Fn” key and “L” key, the EC processing unit **310A** outputs, to the BIOS processing unit **115A**, determination result information indicative of the quiet mode. When the operated key is the hot key as the combination of “Fn” key and “M” key, the EC processing unit **310A** outputs, to the BIOS processing unit **115A**, determination result information indicative of the balance mode. Further, when the operated key is the hot key as the combination of “Fn” key and “H” key, the EC processing unit **310A** outputs, to the BIOS processing unit **115A**, determination result information indicative of the performance mode. Then, the procedure proceeds to processing in step **S209**. (Step **S209**) When acquiring the determination result information output from the EC processing unit **310A** in step **S207**, the BIOS processing unit **115A** refers to the CPU table **117A** illustrated in FIG. **12** based on this determination result information to notify the OS processing unit **111** of system setting information to be set to the quiet mode, the balance mode, or the performance mode. For example, when the determination result information output from the EC processing unit **310A** is information indicative of the quiet mode, the BIOS processing unit **115A** refers to the CPU table **117A** to output, to the OS processing unit **111**, system setting information for setting the operating mode of the CPU **111** to the quiet mode. When the determination result information output from the EC processing unit **310A** is information indicative of the balance mode, the BIOS processing unit **115A** refers to the CPU table **117A** to output, to the OS processing unit **111**, system setting information for setting the operating mode of the CPU **111** to the balance mode. Further, when the determination result information output from

the EC processing unit **310A** is information indicative of the performance mode, the BIOS processing unit **115A** refers to the CPU table **117A** to output, to the OS processing unit **111**, system setting information for setting the operating mode of the CPU **111** to the performance mode. Then, the BIOS processing unit **115A** proceeds to processing in step **S211**. (Step **S211**) When acquiring the determination result information output from the EC processing unit **310A** in step **S207**, the BIOS processing unit **115A** notifies the EC processing unit **310A** of fan setting information for setting the fan table **314A**, referred to by the EC processing unit **310A** to control the rotation of the cooling fan **35**, to a table corresponding to the operating mode based on the determination result information. For example, when the determination result information output from the EC processing unit **310A** is information indicative of the quiet mode, the BIOS processing unit **115A** outputs, to the EC processing unit **310A**, fan setting information to be set to the table **FTA_B1** (Quiet) of the quiet mode in the fan table **314A** illustrated in FIG. **11**. When the determination result information output from the EC processing unit **310A** is information indicative of the balance mode, the BIOS processing unit **115A** outputs, to the EC processing unit **310A**, fan setting information to be set to the table **FTA_B2** (Balance) of the balance mode in the fan table **314A** illustrated in FIG. **11**. Further, when the determination result information output from the EC processing unit **310A** is information indicative of the performance mode, the BIOS processing unit **115A** outputs, to the EC processing unit **310A**, fan setting information to be set to the table **FTA_B3** (Performance) of the performance mode in the fan table **314A** illustrated in FIG. **11**.

(109) Note that the order of processing in step **S209** and step **S211** may be changed or the processing in step **S209** and step **S211** may be performed at the same time. (Step **S213**) When acquiring system setting information output from the BIOS processing unit **115A** in step **S209**, the OS processing unit **111** controls the operation of the CPU **11** based on this system setting information. For example, when acquiring system setting information to be set to the quiet mode from the BIOS processing unit **115A**, the OS processing unit **111** controls the operation of the CPU **11** based on the set values of “PL” and “TCC” of the CPU **11** in the quiet mode included in the system setting information. When acquiring system setting information to be set to the balance mode from the BIOS processing unit **115A**, the OS processing unit **111** controls the operation of the CPU **11** based on the set values of “PL” and “TCC” of the CPU **11** in the balance mode included in the system setting information. Further, when acquiring system setting information to be set to the performance mode from the BIOS processing unit **115A**, the OS processing unit **111** controls the operation of the CPU **11** based on the set values of “PL” and “TCC” of the CPU **11** in the performance mode included in the system setting information.

(110) Note that when the OS of the information processing apparatus **10A** is Windows (registered trademark) equipped with the DPTF driver, the OS processing unit **112** controls the operation of the CPU **11** in step **S213** based on the system setting information output from the BIOS processing unit **115A**. For example, when acquiring system setting information to be set to the quiet mode from the BIOS processing unit **115A**, the OS processing unit **112** controls the operation of the CPU **11** based on the settings (PL, TCC, and the like) of the CPU **11** for the quiet mode set by the DPTF driver. When acquiring system setting information to be set to the balance mode from the BIOS processing unit **115A**, the OS processing unit **112** controls the operation of the CPU **11** based on the settings (PL, TCC, and the like) of the CPU **11** for the balance mode set by the DPTF driver. Further, when acquiring system setting information to be set to the performance mode from the BIOS processing unit **115A**, the OS processing unit **112** controls the operation of the CPU **11** based on the settings (PL, TCC, and the like) of the CPU **11** for the performance mode set by the DPTF driver. (Step **S215**) When acquiring fan setting information output from the BIOS processing unit **115A** in step **S211**, the EC processing unit **310** refers to a table based on the fan setting information in the fan table **314A** to control the cooling fan **35**. For example, when acquiring fan setting information to be set to the table **FTA_B1** (Quiet) of the quiet mode, the EC processing unit **310A** refers to the table **FTA_B1** (Quiet) to control the rotation of the cooling fan **35**. When acquiring fan setting

information to be set to the table FTA_B2 (Balance) of the balance mode, the EC processing unit **310A** refers to the table FTA_B2 (Balance) to control the rotation of the cooling fan **35**. Further, when acquiring fan setting information to be set to the table FTA_B3 (Performance) of the performance mode, the EC processing unit **310A** refers to the table FTA_B3 (Performance) to control the rotation of the cooling fan **35**.

(111) As described above, in the information processing apparatus **10A** according to the present embodiment, the embedded controller **31** (EC processing unit **310A**) accepts an operation signal indicative of a key corresponding to a user's operation to the input unit **32** (keyboard) according to the operation as input information, and determines, based on the accepted operation signal, whether the operated key is a specific hot key (a specific combination of keys) or not. When determining that the key is the specific hot key, the EC processing unit **310A** outputs, to the CPU **11** (BIOS processing unit **115A**), determination result information (information indicative of quiet mode/balance mode/performance mode) based on the determination result as notification information. The BIOS processing unit **115A** executes control related to the performance of the system processing based on the determination result information output from the EC processing unit **310A**.

(112) In the information processing apparatus **10A**, the embedded controller **31** determines, depending on the key operated on the keyboard, which of the quiet mode, the balance mode, and performance mode the operation is to select, and the BIOS performs control related to performance based on the determination result to enable highly versatile thermal control independent of the type of OS. Thus, the information processing apparatus **10A** can select the operating mode (quiet mode/balance mode/performance mode) with a user's hot-key operation independently of the type of OS.

(113) For example, the BIOS processing unit **115A** outputs, to the OS processing unit **111** or the OS processing unit **112**, system setting information (the example of the first setting information) for setting the operating mode of the CPU **11** (quiet mode/balance mode/performance mode) preset according to the specific hot key as control related to the performance of the system processing. Based on the system setting information (quiet mode/balance mode/performance mode) output from the BIOS processing unit **115A**, the OS processing unit **111** or the OS processing unit **112** controls the upper limit of the power consumption or the upper limit of the operating frequency of the CPU **11**, and the like.

(114) Thus, since the information processing apparatus **10A** can control the upper limit of the power consumption or the upper limit of the operating frequency of the CPU **11**, and the like corresponding to the quiet mode, the balance mode, or the performance mode according to a user's operation without depending on the type of OS, user convenience is improved.

(115) Further, the BIOS processing unit **115A** outputs, to the EC processing unit **310A**, fan setting information (the example of the second setting information) for setting the operating mode (quiet mode/balance mode/performance mode) related to fan rotation control of the heat dissipation unit preset according to the specific hot key as control related to the performance of the system processing. Based on the fan setting information (quiet mode/balance mode/performance mode) output from the BIOS processing unit **115A**, the EC processing unit **310A** controls the rotation of the cooling fan **35**.

(116) Thus, since the information processing apparatus **10A** can control the rotation of the cooling fan **35** corresponding to the quiet mode, the balance mode, or the performance mode according to the user's operation without depending on the type of OS, user convenience is improved.

(117) While the embodiments of this invention have been described in detail above with reference to the accompanying drawings, the specific configurations are not limited to those described above, and various design changes and the like can be made without departing from the scope of this invention. For example, respective components described in the aforementioned embodiments may be combined arbitrarily.

(118) In the aforementioned embodiments, the example in which both the control of the CPU **11** and the control of the cooling fan **35** are performed as thermal control is described, either one of the control of the CPU **11** and the control of the cooling fan **35** may be performed. For example, the aforementioned embodiments can also be applied to a case of suppressing a rise in chassis temperature of an information processing apparatus without having the cooling fan **35**.

(119) Further, the above-described information processing apparatus **10** (**10A**) has a computer system therein. Then, a program for implementing the function of each of components included in the above-described information processing apparatus **10** (**10A**) may be recorded on a computer-readable recording medium in such a manner that the program recorded on this recording medium is read into the computer system and executed to perform processing in each component included in the above-described information processing apparatus **10** (**10A**). Here, the fact that “the program recorded on the recording medium is read into the computer system and executed” includes installing the program on the computer system. It is assumed that the “computer system” here includes the OS and hardware such as a peripheral device and the like. Further, the “computer system” may also include two or more computers connected through any of networks including the Internet, WAN, LAN, and a communication line such as a dedicated line. Further, the “computer-readable recording medium” means a storage medium such as a flexible disk, a magneto-optical disk, a ROM, a portable medium like a CD-ROM, or a hard disk incorporated in the computer system. The recording medium with the program stored thereon may be a non-transitory recording medium such as the CD-ROM.

(120) A recording medium internally or externally provided to be accessible from a delivery server for delivering the program is included as the recording medium. Note that the program may be divided into plural pieces, downloaded at different timings, respectively, and then united in each component included in the information processing apparatus **10** (**10A**), or delivery servers for delivering respective divided pieces of the program may be different from one another. Further, the “computer-readable recording medium” includes a medium on which the program is held for a given length of time, such as a volatile memory (RAM) inside a computer system as a server or a client when the program is transmitted through the network. The above-mentioned program may also be to implement some of the functions described above. Further, the program may be a so-called differential file (differential program) capable of implementing the above-described functions in combination with a program(s) already recorded in the computer system.

(121) Further, some or all of the functions of the above-described information processing apparatus **10** (**10A**) in the above-described embodiments may be realized as an integrated circuit such as LSI (Large Scale Integration). Each function may be a processor implemented individually, or part or whole thereof may be integrated as a processor. Further, the method of circuit integration is not limited to LSI, and it may be realized by a dedicated circuit or a general-purpose processor. Further, if integrated circuit technology replacing the LSI appears with the progress of semiconductor technology, an integrated circuit according to the technology may be used.

(122) Further, in the above-described embodiments, the example in which the information processing apparatus **10** (**10A**) is a laptop PC is described, but the information processing apparatus **10** (**10A**) may also be a tablet PC or a desktop PC. Further, the information processing apparatus **10** (**10A**) may be a smartphone, a game console, or the like.

DESCRIPTION OF SYMBOLS

(123) **10**, **10A**: information processing apparatus, **101**: first chassis, **102**: second chassis, **103**: hinge mechanism, **11**: CPU, **21**: chipset, **31**: embedded controller, **32**: input unit, **35**: cooling fan, **36**: temperature sensor, **37**: acceleration sensor, **111**: OS processing unit, **115**, **115A**: BIOS processing unit, **116**: thermal control unit, **117**, **117A**: CPU table, **310**, **310A**: EC processing unit, **311**: acceptance unit, **312**: determination unit, **313**: fan control unit, **314**, **314A**: fan table.

(124) Although the disclosure has been described with respect to only a limited number of embodiments, those skilled in the art, having benefit of this disclosure, will appreciate that various

other embodiments may be devised without departing from the scope of the present invention. Accordingly, the scope of the invention should be limited only by the attached claims.

Claims

1. An information processing apparatus comprising: a processor; and a controller that outputs, to the processor, notification information according to input information, wherein the processor: executes system processing based on an operating system (OS), and executes operation of thermal control processing by control of a Basic Input Output System (BIOS) using the notification information output from the controller, wherein the controller: accepts, as the input information, an operation signal indicative of an operated key according to a user's operation on a keyboard, determines whether the operated key is of a specific combination of keys based on the accepted operation signal, and upon making a determination that the operated key is of the specific combination of keys, outputs, to the processor, a result of the determination as the notification information, and without another key being pressed after the result of the determination is output from the controller, the processor executes the thermal control processing based on the result of the determination.
2. The information processing apparatus according to claim 1, wherein the controller further: accepts, as the input information, a detection signal output from a sensor according to movement of the information processing apparatus, determines a placement state of the information processing apparatus based on the accepted detection signal, and upon making a determination of the placement state, outputs, to processor, a result of the determination as the notification information, and the processor further executes the thermal control processing based on the result of the determination output from the controller.
3. The information processing apparatus according to claim 2, wherein the processor further executes the thermal control processing based on first setting information for setting an operating mode of the processor that is preset according to the placement state of the information processing apparatus.
4. The information processing apparatus according to claim 3, further comprising: a fan that replaces air inside a chassis of the information processing apparatus with outside air by rotation of the fan, wherein the processor further executes the thermal control processing by outputting, to the controller, second setting information for setting an operating mode related to control of the rotation of the fan that is preset according to the placement state of the information processing apparatus, and the controller controls the rotation of the fan based on the second setting information output from the processor.
5. The information processing apparatus according to claim 1, wherein the processor further executes the operation of thermal control processing based on first setting information for setting an operating mode of the processor that is preset according to the specific combination of keys.
6. The information processing apparatus according to claim 5, further comprising: a fan that replaces air inside a chassis of the information processing apparatus with outside air by rotation of the fan, wherein the processor further executes the operation of thermal control processing by outputting, to the controller, second setting information for setting an operating mode related to control of the rotation of the fan, and the controller controls the rotation of the fan based on the second setting information output from the processor.
7. The information processing apparatus according to claim 3, wherein the first setting information includes information related to an upper limit of power consumption of the processor.
8. The information processing apparatus according to claim 3, wherein the first setting information includes information related to an upper limit of an operating frequency of the processor.
9. A control method for an information processing apparatus, comprising: executing, by a processor, system processing based on an operating system (OS); outputting, by a controller,

notification information according to input information; executing, by the processor, control related to operation of thermal control processing by control of a Basic Input Output System (BIOS) using the notification information output from the controller; accepting, as the input information by the controller, an operation signal indicative of an operated key according to a user's operation on a keyboard, determining, by the controller, whether the operated key is of a specific combination of keys based on the accepted operation signal, and upon making a determination that the operated key is of the specific combination of keys, without another key being pressed after a result of the determination is output from the controller, executing, by the processor, the operation of thermal control processing based on the result of the determination as the notification information.
