

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410643
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Iwatani; Toshinori

Door lock assembly

Abstract

A door lock assembly includes a door trim including a through hole, and a locking device that is disposed on a vehicular exterior side with respect to the door trim and locks and unlocks a vehicular door. The locking device includes a lock knob holder and a door lock knob. The lock knob holder has a tubular shape and two holes at two opposite ends and one of the two holes is adjacent to the through hole and another one is an insertion hole. The door lock knob has a bar shape and is disposed in the lock knob holder so as to be movable between an unlocked position and a locked position. The door lock assembly further includes an insertion guide portion disposed adjacent to the insertion hole and includes a guide surface having a width that increases as it extends away from the insertion hole.

Inventors:	Iwatani; Toshinori (Mie-ken, JP)
Applicant:	TOYOTA BOSHOKU KABUSHIKI KAISHA (Aichi-ken, JP)
Family ID:	90244704
Assignee:	TOYOTA BOSHOKU KABUSHIKI KAISHA (Aichi-Ken, JP)
Appl. No.:	18/234566
Filed:	August 16, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240093540 A1	Mar. 21, 2024

Foreign Application Priority Data

JP	2022-148750	Sep. 20, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: E05B85/08 (20140101); E05B79/02 (20140101)

U.S. Cl.:

CPC E05B85/08 (20130101); E05B79/02 (20130101);

Field of Classification Search

CPC: E05B (85/08); E05B (85/085); E05B (79/00); E05B (79/02); E05B (79/06); E05B (79/22); E05B (1/00); E05B (1/0038); E05B (1/0046); B60R (13/0243)

USPC: 296/146.7

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2004/0026936	12/2003	Slovesko	292/336.3	E05B 83/36
2019/0106913	12/2018	Fukuchi	N/A	E05B 79/22
2019/0309546	12/2018	Kawamoto	N/A	E05B 79/04

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H07-48964	12/1994	JP	N/A
2021169702	12/2020	JP	N/A
2021187386	12/2020	JP	N/A

Primary Examiner: Mills; Christine M

Assistant Examiner: Sidky; Yahya

Attorney, Agent or Firm: Greenblum & Bernstein, P.L.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION

(1) This application claims priority from Japanese Patent Application No. 2022-148750 filed on Sep. 20, 2022. The entire contents of the priority application are incorporated herein by reference.

TECHNICAL FIELD

(2) The present technology described herein relates to a door lock assembly.

BACKGROUND

(3) A vehicular door of an automobile generally includes a locking device that locks and unlocks a door. Such a locking device includes a door lock knob on a vehicular interior side. The door lock knob is used for performing the locking operation. For example, a bar-shaped door lock knob projects from a hole in the door trim. Such a door lock knob is held in a tubular holder that is disposed on the vehicular exterior surface side with respect to the door trim.

SUMMARY

(4) To mount the bar-shaped door lock knob in the tubular holder, the top end of the door lock knob is moved closer to a hole of the holder and the door lock knob is inserted in the holder. The opening

size of the hole of the holder is not much different from a diameter of the door lock knob. Therefore, positioning of the door lock knob with respect to the hole is not easy and needs to be performed several times to mount the door lock knob in the holder properly.

(5) An object of the present technology described herein is to provide a door lock assembly with which a door lock knob and a lock knob holder can be fitted together easily.

(6) To solve the above problems, a door lock assembly according to the technology described herein includes a door trim including a through hole and a locking device that is disposed on a vehicular exterior side with respect to the door trim and locks and unlocks a vehicular door. The locking device includes a lock knob holder and a door lock knob. The lock knob holder has a tubular shape and two holes at two opposite ends. One of the two holes is adjacent to the through hole and another one of the two holes is an insertion hole. The door lock knob has a bar shape and is disposed in the lock knob holder so as to be movable between an unlocked position at which the door lock knob projects upward from a vehicular interior side surface of the door trim through the through hole and a locked position at which the door lock knob is positioned lower than the unlocked position. The door lock assembly further includes an insertion guide portion that is disposed adjacent to the insertion hole and includes a guide surface having a width that increases as it extends away from the insertion hole.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of a vehicular door including a door lock assembly according to one embodiment.
- (2) FIG. 2 is a cross-sectional view illustrating a cross-sectional configuration of a portion of the vehicular door including an upper cover and a weather strip.
- (3) FIG. 3 is a perspective view illustrating a portion of a door trim including a locking device seen from a vehicular exterior side.
- (4) FIG. 4 is a perspective view of the upper cover.
- (5) FIG. 5 is an elevation view of the upper cover including the lock knob holder.
- (6) FIG. 6 is a bottom view of the upper cover including the lock knob holder.
- (7) FIG. 7 is a cross-sectional view along I-I line in FIG. 5.

DETAILED DESCRIPTION

- (8) A door lock assembly **1** according to one embodiment will be described with reference to FIGS. **1** to **7**. The door lock assembly **1** is for mounting a door lock knob **71** in a lock knob holder **80** that is disposed on a vehicular exterior side with respect to a door trim **11**. The door trim **11** is configured as a vehicular interior side surface of a vehicular door **10**.
- (9) The door trim **11** is disposed below a side window **12** (one example of a window) of the vehicular door **10** and is mounted on a vehicular interior side with respect to a door inner panel **18**. As illustrated in FIG. **1**, the door trim **11** mainly includes a trim board **13** and further includes various components such as an inside handle **14**, an armrest **15**, a speaker grill **16**, a switch device **17**, and a locking device **70** that are mounted on the trim board **13**. In each drawing, the arrows of FR and RR represent a vehicular front side and a vehicular rear side, respectively, and the arrows of UP and DW represent an upper side and a lower side, respectively, and the arrows IN and OUT represent a vehicular interior side and a vehicular exterior side, respectively.
- (10) The trim board **13** includes multiple board members that are joined together. An upper portion of the trim board **13** that is continuous to the side window **12** is an upper board **20**. As illustrated in FIG. **2**, the upper board **20** includes a side wall **21**, a curved portion **22**, and an upper wall **23**. The side wall **21** is configured as a portion of the vehicular interior side surface of the vehicular door **10** and extends in an entire area of the vehicular door **10** with respect to the front-rear direction. The

curved portion **22** extends from an upper edge of the side wall **21** to the upper wall **23** toward the vehicular exterior side with being curved. The upper wall **23** is configured as a portion of an upper surface of the vehicular door **10**. The curved portion **22** is curved such that an angle formed by the side wall **21** and the upper wall **23** is (an acute angle) slightly smaller than a right angle. As illustrated in FIG. 1, the side wall **21** of the upper board **20** becomes wider as it extends rearward from a middle with respect to the front-rear direction.

(11) The locking device **70** is mounted in a rear edge section of the upper board **20**. The locking device **70** is for locking and unlocking the vehicular door **10**.

(12) As illustrated in FIGS. 3 and 7, the locking device **70** includes a lock knob bezel **40**, the door lock knob **71** having a circular bar shape as a whole, and the lock knob holder **80**. The lock knob holder **80** has a tubular shape and is disposed on the vehicular exterior side with respect to the door trim **11** (the upper board **20**). A knob body **71A** of the door lock knob **71** is inserted in the lock knob bezel **40** and the lock knob holder **80** so as to be movable inside the lock knob bezel **40** and the lock knob holder **80**. The upper board **20** includes a board-side through hole **24** in the rear section of the upper wall **23**. The board-side through hole **24** is a circular hole. With the knob body **71A** of the door lock knob **71** being inserted in the lock knob bezel **40** and the lock knob holder **80** and projecting upward through the board-side through hole **24**, the vehicular door **10** is in an unlocked state. With the door lock knob **71** being lower than the board-side through hole **24** as illustrated in FIG. 3, the vehicular door **10** is in a locked state.

(13) As illustrated in FIGS. 3 and 7, the lock knob bezel **40** is mounted in the board-side through hole **24**. The lock knob bezel **40** includes a bezel portion **41** and an insertion portion **42**. The bezel portion **41** has a circular ring shape that surrounds a hole edge of the board-side through hole **24** and is disposed on an upper surface (a design surface) of the upper wall **23** of the upper board **20**. The outer diameter of the bezel portion **41** is greater than an opening diameter of the board-side through hole **24** and greater than the outer diameter of the insertion portion **42**. The insertion portion **42** has a tubular shape and extends from the bezel portion **41** and is inserted through the board-side through hole **24**. As illustrated in FIG. 5, the insertion portion **42** includes stopper projections **43** that project outwardly from an outer surface of the insertion portion **42**. The stopper projections **43** are on a middle of the insertion portion **42** with respect to an axial direction thereof. As illustrated in FIG. 7, the upper board **20** includes a base seat **25** on a vehicular exterior side surface of the hole edge of the board-side through hole **24**. With the stopper projections **43** being stopped by the base seat **25**, the lock knob bezel **40** is fixed to the upper board **20**. The insertion portion **42** includes a mating portion on an opposite end from the bezel portion **41**. The mating portion is to be mated with the lock knob holder **80**.

(14) The lock knob holder **80** is mounted on the upper board **20** via an upper cover **50** (one example of an intervening member). The upper cover **50** will be described below.

(15) As illustrated in FIG. 2, the upper cover **50** is mounted on the vehicular exterior side with respect to the upper board **20**. The upper cover **50** includes a cover body **51** having a plate shape. As illustrated in FIGS. 2 and 4, the cover body **51** extends from a vehicular exterior side edge of the upper wall **23** of the upper board **20** along the curved portion **22** and extends downward along the side wall **21** of the upper board **20**. The cover body **51** also extends in the front-rear direction. As illustrated in FIG. 3, the upper board **20** includes projection walls **27** that project from the vehicular exterior side surface of the upper board **20**. The projection walls **27** are spaced from each other in the extending direction of the curved portion **22** (in the front-rear direction). The projection walls **27** have a rectangular plate shape extending from the upper wall **23** to the side wall **21**. The projection wall **27** includes a positioning projection **28** that projects toward the vehicular exterior side from a corner of the projection wall **27** that is farthest from the curved portion **22**. As illustrated in FIG. 4, the cover body **51** of the upper cover **50** includes positioning holes **52** corresponding to the positioning projections **28** of the upper board **20**. With the positioning projections **28** being fitted in the positioning holes **52**, respectively, the cover body **51** is positioned

with respect to the upper board **20**.

(16) The upper board **20** includes fixing members **29** that have a tubular shape and project from the vehicular exterior side surface of the side wall **21**. The fixing members **29** are disposed below the curved portion **22**. As illustrated in FIG. **3**, reinforcement ribs **30** having a rectangular plate shape extend radially from a basal portion of each fixing member **29**.

(17) As illustrated in FIG. **4**, the upper cover **50** includes mount bases **53** in portions of the cover body **51** corresponding to the respective fixing members **29**. The mount base **53** includes fixing member through holes **55** through which the fixing members **29** are inserted, respectively. A vehicular interior side surface of the mount base **53** is to be contacted with vehicular exterior end surfaces of the reinforcement ribs **30** when the fixing members **29** are inserted through the fixing member through holes **55**. The mount base **53** is supported by the vehicular exterior end surfaces of the reinforcement ribs **30** from the vehicular interior side. With the fixing members **29** being inserted through the respective fixing member through holes **55** and thermally welded, the upper cover **50** is fixed to the upper board **20**.

(18) As illustrated in FIGS. **2** and **4**, the cover body **51** of the upper cover **50** includes stopper pieces **67** that are arranged at intervals in the extending direction of the cover body (the front-rear direction). The stopper pieces **67** extend downward from a curved portion of the cover body **51** and are bent toward the vehicular exterior side and have an L-shape. The stopper pieces **67** include stopper portions **68** that project downward from distal ends thereof. As illustrated in FIG. **2**, the vehicular door **10** includes the weather strip **19** for waterproofing between the side window **12** and the upper board **20** with respect to a vehicular interior-exterior direction (a vehicular width direction). With the stopper portions **68** of the stopper pieces **67** being held by the weather strip **19**, the waterproofing between the upper board **20** and the side window **12** is achieved.

(19) In this embodiment, the lock knob holder **80** is mounted on the upper board **20** via the upper cover **50**. As illustrated in FIGS. **3** and **5**, the lock knob holder **80** includes a tubular holder body **81** and a fixing portion **82**. The fixing portion **82** projects from a one end portion (an upper portion in FIGS. **3** and **5**) of the holder body **81** in a direction crossing an axial direction of the holder body **81**. The fixing portion **82** has a plate surface that extends in the axial direction of the holder body **81**. The fixing portion **82** includes a holder through hole that is through in a direction (the vehicular interior-exterior direction) perpendicular to the axial direction (the upper-bottom direction) of the holder body **81**. The holder body **81** includes a pair of stopper holes **84** that are opposite each other with respect to the axis of the holder body **81**. The stopper holes **84** are in a portion of the holder body **81** closer to another end (a lower end in FIGS. **3** and **5**) of the holder body **81**. One of the stopper holes **84** is on the same side (the left side in FIG. **5**) as the fixing portion **82** is with respect to the axis of the holder body **81**.

(20) As illustrated in FIG. **7**, the knob body **71A** of the door lock knob **71**, which has a columnar bar shape, is fitted in the lock knob holder **80** from a lower side. As illustrated in FIG. **3**, the door lock knob **71** includes a mount member **72** on an end (a lower portion in FIG. **3**) of the knob body **71A** and the knob body **71A** is fitted in the lock knob holder **80** so as to be movable along the axial direction of the door lock knob **71** and the lock knob holder **80**. The mount member **72** includes a mount body **72A** and a pair of arms **73** that radially project outward from the mount body **72A** in opposite directions and extend upward. The arms **73** are opposite each other. The arms **73** include stopper projections **74** at extending ends thereof. The stopper projections **74** project inwardly. With the stopper projections **74** being fitted in the stopper holes **84** in the lock knob holder **80**, the mount member **72** is held by the lock knob holder **80**. The door lock knob **71** is held by the lock knob holder **80** so as to be movable with respect to the lock knob holder **80**.

(21) The holder body **81** of the lock knob holder **80** includes a mating recess in an inner peripheral surface of the one end side portion that includes the fixing portion **82**. The mating portion of the lock knob bezel **40** is mated with the mating recess. With the mating portion being mated with the mating recess, the lock knob holder **80** is connected to the lock knob bezel **40**.

- (22) As illustrated in FIGS. 4 and 7, the cover body 51 of the upper cover 50 includes an extending portion 56 in an area of the cover body 51 that extends in the front-rear direction corresponding to the board-side through hole 24 in the upper board 20 and also extends in the upper-bottom direction. The extending portion 56 is opposite the holder body 81 and extends along the side wall 21 of the upper board 20 with being away from the side wall 21.
- (23) The upper cover 50 includes a cover-side through hole 57. The insertion portion 42 of the lock knob bezel 40 that is inserted through the board-side through hole 24 in the upper board 20 is inserted through the cover-side through hole 57. The cover-side through hole 57 is in a cover upper portion 51A of the cover body 51 and extends horizontally in the vehicular interior-exterior direction (the vehicular width direction) and the front-rear direction and extends to the extending portion 56. Namely, the cover-side through hole 57 is formed by cutting off a corner formed between the cover upper portion 51. A and the extending portion 56. As illustrated in FIG. 7, with the insertion portion 42 of the lock knob bezel 40 that is mounted in the upper board 20 being inserted through the cover-side through hole 57, the insertion portion 42 is exposed on the vehicular exterior side with respect to the upper cover 50. The lock knob holder 80 is connected to the insertion portion 42 that is exposed on the vehicular exterior side and is disposed on the vehicular exterior side with respect to the upper board 20.
- (24) As illustrated in FIG. 4, support bases 59 project from the extending portion 56 toward the vehicular exterior side. As illustrated in FIG. 7, the support bases 59 are adjacent to the cover-side through hole 57 and support the lock knob holder 80 from the vehicular interior side. Two support bases 59 are disposed spaced from each other in the axial direction (the upper-bottom direction) of the lock knob holder 80 and include arched recessed portions 59A.
- (25) As illustrated in FIG. 4, a holder fixing portion 60 having a tubular shape projects from the extending portion 56 toward the vehicular exterior side. The holder fixing portion 60 is adjacent to one of the support bases 59. With the holder body 81 being fitted in the recessed portions 59A of the support bases 59 and the fixing portion 82 being fixed to the holder fixing portion 60, the lock knob holder 80 is fixed to the upper cover 50. With such a configuration, the lock knob holder 80 is disposed to extend along the side wall 21 of the upper board 20 with being away from the side wall 21 and away from the extending portion 56 of the upper cover 50 as illustrated in FIG. 7.
- (26) As illustrated in FIGS. 4 and 5, the upper cover 50 includes an insertion guide portion 61 that extends downward from the cover body 51. The insertion guide portion 61 is adjacent to the insertion hole 86 of the lock knob holder 80. The lock knob holder 80 extends in the upper-bottom direction and has two holes at two ends. An upper hole of the two holes is adjacent to the board-side through hole 24 and a lower hole of the two holes is an insertion hole 86. The insertion hole 86 opens downward. The insertion hole 86 is at an end of the lock knob holder 80 that is an opposite end from the end close to the board-side through hole 24 of the upper board 20. As illustrated in FIG. 7, the insertion guide portion is disposed between the side wall 21 of the upper board 20 and the lock knob holder 80. As illustrated in FIGS. 3 to 7, the insertion guide portion 61 includes a guide surface 62. The guide surface 62 has a width that increases as it extends farther away from the insertion hole 86 of the lock knob holder 80. The guide surface 62 is inclined so as to approach the insertion hole 86 as the guide surface 62 extends upward.
- (27) More in detail, the guide surface of the insertion guide portion 61 includes a curved guide portion 63. The curved guide portion 63 has a shape of a circular truncated cone cut along an axial direction thereof. The curved guide portion 63 is a plate member curved to project toward the side wall 21 of the upper board 20 (the vehicular interior side). As illustrated in FIG. 5, the insertion guide portion 61 is away from the insertion hole 86 of the lock knob holder 80 with respect to the axial direction of the lock knob holder 80. As illustrated in FIGS. 6 and 7, the insertion guide portion 61 is away from the insertion hole 86 of the lock knob holder 80 with respect to the radial direction of the lock knob holder 80.
- (28) As previously described, the bar-shaped door lock knob 71 is mounted in the tubular lock knob

holder **80** with the stopper projections **74** of the arms **73**, which project outwardly than the knob body **71A** and extend upward, being fitted in the stopper holes **84** of the lock knob holder **80** from an outer side. In this embodiment, as illustrated in FIGS. **6** and **7**, the guide surface **62** is disposed between the side wall **21** and the lock knob holder **80** and is on the vehicular interior side with respect to the insertion hole **86** of the lock knob holder **80** such that the arms **73** that project outward than the knob body **71A** do not come into contact with the guide surface **62** of the insertion guide portion **61** at the time of mounting the door lock knob **71** in the lock knob holder **80**.

(29) The guide surface **62** includes the curved guide portion **63** that is a plate member curved to project toward the side wall **21** of the upper board **20** (the vehicular interior side). The guide surface **62** has a curved shape projecting toward the vehicular interior side. As illustrated in FIGS. **4** and **6**, the guide surface **62** has two opposite edges **62A** on two ends with respect to the front-rear direction. The two opposite edges **62A** are on a same plane as a vehicular interior side hole edge of the insertion hole **86** with respect to the front-rear direction or are on a vehicular interior side with respect to the vehicular interior side hole edge.

(30) As illustrated in FIG. **6**, the guide surface **62** does not overlap the insertion hole **86** with respect to the front-rear direction. Specifically, the opposite edges **62A** do not overlap the insertion hole **86** with respect to the front-rear direction. With such a configuration, when the top end portion of the door lock knob **71** is guided by the guide surface **62** and inserted in the insertion hole **86**, the arms **73** that pass near the opposite edges **62A** of the guide surface **62** do not hit the opposite edges **62A**. Furthermore, a distance between the two opposite edges **62A** increases as the curved guide portion **63** extends away from the insertion hole **86**.

(31) According to such a configuration, the top end portion of the door lock knob **71** can be guided along the guide surface **62** to the insertion hole **86** of the lock knob holder **80** with the arms **73** being not contacted with the guide surface **62**.

(32) With the guide surface extending until the opposite edges of the guide surface overlaps the insertion hole **86** to increase the dimension of the curved guide portion in the vehicular interior-exterior direction (vehicular width direction), the top end portion of the door lock knob **71** may be moved to the insertion hole **86** more surely. However, with the guide surface extends until the opposite edges of the guide surface overlap the insertion hole **86**, the opposite edge portions of the guide surface obstruct the way of the arms **73** that move along the guide surface to the insertion hole **86** and the arms **73** hit the opposite edge portions. Accordingly, the door lock knob **71** cannot be mounted in the lock knob holder **80** properly and smoothly.

(33) As previously described, with the guide surface **62** of the insertion guide portion **61** being disposed between the side wall **21** and the lock knob holder **80** and is on the vehicular interior side with respect to the insertion hole **86** of the lock knob holder **80**, the opposite edges **62A** of the guide surface **62** are on the same plane as a vehicular interior side hole edge of the insertion hole **86** or are on the vehicular interior side with respect to the vehicular interior side hole edge. Therefore, as illustrated in FIG. **6**, a gap **G** is created between the guide surface **62** and the insertion hole **86** with respect to the vehicular interior-exterior direction (vehicular width direction). Specifically, the gap **G** is created between the insertion hole **86** and a portion of the curved guide portion **63** that is a most vehicular interior side and closest to the insertion hole **86**. If the gap **G** is large, the top end portion of the door lock knob **71** may hit a hole edge of the insertion hole **86** due to the large gap **G** just before the top end portion of the door lock knob **71** is inserted in the insertion hole **86** of the lock knob holder **80** and the top end portion of the door lock knob **71** may not be inserted in the insertion hole **86** smoothly.

(34) In this embodiment, the guide surface **62** includes a flat guide portion **64**. The flat guide portion **64** is a portion (an upper portion) of the guide surface **62** that is adjacent to the insertion hole **86** and a middle portion of the guide surface **62** with respect to the width direction thereof. The flat guide portion **64** is a portion of the guide surface **62** closest to the side wall **21**. The flat

guide portion **64** is flat and continuous to the curved guide portion **63** and becomes wider as it extends toward the hole edge of the insertion hole **86**. The inclination angle of the flat guide portion **64** with respect to the lock knob holder **80** is determined such that a plan surface extending from the plate surface of the flat guide portion **64** includes or close to the tangent line of the hole edge of the insertion hole **86** of the lock knob holder **80**.

(35) With such a configuration, the top end portion of the door lock knob **71** is guided toward the insertion hole **86** by the curved guide portion **63** of the guide surface **62** and guided more upward by the flat guide portion **64** so as to be farther away from the side wall **21** and closer to the insertion hole **86** than being guided by the curved guide portion **63** just before being inserted in the insertion hole **86**. The flat guide portion **64** has a function of a jump stand. The top end portion of the door lock knob **71** can be easily and smoothly moved to the insertion hole **86** even with the gap **G**, which may be large. Furthermore, the inclination angle of the flat guide portion **64** with respect to the lock knob holder **80** is determined such that a plan surface extending from the plate surface of the flat guide portion **64** includes or close to the tangent line of the hole edge of the insertion hole **86** of the lock knob holder **80**. Therefore, the top end portion of the door lock knob **71** that is moved away from the flat guide portion **64** can be inserted in the insertion hole **86** of the lock knob holder **80** smoothly.

(36) The upper cover **50** includes connection portions **66** that connect the insertion guide portion **61** and the cover body **51**. As illustrated in FIG. **4**, the insertion guide portion **61** includes flat portions **65** on two end portions with respect to the front-rear direction. The flat portions **65** extend along the side wall **21**. The connection portions **66** extend from the extending portion **56** to the two end portions of the flat portions **65**. The flat portions **65** are connected to the extending portion **56** via the connection portions **66** such that the insertion guide portion **61** is integrally connected to the cover body **51**.

(37) Next, operations and effects of this embodiment will be described. The door lock assembly **1** according to this embodiment includes the door trim **11**, the locking device **70**, and the insertion guide portion **61**. The locking device **70** locks and unlocks the vehicular door **10**. The locking device **70** includes the door lock knob **71** and the lock knob holder **80**. The door lock knob **71** has a columnar bar shape and is movable between an unlocked position and a locked position with respect to the door trim **11** (the upper board **20**). In the unlocked position, the door lock knob **71** projects from a vehicular interior side surface of the door trim **11** that is configured as a vehicular interior side surface of the vehicular door **10**. In the locked position, the door lock knob **71** moves down from the unlocked position. The lock knob holder **80** has a tubular shape and is disposed on the vehicular exterior side with respect to the door trim **11**. The door lock knob **71** is inserted in and held by the lock knob holder **80** so as to be movable inside the lock knob holder **80**. The lock knob holder **80** has at least two holes at two ends and one of the two holes is the insertion hole **86**. The door trim **11** (the upper board **20**) includes the board-side through hole **24** through which the door lock knob **71** can pass. Another one of the two holes of the lock knob holder **80** is close to the board-side through hole **24** and the insertion hole **86** is on an opposite side from the board-side through hole **24**. The insertion guide portion **61** is disposed adjacent to the insertion hole **86** and includes the guide surface **62** that increases its width as it extends away from the insertion hole **86**.

(38) According to the above configuration, when the door lock knob **71** having the columnar bar shape is inserted and mounted in the tubular lock knob holder **80**, the top end portion of the door lock knob **71** can be guided toward the insertion hole **86** of the lock knob holder **80** by the insertion guide portion **61**. Accordingly, the mounting operation becomes easy.

(39) The upper board **20** includes the side wall **21** that is configured as the vehicular interior side surface of the vehicular door **10** and the upper wall **23** that extends toward the vehicular exterior side from the upper end of the side wall **21**. The board-side through hole **24** is in the upper wall **23**. The lock knob holder **80** is disposed to extend along the side wall **21** with being away from the side wall **21**. The guide surface **62** of the insertion guide portion **61** is on the vehicular interior side with

respect to the insertion hole **86** of the lock knob holder **80**.

(40) The columnar bar-shaped door lock knob **71** includes the two arms **73** that project outward from the knob body **71A** and are opposite each other. With the stopper projections **74** of the arms **73** being fitted in the stopper holes **84** in the lock knob holder **80**, the arms **73** project outward than the tubular lock knob holder **80** and the columnar bar-shaped door lock knob **71** is held by the tubular lock knob holder **80**. With the door lock knob **71** including the arms **73** that project outward from the knob body **71A**, the arms **73** may be contacted with the guide surface **62** of the insertion guide portion **61** at the time of mounting the door lock knob **71** in the lock knob holder **80**.

However, with the arms **73** being included in the door lock knob **71** so as not to face the guide surface **62**, the arms **73** do not come in contact with the guide surface **62**. Accordingly, the mounting operation is performed smoothly.

(41) The guide surface **62** of the insertion guide portion **61** includes the curved guide portion **63** and the flat guide portion **64**. The curved guide portion **63** has a shape of a circular truncated cone cut along the axial direction and has a curved surface. The flat guide portion **64** is adjacent to the insertion hole **86** and continuous from the curved guide portion **63**. The flat guide portion **64** has a flat surface having a width that increases toward the insertion hole **86**.

(42) When the door lock knob **71** is mounted in the lock knob holder **80**, the top end portion of the door lock knob **71** is guided by the guide surface **62** and approaches the insertion hole **86** of the lock knob holder **80**. As previously described, with the guide surface **62** of the insertion guide portion **61** being disposed on the vehicular interior side with respect to the insertion hole **86**, the gap **G** is created between the guide surface **62** and the insertion hole **86** with respect to the vehicular interior-exterior direction (vehicular width direction). Specifically, the gap **G** is created between the insertion hole **86** and a portion of the curved guide portion **63** that is a most vehicular interior side and closest to the insertion hole **86**. With such a configuration, the top end portion of the door lock knob **71** may hit the hole edge of the insertion hole **86** due to the gap **G**, which may be large, just before the top end portion of the door lock knob **71** is inserted in the insertion hole **86** and the top end portion of the door lock knob **71** may not be inserted in the insertion hole **86** smoothly.

(43) With the above configuration, the top end portion of the door lock knob **71** is guided toward the insertion hole **86** by the curved guide portion **63** of the guide surface **62** and then guided upward by the flat guide portion **64** so as to be farther away from the side wall **21** and closer to the insertion hole **86** and farther away from the side wall **21** just before being inserted in the insertion hole **86**. The top end portion of the door lock knob **71** can be easily and smoothly moved to the insertion hole **86** even with the gap **G**, which is large. The flat guide portion **64** has a function of a jump stand and the insertion operation can be performed more effectively.

(44) The vehicular door **10** includes the weather strip **19** for waterproofing between the side window **12** and the upper board **20** with respect to the vehicular interior-exterior direction. The upper board **20** is fixed to the weather strip **19** via the upper cover **50** that is disposed on the vehicular exterior side with respect to the upper board **20**. The lock knob holder **80** is supported by the support bases **59**, which project toward the vehicular exterior side from the upper cover **50**, from the upper board **20** side with being away from the side wall **21**. The insertion guide portion **61** is integrally included in the upper cover **50**.

(45) According to the above configuration, with using the upper cover **50** for fixing the upper board **20** to the weather strip **19**, the lock knob holder **80** can be positioned to be away from the side wall **21** and the insertion guide portion **61** can be integrally included in the upper cover **50**. This reduces the number of components compared to the configuration including separate members for the respective components.

Other Embodiments

(46) The technology described herein is not limited to the embodiments described above with reference to the drawings. The following embodiments may be included in the technical scope. The

technology described herein may be modified within the technical scope. (1) In the above embodiment, the insertion guide portion **61** is integrally included in the upper cover **50**. However, the insertion guide portion may be included as a separate component. (2) The insertion guide portion may be integrally included with a component other than the upper cover, for example, a reinforcement member. (3) If the door lock knob does not include a projection that projects outward from the knob body, the insertion guide portion may be disposed such that the guide surface of the insertion guide portion is on a same plane to be continuous to the hole edge of the insertion hole of the lock knob holder. (4) The guide surface of the insertion guide portion may not include the flat guide portion.

Claims

1. A door lock assembly comprising: a door trim including a through hole; a locking device that is disposed on a vehicular exterior side with respect to the door trim and locks and unlocks a vehicular door, the locking device including a lock knob holder having a tubular shape and having two holes at two opposite ends, one of the two holes being adjacent to the through hole and another one of the two holes being an insertion hole, and a door lock knob having a bar shape and disposed in the lock knob holder so as to be movable between an unlocked position at which the door lock knob projects upward from a vehicular interior side surface of the door trim through the through hole and a locked position at which the door lock knob is positioned lower than the unlocked position; and an insertion guide portion disposed adjacent to the insertion hole and including a guide surface having a width that increases as it extends away from the insertion hole, wherein the guide surface of the insertion guide portion includes a curved guide portion and a flat guide portion, the curved guide portion has a shape of a circular truncated cone cut along an axial direction and has a curved surface, the flat guide portion is flat and adjacent to the insertion hole and continuous from the curved guide portion and has a width that increases in a vehicular front-rear direction as the flat guide portion extends toward the insertion hole, and an axis of the flat portion is tilted relative to a longitudinal axis of the locking device.

2. The door lock assembly according to claim 1, wherein, the door trim includes an upper board that is disposed adjacent to a window of the vehicular door, the upper board includes a side wall that is configured as the vehicular interior side surface of the vehicular door and an upper wall that extends toward the vehicular exterior side from an upper edge of the side wall, the through hole is included in the upper wall, the lock knob holder extends along the side wall and is away from the side wall, and the guide surface of the insertion guide portion is disposed between the side wall and the lock knob holder and is on a vehicular interior side with respect to the insertion hole of the lock knob holder.

3. The door lock assembly according to claim 2, further comprising an intervening member disposed on the vehicular exterior side with respect to the upper board, the intervening member integrally including the insertion guide portion, and the intervening member including a body, and a holder support base that projects toward the vehicular exterior side from the body and supports the lock knob holder from an upper board side to be away from the side wall.

4. The door lock assembly according to claim 1, wherein the lock knob holder extends in an upper-bottom direction and includes the one of the two holes on an upper end and the insertion hole on a lower end and the insertion hole opens downward, and the guide surface does not overlap the insertion hole with respect to the vehicular front-rear direction.

5. The door lock assembly according to claim 1, wherein the insertion guide portion is between the lock knob holder and the door trim, and the guide surface of the insertion guide portion includes a curved guide portion that is a plate member curved to project toward the door trim.

6. The door lock assembly according to claim 5, wherein the guide surface further includes a flat guide portion, and the flat guide portion is flat and adjacent to the insertion hole and continuous

from the curved guide portion and has a width that increases toward the insertion hole.

7. The door lock assembly according to claim 5, wherein the curved guide portion has two opposite edges that are opposite each other with respect to the vehicular front-rear direction, and a distance between the two opposite edges increases as the curved guide portion extends away from the insertion hole.

8. The door lock assembly according to claim 7, wherein the guide surface further includes a flat guide portion, and the flat guide portion is flat and adjacent to the insertion hole and continuous from the curved guide portion and the flat guide portion has a width that increases toward the insertion hole.

9. The door lock assembly according to claim 7, wherein the lock knob holder extends in an upper-bottom direction and includes the one of the two holes on an upper end and the insertion hole on a lower end, the insertion hole opens downward, and the two opposite edges do not overlap the insertion hole with respect to the vehicular front-rear direction.

10. The door lock assembly according to claim 7, wherein the lock knob holder extends in an upper-bottom direction and includes the one of the two holes on an upper end and the insertion hole on a lower end, the insertion hole opens downward, and the two opposite edges are on a same plane as a vehicular interior side hole edge of the insertion hole with respect to the vehicular front-rear direction or are on a vehicular interior side with respect to the vehicular interior side hole edge.

11. The door lock assembly according to claim 1, wherein the guide surface is inclined so as to approach the insertion hole as the guide surface extends upward.

12. The door lock assembly according to claim 2, wherein the guide surface of the insertion guide portion includes a curved guide portion that is a plate member curved to project toward the door trim, the curved guide portion has two opposite edges that are opposite each other with respect to the vehicular front-rear direction, and a distance between the two opposite edges increases as the curved guide portion extends away from the insertion hole.
