

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411431
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Tagawa; Yuki et al.

Charging system and image forming system

Abstract

A charging system includes a charging member that rotates while following a rotating image holding body and that charges the image holding body, a removing member that rotates while following the rotating charging member in a state of being arranged at a contact position in contact with the charging member and that removes an adhered deposit adhered to the charging member, a moving member that moves the removing member to a separation position separated from the charging member and the contact position, and at least one processor, in which the processor is configured to cause the removing member to remove the adhered deposit adhered to the charging member only for a removal time by controlling the moving member to move the removing member arranged at the separation position to the contact position at a time determined in advance.

Inventors: Tagawa; Yuki (Kanagawa, JP), Hayashi; Yoshiyuki (Kanagawa, JP), Kawabata; Yukimi (Kanagawa, JP), Yamakoshi; Kenta (Kanagawa, JP)

Applicant: FUJIFILM Business Innovation Corp. (Tokyo, JP)

Family ID: 89983594

Assignee: FUJIFILM Business Innovation Corp. (Tokyo, JP)

Appl. No.: 18/444753

Filed: February 18, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250053110 A1	Feb. 13, 2025

Foreign Application Priority Data

JP	2023-129638	Aug. 08, 2023
----	-------------	---------------

Publication Classification

Int. Cl.: G03G15/00 (20060101); G03G15/02 (20060101)

U.S. Cl.:

CPC G03G15/0225 (20130101); G03G2215/021 (20130101)

Field of Classification Search

CPC: G03G (15/0225)

USPC: 399/91; 399/98-100

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7756439	12/2009	Kosuge	399/100	G03G 15/025
8934808	12/2014	Amemiya	399/100	G03G 15/0225
8953971	12/2014	Hayashi	399/176	G03G 15/0225
9176456	12/2014	Tsuji	N/A	G03G 15/0225
2008/0025753	12/2007	Yamamoto et al.	N/A	N/A
2008/0292354	12/2007	Shinkawa et al.	N/A	N/A
2009/0060554	12/2008	Kosuge et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2003140449	12/2002	JP	N/A
2007347912	12/2003	JP	N/A
2007193207	12/2006	JP	N/A
2008203366	12/2007	JP	N/A
2009258522	12/2008	JP	N/A

OTHER PUBLICATIONS

“Search Report of Europe Counterpart Application”, issued on Jul. 18, 2024, pp. 1-9. cited by applicant

“Office Action of Europe Counterpart Application”, issued on Jul. 2, 2025, p. 1-p. 6. cited by applicant

Primary Examiner: Tran; Hoan H

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is based on and claims priority under 35 USC 119 from Japanese Patent

BACKGROUND

(i) Technical Field

(2) The present invention relates to a charging system and an image forming system.

(ii) Related Art

(3) An image forming apparatus described in JP2007-193207A has an image holder on which an image is formed, a charging roll that charges the image holder, a first support unit that supports the charging roll, a cleaning member that cleans the charging roll, a second support unit that supports the first support unit, and a moving unit that moves the second support unit, in which the second support unit supports the first support unit such that the charging roll moves to a print position in contact with an image holder surface and a retracted position not in contact with the image holder surface in response to the movement of the second support unit.

SUMMARY

(4) There is a removing member that removes an adhered deposit adhered to the rotating charging member. The removing member is in contact with the charging member at all times and removes the adhered deposit adhered to the charging member by rotating while following the rotating charging member.

(5) However, the adhered deposit remaining on the charging member without being removed by the removing member is pressed against the charging member by the removing member that rotates while following the charging member as being in contact therewith. Accordingly, a layer of the adhered deposit is formed on the charging member in some cases.

(6) Aspects of non-limiting embodiments of the present disclosure relate to a charging system and an image forming system that suppress formation of a layer of an adhered deposit to a charging member compared to a case where a removing member rotating while following the charging member is in contact with the charging member at all times.

(7) Aspects of certain non-limiting embodiments of the present disclosure overcome the above disadvantages and/or other disadvantages not described above. However, aspects of the non-limiting embodiments are not required to overcome the disadvantages described above, and aspects of the non-limiting embodiments of the present disclosure may not overcome any of the disadvantages described above.

(8) According to an aspect of the present disclosure, there is provided a charging system including a charging member that rotates while following a rotating image holding body and that charges the image holding body, a removing member that rotates while following the rotating charging member in a state of being arranged at a contact position in contact with the charging member and that removes an adhered deposit adhered to the charging member, a moving member that moves the removing member to a separation position separated from the charging member and the contact position, and at least one processor, in which the processor is configured to cause the removing member to remove the adhered deposit adhered to the charging member only for a removal time by controlling the moving member to move the removing member arranged at the separation position to the contact position at a time determined in advance.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Exemplary embodiment(s) of the present invention will be described in detail based on the following figures, wherein:

(2) FIG. 1 is a schematic configuration view showing an image forming apparatus according to a first exemplary embodiment of the present disclosure;

(3) FIG. 2 is a configuration view showing an image forming unit and a transfer device included in

the image forming apparatus according to the first exemplary embodiment of the present disclosure;

(4) FIG. 3 is a configuration view showing a charging device according to the first exemplary embodiment of the present disclosure;

(5) FIG. 4 is a perspective view showing an end portion of a removing member included in the charging device according to the first exemplary embodiment of the present disclosure;

(6) FIGS. 5A and 5B show the charging device according to the first exemplary embodiment of the present disclosure and are state views showing a state where the removing member is arranged at a contact position and a state where the removing member is arranged at a separation position;

(7) FIGS. 6A and 6B are diagrams showing a hardware configuration and a functional configuration of a control unit provided in the charging device according to the first exemplary embodiment of the present disclosure;

(8) FIG. 7 is a flowchart showing a removing step of removing an adhered deposit adhered to a charging roll of the charging device according to the first exemplary embodiment of the present disclosure;

(9) FIG. 8 is a drawing in which evaluation results of examples and a comparative example according to the first exemplary embodiment of the present disclosure are shown in a graph;

(10) FIG. 9 is a drawing in which the evaluation results of the examples and the comparative example according to the first exemplary embodiment of the present disclosure are shown in a table;

(11) FIGS. 10A and 10B are diagrams showing a hardware configuration and a functional configuration of a control unit provided in a charging device according to a second exemplary embodiment of the present disclosure;

(12) FIG. 11 is a flowchart showing a removing step of removing an adhered deposit adhered to a charging roll of the charging device according to the second exemplary embodiment of the present disclosure;

(13) FIG. 12 is a configuration view showing a charging device according to a third exemplary embodiment of the present disclosure;

(14) FIGS. 13A and 13B are diagrams showing a hardware configuration and a functional configuration of a control unit provided in the charging device according to the third exemplary embodiment of the present disclosure; and

(15) FIG. 14 is a flowchart showing a removing step of removing an adhered deposit adhered to a charging roll of the charging device according to the third exemplary embodiment of the present disclosure.

DETAILED DESCRIPTION

First Exemplary Embodiment

(16) An example of a charging device and an image forming apparatus according to a first exemplary embodiment of the present disclosure will be described with reference to FIGS. 1 to 9. An arrow H shown in the drawing indicates an apparatus up-down direction (vertical direction), an arrow W indicates an apparatus width direction (horizontal direction), and an arrow D indicates an apparatus depth direction (horizontal direction).

(17) Image Forming Apparatus 10

(18) As shown in FIG. 1, the image forming apparatus 10 is configured to include a first housing 12, a second housing 14, an image forming unit 16, a medium transport unit 50, a post-processing unit 60, and a control unit 68. The control unit 68 controls respective units (respective units or the like configuring the image forming unit 16) configuring the image forming apparatus 10. The image forming apparatus 10 is an example of an image forming system.

(19) In addition, the first housing 12 and the second housing 14 are arranged side by side in the apparatus width direction and are connected to each other by a connecting mechanism 44.

(20) Image Forming Unit 16

(21) The image forming unit **16** includes a toner image forming unit **20** that is arranged inside the first housing **12** as shown in FIG. **1** and that forms a toner image as shown in FIG. **2** and a transfer device **30** that transfers an image formed by the toner image forming unit **20** to a sheet member **P** which is a recording medium. Further, the image forming unit **16** includes a fixing device **40** that fixes the toner image, which is transferred to the sheet member **P**, to the sheet member **P**. The image forming unit **16** forms an image on the sheet member **P** through an electrophotographic image method.

(22) Toner Image Forming Unit **20**

(23) As shown in FIG. **2**, the toner image forming unit **20** is configured to include an image holding body **21**, a charging device **22**, an exposure device **23**, and a developing device **24**. A plurality of toner image forming units **20** are included to form toner images for respective colors. In the present exemplary embodiment, in total, four colors of yellow (Y), magenta (M), cyan (C), and black (K) toner image forming units **20** are provided. In addition, the toner image forming unit **20** of each color has the same structure, and in a circumferential direction of a transfer belt **31** included in the transfer device **30**, the yellow (Y), magenta (M), cyan (C), and black (K) toner image forming units **20** of respective colors are arranged in this order from an upstream side. In addition, the image holding body **21** of each color is in contact with the transfer belt **31**. The toner image forming units **20** of respective colors are arranged in the apparatus width direction. In a case where it is not necessary to distinguish Y, M, C, and K, Y, M, C, and K may be omitted.

(24) The image holding body **21** is formed in a cylindrical shape and is rotationally driven about an axis thereof by a driver (not shown). For example, a photosensitive layer having a negative charging polarity is formed on an outer peripheral surface of the image holding body **21**. An overcoat layer may be formed on the outer peripheral surface of the image holding body **21**.

(25) The charging device **22** includes a charging roll **70** that is an example of a charging member which is in contact with the outer peripheral surface (photosensitive layer) of the image holding body **21**, which rotates while following the rotating image holding body **21**, and which negatively charges the outer peripheral surface of the image holding body **21**. The charging device **22** is an example of a charging system. Details of the charging device **22** will be described later.

(26) The exposure device **23** forms an electrostatic latent image on the outer peripheral surface of the image holding body **21**. Specifically, the outer peripheral surface of the image holding body **21** charged by the charging device **22** is irradiated with modulated exposure light **L** according to image data. Then, the electrostatic latent image is formed on the outer peripheral surface of the image holding body **21** with irradiation of the exposure light **L**.

(27) By developing an electrostatic latent image formed on the outer peripheral surface of the image holding body **21** with a developer **G** containing a toner **T** (an example of powder) and a carrier **CA** as a toner image, the developing device **24** forms the toner image on the outer peripheral surface of the image holding body **21**. A toner cartridge **39** for replenishing the developing device **24** with the toner **T** is connected to the developing device **24** via a transport path (not shown). The toner cartridges **39** of respective colors are arranged side by side in the apparatus width direction above the exposure devices **23** and are individually attachable and detachable (replaceable) with respect to the first housing **12**.

(28) The transfer device **30** includes the endless transfer belt **31** to which a toner image of the image holding body **21** of each color is transferred, and the transfer belt **31** is wound around a plurality of rolls **32** to determine a posture. In the present exemplary embodiment, the transfer belt **31** is in a posture having an inverted obtuse triangle shape which is long in the apparatus width direction in a case of being viewed from a front side.

(29) A roll **32d** of the plurality of rolls **32** functions as a drive roll that makes the transfer belt **31** go around in an arrow **A** direction. In addition, a roll **32t** of the plurality of rolls **32** functions as a tension applying roll that applies tension to the transfer belt **31**. The roll **32b** of the plurality of rolls **32** functions as a facing roll of a secondary transfer roll **34** to be described later.

(30) Further, each primary transfer roll **33** that transfers a toner image formed on the outer peripheral surface of the image holding body **21** to the transfer belt **31** is provided on an opposite side of the image holding body **21** of each color with the transfer belt **31** sandwiched therebetween. (31) Further, the secondary transfer roll **34** that transfers a toner image transferred to the transfer belt **31** to the sheet member P is in contact with a top portion of the transfer belt **31** on a lower end side, which forms an obtuse angle, and a transfer nip NT is formed by the transfer belt **31** and the secondary transfer roll **34**.

(32) The fixing device **40** fixes a toner image to the sheet member P to which a toner image is transferred by the transfer device **30**. In the present exemplary embodiment, the fixing device **40** fixes the toner image to the sheet member P by pressurizing the toner image while heating the toner image at a fixing nip NF.

(33) Medium Transport Unit **50**

(34) As shown in FIG. 1, the medium transport unit **50** is configured to include a medium supply unit **52** that supplies the sheet member P to the image forming unit **16** and a medium discharge unit **54** that discharges the sheet member P on which an image is formed. Further, the medium transport unit **50** is configured to include a medium return unit **58** used in a case of forming an image on both sides of the sheet member P and an intermediate transfer unit **59** that transports the sheet member P from the transfer device **30** to the fixing device **40**.

(35) The medium supply unit **52** supplies the sheet member P one by one to the transfer nip NT of the image forming unit **16** in accordance with a transfer timing. On the contrary, the medium discharge unit **54** discharges the sheet member P, to which a toner image is fixed by the fixing device **40**, outside the device. Further, the medium return unit **58** returns the sheet member P to the image forming unit **16** (medium supply unit **52**) by reversing the front and back of the sheet member P in a case of forming an image on the other surface of the sheet member P having one surface to which a toner image is fixed.

(36) Post-Processing Unit **60**

(37) As shown in FIG. 1, the post-processing unit **60** is configured to include a medium cooling unit **62** that is arranged inside the second housing **14** and that cools the sheet member P on which an image is formed, a correction device **64** that corrects the bending of the sheet member P, and an image inspection unit **66** that inspects the image.

(38) In addition, respective units configuring the post-processing unit **60** are arranged in the medium discharge unit **54** of the medium transport unit **50**, and the medium cooling unit **62**, the correction device **64**, and the image inspection unit **66** are arranged in this order from an upstream side in a discharge direction of the sheet member P.

(39) Action of Image Forming Apparatus **10**

(40) Next, the outline of an image forming step and a post-processing step on the sheet member P by the image forming apparatus **10** will be described.

(41) In a case of forming an image on the sheet member P, developing rolls (reference symbol omitted) included in the image holding body **21** and the developing device **24** are rotated, and the transfer belt **31** is made go around. Further, a pressurizing roll **42** included in the fixing device **40** is rotated, and a fixing belt (reference symbol omitted) is made go around.

(42) Then, the image holding body **21** of each color is charged by the charging device **22** while rotating. In addition, the exposure device **23** of each color emits the exposure light L of each color according to image data and exposes the charged image holding body **21** of each color. In addition, an electrostatic latent image is formed on the outer peripheral surface of the image holding body **21** of each color. The electrostatic latent image formed on the image holding body **21** of each color is developed as a toner image with the developer G supplied from the developing device **24**.

Accordingly, a toner image of a corresponding color, among yellow (Y), magenta (M), cyan (C), and black (K), is formed on the image holding body **21** of each color.

(43) Further, a toner image of each color formed on the image holding body **21** of each color is

transferred in turn by the primary transfer roll **33** of each color to the transfer belt **31** that goes around. Accordingly, a toner image obtained by superimposing toner images of four colors is formed on the transfer belt **31**. The toner image is transported to the transfer nip NT as the transfer belt **31** goes around. At the transfer nip NT, the toner image is transferred from the transfer belt **31** to the transported sheet member P.

(44) The sheet member P to which a toner image is transferred is transported from the transfer nip NT of the transfer device **30** toward the fixing nip NF of the fixing device **40** by the intermediate transfer unit **59**. The fixing device **40** applies heat and a pressurizing force (fixing energy) to the sheet member P passing through the fixing nip NF. Accordingly, the toner image transferred to the sheet member P is fixed to the sheet member P.

(45) The sheet member P heated by the fixing device **40** is first cooled by the medium cooling unit **62**. Next, the bending of the sheet member P is corrected by the correction device **64**. Further, the presence or absence or a degree of a toner density defect, an image defect, an image position defect, and the like of a toner image fixed to the sheet member P is detected by the image inspection unit **66**. Then, the sheet member P is discharged to an outside of the second housing **14** by the medium discharge unit **54**.

(46) On the other hand, in a case where an image is formed on a non-image surface (back surface) of the sheet member P, on which no image is formed (a case of two-sided printing), a transport path for the sheet member P which has passed through the image inspection unit **66** is switched from the medium discharge unit **54** to the medium return unit **58**. Accordingly, the front and back of the sheet member P are reversed, and the sheet member P is sent into the medium supply unit **52**. An image is formed (fixed) on the back surface of the sheet member P in a step which is the same as the step described above, and the sheet member P is discharged to the outside of the second housing **14** by the medium discharge unit **54**.

(47) Major Portion Configuration

(48) Next, the charging device **22** will be described.

(49) As shown in FIG. 3, the charging device **22** includes the charging roll **70** that is arranged above the image holding body **21** and that negatively charges the outer peripheral surface of the image holding body **21** and a removing member **72** that removes an adhered deposit from the surface of the charging roll **70**. Further, the charging device **22** includes a moving member **80** that rotatably supports the removing member **72** and that moves the removing member **72** to a separation position separated from the charging roll **70** and a contact position in contact with the charging roll **70**, and a control unit **90** (see FIGS. 6A and 6B) that controls respective units.

(50) Charging Roll **70**

(51) As shown in FIG. 3, the charging roll **70** includes a shaft member **70a** that is in a columnar shape extending in the apparatus depth direction and a cylindrical roll portion **70b** through which the shaft member **70a** penetrates. The charging roll **70** is an example of the charging member.

(52) In addition, the roll portion **70b** is in contact with the outer peripheral surface of the image holding body **21** from above the image holding body **21**.

(53) In the configuration, the charging roll **70** rotates while following the rotating image holding body **21**. Then, as a voltage is applied from a power source to the charging roll **70** that rotates while following the image holding body **21**, the charging roll **70** charges the outer peripheral surface of the image holding body **21**.

(54) Removing Member **72**

(55) As shown in FIG. 3, the removing member **72** includes a core material **74** that is in a columnar shape extending in the apparatus depth direction and a removing material **76** that is spirally wound around an outer peripheral surface of the core material **74**.

(56) In addition, the removing material **76** is in contact with the outer peripheral surface of the charging roll **70** from above the charging roll **70**. Further, the core material **74** of the removing member **72** is rotatably supported by a pair of support members **82** arranged at both end portions of

the removing member **72**. In other words, the core material **74** is rotatably supported about an axis of the core material **74** by the support members **82**.

(57) For example, the core material **74** is formed of a resin material (for example, a polyacetal resin or the like). In addition, for example, the removing material **76** is formed by foaming a urethane resin and has a rectangular section in a free state where the removing material **76** is not wound around the outer peripheral surface of the core material **74**. Then, the removing material **76** is fixed to the outer peripheral surface of the core material **74** by using a double-sided tape (not shown).

(58) As shown in FIG. **4**, hole portions **78** extending in an axial direction of the core material **74** are formed respectively in both end portions of the core material **74** (only one side is shown in FIG. **4**). Then, both end portions of the removing material **76** are compressed in a thickness direction and are fitted to hole portions **78**.

(59) In the configuration, as the removing material **76** comes into contact with the roll portion **70b** of the rotating charging roll **70** and the removing member **72** rotates while following, the removing material **76** scrapes off and removes an adhered deposit adhered to the roll portion **70b**.

(60) Moving Member **80**

(61) As shown in FIG. **3**, the moving members **80** are respectively arranged at both end portions of the removing member **72**. In addition, each of the moving members **80** includes the support member **82** that rotatably supports the removing member **72**, a solenoid **84** that moves the support member **82** in directions of being close to and separated away from the charging roll **70**, and a biasing member **86** that biases the removing member **72** toward the charging roll **70**.

(62) The support member **82** is in a rectangular parallelepiped shape and supports the core material **74** of the removing member **72** via a bearing. The solenoid **84** is arranged above the support member **82**. The biasing member **86** is a compression coil spring extending in an up-down direction and is arranged between the support member **82** and the solenoid **84**.

(63) In the configuration, in a non-energized state of the solenoid **84**, the moving member **80** moves the removing material **76** to the separation position separated from the charging roll **70** as shown in FIG. **5B**. On the other hand, in a case where the solenoid **84** is energized, the moving member **80** moves the removing material **76** to the contact position in contact with the charging roll **70** as shown in FIG. **5A**. Then, the removing member **72** moved to the contact position rotates while following the rotating charging roll **70** and scrapes off and removes an adhered deposit adhered to the charging roll **70**.

(64) Control Unit **90**

(65) Hardware Configuration of Control Unit **90**

(66) As shown in FIG. **6A**, the control unit **90** has a central processing unit (CPU) **91**, a read only memory (ROM) **92**, a random access memory (RAM) **93**, a storage **94**, and a communication interface (I/F) **95**. In addition, the respective configurations are communicably connected to each other via a bus **99**. The CPU **91** is an example of a processor.

(67) The CPU **91** is a central processing unit and executes various types of programs or controls respective units. That is, the CPU **91** reads the program from the ROM **92** or the storage **94** and executes a program using the RAM **93** as a work area. The CPU **91** controls each configuration and performs various types of calculation processing in accordance with the program stored in the ROM **92** or the storage **94**.

(68) In the present exemplary embodiment, for example, a drive program for energizing the solenoid **84** based on information of a print job is stored in the ROM **92** or the storage **94**.

(69) The RAM **93** temporarily stores a program or data as a work area. The storage **94** is configured by a hard disk drive (HDD) or a solid state drive (SSD) and stores various types of programs including an operating system and various types of data.

(70) The communication interface **95** is an interface for communicating with the solenoid **84** and the like. For example, standards, such as ETHERNET (registered trademark), FDDI, and Wi-Fi (registered trademark), are used.

(71) In a case of executing the drive program described above, the control unit **90** realizes various types of functions using the hardware resources. Next, a functional configuration of the control unit **90** in which the control unit **90** realizes various types of functions will be described.

(72) Functional Configuration of Control Unit **90**

(73) As shown in FIG. **6B**, the control unit **90** has a receiving unit **96**, a determination unit **97**, and an operating unit **98**. Each functional configuration is realized by causing the CPU **91** to read and execute the drive program stored in the ROM **92** or the storage **94**. Details of the control unit **90** will be described together with action to be described later.

(74) Action of Major Portion Configuration

(75) Next, a removing step of removing an adhered deposit adhered to the charging roll **70** using the removing member **72** will be described with reference to a flowchart of FIG. **7**. In an initial state before entering the removing step, the removing member **72** is arranged at the separation position.

(76) In a case where the receiving unit **96** of the control unit **90** receives information of a print job to be executed by the image forming apparatus **10** from now on from the control unit **68** of the image forming apparatus **10**, in step **S100**, the determination unit **97** of the control unit **90** determines whether or not the number of images from the previous removal reaches a threshold based on the information of the print job.

(77) Specifically, the determination unit **97** determines whether or not a cumulative number of images reaches the threshold in a case where a received print job is executed after the removing member **72** moves to the contact position and removes an adhered deposit of the charging roll **70**. In the present exemplary embodiment, for example, the threshold of the number of images is 50,000 sheets. That is, the determination unit **97** determines whether or not the cumulative number of images reaches 50,000 sheets in a case where the received print job is executed after the removing member **72** moves to the contact position and removes the adhered deposit of the charging roll **70**. In a case where the number of images reaches the threshold, processing proceeds to step **S200**, and in a case where the number of images does not reach the threshold, step **S100** is executed again.

(78) In step **S200**, the receiving unit **96** receives operating information of the image forming apparatus **10** from the control unit **68** of the image forming apparatus **10**, and the determination unit **97** determines whether or not the print job has ended. In a case where the print job ends, processing proceeds to step **S300**, and in a case where the print job is not ended, step **S200** is executed again.

(79) In step **S300**, the operating unit **98** energizes the solenoid **84**, and the removing member **72** at the separation position (see FIG. **5B**) is moved to the contact position (see FIG. **5A**) only for a time determined in advance. The removing member **72** moved to the contact position rotates while following the rotating charging roll **70** and scrapes off and removes an adhered deposit adhered to the charging roll **70**. In the present exemplary embodiment, for example, a time for which the removing member **72** is at the contact position is 120 [sec]. That is, a removal time for removing the adhered deposit is 120 [sec]. In a case where 120 [sec] is reached after the removing member **72** moves to the contact position, the operating unit **98** brings the solenoid **84** into a non-energized state and moves the removing member **72** at the contact position (see FIG. **5A**) to the separation position (see FIG. **5B**). In a case where the removing member **72** moves to the separation position, processing proceeds to step **S400**.

(80) In step **S400**, the receiving unit **96** receives presence or absence information of a print job to be executed by the image forming apparatus **10** from now on from the control unit **68** of the image forming apparatus **10**. In a case where there is a print job, processing returns to step **S100** again, and the step described above is executed. On the other hand, in a case where there is no print job, an operation of an example is ended.

(81) Actual Device Test

(82) Herein, the following actual device test is conducted using DocuCentre-VI C7771 manufactured by FUJIFILM Business Innovation Corp. Hereinafter, evaluation conditions, evaluation items, and evaluation results of the actual device test will be described.

(1) Example 1

(83) Evaluation Conditions

(84) An image having an image density (area coverage) of 80% is printed using black on 250,000 sheets of A4 size paper.

(85) In Example 1, a threshold of the number of images is 50,000 sheets (50 kPV). That is, the removing member **72** is moved to the contact position for each of 50,000 sheets (50 kPV). A removal time is 120 [sec]. That is, a contact state of the removing member **72** is maintained for 120 [sec].

(86) Evaluation Items

(87) The volume resistivity of the charging roll **70** is measured for each of 50,000 sheets (50 kPV). The target value of the volume resistivity of the charging roll **70** after printing 250,000 sheets is less than 10.5 [$\Omega \cdot \text{cm}$].

(88) As for the volume resistivity, a sheet-like measurement sample is collected from a measurement target. A voltage adjusted such that an electric field (applied voltage/composition sheet thickness) reached 1,000 V/cm is applied to the measurement sample for 30 seconds by using a measuring jig (R12702A/B resistivity chamber: manufactured by Advantest Corporation) and a high resistance meter (R8340A digital high resistance/micro ammeter: manufactured by Advantest Corporation) in conformity with JIS K 6911 (1995), and the volume resistivity is calculated from a flowing current value according to the following equation.

Volume resistivity ($\Omega \cdot \text{cm}$) = (19.63 × applied voltage (V)) / (current value (A) × measurement sample thickness (cm))

(89) Further, after printing 250,000 sheets (250 kPV), a change in the volume resistivity of the charging roll **70** is derived. The target value of the change in the volume resistivity after printing 250,000 sheets (250 kPV) is less than 2.0 [$\Omega \cdot \text{cm}$].

(90) In addition, after printing 250,000 sheets (250 kPV), the thickness of an adhered deposit (discharge products, external additives, and the like) deposited on the charging roll **70** is measured through SEM observation. The target value of the thickness of a layer of the adhered deposit after printing 250,000 sheets (250 kPV) is less than 2.0 [μm].

(91) Further, the grade of density unevenness of an output image caused by contamination of the charging roll **70** is evaluated on a four-point scale of A, B, C, and D. As for the grade of density unevenness, the output image is visually checked, a level acceptable for the product is “A”, and “B”, “C”, and “D” are levels unacceptable for the product in ascending order of an unacceptable degree.

(92) Evaluation Results

(93) A change in the volume resistivity of the charging roll **70** of Example 1 is described in the graph shown in FIG. 8. The horizontal axis in the graph is the number of prints (the number of images), and the vertical axis is the volume resistivity. A solid line in the graph indicates a change in the volume resistivity of the charging roll **70** of Example 1. In addition, a broken line in the graph indicates from the volume resistivity after the previous removing step of an adhered deposit to the volume resistivity before the next removing step of an adhered deposit such that a change in the volume resistivity before and after removing the adhered deposit can be seen in Example 1.

(94) As can be seen from the graph, in Example 1, the volume resistivity of the charging roll **70** after printing 250,000 sheets (250 kPV) is less than 10.5 [$\Omega \cdot \text{cm}$], and the target is satisfied.

(95) Further, in Example 1, a change in the volume resistivity of the charging roll **70** after printing 250,000 sheets (250 kPV) is 0.1 [$\Omega \cdot \text{cm}$] as described in the table shown in FIG. 9, and the target is satisfied.

(96) In addition, in Example 1, the thickness of a layer of an adhered deposit of the charging roll **70**

after printing 250,000 sheets (250 kPV) is 0.0 [μm] as described in the table shown in FIG. 9. As described above, the thickness of the layer of the adhered deposit is less than 2.0 [μm], and the target is satisfied.

(97) In addition, in Example 1, a grade of density unevenness of an output image after printing 250,000 sheets (250 kPV) is “A” as described in the table shown in FIG. 9. That is, density unevenness is a level acceptable for the product.

(2) Example 2

(98) Evaluation Conditions

(99) In Example 2, a threshold of the number of images is 5,000 sheets (5 kPV). That is, the removing member 72 is moved to the contact position for each of 5,000 sheets (5 kPV). A removal time is 60 [sec]. That is, a contact state of the removing member 72 is maintained for 60 [sec]. Other conditions are the same as in Example 1.

(100) Evaluation Items

(101) Evaluation items are the same as in Example 1.

(102) Evaluation Results

(103) A change in the volume resistivity of the charging roll 70 of Example 2 is described in the graph shown in FIG. 8. Specifically, a one-dot chain line in the graph indicates a change in the volume resistivity of the charging roll 70 of Example 2. As can be seen from the graph, in Example 2, the volume resistivity of the charging roll 70 after printing 250,000 sheets (250 kPV) is less than 10.5 [$\Omega\cdot\text{Math.cm}$], and the target is satisfied.

(104) Further, in Example 2, a change in the volume resistivity of the charging roll 70 after printing 250,000 sheets (250 kPV) is 0.5 [$\Omega\cdot\text{Math.cm}$] as described in the table shown in FIG. 9, and the target is satisfied.

(105) In addition, in Example 2, the thickness of a layer of an adhered deposit of the charging roll 70 after printing 250,000 sheets (250 kPV) is 0.5 [μm] as described in the table shown in FIG. 9. As described above, the thickness of the layer of the adhered deposit is less than 2.0 [μm], and the target is satisfied.

(106) In addition, in Example 2, a grade of density unevenness of an output image after printing 250,000 sheets (250 kPV) is “A” as described in the table shown in FIG. 9. That is, density unevenness is a level acceptable for the product.

(3) Example 3

(107) Evaluation Conditions

(108) In Example 3, a threshold of the number of images is 100 sheets (100 PV). That is, the removing member 72 is moved to the contact position for each of 100 sheets (100 PV). A removal time is 10 [sec]. That is, a contact state of the removing member 72 is maintained for 10 [sec]. Other conditions are the same as in Example 1.

(109) Evaluation Items

(110) Evaluation items are the same as in Example 1.

(111) Evaluation Results

(112) A change in the volume resistivity of the charging roll 70 of Example 3 is described in the graph shown in FIG. 8. Specifically, a two-dot chain line in the graph indicates a change in the volume resistivity of the charging roll 70 of Example 3. As can be seen from the graph, in Example 3, the volume resistivity of the charging roll 70 after printing 250,000 sheets (250 kPV) is less than 10.5 [$\Omega\cdot\text{Math.cm}$], and the target is satisfied.

(113) Further, in Example 3, a change in the volume resistivity of the charging roll 70 after printing 250,000 sheets (250 kPV) is 1.7 [$\Omega\cdot\text{Math.cm}$] as described in the table shown in FIG. 9, and the target is satisfied.

(114) In addition, in Example 3, the thickness of a layer of an adhered deposit of the charging roll 70 after printing 250,000 sheets (250 kPV) is 1.0 [μm] as described in the table shown in FIG. 9. As described above, the thickness of the layer of the adhered deposit is less than 2.0 [μm], and the

target is satisfied.

(115) In addition, in Example 3, a grade of density unevenness of an output image after printing 250,000 sheets (250 kPV) is “A” as described in the table shown in FIG. 9. That is, density unevenness is a level acceptable for the product.

(4) Comparative Example

(116) Evaluation Conditions

(117) In a comparative example, a state where the removing member 72 is moved to the contact position is maintained. That is, the removing member 72 is brought into contact with the charging roll 70 at all times.

(118) Evaluation Items

(119) Evaluation items are the same as in Example 1.

(120) Evaluation Results

(121) A change in the volume resistivity of the charging roll 70 of the comparative example is described in the graph shown in FIG. 8. Specifically, a dotted line in the graph indicates a change in the volume resistivity of the charging roll 70 of the comparative example. As can be seen from the graph, in the comparative example, the volume resistivity of the charging roll 70 after printing 250,000 sheets (250 kPV) is 10.5 [$\Omega \cdot \text{Math.cm}$] or more, and the target is not satisfied.

(122) Further, in the comparative example, a change in the volume resistivity of the charging roll 70 after printing 250,000 sheets (250 kPV) is 2.6 [$\Omega \cdot \text{Math.cm}$] as described in the table shown in FIG. 9, and the target is not satisfied.

(123) In addition, in the comparative example, the thickness of a layer of an adhered deposit of the charging roll 70 after printing 250,000 sheets (250 kPV) is 2.0 [μm] as described in the table shown in FIG. 9. As described above, the thickness of the layer of the adhered deposit is 2.0 [μm] or more, and the target is not satisfied.

(124) In addition, in the comparative example, a grade of density unevenness of an output image after printing 250,000 sheets (250 kPV) is “C” as described in the table shown in FIG. 9. That is, density unevenness is not a level acceptable for the product.

(125) Hereinafter, in the comparative example, a reason why the thickness of a layer of an adhered deposit of the charging roll 70 increases and the volume resistivity of the charging roll 70 increases will be considered.

(126) The removing member 72 at the contact position removes an adhered deposit adhered to the charging roll 70 by rotating while following the charging roll 70. However, since the removing member 72 is arranged at the contact position at all times, the adhered deposit remaining on the charging roll 70 without being removed by the removing member 72 is pressed against the charging roll 70 by the removing member 72 and becomes a layer on the surface of the charging roll 70 so as to be fixed, and filming proceeds. Accordingly, in the comparative example, it is considered that the thickness of the adhered deposit of the charging roll 70 increases and the volume resistivity of the charging roll 70 increases.

(127) Summary

(128) As described above, in the charging device 22, the CPU 91 of the control unit 90 controls the moving member 80 to move the removing member 72 arranged at the separation position to the contact position at a time determined in advance and causes the removing member 72 to remove an adhered deposit adhered to the charging roll 70 only for a removal time. Accordingly, compared to a case where the removing member that rotates while following the charging roll is in contact with the charging roll at all times as in the comparative example, formation of a layer of the adhered deposit on the surface of the charging roll 70 is suppressed.

(129) In addition, in the charging device 22, after the number of images from the previous removal of an adhered deposit has reached a number determined in advance, the removing member 72 arranged at the separation position is moved to the contact position, and the adhered deposit adhered to the charging roll 70 is removed by the removing member 72 only for a removal time.

Accordingly, compared to a case where the adhered deposit is removed for each time determined in advance, formation of a layer of the adhered deposit on the surface of the charging roll **70** is effectively suppressed.

(130) In addition, in the charging device **22**, after the number of images from the previous removal of an adhered deposit has reached a number determined in advance and in a case of non-image formation, the removing member **72** arranged at the separation position is moved to the contact position, and the adhered deposit adhered to the charging roll **70** is removed by the removing member **72** only for a removal time. Accordingly, compared to a case where the removing member arranged at the separation position moves to the contact position in a case of image formation, rotation of the charging roll **70** in a case of image formation is stable, and thereby a decrease in image quality is suppressed. Herein, a case of non-image formation is a state where a print job is not executed.

(131) In addition, as the image forming apparatus **10** includes the charging device **22**, density unevenness of an output image is suppressed compared to a case of including the charging device in which the removing member is in contact with the charging roll at all times.

Second Exemplary Embodiment

(132) Next, an example of a charging device and an image forming apparatus according to a second exemplary embodiment will be described with reference to FIGS. **10A** to **11**. A portion of the second exemplary embodiment different from the first exemplary embodiment will be generally described.

(133) Control Unit **190**

(134) Hardware Configuration of Control Unit **190**

(135) As shown in FIG. **10A**, a control unit **190** of a charging device **122** of the second exemplary embodiment has a central processing unit (CPU) **191**, a read only memory (ROM) **192**, a random access memory (RAM) **193**, a storage **194**, and a communication interface (I/F) **195**. In addition, the respective configurations are communicably connected to each other via a bus **199**. The charging device **122** is an example of the charging system, and the CPU **191** is an example of the processor.

(136) Functional Configuration of Control Unit **190**

(137) As shown in FIG. **10B**, the control unit **190** has a receiving unit **196**, a determination unit **197**, and an operating unit **198**. Each functional configuration is realized by causing the CPU **191** to read and execute a drive program stored in the ROM **192** or the storage **194**. Details of the control unit **190** will be described together with action to be described later.

(138) Action of Major Portion Configuration

(139) Next, a removing step of removing an adhered deposit adhered to the charging roll **70** using the removing member **72** will be described with reference to a flowchart of FIG. **11**.

(140) In a case where the receiving unit **196** of the control unit **190** receives information of a print job to be executed by the image forming apparatus **10** from now on from the control unit **68** of the image forming apparatus **10**, in step **S1100**, the determination unit **197** of the control unit **190** determines whether or not the number of cycles (number of rotations) of the image holding body **21** from the previous removal reaches a threshold based on the information of the print job.

(141) Specifically, the determination unit **197** determines whether or not the number of cycles of the image holding body **21** reaches a threshold in a case where a received print job is executed after the removing member **72** moves to the contact position and removes an adhered deposit of the charging roll **70**. In the present exemplary embodiment, for example, a threshold of the number of cycles of the image holding body **21** is 200,000 [cycle]. That is, the determination unit **197** determines whether or not the cumulation of the number of cycles of the image holding body **21** reaches 200,000 [cycle] (200 kcycle) in a case where the received print job is executed after the removing member **72** moves to the contact position and removes the adhered deposit of the charging roll **70**.

(142) In a case where the number of cycles of the image holding body **21** reaches 200,000 [cycle] (200 kcycle), processing proceeds to step **S1200**, and in a case where the number of cycles of the image holding body **21** does not reach 200,000 [cycle] (200 kcycle), step **S1100** is executed again.
(143) In step **S1200**, the receiving unit **196** receives operating information of the image forming apparatus **10** from the control unit **68** of the image forming apparatus **10**, and the determination unit **197** determines whether or not the print job has ended. In a case where the print job ends, processing proceeds to step **S1300**, and in a case where the print job is not ended, step **S1200** is executed again.

(144) In step **S1300**, the operating unit **198** energizes the solenoid **84**, and the removing member **72** at the separation position (see FIG. 5B) is moved to the contact position (see FIG. 5A) only for a time determined in advance. The removing member **72** moved to the contact position rotates while following the rotating charging roll **70** and scrapes off and removes an adhered deposit adhered to the charging roll **70**. In the present exemplary embodiment, for example, a time determined in advance for the number of images is 120 [sec]. That is, a removal time for removing the adhered deposit is 120 [sec]. In a case where 120 [sec] is reached after the removing member **72** moves to the contact position, the operating unit **198** brings the solenoid **84** into a non-energized state and moves the removing member **72** at the contact position (see FIG. 5A) to the separation position (see FIG. 5B). In a case where the removing member **72** moves to the separation position, processing proceeds to step **S1400**.

(145) In step **S1400**, the receiving unit **196** receives presence or absence information of a print job to be executed by the image forming apparatus **10** from now on from the control unit **68** of the image forming apparatus **10**. In a case where there is a print job, processing returns to step **S1100** again, and the step described above is executed. On the other hand, in a case where there is no print job, an operation of an example is ended.

(146) Actual Device Test

(147) The following actual device test is conducted using DocuCentre-VI C7771 manufactured by FUJIFILM Business Innovation Corp. Hereinafter, conditions, evaluation items, and evaluation results of the actual device test will be described.

(1) Example 4

(148) Evaluation Conditions

(149) In Example 4, a threshold of the number of cycles of the image holding body **21** is 200,000 [cycle] (200 kcycle).

(150) That is, the removing member **72** is moved to the contact position every 200,000 [cycle] (200 kcycle).

(151) A removal time is 120 [sec]. That is, a contact state of the removing member **72** is maintained for 120 [sec]. Other conditions are the same as in Example 1.

(152) Evaluation Items

(153) Evaluation items are the same as in Example 1.

(154) Evaluation Results

(155) Further, in Example 4, a change in the volume resistivity of the charging roll **70** after printing 250,000 sheets (250 kPV) is 0.2 [Ω .Math.cm] as described in the table shown in FIG. 9, and the target is satisfied.

(156) In addition, in Example 4, the thickness of a layer of an adhered deposit of the charging roll **70** after printing 250,000 sheets (250 kPV) is 0.2 [μ m] as described in the table shown in FIG. 9. As described above, the thickness of the layer of the adhered deposit is less than 2.0 [μ m], and the target is satisfied.

(157) In addition, in Example 4, a grade of density unevenness of an output image after printing 250,000 sheets (250 kPV) is "A" as described in the table shown in FIG. 9. That is, density unevenness is a level acceptable for the product.

(158) Summary

(159) As described above, in the charging device **122**, after the number of cycles of the image holding body **21** from the previous removal of an adhered deposit has reached a number determined in advance, the removing member **72** arranged at the separation position is moved to the contact position, and the adhered deposit adhered to the charging roll **70** is removed by the removing member **72** only for a removal time. Accordingly, compared to a case where the adhered deposit is removed for each time determined in advance, formation of a layer of the adhered deposit on the surface of the charging roll **70** is effectively suppressed.

(160) In addition, in the charging device **122**, after the number of cycles of the image holding body **21** from the previous removal of an adhered deposit has reached a number determined in advance and in a case of non-image formation, the removing member **72** arranged at the separation position is moved to the contact position, and the adhered deposit adhered to the charging roll **70** is removed by the removing member **72** only for a removal time. Accordingly, compared to a case where the removing member arranged at the separation position moves to the contact position in a case of image formation, rotation of the charging roll **70** in a case of image formation is stable, and thereby a decrease in image quality is suppressed.

Third Exemplary Embodiment

(161) Next, an example of a charging device and an image forming apparatus according to a third exemplary embodiment will be described with reference to FIGS. **12** to **13B**. A portion of the third exemplary embodiment different from the first exemplary embodiment will be generally described.

(162) As shown in FIG. **12**, a charging device **222** according to the third exemplary embodiment includes a resistance detector **224** that detects an electrical resistance between the charging roll **70** and the image holding body **21**. The charging device **222** is an example of the charging system, and the resistance detector **224** is an example of a detection unit.

(163) Control Unit **290**

(164) Hardware Configuration of Control Unit **290**

(165) As shown in FIG. **13A**, a control unit **290** of the charging device **222** has a central processing unit (CPU) **291**, a read only memory (ROM) **292**, a random access memory (RAM) **293**, a storage **294**, and a communication interface (I/F) **295**. In addition, the respective configurations are communicably connected to each other via a bus **299**. The CPU **291** is an example of the processor.

(166) Functional Configuration of Control Unit **290**

(167) As shown in FIG. **13B**, the control unit **290** has a receiving unit **296**, a determination unit **297**, and an operating unit **298**. Each functional configuration is realized by causing the CPU **291** to read and execute a drive program stored in the ROM **292** or the storage **294**. Details of the control unit **290** will be described together with action to be described later.

(168) Action of Major Portion Configuration

(169) Next, a removing step of removing an adhered deposit adhered to the charging roll **70** using the removing member **72** will be described with reference to a flowchart of FIG. **14**.

(170) The receiving unit **296** of the control unit **290** receives information of a print job to be executed by the image forming apparatus **10** from now on from the control unit **68** of the image forming apparatus **10**. In a case where an electrical resistance between the charging roll **70** and the image holding body **21** after the previous removal of an adhered deposit is received from the resistance detector **224**, in step **S2100**, the receiving unit **296** monitors the electrical resistance detected from the resistance detector **224** in a case of image formation, and the determination unit **297** determines whether or not the electrical resistance from the previous removal has increased by an amount determined in advance based on the monitored electrical resistance.

(171) Specifically, the determination unit **297** determines whether or not an increased amount of the electrical resistance reaches a threshold after the removing member **72** moves to the contact position and removes an adhered deposit of the charging roll **70**. In the present exemplary embodiment, a threshold of the increased amount of the electrical resistance is, for example, 1.0 [log Ω]. That is, the determination unit **297** determines whether or not the increased amount of the

electrical resistance has reached 1.0 [$\log \Omega$] after the removing member **72** moves to the contact position and removes the adhered deposit of the charging roll **70**. In a case where the increased amount of the electrical resistance has reached 1.0 [$\log \Omega$], processing proceeds to step **S2200**, and in a case where the increased amount of the electrical resistance has not reached 1.0 [$\log \Omega$], step **S2100** is executed again.

(172) In step **S2200**, the receiving unit **296** receives operating information of the image forming apparatus **10** from the control unit **68** of the image forming apparatus **10**, and the determination unit **297** determines whether or not the print job has ended. In a case where the print job ends, processing proceeds to step **S2300**, and in a case where the print job is not ended, step **S2200** is executed again.

(173) In step **S2300**, the operating unit **298** energizes the solenoid **84**, and the removing member **72** at the separation position (see FIG. 5B) is moved to the contact position (see FIG. 5A) only for a time determined in advance. The removing member **72** moved to the contact position rotates while following the rotating charging roll **70** and scrapes off and removes an adhered deposit adhered to the charging roll **70**. In the present exemplary embodiment, for example, a time determined in advance for the number of images is 60 [sec]. That is, a removal time for removing the adhered deposit is 60 [sec]. In a case where 60 [sec] is reached after the removing member **72** moves to the contact position, the operating unit **298** brings the solenoid **84** into a non-energized state and moves the removing member **72** at the contact position (see FIG. 5A) to the separation position (see FIG. 5B). In a case where the removing member **72** moves to the separation position, processing proceeds to step **S2400**.

(174) In step **S2400**, the receiving unit **296** receives presence or absence information of a print job to be executed by the image forming apparatus **10** from now on from the control unit **68** of the image forming apparatus **10**. In a case where there is a print job, processing returns to step **S2100** again, and the step described above is executed. On the other hand, in a case where there is no print job, an operation of an example is ended.

(175) Although the removal time is 60 [sec] in step **S2300**, the control unit **290** derives a difference in the electrical resistance before and after removal of an adhered deposit, and in a case where the difference in the electrical resistance is small, the next removal time may be long compared to a case where the difference in the electrical resistance is large. Accordingly, compared to a case where the removal time is the same at all times, the adhered deposit adhered to the charging roll **70** is effectively removed.

(176) Actual Device Test

(177) The following actual device test is conducted using DocuCentre-VI C7771 manufactured by FUJIFILM Business Innovation Corp. Hereinafter, specifications, evaluation items, and evaluation results of the actual device test will be described.

(1) Example 5

(178) Evaluation Conditions

(179) In Example 5, a threshold of an increased amount in an electrical resistance is 1.0 [$\log \Omega$]. That is, the removing member **72** is moved to the contact position each time the electrical resistance increased by 1.0 [$\log \Omega$]. A removal time is 60 [sec]. That is, a contact state of the removing member **72** is maintained for 60 [sec]. Other conditions are the same as in Example 1.

(180) Evaluation Items

(181) Evaluation items are the same as in Example 1.

(182) Evaluation Results

(183) In Example 5, a change in the volume resistivity of the charging roll **70** after printing 250,000 sheets (250 kPV) is 0.4 [$\Omega \cdot \text{cm}$] as described in the table shown in FIG. 9, and the target is satisfied.

(184) In addition, in Example 5, the thickness of a layer of an adhered deposit of the charging roll **70** after printing 250,000 sheets (250 kPV) is 0.4 [μm] as described in the table shown in FIG. 9.

As described above, the thickness of the layer of the adhered deposit is less than 2.0 [μm], and the target is satisfied.

(185) In addition, in Example 5, a grade of density unevenness of an output image after printing 250,000 sheets (250 kPV) is “A” as described in the table shown in FIG. 9. That is, density unevenness is a level acceptable for the product.

(186) Summary

(187) As described above, in the charging device **222**, after the electrical resistance has increased by the amount determined in advance from the previous removal of an adhered deposit, the removing member **72** arranged at the separation position is moved to the contact position, and the adhered deposit adhered to the charging roll **70** is removed by the removing member **72** only for a removal time. Accordingly, compared to a case where the adhered deposit is removed for each time determined in advance, formation of a layer of the adhered deposit on the surface of the charging roll **70** is effectively suppressed.

(188) In addition, in the charging device **222**, after the electrical resistance from the previous removal of an adhered deposit has increased by the amount determined in advance and in a case of non-image formation, the removing member **72** arranged at the separation position is moved to the contact position, and the adhered deposit adhered to the charging roll **70** is removed by the removing member **72** only for a removal time. Accordingly, compared to a case where the removing member arranged at the separation position moves to the contact position in a case of image formation, rotation of the charging roll **70** is stable in a case of image formation, and thereby a decrease in image quality is suppressed.

(189) Although details of a certain exemplary embodiment of the present disclosure have been described in detail, the present disclosure is not limited to such an exemplary embodiment, and it is clear for those skilled in the art that the present disclosure can take other various exemplary embodiments within the scope of the present disclosure. For example, although a removing operation of removing an adhered deposit has been executed in a case of non-image formation in the exemplary embodiments, the removing operation of removing the adhered deposit may be executed in a case of image formation. However, in this case, action achieved by removing the adhered deposit in a case of non-image formation is not achieved.

(190) In addition, although not particularly described in the exemplary embodiments, the removing operation may be executed at each time determined in advance. However, in this case, action achieved by performing the removing operation based on the number of images, the number of cycles of the image holding body **21**, or the increased amount of the electrical resistance is not achieved.

(191) In addition, the threshold of the number of images described in the first exemplary embodiment is merely an example, and other thresholds may be used.

(192) In addition, the threshold of the number of cycles of the image holding body **21** described in the second exemplary embodiment is merely an example, and other thresholds may be used.

(193) In addition, the threshold of the increased amount of the electrical resistance described in the third exemplary embodiment is merely an example, and other thresholds may be used.

(194) In addition, although the removal time is described as an example in the exemplary embodiments, an actual removal time may be shorter and may be longer than the described removal time.

(195) In addition, although the control units **90**, **190**, and **290** of the charging devices **22**, **122**, and **222** are provided separately from the control unit **68** of the image forming apparatus **10** in the exemplary embodiments, the control unit of the charging device may configure a part of the control unit **68** of the image forming apparatus **10**.

(196) In addition, although not particularly described in the exemplary embodiments, the charging devices **22**, **122**, and **222** and the image forming apparatus **10** may be configured by a single device or may be configured by a plurality of devices.

(197) (((1)))

(198) A charging system comprising: a charging member that rotates while following a rotating image holding body and that charges the image holding body; a removing member that rotates while following the rotating charging member in a state of being arranged at a contact position in contact with the charging member and that removes an adhered deposit adhered to the charging member; a moving member that moves the removing member to a separation position separated from the charging member and the contact position; and at least one processor, wherein the processor is configured to: cause the removing member to remove the adhered deposit adhered to the charging member only for a removal time by controlling the moving member to move the removing member arranged at the separation position to the contact position at a time determined in advance.

(((2)))

(199) The charging system according to (((1))), wherein the processor is configured to: cause the removing member to remove the adhered deposit adhered to the charging member only for the removal time by moving the removing member arranged at the separation position to the contact position after the number of images formed on the image holding body from previous removal of the adhered deposit has reached a number determined in advance.

(200) (((3)))

(201) The charging system according to (((1))) or (((2))), wherein the processor is configured to: move the removing member arranged at the separation position to the contact position after the number of images from previous removal of the adhered deposit has reached a number determined in advance and in a case of non-image formation.

(((4)))

(202) The charging system according to (((1))), wherein the processor is configured to: cause the removing member to remove the adhered deposit adhered to the charging member only for the removal time by moving the removing member arranged at the separation position to the contact position after the number of cycles of the image holding body from previous removal of the adhered deposit has reached a number determined in advance.

(((5)))

(203) The charging system according to (((1))) or (((4))), wherein the processor is configured to: move the removing member arranged at the separation position to the contact position after the number of cycles from previous removal of the adhered deposit has reached a number determined in advance and in a case of non-image formation.

(((6)))

(204) The charging system according to (((1))), further comprising: a detection unit that detects an electrical resistance between the charging member and the image holding body, wherein the processor is configured to: cause the removing member to remove the adhered deposit adhered to the charging member only for the removal time by moving the removing member arranged at the separation position to the contact position after the electrical resistance from previous removal of the adhered deposit has increased by an amount determined in advance.

(((7)))

(205) The charging system according to (((1))) or (((6))), wherein the processor is configured to: move the removing member arranged at the separation position to the contact position after an increased amount of an electrical resistance from previous removal of the adhered deposit has reached a threshold determined in advance and in a case of non-image formation.

(((8)))

(206) The charging system according to (((6))) or (((7))), wherein the processor is configured to: derive a difference in the electrical resistance before and after removal of the adhered deposit; and make the next removal time long in a case where the difference in the electrical resistance is small, compared to a case where the difference in the electrical resistance is large.

((9))

(207) An image forming system comprising: the charging system according to any one of ((1)) to ((8)); an image holding body that is charged by the charging system and on which an image is formed; and a transfer device that transfers the image formed on the image holding body to a recording medium.

(208) In the embodiments above, the term “processor” refers to hardware in a broad sense. Examples of the processor include general processors (e.g., CPU: Central Processing Unit) and dedicated processors (e.g., GPU: Graphics Processing Unit, ASIC: Application Specific Integrated Circuit, FPGA: Field Programmable Gate Array, and programmable logic device). In the embodiments above, the term “processor” is broad enough to encompass one processor or plural processors in collaboration which are located physically apart from each other but may work cooperatively. The order of operations of the processor is not limited to one described in the embodiments above, and may be changed.

(209) The foregoing description of the exemplary embodiments of the present invention has been provided for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Obviously, many modifications and variations will be apparent to practitioners skilled in the art. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, thereby enabling others skilled in the art to understand the invention for various embodiments and with the various modifications as are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the following claims and their equivalents.

Claims

1. A charging system comprising: a charging member that rotates while following a rotating image holding body and that charges the image holding body; a removing member that rotates while following the rotating charging member in a state of being arranged at a contact position in contact with the charging member and that removes an adhered deposit adhered to the charging member; a moving member that moves the removing member to a separation position separated from the charging member and the contact position; and at least one processor, wherein the processor is configured to: cause the removing member to remove the adhered deposit adhered to the charging member only for a removal time by controlling the moving member to move the removing member arranged at the separation position to the contact position at a time determined in advance, and cause the removing member to remove the adhered deposit adhered to the charging member only for the removal time by moving the removing member arranged at the separation position to the contact position after the number of images formed on the image holding body from previous removal of the adhered deposit has reached a number determined in advance.

2. The charging system according to claim 1, wherein the processor is configured to: move the removing member arranged at the separation position to the contact position after the number of images from previous removal of the adhered deposit has reached a number determined in advance and in a case of non-image formation.

3. An image forming system comprising: the charging system according to claim 2; an image holding body that is charged by the charging system and on which an image is formed; and a transfer device that transfers the image formed on the image holding body to a recording medium.

4. An image forming system comprising: the charging system according to claim 1; an image holding body that is charged by the charging system and on which an image is formed; and a transfer device that transfers the image formed on the image holding body to a recording medium.

5. A charging system comprising: a charging member that rotates while following a rotating image holding body and that charges the image holding body; a removing member that rotates while following the rotating charging member in a state of being arranged at a contact position in contact

with the charging member and that removes an adhered deposit adhered to the charging member; a moving member that moves the removing member to a separation position separated from the charging member and the contact position; and at least one processor, wherein the processor is configured to: cause the removing member to remove the adhered deposit adhered to the charging member only for a removal time by controlling the moving member to move the removing member arranged at the separation position to the contact position at a time determined in advance, and cause the removing member to remove the adhered deposit adhered to the charging member only for the removal time by moving the removing member arranged at the separation position to the contact position after the number of cycles of the image holding body from previous removal of the adhered deposit has reached a number determined in advance.

6. The charging system according to claim 5, wherein the processor is configured to: move the removing member arranged at the separation position to the contact position after the number of cycles from previous removal of the adhered deposit has reached a number determined in advance and in a case of non-image formation.

7. An image forming system comprising: the charging system according to claim 6; an image holding body that is charged by the charging system and on which an image is formed; and a transfer device that transfers the image formed on the image holding body to a recording medium.

8. An image forming system comprising: the charging system according to claim 5; an image holding body that is charged by the charging system and on which an image is formed; and a transfer device that transfers the image formed on the image holding body to a recording medium.

9. A charging system comprising: a charging member that rotates while following a rotating image holding body and that charges the image holding body; a removing member that rotates while following the rotating charging member in a state of being arranged at a contact position in contact with the charging member and that removes an adhered deposit adhered to the charging member; a moving member that moves the removing member to a separation position separated from the charging member and the contact position; at least one processor; and a detection unit that detects an electrical resistance between the charging member and the image holding body, wherein the processor is configured to: cause the removing member to remove the adhered deposit adhered to the charging member only for a removal time by controlling the moving member to move the removing member arranged at the separation position to the contact position at a time determined in advance, and cause the removing member to remove the adhered deposit adhered to the charging member only for the removal time by moving the removing member arranged at the separation position to the contact position after the electrical resistance from previous removal of the adhered deposit has increased by an amount determined in advance.

10. The charging system according to claim 9, wherein the processor is configured to: move the removing member arranged at the separation position to the contact position after an increased amount of an electrical resistance from previous removal of the adhered deposit has reached a threshold determined in advance and in a case of non-image formation.

11. An image forming system comprising: the charging system according to claim 10; an image holding body that is charged by the charging system and on which an image is formed; and a transfer device that transfers the image formed on the image holding body to a recording medium.

12. The charging system according to claim 9, wherein the processor is configured to: derive a difference in the electrical resistance before and after removal of the adhered deposit; and make the next removal time long in a case where the difference in the electrical resistance is small, compared to a case where the difference in the electrical resistance is large.

13. An image forming system comprising: the charging system according to claim 12; an image holding body that is charged by the charging system and on which an image is formed; and a transfer device that transfers the image formed on the image holding body to a recording medium.

14. An image forming system comprising: the charging system according to claim 9; an image

holding body that is charged by the charging system and on which an image is formed; and a transfer device that transfers the image formed on the image holding body to a recording medium.
