

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411873
Kind Code	B1
Date of Patent	September 09, 2025
Inventor(s)	Tuteja; Deepali et al.

Aggregating data ingested from disparate sources for processing using machine learning models

Abstract

Presented herein are systems and methods for aggregating data from disparate sources to output information. A computing system may transform a first plurality of datasets of a plurality of data sources by converting a first format of the corresponding data source for each of the first plurality of datasets to generate a second plurality of datasets in a second format of the computing system. The computing system may identify, from the second plurality of datasets, a subset of datasets using a feature selected for evaluation of a utility of the feature. The computing system may apply a machine learning model configured for the selected feature to the subset of datasets to generate an output that measures a likelihood of usefulness. The computing system may cause a visualization of the output for the feature to be displayed for presentation on a dashboard interface based on a template configured for the feature.

Inventors: Tuteja; Deepali (Coppell, TX), Wali; Girish (Flower Mound, TX), Arulraj; David Anandaraj (Mason, OH)

Applicant: CITIBANK, N.A. (New York, NY)

Family ID: 90365518

Assignee: CITIBANK, N.A. (New York, NY)

Appl. No.: 19/215019

Filed: May 21, 2025

Related U.S. Application Data

continuation parent-doc US 18123179 20230317 US 12314289 child-doc US 19215019

Publication Classification

Int. Cl.: G06F16/28 (20190101); G06F16/21 (20190101); G06F16/25 (20190101)

U.S. Cl.:

CPC G06F16/287 (20190101); G06F16/213 (20190101); G06F16/258 (20190101);

Field of Classification Search

CPC: G06F (16/287); G06F (16/258); G06F (16/213)

USPC: 707/737

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5963948	12/1998	Shilcrat	N/A	N/A
6489968	12/2001	Ortega et al.	N/A	N/A
9779147	12/2016	Sherman et al.	N/A	N/A
10748100	12/2019	Boroumand et al.	N/A	N/A
10789526	12/2019	Wilson et al.	N/A	N/A
11187546	12/2020	Rolf et al.	N/A	N/A
11232383	12/2021	Burns et al.	N/A	N/A
11436284	12/2021	Merritt	N/A	G06F 16/252
11526480	12/2021	Rolf et al.	N/A	N/A
2002/0130907	12/2001	Chi et al.	N/A	N/A
2004/0122803	12/2003	Dom et al.	N/A	N/A
2011/0169833	12/2010	Basak	N/A	N/A
2011/0184945	12/2010	Das et al.	N/A	N/A
2012/0131460	12/2011	Coyle-Gilchrist	N/A	N/A
2015/0142796	12/2014	Floreskul et al.	N/A	N/A
2016/0117602	12/2015	Hassanzadeh et al.	N/A	N/A
2017/0060989	12/2016	Shinkuma et al.	N/A	N/A
2018/0224293	12/2017	Xu et al.	N/A	N/A
2018/0302300	12/2017	Moeller-Bertram	N/A	H04L 41/16
2019/0287018	12/2018	Coupe et al.	N/A	N/A
2019/0342194	12/2018	Mermoud	N/A	G06N 20/20
2021/0064595	12/2020	Lee et al.	N/A	N/A
2021/0342723	12/2020	Rao	N/A	G06Q 40/12
2021/0374866	12/2020	Garg et al.	N/A	N/A
2021/0390395	12/2020	Ait-Mokhtar et al.	N/A	N/A
2022/0035775	12/2021	Sriharsha	N/A	G06F 18/2115
2022/0053011	12/2021	Rao	N/A	G06F 21/577
2022/0171971	12/2021	Guzik	N/A	G06F 18/214
2022/0292085	12/2021	Shahriar et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2016/049799	12/2015	WO	N/A

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present application claims the benefit of and priority to under 35 U.S.C. § 120 as a continuation of U.S. application Ser. No. 18/123,179, filed Mar. 17, 2023, and titled “AGGREGATING DATA INGESTED FROM DISPARATE SOURCES FOR PROCESSING USING MACHINE LEARNING MODELS,” which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(1) This application generally relates to managing databases in networked environments. In particular, the present application relates to aggregating data ingested from disparate sources for centralized processing using machine learning (ML) models.

BACKGROUND

(2) In a computer networked environment, various processes, applications, or services running on servers, clients, and other computing devices may produce an immense amount of data. The data from these sources may be communicated over the network for storage across a multitude of databases. Each database may be designated for storing and maintaining data for a single or a subset of processes, even within an application or service. Furthermore, each database may arrange and maintain pieces of this data in accordance with the specifications of the database, independently of other databases. Because the data is stored across multiple databases each with its own specifications, a network administrator may have to access each individual database to gain any visibility into a portion of processes in the network. As a result, the network administrator may be left with a myopic view of the overall network, as it may be difficult for the administrator to obtain insight into multiple aspects of applications accessed through the network from accessing individual databases. This issue may be exacerbated with the immense quantity of data stored across a myriad of different databases. Due to this difficulty in accessing data across the myriad of databases, any problems or issues affecting the performance of the processes, applications, or services accessed through the network may remain undiagnosed and unaddressed.

SUMMARY

(3) Disclosed herein are systems and methods for aggregating data from disparate sources to process and output information using machine learning (ML) models. Through a network environment (e.g., an enterprise including data center, branch offices, and remote users), end-users on client devices may access applications hosted on a multitude of servers. In this environment, the processes of one application may affect or be related to the processes of other applications within the network. In connection with running processes of the applications, the servers may produce vast quantities of data. The servers may provide the produced data for storage across a variety of databases. Even for a single application, the servers may store the data on different databases depending on the type of operation carried out for the application. Each database may store and maintain the data in accordance with its own different or disparate specifications, such as those for arrangement, formatting, and content, among others.

(4) A user may view the data from these databases for further analysis and diagnosis in an attempt to gain insight into the operations of the applications or servers across the network environment. Because the data for a particular application or set of processes is stored in different databases, the user may have to resort to accessing individual databases to retrieve the data maintained therein. For instance, a network administrator may have to access a specific server for a certain application

to obtain performance-related metrics for the application. Expanding this to metrics for applications accessible through the network, the user may have to manually retrieve the data from a myriad of databases associated with different operations or applications.

(5) As a consequence, it may be very difficult for the user to gather holistic information across multiple applications or servers within the network environment (e.g., across an enterprise), resulting in the user having to spend enormous tedious and manual efforts to fetch the data from different databases. Even when the data is collected, the data may not be ready for immediate use, because the retrieved data may be stored in a different manner using particular formatting and specifics. Due to the inability to access data across multiple databases, any issues or problems affecting performance across multiple applications or servers within the network may remain undetected or unresolved. These issues may be exacerbated by the fact that while processes of one application may affect the processes of another or the same application, the data stored across multiple databases may not reflect these relationships.

(6) To address these and other technical problems, a service may aggregate data from multiple data sources of the network environment using machine learning (ML) models in order to output information. The server may establish and maintain a set of ML models to provide various outputs regarding the data of the environment, such as application function, application deployment, risk assessment, or project key performance indicators, among others. The ML models may include models trained in accordance with supervised learning (e.g., an artificial neural network (ANN), decision tree, regression model, Bayesian classifier, or support vector machine (SVM)) and models trained in accordance with unsupervised learning (e.g., clustering models), among others.

(7) The service may access multiple databases to ingest the data therein over a sampling period. With the aggregation of the data, the service may transform the data for input into one of the ML models. As part of the transformation, the service may convert the formatting of the data from the original of the data source to a formatting compatible for inputting into one of the ML models. The service may also automatically perform correction and augmentation of the data from other sources. The service may generate category tags for each piece of data based on the contents therein, with each category tag for one or more of the ML models. The service may group or segment the data by category tags for storage prior to input. The groups of data may be from multiple data sources and in a format compatible for input into one of the ML models maintained by the service.

(8) For a given group of transformed data, the service may select a ML model from the set to apply. The selection may be based on the category tag associated with the group. For instance, the service may maintain one ML model to process application data (e.g., with application process category tags) and another ML model to process financial data (e.g., with financial transaction category tags). With the selection, the service may feed the group of data as input into the ML model and process the data in accordance with the weights of the ML model to produce an output. Under learning mode, the service may use the output to further train the ML model, for example, by updating the weights of the model using a loss between the produced output and the expected output. The service may use data from previous sampling periods as part of training and validation to refine the ML model.

(9) Under runtime mode, the service may generate a visualization of the output from the ML model using a template for the type of output. The template may define the visualization of information as identified in the output from the ML model for fast and easy comprehension by the user viewing the visualization. The visualization may be in the form of a bar graph, pie chart, histogram, or Venn diagram, other graphic for presenting insights and analytics for various operations and applications in the network environment. With the visualizations, the user may be able quickly assess and pinpoint any problems or potential risks affecting the performance of applications or processes on servers across the network.

(10) In this manner, the service may provide for an automated data analysis to reduce the amount of

time and effort spent by users in attempting to manually track down, fetch, and evaluate data. Since the data originally stored across multiple databases can be retrieved, transformed, and processed by the service to provide outputs regarding the data, any issues with applications or processes whose data is stored across these databases can now be detected. Combined with the visualization of the output from the ML models using templates, a user may be able to readily and quickly assess any such problems or risks in the network. Furthermore, with the use of data from prior sampling periods to train and update the ML models, the service may be able to provide more accurate and refined outputs for the data retrieved from these sources. As such, problems or risks affecting the performance of applications or processes on servers across the network (e.g., across an enterprise) may be pinpointed and addressed. This may also improve the overall performance of the servers and client devices in the network, for instance, by reducing the computer and network resources tied up due to previously undetectable issues.

(11) Aspects of present disclosure are directed to systems, methods, and non-transitory computer readable media for aggregating data from disparate sources to output information. A computer system may maintain a plurality of machine learning (ML) models configured for evaluating a plurality of feature. The computing system may transform a first plurality of datasets of a plurality of data sources over a first time period by converting a first format of the corresponding data source for each of the first plurality of datasets to generate a second plurality of datasets in a second format of the computing system and configured for input to one of the plurality of ML models. The computing system may identify from the second plurality of datasets, a subset of datasets using a feature selected from the plurality of features for evaluation of a utility of the feature. The computing system may apply an ML model of the plurality of ML models configured for the selected feature to the subset of datasets to generate an output that measures a likelihood of usefulness. The ML model may be trained using a third plurality of datasets for the feature from the plurality of data sources over a second time period. The computing system may cause a visualization of the output for the feature to be displayed for presentation on a dashboard interface based on a template configured for the feature.

(12) In one embodiment, the computing system may receive, via the dashboard interface, a selection of a plurality of categories for the plurality of features to be evaluated. The computing system may generate a tag identifying a category of the plurality of categories for each dataset of the second plurality of datasets. The computing system may identify the subset of datasets using the tag identifying the category of each dataset of the second plurality of datasets.

(13) In another embodiment, the computing system may determine that more data is to be added to the subset of datasets for evaluating the utility of the feature. The computing system may retrieve a second subset of data from the second plurality of datasets to supplement the subset of datasets.

(14) In yet another embodiment, the computing system may retrieve a fourth plurality of datasets from the plurality of data sources over a third time period. The computing system may identify a subset of ML models from the plurality of ML models corresponding to a subset of features from the plurality of features present in the fourth plurality of datasets. The computing system may re-train the subset of the plurality of ML models using the fourth plurality of datasets.

(15) In yet another embodiment, the computing system may generate from the second plurality of datasets a plurality of subsets of data corresponding to the plurality of ML models for evaluating the corresponding plurality of features. The computing system may identify the subset from the plurality of subsets based on the feature selected from the plurality of features.

(16) In yet another embodiment, the computing system may receive, via the dashboard interface, a selection of the feature from the plurality of features to be evaluated for utility. The computing system may select, from the plurality of ML models, the ML model to be applied to the subset of datasets based on the selection of the feature.

(17) In yet another embodiment, the computing system may retrieve the first plurality of datasets from the plurality of data sources for one or more applications over the first time period. Each of

the first plurality of datasets may identify at least one of a function type, a usage metric, a security risk factor, or a system criticality measure. The computing system may identify, from the second plurality of datasets transformed from the first plurality of datasets, a second subset of datasets and a third subset of datasets for evaluation of the an application of the one or more applications. The computing system may train the ML model configured for evaluating the one or more applications using the second subset of dataset. The computing system may validate the ML model using the third subset of datasets.

(18) In yet another embodiment, the computing system may apply the ML model to the subset of datasets to generate the output to identify whether the application is deprecated from use. The computing system may cause the visualization of the output for the identification of whether application is deprecated. In yet another embodiment, the computing system may maintain the plurality of ML models comprising a first subset of ML models trained in accordance with supervised learning and a second subset of ML models trained in accordance with unsupervised learning. In yet another embodiment, the computing system may identify, from a plurality of templates corresponding to the plurality of features, a template corresponding to the feature to use for generating the visualization of the output.

(19) It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the embodiments described herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings constitute a part of this specification, illustrate an embodiment, and together with the specification, explain the subject matter of the disclosure.

(2) FIG. 1 depicts a block diagram of a platform for aggregating and visualizing data from disparate sources in accordance with an illustrative embodiment;

(3) FIG. 2 depicts a block diagram of a system for aggregating data from disparate sources to output information using machine learning (ML) models in accordance with an illustrative embodiment;

(4) FIG. 3 depicts a block diagram of a system for aggregating data from disparate sources in accordance with an illustrative embodiment;

(5) FIG. 4 depicts a block diagram of a system for training ML models using aggregated data in accordance with an illustrative embodiment;

(6) FIG. 5 depicts a block diagram of a system for processing aggregated data using ML models for output in accordance with an illustrative embodiment;

(7) FIG. 6 depicts a flow diagram of a method of aggregating data from disparate sources to output information using ML models in accordance with an illustrative embodiment;

(8) FIGS. 7A-C depict screenshots of information on processes and application mapping presented on a dashboard interface in accordance with an illustrative embodiment;

(9) FIGS. 8A-C depict screenshots of information characterizing applications generated presented on a dashboard interface in accordance with an illustrative embodiment;

(10) FIGS. 9A-E depict screenshots of information of risk factors from application processes presented on a dashboard interface in accordance with an illustrative embodiment; and

(11) FIGS. 10A-D depict a flow diagram of a use case for aggregate data related to applications and outputting information on application commission using machine learning (ML) models in accordance with an illustrative embodiment.

DETAILED DESCRIPTION

(12) Reference will now be made to the embodiments illustrated in the drawings, and specific

language will be used here to describe the same. It will nevertheless be understood that no limitation of the scope of the disclosure is thereby intended. Alterations and further modifications of the features illustrated here, as well as additional applications of the principles as illustrated here, which would occur to a person skilled in the relevant art and having possession of this disclosure, are to be considered within the scope of the disclosure.

(13) The present disclosure is directed to systems and methods for aggregating data from multiple data sources of the network environment to output information using ML models. The server may establish and maintain a set of ML models to provide various outputs regarding the data of the environment. The service may access multiple databases to perform ingestion of the data therein over a sampling period for the applications and processes of the network environment. With the aggregation of the data, the service may transform the data to make the data compatible for input into one of the ML models. For a given group of transformed data, the service may select a ML model from the set to apply. With the selection, the service may feed the group of data as input into the ML model and process the data in accordance with the weights of the ML model to produce an output. Under runtime mode, the service may generate a visualization of the output from the ML model using a template for the type of output. The visualization may be used to present insights and analytics for various operations and applications in the network environment.

(14) FIG. 1 depicts a block diagram of a platform **100** for aggregating and visualizing data from disparate sources. The platform **100** may carry out or include a data pipeline **105**, a model pipeline **110**, and a data visualization **115**, among others. In the data pipeline **105**, the platform **100** may access data sources for retrieval of various pieces of data **120**. In the depicted example, the data may include application function, end-user computing (EUC), corrective action plan (CAP), matters requiring attention (MRA), matters requiring immediate attention (MRIA), trading service (TS), and other data repositories, among others. With the retrieval, the platform **100** may perform data ingestion to store on a database **125**. The platform **100** may perform a data transformation as part of the data ingestion **130**. In transforming, the platform **100** may scan data points **135**, reformat and correct the data **140**, generate category tags **145**, and segment data based on models **150**, among others.

(15) Continuing on, in the model pipeline **110**, the platform **100** may maintain a set of ML models, including one subset of models established in accordance with supervised learning **155** and another subset of models established in accordance with unsupervised learning **160**. Based on the segment to which the data is assigned, the platform **100** may select one of the ML models to apply to the data to produce an output. Under training mode, the platform **100** may use the output to train and update the weights of the models. Under evaluation or runtime mode, the platform **100** may further use the output to provide to the end user. Under data visualization **115**, the platform **100** may use the output to generate visualizations to present on a dashboard interface. The generation of the visualization may be in accordance with a template for the type of output, such as delivery monitoring, decommissioning, application landscape, process landscape, application and function lifecycle, deployment index, project delivery monitoring, cost monitoring, risk assessment, governance strategies, and project key performance indicator (KPI), among others.

(16) FIG. 2 depicts a block diagram of a system **200** for aggregating data from disparate sources to output information using ML models. The system **200** may include at least one data processing system **202** (sometimes referred herein generally as a computing system or a service) and a set of data sources **204A-N** (hereinafter generally referred to data sources **204**), among others, communicatively coupled with one or more networks **206**. The data processing system **202** may include at least one data aggregator **208**, at least one data transformer **210**, at least one tag generator **212**, at least one feature evaluator **214**, at least one model manager **216**, at least one model applier **218**, at least one interface handler **220**, at least one output visualizer **222**, and a set of evaluation models **224A-N** (hereinafter generally referred to as evaluation models **224**), among others. The data processing system **202** may provide at least one user interface **226**, among others.

The data processing system **202** may include or may have accessibility to at least one data storage **228**.

(17) Various hardware and software components of one or more public or private networks **206** may interconnect the various components of the system **200**. Non-limiting examples of such networks may include Local Area Network (LAN), Wireless Local Area Network (WLAN), Metropolitan Area Network (MAN), Wide Area Network (WAN), and the Internet. The communication over the network may be performed in accordance with various communication protocols, such as Transmission Control Protocol and Internet Protocol (TCP/IP), User Datagram Protocol (UDP), and IEEE communication protocols, among others.

(18) The data processing system **202** may be any computing device comprising one or more processors coupled with memory and software and capable of performing the various processes and tasks described herein. The data processing system **202** may be in communication with the data sources **204**, among others via the network **206**. Although shown as a single component, the data processing system **202** may include any number of computing devices. For instance, the data aggregator **208**, the data transformer **210**, the tag generator **212**, the feature evaluator **214**, the model manager **216**, the model applier **218**, the interface handler **220**, and the output visualizer **222** may be executed across one or more computing systems **202**.

(19) Within the data processing system **202**, the data aggregator **208** may retrieve data from one or more of the data sources **204**. The data transformer **210** may perform pre-processing on the retrieved data. The tag generator **212** may generate tags identifying topic categories for data. The feature evaluator **214** may group the data using the tags identifying the categories. The model manager **216** may train, establish, and maintain the evaluation models **224**. The model applier **218** may feed and process the data using at least one of the evaluation models **224**. The interface handler **220** may manage inputs and output via the user interface **226**. The output visualizer **222** may generate visualization using the output from the evaluation models **224**. The data source **228** may store and maintain data for use by the components of the data processing system **202**.

(20) Each data source **204** may store and maintain various datasets associated with servers, client devices, and other computing devices in a network environment (e.g., the networks **206**). In some embodiments, the network environment may correspond to an enterprise network for a group of end-users including at least one data center, one or more branch offices, and remote users. The data source **204** may include a database management system (DBMS) to arrange and organize the data maintained thereon. The data on the data source **204** may be produced from a multitude of applications and processes accessible through the network environment. The applications may be an online banking application, a securities trading platform, a word processor, a spreadsheet program, a multimedia player, a video game, or a software development kit, among others. For instance, the data source **204** may store and maintain a transaction log identifying communications exchanged over the network environment, such as between end-user client devices and the servers. Upon production, the servers or end-user client devices may store and maintain the data on the data source **204**. The data source **204** may store and maintain the data in accordance with its own specifications, such as formatting and contents of the data. The data maintained on the data source **204** may be accessed by the data processing system **202**.

(21) FIG. 3 depicts a block diagram of a system **300** for aggregating data from disparate sources. The system **300** may include at least one data processing system **302** and one or more data sources **304A-N** (hereinafter generally referred to as data sources **304**), communicatively coupled with one another via at least one network **306**. The data processing system **302** may include at least one data aggregator **308**, at least one transformer **310**, at least one tag generator **312**, at least one interface handler **320**, and at least one data storage **328**, among others. The data processing system **302** may provide at least one user interface **326**. Embodiments may comprise additional or alternative components or omit certain components from those of FIG. 3 and still fall within the scope of this disclosure. Various hardware and software components of one or more public or private networks

306 may interconnect the various components of the system **300**. Each component in system **300** (such as the data processing system **302** and its subcomponents and the one or more data sources **304**) may be any computing device comprising one or more processors coupled with memory and software and capable of performing the various processes and tasks described herein.

(22) Each data source **304** may store and maintain one or more datasets **330A-1** to **330N-X** (hereinafter generally referred to datasets **330**). The data source **304** may accept, obtain, or otherwise receive the datasets **330** from one or more servers or client devices in a network environment. Each data source **304** may store and maintain the datasets **330** for one or more applications or processes accessible via the network environment. For instance, the first data source **304A** may store datasets **330** related to an account balance check operation of an online banking application, whereas the second data source **304B** may store datasets **330** associated with an institutional risk management platform. In another example, one or more of the data sources **304** may store and maintain datasets **330** such as a function type, a usage metric, a security risk factor, or a criticality indicator, among others.

(23) The datasets **330** may be stored and maintained in accordance with the specification of the data source **304**. The specifications may include, for example, a formatting and contents for the datasets **330**. The formatting may identify, specify, or otherwise define a structure of the datasets **330** stored on the data source **304**. For instance, the formatting may define a file format or database model for storing and arranging the datasets **330** in the data source **304**. The contents may identify, specify, or otherwise define a type of data for the datasets **330** stored on the data source **304**. For example, the specified content may define types of fields (sometimes referred herein as attribute or key) and corresponding values in the datasets **330**. The specifications for the dataset **330** in one data source **304** may differ from the specifications (e.g., at least one of formatting or content type) for the dataset **330** of another data source **304**. For instance, the first data source **304A** may have specifications that datasets **330** are to be in the form of field-value pairs for customer relationship management, whereas the second data source **304B** may have specifications that datasets **330** may be in the form of a transaction log for invocation of operations of a particular application.

(24) The data aggregator **308** executing on the data processing system **302** may access each data source **304** to obtain, identify, or otherwise retrieve the datasets **330** from the data source **304**. In some embodiments, the data aggregator **308** may accept or receive the datasets **330** sent from each data source **304**. The datasets **330** retrieved by the data aggregator **308** may correspond to datasets **330** generated or stored by the data source **304** over a period of time. The period of time may correspond to a sampling window over which the datasets **330** were generated at each data source **304**. The period of time may span any amount of time, for example, from a 5 minutes to 2 months since the previous retrieval of the datasets **330** from the data sources **304**. In some embodiments, the data aggregator **308** may instruct, command, or otherwise request the datasets **330** from each data source **304** for the specified period of time. With the retrieval, the data aggregator **308** may store and maintain the datasets **330** retrieved from the data sources **304** in the data storage **328** in the original specifications for the datasets **330**. The data aggregator **308** may also perform initial scanning of the datasets **330** retrieved from the data sources **304**.

(25) With the retrieval, the data transformer **310** executing on the data processing system **302** may perform one or more transformations on the datasets **330**. When received, the datasets **330** may initially be in the original specifications (e.g., formatting and content type) of the data source **304**. For each dataset **330**, the data transformer **310** may change, modify, or otherwise convert the format of the dataset **330** from the original format to at least one format of the data processing system **302** to generate a corresponding new dataset **330'A-X** (hereinafter generally referred to as dataset **330'**). In some embodiments, the data transformer **310** may generate the new dataset **330'** using multiple datasets **330** from one or more data sources **304**. The format for the new dataset **330'** may be for entry, feeding, or input to one of the evaluation models of the data processing system **302**. The format for the new dataset **330'** may differ from the original format of the dataset **330**. In

some embodiments, the data transformer **310** may select or identify the format from a set of formats to convert to based on any number of factors, such as the data source **304** or the contents of the original datasets **330**, among others. For example, the data transformer **310** may identify the data source **304** as associated with application log data, and may select the format for processing the application log data at the data processing system **302**.

(26) Continuing on, the data transformer **310** may perform data correction on the datasets **330'** (or datasets **330**). With the conversion, the dataset **330'** may include one or more fields for which there are no values from the original corresponding dataset **330**. For each dataset **330'**, the data transformer **310** may identify or determine whether more data is to be added to the dataset **330'**. If there are no missing values in the dataset **330'**, the data transformer **310** may determine that no supplemental data is to be added to the dataset **330'**. With the determination, the data transformer **310** may maintain the dataset **330'** as is. On the contrary, if there is any portion of the dataset **330'** with missing values, the data transformer **310** may determine that more data is to be added to the dataset **330'**. The data transformer **310** may continue to traverse through the datasets **330'** to determine whether more data is to be added.

(27) With the determination that more data is to be added, the data transformer **310** may generate, identify, or retrieve supplemental data to add to the dataset **330'**. In some embodiments, the data transformer **310** may identify associated datasets **330'** for the supplemental data. For example, the dataset **330'** with the missing values may be associated with a particular application. In this case, the data transformer **310** may retrieve or identify other datasets **330'** also associated with the application to retrieve the supplemental data. With the retrieval, the data transformer **310** may add the supplemental data to the dataset **330'**. In some embodiments, the data transformer **310** may determine or generate the supplemental data using other values in the dataset **330'**. For example, the dataset **330'** may have missing values for fields that can be derived from values of other fields in the same dataset **330'**. Based on the other values, the data transformer **310** may generate the supplemental data to insert into the dataset **330'**. In some embodiments, the data transformer **310** may access or search a knowledge base for the supplemental data to add to the dataset **330'**. The knowledge base may be constructed using information from the network environment (e.g., the enterprise network) besides the data sources **304**, and may include information about the network environment.

(28) The tag generator **312** executing on the data processing system **302** may determine or generate at least one tag **332A-X** (hereinafter generally referred to tag **332**) for each dataset **330'** (or dataset **330**). The tag **332** may define or identify a topic category of the associated dataset **330'**. The topic categories may include, for example, delivery monitoring, decommissioning, application landscape, process landscape, application and function lifecycle, deployment index, project delivery monitoring, cost monitoring, risk assessment, governance strategies, and project key performance indicator (KPI), among others. The topic categories may correspond to features to be evaluated using one or more ML models for outputting information on the datasets **330'**. The tag **332** may be generated and maintained using one or more data structures, such as an array, a linked list, a tree, a heap, or a matrix, among others.

(29) To identify the topic category, the tag generator **312** may process or parse the fields or values within the dataset **330'** using natural language processing (NLP) algorithms, such as automated summarization, text classification, or information extraction, among others. In some embodiments, the tag generator **312** may generate the tag **332** based on the data source **304** from which the dataset **330** is retrieved. For example, the tag generator **312** may identify the topic category for the dataset **330'** as for application-related metrics based on an identification of the data source **304** as storing data for one or more applications in the network environment. With the identification, the tag generator **312** may generate the tag **332** to identify the topic category for the dataset **330'**.

(30) In some embodiments, the tag generator **312** may identify or select the topic category from a set of candidate topic categories for the datasets **330'** retrieved from the data sources **304**. The tag

generator **312** in conjunction with the interface handler **320** may retrieve, identify, or otherwise receive the set of candidate topic categories via the user interface **326**. The interface handler **320** may provide the user interface **326** for presentation on a display coupled with the data processing system **302** or a computing device (e.g., administrator's computing device) in communication with the data processing system **302**. The user interface **326** may include one or more user interface elements for defining the candidate topic categories. Upon entry or input via the user interface **326** (e.g., by the user), the interface handler **320** may retrieve or identify the definitions for the topic categories.

(31) With the definitions, the tag generator **312** may compare with the fields and values of each dataset **330'** (or dataset **330**) with the set of candidate topic categories. The comparison may be facilitated using NLP techniques as discussed above. Based on the comparison, the tag generator **312** may identify or select the topic category to use as the tag **332** for the dataset **330'**. For instance, the tag generator **312** may use a knowledge graph to compare the topic category derived from the dataset **330'** with the candidate topic categories to calculate a semantic distance. The tag generator **312** may select the candidate topic category with the closest semantic distance with the derived topic category to use for the tag **332** for the dataset **330'**. In some embodiments, the tag generator **312** may generate or generate a segment corresponding to a group of datasets **330'**. The segment may be defined using the common topic category identified in the tags **332** of the subset of datasets **330'**.

(32) Upon generation, the tag generator **312** may store and maintain the tags **332** along with the datasets **330'** on the data storage **328**. In some embodiments, the tag generator **312** may insert or add the tags **332** to the datasets **330'**. For instance, the tag generator **312** may add the tag **332** as a field-value pair along with other field-value pairs of the associated dataset **330'**. In some embodiments, the tag generator **312** may determine or generate at least one association between the tag **332** and the corresponding dataset **330'** from which the tag **332** was generated. The tag generator **312** may store the association on the data storage **328**. In some embodiments, the tag generator **312** may store the segment corresponding to group of datasets **330'** defined using the common topic category of tags **332** of each dataset **330'** in the group. The tag generator **312** may store and maintain an association between the segment of the datasets **330'** with the tag **332** on the data storage **318**.

(33) FIG. 4 depicts a block diagram of a system **400** for training ML models using aggregated data. The system **400** may include at least one data processing system **402**. The data processing system **402** may include at least one feature evaluator **414**, at least one model manager **416**, at least one model applier **418**, one or more evaluation models **424A-N** (hereinafter generally referred to as evaluation models **424**), and at least one data storage **428**, among others. In the system **400**, the data processing system **402** and its components may be in a training or learning mode to train at least one of the evaluation models **424**. Embodiments may comprise additional or alternative components or omit certain components from those of FIG. 4 and still fall within the scope of this disclosure. Various hardware and software components of one or more public or private networks may interconnect the various components of the system **400**. Each component in system **400** (such as the data processing system **402** and its subcomponents) may be any computing device comprising one or more processors coupled with memory and software and capable of performing the various processes and tasks described herein.

(34) The feature evaluator **414** executing on the data processing system **402** may identify or select a subset of datasets **430''A-X** (hereinafter generally referred to as datasets **430''**) using at least one feature for evaluation using at least one of the evaluation models **424**. The feature may correspond to at least one topic category for the datasets **430''** to be evaluated or analyzed for at least one metric, such as utility, risk level, performance, health, among others. The utility may indicate a degree of usefulness of the feature evaluated. The risk level may correspond to a degree of vulnerabilities or susceptibility to lapses (e.g., security, downtime, failure, or breakdown) from the

feature assessed. The performance may be a metric indicating proper functioning of components of the feature evaluated. The health may correspond to a condition of the features evaluated. The subset of datasets **430''** may be obtained, received, or otherwise retrieved from over a period of time. The period of time may correspond to a sampling window over which the datasets were generated at each data source. The datasets **430''** may be converted into the format compatible for inputting into the evaluation model **424**.

(35) In some embodiments, the feature evaluator **414** may select or identify the subset of datasets **430''** using the at least one tag **432**. The tag **432** may identify the topic category for each associated dataset **430''**. The topic category defined by the tag **432** may correspond to the feature to be evaluated for the metric (e.g., utility or risk level). The feature evaluator **414** may traverse through the set of possible topic categories identified across the tags **432** of the data storage **428** to identify corresponding subsets of datasets **430''**. In some embodiments, the feature evaluator **414** may identify the subset of datasets **430''** using the corresponding period of time to be evaluated for the network environment. In some embodiments, the feature evaluator **414** may produce or generate a segment corresponding to the subset of datasets **430''**. The segment may be defined using the feature or by extension the common topic category identified in the tags **432** of the subset of datasets **430''**. In some embodiments, the feature evaluator **414** may identify the segment corresponding to the subset of datasets **430''** (e.g., previously defined by the tag generator) stored on the data storage **428**.

(36) In conjunction, the model manager **416** executing on the data processing system **402** may initialize, establish, and maintain the set of evaluation models **424**. The set of evaluation models **424** may be for evaluating or analyzing the corresponding set of features. Each evaluation model **424** may correspond to at least one of the topic categories present in the tags **432** of the datasets **430''**. Each evaluation model **424** may be dedicated or otherwise configured to process datasets **430''** of the feature and by extension the associated topic category of the tag **432**. In general, each evaluation model **424** may have: at least one input corresponding to the subset of datasets **430''**, at least one output from processing the input, and a set of parameters (e.g., weights) to process the inputs to generate the output. To train the evaluation model **424**, the model manager **416** may invoke the model applier **418** to apply the identified datasets **430''**.

(37) At least one of the evaluation models **424** may be initialized, trained, or established in accordance with supervised learning. For example, the evaluation model **424** may be an artificial neural network (ANN), decision tree, regression model, Bayesian classifier, or support vector machine (SVM), among others. At least one of the evaluation models **424** may be initialized, trained, or established in accordance with unsupervised learning. For instance, the evaluation model **424** may be a clustering model, such as hierarchical clustering, centroid-based clustering (e.g., k-means), distribution model (e.g., multivariate distribution), or a density-based model (e.g., density-based spatial clustering of applications with noise (DBSCAN)), among others. Other techniques may be used to initialize, train, and establish the evaluation models **424**, such as weakly supervised learning, reinforcement learning, and dimension reduction, among others.

(38) In some embodiments, the model manager **416** in conjunction with the feature evaluator **414** may identify or select the evaluation model **424** from the set of evaluation models **424** to be trained. The selection may be based on the subset of datasets **430''**, the feature to be evaluated, or the topic category identified in the tags **432** of the selected subset, among others. For instance, each evaluation model **424** may be dedicated or configured to process subsets of datasets **430''** for a particular feature or by extension category topic. The model manager **416** may identify the evaluation model **424** to be used to process the identified subset of datasets **430''**. In some embodiments, the model manager **416** may determine whether an evaluation model **424** exists or is otherwise established for the feature. If the evaluation model **424** does not exist, the model manager **416** may create and initialize the evaluation model **424**. For example, the model manager **416** may instantiate the evaluation model **424** for processing the datasets **430''** for the feature to be

evaluated. Otherwise, if the evaluation model **424** does exist, the model manager **416** may use the evaluation model **424** to continue training using the selected subset of datasets **430''**.

(39) In some embodiments, the model manager **416** may select or identify a testing dataset and a validation dataset from the subset of datasets **430''**. The model manager **416** may select, define, or otherwise assign a portion of the subset of datasets **430''** as the testing dataset. In addition, the model manager **416** may select, define, or otherwise assign a remaining portion of the subset of datasets **430''** as the validation dataset. The testing dataset may be used as input to the evaluation model **424** to generate a predicted output and the validation dataset may be used to as the expected output to check the predicted output against. The checking of the expected output form the validation dataset with the predicted output from inputting the testing dataset into the evaluation model **424** may be used to update the parameters of the evaluation model **424**. With the definition of the testing and validation datasets, the model manager **416** may provide or pass datasets **430''** corresponding to the testing dataset to the model applier **418** to apply to the identified evaluation model **424**.

(40) The model applier **418** executing on the data processing system **402** may apply at least one of the evaluation models **424** to the subset of datasets **430''** (e.g., the test dataset). With the selection of the evaluation model **424**, the model applier **418** may feed the subset of datasets **430''** into the inputs of the evaluation model **424**. In feeding, the model applier **418** may process the input dataset **430''** in accordance with the parameters of the evaluation model **424**. From processing with the evaluation model **424**, the model applier **418** may produce or generate at least one output **434** for the input dataset **430''**. The output **434** may correspond to, identify, or otherwise measure a predicted usefulness, risk level, performance metric, health level, among others. For example, for an input dataset **430''** with application-related data, the output **434** may identify a likelihood that a particular feature of the application is deprecated or in current use.

(41) The model applier **418** may apply the parameters of the evaluation model **424** in accordance with the model architecture. For example, when the evaluation model **424** is an artificial neural network, the model applier **418** may process the input dataset **430''** using the kernel weights of the artificial neural network to generate the output **436**. The output may indicate a degree of usefulness, risk, performance, or health for the input dataset **430''**. When the evaluation model **424** is a clustering model, the model applier **418** may identify the output **434** from where the input dataset **430''** is situated within a region of the feature space defined by the clustering model. The region may correspond to a classification for the input dataset **430''** indicating usefulness, risk level, performance metric, or health level, among others.

(42) Using the output **434**, the model manager **416** may calculate, determine, or otherwise generate at least one feedback **436** for the evaluation model **424**. The generation of the feedback **436** may be in accordance with the learning technique used to establish or train the evaluation model **424**. In some embodiments, the model manager **416** may validate the evaluation model **424** using the output **434** and at least a portion of the datasets **430''** (e.g., the validation dataset). When supervised learning is used, the model manager **416** may compare the output **434** from the input dataset **430''** of the test dataset with the expected output. The expected output may be acquired or obtained from the validation dataset. Based on the comparison, the model manager **416** may determine the feedback **436** to indicate an amount of deviation between the predicted output **434** and the expected output. When unsupervised learning is used, the model manager **416** may determine a shift in parameters for the evaluation model **424** to use at the feedback **436**. For instance, for a clustering model, the feedback **436** may indicate the amount that a centroid for a particular classification is to be modified based on the newly fed input datasets **430''**. According to the feedback **436**, the model manager **416** may modify, change, or otherwise update the parameters of the evaluation model **424**.

(43) The model manager **416** may update and re-train the evaluation models **424** any number of times, and repeat the operations discussed above. For example, the model manager **416** in conjunction with the feature evaluator **414** may identify another subset of datasets **430''** for a

feature to be evaluated from another (e.g., subsequent) time period. With the identification, the model manager **416** may select the evaluation model **424** to process the subset of datasets **430**". The model applier **418** may apply the selected evaluation model **424** to the subset of datasets **430**" to generate the output **434**. Using the output **434**, the model manager **416** may determine the feedback **436** with which to update the parameters of the evaluation model **424**. The data processing system **402** may switch between the training mode to retrain and update the evaluation model **424**, and the runtime mode to apply the evaluation models **424** to newly acquired data.

(44) FIG. 5 depicts a block diagram of a system **500** for processing aggregated data using ML models for output. The system **500** may include at least one data processing system **502**. The data processing system **502** may include at least one feature evaluator **514**, at least one model applier **518**, at least one interface handler **520**, at least one output visualizer **522**, one or more evaluation models **524A-N** (hereinafter generally referred to as evaluation models **524**), and at least one data storage **528**, among others. In the system **500**, the data processing system **502** and its components may be in a runtime or evaluation mode to apply at least one of the evaluation models **524** to new incoming data. Embodiments may comprise additional or alternative components or omit certain components from those of FIG. 5 and still fall within the scope of this disclosure. Various hardware and software components of one or more public or private networks may interconnect the various components of the system **500**. Each component in system **500** (such as the data processing system **502** and its subcomponents) may be any computing device comprising one or more processors coupled with memory and software and capable of performing the various processes and tasks described herein.

(45) The interface handler **520** executing on the data processing system **502** may provide the user interface **526** with which to select the feature to be evaluated using at least one of the evaluation models **524**. The interface handler **520** may provide the user interface **526** for presentation on a display coupled with the data processing system **502** or a computing device (e.g., administrator's computing device) in communication with the data processing system **502**. The user interface **526** may include one or more user interface elements (e.g., command button, radio button, check box, slider, or text box) for identifying or selecting the feature (or the topic category) to be evaluated. For instance, the user interface **526** may include a set of user interface elements corresponding to a menu of features from which the user can check or select for analysis.

(46) With the presentation, the interface handler **520** may monitor the user interface **526** for at least one input **538** by the user. The interface handler **520** may use event handlers in the user interface elements of the user interface **526** to monitor. Upon detection of the input **538** on the user interface **526**, the interface handler **520** may obtain, identify, or otherwise receive the selection of the feature to be evaluated. The input **538** may correspond to a user interface on the user interface element of the user interface **526**. The feature may correspond to the user interface element in the user interface **526** on which the input **538** is detected.

(47) The feature evaluator **514** executing on the data processing system **502** may identify or select a subset of datasets **530**"A-X (hereinafter generally referred to as datasets **530**"") using at least one feature for evaluation using at least one of the evaluation models **524**. The feature may correspond to at least one topic category for the datasets **530**" to be evaluated or analyzed for at least one metric, such as utility, risk level, performance, health, among others. The subset of datasets **530**" may be obtained, received, or otherwise retrieved from over a period of time. The period of time may correspond to a sampling window over which the datasets were generated at each data source. The period of time for the datasets **530**" for evaluation may differ from the period of time of datasets that were used to initialize, train, and establish the evaluation models **524**.

(48) In some embodiments, the feature evaluator **514** may select or identify the subset of datasets **530**" using the selection of the feature via the user interface **526**. In some embodiments, the feature evaluator **514** may find, select, or otherwise identify the tag **532** corresponding to the selected feature. The tag **532** may identify the topic category for each associated dataset **530**". The topic

category defined by the tag **532** may correspond to the feature to be evaluated for the metric (e.g., utility or risk level). With the identification, the feature evaluator **514** may select or identify the subset of datasets **530''** using the tag **532** corresponding to the selected feature. In some embodiments, the feature evaluator **514** may identify the segment corresponding to the subset of datasets **530''** (e.g., previously defined by the tag generator) stored on the data storage **528**. The segment may correspond to the datasets **530''** associated with the selected feature.

(49) In conjunction, the feature evaluator **514** may identify or select the evaluation model **524** from the set of evaluation models **524** to be used to process the dataset **530''**. The selection may be based on the subset of datasets **530''**, the feature to be evaluated, or the topic category identified in the tags **532** of the selected subset, among others. For instance, each evaluation model **524** may be dedicated or configured to process subsets of datasets **530''** for the selected feature or by extension category topic. In general, each evaluation model **524** may have: at least one input corresponding to the subset of datasets **530''**, at least one output from processing the input, and a set of parameters (e.g., weights) to process the inputs to generate the output. To train the evaluation model **524**, the feature evaluator **514** may invoke the model applier **518** to apply the identified datasets **530''**.

(50) The model applier **518** executing on the data processing system **502** may apply at least one of the evaluation models **524** to the subset of datasets **530''** identified using the selected feature. With the selection of the evaluation model **524**, the model applier **518** may feed the subset of datasets **530''** into the inputs of the evaluation model **528**. In feeding, the model applier **518** may process the input dataset **530''** in accordance with the parameters of the evaluation model **524**. From processing with the evaluation model **524**, the model applier **518** may produce or generate at least one output **534** for the input dataset **530''**. The output **534** may correspond to, identify, or otherwise measure a predicted usefulness, risk level, performance metric, health level, among others. For example, for an input dataset **530''** with application-related data, the output **534** may identify a likelihood that a particular feature of the application is deprecated or in current use.

(51) The output visualizer **522** executing on the data processing system **502** may render, display, or otherwise present at least one visualization of the output **534** on the user interface **526** using at least one template **540** for the feature. The output visualizer **522** may identify or select the template **540** from a set of templates for the set of potential features and by extension the topic categories for the tags **532**. The selection of the template **540** may be based on the selected feature, the topic categories for the tag **532** associated with the input dataset **530''**, the output **534** from the evaluation model **524**, the evaluation model **524** used to generate the output **534**, among others. Each template **540** may be pre-generated or pre-configured for presenting the information from the output **534**.

(52) In accordance with the template **540**, the output visualizer **522** may create, produce, or otherwise generate the visualization of the output **534**. The template **540** may define or specify a visualization of the information identified in the output **534**. For example, the template **540** may specify the information (e.g., predicted usefulness, risk level, performance metric, or health level) as indicated in the output **534** to be presented in a bar graph, a table, a box plot, a scatter plot, a pie chart, a Venn diagram, histogram, or fan chart, among others. The template **540** may identify one or more user interface elements with which the user can use to drill down or navigate the information for the output **534**. Using the specifications of the template **540**, the output visualizer **522** may generate the visualization of the information as identified in the output **534**. Examples of the visualizations are shown in FIGS. 7A-9E.

(53) In this manner, the data processing system may reduce the amount of time and effort spent by user in trying to manually track down individual data sources to track and fetch data by retrieving datasets originally stored across disparate data sources in the network environment. With the ready retrieval of the datasets, the data processing system may transform the datasets in a manner amenable for processing by evaluation models. The ability to process the datasets for evaluation models can result in uncovering and detecting issues across multiple applications and processes in the network environment. With repeated training of the evaluation models using datasets with

successive sampling periods, the data processing system may be able to provide more accurate and refined output.

(54) Furthermore, the data processing system can also use the templates to produce visualizations for easy digestion via the dashboard information by the users. As such, problems affecting the performance of applications or processes on servers across the network may be quickly and readily pinpointed and addressed. In addition, the insight and information from these visualizations of the output may be used to assess and create a long-term (e.g., 1 to 10 years) strategy for improving performance and enhancing risk management of the overall network environment. The output generated by the data processing system may also improve the overall performance of the servers and client devices in the network, for instance, by reducing the computer and network resources tied up due to previously undetectable issues.

(55) FIG. 6 depicts a flow diagram of a method **600** of aggregating data from disparate sources to output information using ML models. Embodiments may include additional, fewer, or different operations from those described in the method **600**. The method **600** may be performed by a service (e.g., a data processing system) executing machine-readable software code, though it should be appreciated that the various operations may be performed by one or more computing devices and/or processors.

(56) At step **605**, a service may retrieve datasets from data sources. Each of the data sources may store and maintain datasets, in accordance to the specification of the data source. The specifications may include a format and contents for datasets to be stored and maintained at the data source. The data for the datasets may be generated by various applications, processes, and computing devices in the computing network (e.g., enterprise network). The service may retrieve the datasets from these data sources over a period of time.

(57) At step **610**, the service may transform the datasets retrieved from the data sources. Upon retrieval from the data source, the service may transform each dataset from the original formatting to a formatting for application to one of a set of machine learning models. In addition, the service may perform data correction or augmentation for missing data in the converted datasets. At step **615**, the service may generate tags for each datasets using the contents (e.g., fields or values) of the dataset. The tag may identify a topic category for the dataset. At step **620**, the service may segment the datasets by the topic categories as identified in the tags.

(58) At step **625**, the service may select a machine learning model for evaluating the dataset. The service may maintain a set of machine learning models. Each model may be dedicated to or configured to process datasets for certain topic categories. The service may select the model based on the feature or topic category to be evaluated. At step **630**, the service may apply the selected model to the segment of datasets identified using the tags. In applying, the service may process the segment of datasets in accordance with the parameters of the machine learning model to generate an output.

(59) At step **635**, the service may identify a template with which to generate a visualization of the output from the machine learning model. The template may specify a form for visualizing the information identified in the output from the model. The template may be identified using the feature or topic category analyzed from applying the machine learning model to the segment of dataset. At step **640**, the service may generate the visualization of the output in accordance with the template. With the generation, the service may present the visualization of the information of the output on a dashboard interface.

(60) FIGS. 7A-C depict screenshots of visualizations **700-710** of processes and application mapping presented on a dashboard interface. The visualization **700** may provide a view of level 1 (L1), level 2 (L2), and level 3 (L3) processes in L1, L2, L3 business process taxonomy defined to have a common vocabulary for the classification of business processes that facilitates easier communication, governance, and reporting, helping improve diverse stakeholder alignment and managements in a table view. L1 may correspond to a lifecycle of services provided internally and

externally through the enterprise and may be outside of a line (e.g., a process) and may be unique to a specific function (e.g., addition of a user). L2 may correspond to a logical order of processes directly underpinning the delivery of the L1 and may be not overly specific to a particular function or business or the same as a L1 (e.g., account opening and setup). L3 may correspond to unique and distinct processes needed to complete the L2 process, and may be anything other than a process step that is to connect to a L2 process (e.g., Know Your Customer (KYC) onboarding review). The visualization **705** may provide a view on a number of enterprise and sector applications mapped to distinct processes, among others, in a table view. The visualization **710** may provide the view of total applications which are mapped and not mapped to the process defined to services in a table view.

(61) FIGS. **8A-C** depict screenshots of visualizations **800-810** characterizing applications generated as presented on a dashboard interface. The visualizations **800-810** may identify how the applications can provide recommendations regarding process cycles, leveraging the evaluations models and insights. The visualization **800** may provide a histogram view of multiple technology applications supporting more than business functions for a particular line of and can identify opportunities to optimize as part of target state. The visualization **805** may be a timeline view of a number of applications to be decommissioned, maintained, or updated, among other statistics. The visualization **805** may identify mapping of functions such as (1) customer information collection, (2) customer account review, (3) account set up, and (4) checking creation and delivery along with tags of invest, decommission, or maintain. The visualization **805** may also provide how many applications can be decommissioned over time. The visualization **810** may provide a bar chart view of multiple processes that are supported by more than or equal to ten applications for a particular line or group in the enterprise.

(62) FIGS. **9A-E** depict screenshots of visualizations **900-920** of risk factors from application processes as presented on a dashboard interface. The visualization **900** may be a graph of the forecasting of application decommissions. The visualization **900** may show the forecast of retirement of applicable applications, remediation of application components that are end of life (EOL), remediation of application components that are end of vendor support (EOVS) and other decommissioning or remediation details for the next year. The visualization **905** may be a histogram, or multiple histograms, showing monetary values for retiring various applications. In the visualization **905**, the summary of the application retirement status and the monthly chargeback details for applications that are past due and for applications that would be due within 180 days are visualized with the ingested data.

(63) The visualization **910** may be a summary graph of trends and forecasts for remediating applications. The visualization **910** may provide the end of vendor support remediation projection for application components within a particular sector are depicted along with the projected trend and forecast for the EOVS remediation. The visualization **915** may be a graph of a risk appetite across time. The visualization **915** shows the risk appetite forecast against monthly open end of vendor support (EOVS) components. This chart forecast the risk appetite for the next 12 months and indicates the number of EOVS items that needs to be remediated to mitigate the risk (Risk Appetite: color 1 $\geq 99.4\%$, color 2 between 99.0% and 99.4% and color 3 $< 99.0\%$). The visualization **920** may be a pie chart of component counts for various applications. In the visualization **920**, the pie chart may list the impacted applications and the corresponding component count that are still end of vendor support (EOVS) from December 2015 and not yet remediate.

(64) FIGS. **10A-D** depict a flow diagram of a method **1000** for aggregating data related to applications and outputting information on application commission using ML models. Embodiments may include additional, fewer, or different operations from those described in the method **1000**. The method **1000** may be performed by a service (e.g., a data processing system) executing machine-readable software code, though it should be appreciated that the various

operations may be performed by one or more computing devices and/or processors. Starting from FIG. **10A**, a service may access data from a data repository **1002**. The data repository may include application tech data including information related to application, server, and data center, server costs, and application and service level agreements, among others. In conjunction, moving onto FIG. **10B**, the service may access data from a sector data repository **1004**. The sector data repository may include data for processes with functions and applications with functions from individual sectors **1** through **n**.

(65) Continuing onto FIG. **10C**, the service may aggregate the data from multiple data sources **1006**. The data sources may include from the data repository **1002** or the sector data repository **1004**, as well as from a project tracking system (PTS). The PTS may be a management tool used to create and maintain projects, budgets, forecast and actual in both full time equivalent (FTE), as well as the status and the start or end date for each project. The PTS may also allow managers to track resource allocation. With the aggregation, the service may reformat, structure, cluster, profile, and enrich the aggregated data **1008**. In addition, the service may collect information on existing functions to identify redundancies, risk factors, necessity, criticality, and cost benefits for the enterprise network and customers **1010**. The service may identify components, applications, and functions to be decommissioned in the aggregated data **1012**. The components may be at an end of life (EOL) in which the component vendor has announced that maintenance and extended support is to be terminated. The components may be at an end of vendor support (EOVS) in which the vendor for the component announced that publicly available extended support is to end for a given product version. The service may determine a total number of system inventory items (Sis) impacted **1014**. The SI may identify profiles of applications and may aggregate details from messages, user interfaces, infrastructure or software deployment details, and other information. From the total number, the service may remove SIs which are past the EOL or retired **1016**. The service may then compile a final CSI list **1018**. The service may generate training and validation datasets including a list of CSIs for commissions and a list of functions for decommission **1020** and **1022**.

(66) Referring now to FIG. **10D**, the service may split the data by using the 80% of the list of CSI for decommission as training data **1024** and using the remaining 20% for validation (**1026**). The service may use the training dataset to perform hyper parameter optimization **1028**. The service may use one or more learning models to train, such as a deep learning model, a nearest neighbors model, a decision tree, a radio frequency mode, a gradient boosting machine, or a support vector machine, among others **1030**. The service may perform a feature selection optimization **1032** to derive a cross validation model **1034** and to generate a training model **1036**. The service may use the trained model to generate predicted values **1038** and use the predicted values to evaluate performance **1040**. The service may classify and regress the predicted values to add to the validation dataset.

(67) The foregoing method descriptions and the process flow diagrams are provided merely as illustrative examples and are not intended to require or imply that the steps of the various embodiments must be performed in the order presented. The steps in the foregoing embodiments may be performed in any order. Words such as “then,” “next,” etc. are not intended to limit the order of the steps; these words are simply used to guide the reader through the description of the methods. Although process flow diagrams may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be re-arranged. A process may correspond to a method, a function, a procedure, a subroutine, a subprogram, and the like. When a process corresponds to a function, the process termination may correspond to a return of the function to a calling function or a main function.

(68) The various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the embodiments disclosed herein may be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of

hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present disclosure.

(69) Embodiments implemented in computer software may be implemented in software, firmware, middleware, microcode, hardware description languages, or any combination thereof. A code segment or machine-executable instructions may represent a procedure, a function, a subprogram, a program, a routine, a subroutine, a module, a software package, a class, or any combination of instructions, data structures, or program statements. A code segment may be coupled to another code segment or a hardware circuit by passing and/or receiving information, data, arguments, parameters, or memory contents. Information, arguments, parameters, data, etc. may be passed, forwarded, or transmitted via any suitable means including memory sharing, message passing, token passing, network transmission, etc.

(70) The actual software code or specialized control hardware used to implement these systems and methods is not limiting. Thus, the operation and behavior of the systems and methods were described without reference to the specific software code being understood that software and control hardware can be designed to implement the systems and methods based on the description herein.

(71) When implemented in software, the functions may be stored as one or more instructions or code on a non-transitory computer-readable or processor-readable storage medium. The steps of a method or algorithm disclosed herein may be embodied in a processor-executable software module, which may reside on a computer-readable or processor-readable storage medium. A non-transitory computer-readable or processor-readable media includes both computer storage media and tangible storage media that facilitate transfer of a computer program from one place to another. A non-transitory processor-readable storage media may be any available media that may be accessed by a computer. By way of example, and not limitation, such non-transitory processor-readable media may comprise RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other tangible storage medium that may be used to store desired program code in the form of instructions or data structures and that may be accessed by a computer or processor. Disk and disc, as used herein, include compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk, and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers.

Combinations of the above should also be included within the scope of computer-readable media. Additionally, the operations of a method or algorithm may reside as one or any combination or set of codes and/or instructions on a non-transitory processor-readable medium and/or computer-readable medium, which may be incorporated into a computer program product.

(72) The preceding description of the disclosed embodiments is provided to enable any person skilled in the art to make or use the present disclosure. Various modifications to these embodiments will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments without departing from the spirit or scope of the disclosure. Thus, the present disclosure is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent with the following claims and the principles and novel features disclosed herein.

(73) While various aspects and embodiments have been disclosed, other aspects and embodiments are contemplated. The various aspects and embodiments disclosed are for purposes of illustration and are not intended to be limiting, with the true scope and spirit being indicated by the following claims.

Claims

1. A method of identifying artificial intelligence (AI) models to detect vulnerabilities in network environments, comprising: retrieving, by one or more processors, a first plurality of datasets generated by a plurality of data sources associated with the network environment over a first time period; identifying, by the one or more processors and from the first plurality of datasets, at least one dataset corresponding to a process selected from a plurality of processes; selecting, by the one or more processors and from a plurality of AI models, an AI model based on the process of the plurality of processes, wherein the AI model is trained using a second plurality of datasets for the process over a second time period; applying, by the one or more processors, the AI model to the at least one dataset corresponding to the process; generating, by the one or more processors and based on applying the AI model to the at least one dataset, an output including a risk level indicating a degree of vulnerability of the process to failure; and causing, by the one or more processors, presentation of the output including the risk level indicating the degree of vulnerability of the process to failure via a user interface.
2. The method of claim 1, further comprising: retrieving, by the one or more processors, a third plurality of datasets from the plurality of data sources over a third time period; selecting, by the one or more processors, from the plurality of AI models, a subset of AI models corresponding to a subset of processes from the plurality of processes present in the third plurality of datasets; and training, by the one or more processors, the subset of AI models using at least a portion of the third plurality of datasets.
3. The method of claim 2, further comprising identifying, by the one or more processors, the portion of the third plurality of datasets to use for training the subset of AI models and a second portion of the third plurality of datasets to use for validating the subset of AI models; and validating, by the one or more processors, at least one of the subset of AI models using the second portion of the third plurality of datasets.
4. The method of claim 1, further comprising: determining, by the one or more processors, that data correction is to be performed on the at least one dataset based on one or more values of the at least one dataset; and identifying, by the one or more processors, supplemental data from the network environment to add to the at least one dataset, responsive to determining that data correction is to be performed.
5. The method of claim 1, further comprising generating, by the one or more processors, for each dataset of the plurality of datasets, a tag indicating a category of a plurality of categories for the plurality of processes to be evaluated, the plurality of categories including at least one of the risk level, a usage, a health, or a performance; wherein identifying the at least one dataset further comprises identifying, from the plurality of datasets, the at least one dataset associated with the tag indicating the risk level.
6. The method of claim 1, further comprising providing, by the one or more processors, the user interface comprising a plurality of user interface elements corresponding to the plurality of processes; and selecting, by the one or more processors, the process from the plurality of processes, responsive to interaction with a user interface elements of the plurality of user interface elements corresponding to the process.
7. The method of claim 1, further comprising identifying, by the one or more processors, from a plurality of templates, a template with which to display the output based on the process, wherein causing the presentation further comprises causing displaying of the output including the risk level indicating the degree of vulnerability of the process via the user interface.
8. The method of claim 1, further comprising converting, by the one or more processors, the least one dataset of the first plurality of datasets from a first format to a second format, the first format used by at least one of the plurality of data sources to generate the at least one dataset, the second

format compatible as input for the AI model.

9. The method of claim 1, further comprising maintaining, by the one or more processors, the plurality of AI models comprising at least one of (i) a first AI model configured to generate a first output indicating usefulness of the process, (ii) a second AI model configured to generate a second output indicating performance metric, (iii) a third AI model configured to generate a third output indicating a health level, or (iv) the AI model configured to generate the output, each AI model of the plurality of AI models corresponding to a respective process of the plurality of processes in network environment.

10. The method of claim 1, further comprising addressing a risk in the network environment based on the output including the risk level indicating the degree of the vulnerability of the process to failure.

11. A system for identifying artificial intelligence (AI) models to detect vulnerabilities in network environments, comprising: one or more processors coupled with memory, configured to: retrieve a first plurality of datasets generated by a plurality of data sources associated with the network environment over a first time period; identify, from the first plurality of datasets, at least one dataset corresponding to a process selected from a plurality of processes; select, from a plurality of AI models, an AI model based on the process of the plurality of processes, wherein the AI model is trained using a second plurality of datasets for the process over a second time period; apply the AI model to the at least one dataset corresponding to the process; generate, based on applying the AI model to the at least one dataset, an output including a risk level indicating a degree of vulnerability of the process to failure; and cause presentation of the output including the risk level indicating the degree of vulnerability of the process to failure via a user interface.

12. The system of claim 11, wherein the one or more processors are further configured to: retrieve a third plurality of datasets from the plurality of data sources over a third time period; select, from the plurality of AI models, a subset of AI models corresponding to a subset of processes from the plurality of processes present in the third plurality of datasets; and train the subset of AI models using at least a portion of the third plurality of datasets.

13. The system of claim 12, wherein the one or more processors are further configured to: identify the portion of the third plurality of datasets to use for training the subset of AI models and a second portion of the third plurality of datasets to use for validating the subset of AI models; and validate at least one of the subset of AI models using the second portion of the third plurality of datasets.

14. The system of claim 11, wherein the one or more processors are further configured to: determine that data correction is to be performed on the at least one dataset based on one or more values of the at least one dataset; and identify supplemental data from the network environment to add to the at least one dataset, responsive to determining that data correction is to be performed.

15. The system of claim 11, wherein the one or more processors are further configured to: generate, for each dataset of the plurality of datasets, a tag indicating a category of a plurality of categories for the plurality of processes to be evaluated, the plurality of categories including at least one of the risk level, a usage, a health, or a performance; and identify, from the plurality of datasets, the at least one dataset associated with the tag indicating the risk level.

16. The system of claim 11, wherein the one or more processors are further configured to: provide the user interface comprising a plurality of user interface elements corresponding to the plurality of processes; and select the process from the plurality of processes, responsive to interaction with a user interface elements of the plurality of user interface elements corresponding to the process.

17. The system of claim 11, wherein the one or more processors are further configured to: identify, from a plurality of templates, a template with which to display the output based on the process, cause displaying of the output including the risk level indicating the degree of vulnerability of the process via the user interface.

18. The system of claim 11, wherein the one or more processors are further configured to convert the least one dataset of the first plurality of datasets from a first format to a second format, the first

format used by at least one of the plurality of data sources to generate the at least one dataset, the second format compatible as input for the AI model.

19. The system of claim 11, wherein the one or more processors are further configured to maintain the plurality of AI models comprising at least one of (i) a first AI model configured to generate a first output indicating usefulness of the process, (ii) a second AI model configured to generate a second output indicating performance metric, (iii) a third AI model configured to generate a third output indicating a health level, or (iv) the AI model configured to generate the output, each AI model of the plurality of AI models corresponding to a respective process of the plurality of processes in network environment.

20. The system of claim 11, wherein a risk in the network environment is addressed based on the output including the risk level indicating the degree of the vulnerability of the process to failure.
