

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412675
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Shutayfi; Mohammed

Shielded electromagnetic pumps for nuclear reactors

Abstract

An electromagnetic pump (EMP) for a liquid metal-cooled nuclear reactor includes a pump casing, concentric inner and outer flow ducts collectively defining a flow annulus extending coaxially with a longitudinal axis of the EMP, and induction coils configured to control the flow of liquid metal coolant through the flow annulus based on electrical power received from the power supply. At least one of the inner flow duct or the outer flow duct includes a gamma shielding material configured to block gamma rays from entering an interior of the EMP from the flow annulus. The pump casing may include a neutron absorber material configured to absorb neutrons entering the pump casing from an exterior of the EMP. The EMP may include a neutron moderator material on an outer surface of the pump casing and configured to moderate neutrons entering the pump casing to be absorbed by the neutron absorber material.

Inventors:	Shutayfi; Mohammed (Wilmington, NC)
Applicant:	GE-Hitachi Nuclear Energy Americas LLC (Wilmington, NC)
Family ID:	89769538
Assignee:	GE-Hitachi Nuclear Energy Americas LLC (Wilmington, NC)
Appl. No.:	17/881916
Filed:	August 05, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240047089 A1	Feb. 08, 2024

Publication Classification

Int. Cl.: G21C15/247 (20060101); G21C11/02 (20060101); H02K5/20 (20060101); H02K44/06 (20060101)

U.S. Cl.:

CPC **G21C15/247** (20130101); **G21C11/026** (20130101); **H02K5/20** (20130101); **H02K44/06** (20130101);

Field of Classification Search

CPC: H02K (44/02); H02K (44/06); G21C (15/24); G21C (15/243); G21C (15/247)

USPC: 417/50

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3075925	12/1962	Dunegan	376/288	G21F 1/106
4174190	12/1978	Craig et al.	N/A	N/A
4828459	12/1988	Behrens	N/A	N/A
5195231	12/1992	Fanning et al.	N/A	N/A
2009/0279656	12/2008	Defilippis	376/260	F16F 9/19
2013/0207401	12/2012	Makhlouf	290/1R	F02C 1/10
2016/0125963	12/2015	McDaniel	N/A	N/A
2017/0162283	12/2016	Loewen	N/A	H02K 44/06
2017/0186502	12/2016	Kingham	N/A	G21B 1/13

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
S5289796	12/1976	JP	N/A
S62113093	12/1986	JP	Y02E 30/30

OTHER PUBLICATIONS

Hayashi translation (Year: 1987). cited by examiner

Gamma Ray Attenuation Properties—MarShield (Year: 2022). cited by examiner

“Neutron Shielding Materials”—McAlister (Year: 2016). cited by examiner

Nashine, B.K., et al., “Design, development and testing of a sodium submersible Annular Linear Induction Pump for application in sodium cooled fast reactor”, Annals of Nuclear Energy, vol. 145, (2020), 107494, p. 1-12. <<https://doi.org/10.1016/j.anucene.2020.107494>>. cited by applicant

Ota, Hiroyuki, et al., “Development of 160 m³/min Large Capacity Sodium-Immersed Self-Cooled Electromagnetic Pump”, Journal of Nuclear Science and Technology, vol. 41, No. 4, p. 511-523 (2004). DOI: 10.1080/18811248.2004.9715514. cited by applicant

Aizawa, Kosuke, et al., “Electromagnetic Pumps for Main Cooling Systems of Commercialized Sodium-Cooled Fast Reactor”, Journal of Nuclear Science and Technology, vol. 48, No. 3, p. 344-352 (2011). DOI: 10.1080/18811248.2011.9711709. cited by applicant

Buhler, Leo, “Liquid Metal Magnetohydrodynamics for Fusion Blankets.” In: “Magnetohydrodynamics, Historical Evolution and Trends” by Sergei S. Molokov et al. (eds.), Springer, p. 171-194 (2007). cited by applicant

Waltar, Alan, et al. (eds.), “Fast Spectrum Reactors,” Springer, p. 354-361 (2011). cited by applicant

Waltar, Alan, et al. (eds.), “Fast Spectrum Reactors,” Springer, p. 138, footnote 2 (2011). cited by applicant

Mikhaelia, L.Y, et al., “Comparison of Boron Carbide, Gadolinium Oxide, and Hafnium as Qualified Molten Salt Reactor's Control Rods Material,” Journal of Physics: Conference Series, 1825 (2004), p. 1-6. cited by applicant
McAlister, Daniel, “Gamma Ray Attenuation Properties of Common Shielding Materials,” PG Research Foundation, Inc., (2018), p. 1-25. cited by applicant
McAlister, Daniel, “Neutron Shielding Materials,” PG Research Foundation, Inc., (2016), p. 1-14. cited by applicant
International Search Report and Written Opinion thereof mailed Jul. 22, 2024 for corresponding International Application No. PCT/US2023/071499. cited by applicant
International Preliminary Report on Patentability dated Feb. 4, 2025 for corresponding International Application No. PCT/US2023/071499. cited by applicant

Primary Examiner: Stimpert; Philip E

Attorney, Agent or Firm: Harness, Dickey & Pierce, P.L.C.

Background/Summary

BACKGROUND

Field

(1) The present inventive concepts relate in general to nuclear reactors and in particular to electromagnetic pumps used to control liquid metal coolant circulation through a reactor core of a liquid metal-cooled nuclear reactor and further in particular to providing improved protection of electromagnetic pumps against radiation and/or thermal aspects of operating environments of nuclear reactors.

Description of Related Art

(2) Nuclear reactors included in nuclear plants may be configured to be cooled via heat transfer to one or more coolants circulated through the core. Various coolants may be utilized to remove heat from the reactor core. A coolant may include one or more various substances, including water, liquid metal, molten salt, a gaseous substance, some combination thereof, etc.

(3) In some nuclear plants, a coolant removing heat from a reactor core, also referred to herein as a primary coolant, is circulated through a heat exchanger to transfer the heat to another coolant, also referred to herein as a secondary coolant. In some cases, the secondary coolant is used to perform work, including driving an electrical generator via circulating through a turbine device included in the nuclear plant. In some nuclear plants, a coolant may be used to provide process heat to support one or more industrial processes, including desalination, hydrogen production, etc.

(4) In some cases, a nuclear reactor is configured to be cooled by liquid metal circulation. Such a nuclear reactor is referred to herein interchangeably as a liquid metal-cooled nuclear reactor and may include a primary coolant loop via which one or more liquid metal substances are circulated as the primary coolant. Such one or more liquid metal substances circulating through the primary coolant loop may be circulated at least partially through a reactor core of the nuclear reactor and are referred to herein as liquid metal coolants.

(5) In some cases, a liquid metal coolant that may be circulated through a nuclear reactor includes a conductive liquid metal substance. A liquid metal-cooled nuclear reactor configured to be cooled via a conductive liquid metal substance may include one or more electromagnetic pumps (EMPs, also referred to herein interchangeably as EM pumps) configured to circulate the conductive liquid metal coolant through the nuclear reactor.

SUMMARY

(6) According to some example embodiments, a nuclear reactor configured to be cooled via liquid metal circulation may include a reactor pressure vessel, a reactor core within the reactor pressure vessel, and an electromagnetic pump (EMP) within the reactor pressure vessel. The EMP may be configured to circulate a flow of liquid metal coolant through a primary coolant flow path that includes the reactor core. The EMP may include a pump casing having a longitudinal axis extending in a longitudinal direction, the pump casing at least partially defining an interior of the EMP, concentric inner and outer flow ducts extending coaxially with the longitudinal axis and collectively defining a flow annulus extending coaxially with the longitudinal axis, and a plurality of induction coils within the interior of the EMP and configured to be electrically connected to a power supply, the plurality of induction coils configured to control the flow of liquid metal coolant through the primary coolant flow path via the flow annulus based on electrical power received from the power supply. At least one flow duct of the inner flow duct or the outer flow duct may include a gamma shielding material that is configured to block gamma rays from entering the interior of the EMP from the flow annulus.

(7) The at least one flow duct may include concentric cylindrical duct walls defining a duct annulus between the concentric cylindrical duct walls. The gamma shielding material may be located within the duct annulus.

(8) The at least one flow duct may include a material at least partially defining an inner surface or an outer diameter surface of the flow annulus, the material including the gamma shielding material.

(9) Each of the inner flow duct and the outer flow duct may include the gamma shielding material.

(10) The pump casing may include a neutron absorber material that is configured to absorb neutrons entering the pump casing from an exterior of the EMP.

(11) The pump casing may include concentric cylindrical casing walls defining a casing annulus between the concentric cylindrical casing walls. The neutron absorber material may be located within the casing annulus.

(12) The EMP may further include a neutron moderator material on an outer surface of the pump casing. The neutron moderator material may be configured to moderate neutrons received from the exterior of the EMP such that the neutrons entering the pump casing from the exterior of the EMP are moderated neutrons, and the neutron absorber material may be configured to absorb the moderated neutrons.

(13) The nuclear reactor may further include a control system configured to control the power supply to control a supply of the electrical power to the EMP, to control the flow of liquid metal coolant through the primary coolant flow path.

(14) The plurality of induction coils may include at least one of inner induction coils located within a central region at least partially defined by an inner surface of the inner flow duct, or outer induction coils located within an annular region at least partially defined between an outer surface of the outer flow duct and an inner surface of the pump casing.

(15) According to some example embodiments, an electromagnetic pump (EMP) may include a pump casing having a longitudinal axis extending in a longitudinal direction, the pump casing at least partially defining an interior of the EMP, concentric inner and outer flow ducts extending coaxially with the longitudinal axis and collectively defining a flow annulus extending coaxially with the longitudinal axis; and a plurality of induction coils within the interior of the EMP and configured to be electrically connected to a power supply, the plurality of induction coils configured to control a flow of liquid metal coolant through the flow annulus based on electrical power received from the power supply. At least one flow duct of the inner flow duct or the outer flow duct may include a gamma shielding material that is configured to block gamma rays from entering the interior of the EMP from the flow annulus.

(16) The at least one flow duct may include concentric cylindrical duct walls defining a duct annulus between the concentric cylindrical duct walls. The gamma shielding material may be located within the duct annulus.

- (17) The at least one flow duct may include a material at least partially defining an inner surface or an outer diameter surface of the flow annulus. The material may include the gamma shielding material.
- (18) Each of the inner flow duct and the outer flow duct may include the gamma shielding material.
- (19) The pump casing may include a neutron absorber material that is configured to absorb neutrons entering the pump casing from an exterior of the EMP.
- (20) The pump casing may include concentric cylindrical housing walls defining a housing annulus between the concentric cylindrical housing walls. The neutron absorber material may be located within the housing annulus.
- (21) The EMP may further include a neutron moderator material on an outer surface of the pump casing. The neutron moderator material may be configured to moderate neutrons received from the exterior of the EMP such that the neutrons entering the pump casing from the exterior of the EMP are moderated neutrons, and the neutron absorber material may be configured to absorb the moderated neutrons.
- (22) The plurality of induction coils may include at least one of inner induction coils located within a central region at least partially defined by an inner surface of the inner flow duct, or outer induction coils located within an annular region at least partially defined between an outer surface of the outer flow duct and an inner surface of the pump casing.
- (23) According to some example embodiments, a method for operating the EMP may include controlling a supply of electrical power to the EMP to cause the plurality of induction coils to generate one or more magnetic fields to induce the flow of liquid metal coolant through the flow annulus, and blocking, at the gamma shielding material included in the at least one flow duct, gamma rays emitted from liquid metal coolant located in the flow annulus from entering an interior of the EMP that is external to the flow annulus.
- (24) The pump casing may include a neutron absorber material that is configured to absorb neutrons entering the pump casing from an exterior of the EMP, and the method may further include absorbing, at the neutron absorber material, neutrons received at the pump casing from the exterior of the EMP.
- (25) According to some example embodiments, a method for configuring a nuclear reactor to improve liquid metal coolant flow control in the nuclear reactor may include installing an electromagnetic pump (EMP) in a primary coolant loop in a nuclear reactor pressure of the nuclear reactor. The EMP may include a pump casing having a longitudinal axis extending in a longitudinal direction, the pump casing at least partially defining an interior of the EMP, concentric inner and outer flow ducts extending coaxially with the longitudinal axis and collectively defining a flow annulus extending coaxially with the longitudinal axis, and a plurality of induction coils within the interior of the EMP and configured to be electrically connected to a power supply, the plurality of induction coils configured to control a flow of liquid metal coolant through the flow annulus based on electrical power received from the power supply, wherein at least one flow duct of the inner flow duct or the outer flow duct includes a gamma shielding material that is configured to block gamma rays from entering the interior of the EMP from the flow annulus. The method may include electrically connecting the EMP to the power supply via a power cable, and communicatively coupling the EMP to a control system, the control system including a memory storing a program of instructions and a processor configured to execute the program of instructions to control the flow of liquid metal coolant through the primary coolant loop based on controlling the supply of electrical power supplied from the power supply to the EMP.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The various features and advantages of the non-limiting embodiments herein may become more apparent upon review of the detailed description in conjunction with the accompanying drawings. The accompanying drawings are merely provided for illustrative purposes and should not be interpreted to limit the scope of the claims. The accompanying drawings are not to be considered as drawn to scale unless explicitly noted. For purposes of clarity, various dimensions of the drawings may have been exaggerated.

(2) FIG. 1 is a schematic view of a nuclear plant that includes a liquid metal-cooled nuclear reactor and at least one EM pump, according to some example embodiments.

(3) FIG. 2A is a perspective view of a liquid metal-cooled nuclear reactor, according to some example embodiments.

(4) FIG. 2B is a plan view of a liquid metal-cooled nuclear reactor, according to some example embodiments.

(5) FIG. 3A is a perspective view of an EM Pump (EMP), according to some example embodiments.

(6) FIG. 3B is a perspective cross-sectional view along cross-sectional view line IIIB-IIIB' shown in FIG. 3A, according to some example embodiments.

(7) FIG. 4A is a cross-sectional view of the EMP of FIG. 3A along cross-sectional view line IVA-IVA' shown in FIG. 3A, according to some example embodiments.

(8) FIG. 4B is a cross-sectional view of the EMP of FIG. 4A along cross-sectional view line IVB-IVB' shown in FIG. 3A, according to some example embodiments.

(9) FIG. 4C is a cross-sectional view of the EMP of FIG. 4A along cross-sectional view line IVC-IVC' shown in FIG. 3A, according to some example embodiments.

(10) FIG. 4D is a cross-sectional view of the EMP of FIG. 3A along cross-sectional view line IVA-IVA' shown in FIG. 3A, according to some example embodiments.

(11) FIG. 5 is a flowchart illustrating a method for operating an EMP, according to some example embodiments.

(12) FIG. 6 is a flowchart illustrating a method for configuring a nuclear reactor to improve reliability and protection of liquid metal coolant flow control in the nuclear reactor, according to some example embodiments.

DETAILED DESCRIPTION

(13) Reference will now be made in detail to example embodiments, some of which are illustrated in the accompanying drawings, wherein like reference labels refer to like elements throughout.

(14) It should be understood that when an element or layer is referred to as being “on,” “connected to,” “coupled to,” or “covering” another element or layer, it may be directly on, connected to, coupled to, or covering the other element or layer or intervening elements or layers may be present. In contrast, when an element is referred to as being “directly on,” “directly connected to,” or “directly coupled to” another element or layer, there are no intervening elements or layers present. Like numbers refer to like elements throughout the specification. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

(15) It should be understood that, although the terms first, second, third, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers, and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer, or section from another region, layer, or section. Thus, a first element, component, region, layer, or section discussed below could be termed a second element, component, region, layer, or section without departing from the teachings of example embodiments.

(16) Spatially relative terms (e.g., “beneath,” “below,” “lower,” “above,” “upper,” and the like) may be used herein for ease of description to describe one element or feature's relationship to

another element(s) or feature(s) as illustrated in the figures. It should be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the term “below” may encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

(17) The terminology used herein is for the purpose of describing various embodiments only and is not intended to be limiting of example embodiments. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(18) Example embodiments are described herein with reference to cross-sectional illustrations that are schematic illustrations of idealized embodiments (and intermediate structures) of example embodiments. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, example embodiments should not be construed as limited to the shapes of regions illustrated herein but are to include deviations in shapes that result, for example, from manufacturing. For example, an implanted region illustrated as a rectangle will, typically, have rounded or curved features and/or a gradient of implant concentration at its edges rather than a binary change from implanted to non-implanted region. Likewise, a buried region formed by implantation may result in some implantation in the region between the buried region and the surface through which the implantation takes place. Thus, the regions illustrated in the figures are schematic in nature and their shapes are not intended to illustrate the actual shape of a region of a device and are not intended to limit the scope of example embodiments.

(19) Example embodiments may be described with reference to acts and symbolic representations of operations (e.g., in the form of flow charts, flow diagrams, data flow diagrams, structure diagrams, block diagrams, etc.) that may be implemented in conjunction with units and/or devices discussed in more detail below. Although discussed in a particular manner, a function or operation specified in a specific block may be performed differently from the flow specified in a flowchart, flow diagram, etc. For example, functions or operations illustrated as being performed serially in two consecutive blocks may actually be performed simultaneously, or in some cases be performed in reverse order.

(20) Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which example embodiments belong. It will be further understood that terms, including those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

(21) Units, systems, and/or devices according to some example embodiments may be implemented using one or more instances of hardware, software, and/or a combination thereof. For example, hardware devices may be implemented using processing circuitry such as, but not limited to, a processor, Central Processing Unit (CPU), a controller, an arithmetic logic unit (ALU), a digital signal processor, a microcomputer, a field programmable gate array (FPGA), a System-on-Chip (SoC), a programmable logic unit, a microprocessor, or any other device capable of responding to and executing instructions in a defined manner.

(22) Software may include a computer program, program code, instructions, or some combination

thereof, for independently or collectively instructing or configuring a hardware device to operate as desired. The computer program and/or program code may include program or computer-readable instructions, software components, software modules, data files, data structures, and/or the like, capable of being implemented by one or more hardware devices, such as one or more of the hardware devices mentioned above. Examples of program code include both machine code produced by a compiler and higher level program code that is executed using an interpreter.

(23) For example, when a hardware device is a computer processing device (e.g., a processor, Central Processing Unit (CPU), a controller, an arithmetic logic unit (ALU), a digital signal processor, a microcomputer, a microprocessor, etc.), the computer processing device may be configured to carry out program code by performing arithmetical, logical, and input/output operations, according to the program code. Once the program code is loaded into a computer processing device, the computer processing device may be programmed to perform the program code, thereby transforming the computer processing device into a special purpose computer processing device. In a more specific example, when the program code is loaded into a processor, the processor becomes programmed to perform the program code and operations corresponding thereto, thereby transforming the processor into a special purpose processor.

(24) Software and/or data may be embodied permanently or temporarily in any type of machine, component, physical or virtual equipment, or computer storage medium or device, capable of providing instructions or data to, or being interpreted by, a hardware device. The software also may be distributed over network coupled computer systems so that the software is stored and executed in a distributed fashion. In particular, for example, software and data may be stored by one or more computer readable recording mediums, including the tangible or non-transitory computer-readable storage media discussed herein.

(25) According to some example embodiments, computer processing devices may be described as including various functional units that perform various operations and/or functions to increase the clarity of the description. However, computer processing devices are not intended to be limited to these functional units. For example, in some example embodiments, the various operations and/or functions of the functional units may be performed by other ones of the functional units. Further, the computer processing devices may perform the operations and/or functions of the various functional units without sub-dividing the operations and/or functions of the computer processing units into these various functional units.

(26) Units and/or devices according to some example embodiments may also include one or more storage devices. The one or more storage devices may be tangible or non-transitory computer-readable storage media, such as random access memory (RAM), read only memory (ROM), a permanent mass storage device (such as a disk drive), solid state (e.g., NAND flash) device, and/or any other like data storage mechanism capable of storing and recording data. The one or more storage devices may be configured to store computer programs, program code, instructions, or some combination thereof, for one or more operating systems and/or for implementing the example embodiments described herein. The computer programs, program code, instructions, or some combination thereof, may also be loaded from a separate computer readable storage medium into the one or more storage devices and/or one or more computer processing devices using a drive mechanism. Such separate computer readable storage medium may include a Universal Serial Bus (USB) flash drive, a memory stick, a Blu-ray/DVD/CD-ROM drive, a memory card, and/or other like computer readable storage media. The computer programs, program code, instructions, or some combination thereof, may be loaded into the one or more storage devices and/or the one or more computer processing devices from a remote data storage device via a network interface, rather than via a local computer readable storage medium. Additionally, the computer programs, program code, instructions, or some combination thereof, may be loaded into the one or more storage devices and/or the one or more processors from a remote computing system that is configured to transfer and/or distribute the computer programs, program code, instructions, or some

combination thereof, over a network. The remote computing system may transfer and/or distribute the computer programs, program code, instructions, or some combination thereof, via a wired interface, an air interface, and/or any other like medium.

(27) The one or more hardware devices, the one or more storage devices, and/or the computer programs, program code, instructions, or some combination thereof, may be specially designed and constructed for the purposes of the example embodiments, or they may be known devices that are altered and/or modified for the purposes of example embodiments.

(28) A hardware device, such as a computer processing device, may run an operating system (OS) and one or more software applications that run on the OS. The computer processing device also may access, store, manipulate, process, and create data in response to execution of the software. For simplicity, some example embodiments may be exemplified as one computer processing device; however, one skilled in the art will appreciate that a hardware device may include multiple processing elements and multiple types of processing elements. For example, a hardware device may include multiple processors or a processor and a controller. In addition, other processing configurations are possible, such as parallel processors.

(29) Although described with reference to specific examples and drawings, modifications, additions and substitutions of example embodiments may be variously made according to the description by those of ordinary skill in the art. For example, the described techniques may be performed in an order different with that of the methods described, and/or components such as the described system, architecture, devices, circuit, and the like, may be connected or combined to be different from the above-described methods, or results may be appropriately achieved by other components or equivalents.

(30) The inventive concepts relate to electromagnetic pumps (EMPs) configured to provide improved control, including improved reliability of such control, of liquid metal coolant flow through at least a portion of a nuclear reactor, liquid metal-cooled nuclear reactors including one or more of the electromagnetic pumps, and methods of configuring and/or operating the electromagnetic pumps and/or nuclear reactors.

(31) The electromagnetic pumps (EMPs) according to some example embodiments of the inventive concepts may include an Annular Linear Induction Pump (ALIP). An Annular Linear Induction Pump (ALIP) may be an electromagnetic pump that is configured to pump liquid metals based on applying electromagnetic forces on a liquid metal coolant to cause the liquid metal coolant to flow through the length (e.g., in parallel with the longitudinal axis) of the pump. This may be performed based on applying AC current at specified AC frequencies and phase angles to induction coils of the ALIP that surround a flow annulus that extends along the length of the pump (e.g., coaxially with the longitudinal axis of the pump).

(32) In some example embodiments, an EMP may be configured to provide self-cooling during operation, for example based on rejecting heat generated in the EMP into the flow of liquid metal coolant flowing through the EMP. In some example embodiments, some or all of the heat generated by the EMP is removed from the stators of the EMP to the liquid metal coolant rather than the traditional approach of an active auxiliary cooling system located external to the reactor as required in prior EM pump designs. For example, the EMP may draw liquid metal coolant from a cold pool (e.g., a suction reservoir as described herein) at an inlet temperature of approximately 350° C. that is strongly activated (Na-24), which might result in the nuclear reactor having a secondary, or intermediate coolant loop that includes liquid metal coolant such as sodium or lead. Self-cooled EMPs may reduce, minimize, or prevent downsides associated with external cooling methods. The internal components of the EMP, such as electrical insulation, induction coils, and stators, are configured to endure the harsh thermal and radiation environment in-vessel for the primary coolant loop.

(33) In some example embodiments, an EMP may be configured to provide at least partial shielding of some or all internal components of the EMP from gamma rays emitted from liquid

metal coolant flowing through the EMP, based on including one or more gamma shielding materials. And thereby providing gamma ray shielding to the EMP. In some example embodiments, an EMP may be configured to provide shielding of some or all internal components of the EMP from neutrons received from an exterior of the EMP (e.g., ambient neutrons received from an ambient environment surrounding the EMP), based on including one or more neutron absorber materials and thereby providing neutron exposure shielding to the EMP. Based on including one or more gamma shielding materials in one or more components of the EMP and/or based on including one or more neutron absorber materials in one or more components of the EMP, wear and/or damage which may otherwise be incurred by the EMP due to the gamma rays and/or ambient neutrons entering the EMP and contacting one or more internal components thereof (e.g., induction coils, electrical insulation, circuitry, stators, etc.) may be reduced, minimized, or prevented. As a result, the service lifetime of the EMP may be improved, the reliability of the EMP may be increased, maintenance of the EMP may be reduced, and/or decommissioning of the EMP may be simplified due to reduced irradiation and/or activation of internal components of the EMP.

(34) Additionally, based on being configured to have gamma ray shielding and/or ambient neutron shielding, the EMP may be configured to be positioned in a nuclear reactor in closer proximity to the nuclear reactor core as the EMP may have improved shielding from ambient neutrons of the high radiation, high temperature ambient environment that is in close proximity to the nuclear reactor core and further having shielding from gamma rays emitted by liquid metal coolant circulated (e.g., flowing) through the nuclear reactor, thereby enabling improved compactness of the nuclear reactor design. Additionally, the EMP may, based on including the gamma shielding material and/or neutron absorber material, may configure the EMP to have reduced likelihood of pump failure due to radiation insulation degradation effects, reduce component activation level of components of the EMP, simplify decommissioning procedures, and fully utilize the advantages of large EMPs in liquid metal-cooled nuclear reactors.

(35) As described herein, the internal components of an EMP include the pump ducts (also referred to herein as flow ducts) and pump housing (also referred to herein as pump casing). The flow ducts collectively define a flow conduit (e.g., a flow annulus) configured to contain liquid metal coolant flowing therein. The flow ducts may each have a radial thickness in order to possess some structural integrity in high pressure systems. Additionally, the flow ducts may be configured to separate received liquid metal coolant entering the flow conduit (e.g., activated sodium) from other pump components (also referred to herein as internal components) such as coils, stators, insulation, nitrogen gas, or the like. Similarly to the flow ducts, the pump casing may have some radial thickness in order to give the EMP some structural integrity and allow it to be lifted and orientated in various directions. The flow ducts may have sufficient thickness to accommodate a gamma shielding material therein, for example as a filler material within an annulus defined by cylindrical duct walls (e.g., stainless steel walls). The pump casing, and/or any structures thereof, may have sufficient thickness to accommodate a neutron absorber material therein, for example as a filler material within an annulus defined by cylindrical casing walls (e.g., stainless steel walls).

(36) In some example embodiments, the EMP is configured to include the gamma shielding material in at least one flow duct at least partially defining a flow annulus through which the liquid metal coolant flows through the EMP, thereby shielding internal components of the EMP outside the flow annulus from gamma rays emitted by the liquid metal coolant. The gamma shielding material may include one or more materials including, without limitation, one or more of Lead, Iron and Steel-Alloys, Tin, Bismuth, Tungsten and its Alloys, Water, or Borated Paraffin or Polyethylene. In some example embodiments, the EMP is configured to include the neutron absorber material in at least a portion of the pump casing at least partially defining the outer surface and/or outer structure of the EMP, to absorb ambient neutrons received from the ambient environment external to the EMP and thereby reducing, minimizing, or preventing penetration of such ambient neutrons to the interior of the EMP to wear or damage internal components of the

EMP. The neutron absorber material may include one or more materials including, without limitation, one or more of Gadolinium, Cadmium, Boron, Boron Carbide, Gadolinium oxide, Hafnium Lithium, Tantalum, Europium, Gadolinium Stainless Steel, Hafnium, Silver, Xenon, or Indium.

(37) An EMP according to some example embodiments may include a neutron absorber material as a filler within a space (e.g., a casing annulus) within at least a portion of the pump casing of the EMP while using a gamma shielding material as a filler within a space (e.g., a duct annulus) within at least one flow duct of the inner or outer flow ducts at least partially defining the flow annulus through which liquid metal coolant may flow in the EMP. These neutron absorber materials and gamma shielding materials, when included in the EMP, may configure the EMP to have neutron absorption characteristics in low or high energy neutron fluxes, well characterized irradiated performance and thermophysical properties, and ability to support a long design reactor lifetime.

(38) While the EMP according to some example embodiments may be included in a liquid metal cooled nuclear reactor, such as a liquid metal fast-cooled nuclear reactor, the EMP according to some example embodiments could be included in various other environments and for other purposes, such as fusion liquid metal blankets where liquid metals such as lithium or lithium-lead alloys are used as possible liquid metal coolants pumped by EMPs.

(39) Based on the EMP including gamma shielding material and/or a neutron absorber material therein, the EMP may reduce, minimize, or prevent expensive radiation testing, allow many flexible reactor designs since the EMP can be located anywhere in the reactor vessel, and enhance heat transfer between pump components and liquid metal coolant to enable self-cooling of the EMP. Additionally, the EMP having the gamma shielding material and/or neutron absorber material according to some example embodiments may be configured to be easily and quickly implemented without requiring component program development or significant research efforts.

(40) An EMP including a gamma shielding material and/or a neutron absorber material according to any of the example embodiments may be configured to reduce, minimize, or prevent pump material and/or component wear and/or damage (e.g., degradation and/or activation) due to radiation (e.g., received gamma rays and/or ambient neutrons from the ambient environment that is external to the EMP). The EMP may thus have an extended lifetime while being located in the nuclear reactor vessel, may enable improved flexibility in reactor design since the EMP can be located closer to the reactor core, thus decreasing the cost of the reactor vessel system, may enable reduction, minimization, or elimination of expensive irradiation testing to qualify insulation lifetime under temperature, voltage, and radiation conditions within an interior of a nuclear reactor, may reduce gamma ray and neutron exposure to EMP components (e.g., internal components) at high temperatures to thereby would improve EMP reliability, may be implemented in various configurations of EMPs, including self-cooling EMPs, without limitation from design, size, or performance requirements, may maintain compatibility with other pump components and reactor structural materials in terms of thermophysical and neutronic properties, and may reduce, minimize, or prevent activation in pump components, which would considerably allow quick maintenance and less complicated pump decommissioning procedures.

(41) FIG. 1 is a schematic view of a nuclear plant that includes a liquid metal-cooled nuclear reactor, according to some example embodiments.

(42) The nuclear plant **100** includes a liquid metal-cooled nuclear reactor (referred to herein as simply a “nuclear reactor”) **110**, a primary coolant loop **119**, an intermediate coolant loop **160**, a power supply **144** (e.g., a polyphase power supply), and an EMP control system **150**. The primary coolant loop **119** includes an EMP **120** (e.g., an ALIP) that is electrically connected to the power supply **144** via a power cable **146** (e.g., a polyphase power cable, also referred to herein as one or more power conductors, power wires, etc.) configured to supply power (e.g., polyphase power) to the EMP **120**.

(43) The nuclear reactor **110** includes a nuclear reactor pressure vessel **111**. The nuclear reactor

pressure vessel **111** includes a nuclear reactor core **112** and multiple components within a volume space at least partially defined by an outer wall **111S**. The multiple components comprise a primary coolant loop **119**, also referred to herein as a primary loop. The primary coolant loop **119** may be configured to remove heat generated at the nuclear reactor core **112** as a result of nuclear reactions within the nuclear reactor core **112**. The primary coolant loop **119** illustrated in FIG. 1 is configured to circulate a liquid metal coolant **190** through at least a portion of the nuclear reactor core **112** to remove, from the nuclear reactor core **112**, heat generated at the nuclear reactor core **112** as a result of nuclear reactions within the nuclear reactor core **112**. Such heat removal may also be referred to herein as core heat rejection.

(44) As shown, the primary coolant loop **119** includes a primary heat exchanger **114**. The primary heat exchanger **114** is configured to transfer heat from the liquid metal coolant **190** exiting the nuclear reactor core **112** to another coolant. The other coolant circulates through an intermediate coolant loop **160**. The other coolant, in some example embodiments, may include a liquid metal coolant. Liquid metal coolants circulating through the primary and intermediate coolant loops may be a common liquid metal substance or different liquid metal substances.

(45) The primary coolant loop **119** includes a suction reservoir **116**, which may be referred to as a “cold” reservoir or pool. The suction reservoir **116** is configured to receive liquid metal coolant **190** that leaves the primary heat exchanger **114** subsequent to the liquid metal coolant **190** transferring core-generated heat to the intermediate coolant loop **160**.

(46) The primary coolant loop **119** includes an EMP **120**. The EMP **120** is configured to operate to cause liquid metal coolant **190** to circulate through the nuclear reactor **110**, as shown in FIG. 1. While FIG. 1 shows only one power supply **144** and one EMP **120** within the nuclear reactor **110**, and the following description of FIG. 1 may refer to “a” or “the” EMP **120** and “a” or “the” power supply **144**, it will be understood that multiple EMPs **120** may be included within the nuclear reactor **110**, where at least some of the multiple EMPs **120** may be configured to operate in parallel or in series with each other to circulate liquid metal coolant through the nuclear reactor. Additionally, multiple power supplies **144** may be included in the nuclear plant **100**, and each EMP **120** of multiple EMPs **120** in the nuclear reactor **110** may be electrically connected a same or different power supplies **144** as the other EMPs **120** within the nuclear reactor **110**.

(47) The EMP **120** is coupled, at an intake orifice or inlet **122**, to the suction reservoir **116** via a suction line **121**, also referred to herein as a pump inlet manifold. As shown in at least FIG. 2B, the EMP **120** may be further coupled, at the intake orifice or inlet **122**, to the suction reservoir **116** via one or more fixed shield cylinders **204**. The EMP **120** is coupled, at an outlet orifice or outlet **123**, to a core inlet plenum **118** via one or more return lines **124**, which are also referred to as one or more pump discharge pipes. The EMP **120** is configured to drive at least a portion of, or all of, the liquid metal coolant **109** to the core inlet plenum **118** and is further configured to generate at least a portion of, or all of, a pressure head, downstream of the EMP **120**. The pressure head may provide a driving force to circulate the liquid metal coolant through the nuclear reactor core **112** as shown.

(48) As further shown in at least FIG. 2B, the nuclear reactor may include a “hot” reservoir **202**, also referred to herein as a hot pool, in which liquid metal coolant exiting the nuclear reactor core **112** may circulate between the nuclear reactor core **112** and the primary heat exchanger **114**, and “hot” liquid metal coolant may circulate from the hot reservoir **202** to the suction reservoir **116** via the primary heat exchanger such that the liquid metal coolant exiting the primary heat exchanger **114** into the suction reservoir may be “cold” liquid metal coolant that is colder than the hot liquid metal coolant in the hot reservoir **202**.

(49) The power supply **144** may be any power supply or power source configured to supply electrical power, including for example polyphase electrical power (e.g., three phase AC power). The power supply **144** may be an AC power supply. For example, the power supply **144** may be an adjustable speed drive, also called a variable speed drive, that is configured to receive AC (“alternating current”) power at 60 Hz (e.g., from plant main power supply **140** and/or generator

141), convert the received AC power to DC (“direct current”), and then convert the power from DC to AC at a specific (“particular”) current and frequency of polyphase electrical power to be supplied to the EMP **120**.

(50) As further shown, the power supply **144** is electrically coupled to one or more of a main power supply **140** of the nuclear plant **100** or a generator **141**. In some example embodiments, the nuclear plant **100** includes one or more switchgear devices (not illustrated in FIG. **1**) configured to selectively supply electrical power, to the power supply **144**, from one or more of the main power supply **140** or one or more generators **141**. A generator **141** may include one or more of a combustion engine, a fuel cell device, a battery, an uninterruptible power supply (UPS), some combination thereof, etc. The plant main power supply **140** may include a power supply configured to supply power generated based on the process fluid circulating through the power generation loop **170**.

(51) In some example embodiments, where the EMP **120** includes a plurality of induction coils configured to be electrically connected to the power supply **144** (e.g., a polyphase power supply) via a power cable **146** (e.g., a polyphase power cable, also referred to herein as a “multi-wire power line”), the power cable **146** may be configured to supply electrical power (e.g., polyphase electrical power) to the induction coils of the EMP **120**. The power cable **146** may extend into the EMP **120** and may be electrically coupled to the induction coils of the EMP **120**. Accordingly, the induction coils of the EMP **120** may be electrically connected to the power cable **146**.

(52) As shown in FIG. **1**, the power cable **146** may be located in (e.g., at least partially or completely encased in, at least partially or completely enclosed in, or the like) a single power supply conductor **180** (also referred to herein as a “power supply conductor cable,” “conduit,” or “extension cable”) that extends from the EMP **120** (e.g., at least a pump casing, also referred to herein as an outer housing, of the EMP **120**) to at least an exterior of the nuclear reactor pressure vessel **111** through an opening or “penetration” **182** in the outer wall **111S** of the nuclear reactor pressure vessel **111**, so that the plurality of induction coils of the EMP **120** may be electrically coupled to the power supply **144** via the opening **182** in the outer wall **111S** of the nuclear reactor pressure vessel **111**. As a result, the electrical connection between the EMP within the nuclear reactor pressure vessel **111** and the power supply **144** outside of the nuclear reactor pressure vessel **111** may be accomplished with the opening **182** (e.g., penetration) through the nuclear reactor pressure vessel **111** sidewall.

(53) While FIG. **1** illustrates the power supply conductor **180** extending through the opening **182** and further extending to the power supply **144**, it will be understood that the power supply conductor **180** may terminate at any point outside the nuclear reactor pressure vessel **111** between opening **182** and the power supply **144**, and the power cable **146** may extend out of the termination end of the power supply conductor **180** and continue to extend from the end of the power supply conductor **180** to the power supply **144**.

(54) The nuclear plant **100** includes an intermediate coolant loop **160**, also referred to herein as a secondary coolant loop, secondary loop, or the like. The intermediate coolant loop **160** includes a flow of coolant circulating through lines **161** between the primary heat exchanger **114** and an intermediate heat exchanger **162**. The intermediate coolant loop **160** may transfer core-rejected heat from the liquid metal coolant **190** circulating through the primary coolant loop **119** to a process fluid circulating through the power generation loop **170** via heat transfer at the intermediate heat exchanger **162**. In some example embodiments, the coolant circulating through the intermediate coolant loop includes a liquid metal coolant. The liquid metal coolant circulating through the intermediate coolant loop may be similar or different in composition relative to a liquid metal coolant **190** circulating through the primary coolant loop **119**.

(55) The nuclear plant **100** includes a power generation loop **170** configured to circulate a process fluid that receives heat from the intermediate coolant loop **160** via heat exchanger **162** and performs work, including driving a turbine. The turbine may operate an electrical power generator.

The process fluid may include water in one or more various phases. In some example embodiments, the power generation loop **170** comprises a steam generator device in which the intermediate heat exchanger **162** is at least partially located, and the heat exchanger **162** is configured to transfer heat from the coolant circulating through the intermediate coolant loop **160** to water located in the steam generator to vaporize the water and generate steam. The generated steam may be used to perform work, including driving a turbine connected to an electrical generator to generate electrical power.

(56) In some example embodiments, a nuclear reactor includes one or more control systems configured to monitor and/or control operation of the EMP **120**, including controlling the supply of electrical power (e.g., magnitude, frequency, etc.) to the induction coils within the EMP **120** in order to adjustably control the flow (e.g., the flow rate, which may be the mass flow rate and/or the volumetric flow rate) of liquid metal coolant **190** within the nuclear reactor **110**, the performance of the nuclear reactor **110**, and/or the operational efficiency of the nuclear reactor **110**. As shown in FIG. **1**, the nuclear reactor **110** may include an EMP control system **150**. The EMP control system **150** may be communicatively coupled **151**, via one or more communication lines, power transmission lines, etc., to the power supply **144**. In some example embodiments, the EMP control system **150** may be communicatively coupled, via one or more communication lines, power transmission lines, etc., to one or more sensor devices (e.g., a sensor, which may be one or more flowmeters such as one or more Venturi flow meters that may be configured to generate sensor data indicating a flow rate of liquid metal coolant **190** through the suction line **121**, return line **124**, and/or the EMP **120**, one or more pressure sensors that may be configured to generate sensor data indicating a pressure of liquid metal coolant **190** at one or more locations in the suction line **121**, return line **124**, and/or the EMP **120**, or the like) and/or devices within the nuclear reactor pressure vessel **111**, including for example the EMP **120**, but example embodiments are not limited thereto.

(57) The EMP control system **150** may, in some example embodiments, be coupled to one or more sensor devices (e.g., a sensor, which may be one or more flowmeters such as one or more Venturi flow meters that may be configured to generate sensor data indicating a flow rate of liquid metal coolant **190** through the suction line **121**, return line **124**, and/or the EMP **120**, one or more pressure sensors that may be configured to generate sensor data indicating a pressure of liquid metal coolant **190** at one or more locations in the suction line **121**, return line **124**, and/or the EMP **120**, or the like) configured to generate sensor data associated with one or more of the power supply **144**, the EMP **120**, or the like.

(58) The EMP control system **150** may monitor the operation of the EMP **120**, based on monitoring information associated with the power supply **144**, one or more sensor devices (which may be one or more flowmeters such as one or more Venturi flow meters that may be configured to generate sensor data indicating a flow rate of liquid metal coolant **190** through the suction line **121**, return line **124**, and/or the EMP **120**, one or more pressure sensors that may be configured to generate sensor data indicating a pressure of liquid metal coolant **190** at one or more locations in the suction line **121**, return line **124**, and/or the EMP **120**, or the like), the EMP **120**, etc. For example, the EMP control system **150** may receive sensor data generated by one or more sensor devices, where the sensor data may include information indicating a flow of electrical power from a given power supply to a given multistage EMP **120**. In another example, the EMP control system **150** may receive sensor data generated by one or more sensor devices, where the sensor data may include information indicating a strength of a magnetic field generated by induction coils of a given EMP **120**.

(59) The EMP control system **150** may be configured to control operation of an EMP **120**, for example to control the flow rate of liquid metal coolant through the EMP **120**, based on independently controlling and/or adjusting the supplying of electrical power by the power supply **144**. For example, where the EMP **120** includes a plurality of induction coils that are electrically connected to the power supply **144** via a power cable **146**, the EMP control system **150** may

independently control and/or adjust the electrical power (e.g., the polyphase electrical power) supplied by the power supply **144** to control the EMP **120**. Such control of the power supply **144** may include causing the power supply **144** to initiate a supply of polyphase electrical power to the induction coils of the EMP **120** via the power cable **146**, causing the power supply **144** to adjust a frequency and/or current of the electrical power supplied by the power supply **144**, and/or causing the power supply **144** to inhibit a supply of electrical power to the electrically connected induction coils of the EMP **120** via the power cable **146**. Such control may be implemented based on the EMP control system **150** generating a control signal and transmitting the control signal to the power supply **144**, based on the EMP control system **150** executing code stored on a memory.

(60) The EMP control system **150**, in some example embodiments, includes one or more computer systems. A computer system may include one or more instances of circuitry. The one or more instances of circuitry may include one or more processor devices (“processors”) coupled to one or more instances (e.g., articles, units, etc.) of memory. The one or more processors may include one or more central processor units (CPUs). The one or more processors may be configured to implement the EMP control system. For example, the one or more instances of memory (e.g., one or more memories) may include a non-transitory computer-readable medium storing a program of instructions (e.g., a solid state drive), and the one or more processors may include processing circuitry configured to execute the program of instructions stored on the non-transitory computer-readable medium to perform one or more operations of any of the methods according to any of the example embodiments.

(61) In some example embodiments, an EMP **120** provides improved flexibility and control over the liquid metal coolant flow rate in the primary coolant loops **119**, as the EMP control system **150** can apply more flexible control over the flow rate based on controlling the EMP **120** based on controlling the polyphase electrical power that is supplied by the power supply **144** to the separate induction coils of the EMP **120**. Various configurations (e.g., parameters) of polyphase electrical power supplied to the EMP **120** may increase the range of operational states of the EMP **120** that can be achieved by the EMP control system **150**, including an increased range (e.g., increased quantity) of separate, discrete flow rates of the liquid metal coolant **190** that can be induced by the EMP **120**. As a result, operational performance and/or efficiency of the primary coolant loop **119**, and thus the nuclear reactor **110** and nuclear plant **100** as a whole, may be improved based on the improved control over the liquid metal coolant **190** flow that is enabled by the EMP **120**.

(62) In some example embodiments, and as described herein the EMP **120** may be self-cooling and configured to reject heat therefrom without including an additional and/or separate coolant circulating through an interior of the EMP **120**. For example, the EMP **120** may be configured to conduct heat generated by internal components thereof (e.g., stators, induction coils, etc.) to a flow conduit (e.g., flow annulus) through which the liquid metal coolant **190** flows in the EMP **120**, so that the liquid metal coolant **190** absorbs the conducted heat and remove the heat from the EMP **120** when the liquid metal coolant **190** exits the EMP **120** via the outlet **123**.

(63) In some example embodiments, the intermediate coolant loop **160** includes one or more EMPs **120** which are illustrated to be included in the primary coolant loop **119**. An EMP **120** included in the intermediate coolant loop **160** may be configured to operate similarly to the EMP **120** included in the primary coolant loop **119**. A set of one or more EMPs **120** included in the intermediate loop may be located internal or external to the nuclear reactor pressure vessel **111**.

(64) As referred to herein, the liquid metal coolant may include one or more various liquid metal substances, including one or more of sodium, mercury, lead, bismuth, or tin. The one or more liquid metal substances may be conductive metal substances, such that an EMP **120** is configured circulate the liquid metal coolant.

(65) FIG. 2A is a perspective view of a liquid metal-cooled nuclear reactor, according to some example embodiments. FIG. 2B is a plan view of a liquid metal-cooled nuclear reactor, according to some example embodiments. The nuclear reactor **110** illustrated in FIGS. 2A-2B may be

included in any of the embodiments of nuclear reactors included herein, including the nuclear reactor **110** shown in FIG. 1.

(66) As shown in FIGS. 2A-2B, a nuclear reactor **110** may include a nuclear reactor pressure vessel **111** and may further include, within the nuclear reactor pressure vessel **111**, a set of multiple EMPs **120**, although it will be understood that in some example embodiments only a single EMP **120** may be included within the nuclear reactor pressure vessel **111**. As shown in FIGS. 2A-2B, where the nuclear reactor **110** includes multiple EMPs **120**, the EMPs **120** may be coupled in parallel to separate, parallel return lines **124** and may be configured to operate in parallel in the primary coolant loop **119** such that each EMP **120** may induce parallel flows of separate portions of the liquid metal coolant **190** through the primary coolant loop **119**.

(67) Each of the EMPs **120** shown in FIGS. 2A-2B may be structurally identical or different from each other. For example, the EMPs **120** may have identical configurations of induction coils, component structures, and/or component intrinsic properties. In some example embodiments, the EMPs **120** may have different configurations of induction coils, component structures, and/or component intrinsic properties.

(68) FIG. 3A is a perspective view of an EM Pump (EMP), according to some example embodiments. FIG. 3B is a perspective cross-sectional view along cross-sectional view line IIIB-IIIB' shown in FIG. 3A, according to some example embodiments. FIG. 4A is a cross-sectional view of the EMP of FIG. 3A along cross-sectional view line IVA-IVA' shown in FIG. 3A, according to some example embodiments. FIG. 4B is a cross-sectional view of the EMP of FIG. 4A along cross-sectional view line IVB-IVB' shown in FIG. 3A, according to some example embodiments. FIG. 4C is a cross-sectional view of the EMP of FIG. 4A along cross-sectional view line IVC-IVC' shown in FIG. 3A, according to some example embodiments. FIG. 4D is a cross-sectional view of the EMP of FIG. 3A along cross-sectional view line IVA-IVA' shown in FIG. 3A, according to some example embodiments.

(69) The EMP **120** shown in FIGS. 3A-4C and the EMP **120** shown in FIG. 4D may be included in any of the EMPs **120** included herein, including the one or more EMPs **120** illustrated in FIG. 1 and/or FIGS. 2A-2B. While the EMPs **120** shown in FIGS. 3A-4D may be an ALIP, example embodiments of the EMP are not limited to an ALIP and may include any type of EMP.

(70) The EMP **120** shown in FIGS. 3A-4C is illustrated as a dual-stator EMP, but example embodiments are not limited thereto and the description herein with regard to any EMP **120** and any portion thereof may be applied to any EMP **120** having more or fewer than two stators, such as the single-stator EMP shown in FIG. 4D.

(71) Referring to FIGS. 3A-4D, an EMP **120** may include a pump casing **302** (also referred to as an outer housing, outer casing, casing structure, etc.) having a central longitudinal axis and extending in a longitudinal direction. As shown in FIGS. 3A-3B, the pump casing **302** may partially or fully define (e.g., at least partially define) an interior space (e.g., interior **380**) of the EMP **120**. As further shown, the central longitudinal axis of the pump casing **302** may be paraxial to and/or may be coaxial with (e.g., may be the same as and/or may at least partially define) the longitudinal axis **306** of the EMP **120**.

(72) While the pump casing **302** may include one or more structures (e.g., one or more pieces of material) and/or may be open at the opposite longitudinal ends of the EMP **120**, it will be understood that in some example embodiments the pump casing **302** may include one or more structures which may partially or fully seal the opposite longitudinal ends of the interior space, except for openings in the pump casing **302** that define the inlet **122** and outlet **123** of the EMP **120**. For example, as shown in at least FIGS. 3A-3B, 4A, and 4D, the pump casing **302** may include an outer sidewall structure **302-1**, which may be a hollow cylinder structure, and which may at least partially define an interior **380** of the EMP **120** as a hollow cylindrical volume. The pump casing **302** may further include respective ring-shaped end structures **302-2** that at least partially structurally enclose the inlet-side longitudinal end of the EMP **120** and/or the outlet-side

longitudinal end of the EMP **120**, except for one or more openings to an inlet-side longitudinal end of the flow annulus **312** and/or an outlet-side longitudinal end of the flow annulus **312**, where the one or more openings (e.g., one or more arcuate and/or annular openings) at least partially define the inlet **122** into the flow annulus **312** and/or the outlet **123** of the flow annulus **312** and thus into and/or out of the EMP **120**. While the end structures **302-2** are shown as being separate structures (e.g., separate pieces of material) from the outer sidewall structure **302-1**, example embodiments are not limited thereto and in some example embodiments the end structures **302-2** and the outer sidewall structure **302-1** may each include separate portions of a single, unitary piece of material. In some example embodiments, the end structures **30-2** may be omitted from the pump casing **302**. As shown in at least FIGS. **3A-3B**, the pump casing **302** (e.g., at least the outer sidewall structure **302-1** may have a longitudinal axis extending in a longitudinal direction that at least partially defines (e.g., is coaxial with, is the same as, etc.) the longitudinal axis **306** of the EMP **120**.

(73) Still referring to at least FIGS. **3A-3B**, **4A**, and **4D**, the pump casing **302** may include an inner sidewall structure **302-3** that, collectively with the outer sidewall structure **302-3**, at least partially define an outer annular space **304** extending coaxially with the longitudinal axis **306**. The outer annular space **304** may include an empty space and/or may include one or more materials, such as one or more thermal insulation materials, one or more electrical insulation materials, or the like. In some example embodiments, the inner sidewall structure **302-3** may be omitted. In some example embodiments, the pump casing **302** may comprise the outer sidewall structure **302-1** alone or in combination with one or more end structures **302-2**. In some example embodiments, the inner sidewall structure **302-3**, the end structures **302-2**, and the outer sidewall structure **302-1** may include separate pieces of material and/or may each include separate portions of a single, unitary piece of material.

(74) The pump casing **302**, the inlet-side structure **302-1**, and/or the outlet-side structure **302-2**, may comprise one or more metal materials, for example stainless steel (e.g., 304 stainless steel), carbon steel, or the like.

(75) As shown in FIGS. **3A-3B**, an EMP **120** may include concentric flow ducts **310**, extending coaxially with the longitudinal axis **306** and collectively defining a flow annulus **312** extending coaxially with the longitudinal axis **306** along the length (e.g., the entire length as shown in FIG. **3A**) of the EMP **120**. As shown, the concentric flow ducts **310** may include an inner flow duct **310-1** and an outer flow duct **310-2**, each of which may be a cylindrical structure (e.g., a cylindrical tube, a hollow cylinder structure, or the like), although example embodiments are not limited thereto. As shown, an outer surface **310-1os** of the inner flow duct **310-1** and an inner surface **310-2is** of the outer flow duct **310-2** collectively define the flow annulus **312** as an annular space, or “annulus,” between these surfaces. As shown in FIGS. **3A-3B**, the concentric flow ducts **310** (also referred to herein as concentric annular walls) may each be a cylindrical tube, but example embodiments are not limited thereto.

(76) Still referring to FIGS. **3A-3B**, the EMP **120** may include a plurality of induction coils **320** (which may include, for example coils of wound copper wire) within the interior space of the EMP **120**. As shown, each induction coil **320** surrounds the longitudinal axis **306** and has a central axis that is coaxial with the longitudinal axis **306**. As shown in at least FIGS. **3B**, **4A**, and **4D**, the induction coils **320** are spaced apart from each other (e.g., isolated from direct contact with each other) in the longitudinal direction extending paraxial with the longitudinal axis **306**. In some example embodiments, the induction coils **320** may be referred to as “solenoids” of a stator of the EMP **120**. The induction coils **320** may each comprise one or more conductive materials (e.g., windings of one or more conductive materials), including copper, silver, or the like.

(77) As further shown in FIGS. **3A-3B**, **4A**, **4B**, and **4D**, the EMP **120** may include stators **322**, including an outer stator **322-1** that is located radially distal to the longitudinal axis **306** in relation to the outer flow duct **310-2** and an inner stator **322-2** that is located radially proximate to the longitudinal axis **306** in relation to the inner flow duct **310-1**. The stators **322** comprise one or more

magnetic materials, for example magnetic iron. The outer stator **322-1** and the inner stator **322-2** may comprise a same material composition or different material compositions. For example, the outer stator **322-1** and the inner stator **322-2** may each comprise iron (e.g., magnetic iron), but example embodiments are not limited thereto. For example, at least one of the outer stator **322-1** or the inner stator **322-2** may at least partially comprise stainless steel in some example embodiments. (78) While each of the outer stator **322-1** and the inner stator **322-2** are shown to be a single structure, at least one of the outer stator **322-1** or the inner stator **322-2** may comprise a plurality of stator structures (e.g., block structures), for example eight block structures. The block structures may be linear beam or rod-shaped structures (e.g., linear beam or rod-shaped block structures) that each extend paraxial to the longitudinal axis **306** along the length of the EMP **120** and may be at least partially spaced apart azimuthally around the longitudinal axis **306**. In some example embodiments, the outer stator **322-1** may comprise one or more arcuate structures, or a single cylindrical structure that extends around some or all of the circumference of the outer surface **310-2os** of the outer flow duct **310-2**. However, an outer stator **322-1** that includes multiple, spaced-apart block structures may provide weight savings in the EMP **120** in relation to an outer stator **322-1** that is a single-piece cylindrical structure.

(79) As shown in FIGS. **3A-3B**, **4A-4B**, and **4D**, in some example embodiments, the inner stator **322-2** may comprise a singular cylindrical structure that extends around the longitudinal axis **306** and further extends in the longitudinal direction coaxially with the longitudinal axis **306**.

(80) Referring to FIGS. **3A-4D**, the EMP **120** may include a plurality of induction coils **320** which may include at least one of inner induction coils **320-2** located within a central region **382** of the EMP **120** interior **380** that is at least partially defined by an inner surface **310-1is** of the inner flow duct **310-1**, or outer induction coils **320-1** located within an annular region **384** of the EMP **120** interior **380** that is at least partially defined between an outer surface **310-2os** of the outer flow duct **310-2** and an inner surface **302** is of the pump casing **302**.

(81) As shown in at least FIGS. **3B** and **4A** and **4D**, the outer stator **322-1** may include longitudinally-spaced tooth structures **324-1** configured to receive and enclose separate induction coils **320** (e.g., outer induction coils **320-1**) therebetween in at least the longitudinal direction paraxial to the longitudinal axis **306** and a radial direction distally from the longitudinal axis **306**. As shown in at least FIGS. **3B** and **4D**, in example embodiments where the EMP **120** is a double-stator EMP having inner induction coils **320-2**, the inner stator **322-1** may include longitudinally-spaced tooth structures **324-2** configured to receive and enclose separate inner induction coils **320-2** therebetween in at least the longitudinal direction paraxial to the longitudinal axis **306** and a radial direction distally from the longitudinal axis **306**. As shown in at least FIG. **4D**, in example embodiments where the EMP **120** is a single-stator EMP **120**, the inner stator **322-2** may be a hollow cylindrical structure.

(82) As shown, each tooth structure **324-1** or **324-2** may define, together with a proximate flow duct **310**, an annular space **332** in which a separate induction coil **320** may be located. A remainder of the annular space **332** not occupied by the induction coil **320** may include an electrical insulation material **336** that surrounds the induction coil **320**. Such electrical insulation material **336** may partially or completely fill the remainder of the annular space **332** not occupied by the induction coil **320**. Such electrical insulator material **336** may include any known electrical insulation material, including for example, polyvinyl chloride (PVC). The electrical insulation material **336** may be thermally conductive and may be further configured to conduct heat from the induction coils **320** and/or the stators **322** to the flow annulus **312** via the flow ducts **310** to facilitate self-cooling of the EMP **120** based on rejecting internally-generated heat to the liquid metal coolant **190** flowing through the flow annulus **312**. For example, in some example embodiments, the electrical insulation material **336** may include any known electrically insulating, thermally conductive material, including for example Mica (Phyllosilicate)). The electrical insulation material **336** may conduct heat generated at any of the induction coils **320** and/or the stators **322** to the flow ducts

310 to enable the heat to be conducted through the flow ducts **310** into the flow annulus **312** to be absorbed by liquid metal coolant **190** flowing therethrough, thereby enabling self-cooling of the EMP **120** internal components via heat rejection to the liquid metal coolant **190** flowing therethrough and exiting the EMP **120** via the outlet **123**.

(83) Still referring to FIGS. **3A-3B**, **4A**, and **4D**, in some example embodiments, the EMP **120** may include a central core **326** (which may comprise a material such as stainless steel, magnetic iron, or the like) which may be a hollow cylindrical structure having one or more inner cylindrical sidewall surfaces that define a central space **328** (e.g., central void) that extends coaxially with the longitudinal axis **306** (e.g., located at a radial center of the EMP **120**). In some example embodiments, the central core **326** may be omitted, such that the inner stator **322-2** includes one or more inner cylindrical sidewall surfaces that define the central space **328** (e.g., central void) as described herein. The central space **328** may be configured to accommodate (e.g., house) cabling for the EMP **120**, may be configured to direct a heat exchange fluid (e.g., coolant gas, such as helium) therethrough to provide cooling to the EMP **120**, or the like. In some example embodiments, the central core **326** or the inner stator **322-2** may be a solid cylindrical structure that occupies some or all of the space defined by the inner diameter of the inner flow duct **310-1**, such that the central space **328** may be omitted from the EMP **120**.

(84) In some example embodiments, the outer annular space **304** (e.g., an outer void) at least partially defined by the outer sidewall structure **302-1** may extend around the outer stator **322-1** and induction coils **320** (e.g., radially distally therefrom) and between the inner surface **302is** of the pump casing and outer surfaces of the induction coils **320** and/or outer stator **322-1**. The outer annular space **304** may be an empty space and/or may be at least partially filled with a material (e.g., nitrogen gas, insulation material, circuitry, or the like).

(85) Still referring to FIGS. **3A-3B**, the inner flow duct **310-1**, inner stator **322-2**, central core **326**, and/or any structures located radially inward from the inner flow duct **310-1** in the EMP **120** may be structurally connected to the outer flow duct **310-2**, outer stator **322-1**, induction coils **320**, pump casing **302**, and/or any structures located radially outward from the outer flow duct **310-2** in the EMP **120** via one or more support ribs (also referred to as “stilts”) extending radially outward between the concentric flow ducts **310** in the flow annulus **312** to structurally connect the inner and outer flow ducts **310-1** and **310-2** to each other, thereby structurally coupling the central/inner portion of the EMP **120** to the outer portion of the EMP **120** and thus structurally stabilizing and supporting the central/inner portion (e.g., inner flow duct **310-1**, inner stator **322-2**, inner induction coils **320-2**, etc.) in relation to the outer portion (e.g., outer flow duct **310-2**, outer stator **322-1**, outer induction coils **320-1**, pump casing **302**, etc.). In some example embodiments, support ribs may further extend through the outer annular space **304** between the outer stator **322-1** and the pump casing **302** to structurally stabilize and support at least the outer stator **322-1** in relation to the pump casing **302**. In some example embodiments, support ribs may be omitted from the EMP **120**. The pump casing **302** may include an inlet-side end structure **302-2** and an outlet-side end structure **302-2** which are coupled to the outer sidewall structure **302-1** of the pump casing **302** that has the longitudinal axis **306**, where end structures **302-2** may be structurally connected to one or both of the outer portion of the EMP **120** (e.g., the outer flow duct **310-2**, outer stator **322-1**, and/or outer induction coils **320-1**) and the central/inner portion of the EMP **120** (e.g., the inner flow duct **310-1**, inner stator **322-2**, inner induction coils **320-2**, and/or central core **326**) and thus the inlet-side end structure **302-2** and outlet-side end structure **302-2** may structurally couple, stabilize, and support the outer and central/inner portions of the EMP **120** in relation to each other.

(86) Still referring to FIGS. **3A-4D**, the EMP **120** may be configured to pump (e.g., induce flow) of liquid metal coolant **190** through the flow annulus **312** based on applying electromagnetic forces on the flowing liquid metal coolant **109** through the length (e.g., longitudinal direction extending paraxially to the longitudinal axis **306**) of the EMP **120**. This may be performed based on applying (e.g., supplying) electrical power (e.g., polyphase electrical power) to the induction coils **320** at

particular frequencies and phase angles. For example, polyphase electrical power as described herein may include AC power, for example three phase AC power, which may be applied at specified AC frequencies and phase angles to induction coils **320** that surround the flow annulus **312**.

(87) For example, referring to FIG. **4D**, the induction coils **320** may include multiple separate sets, or “slots” **330-1** to **330-3** of induction coils **320**, a fixed phase of polyphase electrical power from a particular, electrically connected polyphase power source may be applied to each induction coil **320**, and the phase of a given induction coil in a given set (e.g., **330-1**, **330-2**, or **330-3**) may be the phase of the previous longitudinally adjacent induction coil **320** (in a direction opposite the longitudinal direction paraxial to the longitudinal axis **306**), plus 60 or 120 degrees, to allow for a sequence, in the longitudinal direction, of induction coils **320**, to complete an AC cycle of 360 degrees. The collection of induction coils **320** that complete this 360 degree AC cycle is called a pole (T) or a “slot”. The length of a pole is called the pole pitch (T).

(88) The supply of polyphase electrical power to the induction coils **320** may be controlled, for example based on controlling a frequency, power amplitude (e.g., current and/or voltage), and/or phase angles of the supplied polyphase electrical power, in order to cause a specific pressure rise in the liquid metal coolant **190** in the flow annulus **312** along the length of the EMP **120** (e.g., in the longitudinal direction that is paraxial to the longitudinal axis **306**). With the electrical phase of each induction coil **320** being fixed based on connection to a separate wire of a particular power cable **146**, and the internal components being stationary within the pump casing **302**, the pressure rise may be controlled based on controlling and/or adjusting the frequency, power amplitude (e.g., current and/or voltage), and/or phase angles of the polyphase electrical power supplied from an electrically connected polyphase power supply (e.g., power supply **144**) to the induction coils **320**.

(89) Given a volumetric flow rate, the applied current, voltage, and/or frequency of polyphase electrical power (e.g., three-phase AC power) supplied to a given set of induction coils **320** may be adjusted to provide a desired pressure rise in the liquid metal coolant **190** in a EMP **120**. This is because the current and frequency changes of the power supplied by a polyphase power supply (e.g., power supply **144**) are applied to every induction coil **320** that is electrically connected to that same polyphase power supply. Accordingly, the flow operating range and sensitivity of an EMP **120** may be therefore based on the polyphase power supply(ies) to which the induction coils **320** are electrically connected via a power cable **146**.

(90) Still referring to FIGS. **4D**, while the induction coils **320** are shown to include three “slots” **330-1** to **330-3**, it will be understood that greater or fewer repeating “slots” may be present in the EMP **120**, such that the number of slots associated with a given phase may be a plurality of “N” slots **330-1** to **330-N** of induction coils **320**, “N” being any positive integer.

(91) Still referring to FIG. **4D**, the induction coils **320** may be connected via a polyphase power cable **146** (e.g., a three-phase conductor delivering phases A, B, C of three-phase AC power from a polyphase power supply **144**) and thus may be controlled based on independently controlling the power supplied by the polyphase power supply **144**. Referring to FIGS. **3A-4A**, in a dual-stator EMP **120**, the inner and outer induction coils **322-2** and **322-1** at a given longitudinal position along the longitudinal axis **306** may be coupled to the same or separate phases of polyphase electrical power provided by a polyphase power supply.

(92) Referring generally to FIGS. **3A-4D**, polyphase electrical power (e.g., three phase AC power) may be applied to the induction coils **320** of the EMP **120** where the phase and current directions for each induction coil **320** are fixed, or predetermined, so that the application of polyphase electrical power to the induction coils **320** causes the induction coils **320** to generate a travelling electromagnetic (EM) wave that induces a continuous flow of liquid metal coolant **190** located in the flow annulus **312** in the longitudinal direction paraxial to the longitudinal axis **306** from the inlet **122** to the outlet **123**. The polyphase electrical power applied to one or more sets **330-1** to **330-3** of induction coils **320**, may have a particular frequency and power amplitude (e.g., current

and/or voltage) which may be set (e.g., controlled and/or adjusted) by EMP control system **150** via controlling the power supply **144** that is electrically connected to the induction coils **320**. Accordingly, the frequency and/or power amplitude (e.g., voltage and/or current) of the polyphase electrical power supplied by the power supply **144** may be controlled and/or adjusted (e.g., initiated, adjusted, and/or inhibited). Such control and/or adjustment of the frequency and/or power amplitude of polyphase electrical power applied to one or more sets of induction coils **320** of the EMP **120** changes the performance of the multistage ALIP in pumping (e.g., inducing flow of) liquid metal coolant **190** therethrough.

(93) Still referring to FIGS. **4A-4D**, in some example embodiments, at least one flow duct of the inner flow duct **310-1** or the outer flow duct **310-2** may include a gamma shielding material. The gamma shielding material may be configured to block gamma rays **460** (also referred to herein as simply gammas) emitted from the liquid metal coolant **190** flowing through the flow annulus **312** from entering the interior **380** of the EMP **120** that is at least partially defined by the pump casing **302** and which is external to the flow annulus **312** (e.g., the central interior space **382** at least partially defined by an inner surface **310-1is** of the inner flow duct **310-1** and/or the annular interior space **384** at least partially defined by an outer surface **310-2os** of the outer flow duct **310-2** and an inner surface **302is** of the pump casing **302**). For example, the liquid metal coolant **190** that is drawn into the flow annulus **312** via an inlet **122** of the EMP **120** may be at a relatively high temperature, for example an inlet temperature of approximately 350° C., and may be strongly activated, for example a liquid sodium coolant including Na-24. Such a liquid metal coolant **190**, being strongly activated and at a relatively high temperature, may emit gamma rays **460** from the liquid metal coolant **190**. Such gamma rays **460** may have the potential to wear and/or damage (e.g., degrade and/or activate) internal components of the EMP **120**, including any of the stators **322**, induction coils **320**, conductive circuits, insulation such as electrical insulation material **336**, or the like. A gamma shielding material in at least one flow duct of the inner flow duct **310-1** or the outer flow duct **310-2** may block such gamma rays **460** in the flow annulus **312** from entering the interior **380** of the EMP **120** (e.g., the central interior space **382** at least partially defined by the inner surface **310-1is** of the inner flow duct **310-1** and/or the annular interior space **384** at least partially defined by the outer surface **310-2os** of the outer flow duct **310-2** and the inner surface **302is** of the pump casing **302**) from the flow annulus **312**.

(94) As described herein, “blocking” gamma rays, also referred to herein as “attenuation” and/or “shielding” of gamma rays, by a gamma shielding material may include reducing, minimizing, or preventing penetration of incident gamma rays through the gamma shielding material so as to exit the gamma shielding material (e.g., to pass entirely through the gamma shielding material) and be incident on (e.g., contact) another material, element, space, or the like subsequently to exiting the gamma shielding material. As described herein, a gamma shielding material may “block” (e.g., “attenuate”) gamma rays (also referred to herein as gamma radiation) based on various mechanisms. For example, a gamma shielding material may “block” (e.g., “attenuate”) gamma rays (e.g., incident gamma rays that are incident on the gamma shielding material) at least partially based on photoelectric absorption of gamma rays by the gamma shielding material, including a complete transfer of energy from an incident gamma ray photon to an atomic electron of the gamma shielding material. In another example, a gamma shielding material may “block” (e.g., “attenuate”) gamma rays (e.g., incident gamma rays that are incident on the gamma shielding material) at least partially based on scattering (e.g., Compton scattering) of gamma rays by the gamma shielding material, including a transfer of part of the energy of an incident gamma ray photon to an atomic electron of the gamma shielding material, such that the gamma ray photon may undergo further scattering or absorption interactions shielding material and/or emerge from the shielding material with diminished energy. In another example, a gamma shielding material may “block” (e.g., “attenuate”) gamma rays (e.g., incident gamma rays that are incident on the gamma shielding material) at least partially based on pair production, including interaction of a relatively

high-energy (e.g., at least 1022 keV) incident gamma ray photon with the nucleus of an atom of the gamma shielding material which results in the creation of beta particle and a positron that then undergoes an annihilation reaction with an electron to produce two lower-energy (e.g., 511 keV) gamma rays.

(95) In example embodiments where at least one flow duct of the inner flow duct **310-1** or the outer flow duct **310-2** includes a gamma shielding material, the gamma shielding material may reduce, minimize, or prevent such gamma rays **460** from passing through the at least one flow duct to reach internal components of the EMP **120** to wear and/or damage such components. As described herein, a gamma shielding material, in any example embodiments (e.g., at least one of the gamma shielding materials **414**, **424** as shown in FIG. **4B**), may include one or more of Lead, Iron and Steel-Alloys, Tin, Bismuth, Tungsten and its Alloys, Water, or Borated Paraffin or Polyethylene. In some example embodiments, the at least one flow duct may include the gamma shielding material as a filler material within an annular duct space defined between concentric cylindrical duct walls. The concentric cylindrical duct walls may provide structural support for the at least one flow duct, and the gamma shielding material provided as a filler material (e.g., filler) therebetween may or may not provide structural integrity of the at least one flow duct. In some example embodiments, the at least one flow duct may comprise the gamma shielding material in a structure having a surface at least partially defining the flow annulus **312**, such that at least some of the gamma shielding material may be directly exposed to the flow annulus **312**. Restated, where at least one flow duct **310** includes a material at least partially defining an inner surface or an outer diameter surface of the flow annulus **312** (e.g., inner surface **310-2is** or **310-1os**, respectively), the material may include the gamma shielding material.

(96) In some example embodiments, the at least one flow duct may comprise a single piece of material that includes the gamma shielding material alone or in combination with one or more additional materials (e.g., a mixture of at least one of the aforementioned gamma shielding materials and stainless steel).

(97) In some example embodiments, at least one flow duct of the inner flow duct **310-1** or the outer flow duct **310-2** may include concentric cylindrical duct walls defining a duct annulus between the concentric cylindrical duct walls, and a gamma shielding material may be located within the duct annulus, for example as a filler material in the duct annulus. For example, as shown in at least FIG. **4B**, the inner flow duct **310-1** may include concentric cylindrical duct walls **410-1** and **410-2** collectively defining an inner duct annulus **412** between respective outer and inner surfaces **410-1os** and **410-2is** thereof, where the inner surface **410-1is** of the inner cylindrical duct wall **410-1** defines the inner surface of the inner flow duct **310-1**, and the outer surface **410-2os** of the outer cylindrical duct wall **410-2** defines the outer surface **310-1os** of the inner flow duct that at least partially defines the flow annulus **312** of the EMP **120**. As shown, a gamma shielding material **414** may be located (e.g., may partially or entirely fill) the inner duct annulus **412**, for example as a filler material partially or entirely filling the inner duct annulus **412**. As shown, the gamma shielding material **414** may be one or more pieces of material and may have an outer surface **414os** in contact with the inner surface **410-2is** of the outer cylindrical duct wall **410-2**, but example embodiments are not limited thereto. As shown, the gamma shielding material **414** may be one or more pieces of material and may have an inner surface **414is** in contact with the outer surface **410-1os** of the inner cylindrical duct wall **410-1**, but example embodiments are not limited thereto. While the gamma shielding material **414** may be provided as a filler material within the inner duct annulus **412**, example embodiments are not limited thereto. In some example embodiments, one or more of the cylindrical duct walls **410-1** or **410-2** may be omitted from the inner flow duct **310-1**, and in some example embodiments the gamma shielding material **414** may contribute to structural support and/or integrity of at least the inner flow duct **310-1**. In some example embodiments, the inner flow duct **310-1** may comprise a single piece of material that includes the gamma shielding material, alone or as a mixture of the gamma shielding material with one or more additional

materials (e.g., stainless steel).

(98) In another example, as shown in at least FIG. 4B, the outer flow duct **310-2** may include concentric cylindrical duct walls **420-1** and **420-2** collectively defining an outer duct annulus **422** between respective outer and inner surfaces **420-1os** and **420-2is** thereof, where the inner surface **420-1is** of the inner cylindrical duct wall **420-1** defines the inner surface of the outer flow duct **310-2** that at least partially defines the flow annulus **312** of the EMP **120**, and the outer surface **420-2os** of the outer cylindrical duct wall **420-2** defines the outer surface **310-2os** of the outer flow duct. As shown, a gamma shielding material **424** may be located (e.g., may partially or entirely fill) the outer duct annulus **422** and may be provided as a filler material partially or entirely filling the outer duct annulus **422**. As shown, the gamma shielding material **424** may be one or more pieces of material and may have an outer surface **424os** in contact with the inner surface **420-2is** of the outer cylindrical duct wall **420-2**, but example embodiments are not limited thereto. While the gamma shielding material **424** may be provided as a filler material within the outer duct annulus **422**, example embodiments are not limited thereto. As shown, the gamma shielding material **424** may be one or more pieces of material and may have an inner surface **424is** in contact with the outer surface **420-1os** of the inner cylindrical duct wall **420-1**, but example embodiments are not limited thereto. In some example embodiments, one or more of the cylindrical duct walls **420-1** or **420-2** may be omitted from the outer flow duct **310-2**, and in some example embodiments the gamma shielding material **424** may contribute to structural support and/or integrity of at least the outer flow duct **310-2**. In some example embodiments, the outer flow duct **310-2** may comprise a single piece of material that includes the gamma shielding material, alone or as a mixture of the gamma shielding material with one or more additional materials (e.g., stainless steel).

(99) In some example embodiments, at least one flow duct of the inner flow duct **310-1** or the outer flow duct **310-2** may include a material at least partially defining an inner surface **310-1os** or an outer surface **310-2is** of the flow annulus **312**, where the material includes the gamma shielding material. For example, in some example embodiments the outer cylindrical structure **410-2** and the gamma shielding material **414** may be replaced with a single cylindrical structure having an outer surface at least partially defining the outer surface **310-1os** of the inner flow duct **310-1** and including the gamma shielding material alone or in combination with another material, and the inner cylindrical structure **410-1** may be present or absent from the inner flow duct **310-1**. In another example, in some example embodiments the inner cylindrical structure **420-1** and the gamma shielding material **424** may be replaced with a single cylindrical structure having an inner surface at least partially defining the inner surface **310-2is** of the outer flow duct **310-2** and including the gamma shielding material alone or in combination with another material, and the outer cylindrical structure **420-2** may be present or absent from the outer flow duct **310-2**. As shown in at least FIG. 4B, each of the inner flow duct **310-1** and the outer flow duct **310-2** may include one or more gamma shielding materials. In some example embodiments, the inner flow duct **310-1** and the outer flow duct **310-2** may include a same or different gamma shielding materials. In some example embodiments, one of the inner flow duct **310-1** or the outer flow duct **310-2** does not include any gamma shielding material.

(100) Based on the EMP **120** including a gamma shielding material (e.g., **414** and/or **424**) in at least one flow duct of the inner flow duct **310-1** or the outer flow duct **310-2**, the EMP **120** may be configured to reduce, minimize, or prevent wear and/or damage to the EMP **120** (e.g., internal components thereof including the stators **322**, induction coils **320**, electrical insulation material **336**, or the like). As a result, the EMP **120** may be configured to reduce, minimize, or prevent expensive radiation testing, enable many flexible reactor designs since the EMP can be located anywhere in the reactor vessel, and enhance heat transfer between pump components and liquid metal coolant **190** (e.g., via thermally conductive electrical insulation material **336**) to enable self-cooling of the EMP. Additionally, the EMP having the gamma shielding material according to some example embodiments may be configured to be easily and quickly implemented without requiring

component program development or significant research efforts. Additionally, based on including gamma shielding material **414** and/or **424** in at least one flow duct in the EMP **120**, the EMP **120** may be configured to reduce, minimize, or prevent pump material degradation (e.g., wear) and/or damage due to radiation at elevated temperatures within an interior of the nuclear reactor pressure vessel **111**.

(101) While example embodiments shown in at least FIG. **4B** illustrate gamma shielding material being included in at least one flow duct **310** (also referred to herein as at least one duct) of the inner flow duct **310-1** or the outer flow duct **310-2**, example embodiments are not limited thereto, and in some example embodiments a gamma shielding material may be included in any of the components of the EMP **120** (e.g., included in the pump casing **302**, for example as a filler and/or as part of an alloy material at least partially comprising the pump casing **302**).

(102) Still referring to FIGS. **3A-4D**, in some example embodiments, the pump casing **302** may include a neutron absorber material. The neutron absorber material may be configured to absorb neutrons (e.g., ambient neutrons **470**) entering the pump casing **302** from an exterior of the EMP **120** (e.g., an ambient environment **450** that is external to the EMP **120**), thereby reducing, minimizing, or preventing wear and/or damage to the EMP **120** and/or any internal components thereof due to receiving ambient neutrons **470** from an ambient environment **450** that is at a relatively high temperature and high radiation environment within the nuclear reactor pressure vessel **111**. A neutron absorber material, in any example embodiments, may include one or more of Gadolinium, Cadmium, Boron, Boron Carbide, Gadolinium oxide, Hafnium Lithium, Tantalum, Europium, Gadolinium Stainless Steel, Hafnium, Silver, Xenon, or Indium. The neutron absorber material may be provided as a filler material within (e.g., partially or entirely filling) an annulus at least partially defined between concentric cylindrical casing walls, but example embodiments are not limited thereto. In some example embodiments, the neutron absorber material may partially or entirely comprise one or more structures of the pump casing **302** (e.g., the outer sidewall structure **302-1**, end structures **302-2**, and/or inner sidewall structure **302-3**), for example such that the pump casing **302** (e.g., the outer sidewall structure **302-1**) includes a material at least partially defining an outer surface **302os** of the pump casing **302** and thus an outer surface of the EMP **120** where the material includes the neutron absorber material, but example embodiments are not limited thereto. In some example embodiments, the neutron absorber material may be provided as an outer layer of material (e.g., a cylindrical jacket of neutron absorber material) on an outer surface **302os** of the pump casing **302**, but example embodiments are not limited thereto.

(103) In FIG. **4C**, a view of an outer sidewall structure **302-1** that includes neutron absorber material **434** is shown, but it will be understood that the view provided in FIG. **4C** and the structures of the outer sidewall structure **302-1** shown therein may be included in any portion of the pump casing **302**, including any portion of the end structure **302-2** and/or inner sidewall structures **302-3**.

(104) Referring to FIGS. **4A** and **4C**, in some example embodiments, at least a part of the pump casing **302** (e.g., the outer sidewall structure **302-1** as shown in FIG. **4C**) may include concentric cylindrical casing walls defining a casing annulus between the concentric cylindrical casing walls, and the neutron absorber material may be located within the casing annulus, for example as a filler material partially or entirely filling the casing annulus, although example embodiments are not limited thereto. For example, as shown in at least FIG. **4C**, at least the outer sidewall structure **302-1** of the pump casing **302** may include concentric cylindrical casing walls **430-1** and **430-2** collectively defining a casing annulus **432** between respective outer and inner surfaces **430-1os** and **430-2is** thereof, where the inner surface **430-1is** of the inner cylindrical casing wall **430-1** defines the inner surface **302is** of the portion of the pump casing **302** (e.g., an inner surface of the outer sidewall structure **302-1**), and the outer surface **430-2os** of the outer cylindrical casing wall **430-2** defines the outer surface **302os** of the portion of the pump casing **302** and thus may at least partially define an outer surface of the EMP **120** that is directly exposed to the ambient

environment **450** surrounding the EMP **120**.

(105) As shown, a neutron absorber material **434** may be located (e.g., may partially or entirely fill, as a filler material) the casing annulus **432**. As shown, the neutron absorber material **434** may be one or more pieces of material and may have an outer surface **434os** in contact with the inner surface **430-2is** of the outer cylindrical casing wall **430-2**, but example embodiments are not limited thereto. As shown, the neutron absorber material **434** may be one or more pieces of material and may have an inner surface **434is** in contact with the outer surface **430-1os** of the inner cylindrical casing wall **430-1**, but example embodiments are not limited thereto. In some example embodiments, one or more of the cylindrical casing walls **430-1** or **430-2** may be omitted from the portion of the pump casing **302**, such that the portion of the pump casing **302** (e.g., the outer sidewall structure **302-1** as shown) may be at least partially defined by and/or comprised of the neutron absorber material **434**. In some example embodiments, the portion of the pump casing **302** (e.g., the outer sidewall structure **302-1** as shown) may comprise a single piece of material that includes the neutron absorber material, alone or as a mixture of the neutron absorber material with one or more additional materials (e.g., stainless steel).

(106) The neutron absorber material **434** may be configured to absorb ambient neutrons **470** entering the EMP **120** from an exterior of the EMP **120**, for example an ambient environment **450** at least partially surrounding the EMP **120**. The ambient environment **450** may be a relatively high-temperature (e.g., at least 350C), high radiation environment, such that the ambient neutrons **470** may be relatively high-energy neutrons which may wear and/or damage (e.g., degrade and/or activate) internal components of the EMP **120** that the ambient neutrons **470** contact. The neutron absorber material **434** may absorb at least some or all of such ambient neutrons **470** to reduce, minimize, or prevent such ambient neutrons **470** from penetrating further into an interior **380** of the EMP **120** to contact internal components thereof. Accordingly, an EMP **120** may be configured to reduce, minimize, or prevent neutron exposure of internal EMP components to the ambient neutrons **470** of the ambient environment **450**, thereby improving the service life, performance, maintenance schedule, and/or decommissioning process for the EMP **120**.

(107) Based on the EMP **120** including the neutron absorber material **434** therein, the EMP **120** may be configured to be easily and quickly implemented without requiring component program development or significant research efforts. Based on including the neutron absorber material **434**, the EMP **120** may be configured to reduce, minimize, or prevent pump material degradation (e.g., wear) and/or damage due to neutron exposure to EM pump components from a high-temperature, high-radiation ambient environment **450**. An EMP **120** including the neutron absorber material **434** according to any of the example embodiments may have an extended lifetime while being located in the nuclear reactor pressure vessel **111**, may enable improved flexibility in reactor design since the EMP can be located closer to the reactor core, thus decreasing the cost of reactor vessel system, may enable reduction, minimization, or elimination of expensive irradiation testing to qualify insulation lifetime under temperature, voltage, and radiation conditions within an interior of a nuclear reactor, may reduce, minimize, or prevent neutron exposure to EM pump components at high temperatures to thereby would improve EMP reliability, may be implemented in various configurations of EMPs, including self-cooling EMPs, without limitation from design, size, or performance requirements, may maintain compatibility with other pump components and reactor structural materials in terms of thermophysical and neutronic properties, and may reduce, minimize, or prevent activation in pump components, which would considerably allow quick maintenance and less complicated pump decommissioning procedures.

(108) While example embodiments shown in at least FIG. **4C** illustrate neutron absorber material being included in at least a portion of the pump casing **302** (e.g., the outer sidewall structure **302-1**), example embodiments are not limited thereto, and in some example embodiments a neutron absorber material may be included in any of the components of the EMP **120** (e.g., included in at least one flow duct **310**, for example as a filler and/or as part of an alloy material at least partially

comprising the at least one flow duct).

(109) Still referring to FIGS. 4A, 4C, and 4D, in some example embodiments, the EMP 120 may include a neutron moderator material 452 on an outer surface 302os of the pump casing 302. The neutron moderator material 452 may at least partially surround, enclose, or the like some or all of the EMP 120, for example the neutron moderator material 452 may cover exposed outer surfaces 302os of the pump casing 302, with openings in the neutron moderator material 452 to enable power cable 146 to enter the EMP 120 and openings for the inlet 122 and the outlet 123 of the EMP 120. The neutron moderator material 452 may be provided as a jacket surrounding the outer surface 302os of the pump casing 302 and may be located as a filler material within a jacket of concentric cylindrical jacket walls (e.g., comprising stainless steel) defining a jacket annulus therebetween that may be at least partially filled by the neutron moderator material, although example embodiments are not limited thereto and in some example embodiments the neutron moderator material 452 may be provided as a single-material jacket at least partially surrounding the pump casing 302. A neutron moderator material, in any example embodiments, may include one or more of Graphite, Heavy water, Light water, Paraffin, polyethylene, concrete, or Beryllium.

(110) In some example embodiments, the neutron moderator material 452 may be configured be located between the neutron absorber material 434 and the ambient environment 450 and thus may be configured to slow down (e.g., moderate) ambient neutrons 470-1 received from the ambient environment 450 that is external to the EMP 120 such that the neutrons entering the pump casing 302 from the exterior of the EMP 120 (e.g., ambient environment 450) are moderated neutrons 470-2, and the neutron absorber material 434 included in the pump casing 302 (e.g., neutron absorber material 434 as shown in FIG. 4C) may be configured to absorb the moderated neutrons 470-2. Based on including a neutron moderator material 452 that is configured to moderate ambient neutrons 470-1 prior to the ambient neutrons reaching the neutron absorber material 434, the probability of absorption of the ambient neutrons by the neutron absorber material 434 may be improved, thereby further reducing, minimizing, or preventing neutron exposure by internal components of the EMP 120 (e.g., stators 322, induction coils 320, etc.).

(111) FIG. 5 is a flowchart illustrating a method for operating an EMP, according to some example embodiments. The method shown in FIG. 5 may be implemented with regard to any EMP according to any of the example embodiments. The method shown in FIG. 5 may be at least partially implemented by an EMP control system 150 such as the EMP control system 150 shown in FIG. 1 and with regard to one or more power supplies such as the power supply 144 shown in FIG. 1.

(112) As shown in FIG. 5, the method may include, at S502, initiating the supply of electric power (e.g., polyphase electric power) supplied to the EMP 120 (e.g., to the plurality of induction coils 320 thereof) from the power supply 144 (e.g., a polyphase power supply). As a result, at S504, the EMP 120 (e.g., the plurality of induction coils 320) operate to cause liquid metal coolant 190 to flow through the flow annulus 312, for example based on induction coils 320 generating one or more magnetic fields based on the received electrical power which causes the liquid metal coolant 190 to flow through the flow annulus 312. Operation S502 may include determining whether to initiate (e.g., turn on) a supply of polyphase electrical power the power supply 144. If so, at S502, a control signal may be generated and transmitted to the power supply 144 to cause the power supply 144 to initiate the supply of polyphase electrical power to the EMP 120. The control signal may be generated and transmitted by the EMP control system 150. The control signal may cause the power supply 144 to initiate a supply of polyphase electrical power having a particular (e.g., predetermined) frequency, power amplitude (e.g., voltage and/or current), phases, or the like.

(113) At S506, at least partially concurrently with the EMP 120 (e.g., the plurality of induction coils 320) operating to cause liquid metal coolant 190 to flow through the flow annulus 312, a gamma shielding material included in at least one of an inner flow duct 310-1 or an outer flow duct 310-2 of the EMP 120 may reduce, minimize, or prevent gamma ray 460 penetration from the

liquid metal coolant **190** that is in the flow annulus **312** to an interior **380** of the EMP **120** that is external to the flow annulus **312** (e.g., to the induction coils **320**, any stators included in the EMP **120**, any circuitry included in the EMP **120**, any conductive elements included in the EMP **120**, or the like). As a result, the gamma shielding material may reduce, minimize, or prevent any wear and/or damage of the EMP **120** and/or any portions thereof due to gamma rays **460** emitted from the liquid metal coolant **190** flowing through the flow annulus **312**. Thus, the gamma shielding material in at least one of the inner flow duct **310-1** or the outer flow duct **310-2** may provide improved performance and/or reliability of the EMP **120**, extended service life of the EMP **120**, and reduced frequency of repair, maintenance, and/or replacement of the EMP **120** that might otherwise occur due to the EMP incurring wear and/or damage due to gamma rays **460** emitted from the liquid metal coolant **190** flowing through the flow annulus **312**. It will be understood that the gamma shielding material included in at least one of an inner flow duct **310-1** or an outer flow duct **310-2** of the EMP **120** reducing, minimizing, or preventing gamma ray **460** penetration from the liquid metal coolant **190** that is in the flow annulus **312** may occur while no flow of the liquid metal coolant **190** is occurring in the flow annulus **312**, such that liquid metal coolant **190** is present in the flow annulus **312** and has no or substantially no flow rate (e.g., mass and/or volumetric flow rate) through the flow annulus **312**.

(114) At **S508**, at least partially concurrently with the EMP **120** (e.g., the plurality of induction coils **320**) operating to cause liquid metal coolant **190** to flow through the flow annulus **312**, a neutron absorber material included in the pump casing **302** of the EMP **120** may absorb neutrons (e.g., ambient neutrons **470**) received at the pump casing **302** (e.g., the outer sidewall structure **302-1**) from an exterior of the EMP **120** (e.g., an ambient environment **450** of an interior of the nuclear reactor **110** in which the EMP **120** is located). As a result, the neutron absorber material may reduce, minimize, or prevent any wear and/or damage of the EMP **120** and/or any portions thereof due to neutrons (e.g., ambient neutrons) entering the EMP **120** (e.g., at least the pump casing **302**) from an external environment (e.g., liquid metal coolant **190** and/or structures of the nuclear reactor **110** surrounding the EMP **120** within the nuclear reactor **110**) emitted from the liquid metal coolant **190** flowing through the flow annulus **312**. Thus, the neutron absorber material in the pump casing **302** of the EMP **120** may provide improved performance and/or reliability of the EMP **120**, extended service life of the EMP **120**, and reduced frequency of repair, maintenance, and/or replacement of the EMP **120** that might otherwise occur due to the EMP **120** incurring wear and/or damage due to ambient neutrons **470** received at the EMP **120** and/or entering the EMP **120** from an exterior of the EMP **120** (e.g., an ambient environment **450**). It will be understood that the neutron absorber material may be absent from the EMP **120** in some example embodiments. It will be understood that the neutron absorber material may absorb ambient neutrons **470** in the absence of any flow of the liquid metal coolant **190** through the flow annulus **312**.

(115) In some example embodiments, the EMP **120** may include a neutron moderator material **452** on an outer surface **302os** of the pump casing **302**, and at **S508** the neutron moderator material may moderate one or more ambient neutrons **470-1** received at the neutron moderator material **452** from the exterior of the EMP **120** to establish moderated neutrons **470-2** which may then enter at least the pump casing **302** of the EMP **120** and be absorbed by the neutron absorber material therein. As a result, the EMP **120** may be configured to sufficiently moderate ambient neutrons to improve the likelihood of absorbance thereof by the neutron absorber material in the pump casing **302**, thereby further improving performance and reliability of the EMP **120** due to reduced, minimized, or prevented entry of the ambient neutrons into the interior **380** of the EMP **120** to potentially wear and/or damage any portions of the EMP **120**.

(116) At **S510**, a determination may be made whether to adjust a supply of electric power from the power supply **144** to the EMP **120** (e.g., adjust the magnitude of voltage, current, or the like of electric power supplied to the EMP **120** to adjust the flow rate of the flow of liquid metal coolant **190** through the flow annulus **312** that is induced by the EMP **120**). If so, at **S512** the adjustment is

implemented. If not, at S514, a determination may be made whether to terminate or inhibit the supply of electric power electric power from the power supply 144 to the EMP 120. If so, at S516 the supply is terminated or inhibited, thereby slowing or stopping the flow of liquid metal coolant 190 through the flow annulus 312 of the EMP due to the inhibition of driving force applied to the liquid metal coolant 190 in the flow annulus 312 by the EMP 120.

(117) Operation S510 may include determining whether to adjust a frequency of the polyphase electrical power supplied by power supply 144 to the EMP 120. If so, at S512, a control signal may be generated and transmitted to the power supply 144 to cause the power supply 144 to adjust a frequency of the supply of polyphase electrical power that is being supplied to the EMP 120. The control signal may be generated and transmitted by the EMP control system 150. The control signal may cause the power supply 144 to adjust the frequency of the supply of polyphase electrical power to a new particular frequency.

(118) Operation S510 may include determining whether to adjust a power amplitude (e.g., voltage and/or current) of the polyphase electrical power supplied by the power supply 144 to the EMP 120. If so, at S512, a control signal may be generated and transmitted to the power supply 144 to cause the power supply 144 to adjust a power amplitude (e.g., voltage and/or current) of the supply of polyphase electrical power that is being supplied to the EMP 120. The control signal may be generated and transmitted by the EMP control system 150. The control signal may cause the power supply 144 to adjust the power amplitude (e.g., voltage and/or current) of the supply of polyphase electrical power to a new particular power amplitude (e.g., voltage and/or current).

(119) Operation S514 may include determining whether to inhibit (e.g., turn off) a supply of polyphase electrical power from the power supply 144 to the EMP 120. If so, at S516, a control signal may be generated and transmitted to the power supply 144 to cause the power supply 144 to inhibit the supply of polyphase electrical power to the EMP 120. The control signal may be generated and transmitted by the EMP control system 150. The control signal may cause the power supply 144 to inhibit a supply of polyphase electrical power to the EMP 120.

(120) It will be understood that any of the operations of the method shown in FIG. 5 may be performed in any order, including being performed simultaneously. It will be understood that, in some example embodiments, any of the operations of the method shown in FIG. 5 may be performed independently of each other. In some example embodiments, any of the operations shown in FIG. 5 may be omitted and/or one or more additional operations may be added to the method shown in FIG. 5. In some example embodiments, each of the determinations and/or operations as shown in FIG. 5 may be performed in response to receiving an input command via a user interface (e.g., keyboard, button, touchscreen, mouse, etc.) and/or communication interface (e.g., wireless network communication receiver) and/or in response to processing sensor data received from one or more sensor devices (e.g., one or more flowmeters such as one or more Venturi flow meters in the suction line 121 and/or the return line 124 that may be configured to generate sensor data indicating a flow rate of liquid metal coolant 190 through the suction line 121, return line 124, and/or EMP 120, one or more pressure sensors that may be configured to generate sensor data indicating a pressure of liquid metal coolant 190 at one or more locations in the suction line 121, return line 124, and/or EMP 120, or the like).

(121) In some example embodiments, an adjustment of frequency and/or power amplitude of polyphase electrical power that is supplied to the EMP 120 may include determining a particular frequency and/or power amplitude and controlling a polyphase electrical power supply (e.g., power supply 144) to cause the polyphase electrical power supply to supply polyphase electrical power having the particular frequency and/or power amplitude to the EMP 120. The determining the particular frequency and/or power amplitude may be in response to receiving an input command that specifies a particular frequency and/or power amplitude of polyphase electrical power to be supplied to the EMP 120 and/or in response to processing sensor data received from one or more sensor devices (e.g., one or more flowmeters such as one or more Venturi flow meters that may be

configured to generate sensor data indicating a flow rate of liquid metal coolant **190** through the suction line **121**, return line **124**, and/or EMP **120**, one or more pressure sensors that may be configured to generate sensor data indicating a pressure of liquid metal coolant **190** at one or more locations in the suction line **121**, return line **124**, and/or EMP **120**, or the like).

(122) The input command and/or sensor data may be processed to determine a desired or target flow rate and/or pressure rise distribution of liquid metal coolant through at least the EMP **120**, an actual flow rate and/or pressure rise distribution of liquid metal coolant through at least the EMP **120** and/or primary coolant loop **119**, or the like. In some example embodiments, where an actual flow rate and/or pressure rise distribution is determined based on processing sensor data, a target flow rate and/or pressure rise distribution may be determined based on comparing the actual flow rate and/or pressure rise distribution with a desired, threshold, or target flow rate and/or pressure rise distribution that may be stored in a memory and/or database. The comparing may include determining a new target flow rate and/or pressure rise distribution based on a determination that the actual flow rate and/or pressure rise distribution exceeds one or more threshold flow rates and/or pressure rise distributions.

(123) The determining the particular frequency and/or power amplitude may include, for example in response to an input command and/or processing of received sensor data (e.g., in response to determining a desired, target, and/or actual flow rate and/or pressure rise distribution of liquid metal coolant through at least the EMP **120** and/or primary coolant loop **119**, or the like), accessing an empirically-generated look-up table that associates an actual, target, and/or desired liquid metal coolant **190** flow rate and/or pressure rise distribution in the EMP **120** with specific parameters (e.g., frequency and/or power amplitude, initiated or inhibited state, etc.) of polyphase electrical power to be supplied to the EMP to implement the associated liquid metal coolant **190** flow rate and/or pressure rise distribution. In some In some example embodiments, the look-up table may be accessed in response to receiving an input of a desired, target, and/or actual liquid metal coolant **190** flow rate and/or pressure rise distribution in the EMP **120** in order to identify specific parameters (e.g., frequency and/or power amplitude, initiated or inhibited state, etc.) of polyphase electrical power to be supplied by the polyphase power supply to an EMP to implement the desired and/or target liquid metal coolant flow rate and/or pressure rise distribution. The operations **S504**, **S512**, and/or **S516** may include transmitting control signals to a polyphase power supply to cause the polyphase power supply to adjust the polyphase electrical power supplied thereby to the EMP **120** pursuant to the specific parameters (e.g., frequency and/or power amplitude, initiated or inhibited state, etc.) of polyphase electrical power to be supplied by a polyphase power supply to a corresponding EMP to implement the desired and/or target liquid metal flow rate and/or pressure rise distribution.

(124) FIG. **6** is a flowchart illustrating a method for configuring **S600** a nuclear reactor to improve performance and reliability of liquid metal coolant flow circulation and/or control in the nuclear reactor, according to some example embodiments. The configuring may be implemented with regard to any example embodiment of nuclear reactors included herein, including the nuclear reactor **110** illustrated in FIG. **1**.

(125) At **S602**, the configuring **S600** may include installing an EMP **120** in a primary coolant loop **119** within the nuclear reactor pressure vessel **111**. The EMP **120** may be any of the EMPs **120** according to any of the example embodiments. The installing may be implemented by a human operator. Such installing may include connecting the inlet **122** of the EMP **120** to a suction line **121** of the primary coolant loop **119** and connecting the outlet **123** of the EMP **120** to a return line **124** of the primary coolant loop **119**. The installing may include connecting the pump casing **302** of the EMP **120** to a structural support member of the nuclear reactor **110**, to structurally connect the EMP **120** to the nuclear reactor pressure vessel **111**, the core inlet plenum **118**, the nuclear reactor core **112**, the primary heat exchanger **114**, the suction reservoir **116**, or any combination thereof.

(126) At **S604**, the configuring **S600** may include electrically coupling the EMP **120** to a power

supply **144** (e.g., a polyphase power supply configured to supply polyphase electrical power), thereby electrically connecting the EMP **120** to the power supply **144**. The coupling may be implemented by a human operator. The electric coupling at **S604** may include electrically connecting the plurality of induction coils **320** of the EMP **120** to a power cable **146** where the power cable **146** extends through a power supply conductor **180**, or extension cord from the EMP **120** to at least an exterior of the nuclear reactor pressure vessel **111** via an opening **182** (e.g., penetration) through the outer wall **111S** of the nuclear reactor pressure vessel **111**. The power cable **146** may be configured to connect the power supply **144** to the EMP **120**.

(127) At **S606**, the configuring **S600** may include coupling (e.g., electrically coupling and/or communicatively coupling) the EMP **120** to one or more EMP control systems (also referred to herein as one or more control systems). The coupling may be implemented by a human operator. The coupling may include communicatively coupling the EMP **120** to one or more portions of the EMP control system **150** via one or more communication lines, electrically coupling the power supply **144** to the EMP control system **150**, thereby indirectly communicatively coupling the EMP control system **150** to EMP **120** via the power supply **144** via one or more communication lines, power lines, etc. The EMP control system **150** may include a memory (e.g., a solid state drive or SSD) storing a program of instructions and a processor (e.g. a central processor unit or CPU) configured to execute the program of instructions to independently control the EMP **120**, and thus to control a flow of liquid metal coolant through at least the flow annulus of the EMP **120**, and thus through the primary coolant loop **119**, based on controlling electrical power (e.g., polyphase electrical power) supplied by the power supply **144**.

(128) While a number of example embodiments have been disclosed herein, it should be understood that other variations may be possible. Such variations are not to be regarded as a departure from the spirit and scope of the present disclosure, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims. In addition, while processes have been disclosed herein, it should be understood that the described elements of the processes may be implemented in different orders, using different selections of elements, some combination thereof, etc. For example, some example embodiments of the disclosed processes may be implemented using fewer elements than that of the illustrated and described processes, and some example embodiments of the disclosed processes may be implemented using more elements than that of the illustrated and described processes.

Claims

1. An electromagnetic pump (EMP), comprising: a pump casing having a longitudinal axis extending in a longitudinal direction, the pump casing at least partially defining an interior of the EMP; concentric inner and outer flow ducts extending coaxially with the longitudinal axis and collectively defining a flow annulus extending coaxially with the longitudinal axis; and a plurality of induction coils within the interior of the EMP and configured to be electrically connected to a power supply, the plurality of induction coils configured to control a flow of liquid metal coolant through the flow annulus based on electrical power received from the power supply, wherein at least the outer flow duct includes a gamma shielding material that is configured to block gamma rays emitted from the liquid metal coolant flowing through the flow annulus from entering the interior of the EMP from the flow annulus, wherein the outer flow duct includes first concentric cylindrical duct walls defining a first duct annulus between the first concentric cylindrical duct walls, the first concentric cylindrical duct walls including a first outer cylindrical duct wall and a first inner cylindrical duct wall, the first concentric cylindrical duct walls defining the first duct annulus between an inner surface of the first outer cylindrical duct wall and an outer surface of the first inner cylindrical duct wall, an inner surface of the first inner cylindrical duct wall partially defining the flow annulus, the gamma shielding material is in the first duct annulus between the

first outer cylindrical duct wall and the first inner cylindrical duct wall, such that the first inner cylindrical duct wall is between the gamma shielding material and the flow annulus, and the gamma shielding material is a filler material in the first duct annulus.

2. The EMP of claim 1, wherein the pump casing includes a neutron absorber material, the neutron absorber material configured to absorb neutrons entering the pump casing from an exterior of the EMP.
3. The EMP of claim 2, wherein the pump casing includes concentric cylindrical housing walls defining a housing annulus between the concentric cylindrical housing walls, and the neutron absorber material is located within the housing annulus.
4. The EMP of claim 2, wherein the EMP further includes a neutron moderator material on an outer surface of the pump casing, the neutron moderator material configured to moderate neutrons received from the exterior of the EMP such that the neutrons entering the pump casing from the exterior of the EMP are moderated neutrons, the neutron absorber material configured to absorb the moderated neutrons.
5. The EMP of claim 1, wherein the plurality of induction coils includes at least one of inner induction coils located within a central region at least partially defined by an inner surface of the inner flow duct, or outer induction coils located within an annular region at least partially defined between an outer surface of the outer flow duct and an inner surface of the pump casing.
6. A method for operating the EMP of claim 1, the method comprising: controlling a supply of electrical power to the EMP to cause the plurality of induction coils to generate one or more magnetic fields to induce a flow of liquid metal coolant through the flow annulus; and blocking, at the gamma shielding material included in the outer flow duct, gamma rays emitted from liquid metal coolant located in the flow annulus from entering an interior of the EMP that is external to the flow annulus.
7. The method of claim 6, wherein, the pump casing includes a neutron absorber material, the neutron absorber material configured to absorb neutrons entering the pump casing from an exterior of the EMP, and the method further includes absorbing, at the neutron absorber material, neutrons received at the pump casing from the exterior of the EMP.
8. A method for configuring a nuclear reactor to improve liquid metal coolant flow control in the nuclear reactor, the method comprising: installing the EMP of claim 1 in a primary coolant loop in a nuclear reactor pressure vessel of the nuclear reactor; electrically connecting the EMP to the power supply via a power cable; and communicatively coupling the EMP to a control system, the control system including a memory storing a program of instructions and a processor configured to execute the program of instructions to control a flow of liquid metal coolant through the primary coolant loop based on controlling the supply of electrical power supplied from the power supply to the EMP.
9. A nuclear reactor configured to be cooled via liquid metal circulation, the nuclear reactor comprising: a reactor pressure vessel; a reactor core within the reactor pressure vessel; and the EMP of claim 1 within the reactor pressure vessel, the EMP configured to circulate a flow of liquid metal coolant through a primary coolant loop that includes the reactor core.
10. The nuclear reactor of claim 9, further comprising: a control system configured to control the power supply to control a supply of electrical power to the EMP, to control the flow of liquid metal coolant through the primary coolant loop.
11. The EMP of claim 1, wherein the gamma shielding material is configured to block an incident gamma ray photon emitted from the liquid metal coolant flowing through the flow annulus based on at least one of photoelectric absorption of gamma rays by the gamma shielding material, including a complete transfer of energy from the incident gamma ray photon to an atomic electron of the gamma shielding material, scattering of gamma rays by the gamma shielding material, the scattering including a transfer of part of energy of the incident gamma ray photon to an atomic electron of the gamma shielding material, such that the gamma shielding material causes the

incident gamma ray photon to perform at least one of further scattering or absorption interactions with the gamma shielding material, or emerge from the gamma shielding material with diminished energy; or pair production, the pair production including interaction of the incident gamma ray photon with a nucleus of an atom of the gamma shielding material which results in creation of a beta particle and a positron that then undergoes an annihilation reaction with an electron to produce two lower-energy gamma rays.

12. The EMP of claim 1, wherein the gamma shielding material includes one or more of Lead, Tin, Bismuth, Tungsten, Water, Borated Paraffin, or Borated Polyethylene.

13. The EMP of claim 2, wherein the neutron absorber material includes one or more of Gadolinium, Cadmium, Gadolinium oxide, Hafnium Lithium, Europium, Gadolinium Stainless Steel, Silver, Xenon, or Indium.

14. The EMP of claim 1, wherein the inner flow duct and the outer flow duct each include at least one gamma shielding material that is configured to block gamma rays emitted from the liquid metal coolant flowing through the flow annulus from entering the interior of the EMP from the flow annulus.

15. The EMP of claim 1, wherein the inner flow duct includes second concentric cylindrical duct walls defining a second duct annulus between second first concentric cylindrical duct walls, the second concentric cylindrical duct walls including a second outer cylindrical duct wall and a second inner cylindrical duct wall, the second concentric cylindrical duct walls defining the second duct annulus between an inner surface of the second outer cylindrical duct wall and an outer surface of the second inner cylindrical duct wall, the outer flow duct and the inner flow duct collectively define the flow annulus between the inner surface of the first inner cylindrical duct wall of the outer flow duct and an outer surface of the second outer cylindrical duct wall of the inner flow duct, an additional gamma shielding material is in the second duct annulus between the second outer cylindrical duct wall and the second inner cylindrical duct wall, such that the second outer cylindrical duct wall is between the additional gamma shielding material and the flow annulus, the additional gamma shield material in the second duct annulus and the gamma shielding material in the first duct annulus are a same gamma shielding material, and the additional gamma shielding material is a filler material in the second duct annulus.

16. The EMP of claim 1, wherein the gamma shielding material includes one or more of Water, Borated Paraffin, or Borated Polyethylene.

17. The EMP of claim 15, wherein the gamma shielding material and the additional gamma shielding material are each a same one or more of Water, Borated Paraffin, or Borated Polyethylene.

18. The EMP of claim 3, wherein the neutron absorber material is a filler material within the housing annulus.

19. The EMP of claim 1, wherein the gamma shielding material does not provide structural integrity of the outer flow duct.

20. The EMP of claim 15, wherein the additional gamma shielding material does not provide structural integrity of the inner flow duct.
