

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413126
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Wang; Junsheng et al.

Vibration exciter

Abstract

The present application provides a vibration exciter, including a casing with an accommodating cavity, a stator assembly assembled in the casing, and a vibrator assembly assembled in the accommodating cavity and driven by the stator assembly to vibrate. The stator assembly includes a polar core fixed on an inner side of the casing and a magnetic steel fixed on one side of the polar core away from the casing. The vibrator assembly includes a skeleton elastically connected to the casing, a mass block fixed to the skeleton, and a coil wound around the outer side of the skeleton. The skeleton is integrally formed and has a solid structure. In the present application, since the skeleton is a solid structure formed integrally, the skeleton is not easy to be deformed when the coils are wound, and the shape of the coils can be controlled, thus having a better shape.

Inventors: Wang; Junsheng (Shenzhen, CN), Wu; Jie (Shenzhen, CN), Zhu; Aijie (Shenzhen, CN), Zhang; Qiang (Shenzhen, CN)

Applicant: AAC Microtech (Changzhou) Co., Ltd. (Changzhou, CN)

Family ID: 90140683

Assignee: AAC Microtech (Changzhou) Co., Ltd. (Changzhou, CN)

Appl. No.: 18/090529

Filed: December 29, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240088769 A1	Mar. 14, 2024

Foreign Application Priority Data

CN	202222407217.7	Sep. 09, 2022
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/CN2022/122707 20220929 PENDING child-doc US 18090529

Publication Classification

Int. Cl.: H02K5/04 (20060101); H02K1/34 (20060101); H02K33/06 (20060101); H02K33/18 (20060101)

U.S. Cl.:

CPC H02K33/06 (20130101); H02K1/34 (20130101); H02K5/04 (20130101); H02K33/18 (20130101); H02K2203/03 (20130101)

Field of Classification Search

CPC: H02K (33/18); H02K (1/34); H02K (33/06); H02K (5/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2769103	12/1955	Kristiansen	335/230	H02K 33/06
6707196	12/2003	Mayumi	310/49.15	H02K 5/1672
2002/0175572	12/2001	Cho	310/216.001	H02K 29/06
2021/0265902	12/2020	Wang	N/A	B06B 1/045
2023/0198364	12/2022	Li	310/28	H02K 33/16

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
20220017449	12/2021	KR	N/A

Primary Examiner: Kayes; Sean

Attorney, Agent or Firm: Wiersch Law Group

Background/Summary

TECHNICAL FIELD

(1) The present application relates to the technical field of vibration equipment, in particular to a vibration exciter.

BACKGROUND

(2) At present, a vibration exciter in the related art mainly consists of a casing, a cover plate, a polar core, magnetic steel, a soft magnetic ring, a coil, and a coil support, and a vibration exciter system generates an induced electromotive force by cutting magnetic induction lines through the coil alternating current, so as to drive other related members to work. However, in the vibration exciter system in the related art, the coil is wound around a hollow support, and the hollow support is easy

to deform, so that the shape of the coil is difficult to control while winding the coil, which affects the quality of the vibration exciter.

SUMMARY

(3) An object of the present application is to provide a vibration motor, which can increase a winding speed of a coil and stabilize an outer shape of the coil.

(4) The technical solutions of the present application are as follows.

(5) The present application provides a vibration exciter, comprising: a casing with an accommodating cavity; a stator assembly assembled in the casing, comprising: a polar core fixed on the inner side of the casing; a magnetic steel fixed on one side of the polar core away from the casing; and a vibrator assembly assembled in the accommodating cavity and driven to vibrate by the stator assembly, comprising: a skeleton elastically connected to the casing; a mass block fixed to the skeleton, the skeleton being integrally formed and provided with a solid structure; and a coil wound around an outer side of the skeleton.

(6) In an embodiment, the skeleton comprises a main body elastically connected to the casing, a first positioning protrusion and a second positioning protrusion extended in parallel in a direction toward the casing from two ends of the main body, wherein a gap is formed between the first positioning protrusion and the second positioning protrusion, and the coil is wound around the main body and located in the gap.

(7) In an embodiment, the mass block comprises a first mass block fixedly assembled on a side of the first positioning protrusion away from the coil and a second mass block fixedly assembled on a side of the second positioning protrusion away from the coil.

(8) In an embodiment, the vibration exciter further comprises a flexible printed circuit (FPC), wherein one end of the FPC is connected to one surface of the second positioning protrusion facing toward the coil, the coil being electrically connected to the FPC, and the other end of the FPC is led out to an outer side of the casing.

(9) In an embodiment, an outer edge of one side of the second positioning protrusion is extended toward the casing to form an assembly block; one end of the FPC is fixed to the assembly block, and the other end of the FPC is bent and fixed to the outer side of the casing.

(10) In an embodiment, the main body comprises a first end surface and a second end surface respectively located at two ends of the main body, and the vibration exciter comprises a first spring piece fixed to the first end surface and the casing, and a second spring piece fixed to the second end surface and the casing.

(11) In an embodiment, a first threaded hole is provided on the first end surface of the main body, and a second threaded hole is provided on the second end surface of the main body; the vibration exciter further comprises a first screw arranged through the first spring piece and connected to the first threaded hole, and a second screw arranged through the second spring piece and connected to the second threaded hole; and/or, a first assemble hole is provided on the first end surface of the main body, and a second assemble hole is provided on the second end surface of the main body; the vibration exciter further comprises a first rivet arranged through the first spring piece and riveted to the first assemble hole, and a second rivet arranged through the second spring piece and riveted to the second assemble hole; and/or, the first spring piece is fixedly welded to the first end surface at a first welding spot, and the second spring piece is fixedly welded to the second end surface at a second welding spot.

(12) In an embodiment, an inner side of the casing is protruded inward to form a third positioning protrusion, wherein a side of the third positioning protrusion away from the casing is provided with a positioning groove, and the polar core and the corresponding magnetic steel are both embedded in the positioning groove; when the vibrator assembly is in an initial state, the positioning groove directly faces the coil.

(13) In an embodiment, the casing comprises an outer casing, an upper cover plate mounted at one end of the casing, and a lower cover plate assembled at the other end of the outer casing; the first

spring piece and the second spring piece are respectively connected to two ends of the casing by means of glue dispensing and welding; the first spring piece is clamped and fixed by the upper cover plate and the outer casing, and the second spring piece is clamped and fixed by the lower cover plate and the outer casing.

(14) In an embodiment, the lower cover plate comprises a positioning plate extending from a periphery of the lower cover plate to the upper cover plate; a notch corresponding to the positioning plate is arranged on a side of the outer casing close to the lower cover plate, and the positioning plate is embedded in the notch.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a structural view of a vibration exciter after assembled according to an embodiment of the present application.

(2) FIG. 2 is a structural diagram of a skeleton of the vibration exciter of the present application.

(3) FIG. 3 is an exploded view of the vibration exciter according to an embodiment of the present application.

(4) FIG. 4 is a cross-sectional view of the vibration exciter taken along a line B-B in FIG. 1 according to a first embodiment of the present application.

(5) FIG. 5 is a cross-sectional view of the vibration exciter taken along a line A-A in FIG. 1 according to the first embodiment of the present application.

(6) FIG. 6 is a cross-sectional view of the vibration exciter taken along the line A-A according to a second embodiment of the present application.

(7) FIG. 7 is a cross-sectional view of the vibration exciter taken along the line A-A according to a third embodiment of the present application.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(8) The present application will be further described below in conjunction with the accompanying drawings and embodiments.

(9) As shown in FIGS. 1-5, a vibration exciter includes a casing 1 with an accommodating cavity, a stator assembly 2 assembled in the casing 1, and a vibrator assembly 3 assembled in the accommodating cavity and driven to vibrate by the stator assembly 2. The stator assembly 2 includes a polar core 21 fixed at an inner side of the casing 1 and a magnetic steel 22 fixed at a side of the polar core 21 away from the casing 1. The vibrator assembly 3 includes a skeleton 31 elastically connected to the casing 1, a mass block 32 fixed to the skeleton 31, and a coil 34 wound around an outer side of the skeleton 31. The skeleton 31 is integrally formed and has a solid structure.

(10) In this embodiment, the coil 34 is wound centrally on the skeleton 31. Since the skeleton 31 is a solid structure formed by integral injection molding, when the coil 34 is wound, the skeleton 31 is not easy to be deformed, and the shape of the coil 34 can be controlled, thus having a better shape.

(11) As shown in FIG. 2, the skeleton 31 includes a main body 33 elastically connected to the casing 1, a first positioning protrusion 35 and a second positioning protrusion 36 respectively extended and protruded from two ends of the main body 33 in parallel to the direction of the casing 1. A gap is formed between the first positioning protrusion 35 and the second positioning protrusion 36, and the coil 34 is wound around the main body 33 and located in the gap.

(12) In this embodiment, the coil 34 is wound centrally on the main body 33, so that when the vibration exciter of the present invention is processed, the winding speed of the coil 34 becomes faster. The first positioning protrusion 35 and the second positioning protrusion 36 are located close to two ends of the main body 33, respectively, and they are two symmetrically distributed rectangular blocks. In other embodiments, the outer contour shapes of the first positioning

protrusion **35** and the second positioning protrusion **36** may be consistent with the outer contour shape of the main body **33**. However, this contour needs to be larger than that of the main body **33** after the coil **34** is assembled.

(13) As shown in FIG. **3**, the mass block includes a first mass block **321** fixedly assembled on one side of the first positioning protrusion **35** away from the coil **34** and a second mass block **322** fixedly assembled on one side of the second positioning protrusion **36** away from the coil **34**.

(14) In this embodiment, the effect of assembling the first mass block **321** and the second mass block **322** is to enable the vibration exciter of the present application to perform the stable movement after starting to work, and the first mass block **321** and the second mass block **322** are symmetrically assembled on the skeleton **31**.

(15) As shown in FIGS. **1** and **2**, the vibration exciter further includes a flexible printed circuit (FPC) **4**, one end of which is connected to a surface of the second positioning protrusion **36** facing toward the coil **34**. The coil **34** is electrically connected to the FPC **4**. The other end of the FPC **4** is led out to the outer side of the casing **1**. A peripheral of one side of the second positioning protrusion **36** is extended toward the casing **1** to form an assembling block **361**. One end of the FPC **4** is fixed to the fitting block **361**, and the other end of the FPC **4** is fixed to the outer side of the casing **1**. In this embodiment, the FPC **4** is in a bent form, and a portion of the FPC **4** connected to the assembly block **361** is provided with a first electrode **41**. The coil **34** is connected to the first electrode **41**. The other end of the FPC **4** connected to the casing **1** is provided with a second electrode **42**, which is configured to connect a circuit and provide a power supply for the operation of the vibration exciter.

(16) As shown in FIGS. **2** and **5**, the main body **33** of the skeleton **31** includes a first end surface **39** and a second end surface **30** respectively located at two ends thereof. The vibration exciter includes a first spring piece **37** fixed to the first end surface **39** and the casing **1**, and a second spring piece **38** fixed to the second end surface **30** and the casing **1**. In this embodiment, the first spring piece and the second spring piece are disk-shaped metal objects that are spirally hollowed out.

(17) Combined with FIG. **5**, in the first embodiment, a first threaded hole **311** is provided on the first end surface **39** of the main body **33**, and a second threaded hole **312** is provided on the second end surface **30** of the main body **33**. The vibration exciter further includes a first screw **313** arranged through the first spring piece **37** and connected to the first threaded hole **311**, and a second screw **314** arranged through the second spring piece **38** and connected to the second threaded hole **312**. In this embodiment, when the first screw **313** is connected to the first threaded hole **311**, a first washer **3131** is nested on the first screw **313**. When the second screw **314** is connected to the second threaded hole **312**, a second washer **3132** is nested on the second screw **314**. The function of the washers is to enable the first screw **313** to be connected to the first threaded hole **311** more tightly.

(18) Combined with FIG. **6**, in a second embodiment, a first threaded hole **317** may be arranged on the first end surface **39** of the main body **33**, and a second threaded hole **318** may be arranged on the second end surface **30** of the main body **33**. The vibration exciter further includes a first rivet **315** arranged through the first spring piece **37** and riveted to the first threaded hole **317**, and a second rivet **316** arranged through the second spring piece **38** and riveted to the second threaded hole **318**. In this embodiment, the first spring piece **37** is connected to the first threaded hole **317** through the first rivet **315**, and the second spring piece **38** is connected to the second threaded hole **318** through the second rivet **316**.

(19) Combined with FIG. **7**, in the third embodiment, the first spring piece **37** may also be fixedly welded to the first end surface **39** at a welding spot **319**, and the second spring **38** may also be fixedly welded to the second end surface **30** at a welding spot **310**.

(20) As shown in FIGS. **4-7**, an inner side of the casing **1** is protruded inward to form a third positioning protrusion **133**, and a side of the third positioning protrusion **133** away from the casing **1** is provided with a positioning groove **1331**. The polar core **21** and the corresponding magnetic

steel **22** are both embedded in the positioning groove **1331**. When the vibrator assembly **3** is in the initial state, the positioning groove **1331** is directly opposite to the coil **34**. In this embodiment, a pair of third positioning protrusions **133**, a pair of polar cores **21**, and a pair of magnetic steel bars **22** are arranged in the casing. In other embodiments, the number of the third positioning protrusions **133**, the number of the polar cores **21**, and the number of the magnetic steels **22** may be increased or decreased according to practical situations.

(21) In this embodiment, the magnetic induction is generated by the stator assembly **2** formed by the polar core **21** and the magnetic steel **22**. When the coil **34** is energized, the alternating current of the coil **34** cuts magnetic induction lines of the stator assembly **2**, thereby generating an induced electromotive force and further driving the vibrator assembly **3** to move. In an embodiment, two third positioning protrusions **133** are arranged oppositely on the inner side of the casing **1**, and two stator assemblies **2** (a polar core **21** and a magnetic steel **22**) are arranged oppositely.

(22) As shown in FIGS. 5-7, the casing **1** includes an outer casing **13**, an upper cover plate **11** assembled on one end of the outer casing **13**, and a lower cover plate **12** assembled on the other end of the outer casing **13**. The first spring piece **37** and the second spring piece **38** are respectively connected to two ends of the outer casing **13** by means of glue dispensing and heating. The first spring piece **37** is clamped and fixed by the upper cover plate **11** and the outer casing **13**, and the second spring piece **38** is clamped and fixed by the lower cover plate **12** and the outer casing **13**. In this embodiment, the first spring piece **37** and the second spring **38** are fixed to the casing **1** by means of glue dispensing and heating. The glue dispensing refers to driving glue out by using a glue gun, so that the first spring piece **37** and the second spring piece **38** are bonded to the casing **1**. The heating refers to a plastic point **132** where the first spring piece **37** and the second spring piece **38** are respectively clamped on the outer casing **13**. The plastic points **132** are melted after heating, and the first spring piece **37** and the second spring piece **38** can be fixed on the outer casing **13** after the plastic points **132** are cooled and solidified.

(23) As shown in FIGS. 1, 2, and 5-7, the lower cover plate **12** includes a positioning plate **121** extending from a periphery of the lower cover plate **12** to the upper cover plate **11**. A side of the outer casing **13** close to the lower cover plate **12** is provided with a notch **131** corresponding to the positioning plate **121**. The positioning plate **121** is embedded in the notch **131**. In this embodiment, the positioning plate **121** and the notches **131** are not completely assembled, but a gap is left therebetween. The FPC **4** is bent out from the gap, and the other end thereof is fixedly connected to the casing **1**.

(24) Described above are only embodiments of the present application. It should be noted that, for those skilled in the art, improvements made without departing from the concept of the present application shall fall within the protection scope of the present application.

Claims

1. A vibration exciter, comprising: a casing with an accommodating cavity; a stator assembly assembled in the casing, comprising: a polar core fixed on an inner side of the casing; a magnetic steel fixed on one side of the polar core away from the casing; and a vibrator assembly assembled in the accommodating cavity and driven to vibrate by the stator assembly, comprising: a skeleton elastically connected to the casing; a mass block fixed to the skeleton, the skeleton being integrally formed and provided with a solid structure; and a coil wound around an outer side of the skeleton; wherein the skeleton comprises: a main body elastically connected to the casing; a first positioning protrusion; and a second positioning protrusion extended in parallel in a direction toward the casing from two ends of the main body; wherein a gap is formed between the first positioning protrusion and the second positioning protrusion, and the coil is wound around the main body and located in the gap.

2. The vibration exciter of claim 1, wherein the mass block comprises: a first mass block fixedly

assembled on a side of the first positioning protrusion away from the coil; and a second mass block fixedly assembled on a side of the second positioning protrusion away from the coil.

3. The vibration exciter of claim 1, further comprising a flexible printed circuit (FPC), wherein one end of the FPC is connected to one surface of the second positioning protrusion facing toward the coil, the coil being electrically connected to the FPC, and the other end of the FPC is led out to an outer side of the casing.

4. The vibration exciter of claim 3, wherein an outer edge of one side of the second positioning protrusion is extended toward the casing to form an assembly block; one end of the FPC is fixed to the assembly block, and the other end of the FPC is bent and fixed to the outer side of the casing.

5. The vibration exciter of claim 1, wherein the main body comprises a first end surface and a second end surface located at two ends of the main body, respectively; and the vibration exciter comprises a first spring piece fixed to the first end surface and the casing, and a second spring piece fixed to the second end surface and the casing.

6. The vibration exciter of claim 5, wherein a first threaded hole is provided on the first end surface of the main body, and a second threaded hole is provided on the second end surface of the main body; the vibration exciter further comprises a first screw arranged through the first spring piece and connected to the first threaded hole, and a second screw arranged through the second spring piece and connected to the second threaded hole; and/or, a first assemble hole is provided on the first end surface of the main body, and a second assemble hole is provided on the second end surface of the main body; the vibration exciter further comprises a first rivet arranged through the first spring piece and riveted to the first assemble hole, and a second rivet arranged through the second spring piece and riveted to the second assemble hole; and/or, the first spring piece is fixedly welded to the first end surface at a first welding spot, and the second spring piece is fixedly welded to the second end surface at a second welding spot.

7. The vibration exciter of claim 1, wherein an inner side of the casing is protruded inward to form a third positioning protrusion, wherein a side of the third positioning protrusion away from the casing is provided with a positioning groove, and the polar core and the corresponding magnetic steel are both embedded in the positioning groove; when the vibrator assembly is in an initial state, the positioning groove directly faces the coil.

8. The vibration exciter of claim 5, wherein the casing comprises an outer casing, an upper cover plate mounted at one end of the casing, and a lower cover plate assembled at the other end of the outer casing; the first spring piece and the second spring piece are respectively connected to two ends of the casing by means of glue dispensing and welding; the first spring piece is clamped and fixed by the upper cover plate and the outer casing, and the second spring piece is clamped and fixed by the lower cover plate and the outer casing.

9. The vibration exciter of claim 8, wherein the lower cover plate comprises a positioning plate extending from a periphery of the lower cover plate to the upper cover plate; a notch corresponding to the positioning plate is arranged on a side of the outer casing close to the lower cover plate, and the positioning plate is embedded in the notch.
