

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413568
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Stewart; Norman Vernon Douglas et al.

Method and system for distributing keys

Abstract

A method and system for distributing keys in a key distribution system includes receiving a connection for communication from a first component. A determination is made whether the first component requires a key be generated and distributed. Based upon a security mode for the communication, the key generated and distributed to the first component.

Inventors: Stewart; Norman Vernon Douglas (Markham, CA), Doctor; Mihir Shaileshbhai (Santa Clara, CA), Ahmed; Omar Fakhri (Markham, CA), Jayanna; Hemaprabhu (Santa Clara, CA), Traver; John (Santa Clara, CA)

Applicant: Advanced Micro Devices, Inc. (Santa Clara, CA); ATI Technologies ULC (Markham, CA)

Family ID: 90358876

Assignee: Advanced Micro Devices, Inc. (Santa Clara, CA); ATI Technologies ULC (Ontario, CA)

Appl. No.: 17/955421

Filed: September 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240106813 A1	Mar. 28, 2024

Publication Classification

Int. Cl.: H04L9/40 (20220101); H04W12/04 (20210101)

U.S. Cl.:

Field of Classification SearchUSPC: None

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11831655	12/2022	Lee	N/A	H04L 63/123
2001/0038695	12/2000	Kim	380/283	H04L 9/0852
2006/0178131	12/2005	Huotari	455/410	H04W 12/0431
2009/0164663	12/2008	Ransom	709/243	H04L 45/00
2011/0119489	12/2010	Garcia Morchon	713/169	H04L 63/062
2012/0057697	12/2011	Holtmanns	380/42	H04N 21/6543
2012/0328103	12/2011	Feng	380/270	H04W 12/041
2014/0165216	12/2013	Kwag	726/30	G06F 21/74
2016/0239556	12/2015	Oh	N/A	H04L 67/06
2016/0315762	12/2015	Moon et al.	N/A	N/A
2017/0214717	12/2016	Bush	N/A	G05B 19/4185
2017/0255423	12/2016	Yoshida	N/A	G06F 3/1292
2018/0131511	12/2017	Taylor	N/A	H04L 9/0861
2018/0183581	12/2017	Elbaz et al.	N/A	N/A
2019/0239033	12/2018	Douglas	N/A	H04W 4/06
2020/0296099	12/2019	Shanbhogue et al.	N/A	N/A
2020/0374130	12/2019	Strong et al.	N/A	N/A
2021/0352110	12/2020	Huffman	N/A	H04L 63/02
2022/0303763	12/2021	Guo	N/A	H04W 12/03

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-2015-0131696	12/2014	KR	N/A

Primary Examiner: Abrishamkar; Kaveh*Attorney, Agent or Firm:* Volpe Koenig

Background/Summary**BACKGROUND**

(1) A memory management module, employed by an operating system of a computing system, provides applications with a contiguous memory space, namely, a virtual memory space. The physical memory storage that supports the virtual memory space can be provided by various memory devices, either internal to the computing system (e.g., main memory) or external to it (e.g., hard disk). The memory management model is designed to facilitate efficient utilization of the available virtual memory space, carrying out operations such as allocation of memory blocks for applications or migration of memory blocks to reduce fragmentation.

(2) In such memory spaces, keys (e.g., encryption keys) are used for device secured booting, software decryption/inscription and authentication, secure session communication with peers over standard interfaces, and content protection (e.g., digital write management).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) A more detailed understanding may be had from the following description, given by way of example in conjunction with the accompanying drawings wherein:

(2) FIG. 1 is a block diagram of an example device, based on which one or more features of the disclosure can be implemented;

(3) FIG. 2 is a block diagram of an example key distribution system in a system on chip, based on which one or more features of the disclosure can be implemented; and

(4) FIG. 3 is a flowchart of an example method for distributing keys, based on which one or more features of the disclosure can be implemented.

DETAILED DESCRIPTION

(5) Systems and methods are provided for efficient management of diversified virtual memory by a diversified virtual memory (DVM) engine (also referred to herein as an engine). On behalf of a memory manager of an operating system (OS), the diversified virtual memory engine engages with various memory devices—including distributing commands to perform operations (requested by the memory manager) to the appropriate memory devices, in accordance with interface protocols required by the virtual memory managers (VMM) of the respective memory devices. The diversified virtual memory engine's circuitries are configured to distribute the commands in an order that is in accordance with their respective priority levels, and to combine commands that can be parallelized.

(6) Although further detail is provided below, aspects disclosed in the present application describe a method and apparatus for distributing keys in a computer system. Generally, keys are used for device secured booting, software decryption/inscription and authentication, secure session communication with peers over standard interfaces, and content protection (e.g., digital write management).

(7) For example, in order for a component connected to a computer system to communicate with another component, it may be necessary that the communication be secure. That is, the contents of the communication are known only to the sending component and receiving component and cannot be deciphered by another component. In such a case, a key may be utilized to encrypt the communication such that the sending component and the receiving component are provided the key to decipher the communication, whereas a component not possessing the key will not be able to decipher the information in the communication.

(8) In order to distribute the keys, a key distribution system, (e.g., over a private key distribution bus (PKDB)) is utilized to distribute keys securely from a processor such as a security processor to submodules. The submodules physical locations in a system on chip (SOC) may reside anywhere within the SOC. Accordingly, key distribution capability may be provided with the least amount of hardware use and clock resources.

(9) Although described in additional detail below, a system on chip is a device where many components of an entire system are resident on a chip. For example, a system on chip may include a processor, memory, storage, input and output drivers, and other components on a single chip.

(10) Further, as described in additional detail below, the private key distribution bus is therefore implemented as part of a separate system management network within the system on chip that may include a master security processor which creates and distributes keys and multiple slave modules that utilize keys, such as the submodules mentioned above.

(11) A method for distributing keys in a key distribution system includes receiving a connection for communication from a first component. A determination is made whether the first component requires a key be generated and distributed. Based upon a security mode for the communication, the key generated and distributed to the first component.

(12) A key distribution system includes a first module and a processor operatively coupled with and in communication with the first circuitry. The processor is configured to receive a connection for communication from a first component via the first module, determine whether the first component requires a key be generated and distributed, and based upon a security mode for the communication, generate the key and distribute the key to the first component through the first module.

(13) A non-transitory computer-readable medium for distributing keys in a computer system, the non-transitory computer-readable medium having instructions recorded thereon that, when executed by the processor, cause the processor to perform operations. The operations include receiving a connection for communication from a first component. A determination is made whether the first component requires a key be generated and distributed. Based upon a security mode for the communication, the key generated and distributed to the first component.

(14) FIG. 1 is a block diagram of an example device **100** in which one or more features of the disclosure can be implemented. The device **100** can include, for example, a computer, a server, a gaming device, a handheld device, a set-top box, a television, a mobile phone, or a tablet computer. The device **100** includes a processor **102**, a memory **104**, a storage **106**, one or more input devices **108**, and one or more output devices **110**. For purposes of example, the output device **110** is shown as being a display **110**, however, it is understood that other output devices could be included.

(15) The device **100** can also optionally include an input driver **112** and an output driver **114**. Additionally, the device **100** includes a memory controller **115** that communicates with the processor **102** and the memory **104**, and also can communicate with an external memory **116**. In some embodiments, memory controller **115** will be included within processor **102**. Additionally, the device **100** includes a security processor **210** which will be described in further detail below, which is in communication with the input driver **112**, output driver **114** and the memory controller **115**. It is understood that the device **100** can include additional components not shown in FIG. 1.

(16) As discussed above, the processor **102**, memory **104**, storage **106**, input driver **112**, output driver **114**, memory controller **115** and security processor **210** may be included on a system on chip **101**. Additionally, the memory controller **115** may include a processor, or processing circuitry, for performing operations.

(17) In various alternatives, the processor **102** includes a central processing unit (CPU), a graphics processing unit (GPU), a CPU and GPU located on the same die, or one or more dies, wherein each processor die can be a CPU or a GPU. In various alternatives, the memory **104** is located on the same die as the processor **102**, or is located separately from the processor **102**. The memory **104** includes a volatile or non-volatile memory, for example, random access memory (RAM), dynamic RAM, or a cache.

(18) The storage **106** includes a fixed or removable storage, for example, a hard disk drive, a solid state drive, an optical disk, or a flash drive. The input devices **108** include, without limitation, a keyboard, a keypad, a touch screen, a touch pad, a detector, a microphone, an accelerometer, a gyroscope, a biometric scanner, or a network connection (e.g., a wireless local area network card for transmission and/or reception of wireless IEEE 802 signals). The output devices **110** include, without limitation, a display, a speaker, a printer, a haptic feedback device, one or more lights, an antenna, or a network connection (e.g., a wireless local area network card for transmission and/or reception of wireless IEEE 802 signals).

(19) The input driver **112** communicates with the processor **102** and the input devices **108**, and permits the processor **102** to receive input from the input devices **108**. The output driver **114** communicates with the processor **102** and the output devices **110**, and permits the processor **102** to

send output to the output devices **110**. It is noted that the input driver **112** and the output driver **114** are optional components, and that the device **100** will operate in the same manner if the input driver **112** and the output driver **114** are not present.

(20) The external memory **116** may be similar to the memory **104**, and may reside in the form of off-chip memory. Additionally, the external memory may be memory resident in a server where the memory controller **115** communicates over a network interface to access the external memory **116**. For example, the external memory may be a dynamic random access memory (DRAM) that is external to the system on chip **101**. In addition, the external memory **116** may be external to the system **100**.

(21) FIG. 2 is a block diagram of an example key distribution system **200**, based on which one or more features of the disclosure can be implemented. The key distribution system **200** includes various components, which may be circuitry, software, or software controlled components. Additionally, in an example embodiment, the key distribution system **200** includes components that reside in the system on chip **101**. For example, the key distribution system **200** is a subset of components that are resident in the system on chip **101**.

(22) That is, in an example embodiment as shown in FIG. 2, the key distribution system **200** includes a security processor **210**. The security processor **210** allocates and distributes keys to components based upon a mode of operation of the security processor **210**. For example, the security processor **210** may operate in a secured mode or an unsecured mode.

(23) The security processor communicates with submodules **220** in order to provide keys over a dedicated bus, such as the private key distribution bus. The submodules **220** may include circuitry, software, or software controlled circuitry that is connected to a component that utilizes a key to function.

(24) The submodules may **220** include, for example, a Peripheral Component Interconnect Express (PCIe) module **220A**, a video core next (VCN) module **220B**, a display core next (DCN) module **220C** and a unified memory controller (UMC) module **220N**. Each submodule **220** is connected to the security processor **210** in order to receive information from the security processor **210** as well as communicate to the security processor **210**.

(25) The PCIe module **220A**, for example, may be a PCIe controller or PCIe network adapter. The PCIe module **220A** may have PCIe devices attached to it, such as a video graphics card or a network card to connect to a network, for example. That is, in one example, a PCIe device may be a graphics accelerator card that is utilized for processing graphic images for display. In another example, a PCIe device may be a network interface card, such as a wireless network adapter card to allow connection to a wireless network. The PCIe module **220A** may require a key in order to conduct secure communication, where a key is utilized to encrypt and decrypt data in the communication.

(26) The video core next module **220B** may be for a multimedia processor. For example, the video core next module **220B** may be utilized for processing specific data associated with an application, such as processing a streaming service video stream. Each streaming service may include its own processing technique that is unique from a different streaming service. Accordingly, there may exist multiple video core next modules **220B** for different streaming services which may receive data from a wireless network or the Internet, for example.

(27) The display core next module **220C** may be for a display driver. For example, the display core next module **220C** may be utilized as an output driver (e.g., output driver **114**) to control a display such as display **110**. The display core next module **220C** may control information to and from a display **110** in order to provide video or image information on the display **110** from the system **100**. The display core next module **220C** may require a key in order to permit the display **110** to display data that may be encrypted.

(28) The unified memory controller **220N** may, in an example, be the memory controller **115** as shown in FIG. 1. The unified memory controller **220N** controls access to internal and external

memory such as memory **104** and external memory **116**. Read operations and write operations are controlled by the unified memory controller **220N** to allow a device to perform a write to a memory area or a read from a memory area. Accordingly, the unified memory controller **220N** module may require encryption to read or write encrypted data.

(29) Although four example submodules **220** are shown in FIG. 2 (i.e., PCIe module **220A**, video core next module **220B**, display core next module **220C** and unified memory controller module **220N**), it should be understood that additional submodules (not shown) that may utilize keys can also be connected to the security processor **210** to receive keys for the submodules **220** to utilize for uses such as secure communication, among other uses as described above.

(30) As discussed above, each of these submodules (e.g., PCIe module **220A**) may require a key to enable operations such as secure communication, for example. The security processor **210** accordingly provides keys to the PCIe module **220A**, video core next (video) module **220B**, display core next (display) module **220C** and unified memory controller module **220N**, as well as any other module that may be connected to the security processor **210**. The security processor **210** provides the keys over the secure dedicated private key distribution bus.

(31) FIG. 3 is a flowchart of an example method **300** for distributing keys, based on which one or more features of the disclosure can be implemented. In step **310**, a submodule **220** connects to the security processor **210**.

(32) For example, referring back to FIGS. 1 and 2, a PCIe component (e.g., a PCIe network card) may be connected to the overall system **100**. Upon the connection, the PCIe module **220A** connects to the security processor **210** via the private key distribution network shown in FIG. 2. The security processor **210** detects this connection upon the PCIe component connection with the PCIe module **220A** via the private key distribution bus.

(33) As mentioned above, the security processor **210** may operate in a secure mode or an unsecured mode. The security processor **210** may operate in a secure mode in a case where security is required. For example, where multiple connections of components that should remain isolated from one another are attached to the security processor **210**, the security processor **210** may operate in a secure mode that requires keys for secure connections. It should also be noted that other reasons for having secure communication that are not described may be utilized by the security processor **210** to require keys.

(34) Alternatively, the security processor **210** may be operating in an unsecured mode. In this mode, communications may not need to be secured by a key. For example, the security processor **210** may determine that components do not require isolation from one another and therefore secure communications are not required to be protected by a key. It should also be noted in this case, other reasons that are not described may be utilized by the security processor **210** to not require keys for secure communication.

(35) Accordingly, based upon a security mode that the security processor **210** is in (e.g., secure mode or unsecured mode), the security processor **210** determines whether or not the submodule **220** requires a key (step **320**). That is, it is determined, for example, by the security processor **210** whether or not the submodule **220** requires secure communication that is to be encrypted with a key.

(36) If the submodule **220** is determined by the security processor **210** to require secure communication (step **320**), then the security processor **210** allocates a key to the submodule **220** and distributes the key to the submodule (step **330**). That is, for example, if the security processor **210** is operating in the secure mode, the security processor determines in step **320** that a key is required for the submodule **220** that has connected to the security processor **210**.

(37) The allocation includes, for example, determining a key size by the security processor **210** and any associated rules on the key use by the security processor **210**. For example, the security processor may allocate a 4 byte key for use by the submodule **220** that has connected to the security processor **210**. In addition, the security processor **210** may determine a rule such as the key is only

permitted to be used, but may not be requested to be destroyed by the submodule **220**.

(38) Once the security processor **210** allocates a key size and key for use by the submodule **220**, the security processor distributes the key by sending the key to the submodule **220** over the private key distribution network. In the example of a PCIe network card (e.g., wireless) connecting to the security processor **210** via the PCIe submodule **220A**, the security processor **210** may determine that a particular size key is to be utilized for that component that is communicating wirelessly to an external device.

(39) In this manner, the security processor **210** is in control of the generation/allocation of the key and the distribution of the key to components connected to the security processor **210** via the private key distribution bus. In addition, if the security processor **210** is not operating in the secure mode, the security processor **210** may allow connection by the submodule **220** that has connected to the security processor **210** and also allow communication between that connecting component and the system **100**.

(40) It is also possible that the mode of the security processor **210** may change from secure mode to unsecured mode, and vice versa. Should a change occur, depending on the mode the security processor **210** is operating in, the change in operation mode may require a change in key distribution.

(41) Accordingly, in step **340**, if the security mode of the security processor **210** changes, then the security processor **210** zeroes all keys that have been generated/allocated and distributed to any submodules **220** (step **350**). That is, the security processor **210** destroys existing keys so the keys may no longer be used by a component if requested. For example, if the security processor **210** is operating in a secure mode and changes to an unsecured mode in step **350**, the security processor destroys existing keys that have been distributed to any submodules **220**. The destruction of the keys may include deleting generated/allocated keys and any associated rules for the use of those keys.

(42) In the example described above relating to the connection of the PCIe network card, the security processor **210** may change from a secure operation mode to the unsecured operation mode. Upon changing modes, the security processor **210** may delete a key allocated and distributed to the PCIe submodule **220A** for use by the PCIe network card. Accordingly, the PCIe network card would no longer utilize that key for secure communication.

(43) Accordingly, as described above, a secure unidirectional key distribution system is described. The generation/allocation and distribution of keys are controlled by a security processor (e.g., **210**) that is central in connection to one or more submodules (e.g., PCIe module **220A**, video core next module **220B**, display core next module **220C** and unified memory controller module **220N**).

(44) The security processor **210** that generates/allocates the keys further distributes the keys over a secure network to a submodule **220** upon connection. In this manner, keys are not requested by connecting components to a system controlled by the security processor **210**, but are only distributed by the security processor **210** to submodules **220** upon connection.

(45) The keys may be zeroed (e.g., destroyed as described above) by the security processor **210** upon the changing of a mode of the security processor **210** from a secure mode to an unsecured mode. In this manner, the security processor **210** determines whether secured or unsecured communication is permitted in the system on chip **101** within the system **100**. Further, the security processor **210** controls all the allocation and distribution of keys to the submodules **220** for use by component connected through the submodules **220** via the private key distribution bus.

(46) Should the security processor be operating in a secure mode or changing from an unsecured mode to a secure mode of operation, then new keys generated and distributed by the security processor **210** to components connecting through a submodule **220** as those components connect to the security processor **210**. Again, the security processor centrally controls all the allocation and distribution of keys to the submodules **220** for use by component connected through the submodules **220** via the private key distribution bus in the secure mode.

(47) It should be noted again that any number of submodules **220** (e.g., components connecting through an associated submodule **220**) can be added or removed from the key distribution system and the security processor **210** adjusts the generation and distribution of keys accordingly based upon the connection of components connected to the system **100** via the submodules **220**. That is, should a component disconnect from the security processor **210**, the key allocated and distributed to that component via the associated submodule **220** may be zeroed as described above. The security processor **210** controls the allocation and the distribution of keys over the private key distribution bus, which is isolated from components outside of security processor **210** and the submodules **220**. The security processor **210** and submodules **220** may be implemented via circuitry, hardware, or software controlled hardware, for example.

(48) It should be understood that many variations are possible based on the disclosure herein. Although features and elements are described above in particular combinations, each feature or element can be used alone without the other features and elements or in various combinations with or without other features and elements.

(49) In addition, it should be understood that, although steps of the methods provided above are shown in a particular order, steps can be performed in a different order than shown. As described above, the method or methods provided above are example methods for distributing keys, based on which one or more features of the disclosure can be implemented. Accordingly, some steps may also be performed independent of others. That is, the methods described above may include one or more steps not being performed, or one or more steps performed simultaneously.

(50) The methods provided can be implemented by system on chip components (of FIGS. **1** and **2**) in a general-purpose computer, a processor, or a processor core. Suitable processors include, by way of example, a general-purpose processor, a special purpose processor, a conventional processor, a digital signal processor (DSP), a plurality of microprocessors, one or more microprocessors in association with a DSP core, a controller, a microcontroller, Application Specific Integrated Circuits (ASICs), Field Programmable Gate Arrays (FPGAs) circuits, any other type of integrated circuit (IC), and/or a state machine. Such processors can be manufactured by configuring a manufacturing process using the results of processed hardware description language (HDL) instructions and other intermediary data including netlists (such as instructions capable of being stored on a computer readable media). The results of such processing can be mask works that are then used in a semiconductor manufacturing process to manufacture a processor which implements aspects of the embodiments.

(51) The methods or flow charts provided herein can be implemented in a computer program, software, or firmware incorporated in a non-transitory computer-readable storage medium for execution by a general-purpose computer or a processor or hardware finite state machines. Examples of a non-transitory computer-readable medium include read only memory (ROM), random-access memory (RAM), a register, cache memory, semiconductor memory devices, magnetic media such as internal hard disks and removable disks, magneto-optical media, and optical media such as CD-ROM disks, and digital versatile disks (DVDs).

Claims

1. A method performed by a system on chip (SOC) for managing security keys, the method comprising: detecting, via a private key distribution bus of the SoC, that a device is connected to a first component of the SoC; in response to the detecting: generating a key based on the device requiring the key and a security mode of the SoC, and distributing, via the private key distribution bus of the SoC, the key to the first component; and selectively destroying the key in response to changes associated with the security mode.
2. The method of claim 1 wherein upon the security mode being a first security mode in operation for communication, the key is generated and distributed to the first component.

3. The method of claim 1 wherein a key size is selected for generation based upon a type of the device.
 4. The method of claim 2, further comprising switching from the first security mode to a second security mode.
 5. The method of claim 1, wherein the key is selectively destroyed when the security mode changes from a secure mode to a non-secure mode.
 6. The method of claim 1, further comprising: destroying the key when the device is disconnected.
 7. The method of claim 6, further comprising deleting an associated rule for the key generated for the first component.
 8. The method of claim 1 wherein the first component includes one or more of a Peripheral Component Interconnect Express (PCIe) component, a video component, a display component or a unified memory controller component.
 9. The method of claim 1, wherein the device is a video graphics card or a network card.
 10. The method of claim 1, wherein the first component is a PCIe controller or PCIe network adapter.
 11. A key distribution system, comprising: a first module; a private key distribution bus; and a processor communicatively the first module via the private key distribution bus, wherein the processor configured to: detect, via the private key distribution bus, that a device connected to the first module, in response to the device being detected: generate a key based on the device requiring the key and a security mode of the processor, and distribute, via the private key distribution bus, the key to the first module, and selectively destroy the key in response to changes associated with the security mode.
 12. The key distribution system of claim 11 wherein upon the security mode being a first security mode in operation for communication, the key is generated and distributed to the first module.
 13. The key distribution system of claim 12, further comprising the processor switching from the first security mode to a second security mode.
 14. The key distribution system of claim 13 wherein the key is selectively destroyed when the security mode changes from a secure mode to a non-secure mode.
 15. The key distribution system of claim 11 wherein a key size is selected for generation based upon a type of the device.
 16. The key distribution system of claim 11 wherein the processor is further configured to destroy the key when the device is disconnected.
 17. The key distribution system of claim 11 wherein the first module includes one or more of a Peripheral Component Interconnect Express (PCIe) component, a video component, a display component or a unified memory controller component.
 18. The key distribution system of claim 11, wherein the device is a video graphics card or a network card.
 19. A non-transitory computer-readable medium for managing security keys, the non-transitory computer-readable medium having instructions recorded thereon that, when executed by a processor of a system on chip (SOC), cause the SoC to perform operations including: detecting, via a private key distribution bus of the SoC, that a device is connected to a first component of the SoC; in response to the detecting: generating a key for the first component based on the device requiring the key and a security mode of the SoC, and distributing, via the private key distribution bus of the SoC, the key to the first component; and selectively destroying the key in response to changes associated with the security mode.
 20. The non-transitory computer-readable medium of claim 19, wherein the device is a video graphics card or a network card.
-