

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413642
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Mesde; Roland et al.

Plug-in orchestrator for vehicle data stream subscription system

Abstract

A vehicle data streaming service may receive requests to register plug-ins to generate synthetic vehicle attribute data streams. A plug-in service of the vehicle data streaming service may configure a given plug-in in an internal containerized environment in a fully automated manner and/or configure the plug-in in an external compute service environment. The vehicle data streaming service may configure the plug-ins to receive input streams to generate synthetic attribute output streams. The vehicle data streaming service and the plug-in service may allow the synthetic attribute output streams to be associated with synthetic vehicle attributes included, or to be included, in a curated catalog of vehicle attributes. The vehicle data streaming service furthermore allows one or more vehicle data stream destinations to subscribe to the synthetic vehicle attributes included in the catalog.

Inventors: Mesde; Roland (Cupertino, CA), Bessonov; Alex (San Jose, CA), Hilario; Paolo Gruenberg (West Linn, OR), Hodara; Roie (Berlin, DE), Pyasi; Madhur (Berlin, DE), Hochmuth; Sebastian (Adlischil, CH)

Applicant: Amazon Technologies, Inc. (Seattle, WA)

Family ID: 90243483

Assignee: Amazon Technologies, Inc. (Seattle, WA)

Appl. No.: 17/809868

Filed: June 29, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240098143 A1	Mar. 21, 2024

Publication Classification

Int. Cl.: H04L67/12 (20220101); H04L41/0806 (20220101)

U.S. Cl.:

CPC H04L67/12 (20130101); H04L41/0806 (20130101);

Field of Classification Search

CPC: H04L (63/123); H04L (2209/84); H04L (43/04); H04L (67/12); H04L (41/0895); H04L (41/0806); H04L (41/149); H04L (67/1396); G06F (16/9035); G06F (16/908); G06Q (30/0252); G06Q (30/0603); G06N (5/022)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7177859	12/2006	Pather	N/A	G06F 16/9535
10160456	12/2017	Jun	N/A	N/A
11832416	12/2022	Albright	N/A	G06T 19/003
11924210	12/2023	Zhang	N/A	G06F 21/6218
2008/0164997	12/2007	Aritsuka	340/539.13	G01S 5/0009
2008/0178143	12/2007	Dougan	717/100	G06F 8/20
2014/0189814	12/2013	Marten	726/4	G08G 1/205
2014/0280177	12/2013	Ish, II	N/A	N/A
2016/0050269	12/2015	Botticelli	N/A	N/A
2016/0241676	12/2015	Armstrong	N/A	G06F 16/24568
2017/0011129	12/2016	Matsumoto	N/A	G06F 40/194
2017/0026858	12/2016	Mckee	N/A	H04W 24/04
2017/0138625	12/2016	Shiratori	N/A	F24F 11/89
2018/0183873	12/2017	Wang	N/A	H04L 67/12
2018/0268115	12/2017	Zhang	N/A	G06F 9/455
2019/0036830	12/2018	Yamato	N/A	H04M 11/00
2019/0280944	12/2018	Bellini	N/A	G06F 16/2379
2019/0349447	12/2018	Adams	N/A	G06F 9/5027
2020/0007663	12/2019	Abilay	N/A	H04W 4/48
2020/0036774	12/2019	Tada	N/A	G06F 9/541
2020/0151611	12/2019	McGavran	N/A	G09B 29/102
2020/0312128	12/2019	Higuchi	N/A	G08G 1/096791
2020/0336541	12/2019	Naderi Alizadeh	N/A	H04L 67/01
2021/0035124	12/2020	Morton	N/A	G06F 16/00
2021/0075858	12/2020	Naito	N/A	H04L 67/12
2022/0232010	12/2021	Zhang	N/A	H04L 63/0884
2022/0383019	12/2021	Tremblay	N/A	G06V 40/11
2023/0008976	12/2022	Xu	N/A	H04L 9/3247
2023/0065491	12/2022	Ren	N/A	G06V 40/161
2023/0205670	12/2022	Cardoso	717/126	G06F 11/3692
2023/0325247	12/2022	Hassani	718/103	G06F 9/4881
2023/0377383	12/2022	Makita	N/A	H04L 67/565
2024/0096139	12/2023	Mesde et al.	N/A	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 17/710,585, filed Mar. 31, 2022, Roland Mesde, et al. cited by applicant
U.S. Appl. No. 17/710,634, filed Mar. 31, 2022, Roland Mesde, et al. cited by applicant
U.S. Appl. No. 17/710,644, filed Mar. 31, 2022, Roland Mesde, et al. cited by applicant
U.S. Appl. No. 17/710,551, filed Mar. 31, 2022, Roland Mesde, et al. cited by applicant
U.S. Appl. No. 17/806,434, filed Jun. 10, 2022, Roland Mesde, et al. cited by applicant
U.S. Appl. No. 17/809,878, filed Jun. 29, 2022, Roland Mesde, et al. cited by applicant
U.S. Appl. No. 17/810,301, filed Jun. 30, 2022, Roland Mesde, et al. cited by applicant
U.S. Appl. No. 19/173,992, filed Apr. 9, 2025, Roland Mesde, et al. cited by applicant

Primary Examiner: Dollinger; Tonia L

Assistant Examiner: Nguyen; Linh T.

Attorney, Agent or Firm: Kowert, Hood, Munyon, Rankin & Goetzel, P.C.

Background/Summary

BACKGROUND

(1) Modern vehicles, such as cars, trucks, motorcycles, etc. are often equipped with electronic sensors and computer systems that are programmed to take inputs from such electronic sensors to control various actions for the vehicle (or systems implemented in the vehicle). These electronic sensors and computer systems generate various types and quantities of data. Data generated from these sensors of the vehicle may be stored or transmitted for use by various entities, such as downstream applications or data analytics.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates a vehicle data streaming service includes a plug-in service, wherein the plug-in service is configured to receive a request to register a plug-in. The plug-in service of the vehicle data streaming service, in response to such a request, configures a plug-in in the data streaming service and configures the plug-in to receive input streams to generate a synthetic attribute output stream. The vehicle data streaming service and the plug-in service allow the synthetic attribute output stream to be associated with a synthetic vehicle attribute included, or to be included, in a curated catalog of vehicle attributes managed by the data-streaming service. The vehicle data streaming service also allows a vehicle data stream destination to subscribe to the synthetic vehicle attribute included in the catalog. Additionally, the vehicle data streaming service manages the plug-in service and the vehicle attribute catalog, according to some embodiments.

(2) FIG. 2 illustrates a more detailed view of the vehicle data streaming service that includes the plug-in service and illustrates a registration flow of a data stream source for a synthetic vehicle attribute to be provided by a plug-in. The vehicle data streaming service receives streamed vehicle data to be processed by the plug-in, and the plug-in processes the received data to generate an output stream for a synthetic vehicle attribute. The vehicle data streaming service also manages a subscription flow for the synthetic vehicle attribute, in addition to managing a vehicle attribute catalog comprising synthetic vehicle attributes (along with non-synthetic vehicle attributes). Additionally, the plug-in service of the vehicle data streaming service manages the registration of

the plug-in, while the data streaming service manages subscription of a generated synthetic vehicle attribute to a subscribing destination, according to some embodiments.

(3) FIG. 3 illustrates a more detailed view of the vehicle data streaming service that includes a plug-in service configured to orchestrate configuration of a plug-in using a customer configurable plug-in orchestration environment. For example, the customer configurable plug-in orchestration environment may be configured using a customer specified execution environment in a compute service outside the vehicle data streaming service. The plug-in service of the vehicle data streaming service may configure the plug-in and/or configure input data streams for the plug-in, such that the plug-in is located in the customer specified execution environment and the input data streams are routed to the customer specified execution environment. Also, the plug-in service of the vehicle data streaming service may configure the plug-in and/or configure output data streams from the plug-in, such that the vehicle data streaming service receives a synthetic attribute data stream from the plug-in executing in the customer configurable plug-in orchestration environment, according to some embodiments.

(4) FIG. 4 illustrates a more detailed view of the vehicle data streaming service having a fully automated plug-in orchestrator able to configure an execution environment within the vehicle data streaming service. The fully automated plug-in orchestrator of the vehicle data streaming service may configure the plug-in in a plug-in container and associate a plug-in data stream generated from the plug-in to a synthetic attribute, according to some embodiments.

(5) FIG. 5 illustrates a more detailed view of the vehicle data streaming service and management of the vehicle data streaming service, including management of: a vehicle attribute, a synthetic vehicle attribute, and a plug-in service, according to some embodiments.

(6) FIG. 6 illustrates a more detailed view of the data streaming service, wherein the data streaming service is configured to receive multiple data streams as inputs to a plug-in, and wherein the plug-in is configured to generate multiple synthetic vehicle attributes. The vehicle data streaming service is also configured to manage subscription requests for vehicle attributes and synthetic vehicle attributes. The vehicle data streaming service is also configured to manage changes and/or errors arising from the plug-in and/or inputs to the plug-in from the vehicle data streaming service, according to some embodiments.

(7) FIG. 7 illustrates a flowchart of operations performed by a vehicle data streaming service to register a plug-in for a synthetic vehicle attribute and to provide a plug-in output stream for the synthetic vehicle attribute, according to some embodiments.

(8) FIG. 8 illustrates a flowchart of operations performed by a vehicle data streaming service to provide a plug-in output stream for a synthetic vehicle attribute using a customer specified compute instance or a plug-in container configured within the streaming service, according to some embodiments.

(9) FIG. 9 illustrates a block diagram illustrating an example computer system that implements some or all of the techniques described herein, according to some embodiments.

(10) While embodiments are described herein by way of example for several embodiments and illustrative drawings, those skilled in the art will recognize that embodiments are not limited to the embodiments or drawings described. It should be understood that the drawings and detailed description thereto are not intended to limit embodiments to the particular form disclosed, but on the contrary, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope as defined by the appended claims. The headings used herein are for organizational purposes only and are not meant to be used to limit the scope of the description or the claims. As used throughout this application, the word “may” is used in a permissive sense (i.e., meaning having the potential to), rather than the mandatory sense (i.e., meaning must). Similarly, the words “include,” “including,” and “includes” mean including, but not limited to.

DETAILED DESCRIPTION OF EMBODIMENTS

(11) The systems and methods described herein include techniques for implementing a vehicle data

streaming service for receiving and registering a plug-in, configuring the plug-in, and generating a synthetic attribute output stream. Vehicles may be equipped with electronic sensors which may generate data to be utilized for various applications—from increasing fuel efficiency of a vehicle to enhancing greater degrees of automation using artificial intelligence (AI). Vehicles may use data received from such sensors to improve vehicle performance. In some embodiments, a plug-in may be used to enrich/process such sensor data to generate other useful synthetic data. The vehicle data streaming service may configure a plug-in to receive a stream of vehicle data and provide an output stream for a synthetic vehicle attribute. However, in order to utilize such a plug-in, the vehicle data streaming service may require the vehicle streaming service to manage various components. For example, for a given synthetic vehicle attribute, there may be multiple data stream providers, data processing plug-ins, and data stream receivers that may need to be coordinated. The management of various plug-ins, input sources for plug-ins, recipients of output data from plug-ins (e.g., synthetic vehicle attributes), and presentment of various synthetic vehicle attributes generated by plug-ins to potential subscribers poses a non-trivial challenge. For example, for a given set of data streams generated from a vehicle, there may be a multitude of specialized data stream providers respectively managing portions of the vehicle sensor data. Furthermore, there may be a multitude of data stream destinations respectively interested in receiving all or only certain portions of the vehicle data processed by the plug-in. In some embodiments, the plug-in may be designed to only receive a select portion of vehicle data generated by the vehicle and included in the data streaming service. For example, only a select subset of available vehicle streams may be pertinent to analysis to be performed using the plug-in. Sending all available data from a vehicle (or vehicle data streaming service) may not only create unnecessary network load involved in the transfer of the large amount of data but may also create inefficiencies in requiring the destination to filter out irrelevant vehicle data.

(12) In some embodiments, the vehicle data streaming service may associate vehicle data stream sources to a plug-in that generates synthetic vehicle attributes and allow vehicle data stream consumers to receive the data streams corresponding to the synthetic vehicle attributes that comprise data generated by the plug-in, e.g. plug-in processed data. In some embodiments, the vehicle data streaming service may manage mappings and connections of synthetic vehicle attributes to the plug-ins and to the various subscribers of the synthetic vehicle attributes. Moreover, in some embodiments, the vehicle data streaming service may facilitate the movement of vehicle data from various plug-ins to stream destinations by providing a curated catalog of vehicle attributes, including the synthetic vehicle attributes. The curated catalog of vehicle attributes/synthetic attributes may be used by vehicle plug-in sources to register and associate their plug-in to synthetic vehicle attributes of the catalog. The vehicle data streaming service may allow vehicle data stream destinations (or customers associated with the data stream destinations) to subscribe to the synthetic vehicle attributes in the vehicle catalog. For example, the vehicle data streaming service may obtain the streamed vehicle data from the vehicle data stream source, route at least a portion of the vehicle data to the plug-in, and send streamed data outputted from the plug-in into the vehicle data stream destinations. The vehicle data streaming service may further provide governance of the registration/subscription process for the plug-in (and/or other data streams) and enforce data schema requirements and access requirements. Additionally, the vehicle data streaming service may manage the vehicle attribute catalog and aid the discovery of pertinent vehicle attributes, including synthetic vehicle attributes. In some embodiments, the vehicle streaming service may manage the configuration of one or more plug-ins that are registered. The one or more plug-ins may be instantiated inside the vehicle data streaming service in a fully automated manner and/or outside of the vehicle data streaming service in a customer configurable compute service environment as further discussed in FIGS. 3 and 4.

(13) FIG. 1 illustrates a vehicle data streaming service that receives a request to register a plug-in. The plug-in service of the vehicle data streaming service configures the plug-in and receive input

streams to generate a synthetic attribute output stream. The vehicle data streaming service and the plug-in service allows the synthetic attribute output stream to be associated with a synthetic vehicle attribute included, or to be included, in a curated catalog of vehicle attributes. The vehicle data streaming service also allows a vehicle data stream destination to subscribe to the synthetic vehicle attribute included in the catalog. Additionally, the vehicle data streaming service manages the plug-in service and the vehicle attribute catalog, according to some embodiments.

(14) In FIG. 1, a vehicle data streaming service **100** includes a vehicle attribute catalog **130** and a plug-in service **110**. The plug-in service may receive a request to register a plug-in for a synthetic vehicle attribute **104**. A plug-in service interface **112** of the plug-in service **110** may receive the request to register a plug-in for a synthetic vehicle attribute **104** and send a plug-in configuration instruction request **105** in response. A plug-in may be any software, script, add-on, or extension that processes data for the vehicle data streaming service **100**. In some embodiments, the plug-in may take in as inputs one or more data streams, perform one or more data processing operations, and send as outputs one or more processed data streams associated with synthetic vehicle attributes. The plug-in configuration instruction request **105** may be a request for one or more configurations that are required to instantiate and operate the plug-in via a fully automated plug-in orchestrator **120** and/or a customer configurable plug-in orchestrator **114**. For example, the plug-in configuration may request the destination address of a container or a compute service to run the plug-in. The fully automated plug-in orchestrator **120** will further be described in FIG. 4, and the customer configurable plug-in orchestrator **114** will further be described in FIG. 3.

(15) Once the plug-in service **110** receives the plug-in configuration instruction request **105** wherein the request is in accordance with configuration and instructions requirements for plug-ins, the plug-in source may send the plug-in and configuration instruction **106** to the plug-in service interface **112**. The plug-in configuration instruction may include instructions to instantiate the plug-in in a customer configured environment using the customer configurable plug-in orchestrator **114** and/or automatically instantiate the plug-in on behalf of the customer using the fully automated plug-in orchestrator **120**. In some embodiments, the instructions may include a number of resources to be configured for the plug-in environment. Once the plug-in service interface **112** receives the plug-in, the plug-in may be stored in a plug-in service storage **118**. The plug-in service storage **118** may be implemented as a centralized datastore so that other data storage services may access data stored in the centralized datastore for processing and/or storing within other data storage services, in some embodiments. Such a data storage service **240** may be implemented as an object-based data store and may provide storage and access to various kinds of objects. The data storage service **240** may also be implemented as a file-based data store and provide storage and access to files for putting, updating, and getting various storage objects of various types, sizes pertinent to the plug-in.

(16) In some embodiments, the fully automated plug-in orchestrator **120** may include a plug-in container **122** and a resource management module **124**. The plug-in container **122** may be a software execution environment that implements code and all the code's dependencies allowing an application to run in a way that is agnostic from one computing environment to another. The plug-in container **122** may include and/or be configured with various software components needed to run a plug-in, including: application code, application runtime, system tools, system libraries and settings. The resource management module **124** may monitor the resource impact of the plug-in, for example on the vehicle data streaming service **100** or computing resources allocated for use by the vehicle data streaming service **100**. For example, the resource management module **124** may monitor an amount of memory and/or processing activity of the vehicle data streaming service **100** that is used by the plug-in executing in the plug-in container **122** and may initiate workflows to limit an amount of computing resources used by the plug-in.

(17) The vehicle data streaming service **100** may furthermore enable management of the vehicle attribute catalog **130** and the changing of one or more governance policies of the vehicle data

streaming service **100**. In some embodiments, the vehicle data streaming service **100** may allow one or more users to create, update, or delete vehicle attributes/synthetic vehicle attributes as well as one or more pieces of associated metadata for the vehicle attributes/synthetic vehicle attributes. For example, a name assigned to the synthetic vehicle attribute A **132** and a synthetic vehicle attribute B **134** may be updated using the vehicle data streaming service **100**. The vehicle data streaming service **100** may allow one or more users to manage aspects of the vehicle streaming service **140**, such as what vehicle attributes and/or synthetic vehicle attributes are included in a curated catalog, as well as what names are assigned to the respective vehicle attribute and/or synthetic vehicle attributes. In some embodiments, users may further be able to define access requirements for potential subscribers that would like to subscribe to various data streams. In some embodiments, the one or more users may be able to configure the vehicle data streaming service **100** including a plug-in service **110**. The management of vehicle streaming service will be further described in FIG. 5.

(18) Although FIG. 1 depicts only one plug-in source **102**, any number of plug-in sources may be sent to the vehicle data streaming service **100**. The vehicle data streaming service **100** may, in various embodiments, be an apparatus or system for managing the distribution, storage, retrieval, and/or processing of large-scale vehicle data streams. The vehicle data streaming service **100** may be designed to handle hundreds or even thousands of concurrent data sources and destinations. The term “data stream”, as used herein, refers to a sequence of vehicle data records that may be generated by one or more data sources (e.g., vehicle sensors, vehicle synthetic sensors, etc.) or producers (e.g., a vehicle, a vehicle service center, etc.) and accessed by one or more vehicle data consumers at one or more destinations.

(19) Please note that the previous description of a vehicle data streaming service **100** is a logical illustration and thus is not to be construed as being limited to a specific implementation of network addresses, system interfaces, or various other features. In some embodiments, various other registration flow steps may be used to associate a vehicle data stream from the data stream source **200** (as described below in regard to FIG. 2) to a vehicle attribute of the vehicle attribute catalog **130**. Different combinations or implementations may be implemented in various embodiments.

(20) This specification continues with various examples of a vehicle data streaming service including different components/modules, or arrangements of components/module that may be employed as part of implementing the vehicle data streaming service and the plug-in service included in the vehicle data streaming service. A number of different methods and techniques to implement various methods of implementation of a plug-in and management of the vehicle data streaming service (including the synthetic vehicle attribute catalog) are then discussed, some of which are illustrated in accompanying flowcharts. Finally, a description of an example computing system upon which the various components, modules, systems, devices, and/or nodes may be implemented is provided. Various examples are provided throughout the specification.

(21) FIG. 2 illustrates a more detailed view of the vehicle data streaming service and illustrates a registration flow of a data stream source for a synthetic vehicle attribute. The vehicle data streaming service receives streamed vehicle data to be processed by a plug-in. The plug-in processes the received streamed vehicle data and generates an output stream for a synthetic vehicle attribute. The vehicle data streaming service also handles a subscription flow for the data stream corresponding to the synthetic vehicle attribute, manages a vehicle attribute catalog containing synthetic vehicle attributes, and manages the registration of the plug-in and subscription of the data stream corresponding to the synthetic vehicle attribute by a destination, according to some embodiments.

(22) As an example, in some embodiments, the vehicle data streaming service **100** may receive a request to register data stream source **202** from a data stream source **200**. In some embodiments, the request to register the data stream source **202** may further include a request for a vehicle data stream source to be recognized as a vehicle data stream source by the vehicle data streaming

service **100**. In some embodiments, the request **202** may additionally provide required information to establish a streaming relationship wherein the vehicle data streaming service **100** may be an endpoint of a data pipeline from the vehicle data stream source (wherein the vehicle data streaming service further provides streamed vehicle data provided to the endpoint to vehicle data consumers). In some embodiments, the request to register data stream source **202** may include one or more access credentials required to be recognized as a legitimate data stream source by the vehicle data streaming service **100**. The term “access credentials” or “credentials” are used herein to mean various credentials that verify the identity of the requesting entity and/or authorization granted to the requesting entity that is required to perform the requested action. For example, in some embodiments, the vehicle data streaming service may reject a request made by a user having a verified identity (e.g., known username and password) because the entity associated with the verified identity lacks authorization to access data targeted by the request, e.g., the entity has improper “access credentials” based on a lack of authorization to perform the request.

(23) In some embodiments, the vehicle data streaming service **100** may send registration requirements to the data stream source to complete the registration. The registration requirements may include a source infrastructure identity, a required configuration to conform messages from the data source to a schema, a vehicle attribute to associate to the source, and/or a mapping required to configure the vehicle data schema. The data stream source may further submit the required registration information **110** according to the registration requirements **204** to complete the registration of the data stream source and to effectuate association of the data stream source with one or more vehicle attributes of the vehicle attribute catalog **130**. The various registration interactions may occur through a registration interface **208** of the vehicle data streaming service **100**. In some embodiments, the registration request may require approval by the vehicle data streaming service **100**. In some embodiments, the registration request may require approval obtained as part of interactions involving the management of the vehicle streaming service **140**. Once the registration request is approved, a vehicle data stream conforming to the registration requirements may be streamed to the vehicle data streaming service **210**.

(24) Once the vehicle data streaming service **100** has received the streamed vehicle data, the plug-in service **110** may apply one or more operations to the streamed vehicle data conforming to the registration requirements in order to generate a new output for synthetic attributes. (Note that while this example includes both the registration of a new data stream and the registration of a plug-in, in some embodiments, a plug-in may be configured to use already existing vehicle attributes from already registered data streams).

(25) In some embodiments, the vehicle attribute catalog **130** may generate data for multiple synthetic vehicle attributes. For example, the plug-in service **110** may obtain stream vehicle data **210** from the data stream source **200** to generate synthetic vehicle attribute A **132** and synthetic vehicle attribute B **134**. In some embodiments, one or more data stream destinations **146** may view the vehicle attribute catalog **130** to discover synthetic vehicle attributes available in the vehicle attribute catalog that correspond to data of interest to be received at the data stream destinations. The data stream destination **140** may send a request to view catalog **222** and, based on the received catalog **223**, select one or more vehicle attributes/synthetic vehicle attributes to receive. The subscription request for synthetic attribute **224** and a request to view the catalog **222** may be performed through the subscription interface **226** of the vehicle data streaming service **100**.

(26) In some embodiments, a data stream destination **220** and an entity issuing a request to subscribe to a data stream at the data stream destination may be the same entity or different entities. Upon a successful subscription request for the synthetic attribute **224**, the vehicle data streaming service **100** may create a mapping between the streamed vehicle data conforming to the data stream destination **220**. The vehicle data streaming service **100** may send a streamed vehicle data stream corresponding to the subscription request for the synthetic attribute **224** to the data stream destination **220**. In some embodiments, the streamed vehicle data corresponding to the subscription

request for the synthetic attribute **224** may be modified to conform to the schema of the data stream destination **220**. Furthermore, the data stream destination **220** may be any number of downstream services/applications. In some embodiments, the data stream destination **220** may be a vehicle shadow that allows interaction between a virtual representation of a connected vehicle to a user. In some embodiments, the data stream destination **220** may be a data analytics service, a data lake that provides a repository of vehicle data, and/or other data storage services. In some embodiments, another plug-in may act as a data stream destination for a data stream corresponding to a synthetic vehicle attribute generated by a first plug-in. In such embodiments, the output of the first plug-in may act as a data stream source for the other plug in. A plug-in may receive the streamed vehicle data corresponding to the synthetic attribute as an input stream **229**. For example, one or more plug-ins may be configured during their registration stage (or at different times) to subscribe to a synthetic attribute. Based on the received synthetic attribute data stream, the plug-in may generate another synthetic vehicle attribute. In some embodiments, the required registration information **206** may also contain information similar to the subscription request for the synthetic vehicle attribute **224**. In some embodiments, the plug-in that was previously registered may be modified to subscribe to a different synthetic vehicle attribute and initiate subscription flow as discussed above. (27) Although FIG. 2 depicts only one data stream source **200** and one data stream destination **220**, any number of data sources may send vehicle information to the vehicle data streaming service **100** and any number of data stream destinations may receive vehicle information. Furthermore, as discussed above, in some embodiments, the synthetic vehicle attribute data stream may be streamed to one or more additional plug-ins. Please note that the previous description of a vehicle data streaming service **100** is a logical illustration and thus is not to be construed as being limited to a specific implementation of network addresses, system interfaces, or various other features. In some embodiments, various other registration flow steps may be used to receive a vehicle data stream from the data stream source **200** and process the data stream using a plug-in for a synthetic vehicle attribute of the vehicle attribute catalog **130**. Different combinations or implementations may be implemented in various embodiments.

(28) FIG. 3 illustrates a more detailed view of the vehicle data streaming service that configures a plug-in using a customer configurable plug-in orchestrator. The customer configurable plug-in orchestrator configures a customer specified execution environment in a compute service outside the vehicle data streaming service. A plug-in service of the vehicle data streaming service configures the plug-in and/or configures input data streams for the customer specified execution environment and receives a synthetic attribute data stream, according to some embodiments.

(29) In some embodiments, the customer configurable plug-in orchestrator **114** may send instructions **302** to configure a plug-in in a compute service. The compute service **300** may be configurable by the customer and, in some embodiments, implemented by the provider network of the vehicle data streaming service **100**. The degree in which the customer may configure the compute service **300** may be partial or complete. For example, the compute service **302** may be a service provided for the customer through a same service provider as a service provider providing the data streaming service, or may be a third-party that restricts the customer from configuring the compute service in a certain manner. In some embodiments, the compute service **300** may be implemented by another provider network separate from the provider network of the vehicle data streaming service **100**. The compute service **300** may offer instances, containers, and/or functions according to various configurations for implementing the plug-in, including the generation of a plug-in instance **306**. In some embodiments, the compute service **300** may comprise one or more servers that implement one or more computing instances with respective specified computational capacities. For example, the compute service **300** (and computing instances of the compute service **300**) may be specified by instructions indicating the type and number of CPUs, the main memory size and a specified software stack that are to be used to implement the plug-in. The compute service **300** may provide a virtual operation system or other customers specified execution

environment **304** for executing or implementing the plug-in received by the vehicle data streaming service **100**. The plug-in may be implemented as one or more operations that are performed in response to the vehicle data streaming service **100** sending instructions to configure the plug-in in the compute service **302**. In some embodiments, the instructions to configure plug-in may be instructions to generate the customer specified execution environment **304**. The compute service **300** may receive the instructions to configure the plug-in from the customer configurable plug-in orchestrator **114** and generate the customer specified execution environment **304** according to the instructions. In some embodiments, the instructions to configure the plug-in may establish input data streams **304** and establish synthetic attribute data stream **306**, wherein the input data streams are provided to the compute service **300** and an output stream corresponding to the synthetic vehicle attribute is provided from the compute service **300**. In some embodiments, the customer specified execution environment **304** may be automatically scaled to provide the appropriate number of computing resources to perform the operations in accordance with the plug-in. A number of different types of computing devices may be used singly or in combination to implement the customer specified execution environment **304**, including general purpose or special purpose computer servers, storage devices, network devices and the like.

(30) Various compute instances, containers, and/or functions may be used to operate or implement a variety of different plug-ins. The compute service **300** may support various interpreted or compiled programming languages such as Ruby, Perl, Python, C, C++ and the like, or high-performance computing services. In some embodiments, customer specified execution environment **304** may be configured according to the configuration instruction **106**. For example, the size of compute instances, containers, and/or functions, such as a particular number of virtual CPU cores, memory, cache, storage, as well as any other performance characteristic may be determined by the configuration instruction. Configurations of the compute instances, containers, and/or functions of the customer specified execution environment **304** may furthermore be determined based on the instructions to configure plug-in in the compute service **302**. In various embodiments, the plug-in may be implemented by a particular node or may be distributed across several nodes. Upon establishment of the synthetic attribute data stream **306**, the customer configurable plug-in orchestrator **114** may associate the plug-in stream to one or more synthetic vehicle attributes **308**.

(31) FIG. 4 illustrates a more detailed view of the vehicle data streaming service having a fully automated plug-in orchestrator able to configure an execution environment within the vehicle data streaming service. The fully automated plug-in orchestrator of the vehicle data streaming service may configure the plug-in in a plug-in container and associate a plug-in data stream to a synthetic attribute, according to some embodiments.

(32) In some embodiments, the fully automated plug-in orchestrator **120** may configure a plug-in container **122** to generate an execution environment **410** with a plug-in instance for **412**. Similar to the compute service **300** described in FIG. 3, the plug-in container **122** may be established using one or more computing instances with a specified computational capacity (which may be specified by indicating the type and number of CPUs, the main memory size, and so on). The plug-in container **122** may provide a virtual operation system or other execution environment **410** determined by the vehicle data streaming service **100**. In some embodiments, the execution environment **410** provides a predetermined sandbox environment from which the received plug-in may be configured. The plug-in service **110** may be automatically configured and managed by the plug-in service **110**. In some embodiments, the degree in which the customer may configure the plug-in container **122** may be partial or complete. For example, the plug-in container **122** may provide several pre-configured options for the plug-in container for the customer to choose but may prevent the customer from configuring the plug-in container **112** directly. The plug-in may be implemented as one or more operations that are performed by the vehicle data streaming service **100** on behalf of a customer. In some embodiments, the fully automated plug-in orchestrator **120** may receive instructions (from the plug-in service **110** and/or a customer) to configure the received

plug-in. The fully automated plug-in orchestrator **120** may be used to generate the customer specified execution environment **410** and the plug-in instance **412** in the plug-in container **122**. As discussed in FIG. 1, in some embodiments, the fully automated plug-in orchestrator **120** may include a resource management module **124**. The resource management module **124** may monitor the resource impact of the plug-in on the vehicle data streaming service **100** (or computing instances allocated to the vehicle data streaming service **100** to provide execution environments). For example, the resource management module **124** may monitor an amount of memory and/or processing activity of the vehicle data streaming service **100** that the plug-in utilizes and may initiate workflows to limit the amount of computing resources used by the plug-in. In some embodiments, the resource management module **124** may furthermore be used to automatically scale or limit the resources of the execution environment **410** to an appropriate number of computing resources to perform the operations in accordance with the plug-in. A number of different types of computing devices may be used singly or in combination to implement the execution environment **410** inside the plug-in container **122** (or in another service of a service provider network that provides resources for the execution environment **410**), including general purpose or special purpose computer servers, storage devices, network devices and the like.

(33) Similar to FIG. 3, various compute instances, containers, and/or functions may be used to operate or implement a variety of different plug-ins, such as operating systems of various vehicle models or components. The plug-in container **122** may support various interpreted or compiled programming languages such as Ruby, Perl, Python, C, C++ and the like, or high-performance computing services. In some embodiments, the execution environment **410** in the vehicle data streaming service **100** may be configured according to the manage vehicle streaming service **140** operations. In some embodiments, the execution environment **410** may not be configurable by the plug-in source **102** or other customers. As discussed above, in some embodiments, the plug-in source may be able to configure the execution environment **410** in a limited manner (e.g., only being able to set limits on certain resource configurations). In some embodiments, the fully automated plug-in orchestrator may register the output stream of the plug-in instance **412** with one or more synthetic vehicle attributes **414** using the registration engine **116**.

(34) FIG. 5 illustrates a more detailed view of the vehicle data streaming service and plug-in service showing management functions, including vehicle attribute/synthetic vehicle attribute management and plug-in service management, according to some embodiments.

(35) In some embodiments, a vehicle attribute catalog interface **508** may be used to communicate the vehicle attribute catalog **130** of the vehicle data streaming service **100**. As discussed in FIGS. 1 and 2, the vehicle data streaming service **100** may allow one or more users to manage the vehicle data streaming service **100**, including the vehicle attribute catalog **130**. Metadata associated with vehicle attributes and synthetic vehicle attributes may comprise descriptions of the vehicle attribute/synthetic vehicle attribute, categorization of the vehicle attribute/synthetic vehicle attribute, hierarchical organization of the vehicle attribute/synthetic vehicle attribute, and/or other information to allow data stream destinations and other entities to discover vehicle attribute/synthetic vehicle attribute pertinent to a given application. The vehicle data streaming service **100**, via the vehicle attribute catalog interface **508**, may allow management of the vehicle attribute catalog **130**. For example, one or more authorized users may retrieve vehicle catalog **510**, add/remove vehicle attribute/synthetic vehicle attribute **512**, update vehicle attribute/synthetic vehicle attribute metadata **514**, and update vehicle attribute/synthetic vehicle attribute taxonomy **516**. In some embodiments, a change to the vehicle attribute/synthetic vehicle attribute taxonomy may further result in changing a streaming service vehicle schema according to the change in the vehicle attribute taxonomy. In some embodiments, the one or more vehicle attributes/synthetic vehicle attribute of the vehicle catalog may be retrieved through a categorical navigation provided by the vehicle data streaming service **100**. In some embodiments, vehicle attributes/synthetic vehicle attributes may be arranged in a hierarchical organization or arranged in unique taxonomy to

facilitate the discovery of pertinent vehicle attributes and/or facilitate the navigation of the vehicle attributes. Furthermore, in some embodiments, the vehicle attribute catalog may provide a full text search index to further facilitate the discovery of vehicle attributes/synthetic vehicle attributes.

(36) In some embodiments, the vehicle data streaming service access control **520** may allow one or more users to manage access controls for attributes **522**. The vehicle data streaming service access control **520** may allow one or more users to change the type of access credentials required for registration and/or subscription requests. For example, one or more users may manage access controls for vehicle attributes/synthetic vehicle attribute **506** for the requests to require HTTP authentication using username and password sent alongside an API call, require key authentication using unique keys disclosed to authorized users, or using OAuth authorization framework. In some embodiments, the access credentials required in the request may be specified by managing the access controls for attributes/synthetic vehicle attribute **506**. For example, the vehicle data streaming service access control **520** may determine a username, username password, role, or other identities that may be authorized to register stream source/destination. Similar access control may be applied to plug-in registration **504**. Moreover, in some embodiments, the response that the vehicle data stream source **200** is to take for an unauthorized request with improper access credentials may be managed through the vehicle data streaming service access control **520**. For example, the vehicle data stream source **200** may be configured to respond to an unauthorized request with a notice of the denial of permissions. In some embodiments, different access credentials requirements may be determined for certain vehicle attributes/synthetic vehicle attributes. For example, vehicle attributes/synthetic vehicle attributes having greater access requirements may be identified and set to require greater access privileges. Note that in some embodiments, different access privileges may be associated with different users, independent of a manner in which an identify of the users is determined based on access credentials. For example, different users that access the vehicle data streaming service using a same method of providing access credentials, for example using the various access credential mechanisms described above, may be assigned different access privileges.

(37) In some embodiments, the vehicle data streaming service access control **520** may further be used to complete a registration of a given data stream source and/or plug-ins. For example, a registration request from a data stream source, such as data stream source **200** of FIG. 2, may require that the vehicle data streaming service access control **520** receive an approval of plug-in registration request to complete the registration of the plug-in as the data stream source. In some embodiments, the approval of the registration may be sent based on a determination that the registration request conforms to a schema for the selected vehicle attribute/synthetic vehicle attribute from the registration request. In some embodiments, the vehicle attributes/synthetic vehicle attributes may include aspects that may be considered to be personally identifiable information (“PII”). PII may include any information that may be linked to or linkable to a certain individual and may furthermore be categorized by “PII levels” or degrees to which the vehicle information may be used to personally identify individuals. In order to protect the privacy of individuals, the vehicle data streaming service may provide higher protections for vehicle data that includes aspects that may be PII. For example, greater access credentials may be required to access or subscribe to vehicle attributes comprising such vehicle data streams. The approval of plug-in registration request may require that the requestor has sufficient authorization to access information regarding the PII—including access to any of the dependent attributes/synthetic attributes of the plug-in. The authorization requirements may include other factors beyond PII authorization, such as the jurisdiction of the requester.

(38) In some embodiments, the approval of the registration may be sent based on a determination that the data stream source to be registered to is an authoritative source for the selected vehicle attribute/synthetic vehicle attribute. In some embodiments, the vehicle data streaming service access control may issue the approval of the registration request and may not require receipt of any

approval. In some embodiments, approval may be based both on the proposed data source being an authoritative source for a given attribute and that the data source provides a data stream conforming to a schema of the data streaming service. In some embodiments, the plug-in service **110** may handle request to remove a plug-in for a synthetic vehicle attribute **503**.

(39) In some embodiments, the streamed data from the data stream source having schema may be generated by a plug-in. The vehicle data streaming service **100** may send this processed plug-in data as part of a streamed data having a schema conforming to streaming service schema **530**. In some embodiments, the plug-in streaming data may be sent to a destination having access to the vehicle data streaming service **100** in accordance with access controls **530** based on the vehicle data streaming service access control **532**.

(40) FIG. **6** illustrates a more detailed view of the data streaming service receiving multiple data streams as inputs to a plug-in to generate multiple synthetic vehicle attributes. Furthermore, the vehicle data streaming service handles subscription request for vehicle attributes and synthetic vehicle attributes. The vehicle data streaming service handles changes and/or errors arising from the plug-in and the vehicle data streaming service, according to some embodiments.

(41) In some embodiments, data stream source A **602** and data stream source B **604** may send required registration information to be associated with vehicle attribute X and Y. Upon a successful registration, the data stream source A **602** may send a streamed vehicle data for attribute X from source A **610** to the plug-in service **110**. Moreover, upon a successful registration, the data stream source B **604** may send a streamed vehicle data for attribute Y from source B **612** to the plug-in service **110**. The vehicle attribute catalog **130** may generate and maintain vehicle attribute X **620** and vehicle attribute Y **622** upon approval of the registration requests for the respective data streams. In some embodiments, the plug-in service **110** may configure a plug-in upon approval of the plug-in request. The plug-in service **110** may receive the streamed data for attribute X from source A **610** and streamed data for attribute Y from source B **612** to generate one or more synthetic vehicle attributes. For example, the plug-in service **110** may generate a synthetic vehicle attribute L generated from attribute X **624** and a synthetic vehicle attribute and generator from attributes X and Y **626**.

(42) In some embodiments, various data stream destinations may send subscription requests to be associated with various vehicle attributes/synthetic vehicle attributes. In FIG. **6**, data stream destination D **610**, data stream destination E **612**, and data stream destination F **614** may send subscription requests to the vehicle data streaming service **100** with respective access credentials. In some embodiments, the vehicle data streaming service **100** may approve the subscription requests for attribute X **630** from data stream destination D **610** and based on the approved subscription request, send the streamed vehicle data for attribute X **632**. In some embodiments, the vehicle data streaming service **100** may approve the subscription requests for both a synthetic vehicle attribute and a vehicle attribute. For example, the vehicle data streaming service **100** may receive a subscription request for vehicle attribute X and synthetic vehicle attribute L **634** from data stream destination E **612** and based on the approved subscription request, send the streamed vehicle data for synthetic attributes X and L **636**. In some embodiments, upon detection of changes in stream destination or error, the vehicle data streaming service **100** may notify the data stream destination E **612**. For example, upon disassociation of data stream source A **602** to vehicle attribute X, the data stream destination E **612** may be notified of that dissociation. In some embodiments, the plug-in associated with the synthetic vehicle attribute L may receive an invalid data and generate an error. The vehicle data streaming service **100** may send a notification to the data stream destination E **612** of that error.

(43) In some embodiments, the vehicle data streaming service **100** may reject the subscription request for a synthetic vehicle attribute. For example, the vehicle data streaming service **100** may receive a subscription request for synthetic vehicle attribute M from data stream destination F **614** and based on the rejected subscription request, send a notification of the denied request **642** to the

data stream destination **614**. Although FIG. 6 shows only three data stream destinations, any number of data stream destinations may be associated with vehicle attributes/synthetic vehicle attributes. Moreover, the data stream sources may be associated with multiple vehicle attributes and not limited to a connection between one vehicle attribute to one data stream source.

(44) FIG. 7 illustrates a flowchart of operations performed by a vehicle data streaming service to register a software code for a synthetic vehicle attribute and provide a plug-in output stream for the synthetic vehicle attribute, according to some embodiments.

(45) At block **710** a vehicle data streaming service receives a request to register a software code for a synthetic vehicle attribute to be added in a catalog of vehicle attributes of a vehicle data streaming service. As discussed in FIG. 2, in some embodiments, the required registration information may furthermore contain information similar to the subscription request for the synthetic attribute.

(46) At block **720**, the vehicle data streaming service implements the software code to generate a data stream for the synthetic vehicle attribute. As discussed in FIG. 3 and FIG. 4, in some embodiments, the plug-ins may be instantiated inside the vehicle data streaming service in a fully automated manner and/or outside of the vehicle data streaming service in a customer configurable compute service environment.

(47) At block **730**, the vehicle data streaming service configures one or more registered vehicle data streams corresponding to vehicle attributes of the catalog to be provided to the software code as one or more input streams. As discussed in FIG. 2, various registration interactions may occur through a registration interface of the vehicle data streaming service to register the vehicle data stream to be provided as input streams for the plug-in. In some embodiments, the registration request may have been approved to be registered by the vehicle data streaming service.

(48) At block **740**, the vehicle data streaming service performs operations defined in the software code to convert the input streams into output streams having different data than the input streams. In some embodiments, the operations may be restricted based on the available resources in the vehicle data streaming service as discussed in FIG. 4 with respect to a customer configurable plug-in orchestrator.

(49) At block **750**, the vehicle data streaming service provides the one or more output streams as an additional registered vehicle data stream of the vehicle data streaming service. As discussed in FIG. 5, in some embodiments, subscription request for the output streams may require a valid access credentials of the requesting entity or valid access credentials provided by the request message to be approved.

(50) FIG. 8 illustrates a flowchart of operations performed by a vehicle data streaming service to provide a plug-in output stream for a synthetic vehicle attribute using a customer specified compute instance or a plug-in container configured within the streaming service, according to some embodiments.

(51) At block **810**, a vehicle data streaming service receives a request to register a software code for a synthetic vehicle attribute to be added in a catalog of vehicle attributes of a vehicle data streaming service. As discussed in FIG. 2, in some embodiments, the required registration information may furthermore contain information similar to the subscription request for the synthetic attribute.

(52) At block **820**, the vehicle data streaming service determines whether the software code configures a plug-in in an external customer configurable compute instance. As discussed in FIG. 3 and FIG. 4, the vehicle data streaming service may determine where to configure the software code based on the plug-in registration request.

(53) At block **830**, the vehicle data streaming service performs one or more configuration operations to enable a vehicle data stream compute environment to receive the additional registered vehicle data stream associated with the synthetic vehicle attribute, upon determining that the software code is to be configured in an external customer configurable compute instance. As

discussed in FIG. 3, the degree in which the customer may configure the compute instance may be partial or complete. In some embodiments, the compute service may be implemented by another provider network separate from the provider network of the vehicle data streaming service.

(54) At block **840**, the vehicle data streaming service performs, in the vehicle data stream compute environment, operations defined in the software code to convert the input streams into output streams having different data than the input streams. For example, as discussed in FIGS. 1, and 4, the vehicle data streaming service may apply one or more operations as instructed in the plug-in to the received input streams to generate a processed data for an associated synthetic vehicle attribute.

(55) At block **850**, the vehicle data streaming service provides the one or more output streams as an additional registered vehicle data stream of the vehicle data streaming service. In some embodiments, as discussed in FIG. 6, there may be multiple subscribed vehicle data stream destination receiving the streamed vehicle data based on subscription of multiple destinations.

(56) At block **860**, upon determining that the software code is not to be configured in an external customer configurable compute instance, the vehicle data streaming service configures one or more registered vehicle data streams corresponding to vehicle attributes of the catalog to be provided to the software code implemented inside a container configured in the vehicle data streaming service as one or more input streams.

(57) At block **870**, the vehicle data streaming service performs, in a container configured in the vehicle data streaming service, operations defined in the software code to convert the input streams into output streams having different data than the input streams. For example, as discussed in FIGS. 1 and 4, the vehicle data streaming service may apply one or more operations as instructed in the plug-in to the received input streams to generate a processed data for an associated synthetic vehicle attribute.

(58) At block **880**, the vehicle data streaming service provides the one or more output streams as an additional registered vehicle data stream of the vehicle data streaming service. In some embodiments, as discussed in FIG. 6, there may be multiple subscribed vehicle data stream destination receiving the streamed vehicle data based on subscription of multiple destinations.

(59) Example Computer System

(60) FIG. 9 illustrates exemplary computer system **900** usable to implement aspects of the vehicle data streaming service as described above with reference to FIGS. 1-8. In different embodiments, computer system **900** may be any of various types of devices.

(61) Various embodiments of program instructions for providing a curated catalog of vehicle attributes, allowing a vehicle plug-in source to register a plug-in to the vehicle data streaming system, and allowing a vehicle data stream destination to subscribe to a synthetic vehicle attribute in the vehicle catalog, as described herein, may be executed in one or more computer systems **900**, which may interact with various other devices. Note that any component, action, or functionality described above with respect to FIGS. 1-8 may be implemented on one or more computers configured as computer system **900** of FIG. 9, according to various embodiments. In the illustrated embodiment, computer system **900** includes one or more processors **910** coupled to a system memory **920** via an input/output (I/O) interface **930**. Computer system **900** further includes a network interface **940** coupled to I/O interface **930**, and one or more input/output devices **950**, such as cursor control device **960**, keyboard **970**, and display(s) **980**. In some cases, it is contemplated that embodiments may be implemented using a single instance of computer system **900**, while in other embodiments multiple such computer systems, or multiple nodes making up computer system **900**, may be configured to host different portions or instances program instructions as described above for various embodiments. For example, in one embodiment some elements of the program instructions may be implemented via one or more nodes of computer system **900** that are distinct from those nodes implementing other elements.

(62) In some embodiments, computer system **900** may be implemented as a system on a chip (SoC). For example, in some embodiments, processors **910**, memory **920**, I/O interface **930** (e.g., a

fabric), etc. may be implemented in a single SoC comprising multiple components integrated into a single chip. For example, an SoC may include multiple CPU cores, a multi-core GPU, a multi-core neural engine, cache, one or more memories, etc. integrated into a single chip. In some embodiments, an SoC embodiment may implement a reduced instruction set computing (RISC) architecture, or any other suitable architecture.

(63) System memory **920** may be configured to store compression or decompression program instructions **922** and/or sensor data accessible by processor **910**. In various embodiments, system memory **920** may be implemented using any suitable memory technology, such as static random-access memory (SRAM), synchronous dynamic RAM (SDRAM), nonvolatile/Flash-type memory, or any other type of memory. In the illustrated embodiment, program instructions **922** may be configured to implement any of the functionality described above. In some embodiments, program instructions and/or data may be received, sent or stored upon different types of computer-accessible media or on similar media separate from system memory **920** or computer system **900**.

(64) In one embodiment, I/O interface **930** may be configured to coordinate I/O traffic between processor **910**, system memory **920**, and any peripheral devices in the device, including network interface **940** or other peripheral interfaces, such as input/output devices **950**. In some embodiments, I/O interface **930** may perform any necessary protocol, timing or other data transformations to convert data signals from one component (e.g., system memory **920**) into a format suitable for use by another component (e.g., processor **910**). In some embodiments, I/O interface **930** may include support for devices attached through various types of peripheral buses, such as a variant of the Peripheral Component Interconnect (PCI) bus standard or the Universal Serial Bus (USB) standard, for example. In some embodiments, the function of I/O interface **930** may be split into two or more separate components, such as a north bridge and a south bridge, for example. Also, in some embodiments, some or all of the functionality of I/O interface **930**, such as an interface to system memory **920**, may be incorporated directly into processor **910**.

(65) Network interface **940** may be configured to allow data to be exchanged between computer system **900** and other devices attached to a network **985** (e.g., carrier or agent devices) or between nodes of computer system **900**. Network **985** may in various embodiments include one or more networks including but not limited to Local Area Networks (LANs) (e.g., an Ethernet or corporate network), Wide Area Networks (WANs) (e.g., the Internet), wireless data networks, some other electronic data network, or some combination thereof. In various embodiments, network interface **940** may support communication via wired or wireless general data networks, such as any suitable type of Ethernet network, for example, via telecommunications/telephony networks such as analog voice networks or digital fiber communications networks; via storage area networks such as Fiber Channel SANs, or via any other suitable type of network and/or protocol.

(66) Input/output devices **950** may, in some embodiments, include one or more display terminals, keyboards, keypads, touchpads, scanning devices, voice or optical recognition devices, or any other devices suitable for entering or accessing data by one or more computer systems **900**. Multiple input/output devices **950** may be present in computer system **900** or may be distributed on various nodes of computer system **900**. In some embodiments, similar input/output devices may be separate from computer system **900** and may interact with one or more nodes of computer system **900** through a wired or wireless connection, such as over network interface **940**.

(67) As shown in FIG. 9, memory **920** may include program instructions **922**, which may be processor-executable to implement any element or action described above. In one embodiment, the program instructions may implement the methods described above. In other embodiments, different elements and data may be included.

(68) Computer system **900** may also be connected to other devices that are not illustrated, or instead may operate as a stand-alone system. In addition, the functionality provided by the illustrated components may, in some embodiments, be combined in fewer components or distributed in additional components. Similarly, in some embodiments, the functionality of some of

the illustrated components may not be provided and/or other additional functionality may be available.

(69) Those skilled in the art will also appreciate that, while various items are illustrated as being stored in memory or on storage while being used, these items or portions of them may be transferred between memory and other storage devices for purposes of memory management and data integrity. Alternatively, in other embodiments some or all of the software components may execute in memory on another device and communicate with the illustrated computer system via inter-computer communication. Some or all of the system components or data structures may also be stored (e.g., as instructions or structured data) on a computer-accessible medium or a portable article to be read by an appropriate drive, various examples of which are described above. In some embodiments, instructions stored on a computer-accessible medium separate from computer system **900** may be transmitted to computer system **900** via transmission media or signals such as electrical, electromagnetic, or digital signals, conveyed via a communication medium such as a network and/or a wireless link. Various embodiments may further include receiving, sending or storing instructions and/or data implemented in accordance with the foregoing description upon a computer-accessible medium. Generally speaking, a computer-accessible medium may include a non-transitory, computer-readable storage medium or memory medium such as magnetic or optical media, e.g., disk or DVD/CD-ROM, volatile or non-volatile media such as RAM (e.g., SDRAM, DDR, RDRAM, SRAM, etc.), ROM, etc. In some embodiments, a computer-accessible medium may include transmission media or signals such as electrical, electromagnetic, or digital signals, conveyed via a communication medium such as network and/or a wireless link.

(70) The methods described herein may be implemented in software, hardware, or a combination thereof, in different embodiments. In addition, the order of the blocks of the methods may be changed, and various elements may be added, reordered, combined, omitted, modified, etc. Various modifications and changes may be made as would be obvious to a person skilled in the art having the benefit of this disclosure. The various embodiments described herein are meant to be illustrative and not limiting. Many variations, modifications, additions, and improvements are possible. Accordingly, plural instances may be provided for components described herein as a single instance. Boundaries between various components, operations and data stores are somewhat arbitrary, and particular operations are illustrated in the context of specific illustrative configurations. Other allocations of functionality are envisioned and may fall within the scope of claims that follow. Finally, structures and functionality presented as discrete components in the example configurations may be implemented as a combined structure or component. These and other variations, modifications, additions, and improvements may fall within the scope of embodiments as defined in the claims that follow.

Claims

1. A method, comprising: maintaining a catalog of vehicle attributes that have been registered for sharing vehicle data, wherein the catalog comprises: entries describing vehicle attributes of registered vehicle data streams generated by respective vehicle sensors; and entries describing synthetic vehicle attributes of registered vehicle data streams generated by respective synthetic vehicle sensors; receiving a request to register a software code for a given synthetic vehicle attribute to be added in the catalog, wherein the software code comprises program instructions for generating an additional registered vehicle data stream for the given synthetic vehicle attribute using one or more of the vehicle attributes; adding to the catalog, based on the request to register the software code, an entry describing the given synthetic vehicle attribute; presenting the catalog to customers of the vehicle data streaming service for use in making a subscription selection to subscribe to respective ones of the vehicle attributes and respective ones of the synthetic vehicle attributes, including the given synthetic vehicle attribute, that are available for subscription; in

response to a subscription selection for the given synthetic vehicle attribute, generating a data stream for the given synthetic vehicle attribute using the software code, wherein generating the data stream using the software code comprises: configuring one or more of the registered vehicle data streams corresponding to one or more of the vehicle attributes of the catalog to be provided to the software code as one or more input streams, performing one or more operations defined in the software code to convert the one or more input streams into one or more output streams, wherein the output streams comprise different data than the input streams, and providing the one or more output streams as the additional registered vehicle data stream, corresponding to the given synthetic vehicle attribute.

2. The method of claim 1, further comprising: receiving the subscription request selecting the given synthetic vehicle attribute from the catalog; and performing, based on approval of the subscription request, one or more configuration operations to enable a vehicle data stream destination to receive the additional registered vehicle data stream associated with the selected given synthetic vehicle attribute.

3. The method of claim 2, further comprising: approving the subscription request, wherein the approval of the subscription request comprises: identifying one or more authorizations associated with the subscription request; determining whether the one or more authorizations associated with the subscription request are sufficient to access the given synthetic vehicle attribute from the catalog; and approving the subscription request based on a determination that the one or more authorizations associated with the subscription request are sufficient to access the selected given synthetic vehicle attribute.

4. The method of claim 2, further comprising: approving the subscription request, wherein the approval of the subscription request comprises: identifying one or more authorizations of the vehicle data stream destination; determining whether the one or more authorizations of the vehicle data stream destination are sufficient to access the given synthetic vehicle attribute from the catalog; and approving the subscription request based on a determination that the one or more authorizations of the vehicle data stream destination are sufficient to access the given synthetic vehicle attribute.

5. The method of claim 1, wherein: configuring the one or more of the registered vehicle data streams as the one or more input streams comprises performing one or more configuration operations to enable a vehicle data stream compute environment to receive the additional registered vehicle data stream associated with the given synthetic vehicle attribute; the one or more operations defined in the software code are performed in the vehicle data stream compute environment; and providing the one or more output streams as the additional registered vehicle data stream of the vehicle data streaming service comprises performing one or more additional configuration operations to enable the vehicle data streaming service to provide the one or more output streams via the vehicle data stream compute environment.

6. The method of claim 1, wherein the software code is implemented using a container allocated to the vehicle data streaming service, and wherein the one or more operations defined in the software code to convert the one or more input streams into the one or more output streams are performed in the container.

7. The method of claim 6, further comprising: approving the request to register the software code, wherein approval of the request is based, at least in part, on: a determination that an authorization associated with the request is sufficient to access the one or more of the respective vehicle attributes to be provided to the software code, and a determination that resources required to execute the software code are less than a resource threshold.

8. The method of claim 1, further comprising: detecting an addition of, or a removal of, a vehicle data stream associated with the one or more of the vehicle attributes of the catalog to be provided to the software code; and notifying a vehicle data stream destination configured to receive the additional registered vehicle data stream associated with the given synthetic vehicle attribute of the

detected addition of, or the removal of, the vehicle data stream.

9. The method of claim 1, further comprising: detecting one or more errors in the performing of the one or more operations defined in the software code to convert the one or more input streams into the one or more output streams; and notifying a vehicle data stream destination configured to receive the additional registered vehicle data stream associated with the given synthetic vehicle attribute of the detected one or more errors.

10. The method of claim 1, further comprising: preventing implementation of one or more changes to the registered software code for the given synthetic vehicle attribute until a determination that there are no vehicle data stream destinations configured to receive the additional registered vehicle data stream associated with the given synthetic vehicle attribute.

11. The method of claim 1, further comprising: adding an instance of synthetic vehicle attribute metadata to the catalog or updating an instance of synthetic vehicle attribute metadata in the catalog, wherein the synthetic vehicle attribute metadata provides information about an associated synthetic vehicle attribute, wherein the adding or updating comprises adding or modifying a written description of the given synthetic vehicle attribute or modifying an arrangement of the vehicle attributes and the given synthetic vehicle attribute arranged based on a taxonomy to a different arrangement.

12. A system, comprising: one or more computing devices configured to implement a vehicle data streaming service, wherein the vehicle data streaming service is configured to: maintain a catalog of vehicle attributes that have been registered for sharing vehicle data, wherein the catalog comprises: entries describing vehicle attributes of registered vehicle data streams generated by respective vehicle sensors; and entries describing synthetic vehicle attributes of registered vehicle data streams generated by respective synthetic vehicle sensors; receive a request to register a plug-in for a given synthetic vehicle attribute to be added in the catalog, wherein the plug-in comprises program instructions for generating an additional registered vehicle data stream for the given synthetic vehicle attribute using one or more of the vehicle attributes; add to the catalog, based on the request to register the plug-in, an entry describing the given synthetic vehicle attribute; present the catalog to customers of the vehicle data streaming service for use in making a subscription selection to subscribe to respective ones of the vehicle attributes and respective ones of the synthetic vehicle attributes, including the given synthetic vehicle attribute, that are available for subscription; in response to a subscription selection for the given synthetic vehicle attribute, generate a data stream for the given synthetic vehicle attribute using the plugin, wherein to generate the data stream for the plug-in, the vehicle data streaming service is configured to: perform one or more configuration operations to enable one or more of the registered vehicle data streams corresponding to one or more of the vehicle attributes of the catalog to be provided to the plug-in as one or more input streams, perform one or more operations defined in the program instructions of the plug-in to convert the one or more input streams into one or more output streams, wherein the output streams comprise different data than the input streams, and perform one or more configuration operations to enable the one or more output streams to be provided as the additional registered vehicle data stream, corresponding to the given synthetic vehicle attribute.

13. The system of claim 12, wherein the vehicle data streaming service is further configured to: receive the subscription request selecting the given synthetic vehicle attribute from the catalog; and perform, based on approval of the subscription request, one or more configuration operations to enable a vehicle data stream destination to receive the additional registered vehicle data stream associated with the selected given synthetic vehicle attribute.

14. The system of claim 12, further comprising a provider network, wherein the provider network is configured to provide a plurality of services to clients of the provider network, wherein at least one of the services is the vehicle data streaming service.

15. The system of claim 14, wherein: at least another one of the plurality of services provided by the provider network is a compute service configured to execute the program instructions of the

plug-in to implement the plug-in on a compute instance of the computing service, to implement the plug-in, the vehicle data streaming service is further configured to: configure the one or more of the registered vehicle data streams corresponding to the one or more of the vehicle attributes of the catalog, such that the one or more of the registered vehicle data streams are configured to be provided to the compute instance that implements the plug-in as one or more input streams to perform the one or more operations defined in the plug-in; and wherein the vehicle data streaming service provides the one or more output streams as the additional registered vehicle data stream via the compute instance of the computing service.

16. The system of claim 12, wherein the plug-in is implemented using a container allocated to the vehicle data streaming service, and wherein the one or more operations defined in the plug-in to convert the one or more input streams into the one or more output streams are performed in the container.

17. One or more non-transitory, computer-readable storage media, storing program instructions that when executed on or across one or more processors cause the one or more processors to implement a vehicle data streaming service that implements: maintaining a catalog of vehicle attributes that have been registered for sharing vehicle data, wherein the catalog comprises: entries describing vehicle attributes of registered vehicle data streams generated by respective vehicle sensors; and entries describing synthetic vehicle attributes of registered vehicle data streams generated by respective synthetic vehicle sensors; receiving a request to register a software code for a given synthetic vehicle attribute to be added in the catalog, wherein the software code comprises program instructions for generating an additional registered vehicle data stream for the given synthetic vehicle attribute using one or more of the vehicle attributes; adding to the catalog, based on the request to register the software code, an entry describing the given synthetic vehicle attribute; presenting the catalog to customers of the vehicle data streaming service for use in making a subscription selection to subscribe to respective ones of the vehicle attributes and respective ones of the synthetic vehicle attributes, including the given synthetic vehicle attribute, that are available for subscription; in response to a subscription selection for the given synthetic vehicle attribute, generating a data stream for the given synthetic vehicle attribute using the software code, wherein generating the data stream using the software code comprises: configuring one or more of the registered vehicle data streams corresponding to one or more of the vehicle attributes of the catalog to be provided to the software code as one or more input streams, performing one or more operations defined in the software code to convert the one or more input streams into one or more output streams, wherein the output streams comprise different data than the input streams, and providing the one or more output streams as the additional registered vehicle data stream, corresponding to the given synthetic vehicle attribute.

18. The one or more non-transitory, computer-readable storage media of claim 17, wherein the vehicle data streaming service further implements: receiving the subscription request selecting the given synthetic vehicle attribute from the catalog; and performing, based on approval of the subscription request, one or more configuration operations to enable a vehicle data stream destination to receive the additional registered vehicle data stream associated with the selected given synthetic vehicle attribute.

19. The one or more non-transitory, computer-readable storage media of claim 17, wherein the vehicle data streaming service further implements: detecting an addition of, or a removal of, a vehicle data stream associated with the one or more of the vehicle attributes of the catalog to be provided to the software code; and notifying a vehicle data stream destination configured to receive the additional registered vehicle data stream associated with the given synthetic vehicle attribute of the detected addition of, or the removal of, the vehicle data stream.

20. The one or more non-transitory, computer-readable storage media of claim 17, wherein the vehicle data streaming service further implements: preventing implementation of one or more changes to the registered software code for the given synthetic vehicle attribute until a

determination that there are no vehicle data stream destinations configured to receive the additional registered vehicle data stream associated with the given synthetic vehicle attribute.
