

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413893
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Jang; Youngsang

Deformable ear tips and wearable device including same

Abstract

According to an embodiment, a wearable device includes: a housing, an audio port protruding from the housing in a first direction and configured to transmit an audio signal from an audio output circuit disposed in the housing, and an ear tip including a fastening part inserted in a pit disposed in an end portion of the audio port, an extension part extending from the fastening part in the first direction, a radiation surface including openings spaced apart from the extension part, a wing extending from a periphery of the radiation surface to the audio port. The extension part includes a first material, and the fastening part includes a second material having lower flexibility than a flexibility of the first material.

Inventors:	Jang; Youngsang (Suwon-si, KR)
Applicant:	Samsung Electronics Co., Ltd. (Suwon-si, KR)
Family ID:	90358973
Assignee:	SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)
Appl. No.:	18/362115
Filed:	July 31, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240107220 A1	Mar. 28, 2024

Foreign Application Priority Data

KR	10-2022-0120932	Sep. 23, 2022
KR	10-2022-0133600	Oct. 17, 2022

Related U.S. Application Data

Publication Classification

Int. Cl.: H04R1/10 (20060101)

U.S. Cl.:

CPC H04R1/1066 (20130101); H04R1/1016 (20130101);

Field of Classification Search

CPC: H04R (1/1016); H04R (25/652); H04R (25/656); H04R (2225/025); H04R (2225/77)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8189845	12/2011	Mulvey	N/A	N/A
8348011	12/2012	Huang	381/328	H04R 25/656
8462973	12/2012	Gibbons	N/A	N/A
10123137	12/2017	Chang et al.	N/A	N/A
11012770	12/2020	Hatfield et al.	N/A	N/A
11381897	12/2021	Ko	N/A	H04R 1/1058
11689840	12/2022	Kim et al.	N/A	N/A
11962963	12/2023	Matsumura	N/A	H04R 1/1041
2010/0166241	12/2009	Sabio	N/A	N/A
2014/0355809	12/2013	Killion et al.	N/A	N/A
2020/0107101	12/2019	Grinker et al.	N/A	N/A
2020/0329321	12/2019	de Ruijter	N/A	H04R 25/48
2022/0038806	12/2021	Cheng	N/A	H04R 1/1016
2022/0070572	12/2021	Ko et al.	N/A	N/A
2024/0205573	12/2023	Wang	N/A	H04R 1/1016
2025/0097652	12/2024	Petersen	N/A	H04R 25/656

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
113596666	12/2020	CN	N/A
102012204287	12/2012	DE	H04R 25/656
3232685	12/2020	EP	N/A

5031714	12/2011	JP	N/A
2014-146949	12/2013	JP	N/A
2014146949	12/2013	JP	N/A
2017-147677	12/2016	JP	N/A
7070997	12/2021	JP	N/A
10-2013-0111949	12/2012	KR	N/A
10-2021-0151577	12/2020	KR	N/A
10-2430360	12/2021	KR	N/A
10-2451114	12/2021	KR	N/A
10-2696907	12/2023	KR	N/A
WO-2016188642	12/2015	WO	H04R 1/1016
2019173809	12/2018	WO	N/A

OTHER PUBLICATIONS

Search Report and Written Opinion dated Nov. 14, 2023 issued in International Patent Application No. PCT/KR2023/010781. cited by applicant

Primary Examiner: Robinson; Ryan

Attorney, Agent or Firm: Nixon & Vanderhye, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/KR2023/010781 designating the United States, filed on Jul. 25, 2023, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application Nos. 10-2022-0120932, filed on Sep. 23, 2022, and 10-2022-0133600, filed on Oct. 17, 2022, in the Korean Intellectual Property Office, the disclosures of all of which are incorporated by reference herein in their entireties.

BACKGROUND

Field

(1) The disclosure relates to a deformable ear tip and a wearable device including the same.

Description of Related Art

(2) A wearable device may be worn on a portion of the user's body. The wearable device may receive data from an external electronic device and transmit the data to the user. The wearable device may be configured to transmit visual or auditory information to the user, based on information received from the external electronic device communicating with the wearable device.

SUMMARY

(3) According to an example embodiment, a wearable device may comprise: a housing, an audio output circuit disposed in the housing, an audio port protruding from the housing in a first direction and configured to transmit an audio signal from the audio output circuit and including a pit disposed on an end portion, and an ear tip including a fastening part inserted in the pit, an extension part extending from the fastening part in the first direction, a radiation surface including openings configured to transmit the audio signal to an ear canal of a user wearing the wearable device and spaced apart from the extension part, and a wing extending from a periphery of the radiation surface to the audio port, wherein the extension part may be configured to change an angle between the first direction and the extension part and include a first material, and wherein the fastening part

may include a second material having a lower flexibility than a flexibility of the first material.

(4) According to an example embodiment, an ear tip may comprise: a fastening part including a groove configured to be coupled to an audio port of an electronic device, an extension part extending from the fastening part in a first direction, a radiation surface including openings spaced apart from the extension part and configured to transmit an audio signal to the ear canal of a user wearing the ear tip, and a wing extending from a periphery of the radiation surface toward the audio port. The extension part may be configured to change an angle between the first direction and the extension part and includes a first material. The fastening part may include a second material having a lower flexibility than a flexibility of the first material.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects, features and advantages of certain embodiments of the present disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 is a perspective view of an example wearable device according to various embodiments;
- (3) FIG. 2 is a perspective view illustrating an example ear tip according to various embodiments;
- (4) FIG. 3 is a cross-sectional view of a separated example ear tip and an audio port according to various embodiments;
- (5) FIG. 4 is a cross-sectional view of a coupled example ear tip and an audio port according to various embodiments;
- (6) FIG. 5A is a diagram illustrating an example audio port according to various embodiments;
- (7) FIG. 5B is a diagram illustrating a rear view of an example audio port according to various embodiments;
- (8) FIG. 6 is a cross-sectional view illustrating an example of wearing an example wearable device according to various embodiments;
- (9) FIG. 7 is a cross-sectional view illustrating an example in which an ear tip and the audio port are cut in a state in which the ear tip including an example separation member and the audio port are separated, according to various embodiments;
- (10) FIG. 8 is a cross-sectional view illustrating an example in which an ear tip and the audio port are cut in a state in which the ear tip including an example separation member and the audio port are coupled, according to an embodiment. various embodiments;
- (11) FIGS. 9A and 9B are diagrams illustrating a state in which an example ear tip and an audio port are coupled, according to various embodiments; and
- (12) FIG. 10 is a block diagram illustrating an example electronic device in a network environment according to various embodiments.

DETAILED DESCRIPTION

- (13) FIG. 1 is a perspective view of an example wearable device according to various embodiments.
- (14) Referring to FIG. 1, a wearable device **100** may be worn on a part of a user's body (e.g., an ear). The wearable device **100** may include an earbud that transmits an audio signal to the user wearing the wearable device **100**. The wearable device **100** may receive audio data related to audio information through a wireless communication with an external electronic device and generate an electrical signal based on the audio data. The wearable device **100** may include an audio output circuit therein. The audio output circuit may convert the electrical signal into an audio signal. The audio signal may be generated from vibration energy generated based on the electrical signal. The audio signal may be transmitted to the outside through an audio duct in the wearable device **100** and may be transmitted to the user wearing the wearable device **100**.

(15) According to an embodiment, the wearable device **100** may include a housing **110**, a grill **120**, and an ear tip **130**. The housing **110** may form the appearance of the wearable device **100**. The housing **110** may provide a space in which components of the wearable device **100** are disposed. The housing **110** may be formed of a first housing **110a** and a second housing **110b**. However, it is not limited thereto and may be formed integrally. The first housing **110a** may face the first direction **d1**, and the second housing **110b** may face the second direction **d2**. The first housing **110a** may be a part in contact with the user's body, and the second housing **110b** may be a part exposed to the outside when wearing the wearable device **100**. The first housing **110a** may include sensors (e.g., a proximity sensor or a touch sensor) configured to contact a part of the user's body or identify approach. The second housing **110b** may include a sensor (e.g., a touch sensor) configured to receive a user's input.

(16) According to an embodiment, the grill **120** may be a part of an audio path transmitted to a microphone for obtaining an audio signal related to external noise to remove the external noise. The grill **120** may be a part of a passage (e.g., a ventilation hole) through which external air and air in the user's ears pass while the wearable device **100** is worn. The grill **120** may reduce foreign substances introduced into the wearable device **100** through the path or passage.

(17) According to an embodiment, the ear tip **130** may be a portion in direct contact with the inside of the user's ear (e.g., an ear canal). The ear tip **130** may be formed of an elastic material or a flexible material. The ear tip **130** may be deformed to correspond to the shape of the user's ear canal. The ear tip **130** may be deformed into a shape corresponding to the shape of the inside of the user's ear to fix the wearable device **100** to the inside of the user's body. The ear tip **130** may reduce leakage of a part of the audio signal transmitted from the wearable device **100** to the user to the outside.

(18) According to an embodiment, the housing **110** may include an audio port **111**. The audio port **111** may provide an audio path that transmits an audio signal from the audio output circuit to the ear tip **130**. The audio port **111** may extend from the first housing **110a** in a first direction **d1**. For example, the audio port **111** may protrude from the outer surface of the first housing **110a** in the first direction **d1**. The first direction **d1** may be a direction facing the inside of the user's ear when the user wears the wearable device **100**. The ear tip **130** may be fastened to a part of the audio port **111** and fixed to the housing **110**.

(19) According to the above-described embodiment, the wearable device **100** may clearly transmit the audio signal transmitted from the audio port **111** to the user, based on an ear tip deformable to a shape corresponding to the inside of the user's ear.

(20) FIG. 2 is a perspective view illustrating an example ear tip according to various embodiments.

(21) Referring to FIG. 2, the audio port **111** may include an audio radiation part **210**. The audio radiation part **210** may be disposed in an end portion of an acoustic path. The audio radiation part **210** may include audio outlets **211** that transmit an audio signal to the ear tip **130** through the acoustic path. The audio radiation part **210** may include a pit **220** for fastening with the ear tip **130**. The pit **220** may be disposed in the audio radiation part **210**. For example, the audio radiation part **210** may be formed in a circular shape, and the pit **220** may be disposed in the center of the circular shape. However, it is not limited thereto, and the audio radiation part **210** may have a polygonal shape, and the pit **220** may be disposed at a position substantially the same distance from each side of the polygon.

(22) According to an embodiment, the audio outlets **211** may include a plurality of openings. The audio outlets **211** may penetrate the audio radiation part **210**. The audio outlets **211** including the plurality of openings may be spaced apart from a periphery of the pit **220**. For example, the plurality of openings may be spaced apart from the pit **220**. The plurality of openings may surround the periphery of the pit **220**.

(23) According to an embodiment, the pit **220** may accommodate a part of the ear tip **130**. For example, the pit **220** may include a fastening structure for fastening with the ear tip **130**. The

fastening structure will be described in greater detail below with reference to FIG. 3.

(24) According to an embodiment, the ear tip **130** may include an extension part **230**, a fastening part **231**, a radiation surface **240** and a wing **250**. The extension part **230** may extend from the fastening part **231** to the radiation surface **240** in the first direction **d1**. The extension part **230** may separate the radiation surface **240** from the discharge port **211**. For example, the radiation surface **240** may be spaced apart from the radiation surface **240** at a distance corresponding to a length of the extension part **230**. The fastening part **231** disposed at one end of the extension part **230** facing the second direction **d2** may be inserted into the pit **220**. Based on the fastening part **231** inserted in the pit **220**, the extension part **230** may be fastened to the audio port **111**. For example, the extension part **230** may be disposed between the radiation surface **240** and the audio radiation part **210**. The extension part **230** may be fixed to the audio radiation part **210** to support the radiation surface **240**. The extension part **230** may include the fastening part **231** for being fastened to the audio radiation part **210**. The extension part **230** may include a flexible material. The extension part **230** may be configured to be deformed while being inserted into the user's ear canal. For example, the extension part **230** may be configured to change an angle between the extension part and a direction perpendicular to the audio radiation part **210**. For example, the extension part **230** including the flexible material may be configured to change an angle between the first direction **d1** (e.g., the first direction **d1** of FIG. 1) and the extension part **230**. In a state in which the extension part **230** is inserted into the user's ear canal, the angle between the direction perpendicular to the audio radiation part **210** and the extension part may change based on the shape of the user's ear canal.

(25) According to an embodiment, the radiation surface **240** may transmit an audio signal to be transmitted from the audio outlets **211** to the user. For example, the radiation surface **240** may transmit the audio signal to the ear canal of the user wearing a wearable device (e.g., the wearable device **100** in FIG. 1). The radiation surface **240** may include a plurality of openings **241** through which an audio signal passes. The plurality of openings **241** may penetrate the radiation surface **240**. The radiation surface **240** may be in contact with the extension part **230**. The extension part **230** may be disposed at the center of the radiation surface **240**. For example, the radiation surface **240** may be formed in a circular or polygonal shape. When the radiation surface **240** is formed in a circle, the extension part **230** may be disposed at the center of the circle. When the radiation surface **240** is formed in a polygon, the extension part **230** may be disposed at substantially the same distance from each corner of the polygon. The plurality of openings **241** may surround the center of the extension part or the radiation surface **240**. For example, the plurality of openings **241** may be spaced apart from the extension part **230**. The plurality of openings **241** may surround a contact part between the extension part **230** and the radiation surface **240**. According to an embodiment, when viewing the radiation surface **240** from above, the radiation surface **240** may overlap the audio radiation part **210**. According to an embodiment, when viewing the radiation surface **240** from above, the radiation surface **240** may be substantially concentric to the audio radiation part **210**.

(26) According to an embodiment, the wing **250** may extend from the periphery of the radiation surface **240** toward the audio port **111**. The ear tip **130** may surround the audio port **111**. For example, the wing **250** may extend toward the audio port **111** and surround the audio port **111**. An audio signal emitted from the audio port **111** may be transmitted to the radiation surface **240** through a space formed by the wing **250**. The wing **250** may include a flexible material. The wing **250** may be deformed according to the shape of the ear canal within the user's ear canal. While the wearable device **100** is inserted into the user's ear canal, the outer surface of the wing **250** may contact the ear canal. A thickness of the wing **250** deformable according to the shape of the user's ear canal may be thinner than a thickness of the radiation surface **240**.

(27) According to the above-described embodiment, the wearable device **100** may be stably worn through the ear tip **130** deformable according to the shape of the user's ear canal. The ear tip **130**

deformed into a shape corresponding to the user's ear canal may provide the user with comfort when worn for a long time. The ear tip **130** may be formed of a flexible material, thereby reducing pressure on the user's ears and reducing discomfort caused by wearing. Since the ear tip **130** includes the extension part **230** of the flexible material, it may be bent according to the shape of the ear canal extending inside the user's ear. According to an embodiment, since the ear tip **130** is deformable according to the ear canal of various shapes, the difference in fit that each user feels when wearing may be reduced.

(28) FIG. **3** is a cross-sectional view of a separated example ear tip and an audio port according to various embodiments. FIG. **4** is a cross-sectional view of a coupled example ear tip and an audio port according to various embodiments.

(29) Referring to FIGS. **3** and **4**, the audio port **111** may include the audio radiation part **210**. The audio radiation part **210** may include audio outlets **211** for transmitting an audio signal transmitted to the audio radiation part **210**. The audio radiation part **210** may include the pit **220**. The pit **220** may be disposed at the center of the audio radiation part **210**. For example, the audio radiation part **210** may be formed in a circular shape, and the pit **220** may be disposed at the center of the circular circle. The pit **220** may include a ring-shaped protrusion **311** protruded toward the inside of the pit **220**. For example, the ring-shaped protrusion **311** may protrude from an inner surface of the pit **220**. The ring-shaped protrusion **311** may be integrally formed with the pit **220** formed in the audio radiation part **210**. However, it is not limited thereto, and the ring-shaped protrusion **311** may be formed as a separate member from the pit **220** and may be disposed to protrude from the inner surface of the pit **220**. The ring-shaped protrusion **311** may fix the fastening part **231** when the fastening part **231** is inserted into the pit **220**. For example, the fastening part **231** may be formed to be detachable from the pit **220**. The fastening part **231** may include a groove **332** corresponding to the ring-shaped protrusion **311**. While the fastening part **231** is inserted into the pit **220**, the ring-shaped protrusion **311** may be seated in the groove **332** of the fastening part **231**.

(30) According to an embodiment, the audio radiation part **210** may include a metal plate **301** disposed along a surface where the audio outlets **211** are formed and a surface of the pit **220**. For example, the metal plate **301** of the audio radiation part **210** may be disposed along the outer surface of the audio radiation part **210**. The metal plate **301** may be disposed on the inner surface of the pit **220** and a surface of the end portion of the audio port **111**. For example, the metal plate **301** may be disposed along the outer surface of the audio radiation part **210** facing the ear tip **130**. The metal plate **301** may be additionally disposed on the inner surface of the audio radiation part **210** facing the outer surface of the audio radiation part **210**.

(31) According to an embodiment, when the fastening part **231** is inserted into the pit **220**, the metal plate **301** disposed on the outer surface of the audio radiation part **210** facing the ear tip **130** may be in contact with an outer surface **331** of the fastening part **231**. The outer surface **331** and the groove **332** of the fastening part **231** may correspond to the shape of the pit **220**. For example, the outer surface **331** of the fastening part **231** may have a shape of a surface corresponding to the outer surface of the pit **220**, and the groove **332** of the fastening part **231** may have a shape corresponding to the ring-shaped protrusion **311** disposed in the pit **220**. For example, the groove **332** may be a pit formed along the circumference of the outer surface **331**. While the fastening part **231** of the ear tip **130** is inserted into the pit **220** and fixed, the ring-shaped protrusion **311** may be seated in the groove **332** and engaged. The protrusion **311** engaged with the groove **332** may fix the ear tip **130** to the audio port **111**.

(32) According to an embodiment, the ear tip **130** may include the fastening part **231**, the radiation surface **240**, and the wing **250**. The fastening part **231** may include the groove **332** to be coupled to the audio port **111** of the wearable device **100**. The extension part **230** may extend from the fastening part **231** in the first direction. The radiation surface **240** may include openings **241** that transmit the audio signal to the ear canal of the user wearing the ear tip and are spaced apart from the extension part **230**. The wing **250** may extend from a periphery of the radiation surface **240**

toward the audio port **111**. The thickness of the wing **250** deformable according to the shape of the user's ear canal may be thinner than the thickness of the radiation surface **240**. The shape of the wing **250** may be deformed by an external force. The wing **250** may include a material having elasticity that is restored when the external force is removed. For example, the wing **250** may include silicon, foam, or rubber material. The wing **250** may be configured to be more easily deformed as it moves away from the radiation surface **240**. For example, the wing **250** may become thinner as it moves away from the radiation surface. A thickness of a part of the wing **250** adjacent to the radiation surface **240** may be thicker than a thickness of a remaining part of the wing **250**.

(33) According to an embodiment, the extension part **230** may include the flexible material and may be configured to change the angle between the first direction and the extension part **230**. The fastening part **231** may include a low flexible material. The low flexible material may have lower flexibility than the flexible material. The low flexible material may include a material having lower flexibility or higher rigidity than the flexible material, such as a rigid material, a hard material, a brittle material, and an ultra-low flexible material. For example, the rigid material may be hard silicon. However, it is not limited thereto. A part of the extension part **230** may include the low flexible material, and a remaining part may include the flexible material. For example, the flexible material may be soft silicon. The rigid silicon may have higher rigidity than the soft silicon. The rigid silicon may have a lower elasticity than the flexible silicon. For example, a part of the inside of the extension part **230** extending from the fastening part **231** may be formed of the low flexible material. The extension part **230** may include the flexible material surrounding the low flexible material disposed inside the extension part **230**. For example, the extension part **230** may include hard silicon and soft silicon surrounding the hard silicon. The extension part **230** may provide bending of the extension part **230** while reducing damage to the extension part **230** by including the low flexible material and the flexible material. For example, the low flexible material of the extension part **230** may be disposed inside the extension part **230** and referred to a core of the extension part **230** in terms of reinforcing rigidity. The extension part **230** including soft silicon and hard silicon may be formed through a double injection process. For example, in the double injection process, the extension part **230** may be manufactured to form the core of the extension part **230** with the hard silicon and to surround the hard silicon with the soft silicon.

(34) According to an embodiment, the ear tip **130** may provide a path transmitted from the audio port **111** to the outside of the ear tip **130**, by fastening to the audio port **111**. The ear tip **130** may be configured to provide a space S between the audio port **111** to transmit the audio signal. For example, while the ear tip **130** and the audio port **111** are fastened, the radiation surface **240** and the audio port **111** of the ear tip **130** may be spaced apart from each other. The space S may be surrounded by the radiation surface **240**, the audio port **111**, and the wing **250**.

(35) According to an embodiment, an audio signal A1 transmitted from the audio output circuit **410** may be transmitted to the radiation surface **240** through the space S. The audio output circuit **410** may be disposed in the wearable device **100**. The audio output circuit **410** may generate an audio signal and transmit the audio signal to the space S through the audio outlets **211** of the audio port **111**. The audio signal A1 may be an audio signal provided through vibration energy converted from an electrical signal through the audio output circuit **410**. Some audio signal A2 of the audio signal A1 may be transmitted to the radiation surface **240** through the space S. Some audio signal A2 transmitted to the radiation surface **240** may be transmitted to the outside (e.g., the user's ear or ear canal) through the plurality of openings **241**. Some other audio signal A3 of the audio signal A1 may be transmitted through a path other than the plurality of openings **241**. For example, some other audio signal A3 may be transmitted to the outside through a gap g connected to the space S. The gap g may be a spaced interval between the wing **250** and the audio port **111**. The gap g may be connected to the space S. The gap g may circulate air with the outside from the space S connected to the inside of ear or the ear canal of the user through multiple openings **241**. For example, the gap g may maintain the pressure of the ear canal or the inside of the ear and the

outside substantially equal. The gap **g** may reduce the occurrence of inflammation inside the ear when the ear tip **130** is worn for a long time, by flowing the air inside the ear or the ear canal to the outside.

(36) According to the above-described embodiment, the wearable device **100** may transmit the audio signal to the user through the ear tip **130** coupled to the audio port **111**. Since the wearable device **100** may be deformed to correspond to the shape of the ear canal through the extension part **230**, it may provide a comfortable fit to the user. The wearable device **100** may reduce inflammation of the inside of the user's ear or the ear canal through the gap **g** connected to the space **S**.

(37) FIG. 5A is a diagram illustrating an example audio port according to various embodiments. FIG. 5B is a diagram illustrating a rear view of an example audio port according to various embodiments.

(38) Referring to FIGS. 5A and 5B, the audio port **111** may include an elastic member **510** disposed in the pit **220**. The elastic member **510** may include at least one elastic protrusion **511** that may be inserted into the groove **332** of the fastening part **231**. For example, the elastic protrusion **511** may protrude from at least one portion of the elastic member **510** toward the groove **232**. For example, the elastic protrusion **511** may include a plurality of elastic protrusions facing each other. The elastic member **510** may include a supporting part **512** that fixes the elastic member **510** to the audio port **111** and supports the elastic member **510** fixed to the audio port **111**. The fastening part **231** may be detachable from the pit **220** and may include the groove **332** corresponding to the elastic member **510**. The elastic member **510** may be extended in a radial direction of the pit **220** while the fastening part **231** is inserted into the pit **220**. The elastic member **510** may be deformed to correspond to the groove **332** corresponding to the elastic member **510** in a state that the fastening part **231** and the pit **220** are coupled.

(39) According to an embodiment, when viewing one surface **500a** of the audio radiation part **210**, a part of the elastic member **510** may be exposed by the pit **220** or exposed through the audio outlets **211**. A remaining part of the elastic member **510** may be covered by the audio radiation part **210** when viewing the one surface **500a** of the audio radiation part **210**. The part of the elastic member **510** exposed by the pit **220** may be the elastic protrusion **511**. The elastic protrusion **511** may protrude to the inner surface of the pit **220** formed on one surface **500a** of the audio radiation part **210**. The elastic protrusion **511** may protrude into the inner surface of the pit **220** to form the protrusion **311** of FIG. 3 or 4. However, it is not limited thereto, and the audio port **111** may include the protrusion **311** integrally formed in the pit **220**.

(40) According to an embodiment, the elastic protrusion **511** may be pressed in the radial direction of the pit **220** by the outer surface **331** of the fastening part **231**, while the fastening part **231** is inserted into the pit **220**. When the fastening part **231** is fully inserted into the pit **220**, the elastic protrusion **511** may be deformed into a shape corresponding to the groove **332** of the fastening part **231**. The restored elastic protrusion **511** may be seated in the groove **332** and fix the ear tip **130** to the fastening part **231**.

(41) According to an embodiment, the elastic protrusion **511** may protrude into the inside of the pit **220** and may be exposed to the outside of the audio port **111**, through a slit (not shown) formed along the inner surface of the pit **220**. For example, a part **511a** of the elastic protrusion **511** may protrude inside the pit **220**, and a remaining part **511b** of the elastic protrusion **511** may be disposed outside the pit **220** and may be in contact with another surface **500b** opposite to the one surface **500a** of the audio radiation part **210**.

(42) According to an embodiment, the supporting part **512** may be in contact with the other surface **500b** of the audio radiation part **210**. The supporting part **512** may extend from a periphery of the elastic protrusion **511**. For example, the supporting part **512** may be integrally formed with the elastic protrusion **511**. The supporting part **512** and the elastic protrusion **511** may be formed of an elastic material. For example, the elastic member **510** may include a leaf spring made of a metal

material. However, it is not limited thereto, the supporting part **512** may include a metal material, and the elastic protrusion **511** may include an elastic silicon, polymer, rubber, or foam material. The elastic protrusion **511** and the supporting part **512** may be formed in a shape having a closed curve. The elastic protrusion **511** and the supporting part **512** may be deformed by external force. For example, the supporting part **512** may be configured to provide deformation of the elastic protrusion **511** by the external force applied to the elastic protrusion **511**. Since the supporting part **512** and the elastic protrusion **511** are formed of a material having elasticity, the supporting part **512** may be pressed toward the pit **220** when the elastic protrusion **511** extends in the radial direction of the pit **220**. When both ends of the supporting part **512** are pressed, the elastic protrusion **511** may be deformed, and the elastic protrusion may be inserted into the slit formed in the pit **220**.

(43) According to the above-described embodiment, the wearable devices **100** (e.g., the wearable devices **100** in FIG. 2) may provide convenience in fastening the pit **220** and the fastening part **231** or separating the fastening part **231** from the pit **220**, by including the elastic member **510**.

(44) FIG. 6 is a cross-sectional view illustrating an example of wearing an example wearable device according to various embodiments.

(45) Referring to FIG. 6, when the wearable device **100** is worn on the ear **600** of the user using the wearable device **100**, the wearable device **100** may be deformed according to the internal shape of the ear **600** of the user.

(46) According to an embodiment, the ear tip **130** of the wearable device **100** may be deformed according to a shape of the user's earflap **601** and/or a shape of the ear canal **602**, while the user wears the wearable device **100**. For example, the wing **250** of the ear tip **130** may be deformed to be in close contact with the inside of the user's ear according to the size or width of the earflap **601**. For example, the wing **250** may include a material having flexibility and elasticity. The wing **250** may be formed of the flexible material and deformed to narrow at the boundary between the earflap **601** and the ear canal **602**, so it can be closely attached to a part of the earflap **601** and/or a part of the ear canal **602**. The ear canal **602** may extend from the earflap **601** toward the eardrum (not shown). The width of the ear canal **602** may be relatively narrower than the earflap **601**. The wing **250** of the ear tip **130** closely attached to a part of the earflap **601** and/or a part of the ear canal **602** may prevent and/or reduce leakage (e.g., sound leakage) of an ear canal signal transmitted to the ear canal **602**.

(47) According to an embodiment, the extension part **230** of the ear tip **130** may be deformed according to the shape of the ear canal **602**. The ear canal **602** may extend from the earflap **601**. The ear canal **602** may have different angles extending from the earflap **601** depending on the person.

(48) According to an embodiment, when an angle of the ear canal **602** with respect to the earflap **601** is $-\Theta$ degrees, the extension part **230** may be deformed into the first state **230'**. For example, the extension part **230** including the flexible material may be deformed to be inclined based on the audio port **111** by an extension angle $-\Theta$ of the ear canal **602**, when inserted into the entrance of the ear canal **602** through the earflap **601**.

(49) According to an embodiment, when the angle of the ear canal **602** with respect to the earflap **601** is Θ degrees, the extension part **230** may be deformed into the first state **230''**. For example, the extension part **230** including the flexible material may be deformed to be inclined based on the audio port **111** by the extension angle θ of the ear canal **602**, when inserted into the entrance of the ear canal **602** through the earflap **601**.

(50) According to an embodiment, the extension part **230** may include the flexible material and may have a specified length to provide bending. For example, the extension part **230** may have a length of 4.5 mm to 7 mm from the audio port **111**. Since the extension part **230** has a relatively long length, the fastening part **231** and the pit **220** may be disposed away from the radiation surface **240**. The extension part **230** having a relatively long length may increase the deformation amount

of the ear tip **130**. When the extension part **230** is short, the bending angle of the extension part may be small, even though the extension part **230** includes the flexible material. When the extension part **230** is long, it may be difficult for the wing **250** of the ear tip **130** to come into close contact with the ear canal **602** or the earflap **601**. The extension part **230** may be configured to change the shape of the extension part **230** based on the shape of the ear canal **602** while closely contacting the wing **250** to a part of the earflap **601** or the ear canal **602**.

(51) According to an embodiment, the extension angle of the ear canal **602** may be deformed according to the shape of the ear **600** of the user and the user's posture. For example, when the user's mouth is opened, the ear canal may move in a counterclockwise direction based on the drawing. According to the user's posture or the shape of the user's ear **600**, the deviation of the extension angle of the ear canal **602** from the earflap **601** may have a deviation of about 70 degrees. To correspond to the deviation of the extension angle, the extension part **230** may be configured to be deformed at an angle of approximately -35 degrees to approximately 35 degrees in a direction perpendicular to the surface of the audio port **111**.

(52) According to the above-described embodiment, the ear tip **130** may provide an extension part **230** deformable according to the shape of the ear canal **602**. The ear tip **130** may provide comfort while the user wears the wearable device **100** (e.g., the wearable device **100** of FIG. 2). For example, while the ear tip **130** is inserted into the ear canal **602**, the extension part **230** may be deformed to correspond to the angle of the ear canal **602** extending from the earflap **601**. The ear tip **130** may reduce the pressure applied to the user's ear, while closely contacting the wing **250** of the ear tip **130** to a part of the user's earflap **601** or a part of the ear canal **602** by the deformed extension part **230**.

(53) FIG. 7 is a cross-sectional view illustrating an example in which an ear tip and the audio port are cut in a state in which the ear tip including an example separation member and the audio port are separated, according to various embodiments. FIG. 8 is a cross-sectional view illustrating an example in which an ear tip and the audio port are cut in a state in which the ear tip including an example separation member and the audio port are coupled, according to various embodiments.

(54) Referring to FIGS. 7 and 8, the audio port **111** may include the audio radiation part **210**. The audio radiation part **210** may include audio outlets **211** for transmitting an audio signal transmitted to the audio radiation part **210**. The audio radiation part **210** may include the pit **220**. The pit **220** may be disposed at the center of the audio radiation part **210**. For example, the audio radiation part **210** may be formed in a circular shape, and the pit **220** may be disposed at the center of the circular circle. The pit **220** may include a ring-shaped protrusion **311** protruded toward the inside of the pit **220**. The ring-shaped protrusion **311** may fix the fastening part **231** when the fastening part **231** is inserted into the pit **220**. For example, while the fastening part **231** is inserted inside the pit **220**, the ring-shaped protrusion **311** may be seated in the groove **332** of the fastening part **231**. The ring-shaped protrusion **311** may protrude from the inner surface of the pit **220**. The ring-shaped protrusion **311** may be integrally formed with the pit **220** formed in the audio radiation part **210**. However, it is not limited thereto, the ring-shaped protrusion **311** may be formed as a separate member from the pit **220** and may be disposed to protrude from the inner surface of the pit **220**. For example, the ring-shaped protrusion **311** may include the elastic member **510** of FIGS. 5 and 6. For example, the ring-shaped protrusion **311** including the elastic member **510** may be deformed as the fastening part **231** is inserted into the pit **220**. For example, the protrusion **311** may be deformed in the radial direction of the pit **220**, as the outer surface **331** of the fastening part **231** presses.

(55) According to an embodiment, the fastening part **231** may be formed to be insertable into the pit **220**. For example, the outer surface **331** of the fastening part **231** may have a shape of a surface corresponding to the outer surface of the pit **220**. For example, the groove **332** of the fastening part **231** may have a shape corresponding to the ring-shaped protrusion **311** disposed in the pit **220**. For example, the groove **332** may be a pit formed along the circumference of the outer surface **331**. According to an embodiment, the groove **332** may be one or more pits partially formed on a part of

the outer surface **331**. While the fastening part **231** of the ear tip **130** is inserted into the pit **220** and fixed, the ring-shaped protrusion **311** may be seated in the groove **332** and engaged. The protrusion **311** engaged with the groove **332** may fix the ear tip **130** to the audio port **111**. The fastening part **231** may be inserted into the pit **220**, and the ear tip **130** may be fixed to the audio port **111**.

(56) According to an embodiment, the audio port **111** may include a guide groove **310** that can accommodate a part of the ear tip **130**. For example, a surface on which the pit **220** and the audio outlets **211** are disposed may include the guide groove **310**. The guide groove **310** may be recessed from a surface facing the ear tip **130** of the audio port **111**. The guide groove **310** may be formed to surround the pit **220**. The guide groove **310** may provide a space for seating the protruding area **712** of the separation membrane **711** of the ear tip **130**.

(57) According to an embodiment, the ear tip **130** may include the fastening part **231**, the radiation surface **240**, the wing **250** and the separation membrane **711**. The fastening part **231** may include the groove **332** to be coupled to the audio port **111** of the wearable device **100**. The extension part **230** may extend from the fastening part **231** in the first direction. The radiation surface **240** may include openings **241** spaced apart from the extension part **230** and transmitting the audio signal to the ear canal of the user wearing the ear tip **130**. The wing **250** may extend from the periphery of the radiation surface **240** toward the audio port **111**. The extension part **230** may include the flexible material and may be configured to change the angle between the first direction and the extension part **230**. The fastening part **231** may include a low flexible material.

(58) According to an embodiment, the separation membrane **711** may be seated on the guide groove **310**. The separation membrane **711** may extend from the periphery of the pit **220** to the wing. The separation membrane **711** may divide the inside of the ear tip **130**. For example, the separation membrane **711** may be disposed on the inner surface of the wing **250** of the ear tip **130** and may be divided into an area facing the radiation surface **240** and an area facing the audio port **111**. The separation membrane **711** may include a connection opening **716**. The connection opening **716** may be configured to transmit an audio signal transmitted from the audio outlets. For example, the connection opening **716** may penetrate a part of the separation membrane **711**. The connection opening **716** may overlap the audio outlets **211** of the audio port **111**. The separation membrane **711** may include a protruding area **712** protruding toward the audio port **111**. The protruding area **712** may have a shape corresponding to the guide groove **310**. A surface of the protruding area **712** facing the guide groove **310** of the audio port **111** may be in contact with the audio radiation part **210**. The connection opening **716** of the separation membrane **711** may be formed in the protruding area **712**. The connection opening **716** of the protruding area **712** may be connected to the audio outlets **211** of the audio radiation part **210**. The connection opening **716** connected to the audio outlets **211** may transmit an audio signal **A1'** transmitted from the audio outlets **211** to the space **S'**.

(59) According to an embodiment, the ear tip **130** may be fastened to the audio port **111** to provide a path transmitted from the audio port **111** to the outside of the ear tip **130**. The ear tip **130** may be configured to provide the space **S'** between the audio port **111** and the radiation surface **240** to transmit an audio signal. The space **S'** may be surrounded by the separation membrane **711**, the wing **250** and the radiation surface **240**.

(60) According to an embodiment, the audio signal **A1'** transmitted from the audio output circuit **410** may be transmitted to the radiation surface **240** through the space **S**. The audio output circuit **410** may be disposed in the wearable device **100**. The audio output circuit **410** may generate the audio signal **A1'** and transmit the audio signal **A1'** to the space **S** through the audio outlets **211** of the audio port **111**. The audio signal **A1'** may be an audio signal provided through vibration energy converted from an electrical signal through the audio output circuit **410**. The audio signal **A2'** transmitted to the radiation surface **240** may be transmitted to the outside (e.g., the user's ear or ear canal) through a plurality of openings **241**.

(61) According to an embodiment, the space **S'** and the gap **g** of the ear tips **130** of FIGS. 7 and 8 may not be connected. The separation membrane **711** may reduce the occurrence of sound leakage

to the outside through the gap g.

(62) According to an embodiment, the separation membrane **711** may be divided into a space *S'* facing the radiation surface **240** and a space formed by the gap g. Since the space *S'* and the gap g are separated by the separation membrane **711**, the audio signal (e.g., the audio signal **A3** of FIG. **4**) transmitted through the gap g may be removed. The audio signal **A1'** transmitted to the space *S'* may be substantially the same as the audio signal **A2'** transmitted from the space *S'* to the outside. The ear tip **130** may reduce sound leakage by separating the space *S'* from the gap g. The ear tip **130** with reduced sound leakage may transmit an audio signal with reduced audio loss to the user.

(63) According to an embodiment, the wearable device **100** may transmit an audio signal with reduced loss to the user through the ear tip **130** coupled to the audio port **111**. Since the wearable device **100** may be deformed to correspond to the shape of the ear canal through the extension part **230**, it may provide a comfortable fit to the user. The extension part **230** including the flexible material may provide a comfortable fit for the user, and the fastening part **231** including the low flexible material may provide a stable fastening between the ear tip **130** and the audio port **111**.

(64) FIGS. **9A** and **9B** are diagrams illustrating a state in which an example ear tip and an audio port are coupled, according to various embodiments.

(65) Referring to FIG. **9A**, the ear tip **130** may include the separation membrane **711**. The separation membrane **711** may include an area **712** in contact with the audio port **111**. A part of the area **712** may be disposed along the periphery of the audio port **111**, a remaining part of the area **712** may be connected to the extension part **230** (e.g., the extension part **230** of FIG. **3**) and disposed on the pit **220** (e.g., the fit **220** of FIG. **3**). For example, the remaining part of the area **712** may overlap the pit **220**.

(66) According to an embodiment, the separation membrane **711** may include a connection opening **716** disposed in the area **712** in contact with the audio port **111**. The connection opening **716** may be disposed to overlap the audio outlets **211** formed in the audio radiation part **210**, when the separation membrane **711** is viewed from above. For example, the connection opening **716** may be connected to the audio outlets **211**. The connection opening **716** connected to the audio outlets **211** may provide an audio path through which an audio signal (e.g., the audio signal **A1'** of FIG. **8**) is transmitted.

(67) According to an embodiment, the connection opening **716** may be formed concentrically with the pit **220**. The connection opening **716** may be formed concentrically with components of the ear tip **130**. For example, the connection opening **716** may be concentric with the cross-section of the extension part **230**, and the connection opening **716** may be concentric with the wing **250** (e.g., the wing **250** in FIG. **3**). However, it is not limited thereto. The connection opening **716** may be formed in a donut shape. However, it is not limited thereto, and the connection opening **716** may be formed in a polygon shape. For example, the connection opening **716** may be formed to correspond to the shape of extension part **230**, when the extension part **230** is formed in a shape such as a square, hexagon, or octagon shape. The connection opening **716** may be formed to correspond to the shape of the audio port **111**, when the shape of the audio port **111** is formed in a polygon such as a square, hexagon, or octagon. In addition to the connection opening **716**, the shape of the separation membrane **711** may be formed in various shapes based on the shape of the extension part **230** or the shape of the audio port **111**. The separation membrane **711** may be disposed along an inner surface of the wing (e.g., the wing **250** of FIG. **8**). According to an embodiment, the separation membrane **711** may be disposed along the inner surface of the wing in a closed curve to separate the space (e.g., the space *S'* of FIG. **8**) and the gap (e.g., the gap g of FIG. **8**). According to an embodiment, the separation membrane **711** may be disposed along a part of the inner surface of the wing to connect the space *S'* and the gap g. As another example, the separation membrane **711** may include a mesh pattern or a grid pattern. By including the mesh pattern or the grid pattern, the space *S'* and the gap g may be connected.

(68) According to an embodiment, the separation membrane **711** has been described as including

the connection opening **716**, but a shape of the connection opening **716** is not limited. For example, the separation membrane **711** may surround the audio radiation part **210**, and include the mesh pattern or the grid pattern in an area surrounding the audio radiation part **210**. The separation membrane **711** may include the mesh pattern or the grid pattern in the entire area.

(69) Referring to FIG. **9B**, the separation membrane **711** of the ear tip **130** may include bridges **911a**, **911b**, **911c**, and **911d** that divide the connection opening **716** into a plurality of connection openings **916a**, **916b**, **916c**, and **916d**. The bridges **911a**, **911b**, **911c**, and **911d** may be connected to the extension part (e.g., the extension part **230** of FIG. **7**). The bridges **911a**, **911b**, **911c**, and **911d** may extend from the extension part **230** toward the wing (e.g., the wing **250** of FIG. **7**). For example, the bridges **911a**, **911b**, **911c**, and **911d** may be formed radially based on the extension part **230**. The bridges **911a**, **911b**, **911c**, and **911d** may be in contact with the audio radiation part **210** of the audio port **111**. The bridges **911a**, **911b**, **911c**, and **911d** may be seated in the guide groove (e.g., guide groove **310** of FIG. **7**) of the audio port **111**. The bridges **911a**, **911b**, **911c**, and **911d** may form a part of the protruding area (e.g., the protruding area **712** of FIG. **7**) of the ear tip **130**. The bridges **911a**, **911b**, **911c**, and **911d** may be seated in the guide groove **310** to provide a stable coupling of the ear tip **130** and the audio port **111**.

(70) According to the above-described embodiment, the wearable device **100** (e.g., the wearable device **100** in FIG. **1**) may prevent and/or reduce audio signal leakage (e.g., sound leakage) to the outside by having the separation membrane **711**. The separation membrane **711** with the connection opening **716** or the connection openings **916a**, **916b**, **916c**, and **916d** may transmit the audio signal to the space (e.g., the space **S'** in FIG. **8**).

(71) FIG. **10** is a block diagram illustrating an example electronic device **1001** in a network environment **1000** according to various embodiments.

(72) Referring to FIG. **10**, the electronic device **1001** in the network environment **1000** may communicate with an electronic device **1002** via a first network **1098** (e.g., a short-range wireless communication network), or at least one of an electronic device **1004** or a server **1008** via a second network **1099** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **1001** may communicate with the electronic device **1004** via the server **1008**. According to an embodiment, the electronic device **1001** may include a processor **1020**, memory **1030**, an input module **1050**, a sound output module **1055**, a display module **1060**, an audio module **1070**, a sensor module **1076**, an interface **1077**, a connecting terminal **1078**, a haptic module **1079**, a camera module **1080**, a power management module **1088**, a battery **1089**, a communication module **1090**, a subscriber identification module (SIM) **1096**, or an antenna module **1097**. In various embodiments, at least one of the components (e.g., the connecting terminal **1078**) may be omitted from the electronic device **1001**, or one or more other components may be added in the electronic device **1001**. In various embodiments, some of the components (e.g., the sensor module **1076**, the camera module **1080**, or the antenna module **1097**) may be implemented as a single component (e.g., the display module **1060**).

(73) The processor **1020** may execute, for example, software (e.g., a program **1040**) to control at least one other component (e.g., a hardware or software component) of the electronic device **1001** coupled with the processor **1020**, and may perform various data processing or computation. According to an embodiment, as at least part of the data processing or computation, the processor **1020** may store a command or data received from another component (e.g., the sensor module **1076** or the communication module **1090**) in volatile memory **1032**, process the command or the data stored in the volatile memory **1032**, and store resulting data in non-volatile memory **1034**.

According to an embodiment, the processor **1020** may include a main processor **1021** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **1023** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **1021**. For example, when the electronic device

1001 includes the main processor **1021** and the auxiliary processor **1023**, the auxiliary processor **1023** may be adapted to consume less power than the main processor **1021**, or to be specific to a specified function. The auxiliary processor **1023** may be implemented as separate from, or as part of the main processor **1021**.

(74) The auxiliary processor **1023** may control at least some of functions or states related to at least one component (e.g., the display module **1060**, the sensor module **1076**, or the communication module **1090**) among the components of the electronic device **1001**, instead of the main processor **1021** while the main processor **1021** is in an inactive (e.g., sleep) state, or together with the main processor **1021** while the main processor **1021** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **1023** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **1080** or the communication module **1090**) functionally related to the auxiliary processor **1023**. According to an embodiment, the auxiliary processor **1023** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **1001** where the artificial intelligence is performed or via a separate server (e.g., the server **1008**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(75) The memory **1030** may store various data used by at least one component (e.g., the processor **1020** or the sensor module **1076**) of the electronic device **1001**. The various data may include, for example, software (e.g., the program **1040**) and input data or output data for a command related thereto. The memory **1030** may include the volatile memory **1032** or the non-volatile memory **1034**.

(76) The program **1040** may be stored in the memory **1030** as software, and may include, for example, an operating system (OS) **1042**, middleware **1044**, or an application **1046**.

(77) The input module **1050** may receive a command or data to be used by another component (e.g., the processor **1020**) of the electronic device **1001**, from the outside (e.g., a user) of the electronic device **1001**. The input module **1050** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(78) The sound output module **1055** may output sound signals to the outside of the electronic device **1001**. The sound output module **1055** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(79) The display module **1060** may visually provide information to the outside (e.g., a user) of the electronic device **1001**. The display module **1060** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **1060** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(80) The audio module **1070** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **1070** may obtain the sound via the input module **1050**, or output the sound via the sound output module **1055** or a headphone of an external electronic device (e.g., an electronic device **1002**) directly (e.g., wiredly) or wirelessly coupled

with the electronic device **1001**.

(81) The sensor module **1076** may detect an operational state (e.g., power or temperature) of the electronic device **1001** or an environmental state (e.g., a state of a user) external to the electronic device **1001**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **1076** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(82) The interface **1077** may support one or more specified protocols to be used for the electronic device **1001** to be coupled with the external electronic device (e.g., the electronic device **1002**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **1077** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(83) A connecting terminal **1078** may include a connector via which the electronic device **1001** may be physically connected with the external electronic device (e.g., the electronic device **1002**). According to an embodiment, the connecting terminal **1078** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(84) The haptic module **1079** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **1079** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(85) The camera module **1080** may capture a still image or moving images. According to an embodiment, the camera module **1080** may include one or more lenses, image sensors, image signal processors, or flashes.

(86) The power management module **1088** may manage power supplied to the electronic device **1001**. According to an embodiment, the power management module **1088** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(87) The battery **1089** may supply power to at least one component of the electronic device **1001**. According to an embodiment, the battery **1089** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(88) The communication module **1090** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **1001** and the external electronic device (e.g., the electronic device **1002**, the electronic device **1004**, or the server **1008**) and performing communication via the established communication channel. The communication module **1090** may include one or more communication processors that are operable independently from the processor **1020** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **1090** may include a wireless communication module **1092** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **1094** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **1098** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **1099** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **1092**

may identify and authenticate the electronic device **1001** in a communication network, such as the first network **1098** or the second network **1099**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **1096**.

(89) The antenna module **1097** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **1001**. According to an embodiment, the antenna module **1097** may include an antenna including a radiating element including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **1097** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **1098** or the second network **1099**, may be selected, for example, by the communication module **1090** (e.g., the wireless communication module **1092**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **1090** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **1097**.

(90) According to various embodiments, the antenna module **1097** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(91) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(92) According to an embodiment, commands or data may be transmitted or received between the electronic device **1001** and the external electronic device **1004** via the server **1008** coupled with the second network **1099**. Each of the electronic devices **1002** or **1004** may be a device of a same type as, or a different type, from the electronic device **1001**. According to an embodiment, all or some of operations to be executed at the electronic device **1001** may be executed at one or more of the external electronic devices **1002**, **1004**, or **1008**. For example, if the electronic device **1001** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **1001**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **1001**. The electronic device **1001** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **1001** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In an embodiment, the external electronic device **1004** may include an internet-of-things (IoT) device. The server **1008** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **1004** or the server **1008** may be included in the second network **1099**. The electronic device **1001** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(93) According to an example embodiment, a wearable device (e.g., the wearable device **100** of

FIG. 1) may comprise: a housing (e.g., the housing **110** of FIG. 1), an audio output circuit (e.g., the audio output circuit **410** of FIG. 4) disposed in the housing, an audio port (e.g., the audio port **111** in FIG. 1) protruding from the housing in a first direction and configured to transmit an audio signal from the audio output circuit and including a pit (e.g., the pit **220** in FIG. 2) disposed on an end portion of the audio port, and an ear tip (e.g., the ear tip **130** of FIG. 1) including a fastening part (e.g., the fastening part **231** of FIG. 3) inserted in the pit, an extension part (e.g., the extension part **230** of FIG. 3) extending from the fastening part in the first direction (e.g., **d1**), a radiation surface (e.g., the radiation surface **240** of FIG. 3) including openings (e.g., the openings **241** of FIG. 3) configured to transmit the audio signal to an ear canal of a user wearing the wearable device and spaced apart from the extension part (e.g., **230**), and a wing (e.g., the wing **250** in FIG. 3) extending from a periphery of the radiation surface to the audio port. The extension part may include a first material. The extension part may be configured to be bent based in the first direction. According to an example embodiment, the fastening part may include a second material having a lower flexibility than a flexibility of the first material.

(94) According to an example embodiment, the wearable device may include a deformable extension part. When the user wears the wearable device, the wearable device may provide a comfortable fit to the user based on the deformation of the extension part corresponding to the internal shape of the user's ear.

(95) According to an example embodiment, the pit may include a ring-shaped protrusion (e.g., the ring-shaped protrusion **311** of FIG. 3) disposed along an inner surface of the pit. The fastening part may be attachable to the pit and separable from the pit. The fastening part may include a groove (e.g., the groove **332** of FIG. 3) configured to accommodate or receive the protrusion.

(96) According to an example embodiment, the wearable device may be configured to attach and detach the ear tip by including the pit configured to couple with the fastening part. When the ear tip is damaged, the user may replace the ear tip by separating the damaged ear tip from the pit and inserting a new ear tip into the pit. When the size of the ear tip is bigger than or smaller than the user's ear, the ear tip may be replaced with a new ear tip.

(97) According to an example embodiment, the audio port may include audio outlets (e.g., the audio outlets **211** in FIG. 2) spaced apart from the pit. The audio outlets may surround a periphery of the pit.

(98) According to an example embodiment, the audio signal may be configured to be transmitted from the audio output circuit through the audio outlets, the audio port and a space surrounded by the wing and the openings.

(99) According to an example embodiment, the wearable device may provide an audio signal transmitted through the audio outlets of the audio port. The wearable device may use the audio outlets, the space, and the openings as an audio path.

(100) According to an example embodiment, the wing may include the same material as the first material. The thickness of the wing may be thinner than a thickness of the radiation surface.

(101) According to an example, when the wearable device is worn by the user, the ear tip may adhere to the inside of the user's ear by thinning the thickness of the wings requiring deformation.

(102) According to an example embodiment, the wing may have an elasticity allowing the wing to be deformed in shape by external force and restored based on the external force being removed (e.g., in the absence of an external force).

(103) According to an example embodiment, the thickness of the wing may become thinner as a distance from the radiation surface increases.

(104) According to an example embodiment, the wearable device may provide easy deformation of the ear tip, when worn by the user by thinning the thickness of the wing requiring deformation.

(105) According to an example embodiment, the audio port may include a metal plate (e.g., the metal plate **301** of FIG. 3) disposed on the inner surface of the pit and a surface of the end portion of the audio port.

(106) According to an example embodiment, the wearable device includes a metal plate, thereby increasing the strength of the pit and the audio radiation part of the audio port. The audio radiation part having increased strength may reduce damage to the audio radiation part due to attachment and detachment of the ear tip.

(107) According to an example embodiment, an elastic member comprising a metal plate disposed on the pit may be included. According to an example embodiment, the fastening part may include a fastening pit detachable to the pit and corresponding to the elastic member.

(108) According to an example embodiment, the elastic member may extend in a radial direction of the pit based on the fastening part of the pit being inserted, and may be configured to be deformed to correspond to the size of the fastening pit corresponding to the elastic member in a state of being coupled to the fastening part.

(109) According to an example embodiment, the wearable device may provide easy attachment and detachment of the ear tip through the elastic member disposed on the pit. The elastic member may be deformed such that the pit of the elastic member is widened in the radial direction of the pit when the ear tip is inserted.

(110) According to an example embodiment, the audio port may include audio outlets spaced apart from the pit and surrounding the pit. A surface on which the pit and the audio outlet are disposed may include a guide groove. The guide groove may be recessed in a direction from the audio port toward the inside of the wearable device.

(111) According to an example embodiment, the ear tip may include: a separation membrane (e.g., the separation membrane **711** of FIG. 7) seated on the guide groove. The separation membrane may extend from the periphery of the guide groove to the wing.

(112) According to an example embodiment, the separation membrane may include a connection opening (e.g., the connection opening **716** in FIG. 7) configured to transmit an audio signal from the audio output circuit.

(113) According to an example embodiment, the connection opening may include a plurality of connection openings (e.g., connection openings **916a**, **916b**, **916c**, and **916d** in FIG. 9) by bridges (e.g., bridges **911a**, **911b**, **911c**, and **911d** in FIG. 9) connected to the extension part.

(114) According to an example embodiment, the wearable device may be configured to transmit an audio signal from the audio outlet to the inner space of the ear tip through the connection opening disposed in the separation membrane. The wearable device may reduce leakage of an ear canal signal transmitted to the inner space and transmit the same to the user's ear.

(115) According to an example embodiment, the extension part may further include a core extending from the fastening part including a second material. According to an example embodiment, the core may be disposed in the extension part.

(116) According to an example embodiment, the wearable device may provide bending of the extension part while reducing damage to the extension part, by providing the extension part including the second material and the first material.

(117) According to an example embodiment, the wing may be deformed into a shape corresponding to the user's ear canal while the user wears the wearable device.

(118) According to an example embodiment, the wearable device may be configured to transmit an audio signal through an ear tip coupled to the audio port. The wearable device may be configured to be deformed to correspond to the shape of the ear canal through the extension part, and provide a comfortable fit to the user. The wearable device may reduce inflammation of the inside of the user's ear or the ear canal through a gap connected to the space.

(119) According to an example embodiment, the ear tip (e.g., the ear tip **130** in FIG. 1) may include: a fastening part (e.g., the fastening part **231** in FIG. 3) including a groove configured to be coupled to the audio port of the electronic device. The ear tip may include an extension part (e.g., the extension part **230** in FIG. 3) extending from the fastening part in the first direction. The ear tip may include the radiation surface (e.g., the radiation surface **240** of FIG. 3) including openings

(e.g., the openings **241** of FIG. 3) spaced apart from the extension part and configured to transmit an audio signal to the ear canal of a user wearing the ear tip. The ear tip may include a wing (e.g., the wing **250** of FIG. 3) extending from a periphery of the radiation surface toward the audio port. (120) According to an example embodiment, the extension part may include a first material and may be configured to change an angle between the first direction and the extension part. The fastening part may include a second material.

(121) According to an example embodiment, the wearable device may provide a deformable extension part. When the user wears the wearable device, the wearable device may provide a comfortable fit to the user based on the deformation of the extension part corresponding to the internal shape of the user's ear.

(122) According to an example embodiment, the wing may include the first material. A thickness of the wing may be thinner than a thickness of the radiation surface.

(123) According to an example embodiment, when the wearable device is worn by the user, the ear tip may adhere to the inside of the user's ear, by thinning the thickness of the wing requiring deformation.

(124) According to an example embodiment, the wing may have elasticity allowing the wing to be deformed in shape by external force and restored in the absence of the external force.

(125) According to an example embodiment, a thickness of a part of the wing adjacent to the radiation surface may be thicker than a thickness of a remaining part of the wing.

(126) According to an example embodiment, the wearable device may provide easy deformation of the ear tip when worn by the user, by thinning the thickness of the wing requiring deformation.

(127) The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, a home appliance, or the like. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(128) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(129) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, or any combination thereof, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(130) Various embodiments as set forth herein may be implemented as software (e.g., the program **1040**) including one or more instructions that are stored in a storage medium (e.g., internal memory

1036 or external memory **1038**) that is readable by a machine (e.g., the electronic device **1001**). For example, a processor (e.g., the processor **1020**) of the machine (e.g., the electronic device **1001**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the “non-transitory” storage medium is a tangible device, and may not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(131) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(132) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(133) While the disclosure has been illustrated and described with reference to various example embodiments, it will be understood that the various example embodiments are intended to be illustrative, not limiting. It will be further understood by those skilled in the art that various changes in form and detail may be made without departing from the true spirit and full scope of the disclosure, including the appended claims and their equivalents. It will also be understood that any of the embodiment(s) described herein may be used in conjunction with any other embodiment(s) described herein.

Claims

1. A wearable device comprising: a housing; an audio output circuit disposed in the housing; an audio port protruding from the housing in a first direction and configured to transmit an audio signal from the audio output circuit, the audio port including a pit disposed on an end portion of the audio port; and an ear tip including: a fastening part configured to be inserted in the pit, an extension part extending from the fastening part in the first direction, a radiation surface including openings configured to transmit the audio signal to an ear canal of a user wearing the wearable device, the openings being spaced apart from the extension part, and a wing extending from a periphery of the radiation surface to the audio port; wherein the extension part is configured to

change an angle between the first direction and the extension part and includes a first material, and wherein the fastening part includes a second material having a lower flexibility than a flexibility of the first material.

2. The wearable device according to claim 1, wherein the pit includes a ring-shaped protrusion protruding from a surface of the pit, and wherein the fastening part is detachable from the pit and the fastening part includes a groove configured to receive the protrusion.
3. The wearable device, according to claim 1, wherein the audio port includes audio outlets spaced apart from the pit, and wherein the audio outlets surround a periphery of the pit.
4. The wearable device, according to claim 1, wherein the audio signal is configured to be transmitted from the audio output circuit through the audio outlets, the audio port and a space surrounded by the wing and the openings.
5. The wearable device, according to claim 1, wherein the wing includes the first material, and wherein a thickness of the wing is thinner than a thickness of the radiation surface.
6. The wearable device, according to claim 1, wherein the wing includes an elastic material deformable by an external force and configured to be restored in the absence of the external force.
7. The wearable device, according to claim 1, wherein a thickness of a portion of the wing adjacent to the radiation surface is thicker than a thickness of a remaining portion of the wing.
8. The wearable device, according to claim 1, wherein the audio port includes a metal plate disposed on an inner surface of the pit and a surface of an end portion of the audio port.
9. The wearable device according claim 1, further comprising an elastic member comprising a metal plate having elastic, the elastic member disposed in the pit and wherein the fastening part is detachable from the pit and the fastening part includes a groove configured to receive the elastic member.
10. The wearable device, according to claim 1, wherein the elastic member is configured to expand in a radial direction of the pit based on the fastening part being inserted into the pit and the elastic member is configured to be deformed to correspond to a size of the groove based on the elastic member being coupled with the fastening part.
11. The wearable device, according to claim 1, wherein the audio port includes audio outlets spaced apart from the pit and a guide groove formed on a surface on which the audio outlets are disposed.
12. The wearable device, according to claim 1, wherein the ear tip includes a separation membrane seated in the guide groove, and wherein the separation membrane extends from a periphery of the pit to the wing.
13. The wearable device, according to claim 1, wherein the separation membrane includes a connection opening configured to transmit audio signals from the audio outlet.
14. The wearable device, according to claim 1, wherein the connection opening is divided into a plurality of connection openings by bridges connecting the extension part.
15. The wearable device, according to claim 1, wherein the extension part further includes a core extending from the fastening part having the second material, and wherein the core is disposed in the extension part.
16. The wearable device, according claim 1, wherein based on the wearable device being worn, the wing is deformed into a shape corresponding to an ear canal.
17. An ear tip comprising: a fastening part including a groove configured to couple to an audio port of an electronic device; an extension part extending from the fastening part in a first direction; a radiation surface including openings spaced apart from the extension part and configured to transmit an audio signal to the ear canal of a user wearing the ear tip; and a wing extending from a periphery of the radiation surface toward the audio port; and wherein the extension part is configured to change an angle between a direction perpendicular to the fastening part and the extension part and includes a first material, and wherein the fastening part includes a second material having a lower flexibility than a flexibility of the first material.
18. The ear tip, according to claim 17, wherein the wing includes the first material, and wherein a

thickness of the wing is thinner than a thickness of the radiation surface.

19. The ear tip, according to claim 17, wherein the wing comprises an elastic body configured to be deformed in shape by an external force and to be restored based on the external force being removed.

20. The ear tip, according to claim 17, wherein a thickness of a portion of the wing adjacent to the radiation surface is thicker than a thickness of a remaining portion of the wing.
