

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414385
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Sirski; William et al.

Photovoltaic modules with offset layers

Abstract

A system includes a plurality of photovoltaic modules installed on a roof deck. Each of the photovoltaic modules includes solar cells, a first encapsulant encapsulating the solar cells, a frontsheet and a backsheet. The front sheet includes a glass layer. The backsheet includes a first layer and a second layer. Each of the first and second layers includes first, second, third and fourth edges. The first edge of the first layer is offset from the first edge of the second layer, the second edge of the first layer is offset from the second edge of the second layer, the third edge of the first layer is offset from the third edge of the second layer, and the fourth edge of the first layer is offset from the fourth edge of the second layer.

Inventors: Sirski; William (San Jose, CA), Dohner; Emma (San Francisco, CA), Boitnott; Nicholas (San Francisco, CA)

Applicant: GAF Energy LLC (Parsippany, NJ)

Family ID: 89997914

Assignee: GAF Energy LLC (Parsippany, NJ)

Appl. No.: 18/457114

Filed: August 28, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240072187 A1	Feb. 29, 2024

Related U.S. Application Data

us-provisional-application US 63401976 20220829

Publication Classification

Int. Cl.: H10F19/85 (20250101); H02S20/24 (20140101)

U.S. Cl.:

CPC H10F19/85 (20250101); H02S20/24 (20141201);

Field of Classification Search

CPC: H01L (31/049); H02S (20/23); H02S (20/24); H10F (19/80); H10F (19/85)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1981467	12/1933	Radtke	N/A	N/A
3156497	12/1963	Lessard	N/A	N/A
4258948	12/1980	Hoffmann	N/A	N/A
4349220	12/1981	Carroll et al.	N/A	N/A
4499702	12/1984	Turner	N/A	N/A
4636577	12/1986	Peterpaul	N/A	N/A
5167579	12/1991	Rotter	N/A	N/A
5437735	12/1994	Younan et al.	N/A	N/A
5590495	12/1996	Bressler et al.	N/A	N/A
5642596	12/1996	Waddington	N/A	N/A
6008450	12/1998	Ohtsuka et al.	N/A	N/A
6033270	12/1999	Stuart	N/A	N/A
6046399	12/1999	Kapner	N/A	N/A
6201180	12/2000	Meyer et al.	N/A	N/A
6215060	12/2000	Komori	156/196	B32B 27/308
6220329	12/2000	King et al.	N/A	N/A
6320114	12/2000	Kuechler	N/A	N/A
6320115	12/2000	Kataoka et al.	N/A	N/A
6336304	12/2001	Mimura et al.	N/A	N/A
6341454	12/2001	Koleoglou	N/A	N/A
6407329	12/2001	Iino et al.	N/A	N/A
6576830	12/2002	Nagao et al.	N/A	N/A
6928781	12/2004	Desbois et al.	N/A	N/A
6972367	12/2004	Federspiel et al.	N/A	N/A
7138578	12/2005	Komamine	N/A	N/A
7155870	12/2006	Almy	N/A	N/A
7178295	12/2006	Dinwoodie	N/A	N/A
7487771	12/2008	Eiffert et al.	N/A	N/A
7587864	12/2008	McCaskill et al.	N/A	N/A
7678990	12/2009	McCaskill et al.	N/A	N/A
7678991	12/2009	McCaskill et al.	N/A	N/A
7748191	12/2009	Podirsky	N/A	N/A

7819114	12/2009	Augenbraun et al.	N/A	N/A
7824191	12/2009	Podirsky	N/A	N/A
7832176	12/2009	McCaskill et al.	N/A	N/A
8118109	12/2011	Hacker	N/A	N/A
8168880	12/2011	Jacobs et al.	N/A	N/A
8173889	12/2011	Kalkanoglu et al.	N/A	N/A
8210570	12/2011	Railkar et al.	N/A	N/A
8276329	12/2011	Lenox	N/A	N/A
8312693	12/2011	Cappelli	N/A	N/A
8319093	12/2011	Kalkanoglu et al.	N/A	N/A
8333040	12/2011	Shiao et al.	N/A	N/A
8371076	12/2012	Jones et al.	N/A	N/A
8375653	12/2012	Shiao et al.	N/A	N/A
8404967	12/2012	Kalkanoglu et al.	N/A	N/A
8410349	12/2012	Kalkanoglu et al.	N/A	N/A
8418415	12/2012	Shiao et al.	N/A	N/A
8438796	12/2012	Shiao et al.	N/A	N/A
8468754	12/2012	Railkar et al.	N/A	N/A
8468757	12/2012	Krause et al.	N/A	N/A
8505249	12/2012	Geary	N/A	N/A
8512866	12/2012	Taylor	N/A	N/A
8513517	12/2012	Kalkanoglu et al.	N/A	N/A
8586856	12/2012	Kalkanoglu et al.	N/A	N/A
8601754	12/2012	Jenkins et al.	N/A	N/A
8629578	12/2013	Kurs et al.	N/A	N/A
8646228	12/2013	Jenkins	N/A	N/A
8656657	12/2013	Livsey et al.	N/A	N/A
8671630	12/2013	Lena et al.	N/A	N/A
8677702	12/2013	Jenkins	N/A	N/A
8695289	12/2013	Koch et al.	N/A	N/A
8713858	12/2013	Xie	N/A	N/A
8713860	12/2013	Railkar et al.	N/A	N/A
8733038	12/2013	Kalkanoglu et al.	N/A	N/A
8776455	12/2013	Azoulay	N/A	N/A
8789321	12/2013	Ishida	N/A	N/A
8793940	12/2013	Kalkanoglu et al.	N/A	N/A
8793941	12/2013	Bosler et al.	N/A	N/A
8826607	12/2013	Shiao et al.	N/A	N/A
8835751	12/2013	Kalkanoglu et al.	N/A	N/A
8863451	12/2013	Jenkins et al.	N/A	N/A
8898970	12/2013	Jenkins et al.	N/A	N/A
8925262	12/2014	Railkar et al.	N/A	N/A
8943766	12/2014	Gombarick et al.	N/A	N/A
8946544	12/2014	Jabos et al.	N/A	N/A
8950128	12/2014	Kalkanoglu et al.	N/A	N/A
8959848	12/2014	Jenkins et al.	N/A	N/A
8966838	12/2014	Jenkins	N/A	N/A
8966850	12/2014	Jenkins et al.	N/A	N/A
8994224	12/2014	Mehta et al.	N/A	N/A

9032672	12/2014	Livsey et al.	N/A	N/A
9153950	12/2014	Yamanaka et al.	N/A	N/A
9166087	12/2014	Chihlas et al.	N/A	N/A
9169646	12/2014	Rodrigues et al.	N/A	N/A
9170034	12/2014	Bosler et al.	N/A	N/A
9178465	12/2014	Shiao et al.	N/A	N/A
9202955	12/2014	Livsey et al.	N/A	N/A
9212832	12/2014	Jenkins	N/A	N/A
9217584	12/2014	Kalkanoglu et al.	N/A	N/A
9270221	12/2015	Zhao	N/A	N/A
9273885	12/2015	Rordigues et al.	N/A	N/A
9276141	12/2015	Kalkanoglu et al.	N/A	N/A
9331224	12/2015	Koch et al.	N/A	N/A
9356174	12/2015	Duarte et al.	N/A	N/A
9359014	12/2015	Yang et al.	N/A	N/A
9412890	12/2015	Meyers	N/A	N/A
9528270	12/2015	Jenkins et al.	N/A	N/A
9605432	12/2016	Robbins	N/A	N/A
9711672	12/2016	Wang	N/A	N/A
9755573	12/2016	Livsey et al.	N/A	N/A
9786802	12/2016	Shiao et al.	N/A	N/A
9831818	12/2016	West	N/A	N/A
9912284	12/2017	Svec	N/A	N/A
9923515	12/2017	Rodrigues et al.	N/A	N/A
9938729	12/2017	Coon	N/A	N/A
9991412	12/2017	Gonzalez et al.	N/A	N/A
9998067	12/2017	Kalkanoglu et al.	N/A	N/A
10027273	12/2017	West et al.	N/A	N/A
10115850	12/2017	Rodrigues et al.	N/A	N/A
10128660	12/2017	Apte et al.	N/A	N/A
10156075	12/2017	McDonough	N/A	N/A
10187005	12/2018	Rodrigues et al.	N/A	N/A
10256765	12/2018	Rodrigues et al.	N/A	N/A
10284136	12/2018	Mayfield et al.	N/A	N/A
10454408	12/2018	Livsey et al.	N/A	N/A
10530292	12/2019	Cropper et al.	N/A	N/A
10560048	12/2019	Fisher et al.	N/A	N/A
10563406	12/2019	Kalkanoglu et al.	N/A	N/A
D879031	12/2019	Lance et al.	N/A	N/A
10784813	12/2019	Kalkanoglu et al.	N/A	N/A
D904289	12/2019	Lance et al.	N/A	N/A
11012026	12/2020	Kalkanoglu et al.	N/A	N/A
11177639	12/2020	Nguyen et al.	N/A	N/A
11217715	12/2021	Sharenko	N/A	N/A
11251744	12/2021	Bunea	N/A	N/A
11258399	12/2021	Kalkanoglu et al.	N/A	N/A
11283394	12/2021	Perkins et al.	N/A	N/A
11309828	12/2021	Sirski et al.	N/A	N/A
11394344	12/2021	Perkins et al.	N/A	N/A
11424379	12/2021	Sharenko et al.	N/A	N/A

11431280	12/2021	Liu et al.	N/A	N/A
11431281	12/2021	Perkins et al.	N/A	N/A
11444569	12/2021	Clemente et al.	N/A	N/A
11454027	12/2021	Kuiper et al.	N/A	N/A
11459757	12/2021	Nguyen et al.	N/A	N/A
11486144	12/2021	Bunea et al.	N/A	N/A
11489482	12/2021	Peterson et al.	N/A	N/A
11496088	12/2021	Sirski et al.	N/A	N/A
11508861	12/2021	Perkins et al.	N/A	N/A
11512480	12/2021	Achor et al.	N/A	N/A
11527665	12/2021	Boitnott	N/A	N/A
11545927	12/2022	Abra et al.	N/A	N/A
11545928	12/2022	Perkins et al.	N/A	N/A
11658470	12/2022	Nguyen et al.	N/A	N/A
11661745	12/2022	Bunea et al.	N/A	N/A
11689149	12/2022	Clemente et al.	N/A	N/A
11705531	12/2022	Sharenko et al.	N/A	N/A
11728759	12/2022	Nguyen et al.	N/A	N/A
11732490	12/2022	Achor et al.	N/A	N/A
11811361	12/2022	Farhangi et al.	N/A	N/A
11824486	12/2022	Nguyen et al.	N/A	N/A
11824487	12/2022	Nguyen et al.	N/A	N/A
11843067	12/2022	Nguyen et al.	N/A	N/A
2002/0053360	12/2001	Kinoshita et al.	N/A	N/A
2002/0129849	12/2001	Heckerorth	N/A	N/A
2003/0101662	12/2002	Ullman	N/A	N/A
2003/0132265	12/2002	Villela et al.	N/A	N/A
2003/0217768	12/2002	Guha	N/A	N/A
2004/0000334	12/2003	Ressler	N/A	N/A
2005/0030187	12/2004	Peress et al.	N/A	N/A
2005/0115603	12/2004	Yoshida et al.	N/A	N/A
2005/0144870	12/2004	Dinwoodie	N/A	N/A
2005/0178428	12/2004	Laaly et al.	N/A	N/A
2006/0042683	12/2005	Gangemi	N/A	N/A
2006/0046084	12/2005	Yang et al.	N/A	N/A
2007/0074757	12/2006	Mellott et al.	N/A	N/A
2007/0181174	12/2006	Ressler	N/A	N/A
2007/0193618	12/2006	Bressler et al.	N/A	N/A
2007/0249194	12/2006	Liao	N/A	N/A
2007/0295385	12/2006	Sheats et al.	N/A	N/A
2008/0006323	12/2007	Kalkanoglu et al.	N/A	N/A
2008/0035140	12/2007	Placer et al.	N/A	N/A
2008/0078440	12/2007	Lim et al.	N/A	N/A
2008/0185748	12/2007	Kalkanoglu	N/A	N/A
2008/0271774	12/2007	Kalkanoglu et al.	N/A	N/A
2008/0302030	12/2007	Stancel et al.	N/A	N/A
2008/0315061	12/2007	Fath	N/A	N/A
2009/0000222	12/2008	Kalkanoglu et al.	N/A	N/A
2009/0014058	12/2008	Croft et al.	N/A	N/A
2009/0019795	12/2008	Szacsvey et al.	N/A	N/A

2009/0044850	12/2008	Kimberley	N/A	N/A
2009/0114261	12/2008	Stancel et al.	N/A	N/A
2009/0133340	12/2008	Shiao et al.	N/A	N/A
2009/0159118	12/2008	Kalkanoglu et al.	N/A	N/A
2009/0178350	12/2008	Kalkanoglu et al.	N/A	N/A
2009/0229652	12/2008	Mapel et al.	N/A	N/A
2009/0275247	12/2008	Richter et al.	N/A	N/A
2010/0019580	12/2009	Croft et al.	N/A	N/A
2010/0095618	12/2009	Edison et al.	N/A	N/A
2010/0101634	12/2009	Frank et al.	N/A	N/A
2010/0116325	12/2009	Nikoonahad	N/A	N/A
2010/0131108	12/2009	Meyer	N/A	N/A
2010/0139184	12/2009	Williams et al.	N/A	N/A
2010/0146878	12/2009	Koch et al.	N/A	N/A
2010/0159221	12/2009	Kourtakis et al.	N/A	N/A
2010/0170169	12/2009	Railkar et al.	N/A	N/A
2010/0186798	12/2009	Tormen et al.	N/A	N/A
2010/0242381	12/2009	Jenkins	N/A	N/A
2010/0313499	12/2009	Gangemi	N/A	N/A
2010/0326488	12/2009	Aue et al.	N/A	N/A
2010/0326501	12/2009	Zhao et al.	N/A	N/A
2011/0030761	12/2010	Kalkanoglu et al.	N/A	N/A
2011/0036386	12/2010	Browder	N/A	N/A
2011/0036389	12/2010	Hardikar et al.	N/A	N/A
2011/0048507	12/2010	Livsey et al.	N/A	N/A
2011/0058337	12/2010	Han et al.	N/A	N/A
2011/0061326	12/2010	Jenkins	N/A	N/A
2011/0100436	12/2010	Cleereman et al.	N/A	N/A
2011/0104488	12/2010	Muessig et al.	N/A	N/A
2011/0132427	12/2010	Kalkanoglu et al.	N/A	N/A
2011/0168238	12/2010	Metin et al.	N/A	N/A
2011/0239555	12/2010	Cook et al.	N/A	N/A
2011/0302859	12/2010	Crasnianski	N/A	N/A
2012/0034799	12/2011	Hunt	N/A	N/A
2012/0060902	12/2011	Drake	N/A	N/A
2012/0085392	12/2011	Albert et al.	N/A	N/A
2012/0137600	12/2011	Jenkins	N/A	N/A
2012/0176077	12/2011	Oh et al.	N/A	N/A
2012/0212065	12/2011	Cheng et al.	N/A	N/A
2012/0233940	12/2011	Perkins et al.	N/A	N/A
2012/0240490	12/2011	Gangemi	N/A	N/A
2012/0260977	12/2011	Stancel	N/A	N/A
2012/0266942	12/2011	Komatsu et al.	N/A	N/A
2012/0279150	12/2011	Pisllkak et al.	N/A	N/A
2012/0282437	12/2011	Clark et al.	N/A	N/A
2012/0291848	12/2011	Sherman et al.	N/A	N/A
2013/0008499	12/2012	Verger et al.	N/A	N/A
2013/0014455	12/2012	Grieco	N/A	N/A
2013/0118558	12/2012	Sherman	N/A	N/A
2013/0193769	12/2012	Mehta et al.	N/A	N/A

2013/0247988	12/2012	Reese et al.	N/A	N/A
2013/0284267	12/2012	Plug et al.	N/A	N/A
2013/0306137	12/2012	Ko	N/A	N/A
2014/0090697	12/2013	Rodrigues et al.	N/A	N/A
2014/0150843	12/2013	Pearce et al.	N/A	N/A
2014/0173997	12/2013	Jenkins	N/A	N/A
2014/0179220	12/2013	Railkar et al.	N/A	N/A
2014/0182222	12/2013	Kalkanoglu et al.	N/A	N/A
2014/0254776	12/2013	O'Connor et al.	N/A	N/A
2014/0266289	12/2013	Della Sera et al.	N/A	N/A
2014/0311556	12/2013	Feng et al.	N/A	N/A
2014/0352760	12/2013	Haynes et al.	N/A	N/A
2014/0366464	12/2013	Rodrigues et al.	N/A	N/A
2015/0089895	12/2014	Leitch	N/A	N/A
2015/0129013	12/2014	Nositschka	438/66	H01L 31/048
2015/0162459	12/2014	Lu et al.	N/A	N/A
2015/0340516	12/2014	Kim et al.	N/A	N/A
2015/0349173	12/2014	Morad et al.	N/A	N/A
2016/0105144	12/2015	Haynes et al.	N/A	N/A
2016/0142008	12/2015	Lopez et al.	N/A	N/A
2016/0254776	12/2015	Rodrigues et al.	N/A	N/A
2016/0276508	12/2015	Huang et al.	N/A	N/A
2016/0359451	12/2015	Mao et al.	N/A	N/A
2017/0159292	12/2016	Chihlas et al.	N/A	N/A
2017/0179319	12/2016	Yamashita et al.	N/A	N/A
2017/0179726	12/2016	Garrity et al.	N/A	N/A
2017/0237390	12/2016	Hudson et al.	N/A	N/A
2017/0331415	12/2016	Koppi et al.	N/A	N/A
2018/0094438	12/2017	Wu et al.	N/A	N/A
2018/0097472	12/2017	Anderson et al.	N/A	N/A
2018/0115275	12/2017	Flanigan et al.	N/A	N/A
2018/0254738	12/2017	Yang et al.	N/A	N/A
2018/0351502	12/2017	Almy et al.	N/A	N/A
2018/0367089	12/2017	Stutterheim et al.	N/A	N/A
2019/0030867	12/2018	Sun et al.	N/A	N/A
2019/0081436	12/2018	Onodi et al.	N/A	N/A
2019/0123679	12/2018	Rodrigues et al.	N/A	N/A
2019/0253022	12/2018	Hardar et al.	N/A	N/A
2019/0305717	12/2018	Allen et al.	N/A	N/A
2020/0109320	12/2019	Jiang	N/A	N/A
2020/0144958	12/2019	Rodrigues et al.	N/A	N/A
2020/0220819	12/2019	Vu et al.	N/A	N/A
2020/0224419	12/2019	Boss et al.	N/A	N/A
2020/0343397	12/2019	Hem-Jensen	N/A	N/A
2021/0115223	12/2020	Bonekamp et al.	N/A	N/A
2021/0159353	12/2020	Li et al.	N/A	N/A
2021/0343886	12/2020	Sharenko et al.	N/A	N/A
2022/0149213	12/2021	Mensink et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2829440	12/2018	CA	N/A
700095	12/2009	CH	N/A
202797032	12/2012	CN	N/A
1958248	12/1970	DE	N/A
0 884 432	12/1997	EP	H01L 31/048
1039361	12/1999	EP	N/A
1837162	12/2006	EP	N/A
1774372	12/2010	EP	N/A
2446481	12/2011	EP	N/A
2784241	12/2013	EP	N/A
10046767	12/1997	JP	N/A
2002-106151	12/2001	JP	N/A
2001-098703	12/2001	JP	N/A
2017-027735	12/2016	JP	N/A
2018053707	12/2017	JP	N/A
20090084060	12/2008	KR	N/A
10-2019-0000367	12/2018	KR	N/A
10-2253483	12/2020	KR	N/A
2026856	12/2021	NL	N/A
2011/049944	12/2010	WO	N/A
2015/133632	12/2014	WO	N/A
2018/000589	12/2017	WO	N/A
2019/201416	12/2018	WO	N/A
2020-159358	12/2019	WO	N/A
2021-247098	12/2020	WO	N/A

OTHER PUBLICATIONS

Sunflare, Procduts: “Sunflare Develops Prototype For New Residential Solar Shingles”; 2019 <<sunflaresolar.com/news/sunflare-develops-prototype-for-new-residential-solar-shingles>> retrieved Feb. 2, 2021. cited by applicant

RGS Energy, 3.5kW Powerhouse 3.0 system installed in an afternoon; Jun. 7, 2019 <<facebook.com/RGSEnergy/>> retrieved Feb. 2, 2021. cited by applicant

Tesla, Solar Roof <<tesla.com/solarroof>> retrieved Feb. 2, 2021. cited by applicant

“Types of Roofing Underlayment”, Owens Corning Roofing; <<<https://www.owenscorning.com/en-us/roofing/tools/how-roofing-underlayment-helps-protect-your-home>>> retrieved Nov. 1, 2021. cited by applicant

Primary Examiner: Mowla; Golam

Attorney, Agent or Firm: GREENBERG TRAURIG, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a Section 111(a) application relating to and claiming the benefit of commonly owned, U.S. Provisional Patent Application Ser. No. 63/401,976, filed Aug. 29, 2022, entitled “PHOTOVOLTAIC MODULES WITH OFFSET LAYERS,” the contents of each of which are incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

(1) The present invention relates to photovoltaic modules, and, more particularly, photovoltaic modules having offset layers.

BACKGROUND

(2) Photovoltaic systems having solar panels are commonly installed on roofing of structures.

SUMMARY

(3) In some embodiments, a system comprises a plurality of photovoltaic modules installed on a roof deck, wherein each of the photovoltaic modules includes at least one solar cell, a first encapsulant encapsulating the at least one solar cell, wherein the first encapsulant includes a first surface and a second surface opposite the first surface, a frontsheet juxtaposed with the first surface of the first encapsulant, wherein the frontsheet includes a glass layer, and a backsheet juxtaposed with the second surface of the first encapsulant, wherein the backsheet includes a first layer, wherein the first layer includes a first edge, a second edge opposite the first edge, a third edge extending from the first edge to the second edge, and a fourth edge opposite the third edge and extending from the first edge to the second edge, and a second layer adjacent the first layer, wherein the second layer includes a first edge, a second edge opposite the first edge of the second layer, a third edge extending from the first edge of the second layer to the second edge of the second layer, and a fourth edge opposite the third edge of the second layer and extending from the first edge of the second layer to the second edge of the second layer, wherein the first edge of the first layer is offset from the first edge of the second layer, wherein the second edge of the first layer is offset from the second edge of the second layer, wherein the third edge of the first layer is offset from the third edge of the second layer, and wherein the fourth edge of the first layer is offset from the fourth edge of the second layer.

(4) In some embodiments, a second layer forms a lower surface of the photovoltaic module. In some embodiments, the first layer includes a first length extending from the first edge of the first layer to the second edge of the first layer, wherein the second layer includes a second length extending from the first edge of the second layer to the second edge of the second layer, and wherein the first length is greater than the second length. In some embodiments, the first layer includes a first width extending from the third edge of the first layer to the fourth edge of the first layer, wherein the second layer includes a second width extending from the third edge of the second layer to the fourth edge of the second layer, and wherein the first width is greater than the second width. In some embodiments, the second layer is composed of thermoplastic polyolefin (TPO). In some embodiments, the first layer is composed of a polymer. In some embodiments, the first layer is composed of thermoplastic polyolefin (TPO).

(5) In some embodiments, the glass layer includes a first edge, a second edge opposite the first edge of the glass layer, a third edge extending from the first edge of the glass layer to the second edge of the glass layer, and a fourth edge opposite the third edge of the glass layer and extending from the first edge of the glass layer to the second edge of the glass layer, wherein the first edge of the glass layer is offset from the first edge of the second layer, wherein the second edge of the glass layer is offset from the second edge of the second layer, wherein the third edge of the glass layer is offset from the third edge of the second layer, and wherein the fourth edge of the glass layer is offset from the fourth edge of the second layer.

(6) In some embodiments, the first layer includes a first length extending from the first edge of the first layer to the second edge of the first layer, wherein the second layer includes a second length

extending from the first edge of the second layer to the second edge of the second layer, and wherein the second length is greater than the first length. In some embodiments, the first layer includes a first width extending from the third edge of the first layer to the fourth edge of the first layer, wherein the second layer includes a second width extending from the third edge of the second layer to the fourth edge of the second layer, and wherein the second width is greater than the first width.

(7) In some embodiments, first layer is composed of thermoplastic polyolefin (TPO). In some embodiments, the second layer is composed of a polymer. In some embodiments, the second layer is composed of thermoplastic polyolefin (TPO).

(8) In some embodiments, glass layer includes a first edge, a second edge opposite the first edge of the glass layer, a third edge extending from the first edge of the glass layer to the second edge of the glass layer, and a fourth edge opposite the third edge of the glass layer and extending from the first edge of the glass layer to the second edge of the glass layer, wherein the first edge of the glass layer is offset from the first edge of the first layer, wherein the second edge of the glass layer is offset from the second edge of the first layer, wherein the third edge of the glass layer is offset from the third edge of the first layer, and wherein the fourth edge of the glass layer is offset from the fourth edge of the first layer.

(9) In some embodiments, the first edge of the first layer is offset from the first edge of the second layer by a first distance, wherein the second edge of the first layer is offset from the second edge of the second layer by a second distance, wherein the third edge of the first layer is offset from the third edge of the second layer by a third distance, and wherein the fourth edge of the first layer is offset from the fourth edge of the second layer by a fourth distance. In some embodiments, the first distance, the second distance, the third distance and the fourth distance are equal to one another. In some embodiments, the first distance is equal to the second distance, and wherein the third distance is equal to the fourth distance. In some embodiments, the first layer and the second layer are attached to one another by an adhesive layer. In some embodiments, the frontsheet includes a polymer layer and a second encapsulant, and wherein the polymer layer is attached to the glass layer by the second encapsulant.

(10) In some embodiments, a photovoltaic module includes at least one solar cell, a first encapsulant encapsulating the at least one solar cell, wherein the first encapsulant includes a first surface and a second surface opposite the first surface, a frontsheet juxtaposed with the first surface of the first encapsulant, wherein the frontsheet includes a glass layer, and a backsheet juxtaposed with the second surface of the first encapsulant, wherein the backsheet includes a first layer, wherein the first layer includes a first edge, a second edge opposite the first edge, a third edge extending from the first edge to the second edge, and a fourth edge opposite the third edge and extending from the first edge to the second edge, and a second layer attached to the first layer, wherein the second layer includes a first edge, a second edge opposite the first edge of the second layer, a third edge extending from the first edge of the second layer to the second edge of the second layer, and a fourth edge opposite the third edge of the second layer and extending from the first edge of the second layer to the second edge of the second layer, wherein the first edge of the first layer is offset from the first edge of the second layer, wherein the second edge of the first layer is offset from the second edge of the second layer, wherein the third edge of the first layer is offset from the third edge of the second layer, and wherein the fourth edge of the first layer is offset from the fourth edge of the second layer, wherein the second layer forms a lower surface of the photovoltaic module, and wherein at least one of the first layer and the second layer is composed of thermoplastic polyolefin (TPO).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic view of some embodiments of a photovoltaic module;
- (2) FIG. 2 is a perspective, schematic view of some embodiments of a photovoltaic module;
- (3) FIGS. 3 and 4 are schematic views of some embodiments of a photovoltaic module;
- (4) FIGS. 5 through 7 are schematic views of some embodiments of a photovoltaic module; and
- (5) FIGS. 8 through 10 show enlarged views of a portion of some embodiments of a photovoltaic module.

DETAILED DESCRIPTION

(6) The present invention will be further explained with reference to the attached drawings, wherein like structures are referred to by like numerals throughout the several views. The drawings shown are not necessarily to scale, with emphasis instead generally being placed upon illustrating the principles of the present invention. Further, some features may be exaggerated to show details of particular components.

(7) The figures constitute a part of this specification and include illustrative embodiments of the present invention and illustrate various objects and features thereof. Further, the figures are not necessarily to scale, some features may be exaggerated to show details of particular components. In addition, any measurements, specifications and the like shown in the figures are intended to be illustrative, and not restrictive. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a representative basis for teaching one skilled in the art to variously employ the present invention.

(8) Among those benefits and improvements that have been disclosed, other objects and advantages of this invention will become apparent from the following description taken in conjunction with the accompanying figures. Detailed embodiments of the present invention are disclosed herein; however, it is to be understood that the disclosed embodiments are merely illustrative of the invention that may be embodied in various forms. In addition, each of the examples given in connection with the various embodiments of the invention which are intended to be illustrative, and not restrictive.

(9) Throughout the specification, the following terms take the meanings explicitly associated herein, unless the context clearly dictates otherwise. The phrases “in one embodiment” and “in some embodiments” as used herein do not necessarily refer to the same embodiment(s), though they may. Furthermore, the phrases “in another embodiment” and “in some other embodiments” as used herein do not necessarily refer to a different embodiment, although they may. Thus, as described below, various embodiments of the invention may be readily combined, without departing from the scope or spirit of the invention.

(10) The term “based on” is not exclusive and allows for being based on additional factors not described, unless the context clearly dictates otherwise. In addition, throughout the specification, the meaning of “a,” “an,” and “the” include plural references. The meaning of “in” includes “in” and “on.”

(11) Referring to FIGS. 1 through 3, in some embodiments, a photovoltaic module 10 includes at least one solar cell 12, an encapsulant 14 encapsulating the at least one solar cell 12, and a frontsheet 16 juxtaposed with the encapsulant 14. In some embodiments, the frontsheet 16 is juxtaposed with a first surface of the encapsulant 14. As used herein, the terms “encapsulating” and “encapsulates” mean to partially or fully envelope or enclose, and with respect to certain embodiments of the photovoltaic module 10, the at least one solar cell 12 is fully enveloped by or enclosed within the encapsulant 14, or partially enveloped by or enclosed within the encapsulant 14. In some embodiments, the encapsulant 14 encapsulates 50% to 99.9% of an exterior surface area of the at least one solar cell 12. In another embodiment, the encapsulant 14 encapsulates 55% to 99.9% of an exterior surface area of the at least one solar cell 12. In another embodiment, the encapsulant 14 encapsulates 60% to 99.9% of an exterior surface area of the at least one solar cell

has a thickness of 0.5 mm to 1.5 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 0.5 mm to 1 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 1 mm to 2 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 1 mm to 1.5 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 1.5 mm to 2 mm.

(27) In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 0.2 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 0.3 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 0.4 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 0.45 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 0.5 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 1 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 1.5 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 2 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 2.5 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 3 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 3.5 mm. In some embodiments, the second layer **14b** of the encapsulant **14** has a thickness of 4 mm.

(28) In some embodiments, the thickness of the first layer **14a** is equal to the thickness of the second layer **14b**. In another embodiment, the thickness of the first layer **14a** is different from the thickness of the second layer **14b**.

(29) In some embodiments, the encapsulant **14** may be made from polyolefins, ethyl vinyl acetates, ionomers, silicones, poly vinyl butyral, epoxies, polyurethanes, or combinations/hybrids thereof. In some embodiments, the encapsulant **14** is made from thermosetting polyolefin.

(30) In some embodiments, the photovoltaic module **10** includes a first end **18**, a second end **20** opposite the first end **18**, a first surface **19** extending from the first end **18** to the second end **20**, and a second surface **21** opposite the first surface **19** and extending from the first end **18** to the second end **20**. In some embodiments, the first surface **19** is an upper, sun facing-side surface of the photovoltaic module **10**, and the second surface **21** is a lower surface configured to face a roof deck on which the photovoltaic module **10** is installed on the roof deck. In some embodiments, the polymer layer **24** includes the first surface **19**. In some embodiments, the first surface **19** is textured. In some embodiments, the first surface **19** is textured to impart an appearance of a traditional asphalt roofing shingle. In some embodiments, the first surface **19** is textured to impart an appearance of and aesthetically match a roofing shingle. In some embodiments, the first surface **19** is an embossed surface. In some embodiments, a pattern on the first surface **19** includes a plurality of indentations. In some embodiment, each of the plurality of indentations has a circular shape. In some embodiment, each of the plurality of indentations has a rectangular shape. In some embodiments, each of the plurality of indentations has a square shape. In some embodiments, each of the plurality of indentations has a triangular shape. In some embodiments, each of the plurality of indentations has an elliptical shape. In some embodiments, each of the plurality of indentations has an oval shape. In some embodiments, each of the plurality of indentations has a rhombus shape. In some embodiments, each of the plurality of indentations has a hexagonal shape. In some embodiments, each of the plurality of indentations includes a pentagonal shape. In some embodiments, each of the plurality of indentations has a polygonal shape. In some embodiments, each of the plurality of indentations has a non-polygonal shape. In some embodiments, each of the plurality of indentations has a geometric shape. In some embodiments, each of the plurality of indentations has a non-geometric shape. In some embodiments, the pattern on the first surface **19** includes a plurality of dimples. In some embodiments, the indentations are created by embossing a portion of the first surface **19**. In some embodiments, the texture includes a surface roughness (Ra). In some embodiments, the surface roughness (Ra) is 1 micron to 200 microns. In some embodiments, the pattern on the first surface **19** includes a plurality of lines. In some embodiments,

the pattern on the first surface **19** includes a plurality of grooves. In some embodiments, the pattern on the first surface **19** includes crosshatches.

(31) In some embodiments, the at least one solar cell **12** includes a plurality of the solar cells **12**. In some embodiments, the plurality of solar cells **12** includes two solar cells. In some embodiments, the plurality of solar cells **12** includes three solar cells. In some embodiments, the plurality of solar cells **12** includes four solar cells. In some embodiments, the plurality of solar cells **12** includes five solar cells. In some embodiments, the plurality of solar cells **12** includes six solar cells. In some embodiments, the plurality of solar cells **12** includes seven solar cells. In some embodiments, the plurality of solar cells **12** includes eight solar cells. In some embodiments, the plurality of solar cells **12** includes nine solar cells. In some embodiments, the plurality of solar cells **12** includes ten solar cells. In some embodiments, the plurality of solar cells **12** includes eleven solar cells. In some embodiments, the plurality of solar cells **12** includes twelve solar cells. In some embodiments, the plurality of solar cells **12** includes thirteen solar cells. In some embodiments, the plurality of solar cells **12** includes fourteen solar cells. In some embodiments, the plurality of solar cells **12** includes fifteen solar cells. In some embodiments, the plurality of solar cells **12** includes sixteen solar cells. In some embodiments, the plurality of solar cells **12** includes more than sixteen solar cells.

(32) In some embodiments, the plurality of solar cells **12** is arranged in one row (i.e., one reveal). In another embodiment, the plurality of solar cells **12** is arranged in two rows (i.e., two reveals). In another embodiment, the plurality of solar cells **12** is arranged in three rows (i.e., three reveals). In another embodiment, the plurality of solar cells **12** is arranged in four rows (i.e., four reveals). In another embodiment, the plurality of solar cells **12** is arranged in five rows (i.e., five reveals). In another embodiment, the plurality of solar cells **12** is arranged in six rows (i.e., six reveals). In other embodiments, the plurality of solar cells **12** is arranged in more than six rows. In some embodiments, the at least one solar cell **12** is electrically inactive (i.e., a “dummy” solar cell). In some embodiments, the photovoltaic module **10** does not include the at least one solar cell **12**.

(33) In some embodiments, the frontsheet **16** includes a glass layer **22** and a polymer layer **24** attached to a first surface of the glass layer **22**. In some embodiments, the frontsheet **16** is juxtaposed with the first layer **14a** of the encapsulant **14**. In some embodiments, each of the encapsulant **14**, the glass layer **22**, and the polymer layer **24** is transparent. In some embodiments, the polymer layer **24** is attached to the glass layer **22** by an first adhesive layer **26**. In some embodiments, the first adhesive layer **26** may include polyvinyl butyrate, acrylic, silicone, or polycarbonate. In another embodiment, the first adhesive layer **26** may include pressure sensitive adhesives. In another embodiment, the polymer layer **24** is attached to the glass layer **22** by thermal bonding. In another embodiment, the frontsheet **16** includes at least one of the glass layer **22** or the polymer layer **24**. In some embodiments, the first adhesive layer **26** is transparent. As used herein, the term “transparent” means having a solar weighted transmittance of 80% or greater, and with respect to certain embodiments of the photovoltaic module **10**, a transparent layer of the photovoltaic module has a solar weighted transmittance of 80% or greater. In another embodiment, the frontsheet **16** does not include the glass layer **22**.

(34) In some embodiments, the glass layer **22** has a thickness of 1 mm to 4 mm. In some embodiments, the glass layer **22** has a thickness of 1 mm to 3.5 mm. In some embodiments, the glass layer **22** has a thickness of 1 mm to 3 mm. In some embodiments, the glass layer **22** has a thickness of 1 mm to 2.5 mm. In some embodiments, the glass layer **22** has a thickness of 1 mm to 2 mm. In some embodiments, the glass layer **22** has a thickness of 1 mm to 1.5 mm. In some embodiments, the glass layer **22** has a thickness of 1.5 mm to 4 mm. In some embodiments, the glass layer **22** has a thickness of 1.5 mm to 3.5 mm. In some embodiments, the glass layer **22** has a thickness of 1.5 mm to 3 mm. In some embodiments, the glass layer **22** has a thickness of 1 mm to 2.5 mm. In some embodiments, the glass layer **22** has a thickness of 1.5 mm to 2 mm.

(35) In some embodiments, the glass layer **22** has a thickness of 2 mm to 4 mm. In some embodiments, the glass layer **22** has a thickness of 2 mm to 3.5 mm. In some embodiments, the

glass layer **22** has a thickness of 2 mm to 3 mm. In some embodiments, the glass layer **22** has a thickness of 2 mm to 2.5 mm. In some embodiments, the glass layer **22** has a thickness of 2.5 mm to 4 mm. In some embodiments, the glass layer **22** has a thickness of 2.5 mm to 3.5 mm. In some embodiments, the glass layer **22** has a thickness of 2.5 mm to 3 mm. In some embodiments, the glass layer **22** has a thickness of 3 mm to 4 mm. In some embodiments, the glass layer **22** has a thickness of 3 mm to 3.5 mm. In some embodiments, the glass layer **22** has a thickness of 3.5 mm to 4 mm.

(36) In some embodiments, the glass layer **22** has a thickness of 1 mm. In some embodiments, the glass layer **22** has a thickness of 1.5 mm. In some embodiments, the glass layer **22** has a thickness of 2 mm. In some embodiments, the glass layer **22** has a thickness of 2.5 mm. In some embodiments, the glass layer **22** has a thickness of 3 mm. In some embodiments, the glass layer **22** has a thickness of 3.5 mm. In some embodiments, the glass layer **22** has a thickness of 4 mm.

(37) In some embodiments, the first adhesive layer **26** is composed of thermosetting polyolefin, thermosetting polyolefin encapsulant material, thermosetting ethylene-vinyl acetate (EVA), EVA encapsulants, thermoplastic olefin, thermoplastic polyolefin (TPO) or hybrids/combinations thereof.

(38) In some embodiments, the first adhesive layer **26** has a thickness of 0.2 mm to 2 mm. In some embodiments, the first adhesive layer **26** has a thickness of 0.2 mm to 1.5 mm. In some embodiments, the first adhesive layer **26** has a thickness of 0.2 mm to 1 mm. In some embodiments, the first adhesive layer **26** has a thickness of 0.2 mm to 0.5 mm. In some embodiments, the first adhesive layer **26** has a thickness of 0.5 mm to 2 mm. In some embodiments, the first adhesive layer **26** has a thickness of 0.5 mm to 1.5 mm. In some embodiments, the first adhesive layer **26** has a thickness of 0.5 mm to 1 mm. In some embodiments, the first adhesive layer **26** has a thickness of 1 mm to 2 mm. In some embodiments, the first adhesive layer **26** has a thickness of 1 mm to 1.5 mm. In some embodiments, the first adhesive layer **26** has a thickness of 1.5 mm to 2 mm.

(39) In some embodiments, the first adhesive layer **26** has a thickness of 0.2 mm. In some embodiments, the first adhesive layer **26** has a thickness of 0.3 mm. In some embodiments, the first adhesive layer **26** has a thickness of 0.4 mm. In some embodiments, the first adhesive layer **26** has a thickness of 0.45 mm. In some embodiments, the first adhesive layer **26** has a thickness of 0.5 mm. In some embodiments, the first adhesive layer **26** has a thickness of 1 mm. In some embodiments, the first adhesive layer **26** has a thickness of 1.5 mm. In some embodiments, the first adhesive layer **26** has a thickness of 2 mm. In some embodiments, the first adhesive layer **26** has a thickness of 2.5 mm. In some embodiments, the first adhesive layer **26** has a thickness of 3 mm. In some embodiments, the first adhesive layer **26** has a thickness of 3.5 mm. In some embodiments, the first adhesive layer **26** has a thickness of 4 mm.

(40) In another embodiment, the first adhesive layer **26** has a thickness of 1 μm to 900 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 900 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 850 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 800 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 750 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 700 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 650 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 600 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 550 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 500 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 450 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 400 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 350 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 300 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 250 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm to 200 μm .

embodiments, the first adhesive layer **26** has a thickness of 750 μm to 900 μm . In some embodiments, the first adhesive layer **26** has a thickness of 750 μm to 850 μm . In some embodiments, the first adhesive layer **26** has a thickness of 750 μm to 800 μm . In some embodiments, the first adhesive layer **26** has a thickness of 800 μm to 900 μm . In some embodiments, the first adhesive layer **26** has a thickness of 800 μm to 850 μm . In some embodiments, the first adhesive layer **26** has a thickness of 850 μm to 900 μm .

(54) In some embodiments, the first adhesive layer **26** has a thickness of 1 μm . In some embodiments, the first adhesive layer **26** has a thickness of 50 μm . In some embodiments, the first adhesive layer **26** has a thickness of 100 μm . In some embodiments, the first adhesive layer **26** has a thickness of 1 μm . In some embodiments, the first adhesive layer **26** has a thickness of 150 μm . In some embodiments, the first adhesive layer **26** has a thickness of 200 μm . In some embodiments, the first adhesive layer **26** has a thickness of 250 μm . In some embodiments, the first adhesive layer **26** has a thickness of 300 μm . In some embodiments, the first adhesive layer **26** has a thickness of 350 μm . In some embodiments, the first adhesive layer **26** has a thickness of 400 μm . In some embodiments, the first adhesive layer **26** has a thickness of 450 μm . In some embodiments, the first adhesive layer **26** has a thickness of 500 μm . In some embodiments, the first adhesive layer **26** has a thickness of 550 μm . In some embodiments, the first adhesive layer **26** has a thickness of 600 μm . In some embodiments, the first adhesive layer **26** has a thickness of 650 μm . In some embodiments, the first adhesive layer **26** has a thickness of 700 μm . In some embodiments, the first adhesive layer **26** has a thickness of 750 μm . In some embodiments, the first adhesive layer **26** has a thickness of 800 μm . In some embodiments, the first adhesive layer **26** has a thickness of 850 μm . In some embodiments, the first adhesive layer **26** has a thickness of 900 μm .

(55) In some embodiments, the polymer layer **24** is composed of a fluoropolymer. In certain embodiments, the fluoropolymer may be ethylene tetrafluoroethylene (ETFE), fluoropolymer is polyvinylidene fluoride (PVDF), tetrafluoroethylene-hexafluoropropylene copolymers (FEP), and tetrafluoroethylene-hexafluoropropylene-vinylidene fluoride copolymers (THV), polyvinyl fluoride (PVF), or blends thereof. In some embodiments, the frontsheet is composed of fluoropolymers, acrylics, polyesters, silicones, polycarbonates, or combinations thereof. In other embodiments, the polymer layer **24** is composed of polyethylene terephthalate (PET), polyethylene naphthalate (PEN), polyetheretherketone (PEEK), polyaryletherketone (PAEK), polyarylate (PAR), polyetherimide (PEI), polyarylsulfone (PAS), polyethersulfone (PES), polyamideimide (PAI), polyphenylsulfone (PPSU), polyolefin, cyclic olefin copolymers (CPCs), or polyimide. In some embodiments, the polymer layer **24** is composed of a crosslinked polymeric material. In some embodiments, 50% to 99% of the polymer chains of the polymeric material are crosslinked.

(56) In some embodiments, the polymer layer **24** has a thickness of 0.01 mm to 0.5 mm. In some embodiments, the polymer layer **24** has a thickness of 0.01 mm to 0.45 mm. In some embodiments, the polymer layer **24** has a thickness of 0.01 mm to 0.4 mm. In some embodiments, the polymer layer **24** has a thickness of 0.01 mm to 0.35 mm. In some embodiments, the polymer layer **24** has a thickness of 0.01 mm to 0.3 mm. In some embodiments, the polymer layer **24** has a thickness of 0.01 mm to 0.25 mm. In some embodiments, the polymer layer **24** has a thickness of 0.01 mm to 0.2 mm. In some embodiments, the polymer layer **24** has a thickness of 0.01 mm to 0.15 mm. In some embodiments, the polymer layer **24** has a thickness of 0.01 mm to 0.1 mm. In some embodiments, the polymer layer **24** has a thickness of 0.01 mm to 0.05 mm.

(57) In some embodiments, the polymer layer **24** has a thickness of 0.05 mm to 0.5 mm. In some embodiments, the polymer layer **24** has a thickness of 0.05 mm to 0.45 mm. In some embodiments, the polymer layer **24** has a thickness of 0.05 mm to 0.4 mm. In some embodiments, the polymer layer **24** has a thickness of 0.05 mm to 0.35 mm. In some embodiments, the polymer layer **24** has a thickness of 0.05 mm to 0.3 mm. In some embodiments, the polymer layer **24** has a thickness of 0.05 mm to 0.25 mm. In some embodiments, the polymer layer **24** has a thickness of 0.05 mm to 0.2 mm. In some embodiments, the polymer layer **24** has a thickness of 0.05 mm to 0.15 mm. In

some embodiments, the polymer layer **24** has a thickness of 0.05 mm to 0.1 mm.

(58) In some embodiments, the polymer layer **24** has a thickness of 0.1 mm to 0.5 mm. In some embodiments, the polymer layer **24** has a thickness of 0.1 mm to 0.45 mm. In some embodiments, the polymer layer **24** has a thickness of 0.1 mm to 0.4 mm. In some embodiments, the polymer layer **24** has a thickness of 0.1 mm to 0.35 mm. In some embodiments, the polymer layer **24** has a thickness of 0.1 mm to 0.3 mm. In some embodiments, the polymer layer **24** has a thickness of 0.1 mm to 0.25 mm. In some embodiments, the polymer layer **24** has a thickness of 0.1 mm to 0.2 mm. In some embodiments, the polymer layer **24** has a thickness of 0.1 mm to 0.15 mm. In some embodiments, the polymer layer **24** has a thickness of 0.15 mm to 0.5 mm. In some embodiments, the polymer layer **24** has a thickness of 0.15 mm to 0.45 mm. In some embodiments, the polymer layer **24** has a thickness of 0.15 mm to 0.4 mm. In some embodiments, the polymer layer **24** has a thickness of 0.15 mm to 0.35 mm. In some embodiments, the polymer layer **24** has a thickness of 0.15 mm to 0.3 mm. In some embodiments, the polymer layer **24** has a thickness of 0.15 mm to 0.25 mm. In some embodiments, the polymer layer **24** has a thickness of 0.15 mm to 0.2 mm.

(59) In some embodiments, the polymer layer **24** has a thickness of 0.2 mm to 0.5 mm. In some embodiments, the polymer layer **24** has a thickness of 0.2 mm to 0.45 mm. In some embodiments, the polymer layer **24** has a thickness of 0.2 mm to 0.4 mm. In some embodiments, the polymer layer **24** has a thickness of 0.2 mm to 0.35 mm. In some embodiments, the polymer layer **24** has a thickness of 0.2 mm to 0.3 mm. In some embodiments, the polymer layer **24** has a thickness of 0.2 mm to 0.25 mm. In some embodiments, the polymer layer **24** has a thickness of 0.25 mm to 0.5 mm. In some embodiments, the polymer layer **24** has a thickness of 0.25 mm to 0.45 mm. In some embodiments, the polymer layer **24** has a thickness of 0.25 mm to 0.4 mm. In some embodiments, the polymer layer **24** has a thickness of 0.25 mm to 0.35 mm. In some embodiments, the polymer layer **24** has a thickness of 0.25 mm to 0.3 mm.

(60) In some embodiments, the polymer layer **24** has a thickness of 0.3 mm to 0.5 mm. In some embodiments, the polymer layer **24** has a thickness of 0.3 mm to 0.45 mm. In some embodiments, the polymer layer **24** has a thickness of 0.3 mm to 0.4 mm. In some embodiments, the polymer layer **24** has a thickness of 0.3 mm to 0.35 mm. In some embodiments, the polymer layer **24** has a thickness of 0.35 mm to 0.5 mm. In some embodiments, the polymer layer **24** has a thickness of 0.35 mm to 0.45 mm. In some embodiments, the polymer layer **24** has a thickness of 0.35 mm to 0.4 mm. In some embodiments, the polymer layer **24** has a thickness of 0.4 mm to 0.5 mm. In some embodiments, the polymer layer **24** has a thickness of 0.4 mm to 0.45 mm. In some embodiments, the polymer layer **24** has a thickness of 0.45 mm to 0.5 mm.

(61) In some embodiments, the polymer layer **24** has a thickness of 0.01 mm. In some embodiments, the polymer layer **24** has a thickness of 0.05 mm. In some embodiments, the polymer layer **24** has a thickness of 0.1 mm. In some embodiments, the polymer layer **24** has a thickness of 0.15 mm. In some embodiments, the polymer layer **24** has a thickness of 0.2 mm. In some embodiments, the polymer layer **24** has a thickness of 0.25 mm. In some embodiments, the polymer layer **24** has a thickness of 0.3 mm. In some embodiments, the polymer layer **24** has a thickness of 0.35 mm. In some embodiments, the polymer layer **24** has a thickness of 0.4 mm. In some embodiments, the polymer layer **24** has a thickness of 0.45 mm. In some embodiments, the polymer layer **24** has a thickness of 0.5 mm.

(62) In some embodiments, a backsheet **28** is juxtaposed with a second layer **14b** of the encapsulant **14**. In some embodiments, the backsheet **28** includes a first layer **30**. In some embodiments, the backsheet **28** includes a second layer **32**. In some embodiments, the first layer **30** is juxtaposed with the second layer **14b** of the encapsulant **14**. In some embodiments, the second layer **32** is juxtaposed with the first layer **30**. In some embodiments, the backsheet **28** only includes the first layer **30** (see FIG. 3). In some embodiments, the backsheet **28** includes a scrim. In some embodiments, the scrim is located between the first layer **30** and the second layer **32**.

(63) In some embodiments, the first layer **30** of the backsheet **28** is composed of a polymeric

material. In some embodiments, the first layer **30** of the backsheet **28** is composed of polyethylene terephthalate (“PET”). In another embodiment, the first layer **30** of the backsheet **28** is composed of ethylene tetrafluoroethylene (“ETFE”). In some embodiments, the first layer **30** of the backsheet **28** is composed of an acrylic such as polymethyl methacrylate (“PMMA”). In some embodiments, the first layer **30** of the backsheet **28** is composed of thermoplastic polyolefin (TPO). In some embodiments, the first layer **30** of the backsheet **28** includes of a single ply TPO roofing membrane. In other embodiments, non-limiting examples of TPO membranes are disclosed in U.S. Pat. No. 9,359,014 to Yang et al., which is incorporated by reference herein in its entirety. In another embodiment, the first layer **30** of the backsheet **28** is composed of polyvinyl chloride. In some embodiments, the first layer **30** of the backsheet **28** is composed of ethylene propylene diene monomer (EPDM) rubber. In some embodiments, the first layer **30** of the backsheet **28** includes a flame retardant additive. In some embodiments, the flame retardant additive may be clays, nanoclays, silicas, carbon black, metal hydroxides such as aluminum hydroxide, metal foils, graphite, and combinations thereof. In some embodiments, the first layer **30** is white in color. In some embodiments, the first layer **30** is white TPO.

(64) In some embodiments, the first layer **30** has a thickness of 0.2 mm to 0.5 mm. In another embodiment, the first layer **30** has a thickness of 0.2 mm to 0.4 mm. In another embodiment, the first layer **30** has a thickness of 0.2 mm to 0.3 mm. In some embodiments, the first layer **30** has a thickness of 0.3 mm to 0.5 mm. In another embodiment, the first layer **30** has a thickness of 0.3 mm to 0.4 mm. In some embodiments, the first layer **30** has a thickness of 0.4 mm to 0.5 mm. In some embodiments, the first layer **30** has a thickness of 0.2 mm. In some embodiments, the first layer **30** has a thickness of 0.3 mm. In some embodiments, the first layer **30** has a thickness of 0.4 mm. In some embodiments, the first layer **30** has a thickness of 0.5 mm.

(65) In some embodiments, the second layer **32** of the backsheet **28** is composed of a polymeric material. In some embodiments, the second layer **32** of the backsheet **28** is composed of thermoplastic polyolefin (TPO). In some embodiments, the second layer **32** of the backsheet **28** includes a single ply TPO roofing membrane. In other embodiments, non-limiting examples of TPO membranes are disclosed in U.S. Pat. No. 9,359,014 to Yang et al., which is incorporated by reference herein in its entirety. In another embodiment, the second layer **32** of the backsheet **28** is composed of polyethylene terephthalate (“PET”). In another embodiment, the second layer **32** is composed of styrene acrylic copolymer. In another embodiment, the second layer **32** of the backsheet **28** is composed of ethylene tetrafluoroethylene (“ETFE”). In some embodiments, the second layer **32** of the backsheet **28** is composed of an acrylic such as polymethyl methacrylate (“PMMA”). In another embodiment, the second layer **32** of the backsheet **28** is composed of polyvinyl chloride. In some embodiments, the second layer **32** of the backsheet **28** is composed of ethylene propylene diene monomer (EPDM) rubber. In some embodiments, the second layer **32** of the backsheet **28** includes a flame retardant additive. In some embodiments, the flame retardant additive may be clays, nanoclays, silicas, carbon black, metal hydroxides such as aluminum hydroxide, metal foils, graphite, and combinations thereof. In some embodiments, the second layer **32** is white in color. In some embodiments, the second layer **32** is white TPO.

(66) In some embodiments, the second layer **32** has a thickness of 1 mm to 5 mm. In some embodiments, the second layer **32** has a thickness of 1 mm to 4 mm. In some embodiments, the second layer **32** has a thickness of 1 mm to 3 mm. In some embodiments, the second layer **32** has a thickness of 1 mm to 2 mm. In some embodiments, the second layer **32** has a thickness of 2 mm to 5 mm. In some embodiments, the second layer **32** has a thickness of 2 mm to 4 mm. In some embodiments, the second layer **32** has a thickness of 2 mm to 3 mm. In some embodiments, the second layer **32** has a thickness of 3 mm to 5 mm. In some embodiments, the second layer **32** has a thickness of 3 mm to 4 mm. In some embodiments, the second layer **32** has a thickness of 4 mm to 5 mm. In some embodiments, the second layer **32** has a thickness of 1 mm. In some embodiments, the second layer **32** has a thickness of 2 mm. In some embodiments, the second layer **32** has a

thickness of 3 mm. In some embodiments, the second layer **32** has a thickness of 4 mm. In some embodiments, the second layer **32** has a thickness of 5 mm.

(67) In some embodiments, the first layer **30** is attached to the second layer **32** by a second adhesive layer **34**. In some embodiments, the second adhesive layer **34** may include polyvinyl butyrate, acrylic, silicone, or polycarbonate. In another embodiment, the second adhesive layer **34** may include pressure sensitive adhesives.

(68) In some embodiments, the second adhesive layer **34** is composed of thermosetting polyolefin, thermosetting polyolefin encapsulant material, thermosetting ethylene-vinyl acetate (EVA), EVA encapsulants, thermoplastic olefin, thermoplastic polyolefin (TPO) or hybrids/combinations thereof.

(69) In some embodiments, the second adhesive layer **34** has a thickness of 0.2 mm to 2 mm. In some embodiments, the second adhesive layer **34** has a thickness of 0.2 mm to 1.5 mm. In some embodiments, the second adhesive layer **34** has a thickness of 0.2 mm to 1 mm. In some embodiments, the second adhesive layer **34** has a thickness of 0.2 mm to 0.5 mm. In some embodiments, the second adhesive layer **34** has a thickness of 0.5 mm to 2 mm. In some embodiments, the second adhesive layer **34** has a thickness of 0.5 mm to 1.5 mm. In some embodiments, the second adhesive layer **34** has a thickness of 0.5 mm to 1 mm. In some embodiments, the second adhesive layer **34** has a thickness of 1 mm to 2 mm. In some embodiments, the second adhesive layer **34** has a thickness of 1 mm to 1.5 mm. In some embodiments, the second adhesive layer **34** has a thickness of 1.5 mm to 2 mm.

(70) In some embodiments, the second adhesive layer **34** has a thickness of 0.2 mm. In some embodiments, the second adhesive layer **34** has a thickness of 0.3 mm. In some embodiments, the second adhesive layer **34** has a thickness of 0.4 mm. In some embodiments, the second adhesive layer **34** has a thickness of 0.45 mm. In some embodiments, the second adhesive layer **34** has a thickness of 0.5 mm. In some embodiments, the second adhesive layer **34** has a thickness of 1 mm. In some embodiments, the second adhesive layer **34** has a thickness of 1.5 mm. In some embodiments, the second adhesive layer **34** has a thickness of 2 mm. In some embodiments, the second adhesive layer **34** has a thickness of 2.5 mm. In some embodiments, the second adhesive layer **34** has a thickness of 3 mm. In some embodiments, the second adhesive layer **34** has a thickness of 3.5 mm. In some embodiments, the second adhesive layer **34** has a thickness of 4 mm.

(71) In another embodiment, the second adhesive layer **34** has a thickness of 1 μm to 900 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 900 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 850 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 800 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 750 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 700 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 650 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 600 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 550 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 500 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 450 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 400 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 350 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 300 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 250 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 200 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 150 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 100 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm to 50 μm .

(72) In some embodiments, the second adhesive layer **34** has a thickness of 50 μm to 900 μm . In

embodiments, the second adhesive layer **34** has a thickness of 800 μm to 850 μm . In some embodiments, the second adhesive layer **34** has a thickness of 850 μm to 900 μm .

(85) In some embodiments, the second adhesive layer **34** has a thickness of 1 μm . In some embodiments, the second adhesive layer **34** has a thickness of 50 μm . In some embodiments, the second adhesive layer **34** has a thickness of 100 μm . In some embodiments, the second adhesive layer **34** has a thickness of 1 μm . In some embodiments, the second adhesive layer **34** has a thickness of 150 μm . In some embodiments, the second adhesive layer **34** has a thickness of 200 μm . In some embodiments, the second adhesive layer **34** has a thickness of 250 μm . In some embodiments, the second adhesive layer **34** has a thickness of 300 μm . In some embodiments, the second adhesive layer **34** has a thickness of 350 μm . In some embodiments, the second adhesive layer **34** has a thickness of 400 μm . In some embodiments, the second adhesive layer **34** has a thickness of 450 μm . In some embodiments, the second adhesive layer **34** has a thickness of 500 μm . In some embodiments, the second adhesive layer **34** has a thickness of 550 μm . In some embodiments, the second adhesive layer **34** has a thickness of 600 μm . In some embodiments, the second adhesive layer **34** has a thickness of 650 μm . In some embodiments, the second adhesive layer **34** has a thickness of 700 μm . In some embodiments, the second adhesive layer **34** has a thickness of 750 μm . In some embodiments, the second adhesive layer **34** has a thickness of 800 μm . In some embodiments, the second adhesive layer **34** has a thickness of 850 μm . In some embodiments, the second adhesive layer **34** has a thickness of 900 μm .

(86) In some embodiments, the first layer **30** and the second layer **32** are welded to one another. In some embodiments, the first layer **30** and the second layer **32** are ultrasonically welded to one another. In some embodiments, the first layer **30** and the second layer **32** are heat welded to one another. In some embodiments, the first layer **30** and the second layer **32** are thermally bonded to one another. In some embodiments, the first layer **30** and the second layer **32** are adhered to one another by an adhesive. In some embodiments, the first layer **30** and the second layer **32** are laminated. In some embodiments, the first layer **30** and the second layer **32** are co-extruded. In some embodiments, the first layer **30** and the second layer **32** are mechanically attached to one another.

(87) In some embodiments, the first layer **30** includes a first edge **30a**, a second edge **30b** opposite the first edge **30a**, a third edge **30c** extending from the first edge **30a** to the second edge **30b**, and a fourth edge **30d** opposite the third edge **30c** and extending from the first edge **30a** to the second edge **30b**. In some embodiments, the second layer **32** includes a first edge **32a**, a second edge **32b** opposite the first edge **32a**, a third edge **32c** extending from the first edge **32a** to the second edge **32b**, and a fourth edge **32d** opposite the third edge **32c** and extending from the first edge **32a** to the second edge **32b**.

(88) In some embodiments, the first edge **30a** of the first layer **30** is offset from the first edge **32a** of the second layer **32**. In some embodiments, the second edge **30b** of the first layer **30** is offset from the second edge **32b** of the second layer **32**. In some embodiments, the third edge **30c** of the first layer **30** is offset from the third edge **32c** of the second layer **32**. In some embodiments, the fourth edge **30d** of the first layer **30** is offset from the fourth edge **32d** of the second layer **32**.

(89) In some embodiments, at least one of the first, second, third and fourth edges **30a**, **30b**, **30c**, **30d** of the first layer **30** is offset from the corresponding first, second, third and fourth edges **32a**, **32b**, **32c**, **32d** of the second layer **32**. In some embodiments, at least two of the first, second, third and fourth edges **30a**, **30b**, **30c**, **30d** of the first layer **30** is offset from the corresponding first, second, third and fourth edges **32a**, **32b**, **32c**, **32d** of the second layer **32**. In some embodiments, at least three of the first, second, third and fourth edges **30a**, **30b**, **30c**, **30d** of the first layer **30** is offset from the corresponding first, second, third and fourth edges **32a**, **32b**, **32c**, **32d** of the second layer **32**. In some embodiments, each of the first, second, third and fourth edges **30a**, **30b**, **30c**, **30d** of the first layer **30** is offset from the corresponding first, second, third and fourth edges **32a**, **32b**, **32c**, **32d** of the second layer **32**.

(90) In some embodiments, at least one of the first, second, third and fourth edges **30a**, **30b**, **30c**, **30d** of the first layer **30** is offset from the corresponding first, second, third and fourth edges **32a**, **32b**, **32c**, **32d** of the second layer **32**, while the remaining ones of the first, second, third and fourth edges **30a**, **30b**, **30c**, **30d** of the first layer **30** are not offset from the corresponding first, second, third and fourth edges **32a**, **32b**, **32c**, **32d** of the second layer **32**. In some embodiments, at least two of the first, second, third and fourth edges **30a**, **30b**, **30c**, **30d** of the first layer **30** is offset from the corresponding first, second, third and fourth edges **32a**, **32b**, **32c**, **32d** of the second layer **32**, while the remaining ones of the first, second, third and fourth edges **30a**, **30b**, **30c**, **30d** of the first layer **30** are not offset from the corresponding first, second, third and fourth edges **32a**, **32b**, **32c**, **32d** of the second layer **32**. In some embodiments, at least three of the first, second, third and fourth edges **30a**, **30b**, **30c**, **30d** of the first layer **30** is offset from the corresponding first, second, third and fourth edges **32a**, **32b**, **32c**, **32d** of the second layer **32**, while the remaining ones of the first, second, third and fourth edges **30a**, **30b**, **30c**, **30d** of the first layer **30** are not offset from the corresponding first, second, third and fourth edges **32a**, **32b**, **32c**, **32d** of the second layer **32**.

(91) In some embodiments, the second layer **32** forms a lower surface of the photovoltaic module **10**. In some embodiments, the first layer **30** forms a lower surface of the photovoltaic module **10** (see FIG. 4).

(92) In some embodiments, the first layer **30** includes a first length **L1** extending from the first edge **30a** of the first layer **30** to the second edge of the first layer **30**. In some embodiments, the second layer **32** includes a second length **L2** extending from the first edge **32a** of the second layer **32** to the second edge **32b** of the second layer **32**. Referring to FIG. 1, in some embodiments, the first length **L1** is greater than the second length **L2**. Referring to FIG. 3, in some embodiments, the second length **L2** is greater than the first length **L1**.

(93) In some embodiments, the first layer **30** includes a first width **W1** extending from the third edge **30c** of the first layer **30** to the fourth edge **30d** of the first layer **30**. In some embodiments, the second layer **32** includes a second width **W2** extending from the third edge **32c** of the second layer **32** to the fourth edge **32d** of the second layer **32**. In some embodiments, the first width **W1** is greater than the second width **W2**. In some embodiments, the second width **W2** is greater than the first width **W1**.

(94) Referring to FIG. 5, in some embodiments, the first edge **30a** of the first layer **30** is offset from the first edge **32a** of the second layer **32** by a first distance **D1**. In some embodiments, the second edge **30b** of the first layer **30** is offset from the second edge **32b** of the second layer by a second distance **D2**. In some embodiments, the third edge **30c** of the first layer **30** is offset from the third edge **32c** of the second layer **32** by a third distance **D3**. In some embodiments, the fourth edge **30d** of the first layer **30** is offset from the fourth edge **32d** of the second layer **32** by a fourth distance **D4**.

(95) In some embodiments, the first distance **D1**, the second distance **D2**, the third distance **D3** and the fourth distance **D4** are equal to one another. In some embodiments, the first distance **D1**, the second distance **D2**, the third distance **D3** and the fourth distance **D4** are all different from one another. In some embodiments, the first distance **D1** is equal to the second distance **D2**. In some embodiments, the third distance **D3** is equal to the fourth distance **D4**.

(96) In some embodiments, the first distance **D1** is 1 mm to 10 mm. In some embodiments, the first distance **D1** is 2 mm to 10 mm. In some embodiments, the first distance **D1** is 3 mm to 10 mm. In some embodiments, the first distance **D1** is 4 mm to 10 mm. In some embodiments, the first distance **D1** is 5 mm to 10 mm. In some embodiments, the first distance **D1** is 6 mm to 10 mm. In some embodiments, the first distance **D1** is 7 mm to 10 mm. In some embodiments, the first distance **D1** is 8 mm to 10 mm. In some embodiments, the first distance **D1** is 9 mm to 10 mm. In some embodiments, the first distance **D1** is 1 mm. In some embodiments, the first distance **D1** is 2 mm. In some embodiments, the first distance **D1** is 3 mm. In some embodiments, the first distance **D1** is 4 mm. In some embodiments, the first distance **D1** is 5 mm. In some embodiments, the first

distance **D1** is 6 mm. In some embodiments, the first distance **D1** is 7 mm. In some embodiments, the first distance **D1** is 8 mm. In some embodiments, the first distance **D1** is 9 mm. In some embodiments, the first distance **D1** is 10 mm.

(97) In some embodiments, the first distance **D2** is 1 mm to 10 mm. In some embodiments, the first distance **D2** is 2 mm to 10 mm. In some embodiments, the first distance **D2** is 3 mm to 10 mm. In some embodiments, the first distance **D2** is 4 mm to 10 mm. In some embodiments, the first distance **D2** is 5 mm to 10 mm. In some embodiments, the first distance **D2** is 6 mm to 10 mm. In some embodiments, the first distance **D2** is 7 mm to 10 mm. In some embodiments, the first distance **D2** is 8 mm to 10 mm. In some embodiments, the first distance **D2** is 9 mm to 10 mm. In some embodiments, the first distance **D2** is 1 mm. In some embodiments, the first distance **D2** is 2 mm. In some embodiments, the first distance **D2** is 3 mm. In some embodiments, the first distance **D2** is 4 mm. In some embodiments, the first distance **D2** is 5 mm. In some embodiments, the first distance **D2** is 6 mm. In some embodiments, the first distance **D2** is 7 mm. In some embodiments, the first distance **D2** is 8 mm. In some embodiments, the first distance **D2** is 9 mm. In some embodiments, the first distance **D2** is 10 mm.

(98) In some embodiments, the first distance **D3** is 1 mm to 10 mm. In some embodiments, the first distance **D3** is 2 mm to 10 mm. In some embodiments, the first distance **D3** is 3 mm to 10 mm. In some embodiments, the first distance **D3** is 4 mm to 10 mm. In some embodiments, the first distance **D3** is 5 mm to 10 mm. In some embodiments, the first distance **D3** is 6 mm to 10 mm. In some embodiments, the first distance **D3** is 7 mm to 10 mm. In some embodiments, the first distance **D3** is 8 mm to 10 mm. In some embodiments, the first distance **D3** is 9 mm to 10 mm. In some embodiments, the first distance **D3** is 1 mm. In some embodiments, the first distance **D3** is 2 mm. In some embodiments, the first distance **D3** is 3 mm. In some embodiments, the first distance **D3** is 4 mm. In some embodiments, the first distance **D3** is 5 mm. In some embodiments, the first distance **D3** is 6 mm. In some embodiments, the first distance **D3** is 7 mm. In some embodiments, the first distance **D3** is 8 mm. In some embodiments, the first distance **D3** is 9 mm. In some embodiments, the first distance **D3** is 10 mm.

(99) In some embodiments, the first distance **D4** is 1 mm to 10 mm. In some embodiments, the first distance **D4** is 2 mm to 10 mm. In some embodiments, the first distance **D4** is 3 mm to 10 mm. In some embodiments, the first distance **D4** is 4 mm to 10 mm. In some embodiments, the first distance **D4** is 5 mm to 10 mm. In some embodiments, the first distance **D4** is 6 mm to 10 mm. In some embodiments, the first distance **D4** is 7 mm to 10 mm. In some embodiments, the first distance **D4** is 8 mm to 10 mm. In some embodiments, the first distance **D4** is 9 mm to 10 mm. In some embodiments, the first distance **D4** is 1 mm. In some embodiments, the first distance **D4** is 2 mm. In some embodiments, the first distance **D4** is 3 mm. In some embodiments, the first distance **D4** is 4 mm. In some embodiments, the first distance **D4** is 5 mm. In some embodiments, the first distance **D4** is 6 mm. In some embodiments, the first distance **D4** is 7 mm. In some embodiments, the first distance **D4** is 8 mm. In some embodiments, the first distance **D4** is 9 mm. In some embodiments, the first distance **D4** is 10 mm.

(100) Referring to FIGS. 1 through 4, 6 and 7, In some embodiments, the glass layer **22** includes a first edge **22a**, a second edge **22b** opposite the first edge **22a**, a third edge **22c** extending from the first edge **22a** to the second edge **22b**, and a fourth edge **22d** opposite the third edge **22c** and extending from the first edge **22a** to the second edge **22b**. In some embodiments, the first edge **22a** is offset from the first edge **32a** of the second layer **32**.

(101) In some embodiments, the first edge **22a** is offset from the first edge **32a** of the second layer **32** by the first distance **D1**. In some embodiments, the second edge **22b** of the glass layer **22** is offset from the second edge **32b** of the second layer **32**. In some embodiments, the second edge **22b** of the glass layer **22** is offset from the second edge **32b** of the second layer **32** by the second distance **D2**. In some embodiments, the third edge **22c** of the glass layer **22** is offset from the third edge **32c** of the second layer **32**. In some embodiments, the third edge **22c** of the glass layer **22** is

offset from the third edge **32c** of the second layer **32** by the third distance **D3**. In some embodiments, the fourth edge **22d** of the glass layer **22** is offset from the fourth edge **32d** of the second layer **32**. In some embodiments, the fourth edge **22d** of the glass layer **22** is offset from the fourth edge **32d** of the second layer **32** by the fourth distance **D4**.

(102) In some embodiments, the first edge **22a** of the glass layer **22** is offset from the first edge **30a** of the first layer **30**. In some embodiments, the first edge **22a** of the glass layer **22** is offset from the first edge **30a** of the first layer **30** by the first distance **D1**. In some embodiments, the second edge **22b** of the glass layer **22** is offset from the second edge **30b** of the first layer **30**. In some embodiments, the second edge **22b** of the glass layer **22** is offset from the second edge **30b** of the first layer **30** by the second distance **D2**. In some embodiments, the third edge **22c** of the glass layer **22** is offset from the third edge **30c** of the first layer **30**. In some embodiments, the third edge **22c** of the glass layer **22** is offset from the third edge **30c** of the first layer **30** by the third distance **D3**. In some embodiments, the fourth edge **22d** of the glass layer **22** is offset from the fourth edge **30d** of the first layer **30**. In some embodiments, the fourth edge **22d** of the glass layer **22** is offset from the fourth edge **30d** of the first layer **30** by the fourth distance **D4**.

(103) In some embodiments, the photovoltaic module **10** is laminated. In some embodiments, all of the previously mentioned applicable layers of the photovoltaic module **10** are laminated in one lamination step. In some embodiments, a method of making the photovoltaic module **10** includes a first lamination step and a second lamination step. In an embodiment, the first lamination step includes laminating the layers of the frontsheet **16**. In an embodiment, the first lamination step includes laminating the glass layer **22**, the polymer layer **22**, and the adhesive layer **24**. In some embodiments, the second lamination step includes laminating the frontsheet **16** with the remaining layers of the photovoltaic module **10**. In an embodiment, the second lamination step includes laminating the frontsheet **16**, the encapsulant **14**, the at least one solar cell **12**, and the backsheet **28**.

(104) In some embodiments, a headlap portion is attached to the backsheet **28**. In some embodiments, the headlap portion is attached to the first layer **30**. In some embodiments, the headlap portion is attached to the second layer **32**. In some embodiments, headlap portion and the backsheet **28** are welded to one another. In some embodiments, headlap portion and the backsheet **28** are ultrasonically welded to one another. In some embodiments, headlap portion and the backsheet **28** are heat welded to one another. In some embodiments, headlap portion and the backsheet **28** are thermally bonded to one another. In some embodiments, headlap portion and the backsheet **28** are adhered to one another by an adhesive. In some embodiments, headlap portion and the backsheet **28** are laminated. In some embodiments, headlap portion and the backsheet **28** are co-extruded. In some embodiments, headlap portion and the backsheet **28** are mechanically attached to one another. In some embodiments, headlap portion and the backsheet **28** are attached to one another by at least one fastener. In some embodiments, headlap portion and the backsheet **28** are attached to one another by a plurality of fasteners. In some embodiments, headlap portion and the backsheet **28** are attached to one another by deforming one of headlap portion and the backsheet **28** into the other one of headlap portion and the backsheet **28**. In some embodiments, headlap portion and the backsheet **28** are attached to one another by deforming a portion of one of headlap portion and the backsheet **28** into the other one of headlap portion and the backsheet **28**. In some embodiments, headlap portion and the backsheet **28** are attached to one another by forming at least one hole in one or both of headlap portion and the backsheet **28** and dispensing molten material into the at least one hole to connect headlap portion and the backsheet **28**. In some embodiments, non-limiting examples of fasteners, fastening means and methods for fastening, connecting and attaching the first layer **30** to the second layer **32** are disclosed in U.S. Pat. No. 7,833,371 to Binkley et al, U.S. Pat. No. 8,006,457 to Binkley et al, U.S. Pat. No. 8,127,514 to Binkley et al, and U.S. Pat. No. 8,316,608 to Binkley et al, each of which is incorporated by reference herein in its entirety.

(105) Referring to FIGS. **8** through **10**, in some embodiments, the offset of the backsheet **28** (i.e.,

either the first layer **30** or the second layer **32**) from the glass layer **22** reduces pinchoff on the edges of the photovoltaic module **10**. In some embodiments, as used herein, the terms “pinchoff” or “pinch” is that the thicknesses of the layers of the photovoltaic module **10** causes pressure at the edges **22a** through **22d** of the glass layer **22**, which can squeeze the encapsulant **14** while in a liquid form during lamination of the photovoltaic module **10**, and could result in reduced bond line thickness. In some embodiments, pinchoff can result in premature delamination of the backsheet **28** from the glass layer **22**. In some embodiments, the offset of the backsheet **28** (i.e., either the first layer **30** or the second layer **32**) from the glass layer **22** reduces visibility of any scrim included within the backsheet **28**. In some embodiments, the offset of one or more of the edges **32a**, **32b**, **32c**, **32d** of the second layer **32** relative to the corresponding edges **30a**, **30b**, **30c**, **30d** of the first layer **30** reduces the potential of the first layer **30** to pinch. In some embodiments, the offset of one or more of the edges **30a**, **30b**, **30c**, **30d** of the first layer **30** relative to the corresponding edges **32a**, **32b**, **32c**, **32d** of the second layer **32** reduces the potential of the second layer **32** to pinch. In some embodiments, each of the distances **D1** through **D4** is of a sufficient amount so as to enable the edges **30a** through **30d** of the first layer **30** and/or the edges **32a** through **32d** of the second layer **32** to reduce the potential of the first layer **30** and the second layer **32** to pinch.

(106) In some embodiments, each of the distances **D1** through **D4** is of a sufficient amount so as to enable the edges **30a** through **30d** of the first layer **30** and/or the edges **32a** through **32d** of the second layer **32**, as applicable, to be cut or trimmed when the photovoltaic module **10** is installed on a roof deck **90** for aesthetically matching the photovoltaic module **10** with other ones of the photovoltaic module **10**.

(107) In some embodiments, the roof deck **90** is a steep slope roof deck. As defined herein, a “steep slope roof deck” is any roof deck that is disposed on a roof having a pitch of Y/X , where Y and X are in a ratio of 4:12 to 12:12, where Y corresponds to the “rise” of the roof, and where X corresponds to the “run” of the roof.

(108) In some embodiments, the roof deck **90** may be a sloped roof of a structure. As used herein, a “sloped” roof deck is a roof deck that has a slope less than a slope of a steep slope roof deck, but is not a flat roof deck.

(109) In some embodiments, the roof deck **90** is a component of a commercial roof. In some embodiments, the roof deck **90** has a slope of 3 inches per foot or less. In some embodiments, the roof deck **90** has a slope of 0.25 inch to 3 inches per foot. In some embodiments, the roof deck **90** has a slope of 0.25 inch to 2 inches per foot. In some embodiments, the roof deck **90** has a slope of 0.25 inch to 1 inch per foot. In some embodiments, the roof deck **90** has a slope of 1 inch to 3 inches per foot. In some embodiments, the roof deck **90** has a slope of 1 inch to 2 inches per foot. In some embodiments, the roof deck **90** has a slope of 2 inches to 3 inches per foot.

(110) In some embodiments, a system of at least one of the photovoltaic modules **10** is installed on the roof deck **90**. In some embodiments, a system of a plurality of the photovoltaic modules **10** is installed on the roof deck **90**. In some embodiments, the plurality of the photovoltaic modules **10** includes two of the photovoltaic modules **10**. In some embodiments, the plurality of the photovoltaic modules **10** includes three of the photovoltaic modules **10**. In some embodiments, the plurality of the photovoltaic modules **10** includes four of the photovoltaic modules **10**. In some embodiments, the plurality of the photovoltaic modules **10** includes five of the photovoltaic modules **10**. In some embodiments, the plurality of the photovoltaic modules **10** includes six of the photovoltaic modules **10**. In some embodiments, the plurality of the photovoltaic modules **10** includes more than six of the photovoltaic modules **10**. In some embodiments, the plurality of the photovoltaic modules **10** is installed in an array on the roof deck **90**. In some embodiments, the array includes a plurality of subarrays. In some embodiments, the array includes two subarrays. In some embodiments, the array includes three subarrays. In some embodiments, the array includes four subarrays. In some embodiments, the array includes five subarrays. In some embodiments, the array includes six subarrays. In some embodiments, the array includes more than six subarrays.

(111) In some embodiments, the plurality of photovoltaic modules **10** is installed directly to the roof deck **90**. In some embodiments, each of the plurality of photovoltaic modules **10** is installed on the roof deck **90** by a plurality of fasteners. In some embodiments, the plurality of fasteners are installed through the headlap portion. In some embodiments, the plurality of fasteners includes a plurality of nails. In some embodiments, the plurality of fasteners includes a plurality of screws. In some embodiments, the plurality of fasteners includes a plurality of rivets. In some embodiments, the plurality of fasteners includes a plurality of staples.

(112) In some embodiments, each of the plurality of photovoltaic modules **10** is installed on the roof deck **90** by an adhesive. In some embodiments, the adhesive is adhered directly to the roof deck **90**. In some embodiments, the adhesive is adhered to an underlayment. In some embodiments, the underlayment is adhered directly to the roof deck **90**. In some embodiments, the adhesive is located on a rear surface of the photovoltaic module **10**. In some embodiments, the adhesive includes at least one adhesive strip. In some embodiments, the adhesive includes a plurality of adhesive strips. In some embodiments, the plurality of adhesive strips is arranged intermittently. In some embodiments, the adhesive is located proximate to one edge of the photovoltaic module **10**. In some embodiments, the adhesive is a peel and stick film sheet. In some embodiments, the peel and stick film sheet includes at least one sheet of film removably attached to the rear surface. In some embodiments, the peel and stick film sheet is composed of EverGuard Freedom HW peel and stick membrane manufactured by GAF. In some embodiments, the adhesive includes polyvinyl butyrate, acrylic, silicone, or polycarbonate. In some embodiments, the adhesive includes pressure sensitive adhesives.

(113) In some embodiments, one or more of the photovoltaic modules **10** is a photovoltaic module shown and described in either or both of U.S. application Ser. No. 17/831,307, filed Jun. 2, 2022, titled “Roofing Module System,” and published under U.S. Patent Application Publication No. 2022-0393637 on Dec. 8, 2022; and/or U.S. application Ser. No. 18/169,718, filed Feb. 15, 2023, titled “Roofing Module System,” and published under U.S. Patent Application Publication No. 2023-0203815 on Jun. 29, 2023, the disclosures of each of which are incorporated by reference herein in their entireties. In some embodiments, the photovoltaic module includes a structure, composition, components, and/or function similar to those of one or more embodiments of the photovoltaic modules disclosed in PCT International Patent Publication No. WO 2022/051593, Application No. PCT/US2021/049017, published Mar. 10, 2022, entitled “Building Integrated Photovoltaic System,” owned by GAF Energy LLC, and U.S. Pat. No. 11,251,744 to Bunea et al., issued Feb. 15, 2022, entitled “Photovoltaic Shingles and Methods of Installing Same,” the contents of each of which are incorporated by reference herein in their entirety.

(114) In some embodiments, the system includes a plurality of roofing shingles. In some embodiments, the photovoltaic modules **10** have an appearance that aesthetically match the appearance of the plurality of roofing shingles. In some embodiments, the roofing shingle is a cuttable roofing module. In some embodiments, the roofing shingle is a nailable roofing module. In some embodiments, the roofing shingle is a cuttable roofing module shown and described in U.S. application Ser. No. 17/831,307, filed Jun. 2, 2022, titled “Roofing Module System,” and published under U.S. Patent Application Publication No. 2022-0393637 on Dec. 8, 2022; and/or U.S. application Ser. No. 18/169,718, filed Feb. 15, 2023, titled “Roofing Module System,” and published under U.S. Patent Application Publication No. 2023-0203815 on Jun. 29, 2023, the disclosures of each of which are incorporated by reference herein in their entireties.

Claims

1. A system, comprising: a plurality of photovoltaic modules installed on a roof deck, wherein each of the photovoltaic modules includes at least one solar cell, a first encapsulant encapsulating the at least one solar cell, wherein the first encapsulant includes a first surface and a second surface

opposite the first surface, a frontsheet juxtaposed with the first surface of the first encapsulant, wherein the frontsheet includes a glass layer, and a backsheet juxtaposed with the second surface of the first encapsulant, wherein the backsheet includes a first layer, wherein the first layer includes a first edge, a second edge opposite the first edge, a third edge extending from the first edge to the second edge, and a fourth edge opposite the third edge and extending from the first edge to the second edge, wherein the first layer includes a first length extending from the first edge to the second edge, and a second layer adjacent and below the first layer, wherein the second layer includes a first edge, a second edge opposite the first edge of the second layer, a third edge extending from the first edge of the second layer to the second edge of the second layer, and a fourth edge opposite the third edge of the second layer and extending from the first edge of the second layer to the second edge of the second layer, wherein the second layer includes a second length extending from the first edge of the second layer to the second edge of the second layer, and wherein the first length is greater than the second length, wherein the second layer is the lowermost layer of the photovoltaic module, wherein the first edge of the first layer is offset and extends outwardly from the first edge of the second layer, wherein the second edge of the first layer is offset and extends outwardly from the second edge of the second layer, wherein the third edge of the first layer is offset from the third edge of the second layer, and wherein the fourth edge of the first layer is offset from the fourth edge of the second layer, and an adhesive layer between the first layer and the second layer, wherein the adhesive layer includes a first edge and a second edge opposite the first edge of the adhesive layer, wherein the adhesive layer includes a third length extending from the first edge of the adhesive layer to the second edge of the adhesive layer, and wherein the third length is equal to the second length.

2. The system of claim 1, wherein the first layer includes a first width extending from the third edge of the first layer to the fourth edge of the first layer, wherein the second layer includes a second width extending from the third edge of the second layer to the fourth edge of the second layer, and wherein the first width is greater than the second width.
3. The system of claim 2, wherein the second layer is composed of thermoplastic polyolefin (TPO).
4. The system of claim 2, wherein the first layer is composed of a polymer.
5. The system of claim 4, wherein the first layer is composed of thermoplastic polyolefin (TPO).
6. The system of claim 2, wherein the glass layer includes: a first edge, a second edge opposite the first edge of the glass layer, a third edge extending from the first edge of the glass layer to the second edge of the glass layer, and a fourth edge opposite the third edge of the glass layer and extending from the first edge of the glass layer to the second edge of the glass layer, wherein the first edge of the glass layer is offset from the first edge of the second layer, wherein the second edge of the glass layer is offset from the second edge of the second layer, wherein the third edge of the glass layer is offset from the third edge of the second layer, and wherein the fourth edge of the glass layer is offset from the fourth edge of the second layer.
7. The system of claim 1, wherein the first edge of the first layer is offset from the first edge of the second layer by a first distance, wherein the second edge of the first layer is offset from the second edge of the second layer by a second distance, wherein the third edge of the first layer is offset from the third edge of the second layer by a third distance, and wherein the fourth edge of the first layer is offset from the fourth edge of the second layer by a fourth distance.
8. The system of claim 7, wherein the first distance, the second distance, the third distance and the fourth distance are equal to one another.
9. The system of claim 7, wherein the first distance is equal to the second distance, and wherein the third distance is equal to the fourth distance.
10. The system of claim 1, wherein the frontsheet includes a polymer layer and a second encapsulant, and wherein the polymer layer is attached to the glass layer by the second encapsulant.
11. A photovoltaic module, comprising: at least one solar cell, a first encapsulant encapsulating the at least one solar cell, wherein the first encapsulant includes a first surface and a second surface

opposite the first surface, a frontsheet juxtaposed with the first surface of the first encapsulant, wherein the frontsheet includes a glass layer, and a backsheet juxtaposed with the second surface of the first encapsulant, wherein the backsheet includes a first layer, wherein the first layer includes a first edge, a second edge opposite the first edge, a third edge extending from the first edge to the second edge, and a fourth edge opposite the third edge and extending from the first edge to the second edge, wherein the first layer includes a first length extending from the first edge to the second edge, and a second layer attached to and below the first layer, wherein the second layer includes a first edge, a second edge opposite the first edge of the second layer, a third edge extending from the first edge of the second layer to the second edge of the second layer, and a fourth edge opposite the third edge of the second layer and extending from the first edge of the second layer to the second edge of the second layer, wherein the second layer includes a second length extending from the first edge of the second layer to the second edge of the second layer, and wherein the first length is greater than the second length, wherein the second layer is the lowermost layer of the photovoltaic module, wherein the first edge of the first layer is offset and extends outwardly from the first edge of the second layer, wherein the second edge of the first layer is offset and extends outwardly from the second edge of the second layer, wherein the third edge of the first layer is offset from the third edge of the second layer, and wherein the fourth edge of the first layer is offset from the fourth edge of the second layer, wherein the second layer forms a lower surface of the photovoltaic module, and wherein at least one of the first layer and the second layer is composed of thermoplastic polyolefin (TPO), and an adhesive layer between the first layer and the second layer, wherein the adhesive layer includes a first edge and a second edge opposite the first edge of the adhesive layer, wherein the adhesive layer includes a third length extending from the first edge of the adhesive layer to the second edge of the adhesive layer, and wherein the third length is equal to the second length.

12. A system, comprising: a plurality of photovoltaic modules installed on a roof deck, wherein each of the photovoltaic modules includes at least one solar cell, a first encapsulant encapsulating the at least one solar cell, wherein the first encapsulant includes a first surface and a second surface opposite the first surface, a frontsheet juxtaposed with the first surface of the first encapsulant, and a backsheet juxtaposed with the second surface of the first encapsulant, wherein the backsheet includes a first layer, wherein the first layer includes a first edge and a second edge opposite the first edge, wherein the first layer includes a first length extending from the first edge to the second edge, and a second layer adjacent and below the first layer, wherein the second layer includes a first edge and a second edge opposite the first edge of the second layer, wherein the second layer includes a second length extending from the first edge of the second layer to the second edge of the second layer, and wherein the first length is greater than the second length, wherein the second layer is the lowermost layer of the photovoltaic module, wherein the first edge of the first layer is offset and extends outwardly from the first edge of the second layer, and wherein the second edge of the first layer is offset and extends outwardly from the second edge of the second layer, and an adhesive layer between the first layer and the second layer, wherein the adhesive layer includes a first edge and a second edge opposite the first edge of the adhesive layer, wherein the adhesive layer includes a third length extending from the first edge of the adhesive layer to the second edge of the adhesive layer, and wherein the third length is equal to the second length.

13. The system of claim 12, wherein the second layer is composed of thermoplastic polyolefin (TPO).

14. The system of claim 12, wherein the first layer is composed of a polymer.

15. The system of claim 14, wherein the first layer is composed of thermoplastic polyolefin (TPO).

16. The system of claim 12, wherein the frontsheet includes a glass layer.

17. The system of claim 16, wherein the frontsheet includes a polymer layer and a second encapsulant, and wherein the polymer layer is attached to the glass layer by the second encapsulant.

18. The system of claim 16, wherein the glass layer includes a first edge, and a second edge

opposite the first edge of the glass layer, wherein the first edge of the glass layer is offset from the first edge of the second layer, and wherein the second edge of the glass layer is offset from the second edge of the second layer.

19. The system of claim 18, wherein the glass layer includes a third edge and a fourth edge opposite the third edge of the glass layer, wherein the third edge of the glass layer is offset from the third edge of the second layer, and wherein the fourth edge of the glass layer is offset from the fourth edge of the second layer.
