

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12388161
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Zhu; Jianhua et al.

Battery, battery module, battery pack and electric vehicle

Abstract

A battery includes a housing, at least one end cover, partition plates, and electrode core assemblies. The at least one end cover is arranged on at least one of two opposite ends of the housing. The partition plates are spaced apart from each other in the housing for separating the internal space of the housing into accommodating cavities. Each electrode core assembly is arranged in an accommodating cavity. The electrode core assembly includes at least one electrode core. The electrode core assemblies are connected in series. The partition plate is provided with an electrolyte solution filling channel in communication with an accommodating cavity on at least one side of the partition plate. The electrolyte solution filling channel is closed upon completion of filling the electrolyte solution. A through hole is provided on the partition plate at a position of the housing corresponding to the electrolyte solution filling channel.

Inventors:	Zhu; Jianhua (Shenzhen, CN), Zhu; Yan (Shenzhen, CN), Deng; Dongjun (Shenzhen, CN)
Applicant:	BYD COMPANY LIMITED (Guangdong, CN)
Family ID:	75922344
Assignee:	BYD COMPANY LIMITED (Guangdong, CN)
Appl. No.:	17/778731
Filed (or PCT Filed):	November 18, 2020
PCT No.:	PCT/CN2020/129852
PCT Pub. No.:	WO2021/098739
PCT Pub. Date:	May 27, 2021

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Foreign Application Priority Data

CN

201911171817.4

Nov. 22, 2019

Publication Classification

Int. Cl.: H01M50/645 (20210101); H01M50/184 (20210101); H01M50/474 (20210101);
H01M50/51 (20210101); H01M50/682 (20210101)

U.S. Cl.:

CPC H01M50/645 (20210101); H01M50/184 (20210101); H01M50/474 (20210101);
H01M50/51 (20210101); H01M50/682 (20210101); H01M2220/20 (20130101)

Field of Classification Search

CPC: H01M (50/609); H01M (50/618); H01M (50/627); H01M (50/636); H01M (50/645);
H01M (50/668); H01M (50/474); H01M (50/477); H01M (50/184); H01M (50/186);
H01M (50/188)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2006/0166087	12/2005	Ogata	429/153	H01M 10/0413
2017/0040575	12/2016	Bang	N/A	N/A
2021/0126293	12/2020	Wang	N/A	H01M 50/533

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2852411	12/2005	CN	N/A
102104167	12/2010	CN	N/A
102403479	12/2011	CN	N/A
102683755	12/2011	CN	N/A
106025392	12/2015	CN	N/A
106505169	12/2016	CN	N/A
107230801	12/2016	CN	N/A
110518156	12/2018	CN	N/A
110518174	12/2018	CN	N/A
211743203	12/2019	CN	N/A
211743281	12/2019	CN	N/A
1705731	12/2005	EP	N/A
3113243	12/2016	EP	N/A
2001057199	12/2000	JP	N/A
2010080081	12/2009	JP	N/A
2010153179	12/2009	JP	N/A
2011129668	12/2010	JP	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion issued in Application No. PCT/CN2020/129852, mailed on Feb. 20, 2021, 13 pages. cited by applicant

Primary Examiner: Domone; Christopher P

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a National Phase Application of International Patent Application No. PCT/CN2020/129852, filed on Nov. 18, 2020, which is based on and claims priority to and benefits of Chinese Patent Application No. 201911171817.4, entitled “BATTERY, BATTERY MODULE, BATTERY PACK AND ELECTRIC VEHICLE” and filed on Nov. 22, 2019. The entire content of all of the above-identified applications is incorporated herein by reference.

FIELD

(2) The present disclosure relates to the field of batteries, and more specifically, to a battery, a battery module, a battery pack, and an electric vehicle.

BACKGROUND

(3) With the continuous popularization of new energy automobiles, increasingly high use requirements are imposed on power batteries of the new energy automobiles. In particular, users have requirements for the long mile range of the new energy automobiles. Therefore, power battery packs in the new energy automobiles need to have a high overall capacity. In addition, during the operation of a power battery pack, internal consumption caused by internal resistance is required to be minimized.

(4) Generally, a housing of a battery is provided with only one bare battery core or a number of bare battery cores connected in parallel. However, the single bare battery core or the number of bare battery cores connected in parallel cannot increase the voltage of the entire battery. For example, a voltage of a lithium titanate battery is 2.4 volts, a voltage of a lithium iron phosphate battery is 3.2 volts, a voltage of a ternary battery is 3.7 volts, and a voltage of a multipolymer battery is 4.3 volts. Therefore, when a high voltage (a high capacity) is required, a number of cells need to be connected in series to form a battery module, and then the battery module is assembled into a power battery pack.

(5) Existing new energy automobiles generally have a width greater than 1 meter and a length of a few meters. The power battery pack of the new energy automobile is generally arranged at the bottom of the new energy automobile. Currently, the power battery pack on the market generally has a width roughly the same as the width of the new energy automobile, which is greater than 1 meter. A length of the power battery pack is determined based on a reserved space at the bottom of the new energy automobile, which is generally greater than 2 meters. As a whole, both the length and the width of the power battery pack are greater than 1 meter. However, currently, the length of the battery on the market is generally about 0.3 meters. Therefore, at least three cells or even more need to be connected in series in each battery module. In addition, an external power connector needs to be arranged for power connection between two adjacent cells, resulting in a relatively large number of structural members of the battery. In this way, costs are increased, and the overall weight of the power battery pack is increased. In addition, the structural members occupy a relatively large internal space of the battery pack, resulting in a decrease in an overall capacity of the power battery pack. Therefore, the larger number of cells result in more space wasting. Moreover, a number of external power connectors need to be arranged for power connection, so

that internal consumption of the power battery pack in use is increased with the increased internal resistance.

(6) In order to resolve the above technical problems, some cells are also provided in related arts. A number of electrode core assemblies connected in series are arranged inside a housing of the battery, and two adjacent electrode core assemblies are separated by using a partition plate. In this way, the housing and external structural members can be reduced. Therefore, the space utilization of the battery pack is increased, the internal consumption of the battery pack in use is reduced, and the overall capacity of the power battery pack is ensured.

(7) Since the number of electrode core assemblies are connected in series side by side, the potential difference inside the battery is relatively high. If the number of electrode core assemblies connected in series share electrolyte solution in a cavity, the electrolyte solution is highly likely to decompose due to the high potential difference, resulting in battery failure. In order to resolve the above problem, the partition plate in the above battery is arranged between the two adjacent electrode core assemblies, and the electrode core assemblies are separated in the respective cavities by the partition plates. Each cavity has an individual electrolyte solution. However, since the inside of the housing is separated into a number of individual cavities by the partition plates, technical problems of how to safely and effectively fill the electrolyte solution into each individual cavity and how to implement the sealing during the electrolyte solution filling while ensuring separation between the two adjacent cavities are urgently required to be resolved by those skilled in the art.

SUMMARY

(8) The content of the present disclosure resolves at least one of the technical problems existing in related arts.

(9) A first aspect of the present disclosure provides a battery, including a housing, end covers, partition plates, and a number of electrode core assemblies. The end covers are arranged on two opposite ends of the housing for sealing an internal space of the housing. The partition plates are spaced apart from each other in the housing for dividing the internal space of the housing into a number of accommodating cavities successively arranged along a first direction. Each electrode core assembly is arranged in each accommodating cavity. The number of electrode core assemblies are arranged along the first direction and connected in series. Each partition plate comprises an electrolyte solution filling channel. The electrolyte solution filling channel is in communication with the accommodating cavity on at least one side of the partition plate, and is configured for filling electrolyte solution into the accommodating cavity from an outside of the battery. The electrolyte solution filling channel is in a closed state upon completion of filling the electrolyte solution to prevent communication between the accommodating cavity and the outside of the battery. A through hole is provided at a position of the housing corresponding to the electrolyte solution filling channel on the partition plate, and is configured to communicate the electrolyte solution filling channel with the outside of the battery.

(10) A second aspect of the present disclosure provides a battery module, including the battery.

(11) A third aspect of the present disclosure provides a battery pack, including the battery or the battery module.

(12) A fourth aspect of the present disclosure provides an electric vehicle, including the battery pack, the battery module, or the battery.

(13) According to the battery provided in the present disclosure, the partition plates are arranged inside the housing to separate the number of sealed accommodating cavities to accommodate the number of electrode core assemblies, and the number of electrode core assemblies are connected in series. In this way, the battery can have a higher battery capacity and voltage. Therefore, the overall capacity and voltage of the battery pack can be enhanced, and the endurance capacity of the electric vehicle can be improved. In addition, the electrolyte solution filling channel is provided on the partition plates, and the through holes are provided at the position of the housing corresponding to the electrolyte solution filling channel on the partition plate. In this way, the electrolyte solution

may be filled into each individual accommodating cavity after the battery is assembled. Therefore, the problem of the electrolyte solution filling of the battery including the number of electrode core assemblies connected in series is effectively resolved.

(14) Additional aspects and advantages of the present disclosure will be given in the following description, some of which will become apparent from the following description or may be learned from practices of the present disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic diagram of an overall structure of a battery according to an embodiment of the present disclosure.

(2) FIG. 2 is a cross-sectional view of the battery shown in FIG. 1.

(3) FIG. 3 is a partial enlarged view of part A in FIG. 2.

(4) FIG. 4 is a structural exploded view of a battery according to another embodiment of the present disclosure.

(5) FIG. 5 is a structural exploded view of a battery according to another embodiment of the present disclosure.

(6) FIG. 6 is a schematic structural diagram of a partition plate provided with an electrolyte solution filling channel according to another embodiment of the present disclosure.

(7) FIG. 7 is a schematic structural diagram of a partition plate provided with an electrolyte solution filling channel according to another embodiment of the present disclosure.

(8) FIG. 8 is a schematic structural diagram of a partition plate provided with an electrolyte solution guide hole according to another embodiment of the present disclosure.

(9) FIG. 9 is a schematic structural diagram of sealed mating between a sealing member and a sealing channel according to an embodiment of the present disclosure.

(10) FIG. 10 is a cross-sectional view of the structure shown in FIG. 9.

(11) FIG. 11 is a schematic structural diagram of sealed mating between a sealing member and a sealing channel according to another embodiment of the present disclosure.

(12) FIG. 12 is a front view of the structure shown in FIG. 11.

(13) FIG. 13 is a cross-sectional view of the structure shown in FIG. 11.

(14) FIG. 14 is a schematic structural diagram of sealed mating between a sealing member and a sealing channel according to another embodiment of the present disclosure.

(15) FIG. 15 is a front view of the structure shown in FIG. 14.

(16) FIG. 16 is a cross-sectional view of the structure shown in FIG. 14.

(17) FIG. 17 is a schematic structural diagram of sealed mating between a sealing member and a sealing channel according to another embodiment of the present disclosure.

(18) FIG. 18 is a front view of the structure shown in FIG. 17.

(19) FIG. 19 is a cross-sectional view of the structure shown in FIG. 17.

(20) FIG. 20 is a schematic structural diagram of sealed mating between a sealing member and a sealing channel according to another embodiment of the present disclosure.

(21) FIG. 21 is a schematic structural diagram of a battery pack according to an embodiment of the present disclosure.

(22) FIG. 22 is a schematic structural diagram of a battery pack according to another embodiment of the present disclosure.

(23) FIG. 23 is a schematic structural diagram of a battery module according to an embodiment of the present disclosure.

(24) FIG. 24 is a schematic structural diagram of an electric vehicle according to an embodiment of the present disclosure.

(25) FIG. **25** is a schematic structural diagram of an electric vehicle according to another embodiment of the present disclosure.

(26) FIG. **26** is a schematic structural diagram of an electric vehicle according to another embodiment of the present disclosure.

LIST OF REFERENCE NUMERALS

(27) Battery **100**;

(28) Housing **11**; Through hole **111**, **1122**; Separator film **112**; Sub-separator film **1121**; End cover **121**; Partition plate **122**; Through connecting hole **123**; Packaging structure **124**; Side surface **125**; Circumferential surface **126**; Electrode core assembly **13**; First electrode lead-out member **131**; Second electrode lead-out member **132**; Accommodating cavity **14**; Electrode core connector **15**; Copper connection piece **151**; Aluminum connection piece **152**; Electrolyte solution filling channel **16**; Liquid inlet **161**; Liquid outlet **162**; First channel **163**; Second channel **164**; Third channel **165**; Fourth channel **166**; Blocking member **17**; Electrolyte solution guide hole **18**; Sealing member **19**; Sealing ring **191**; Metal ball **192**; Sealing sleeve **193**; Sealing channel **20**; Pallet **50**;

(29) Battery module **200**; Battery pack **300**; and

(30) Electric vehicle **1000**.

(31) The following implementations are combined with the foregoing accompanying drawings to further describe the present disclosure.

DETAILED DESCRIPTION

(32) The following describes embodiments of the present disclosure in detail. Examples of the embodiments are shown in the accompanying drawings, and same or similar reference signs in all the accompanying drawings indicate same or similar components or components having same or similar functions. The embodiments described below with reference to the accompanying drawings are exemplary and used only for explaining the present disclosure, and should not be construed as a limitation on the present disclosure.

(33) In the description of the present disclosure, it should be understood that orientation or position relationships indicated by the terms such as “center”, “longitudinal”, “transverse”, “length”, “width”, “thickness”, “on”, “below”, “front”, “back”, “left”, “right”, “vertical”, “horizontal”, “top”, “bottom”, “inside”, “outside”, “axial direction”, “radial direction”, and “circumferential direction” are based on orientation or position relationships shown in the accompanying drawings, and are used only for ease and brevity of illustration and description, rather than indicating or implying that the disclosed apparatus or component must have a particular orientation or must be constructed and operated in a particular orientation. Therefore, such terms should not be construed as limiting of the present disclosure.

(34) In the present disclosure, unless otherwise explicitly specified or defined, the terms such as “install”, “connect”, “connection”, and “fix” should be understood in a broad sense. For example, the connection may be a fixed connection, a detachable connection, or an integral connection; or the connection may be a mechanical connection or an electrical connection; a direct connection, an indirect connection through an intermediate, or internal communication between two elements or an interaction relationship between two elements. A person of ordinary skill in the art may understand the specific meanings of the foregoing terms in the present disclosure according to specific situations.

(35) As shown in FIG. **1** and FIG. **2**, the present disclosure provides a battery **100**. The battery **100** includes a housing **11**, end covers **121**, partition plates **122**, and a number of electrode core assemblies **13**. The end covers **121** are arranged on two opposite ends of the housing **11** for sealing an internal space of the housing **11**. The partition plates **122** are spaced apart from each other in the housing **11** for dividing the internal space of the housing **11** into a number of accommodating cavities **14** successively arranged along a first direction. For example, the first direction is an X direction shown in FIG. **1**.

(36) In the present disclosure, the internal space of the housing **11** is divided into the number of

accommodating cavities **14** that are successively arranged along the first direction. The partition plates **122** may divide the housing **11** into a number of parts inside the housing **11**, so as to form the number of accommodating cavities **14**. Alternatively, the partition plates **122** are arranged in the housing **11**, and divide one space arranged in the housing **11** into the number of accommodating cavities **14**. Contents of this section are to be specifically described below.

(37) In this implementation, the battery **100** may be a lithium-ion battery. The first direction is a length direction of the battery **100**. The housing **11** is configured to enhance the strength of the battery **100** to guarantee the safe use of the battery **100**. The housing may be a plastic housing or a metal housing. When the housing is the metal housing, the housing has a desirable heat dissipation performance and a high strength, and may have a function of supporting itself.

(38) In this implementation, each electrode core assembly **13** is arranged in each accommodating cavity **14**. The electrode core assembly **13** includes at least one electrode core. The number of electrode core assemblies **13** are successively arranged along the first direction and connected in series.

(39) In this implementation, one electrode core assembly **13** is arranged in each accommodating cavity **14**. The electrode core assemblies **13** in two adjacent accommodating cavities **14** are connected in series. Therefore, the number of electrode core assemblies **13** are successively connected in series. In other implementations, the number of electrode core assemblies **13** may also be arranged side by side in the accommodating cavity **14**, for example, two or more than two electrode core assemblies.

(40) The electrode core disclosed in the present disclosure is an electrode core commonly used in the field of power batteries. The electrode core and the electrode core assemblies **13** are internal components of the housing **11** of the battery **100**, but cannot be understood as the battery **100** itself. The electrode core may be formed by winding or lamination. Generally, the electrode core includes at least a positive plate, a separator, a negative plate, and electrolyte solution. The electrode core is usually a module that is not completely sealed. Therefore, the battery **100** disclosed in the present disclosure is a single cell, which shall not be simply understood as a battery module because the battery includes a number of electrode cores. In the present disclosure, the electrode core assembly **13** may include an independent electrode core, or may include at least two electrode cores. The electrode core assembly **13** is formed after the at least two electrode cores are connected in parallel.

(41) In the present disclosure, the number of electrode core assemblies **13** are connected in series, thereby achieving a high capacity and a high voltage of the battery **100**, simplifying the manufacturing process, and reducing costs.

(42) Generally, a number of the series-connected electrode core assemblies included in the battery **100** may be determined according to an output voltage of each electrode core assembly **13**, a width of the used battery pack, and an overall voltage requirement of the battery pack. For example, for a vehicle model, a battery system is required to output a voltage of 300 V, and a voltage of a conventional lithium-iron battery is 3.2 V. Therefore, in related arts, 100 batteries are required to be connected in series in the pack to meet the requirements. In the battery pack in the present disclosure, assuming that 2 electrode core assemblies **13** are connected in series in the battery, it is only necessary to arrange 50 batteries **100**. By analogy, if 10 electrode core assemblies **13** are connected in series, it is only necessary to connect 10 batteries **100** in series. In this way, the design of the whole pack and the arrangement of cells are greatly simplified, which can effectively use the space and enhance the space utilization.

(43) In related arts, in order to realize the high capacity and the high voltage of the battery, it is generally necessary to connect two or more than two cells in series. However, power connections between end covers of respective end portions and an external power connector is required at a junction between two adjacent cells connected in series, resulting in a relatively large number of structural members of the battery, which not only increases costs, but also increases the overall weight of the power battery pack. In addition, the structural members occupy a relatively large

internal space of the battery pack, resulting in a decrease in an overall capacity of the power battery pack. In addition, a number of external power connectors need to be arranged for power connection, so that internal consumption of the power battery pack in use is increased with the increased internal resistance.

(44) Compared with related arts, in the present disclosure, the partition plates **122** are spaced apart from each other in the housing **11** to separate the number of accommodating cavities **14** side by side inside the housing **11**. The electrode core assembly **13** is arranged in each accommodating cavity **14**. The electrode core assemblies **13** in the accommodating cavities **14** are connected in series. In this way, the capacity and the voltage of the battery **100** can be effectively increased. In addition, two adjacent accommodating cavities **14** are communicated by one partition plate **122** in a sealed manner. In this way, a structural member of the battery **100** may be simplified, a spacing between the two adjacent electrode core assemblies **13** may be decreased, and internal consumption of the power battery pack is reduced. Therefore, the battery pack may have a larger internal space to accommodate cells, thereby increasing the overall capacity and the voltage of the battery pack, and improving the endurance capacity of an electric vehicle **1000** using the battery pack.

(45) In this implementation, lengths of the housing **11** and the electrode core assemblies **13** both extend along the first direction. The housing **11** is an integrated structure extending along the first direction.

(46) In the present disclosure, as shown in FIG. 1, the battery **100** is generally a cuboid. The battery **100** has a length L , a width H , and a thickness D . The length L of the battery **100** is greater than the width H , and the width H of the battery **100** is greater than the thickness D . The length of the battery **100** may range from 400 mm to 2500 mm. In the present disclosure, a ratio of the length L to the width H of the battery **100** is $L/H=4\sim 21$.

(47) It is to be noted that the battery **100** being generally a cuboid may be understood that, the battery **100** may be in a shape of a cuboid or a cube, or partially special-shaped but substantially in the shape of the cuboid or the cube, or has a notch, a protrusion, a chamfer, a camber, or a crook in part, but is in the shape similar to the cuboid or the cube as a whole.

(48) In related arts, in order to increase the volume utilization of the battery pack, a size of the battery is set to be in a range of 400 mm to 2500 mm. Since the battery is too long, the internal resistance of the battery is too high if only one electrode core is arranged. As a result, a potential difference between a positive electrode and a negative electrode is excessively large, resulting in the electrolyte solution unable to work properly. According to the technical solution of the present disclosure, the battery having the length ranging from 400 mm to 2500 mm can be manufactured conveniently, and the internal resistance and the connection between structural components can be reduced, thereby further reducing the costs.

(49) As shown in FIG. 3, the partition plate **122** includes a side surface **125** facing the adjacent electrode core assemblies **13** and a circumferential surface **126** connected with the side surface **125**. The circumferential surface **126** of the partition plate **122** is coupled with the housing **11** to divide the internal space of the housing **11** into the number of accommodating cavities **14**.

(50) In an implementation, referring to FIG. 2 again, a cavity wall of the accommodating cavity **14** among the number of accommodating cavities **14** on each of two ends of the battery **100** in the first direction includes the partition plate **122** and the end cover **121** that are arranged on the end portions of the accommodating cavity **14**, and a portion of the housing **11** arranged between the partition plate **122** and the end cover **121**. A cavity wall of the accommodating cavity **14** among the number of accommodating cavities **14** arranged in the middle of the battery **100** in the first direction includes two adjacent partition plates **122** arranged on end portions of the accommodating cavity **14** and a portion of the housing **11** arranged between the two adjacent partition plates **122**. That is to say, the partition plates **122** divide the housing **11** into a number of parts in the housing **11**, so as to form the number of accommodating cavities **14**.

(51) In the present disclosure, when the number of electrode core assemblies **13** are connected in

series, an internal short circuit may occur in a case that the electrolyte solution in different electrode core assemblies **13** are communicated with each other, and a potential difference (by using a lithium iron phosphate battery as an example, a potential difference ranges from 4.0 V to 7.6 V) among different electrode core assemblies **13** is relatively large. In this way, the electrolyte solution in the electrode core assemblies may be decomposed due to the large potential difference, which affects the performance of the battery. In order to better achieve the function of insulation, the partition plate **122** may be made of an insulation material. That is to say, the partition plates **122** are insulating partition plates. Therefore, the partition plates **122** may be directly used to isolate the two adjacent electrode core assemblies **13** to maintain the insulation between the electrode core assemblies without performing other operations. The housing **11** may be a metal housing having an insulated inner surface.

(52) In another implementation, as shown in FIG. 4, the battery **100** further includes a separator film **112** arranged in the housing **11**. The partition plates **122** are spaced apart from each other in the separator film **112**. The circumferential surfaces **126** of the partition plates **122** are coupled with the separator film **112** to divide an internal space of the separator film **112** into a number of accommodating cavities **14**. That is to say, the separator film **112** is an integrated film. The partition plates **122** are arranged in the separator film **112**, and divide a receiving space of the separator film **112** into the number of accommodating cavities **14**.

(53) In this implementation, the number of partition plates **122** are arranged in the housing **22** of the battery **100**, to divide the space in the housing **22** into the number of accommodating cavities **14** spaced apart from each other along the first direction. The cavity wall of the accommodating cavity **14** among the number of accommodating cavities **14** on each of two ends of the battery **100** in the first direction includes the partition plate **122** and the end cover **121** arranged on the end portion of the accommodating cavity **14**, and a portion of the separator film **112** arranged between the partition plate **122** and the end cover **121**. In addition, the cavity wall of the accommodating cavity **14** among the number of accommodating cavities **14** arranged in the middle of the battery **100** in the first direction includes two adjacent partition plates **122** arranged on the end portions of the accommodating cavity **14** and a portion of the separator film **112** arranged between the two adjacent partition plates **122**.

(54) In another implementation, as shown in FIG. 5, the battery **100** further includes the separator film **112** arranged inside the housing **11**. The separator film **112** includes a number of sub-separator films **1121** arranged along the first direction and in a one-to-one correspondence with the number of accommodating cavities **14**. Two opposite ends of each sub-separator film **1121** are coupled with the partition plates **122** on two ends of the corresponding accommodating cavity **14**, or the partition plates **122** are coupled with the end covers **121** to form the corresponding accommodating cavity **14**. Two adjacent accommodating cavities **14** share one partition plate **122**.

(55) In this implementation, the number of partition plates **122** are arranged in the housing **22** of the battery **100**, to divide the space in the housing **22** into the number of accommodating cavities **14** spaced apart from each other along the first direction. The cavity wall of the accommodating cavity **14** among the number of accommodating cavities **14** arranged in the middle of the battery **100** in the first direction includes the corresponding sub-separator film **1121** and two partition plates **122** arranged on end portions of the corresponding sub-separator film **1121**. The cavity wall of the accommodating cavity **14** among the number of accommodating cavities **14** arranged on each of the two ends of the battery **100** in the first direction includes the corresponding sub-separator films **1121** and the partition plate **122** and the end cover **121** that are arranged on the end portions of the corresponding sub-separator film **1121**.

(56) The number of sub-separator films **1121** are a number of independent parts separated from each other. That is to say, the separator film **112** is a separated-type separator film. Each sub-separator film **1121** is a cylindrical structure having two open ends. The electrode core assemblies **13** are arranged inside the cylindrical sub-separator film **1121**. The partition plates **122** or the end

covers **121** seal the open ends of the corresponding separator film **112**.

(57) In the present disclosure, a manner in which the separator film **112** is sealed to the partition plates **122** or the end covers **121** and a specific structure are not specially limited. For example, when the partition plate **122** or the end cover **121** is made of a plastic material, and the separator film **112** is made of plastic, the separator film **112** may be sealed to the partition plates **122** or the end covers **121** by hot melting.

(58) In the present disclosure, the number of electrode core assemblies **13** are connected in series. Different voltages among different electrode core assemblies **13** may cause an excessively low local potential of the housing such as an aluminum housing. At this point, lithium ions may be easily embedded in the housing to form an aluminum-lithium alloy and corrode the aluminum housing. In the present disclosure, the separator film **112** is arranged between the housing **11** and the electrode core assembly **13**, so as to effectively prevent contact between the electrolyte solution and the housing **11**.

(59) The separator film **112** has a certain insulating property and a resistance to electrolyte solution corrosion. A material of the separator film **112** is not specially limited, as long as the material has the insulating property and does not react with the electrolyte solution. In some embodiments, the material of the separator film **112** may include polypropylene (PP), polyethylene (PE), or a multilayer composite film. For example, in some embodiments, the multilayer composite film includes an inner layer, an outer layer, and a middle layer between the inner layer and the outer layer. The inner layer includes the plastic material. For example, the inner layer may be made of a material that is less reactive with the electrolyte solution in the separator film **112** and has the insulating property, for example, PP or PE. The middle layer includes a metal material, so as to prevent permeation of water vapor outside the battery **100** and also prevent the leakage of the electrolyte solution inside the battery. An aluminum foil, a stainless steel foil, a copper foil, and the like are preferably used as the metal layer. The outer layer is a protective layer, which is usually made of polyester having a high melting point or a nylon material, and has a strong mechanical property. In this way, an external force is prevented from damaging the battery **100**, thereby protecting the battery **100**. In some implementations, the separator film **112** further has a certain flexibility, which facilitates the molding and machining of the battery **100** and prevents the battery from being pierced.

(60) In the present disclosure, in order to fill the electrolyte solution into the accommodating cavities **14** where the electrode core assemblies **13** are arranged, as shown in FIG. **3**, the partition plate **122** is provided with an electrolyte solution filling channel **16**. The electrolyte solution filling channel **16** is in communication with the accommodating cavity **14** on at least one side of the partition plate **122**, and is configured for filling the electrolyte solution into the accommodating cavity **14** from an outside of the battery **100**. The electrolyte solution filling channel **16** is in a closed state upon completion of the electrolyte solution filling, to prevent communication between the accommodating cavity **14** and the outside of the battery **100**. It may be understood that the electrolyte solution filling channel **16** may also be provided on the end cover for the communication with the accommodating cavity **14** on one side of the end cover **121** according to actual conditions.

(61) Two ends of the electrolyte solution filling channel **16** are respectively formed as a liquid inlet **161** and a liquid outlet **162**. The liquid inlet **161** is arranged on the circumferential surface **126** of the partition plate **122** where the liquid inlet is arranged. The liquid outlet **162** is arranged on the side surface **125** of the partition plate **122** where the liquid outlet is arranged. The electrolyte solution is filled into the electrolyte solution filling channel **16** through the liquid inlet **161**, and filled into the accommodating cavity **14** through the liquid outlet **162**.

(62) In the present disclosure, a shape of the electrolyte solution filling channel **16** may be flexibly configured. For example, the electrolyte solution filling channel may be an arcuate or curved cylindrical channel, or may be an L-shaped channel.

(63) Referring to FIG. 1 and FIG. 3 again, in this implementation, a through hole **111** is provided at a position of the housing **11** corresponding to the electrolyte solution filling channel **16** on the partition plate **122**. The through hole **111** is configured to communicate the electrolyte solution filling channel **16** with the outside of the battery **100**.

(64) It may be understood that, when the integrated separator film **112** is arranged in the housing **11**, as shown in FIG. 4, a through hole **1122** is also provided at a position of the separator film **112** corresponding to the electrolyte solution filling channel **16** on the partition plate **122**. The through hole **1122** is configured to communicate the electrolyte solution filling channel **16** with the outside of the battery **100**.

(65) In the present disclosure, the through holes are provided on the housing **11** of the battery **100** or at the positions of the housing **11** and the separator film **112** corresponding to the electrolyte solution filling channel **16** on the partition plate **122**. In this way, the electrolyte solution may be filled into each individual accommodating cavity **14** after the battery **100** is assembled. Therefore, the problem such as the electrolyte solution filling of the battery including the number of electrode core assemblies connected in series is effectively resolved.

(66) It may be understood that, after the electrolyte solution is filled into the accommodating cavity **14**, the electrolyte solution filling channel **16** is required to be sealed. In an implementation, as shown in FIG. 3, the battery **100** further includes a blocking member **17**. The blocking member **17** is configured to seal the electrolyte solution filling channel **16** upon completion of the electrolyte solution filling. At least part of the blocking member **17** may be arranged in the electrolyte solution filling channel **16**.

(67) In another implementation, a protrusion may protrude outward from the partition plate **122** and is made of plastic. The liquid inlet **161** is arranged on the protrusion. The liquid inlet **161** is sealed by hot melting upon completion of the electrolyte solution filling.

(68) In the present disclosure, two adjacent housings **11** are sealed to each other by using the partition plate **122**. The electrolyte solution filling channel **16** is provided on the partition plate **122**. In this way, once the electrolyte solution in one of the accommodating cavities **14** leaks, other accommodating cavities **14** remain intact. Therefore, the safety problem caused by the leakage of the electrolyte solution will not occur. Upon completion of the electrolyte solution filling, the electrolyte solution filling channel **16** on the partition plate **122** of the cavity wall of the accommodating cavity **14** is in a sealed state. Therefore, on the one hand, the electrolyte solution in the accommodating cavity **14** does not flow out from the accommodating cavity **14** to contact with the housing **11** to cause an internal short circuit. On the other hand, the electrolyte solution does not flow between adjacent accommodating cavities **14**, which does not affect each other, and is not decomposed due to the excessively large potential difference, thereby ensuring the safety and the service life of the battery **100**.

(69) In the field of power batteries, the consistency of working conditions of cells is very important, which directly affects the performance of the entire battery pack. Similarly, the consistency of working conditions of the electrode core assemblies in the battery will also affect the overall performance of each cell, and affect the performance of the entire battery pack. However, an amount of the electrolyte solution inside the battery will affect the performance of the battery, such as a capacity, an activity, and the like. In the present disclosure, when it is ensured that the electrolyte solution can timely and effectively infiltrate the electrode core assemblies, providing the electrolyte solution filling channel **16** on the partition plate **122** may optimize the forming process of the battery **100**.

(70) With regard to a manner in which the electrolyte solution filling channel **16** is arranged, in an implementation, as shown in FIG. 3, one electrolyte solution filling channel **16** may be communicated with the accommodating cavity **14**.

(71) It is to be noted that, when the electrolyte solution filling channel **16** is only communicated with one accommodating cavity **14**, the electrolyte solution filling channel **16** is to be provided on

each partition plate **122**. By forming openings and filling the electrolyte solution a number of times, each accommodating cavity **14** accommodating the electrode core assembly **13** can have an individual channel for filling the electrolyte solution. In this way, a shortest electrolyte solution filling path may be achieved, and the electrolyte solution can timely flow to the corresponding accommodating cavity **14** through the electrolyte solution filling channel **16**, thereby ensuring that the electrolyte solution can timely and effectively infiltrate the electrode core assembly **13**. In addition, a content of the electrolyte solution in each accommodating cavity **14** may be accurately controlled by arranging a number of electrolyte solution filling channels **16**, so as to ensure the consistency of the electrolyte solution in the number of accommodating cavities **14**.

(72) In another implementation, as shown in FIG. **6**, the electrolyte solution filling channel **16** may be simultaneously communicated with the two adjacent accommodating cavities **14**.

(73) The electrolyte solution filling channel **16** includes a first channel **163** and a second channel **164**. The first channel **163** extends through the partition plate **122** where the first channel is arranged, and is configured to communicate the two adjacent accommodating cavities **14** on two sides of the partition plate **122**. The second channel **164** is configured to communicate the first channel **163** with the outside of the battery **100**. That is to say, the circumferential surface **126** of the partition plate **122** is provided with one liquid inlet **161**. The liquid outlet **162** is provided on both side surfaces **125** of the partition plate **122**.

(74) The battery **100** further includes a blocking member **17**. The blocking member **17** is configured to seal the second channel **164** upon completion of filling the electrolyte solution, to block communication between the second channel **164** and the outside. The blocking member **17** is further configured to block at least partial area of the first channel **163**, to block the communication between the two adjacent accommodating cavities **14** through the first channel **163**.

(75) It is to be noted that, when the accommodating cavities **14** on two sides of the partition plate **122** are simultaneously communicated through the electrolyte solution filling channel **16** on the partition plate **122**, it is not necessary to provide the electrolyte solution filling channel **16** on each partition plate **122**. The electrolyte solution filling channel **16** may be provided every other partition plate **122**.

(76) In this implementation, since the accommodating cavities **14** on the two sides of the partition plate **122** are at a relatively small distance from each other, the electrolyte solution may be simultaneously filled into the adjacent accommodating cavities **14** on the two sides of the partition plate **122** through the electrolyte solution filling channel **16** on the partition plate **122**. Due to a relatively short infiltration path of the electrolyte solution, the electrolyte solution may still timely and effectively infiltrate the electrode core assemblies **13** on two sides.

(77) In another implementation, a number of the electrolyte solution filling channels **16** on each partition plate **122** may be 1 or more.

(78) For example, as shown in FIG. **7**, the electrolyte solution filling channel **16** includes a third channel **165** and a fourth channel **166** independent of each other. That is to say, two electrolyte solution filling channels **16** are provided on the partition plate **122**. The third channel **165** is in communication with the accommodating cavity **14** on one side of the partition plate **122** where the third channel is arranged. The fourth channel **166** is in communication with the accommodating cavity **14** on another side of the partition plate **122** where the fourth channel is arranged.

(79) In another implementation, each partition plate **122** is provided with the electrolyte solution filling channel **16**. In this way, each accommodating cavity **14** corresponds to one electrolyte solution filling channel **16**. Therefore, the amount of the electrolyte solution filled into each accommodating cavity **14** can be accurately controlled, thereby ensuring the consistency of the electrolyte solution.

(80) In an implementation, as shown in FIG. **8**, at least one partition plate **122** is provided with an electrolyte solution guide hole **18**. The electrolyte solution guide hole **18** is configured to communicate the two adjacent accommodating cavities **14** on the two sides of the partition plate

122 where the electrolyte solution guide hole is arranged. The electrolyte solution guide hole **18** extends through two opposite side surfaces **125** of the partition plate **122**.

(81) In some implementations, the electrolyte solution filling channel **16** and the electrolyte solution guide hole **18** are provided on different partition plates **122**. One of the two adjacent partition plates **122** is provided with the electrolyte solution filling channel **16**, and another one of the partition plates **122** is provided with the electrolyte solution guide hole **18**.

(82) In some implementations, the electrolyte solution filling channel **16** and the electrolyte solution guide hole **18** are provided on different partition plates **122**. A portion of the number of partition plates **122** is provided with the electrolyte solution filling channel **16**. The electrolyte solution filling channel **16** is in communication with the two adjacent accommodating cavities **14** on the two sides of the partition plate **122** where the electrolyte solution filling channel is arranged. Another portion of the partition plates **122** is provided with the electrolyte solution guide hole **18**.

(83) In some implementations, a portion of the number of partition plates **122** is provided with both the electrolyte solution filling channel **16** and the electrolyte solution guide hole **18** in communication with the electrolyte solution filling channel **16**, and another portion of the partition plates **122** is provided with the electrolyte solution guide hole **18**.

(84) In an implementation, as shown in FIG. **9**, the battery **100** further includes a sealing member **19**. The sealing member **19** can block the electrolyte solution guide hole **18** upon completion of filling the electrolyte solution of the battery **100**, to cause the electrolyte solution guide hole **18** to be in a closed state, so as to block the communication between the two adjacent accommodating cavities **14** through the electrolyte solution guide hole **18**. That is to say, upon completion of filling the electrolyte solution, the sealing member **19** seals the electrolyte solution guide hole **18** to isolate the two adjacent accommodating cavities **14**. In this way, the electrolyte solution does not flow between the adjacent accommodating cavities **14**, so as not to affect each other, and the electrolyte solution is not decomposed due to the excessively large potential difference, thereby ensuring the safety and the service life of the battery **100**.

(85) In an implementation, as shown in FIG. **9** and FIG. **10**, the circumferential surface **126** of the partition plate **122** is further provided with a sealing channel **20** communicated with the electrolyte solution guide hole **18** and extending through the electrolyte solution guide hole **18**. The sealing member **19** can block the electrolyte solution guide hole **18** under the action of an external force.

(86) In some implementations, the sealing member **19** is a sealing plug, and a shape of the sealing channel **20** is coupled with a shape of the sealing plug.

(87) As shown in FIG. **9** and FIG. **10**, the sealing member **19** is a cuboid structure. In an embodiment, the sealing member **19** may also be a cylindrical structure or a cylindrical structure having an elliptical cross-section. The shape of the sealing channel **20** may be flexibly configured according to the shape of the sealing member **19**.

(88) In an embodiment, as shown in FIG. **11**, FIG. **12**, and FIG. **13**, the sealing member **19** is a wedge-shaped block structure.

(89) In an embodiment, as shown in FIG. **14**, FIG. **15**, and FIG. **16**, an inner wall of the sealing channel **20** is provided with threads. The sealing member **19** is a cylinder or a screw having a threaded surface.

(90) In an embodiment, as shown in FIG. **17**, FIG. **18**, and FIG. **19**, the sealing member **19** is a columnar structure, and an elastic sealing ring **191** is sleeved on a position corresponding to the electrolyte solution guide hole **18** in a sealed state.

(91) In some implementations, as shown in FIG. **20**, the sealing member **19** is a sealing ball, and includes a metal ball **192** and a sealing sleeve **193** wrapped around an outer surface of the metal ball. The sealing ball is arranged in the sealing channel **20** by means of interference fit.

(92) In some implementations, before the electrolyte solution filling, during the electrolyte solution filling, or during formation of the battery **100** after the electrolyte solution filling, the sealing member **19** is in a first situation, and the electrolyte solution guide hole **18** is in an open state to

communicate the two adjacent accommodating cavities **14** on two sides of the partition plate **122** where the electrolyte solution guide hole is arranged. After the electrolyte solution filling or during formation of the battery **100** after the electrolyte solution filling, the sealing member **19** is switched from the first situation to a second situation. The sealing member **19** blocks the electrolyte solution guide hole **18** to cause the electrolyte solution guide hole **18** to be in the closed state, so as to block the communication between the two adjacent accommodating cavities **14** through the electrolyte solution guide hole **18**. The sealing member **19** is switchable between the first situation and the second situation.

(93) A first position and a second position are formed in the sealing channel **20**. The sealing member **19** is movable between the first position and the second position by the external force. The first situation is that the sealing member **19** is arranged at the first position. The second situation is that the sealing member **19** is arranged at the second position. The external force is selected from one or more of gravity, an electromagnetic force, an inertial force, or a thermal force.

(94) Referring to FIG. 2 and FIG. 3 again, in the present disclosure, each electrode core assembly **13** includes a first electrode lead-out member **131** and a second electrode lead-out member **132** that are configured to lead out currents. In this implementation, the first electrode lead-out member **131** and the second electrode lead-out member **132** are respectively arranged on two opposite sides of the electrode core assembly **13** along the first direction.

(95) According to the present disclosure, all of the housings **11** and all of the electrode core assemblies **13** are arranged along the first direction, and the first electrode lead-out member **131** and the second electrode lead-out member **132** of the electrode core assembly **13** are respectively arranged on the two opposite sides of the electrode core assembly **13** along the first direction. That is to say, a “head to head” arrangement mode is adopted between the electrode core assemblies **13**. The arrangement mode can conveniently realize series connection between the two adjacent electrode core assemblies **13** in the battery **100**, and the connection structure is simple. In addition, the battery **100** having a relatively large length may be conveniently manufactured by using the arrangement mode.

(96) Generally, each electrode core assembly **13** includes a first electrode lead-out member **131** and a second electrode lead-out member **132** that are configured to lead out currents. If the electrode core assembly **13** includes only one electrode core, the first electrode lead-out member **131** and the second electrode lead-out member **132** may be respectively a positive tab and a negative tab of the electrode core, or respectively the negative tab and the positive tab. If the electrode core assembly **13** includes a number of electrode cores, the first electrode lead-out member may be a lead-out member formed by combining and soldering the positive tabs. The second electrode lead-out member may be a lead-out member formed by combining and soldering the negative tabs. Alternatively, the first electrode lead-out member may be a lead-out member formed by combining and soldering the negative tabs. The second electrode lead-out member may be a lead-out member formed by combining and soldering the positive tabs. “First” and “second” in the first electrode lead-out member **131** and the second electrode lead-out member **132** are merely used for name distinction, and not for limiting numbers. For example, there may be one or more first electrode lead-out members.

(97) The series connection mode provided in this implementation may be series connection between the adjacent electrode core assemblies **13**. An implementation may be that current lead-out members on the adjacent electrode core assemblies **13** are directly connected or may be electrically connected by using an extra conductive component. That is to say, the electrode core assemblies **13** in the two adjacent accommodating cavities **14** may be directly or indirectly electrically connected.

(98) In an implementation, the battery **100** further includes an electrode core connector **15**. The electrode core connector **15** extends through the partition plate **122**. For example, a through connecting hole **123** is provided on the partition plate **122**. The electrode core connector **15** extends through the through connecting hole **123**. That is to say, the electrode core connector **15** penetrates

from one side to another side of the through connecting hole **123**.

(99) In an implementation, the first electrode lead-out member **131** of one of the electrode core assemblies **13** in the two adjacent accommodating cavities **14** is electrically connected with the second electrode lead-out member **132** of another one of the electrode core assemblies **13** by using the electrode core connector **15**. That is to say, the electrode core assemblies **13** in the two adjacent accommodating cavities **14** are indirectly connected.

(100) In an implementation, the two adjacent electrode core assemblies **13** are connected by the electrode core connector **15**, so as to provide a larger design space for the electrode core connector **15**, increase a flow area, and reduce the internal resistance of the battery **100**.

(101) In some implementations, the electrode core connector **15** may be a sheet structure. In some implementations, the electrode core connector **15** may be a columnar structure.

(102) The first electrode lead-out member **131** and the second electrode lead-out member **132** may be directly soldered to the electrode core connector **15** in the corresponding partition plate **122**. Compared with the series connection between the existing cells, soldering procedures and steps are simplified, the risk caused by poor soldering is reduced, and the overall safety and reliability of the battery are enhanced.

(103) As shown in FIG. 3, the electrode core connector **15** includes a copper connection piece **151** and an aluminum connection piece **152** that are electrically connected with each other. Since a difference exists between a potential of copper and a potential of lithium and between a potential of aluminum and the potential of lithium, corrosion easily occurs if a junction of the copper connection piece **151** and the aluminum connection piece **152** are in contact with the electrolyte solution. In an implementation, a position where the copper connection piece **151** is electrically connected with the aluminum connection piece **152** is arranged inside the partition plate **122**.

(104) In order to prevent, from being corroded by the electrolyte solution, the position where the copper connection piece **151** is electrically connected with the aluminum connection piece **152**, and in order to isolate the accommodating cavities **14** on two sides of the partition plate **122** to block interpenetration of the electrolyte solution in the accommodating cavities **14** on the two sides of the partition plate **122**, in some embodiments, as shown in FIG. 7, the battery **100** further includes a packaging structure **124** arranged in the through connecting hole **123**. The packaging structure **124** is configured to package the electrode core connector **15** in the through connecting hole **123**. In addition, the packaging structure **124** can seal the through connecting hole **123**. In this way, a position where the copper connection piece **151** is in contact with the aluminum connection piece **152** is sealed inside the partition plate **122**, to prevent the position from being exposed to an internal space of the battery **100**, especially prevent the position from being in contact with the electrolyte solution, so as to prevent, from being corroded, the position where the copper connection piece is connected with the aluminum connection piece.

(105) In the present disclosure, the packaging structure **124** is only required to have the sealing function, be resistant to electrolyte solution corrosion, and be insulated. For example, the packaging structure may be a rubber stopper.

(106) In the mounting solution using the electrode core connector **15** provided in the above embodiments, a second packaging is required to be performed on the through connecting hole **123**, which is not convenient to operate. In addition, during the second packaging, selected materials used for the packaging structure **124** are complex, and may affect the electrolyte solution inside the battery **100**. In view of this, in another embodiment, as shown in FIG. 3 and FIG. 6, a solution of integrally forming the electrode core connector **15** and the partition plate **122** by means of injection molding is provided. In the solution, the electrode core connector **15** and the partition plate **122** are integrally formed by means of the injection molding. The electrode core connector **15** is first manufactured, and then the partition plate **122** is formed outside the electrode core connector **15** by means of the injection molding. In order to better achieve a sealing effect of the partition plate **122**, during the integral injection molding, a section where plastic is in contact with metal is formed by

using an EPI molding technology. For example, a nano-plastic layer is sintered with a metal surface, such as PPE, PPS, and the like, and then integral injection molding is performed on a plastic member. By using the method, the metal layer and the plastic layer can be bonded together more effectively, thereby improving the sealing performance of the entire structural component. During the assembly, the electrode core assembly **13** and the electrode core connector **15** are directly connected without needing to seal through holes, thereby reducing the risk while simplifying the process.

(107) In yet another implementation, the first electrode lead-out member **131** of one of the electrode core assemblies **13** in the two adjacent accommodating cavities **14** may be electrically connected with the second electrode lead-out member **132** of another one of the electrode core assemblies **13**. The junction of the first electrode lead-out member **131** and the second electrode lead-out member is arranged in the partition plate **122** between the two electrode core assemblies **13**. That is to say, the first electrode lead-out member **131** and the second electrode lead-out member **132** are directly electrically connected. The junction of the first electrode lead-out member **131** and the second electrode lead-out member **132** is a position where the first electrode lead-out member **131** and the second electrode lead-out member **132** are connected with each other.

(108) Similar to the foregoing implementation, in order to facilitate the electrical connection between the first electrode lead-out member **131** and the second electrode lead-out member **132**, the through connecting hole is provided on the partition plate **122**. The junction of the first electrode lead-out member **131** and the second electrode lead-out member **132** is arranged in the through connecting hole of the partition plate **122** between the two electrode core assemblies **13**.

(109) In order to block interpenetration of the electrolyte solution in the accommodating cavities **14** of the electrode core assemblies **13** on the two sides of the partition plate **122**, the battery **100** further includes the packaging structure arranged in the through connecting hole. The packaging structure is configured to package the junction in the through connecting hole, and seals the through connecting hole. In this way, the first electrode lead-out member and the second electrode lead-out member are sealed to the partition plate **122**, to prevent movement of the electrolyte solution in the two adjacent electrode core assemblies **13** on the two sides of the partition plate **122**.

(110) In this implementation, since the two adjacent housings **11** share one partition plate **122**, a spacing between the two electrode core assemblies **13** is greatly reduced. Compared with the connection between two batteries **100** and an external power connector by using the first electrode lead-out member **131** and the second electrode lead-out member **132** in related arts, the subsequent assembling process of the battery pack is simplified. In addition, the material usage is reduced, and the weight is reduced.

(111) In the present disclosure, the battery **100** may further include other structures, such as an explosion-proof valve, a current interrupt device, and the like. For the other structures, reference may be made to general settings in related arts, and the details are not described herein again.

(112) As shown in FIG. **23**, the present disclosure further provides a battery module. The battery module includes the battery **100** according to any of the above embodiments. By using the battery module provided in the present disclosure, fewer assembling processes are required, and costs are relatively low.

(113) As shown in FIG. **21** and FIG. **22**, the present disclosure further provides a battery pack **300**, including a pallet **50** and the battery **100** or the battery module **200** according to any of the above embodiments. The battery **100** or the battery module **200** is arranged inside the pallet **50**. By using the battery pack provided in the present disclosure, fewer assembling processes are required, costs are relatively low, and energy density is high. As shown in FIG. **24** and FIG. **26**, the present disclosure further provides an electric vehicle **1000** using the above battery pack as a power source, including the battery **100**, the battery module **200**, or the battery pack **300**. The electric vehicle **1000** can have a high endurance capacity and relatively low costs by using the battery pack **300** provided in the present disclosure.

(114) In the description of the present disclosure, it should be noted that unless otherwise explicitly specified or defined, the terms such as “mount”, “install”, “connect”, and “connection” should be understood in a broad sense. For example, the connection may be a fixed connection, a detachable connection, or an integral connection; or the connection may be a mechanical connection or an electrical connection; or the connection may be a direct connection, an indirect connection through an intermediary, or internal communication between two components. A person of ordinary skill in the art may understand the specific meanings of the foregoing terms in the present disclosure according to specific situations.

(115) In description of this specification, description of reference terms such as “an embodiment”, “specific embodiments”, or “an example”, means including specific features, structures, materials, or features described in the embodiment or example in at least one embodiment or example of the present disclosure. In this specification, schematic descriptions of the foregoing terms do not necessarily point at a same embodiment or example. In addition, the described specific features, structures, materials, or characteristics may be combined in a proper manner in any one or more of the embodiments or examples.

(116) The embodiments of the present disclosure have been shown and described. Persons of ordinary skill in the art should understand that various changes, modifications, replacements and variations may be made to the embodiments without departing from the principles and spirit of the present disclosure, and the scope of the present disclosure is as defined by the appended claims and their equivalents.

Claims

1. A battery, comprising a housing, at least one end cover, partition plates, and a plurality of electrode core assemblies; wherein the at least one end cover is arranged on at least one of two opposite ends of the housing for sealing an internal space of the housing; the partition plates are spaced apart from each other in the housing for dividing the internal space of the housing into a plurality of accommodating cavities arranged along a first direction; each of the electrode core assemblies is arranged in one of the accommodating cavities; and the plurality of electrode core assemblies are arranged along the first direction and connected in series; each of the partition plates comprises an electrolyte solution filling channel; the electrolyte solution filling channel is in communication with an accommodating cavity of the accommodating cavities on at least one side of the partition plate, and is configured for filling electrolyte solution into the accommodating cavity from an outside of the battery; the electrolyte solution filling channel is in a closed state upon completion of filling the electrolyte solution to prevent communication between the accommodating cavity and the outside of the battery; a through hole is provided at a position of the housing corresponding to the electrolyte solution filling channel on the partition plate; and the through hole of the housing is configured to communicate the electrolyte solution filling channel with the outside of the battery.

2. The battery according to claim 1, wherein the housing is an integrated structure extending along the first direction; each of the partition plates comprises side surfaces facing adjacent electrode core assemblies and circumferential surfaces connected with the side surfaces; the circumferential surfaces of each of the partition plates are coupled with an interior surface of the housing to divide the internal space of the housing into the plurality of accommodating cavities; the at least one end cover comprises two end covers; an accommodating cavity among the plurality of accommodating cavities arranged in the middle of the battery in the first direction are surrounded by two adjacent partition plates and a portion of the housing arranged between the two adjacent partition plates; and an accommodating cavity among the plurality of accommodating cavities arranged on each of two ends of the battery in the first direction are surrounded by a partition plate and one of the two end covers and a portion of the housing arranged between the partition plate and the one of the two end

covers.

3. The battery according to claim 1 or 2, wherein the housing is an integrated structure extending along the first direction; each of the partition plates comprises side surfaces facing adjacent electrode core assemblies and circumferential surfaces connected with the side surfaces; the battery further comprises a separator film arranged in the housing; the partition plates are spaced apart from each other in a space formed by the separator film; the circumferential surfaces of the partition plates are coupled with the separator film to divide an internal space of the separator film into the plurality of accommodating cavities; the at least one end cover comprises two end covers; an accommodating cavity among the plurality of accommodating cavities arranged in the middle of the battery in the first direction are surrounded by two adjacent partition plates and a portion of the separator film arranged between the two adjacent partition plates; and an accommodating cavity among the plurality of accommodating cavities arranged on each of two ends of the battery in the first direction are surrounded by a partition plate and one of the two end covers and a portion of the separator film arranged between the partition plate and the one of the two end covers; the separator film comprises a through hole at a position corresponding to an electrolyte solution filling channel on one of the partition plates; and the through hole of the separator film is configured to communicate the electrolyte solution filling channel with the outside of the battery.

4. The battery according to claim 1, wherein the housing is an integrated structure extending along the first direction; the battery further comprises a separator film arranged in the housing; the at least one end cover comprises two end covers; the separator film comprises a plurality of sub-separator films arranged along the first direction and in a one-to-one correspondence with the plurality of accommodating cavities; two opposite ends of each of the sub-separator films are coupled with partition plates on two ends of a corresponding accommodating cavity, or one of the partition plates is coupled with one of the two end covers to form a corresponding accommodating cavity; and two adjacent accommodating cavities share one of the partition plates; an accommodating cavity among the plurality of accommodating cavities arranged in the middle of the battery in the first direction are surrounded by a corresponding sub-separator film and two partition plates arranged on end portions of the corresponding sub-separator film; and an accommodating cavity among the plurality of accommodating cavities arranged on each of two ends of the battery in the first direction are surrounded by a corresponding sub-separator film, a partition plate, and one of the two end covers that are arranged on the end portions of the corresponding sub-separator film.

5. The battery according to claim 1, wherein the electrolyte solution filling channel comprises a first channel and a second channel; the first channel extends through the partition plate where the first channel is arranged, and is configured to communicate two adjacent accommodating cavities on two sides of the partition plate; and the second channel is configured to communicate the first channel with the outside of the battery.

6. The battery according to claim 5, further comprising a blocking member, wherein the blocking member is configured to seal the second channel upon completion of filling the electrolyte solution, to block communication between the second channel and the outside of the battery.

7. The battery according to claim 5, further comprising a blocking member, wherein the blocking member is configured to block at least a part of the first channel, to block the communication between the two adjacent accommodating cavities.

8. The battery according to claim 1, wherein the electrolyte solution filling channel comprises a third channel and a fourth channel that are independent from each other; the third channel is in communication with an accommodating cavity on a first side of a partition plate where the third channel is arranged; and the fourth channel is in communication with an accommodating cavity on a second side of the partition plate where the fourth channel is arranged.

9. The battery according to claim 1, wherein at least one of the partition plates is provided with an electrolyte solution guide hole; and the electrolyte solution guide hole is configured to communicate two adjacent accommodating cavities on two sides of the partition plate where the

electrolyte solution guide hole is arranged.

10. The battery according to claim 9, wherein the electrolyte solution filling channel and the electrolyte solution guide hole are provided on different partition plates; one of two adjacent partition plates is provided with the electrolyte solution filling channel; and another one of the two adjacent partition plates is provided with the electrolyte solution guide hole; or the electrolyte solution filling channel and the electrolyte solution guide hole are provided on different partition plates; each of a first group of the partition plates is provided with the electrolyte solution filling channel; the electrolyte solution filling channel is in communication with the two adjacent accommodating cavities on two sides of a partition plate where the electrolyte solution filling channel is arranged; and each of a second group of the partition plates is provided with the electrolyte solution guide hole, and the first group is different than the second group; or each of a first group of the partition plates is provided with the electrolyte solution filling channel and a first electrolyte solution guide hole is in communication with the electrolyte solution filling channel; and each of a second group of the partition plates is provided with a second electrolyte solution guide hole, and the first group is different than the second group.

11. The battery according to claim 1, wherein the electrolyte solution filling channel comprises a liquid inlet and a liquid outlet at two ends of the electrolyte solution filling channel, respectively; the electrolyte solution is filled into the electrolyte solution filling channel through the liquid inlet, and is filled into a corresponding accommodating cavity communicated with the electrolyte solution filling channel through the liquid outlet; and a protrusion protrudes outward from the partition plate where the electrolyte solution filling channel is arranged on; and the liquid inlet is arranged on the protrusion.

12. The battery according to claim 9, further comprising a sealing member, wherein the sealing member is configured to cause the electrolyte solution guide hole to be in a closed state upon completion of filling the electrolyte solution, to block the communication between the two adjacent accommodating cavities through the electrolyte solution guide hole.

13. The battery according to claim 12, wherein each of the partition plates comprises side surfaces facing adjacent electrode core assemblies and circumferential surfaces connected with the side surfaces; the electrolyte solution guide hole extends through two opposite side surfaces of the partition plate; and at least one of the circumferential surfaces of the partition plate is further provided with a sealing channel communicated with the electrolyte solution guide hole and extending through the electrolyte solution guide hole; and the sealing member is configured to enter the electrolyte solution guide hole through the sealing channel, to block the electrolyte solution guide hole.

14. The battery according to claim 13, wherein the sealing member comprises a sealing plug; and a shape of the sealing channel matches a shape of the sealing plug.

15. The battery according to claim 14, wherein the sealing member is a cuboid structure, a cylindrical structure, a cylindrical structure having an elliptical cross-section, or a wedge-shaped block structure; or an inner wall of the sealing channel is provided with threads; and the sealing plug is a cylinder or a screw having a threaded surface; or the sealing member is a columnar structure; and an elastic sealing ring is sleeved on a position of the sealing member corresponding to the electrolyte solution guide hole.

16. The battery according to claim 13, wherein the sealing member comprises a sealing ball, and the sealing ball comprises a metal ball and a sealing sleeve wrapped around an outer surface of the metal ball.

17. The battery according to claim 12, wherein before filling the electrolyte solution, during filling the electrolyte solution, or during formation of the battery after filling the electrolyte solution, the electrolyte solution guide hole is in an open state to communicate the two adjacent accommodating cavities on two sides of the partition plate where the electrolyte solution guide hole is arranged; after filling the electrolyte solution, the sealing member blocks the electrolyte solution guide hole

to cause the electrolyte solution guide hole to be in the closed state, to block the communication between the two adjacent accommodating cavities through the electrolyte solution guide hole.

18. The battery according to claim 13, wherein the sealing member is movable between a first position and a second position in the sealing channel.

19. A battery pack, comprising the battery according to claim 1.

20. An electric vehicle, comprising the battery according to claim 1.
