

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414829
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Lambrecht; Bram Gilbert Antoon et al.

Instrument release

Abstract

A medical instrument includes a backend and a pair of release elements. The backend includes a docking feature shaped to engage a docking structure such as a docking port of a surgical robot or a sterile adaptor for a surgical robot. Each release element is coupled to the backend and may include an activation feature on one side of the backend and a push tab extending from either an opposite side or the same side of the backend. Movement of the activation features moves the push tabs from being aligned with the docking feature to pushing on the docking structure, permitting the medical instrument to be disengaged from the docking structure. Optionally, a coupling of the release elements limits a movement of the activation features.

Inventors: Lambrecht; Bram Gilbert Antoon (Redwood City, CA), Holop; Robert E. (Santa Clara, CA)

Applicant: Intuitive Surgical Operations, Inc. (Sunnyvale, CA)

Family ID: 1000008819341

Assignee: Intuitive Surgical Operations, Inc. (Sunnyvale, CA)

Appl. No.: 18/531880

Filed: December 07, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240156555 A1	May. 16, 2024

Related U.S. Application Data

continuation parent-doc US 16317243 US 11890070 WO PCT/US2017/024687 20170329 child-doc US 18531880
us-provisional-application US 62362454 20160714

Publication Classification

Int. Cl.: **A61B34/35** (20160101); **A61B34/30** (20160101); **A61B46/10** (20160101); **A61B90/57** (20160101); A61B17/00 (20060101)

U.S. Cl.:

CPC **A61B34/35** (20160201); **A61B34/30** (20160201); **A61B46/10** (20160201); **A61B90/57** (20160201); A61B2017/00477 (20130101); Y10T403/59 (20150115); Y10T403/595 (20150115)

Field of Classification Search

CPC: A61B (2017/00477); A61B (34/30); A61B (46/10); Y10T (403/59); Y10T (403/595)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
793510	12/1904	Cramer et al.	N/A	N/A
4117359	12/1977	Wehde	N/A	N/A
4259876	12/1980	Belyanin et al.	N/A	N/A
4281447	12/1980	Miller et al.	N/A	N/A
4283165	12/1980	Vertut	N/A	N/A
4341144	12/1981	Milne	N/A	N/A
4696524	12/1986	Cloyd	N/A	N/A
4899608	12/1989	Knappe et al.	N/A	N/A
5441042	12/1994	Putman	N/A	N/A
5674024	12/1996	Daumal et al.	N/A	N/A
5792135	12/1997	Madhani et al.	N/A	N/A
6007550	12/1998	Wang et al.	N/A	N/A
6331181	12/2000	Tierney et al.	N/A	N/A
6371952	12/2001	Madhani et al.	N/A	N/A
6394998	12/2001	Wallace et al.	N/A	N/A
6459926	12/2001	Nowlin et al.	N/A	N/A
6494662	12/2001	De Montalembert	N/A	N/A
6817974	12/2003	Cooper et al.	N/A	N/A
6994708	12/2005	Manzo	N/A	N/A
7261726	12/2006	Jinno et al.	N/A	N/A
7331967	12/2007	Lee et al.	N/A	N/A
7524320	12/2008	Tierney et al.	N/A	N/A
7666191	12/2009	Orban, III et al.	N/A	N/A
7699855	12/2009	Anderson	N/A	N/A
7727244	12/2009	Orban, III et al.	N/A	N/A
7823330	12/2009	Ostrowski et al.	N/A	N/A
7886743	12/2010	Cooper et al.	N/A	N/A
7935130	12/2010	Williams	N/A	N/A
7963913	12/2010	Devengenzo et al.	N/A	N/A
8142447	12/2011	Cooper et al.	N/A	N/A

8333755	12/2011	Cooper et al.	N/A	N/A
8444631	12/2012	Yeung et al.	N/A	N/A
8479969	12/2012	Shelton, IV	N/A	N/A
8506555	12/2012	Ruiz Morales	N/A	N/A
8551115	12/2012	Steger et al.	N/A	N/A
8602031	12/2012	Reis et al.	N/A	N/A
8644988	12/2013	Prisco et al.	N/A	N/A
8771270	12/2013	Burbank	N/A	N/A
8800838	12/2013	Shelton, IV	N/A	N/A
8911471	12/2013	Spivey et al.	N/A	N/A
9028494	12/2014	Shelton, IV et al.	N/A	N/A
9043027	12/2014	Durant et al.	N/A	N/A
9055961	12/2014	Manzo et al.	N/A	N/A
9078684	12/2014	Williams	N/A	N/A
9113899	12/2014	Garrison	N/A	A61B 18/1445
9121494	12/2014	Buchleitner et al.	N/A	N/A
9198714	12/2014	Worrell et al.	N/A	N/A
9204923	12/2014	Manzo et al.	N/A	N/A
9232979	12/2015	Parihar et al.	N/A	N/A
9259274	12/2015	Prisco	N/A	N/A
9291793	12/2015	Cooper	N/A	N/A
9339342	12/2015	Prisco et al.	N/A	N/A
9524022	12/2015	Nakayama	N/A	N/A
9687312	12/2016	Dachs, II et al.	N/A	N/A
9750519	12/2016	Garrison et al.	N/A	N/A
9750578	12/2016	Alden et al.	N/A	N/A
9757149	12/2016	Cooper et al.	N/A	N/A
9839481	12/2016	Blumenkranz et al.	N/A	N/A
9913694	12/2017	Brisson	N/A	N/A
9993313	12/2017	Schuh et al.	N/A	N/A
10016244	12/2017	Cooper et al.	N/A	N/A
10022193	12/2017	Cooper et al.	N/A	N/A
10130366	12/2017	Shelton, IV et al.	N/A	N/A
10271911	12/2018	Cooper et al.	N/A	N/A
10420622	12/2018	Dachs et al.	N/A	N/A
10478256	12/2018	Shelton, IV et al.	N/A	N/A
10543051	12/2019	Schena et al.	N/A	N/A
10582980	12/2019	Scheib et al.	N/A	N/A
10595836	12/2019	Smaby et al.	N/A	N/A
10603125	12/2019	Komuro et al.	N/A	N/A
10624709	12/2019	Remm	N/A	N/A
10631949	12/2019	Schuh et al.	N/A	N/A
10639119	12/2019	Dachs, II et al.	N/A	N/A
10653489	12/2019	Kopp	N/A	N/A
10780573	12/2019	Vaders	N/A	N/A
10912616	12/2020	Dachs, II et al.	N/A	N/A
10932868	12/2020	Solomon et al.	N/A	N/A
10980556	12/2020	Anderson et al.	N/A	N/A
11090124	12/2020	Holop et al.	N/A	N/A

2002/0087048	12/2001	Brock et al.	N/A	N/A
2002/0096885	12/2001	Gomez et al.	N/A	N/A
2002/0111635	12/2001	Jensen et al.	N/A	N/A
2002/0153221	12/2001	Schnepf	N/A	N/A
2004/0035243	12/2003	Duval	N/A	N/A
2005/0042943	12/2004	Mocivnik et al.	N/A	N/A
2005/0089345	12/2004	Yasumoto et al.	N/A	N/A
2005/0277875	12/2004	Selkee	N/A	N/A
2007/0043338	12/2006	Moll et al.	N/A	N/A
2007/0232858	12/2006	Macnamara et al.	N/A	N/A
2008/0046122	12/2007	Manzo et al.	N/A	N/A
2008/0065102	12/2007	Cooper	N/A	N/A
2008/0065105	12/2007	Larkin et al.	N/A	N/A
2008/0087871	12/2007	Schena et al.	N/A	N/A
2008/0103491	12/2007	Omori et al.	N/A	N/A
2008/0196533	12/2007	Bergamasco et al.	N/A	N/A
2009/0088774	12/2008	Swarup et al.	N/A	N/A
2010/0011900	12/2009	Burbank et al.	N/A	N/A
2010/0170519	12/2009	Romo et al.	N/A	N/A
2010/0318101	12/2009	Choi et al.	N/A	N/A
2010/0331820	12/2009	Prisco et al.	N/A	N/A
2011/0015650	12/2010	Choi et al.	N/A	N/A
2011/0118754	12/2010	Dachs, II et al.	N/A	N/A
2011/0160743	12/2010	Espinal	N/A	N/A
2011/0213383	12/2010	Lee et al.	N/A	N/A
2011/0277775	12/2010	Holop et al.	N/A	N/A
2011/0282356	12/2010	Solomon et al.	N/A	N/A
2011/0282357	12/2010	Rogers et al.	N/A	N/A
2011/0295269	12/2010	Swensgard et al.	N/A	N/A
2011/0295270	12/2010	Giordano et al.	N/A	N/A
2012/0021867	12/2011	Rosmarin	N/A	N/A
2012/0111136	12/2011	Kawakami	N/A	N/A
2012/0118917	12/2011	Naughton et al.	N/A	N/A
2012/0123441	12/2011	Au et al.	N/A	N/A
2012/0239060	12/2011	Orban, III et al.	N/A	N/A
2012/0245596	12/2011	Meenink	N/A	N/A
2012/0259337	12/2011	Del et al.	N/A	N/A
2012/0289974	12/2011	Rogers et al.	N/A	N/A
2013/0144116	12/2012	Cooper et al.	N/A	N/A
2014/0005678	12/2013	Shelton, IV et al.	N/A	N/A
2014/0005708	12/2013	Shelton, IV	N/A	N/A
2014/0100558	12/2013	Schmitz et al.	N/A	N/A
2014/0276723	12/2013	Parihar et al.	N/A	N/A
2015/0008090	12/2014	Adamczak et al.	N/A	N/A
2015/0150635	12/2014	Kilroy et al.	N/A	N/A
2015/0157355	12/2014	Price et al.	N/A	N/A
2016/0058443	12/2015	Yates et al.	N/A	N/A
2016/0151115	12/2015	Karguth et al.	N/A	N/A
2016/0184034	12/2015	Holop et al.	N/A	N/A
2016/0184037	12/2015	Cooper et al.	N/A	N/A

2017/0086930	12/2016	Thompson et al.	N/A	N/A
2017/0165017	12/2016	Chaplin et al.	N/A	N/A
2018/0055583	12/2017	Schuh et al.	N/A	N/A
2018/0280097	12/2017	Cooper et al.	N/A	N/A
2019/0021805	12/2018	Roeder et al.	N/A	N/A
2019/0099227	12/2018	Rockrohr	N/A	N/A
2019/0201022	12/2018	Schoettgen et al.	N/A	N/A
2019/0223966	12/2018	Holop et al.	N/A	N/A
2019/0254763	12/2018	Lambrecht et al.	N/A	N/A
2019/0298471	12/2018	Holop	N/A	N/A
2021/0186544	12/2020	Anderson et al.	N/A	N/A
2021/0282793	12/2020	Anderson et al.	N/A	N/A
2023/0054233	12/2022	Millman et al.	N/A	N/A
2023/0210614	12/2022	Cooper et al.	N/A	N/A
2024/0090958	12/2023	Cooper et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
5285298	12/1997	AU	N/A
3635400	12/2000	AU	N/A
2097491	12/1992	CA	N/A
2324967	12/2001	CA	N/A
2573759	12/2002	CN	N/A
1706348	12/2004	CN	N/A
101421080	12/2008	CN	N/A
101856255	12/2009	CN	N/A
102892375	12/2012	CN	N/A
103251434	12/2012	CN	N/A
103445816	12/2012	CN	N/A
1815949	12/2006	EP	N/A
1987786	12/2007	EP	N/A
H06114000	12/1993	JP	N/A
H10249777	12/1997	JP	N/A
2002200091	12/2001	JP	N/A
2003024336	12/2002	JP	N/A
2005288590	12/2004	JP	N/A
2006061364	12/2005	JP	N/A
2010220955	12/2009	JP	N/A
101066196	12/2010	KR	N/A
20110129293	12/2010	KR	N/A
WO-9729690	12/1996	WO	N/A
WO-2005039835	12/2004	WO	N/A
WO-2009123891	12/2008	WO	N/A
WO-2011037394	12/2010	WO	N/A
WO-2013181536	12/2012	WO	N/A
WO-2015023834	12/2014	WO	N/A
WO-2015142290	12/2014	WO	N/A
WO-2024030285	12/2023	WO	N/A

OTHER PUBLICATIONS

Extended European Search Report for Application No. 14836283.3, mailed on Sep. 4, 2017, 11 pages (ISRG04155/EP). cited by applicant

Extended European Search Report for Application No. 14836336.9, mailed on Jun. 16, 2017, 9 pages (ISRG04152/EP). cited by applicant

Extended European Search Report for Application No. 14836512.5, mailed on Aug. 3, 2017, 13 pages (ISRG04151/EP). cited by applicant

Extended European Search Report for Application No. 14836696.6, mailed on Jun. 16, 2017, 9 pages (ISRG04154/EP). cited by applicant

Extended European Search Report for Application No. 14836832.7, mailed on Jun. 9, 2017, 8 pages (ISRG04153/EP). cited by applicant

Extended European Search Report for Application No. EP14836874.9, mailed on Mar. 17, 2017. 10 pages (ISRG04150/EP). cited by applicant

Extended European Search Report for Application No. EP19195298.5 mailed on Nov. 12, 2019, 10 pages (ISRG04151D1/EP). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US14/050838, mailed on Nov. 25, 2014, 11 pages (ISRG04150/PCT). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US14/50957, mailed on Nov. 21, 2014, 11 pages (ISRG04151/PCT). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US14/51001, mailed on Nov. 20, 2014, 11 pages (ISRG04152/PCT). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US14/51074, mailed on Nov. 20, 2014, 13 pages (ISRG04155/PCT). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2012/037269, mailed on Sep. 19, 2012, 10 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2014/051033, mailed on Nov. 19, 2014, 9 pages (ISRG04153/PCT). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2014/051050, mailed on Nov. 25, 2014, 14 pages (IRG04154/PCT). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2017/024687, mailed on Jul. 5, 2017, 10 pages (ISRG08530/PCT). cited by applicant

Office Action for U.S. Appl. No. 16/317,243, mailed Jun. 13, 2023, 07 pages. cited by applicant

Office Action mailed Jun. 22, 2017 for Japanese Application No. 2016177316 filed Sep. 12, 2016, 7 pages (ISRG01880D3/JP). cited by applicant

Office Action mailed Dec. 26, 2014 for Japanese Application No. 20140021913 filed Feb. 7, 2008, 10 pages (ISRG01880D1/JP). cited by applicant

Office Action mailed Nov. 30, 2016 for Chinese Application No. 201510185999.6 filed Sep. 2, 2009, 24 pages (ISRG01880D1/CN). cited by applicant

Office Action mailed Sep. 30, 2015 for Japanese Application No. 20140021913 filed Feb. 7, 2008. 7 pages (ISRG01880D1/JP). cited by applicant

Partial Supplementary European Search Report for Application No. EP14836283.3, mailed on May 17, 2017, 12 pages (ISRG04155/EP). cited by applicant

PCT/US09/55727 International Search Report and Written Opinion of the International Searching Authority, mailed Feb. 3, 2010, 9 pages. cited by applicant

Vertut, J., and Coiffet, P., "Robot Technology: Teleoperation and Robotics Evolution and Development," English translation, Prentice-Hall, Inc., Englewood Cliffs, NJ, USA 1986, vol. 3A, 332 pages. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This patent application is a continuation of U.S. application Ser. No. 16/317,243 (filed Jan. 11, 2019), entitled “INSTRUMENT RELEASE,” which is a U.S. national stage filing under 35 U.S.C. § 371 of International Application No. PCT/US2017/024687 (filed Mar. 29, 2017), entitled “INSTRUMENT RELEASE,” which claims priority to and the benefit of the filing date of U.S. Provisional Patent Application No. 62/362,454 (filed Jul. 14, 2016), entitled “INSTRUMENT RELEASE,” each of which is incorporated by reference herein in its entirety.

BACKGROUND

(1) Some advanced robotic medical systems such as the da Vinci® Surgical System commercialized by Intuitive Surgical, Inc. employ removable medical instruments that may be mounted in docking ports on the arms of a robot. (As used herein, the terms “robot” or “robotically” and the like include teleoperation or telerobotic aspects, and teleoperated surgical systems are often referred to as “surgical robots”.) Such systems generally employ a sterile barrier between the medical instruments and the robot, so that medical instruments, which come into direct contact with a patient, reside in a sterile environment on a patient side of the sterile barrier, while the robot, which never directly contacts a patient, is outside of the sterile environment. The sterile barrier typically includes a drape or sheet of plastic or other material suitable for maintaining the sterile environment, and instrument sterile adapters (ISAs) may be mounted in the sheet and positioned between the medical instruments and the robot. The ISAs typically include structures that enable medical instruments to dock with the robot and enable the robot to mechanically actuate docked medical instruments without compromising the sterile environment. A medical instrument may employ latch and release mechanisms to securely dock the medical instrument with a robot via an ISA and to release the medical instrument from the robot and the ISA, for example, when a procedure is complete.

SUMMARY

(2) In accordance with an aspect of the invention, a medical instrument includes a backend with a pair of release levers. The backend may have a docking feature shaped to engage a docking structure such as a sterile adaptor or a docking port of a robot. Each of the release levers may be coupled to the backend and may include an activation feature (e.g., a release button) on one side of the backend and a push tab extending from an opposite side of the backend. Movement of the activation features moves the push tabs from being aligned with the docking feature to pushing on the docking structure, permitting the medical instrument to be disengaged from the docking structure.

(3) In accordance with another disclosed aspect, a medical instrument includes a backend with a release mechanism. The backend may have a docking feature shaped to engage a docking structure. The release mechanism includes a pair of release levers and a pair of push tabs. A first release lever has an activation feature, such as a button, on one side of the backend, and a second release lever has another activation feature on an opposite side of the backend. Similarly, a first push tab of the push tabs extends from one side of the backend, and a second push tab of the push tabs extends from the other side of the backend. A coupling of the two release levers may limit a movement of the activation features. The movement of the activation features causes the push tabs to move from being aligned with the docking feature to pushing on the docking structure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A shows an implementation of a medical system employing removable instruments.
- (2) FIG. 1B shows a medical instrument being slid into a docking port of a medical system.
- (3) FIG. 1C shows the medical instrument in accordance with the implementation of FIG. 1B when docked in a docking port.
- (4) FIG. 1D shows the docked medical instrument in accordance with the implementation of FIG. 1C when a user moves or activates a release mechanism.
- (5) FIGS. 2A and 2B show perspective and top views of an example implementation of a medical instrument.
- (6) FIG. 3A shows a cut away view revealing one implementation of a release mechanism that may be inside a backend of the instrument of FIGS. 2A and 2B.
- (7) FIG. 3B shows a perspective view of the release mechanism of FIG. 3A without surrounding components in a backend of an instrument.
- (8) FIGS. 4A, 4B, and 4C respectively show front, side, and perspective views of one implementation of a release lever.
- (9) FIGS. 5A, 5B, and 5C are cross-sectional views illustrating installation of a release mechanism in a medical instrument.
- (10) FIG. 5D shows a cross-sectional view illustrating the effect of a user depressing or activating a release mechanism in accordance with the implementation of FIGS. 5A, 5B, and 5C.
- (11) FIG. 6A shows a perspective view of a release mechanism in accordance with an implementation employing multi-piece release levers.
- (12) FIG. 6B is a cutaway view illustrating the interconnection of release buttons on opposite sides of a medical instrument using the release mechanism of FIG. 6A.
- (13) FIG. 6C is a side view illustrating the connection an release button to a link and a push rod that form an implementation of a multi-piece release lever.
- (14) FIG. 6D shows an instrument containing the release mechanism of FIG. 6A when the instrument is engaged with an instrument sterile adapter and a docking port of a robot.
- (15) FIG. 6E shows an instrument containing the release mechanism of FIG. 6A when the release mechanism is activated.
- (16) The drawings illustrate examples for the purpose of explanation and are not of the invention itself. Use of the same reference symbols in different figures indicates similar or identical items.

DETAILED DESCRIPTION

(17) A release mechanism for a medical instrument may push a sterile adapter retention plate away from the medical instrument using coupled levers to simultaneously press on opposite edges of the retention plate. The release mechanism particularly pushes the retention plate away symmetrically, so that the medical instrument does not get cocked to one side, which could prevent the medical instrument from sliding smoothly out of an instrument sterile adapter (ISA). The medical instrument may engage the ISA by being slid into a position at which spring action of the ISA or other docking structure may push projections on opposite sides of the medical instrument or the ISA into notches in the other of the ISA and the medical instrument. Disengaging the instrument may thus require the release mechanism to push the projections out of the notches, so that the instrument can be slid out of (or otherwise removed from) the ISA. Release buttons or other activation features of the release mechanism may be positioned on a housing of the medical instrument so that a user grasping the housing when removing the instrument can naturally activate the release mechanism and reliably push the retention plate and the instrument apart using a grasping force within desired limits.

(18) FIG. 1A shows an example of a medical system **100** including replaceable medical instruments **110** that may contain release mechanisms such as disclosed herein. System **100**, which may, for example, include a da Vinci® Surgical System commercialized by Intuitive Surgical, Inc., employs

multiple surgical instruments **110**, each of which is mounted in a docking port **120** on a manipulator arm **130** of a robot **140**. A sterile barrier (not shown in FIG. **1A**) including a drape and instrument adaptors may be between a patient (not shown) and robot **140**. Robot **140**, including manipulator arms **130** and docking ports **120**, may thus be outside a sterile environment for the patient, while instruments **110** are in the sterile environment on the patient's side of the sterile barrier. Accordingly, robot **140** may not need to be sterilized for medical procedures. In contrast, instruments **110**, which directly contact the patient, are compact and removable so that medical instruments **110** may be removed and sterilized or replaced between medical procedures performed using system **100**. The sterile barrier may be removed from robot **140** after medical instruments **110** are removed, but the sterile barrier is typically disposed of and replaced between medical procedures.

(19) Instruments **110** may vary in structure and purpose but may still be interchangeable, so that a user can select and mount various instruments **110** in docking ports **120** of robot **140** as needed for a particular medical procedure and can swap instruments **110** during a medical procedure to provide desired clinical functions. Each instrument **110** generally includes an end effector or distal tool **112**, an instrument shaft **114**, and a backend. Distal tools **112** may have different designs to implement many different functions. For example, distal tools **112** for different instruments **110** may have many different shapes or sizes and may include forceps, graspers, scalpels, scissors, cautery tools, or needle drivers to name a few possibilities. Instruments **110** having different distal tools **112** may be mounted on different arms **130** of robot **140** and may work cooperatively at the same work site. An endoscopic camera, for example, a stereoscopic camera, can also be mounted on an arm to provide visual information, particularly images of the work site in which distal tools **112** of instruments **110** may be operating.

(20) Docking ports **120** of robot **140** may include actuators such as drive motors that provide mechanical power to actuate mechanical structures in instruments **110** via drive couplings that connect the actuators through an ISA to inputs of instruments **110**. FIG. **1B** illustrates an instrument **110** beginning to engage a docking port **120**. An ISA **150**, which may be part of a sterile barrier, may be mounted on docking port **120** before the engagement process begins. In particular, ISA **150** may be attached to docking port **120**. In the implementation shown, ISA **150** includes an outer frame **158** around a movable plate **157** containing rotatable disks **156**. Outer frame **158**, which is shown in cross-section to better illustrate the structure of ISA **150**, may be disposed in a sheet or drape portion **160** of the sterile barrier and is sized and shaped to fit docking port **120**. Inner frame **157**, which is sometimes referred to herein as a retention plate, may be movable relative to outer frame **158** to adjust to variability in the position of actuators in docking port **120** so that engagement features **122** of the actuators in docking port **120** may couple to disks **156** in ISA **150**. In particular, springs (not shown) in the docking port **120** may provide spring loading that pushes engagement features **122** onto disks **156** and plate **157**. Disks **156** in turn engage engagement features on input spindles **120** of instrument **110** when instrument **110** is fully docked.

(21) ISA **150** further includes rails **152** shaped to guide side rails **232** and projections **234** on opposite sides of backend **116** of instrument **110** as backend **116** is being slid into ISA **150**. When projections **234** reach respective notches **154** in ISA **150**, rails **152** push side rails **232** against retention plate **157** or outer frame **158** of ISA **150** and push each projection **234** into its notch **154** in ISA **150** as shown in FIG. **1C**. In this docked position, engagement features **122** on drive motors in docking port **120** fit into top features of sealed disks **156** in ISA **150**, and engagement features **228** on input spindles of backend **116** fit into bottom features of sealed disks **156** so that drive motors rotating engagement features **122** rotate disks **156** and input spindles **220** of instrument **110**. A computer system, which may be connected to or part of the robot **140** that includes docking port **120** and which may be connected to a user interface device (not shown), may receive user commands from a surgeon or other medical personnel and may execute software that controls drive motors or other actuators in docking ports **120** as needed to rotate engagement features **122**, disks

156, and input spindles 220 and thereby actuate instruments 110 according to the user commands. (22) FIG. 1C shows the projection 234 on one side of backend 116 secured in the notch 154 on one side of ISA 150. Projections 234 and notches 154 act as lock features that prevent instrument 110 from being unintentionally removed from ISA 150. In particular, two projections 234 on opposite sides of backend 116 being pressed into notches 154 on opposite sides of ISA 150 may keep backend 116 from disengaging from docking port 120 and from sliding out of ISA 150. To release instrument 110 from docking port 120 and ISA 150, instrument 110 includes a release mechanism that includes interconnected release levers with push tabs 240 on opposite sides of backend 116. When the release mechanism is not activated, each push tab 240 may be aligned with or recessed relative to a side rail 232 so that backend 116 can slide into place and fully engage with ISA 150 and docking port 120 as shown in FIG. 1C. A user may depress release buttons 250 on opposite sides of backend 116 to activate the release mechanism and cause push tabs 240 to move up past respective rails 232 and to thereby push on ISA 150. Push tabs 240 may particularly push on plate 157, so that plate 157 moves away from backend 116 and disengages backend 116 from notches 154 and/or other engagement features of ISA 150. Push tabs 240 may also push on plate 157, so that plate 157 moves disks 156 away from backend 116 and disengages bottoms of disks 156 from input spindles 220 in backend 116. FIG. 1D shows how the action of push tabs 240 may also keep ISA 150 engaged with docking port 120 while decoupling projections 234 from notches 154 so that medical instrument 110 can be slid out of ISA 150. ISA 150 thus remains on docking port 120 when instrument 110 is released and removed.

(23) FIGS. 2A and 2B illustrate a more detailed example of an implementation of a medical instrument 110. FIG. 2A particularly shows a perspective view of an implementation having an elongated instrument shaft 114 that extends from backend 116 of instrument 110 and having a distal tool 112 at the distal end of instrument shaft 114. In the illustrated implementation, distal tool 112 has six degrees of freedom of movement relative to backend 116. Specifically, the six degrees of freedom may correspond to: pitch and yaw rotations of a portion of tool 112 about two respective perpendicular axes 201 and 202 associated with a first joint or wrist mechanism 211; pitch and yaw rotations or movement of jaws 213 relative to two respective perpendicular axes 203 and 204 associated with a second joint or wrist mechanism 212; opening or closing movement 205 of jaws 213 for “grip” actuation; and “roll” rotations of instrument shaft 114 about its central length axis 206. Other medical instruments may have more, fewer, or different degrees of freedom of movement.

(24) Backend 116 as shown in FIG. 2B has six input spindles 221 to 226 with engagement features that are arranged in a base plate 230 and are shaped to engage actuators, e.g., engagement features of drive motors, in a docking port of a robot via an intervening ISA as illustrated in FIGS. 1B, 1C, and 1D. In general, each input spindle 221 to 226 may be part of a mechanism for actuation of a corresponding degree of freedom of movement of instrument 110. The assignment input spindles 221 to 226 to corresponding degrees of freedom must be known to the robot, so that the robot can identify and use the correct actuator or actuators to rotate the input spindle or spindles that exercise desired degree or degrees of freedom of instrument 110, but assignment of input spindles 221 to 226 to particular degrees of freedom of movement can be otherwise defined by an arbitrary standard or convention.

(25) Base plate 230 further includes side rails 232 on opposite sides of base plate 230, and side rails 232 may be positioned and shaped for sliding of backend 116 into an ISA as illustrated in FIG. 1B. Base plate 230 may further include projections 234 that may be contiguous with respective rails 232 or separated from rails 232. Each projection 234 may be positioned and shaped to slip into a corresponding notch in the ISA so that projections 234 when in respective notches prevent backend 116 from being slid out of the ISA. Removal of the instrument may thus require lifting projections 234 out of the notches in the ISA as described above with reference to FIG. 1D.

(26) FIG. 3A shows a cutaway view of the instrument backend 116 of FIGS. 2A and 2B in

accordance with an implementation in which a release mechanism employs a pair of identical interconnected release levers **310** that each function as a release element of a release mechanism **300**. FIG. 3B shows release mechanism **300** including release levers **310** but without other structures of backend **116** that may obscure the view of the interaction of release levers **310**. In release mechanism **300**, each release lever **310** has a one-piece construction and may be a monolithic or molded structure that integrates and connects one push tab **240** and one release button **250**. Each lever **310** further includes a pair of pivot arms **320** and a lifter arm **330**. Each button **250** is coupled to a crossbar extending between a pair of pivot arms **320**. The two pivot arms **320** on each release lever **310** have pivots **322** (which can be implemented as axles) that extend along a desired rotation axis of the release lever **310**. In backend **116** of FIG. 3A, pivots **322** of a release lever **310** rotatably attach the release lever **310** to base plate **230**. Pivot arms **320** and buttons **250** may particularly be positioned toward outer edges of backend **116**, so that actuation mechanisms such as input spindles **221** to **224** can occupy the central portion of backend **116** as shown in FIG. 3A. The lifter arm **330** of each release lever **310** may extend from the release button **250** of the release lever **310**, between the input spindles of backend **116**, across backend **116**, and upward so that the push tab **240** at the end of lifter arm **330** extends from a side of backend **116** that is opposite the side on which the button **250** resides. Accordingly, a user pushing on a button **250** on one side of backend **116** causes release lever **310** to rotate and the push tab **240** on the opposite side of backend **116** to move.

(27) FIGS. 4A, 4B, and 4C respectively show front, side, and perspective views of an implementation of release lever **310** that can be used in release mechanism **300** of FIG. 3B. Release lever **310** may be a one-piece or monolithic structure and may be molded from a plastic or other sufficiently durable material. The release lever implementation of FIGS. 4A, 4B, and 4C includes guide channel **332** and a guide pin **334** on lifter arm **330** to allow interconnection of a pair of identical release levers **310**. That is, to reduce parts and save manufacturing cost, identical release levers are used for each side, and the release levers are configured to work together in this hermaphroditic configuration. In particular, in assembling release mechanism **300** of FIG. 3B, guide pin **334** on the lifter arm **330** of one release lever **310** may be inserted into the guide channel **332** on the lifter arm **330** of the other release lever **310**. Guide channel **332** may be arc-shaped to accommodate or guide rotations of both release levers **310** about their respective pivots **322**. One of the advantages of the pin-in-slot configuration is that guide channels **332** control the movement of pins **334**, and so both release levers **310** are forced to move symmetrically. Thus, both tabs **240** may push upward on the sterile adapter retention features with the same displacement, and the instrument stays level relative to the sterile adapter and does not get cocked to one side when the tabs **240** push upward. Having two linked release levers **310** on opposite sides of the instrument also means that the force applied to one lever **310** is counteracted in the other **310**, and user activation of release mechanism **300** does not produce a net force that might otherwise push the instrument left or right.

(28) Lifter arm **330** on a release lever **310** extends from an off center location on release button **250** to position guide channel **332** and pin **334** for connection to the lifter arm **330** of an identical release lever **310**. In some implementations, a spring may be inserted in a cavity formed by adjacent guide channels **332** to push guide pins **334** apart when no external pressure is applied to buttons **250**.

(29) A user can operate or activate release mechanism **300** of FIGS. 3A and 3B by grasping a backend **116** and depressing both buttons **250** simultaneously. Depressing buttons **250** causes both release levers **310** to rotate about their individual axes defined by the connection of pivots **322** to base plate **230** and guide pins **334** in channels **332**, and the rotations of release levers **310** lift push tabs **240** relative to base plate **230**.

(30) The implementation of release lever **310** of FIGS. 4A, 4B, and 4C when assembled into the release mechanism **300** of FIGS. 3A and 3B has several advantageous features. In particular, pivot

arms **320** may provide a long radius for rotation of button **250** about pivots **322** so that button **250** moves in a substantially linear direction when depressed. Further, the moment or radius of rotation of push tab **240** about pivot **322** may be roughly equal to moment or radius of rotation of button **250** about pivot **322**, so that the force a user applies on button **250** may be about the same as the force that push tab **240** exerts on the retention plate when release mechanism **300** is activated. Further, the one-piece structure of release levers **310** and the hermaphroditic engagement of release levers **310** in release mechanism **300** allow both release levers **310** to be identical parts, which may reduce the part count and cost of a medical instrument. Release levers **310** can also extend across an instrument backend and wrap around backend mechanical systems such as the input spindles and cables shown in FIG. 3A. Release mechanism **300** may, therefore, be installed in an instrument backend after all cabling and centrally located mechanical systems are assembled, which simplifies the instrument assembly process because release mechanism **300** does not interfere with assembly of other backend mechanical systems.

(31) FIGS. 5A, 5B, and 5C illustrate a process of assembling a pair of identical release levers **310A** and **310B** in a base plate **230** of an instrument backend to form one implementation of an instrument release mechanism **300**. Each release lever **310A** or **310B** may have a one-piece molded construction including two pivot arms **320A** or **320B** and a lifter arm **330A** or **330B** as described above. Release levers **310A** and **310B** may be engaged with each other before being engaged with base plate **230**. In particular, a guide pin **334A** of release lever **310A** may be inserted in a guide channel **332B** of release lever **310B**, and a guide pin **334B** of release lever **310B** may be inserted in a guide channel **332A** of release lever **310A**. A spring **510** may be installed between guide pins **334A** and **334B** in a cavity formed by guide channels **332A** and **332B** and may improve the look and feel of release buttons **250A** and **250B** in the assembled release mechanism **300**.

(32) Each guide channel **332A** and **332B** may extend beyond the range of motion that guide pins **334B** and **334A** have for normal use of release mechanism **300**. In particular, an assembly process may initially separate pivots **322A** and **322B** by a greater distance than required for normal use. The wider separation allows pivots **322A** and **322B** to be inserted into L-shaped slots **236** in base plate **230** as shown in FIG. 5A. Pivots **322A** and **322B** may then be slid up into slots **236** as shown in FIG. 5B before buttons **250A** and **250B**, and pivots **322A** and **322B** shift inward for use as shown in FIG. 5C. Accordingly, guide channels **332A** and **332B** may have extensions that can accommodate the greater separation initially needed between guide pins **334B** and **334A** during assembly of release mechanism **300**.

(33) FIG. 5C also illustrates a housing **520** for the instrument backend that encloses the mechanics of the backend including release mechanism **300**. Housing **520** may include tabs **522** that fit into the L-shaped slots in base plate **230** and help to capture the release lever pivots **322A** and **322B** in their working positions. Housing **520** also captures release buttons **250A** and **250B** at the proper separation so that push tabs **240A** and **240B** are substantially aligned with rails **232**. The bottom cutaways in FIG. 5C show how spring **510** compresses to fit between guide pins **334A** and **334B** in the assembled position, which loads spring **510** to push the release buttons **250A** and **250B** apart. FIG. 5D illustrates how pushing release buttons **250A** and **250B** inward rotates release levers **310A** and **310B** about respective pivots **322A** and **322B**, raising push tabs **240A** and **240B** above rails **232** so that push tabs **240A** and **240B** can push on an ISA or other docking structure.

(34) FIG. 6A shows a release mechanism **600** in accordance with an implementation that positions push tab **240A** on the same side as release button **250A** on an instrument backend, and likewise push tab **240B** is on the same side as release button **250B** on the instrument backend. In release mechanism **600**, release buttons **250A** and **250B** are interconnected using alignment features that limit buttons **250A** and **250B** to moving linearly toward or away from each other. For example, FIG. 6B shows an implementation in which slides **652A** and **652B** on release buttons **250A** and **250B** fit into slots **654B** and **654A** in the opposite release buttons **250B** and **250A**, so that buttons **250A** and **250B** can only move relative to each other along a length axis of slides **652A** and **652B**.

As described above, the release mechanism assemblies for each side are identical and are configured to work together.

(35) Each release button **250A** or **250B** in release mechanism **600** of FIG. **6A** further couples to a three-pivot link **610A** or **610B**. FIG. **6C**, for example, shows a release button **650**, which may be identical to button **250A** or **250B**, having a slot and pin coupling **612** to a three-pivot link **610**, which may be identical to link **610A** or **610B** of FIG. **6A**. A second pivot **614** of link **610** may be fixed on a chassis of a backend of an instrument containing the release mechanism **600**, and a third pivot **616** of link **610** couples link **610** to a push rod **620**. During use of release mechanism **600**, pushing on release button **650** rotates link **610** and thereby pushes push rod **620** upward.

Accordingly, in release mechanism **600** of FIG. **6A**, pushing on button **250A** or **250B** rotates the connected link **610A** or **610B** and moves push rod **620A** or **620B** in a generally upward direction. Push tabs **240A** and **240B** may have guide features that restrict the movement of tabs **240A** and **240B** to desired directions, e.g., up and down. Thus as shown, each assembly of button **250**, slides **652**, link **610**, and push rod **620** functions as a release element of the release assembly.

(36) FIG. **6D** shows an implementation of an instrument backend **116** containing release mechanism **600** of FIG. **6A** when instrument backend **116** is engaged with a docking port **120** via an ISA **150**. In the engaged configuration as shown in FIG. **6D**, push tabs **240** may be aligned with side rails **232** on the housing of backend **116**. As described above with reference to FIG. **1C**, backend **116** and ISA **150** may have complementary projections and notches that fit together and prevent backend **116** from being slid out of ISA **150** while the projections and notches are engaged. When a user presses release both buttons **250A** and **250B** as shown in FIG. **6E**, resulting rotations of links **610A** and **610B** move push rods **620A** and **620B** upward, so that push tabs **240A** and **240B** push on ISA **150**, which can disengage projections and notches on backend **116** and ISA **150**. Pushing release buttons **250A** and **250B** may thus release backend **116** from ISA **150**, while ISA **150** and docking port **120** remain engaged.

(37) Although particular implementations have been disclosed, these implementations are only examples and should not be taken as limitations. Various adaptations and combinations of features of the implementations disclosed are within the scope of the following claims.

Claims

1. A release mechanism for a medical instrument, the release mechanism comprising: an activation feature positioned on a first side of a backend of the medical instrument; a push tab extending from a second side of the backend, the second side being different than the first side; and a lever coupling the activation feature and the push tab, the lever including a pivot arm and a lifter arm, wherein the push tab is configured to push on a portion of a docking structure in response to a movement of the activation feature to separate the portion of the docking structure and the backend of the medical instrument.
2. The release mechanism of claim 1, wherein: the docking structure is a retention plate of an instrument sterile adapter; the instrument sterile adapter is a portion of a sterile barrier; and the sterile barrier separates the medical instrument from a manipulator docking port.
3. The release mechanism of claim 1, wherein: the activation feature, the push tab, the pivot arm, and the lifter arm are formed as a monolithic structure.
4. The release mechanism of claim 1, wherein: the pivot arm extends from the activation feature to a pivot; and the pivot is configured to be movably coupled to a base plate of the backend on the first side.
5. The release mechanism of claim 4, wherein: a radius of rotation of the push tab about the pivot is substantially equal to a radius of rotation of the activation feature about the pivot.
6. The release mechanism of claim 1, wherein: the lifter arm extends from the activation feature to the second side of the backend; and the push tab extends from the lifter arm in a position to exert a

force on the portion of the docking structure.

7. The release mechanism of claim 1, wherein the activation feature is a first activation feature, the push tab is a first push tab, the lever is a first lever, the release mechanism further comprising: a second activation feature positioned on the second side of the backend; a second push tab extending from the first side of the backend; and a second lever coupling the second activation feature and the second push tab, wherein the first push tab and the second push tab are configured to push on the portion of the docking structure in response to the movement of the first activation feature and a movement of the second activation feature to separate the portion of the docking structure and the backend of the medical instrument.

8. The release mechanism of claim 7, wherein: the first lever includes a first pin and a first guide channel; the second lever includes a second pin and a second guide channel; the first pin is positioned within the second guide channel; the second pin is positioned within the first guide channel; and a movement of the first pin is controlled by the second guide channel and a movement of the second pin is controlled by the first guide channel so that the first lever and the second lever move symmetrically in response to the movement of the first activation feature and the second activation feature.

9. The release mechanism of claim 8, wherein: each of the first guide channel and the second guide channel have an arc-shape configured to guide a rotation of each of the first lever and the second lever.

10. The release mechanism of claim 7, wherein: the first lever is operably coupled to the second lever via a plurality of pins and corresponding guide channels; the operable coupling of the first lever and the second lever causes a reactive force in response to an activation force applied to one of the first lever or the second lever; and the reactive force counteracts the activation force so that a net force does not push the backend perpendicular to a direction in which the first push tab and the second push tab move.

11. A medical instrument comprising: a backend including a docking feature shaped to engage a retention plate of an instrument sterile adapter; a first release element coupled to the backend and including a first activation feature on a first side of the backend and a first push tab extending from the first side; and a second release element coupled to the backend and including a second activation feature on a second side of the backend and a second push tab extending from the second side of the backend, the second side being opposite to the first side, wherein a movement of the first and second activation features moves the first and second push tabs from being aligned with the docking feature to pushing on the retention plate to separate the retention plate and the backend.

12. The medical instrument of claim 11, wherein: the instrument sterile adapter is a portion of a sterile barrier; and the sterile barrier separates the medical instrument from a manipulator docking port of a surgical system.

13. The medical instrument of claim 11, wherein: the docking feature includes a rail and a lock feature; the rail is shaped to slidably engage with the retention plate; and the lock feature is shaped to engage the retention plate and prevent the medical instrument from being slid relative to the retention plate when engaged.

14. The medical instrument of claim 13, wherein: the lock feature is positioned to be disengaged from the retention plate on a condition that the first and second push tabs are pushed against the retention plate in response to the movement of the first and second activation features.

15. The medical instrument of claim 11, wherein: the first activation feature is a first button; the second activation feature is a second button; and each of the first button and the second button are positioned so that a user can simultaneously depress the first button and the second button in a singular motion by grasping the backend.

16. The medical instrument of claim 11, wherein: the first release element includes a first link and a first pushrod; the first link includes a first pivot coupled to the backend and a second pivot coupled to the first activation feature; the first link rotates about the first pivot in response to the movement

of the first activation feature; the first pushrod is coupled to a third pivot of the first link; and the first push tab extends from the first pushrod.

17. The medical instrument of claim 16, wherein: the second release element includes a second link and a second pushrod; the second link includes a fourth pivot coupled to the backend and fifth pivot coupled to the second activation feature; the second link rotates about the fourth pivot in response to the movement of the second activation feature; the second pushrod is coupled to a sixth pivot of the second link; and the second push tab extends from the second pushrod.

18. The medical instrument of claim 11, wherein: the first release element and the second release element are operably coupled together; and the first activation feature and the second activation feature are limited to moving linearly toward or away from each other.

19. The medical instrument of claim 11, wherein: the first release element includes a first slide member and defines a first slot; the second release element includes a second slide member and defines a second slot; the first slot is sized to receive the second slide member; and the second slot is sized to receive the first slide member.

20. The medical instrument of claim 11, wherein: the first push tab includes a first guide feature; the first guide feature restricts a movement of the first push tab to a direction that is orthogonal to a direction of movement of the first activation feature and the second activation feature; the second push tab includes a second guide feature; and the second guide feature restricts a movement of the second push tab to the direction that is orthogonal to the direction of movement of the first activation feature and the second activation feature.
