

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent

12414873

Kind Code

B2

Date of Patent

September 16, 2025

Inventor(s)

Bacich; Steven R. et al.

### Apparatus and method for everting catheter for IUD delivery and placement in the uterine cavity

#### Abstract

An everting balloon system is disclosed that can be used for the placement of an IUD within the uterine cavity of a female patient. The everting balloon system with IUD can be used to access a uterine cavity at specific locations in the fundus. A one-handed IUD delivery system for placement with an everting catheter is disclosed. An IUD loading system for placement within an everting catheter is disclosed. The everting catheter with an IUD can simplify the process of IUD placement within the uterine cavity.

**Inventors:** Bacich; Steven R. (Half Moon Bay, CA), Yurek; Matthew Thomas (San Diego, CA), Greelis; Jack (Carlsbad, CA), Vidyarthi; Piush (San Rafael, CA)

**Applicant:** CrossBay Medical, Inc. (San Diego, CA)

**Family ID:** 1000008819365

**Assignee:** CrossBay Medical, Inc. (San Diego, CA)

**Appl. No.:** 18/626186

**Filed:** April 03, 2024

#### Prior Publication Data

**Document Identifier**

**Publication Date**

US 20240245548 A1

Jul. 25, 2024

#### Related U.S. Application Data

continuation parent-doc US 18156268 20230118 ABANDONED child-doc US 18626186

continuation parent-doc US 17185449 20210225 US 11583436 20230221 child-doc US 18156268

division parent-doc US 17067352 20201009 US 11141308 20211012 child-doc US 17185449

us-provisional-application US 62913160 20191009

## Publication Classification

**Int. Cl.:** **A61F6/18** (20060101); **A61F6/14** (20060101); **A61M25/00** (20060101); **A61M25/01** (20060101)

**U.S. Cl.:**

**CPC** **A61F6/18** (20130101); **A61F6/146** (20130101); **A61M25/003** (20130101); **A61M25/0075** (20130101); **A61M25/0119** (20130101); **A61M25/0125** (20130101); **A61M25/0138** (20130101); **A61M25/0155** (20130101); A61M2025/0031 (20130101); A61M2025/0034 (20130101); A61M2210/14 (20130101); A61M2210/1425 (20130101)

## Field of Classification Search

**CPC:** A61M (25/10); A61M (2210/1433); A61M (25/0119); A61M (25/1011); A61M (25/1002); A61F (6/146); A61F (6/18); A61F (6/00); A61F (6/20); A61F (6/12); A61F (6/08); A61F (6/14); A61F (2/0036); A61K (9/0034); A61K (9/0039); A61K (9/0036); A61B (2017/22051)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No. | Issued Date | Patentee Name     | U.S. Cl. | CPC         |
|------------|-------------|-------------------|----------|-------------|
| 2299492    | 12/1941     | Pfauser           | N/A      | N/A         |
| 2437329    | 12/1947     | Moore             | N/A      | N/A         |
| 3053257    | 12/1961     | Birtwell          | N/A      | N/A         |
| 3882852    | 12/1974     | Sinnreich         | N/A      | N/A         |
| 4324262    | 12/1981     | Hall              | N/A      | N/A         |
| 4476814    | 12/1983     | Miller            | N/A      | N/A         |
| 4493711    | 12/1984     | Chin et al.       | N/A      | N/A         |
| 4606347    | 12/1985     | Fogarty et al.    | N/A      | N/A         |
| 4612924    | 12/1985     | Cimber            | 128/839  | A61F 6/16   |
| 4612928    | 12/1985     | Tiep et al.       | N/A      | N/A         |
| 4681123    | 12/1986     | Valtchev          | N/A      | N/A         |
| 4742829    | 12/1987     | Law et al.        | N/A      | N/A         |
| 4946440    | 12/1989     | Hall              | N/A      | N/A         |
| 5171305    | 12/1991     | Schickling et al. | N/A      | N/A         |
| 5236423    | 12/1992     | Mix et al.        | N/A      | N/A         |
| 5265840    | 12/1992     | Gillespie et al.  | N/A      | N/A         |
| 5284473    | 12/1993     | Calabria          | 604/8    | A61M 25/104 |
| 5364345    | 12/1993     | Lowery et al.     | N/A      | N/A         |
| 5374247    | 12/1993     | Lowery et al.     | N/A      | N/A         |
| 5374261    | 12/1993     | Yoon              | N/A      | N/A         |
| 5403310    | 12/1994     | Fischer           | N/A      | N/A         |
| 5554159    | 12/1995     | Fischer           | N/A      | N/A         |
| 5749889    | 12/1997     | Bacich et al.     | N/A      | N/A         |
| 5772628    | 12/1997     | Bacich et al.     | N/A      | N/A         |
| 5879289    | 12/1998     | Yarush et al.     | N/A      | N/A         |
| 6106524    | 12/1999     | Eggers et al.     | N/A      | N/A         |

|              |         |                    |         |              |
|--------------|---------|--------------------|---------|--------------|
| 6645233      | 12/2002 | Ayers et al.       | N/A     | N/A          |
| 6648233      | 12/2002 | Inui et al.        | N/A     | N/A          |
| 6669643      | 12/2002 | Dubinsky           | N/A     | N/A          |
| 6953460      | 12/2004 | Maguire et al.     | N/A     | N/A          |
| 7041084      | 12/2005 | Fojtik             | N/A     | N/A          |
| 7144407      | 12/2005 | Lasersohn          | N/A     | N/A          |
| 8157745      | 12/2011 | Schoot             | N/A     | N/A          |
| 8221322      | 12/2011 | Wang et al.        | N/A     | N/A          |
| 8528563      | 12/2012 | Gruber             | 606/198 | A61N 5/062   |
| 9101391      | 12/2014 | Bacich             | N/A     | A61M 29/02   |
| 9498274      | 12/2015 | Burnett et al.     | N/A     | N/A          |
| 9757264      | 12/2016 | Neisz et al.       | N/A     | N/A          |
| 10136937     | 12/2017 | Cosman et al.      | N/A     | N/A          |
| 10576248     | 12/2019 | Bacich et al.      | N/A     | N/A          |
| 10967149     | 12/2020 | Bacich et al.      | N/A     | N/A          |
| 11090024     | 12/2020 | Roy et al.         | N/A     | N/A          |
| 11583436     | 12/2022 | Bacich             | N/A     | A61M 25/0119 |
| 11819245     | 12/2022 | Bacich et al.      | N/A     | N/A          |
| 2001/0001811 | 12/2000 | Burney et al.      | N/A     | N/A          |
| 2001/0044595 | 12/2000 | Reydel et al.      | N/A     | N/A          |
| 2002/0032438 | 12/2001 | Lafontaine         | N/A     | N/A          |
| 2002/0049441 | 12/2001 | George et al.      | N/A     | N/A          |
| 2002/0193705 | 12/2001 | Burbank et al.     | N/A     | N/A          |
| 2003/0065371 | 12/2002 | Satake             | N/A     | N/A          |
| 2003/0109872 | 12/2002 | Muzzammel          | N/A     | N/A          |
| 2004/0242960 | 12/2003 | Orban              | N/A     | N/A          |
| 2005/0222518 | 12/2004 | Dib                | N/A     | N/A          |
| 2005/0240147 | 12/2004 | Makower et al.     | N/A     | N/A          |
| 2006/0025780 | 12/2005 | James              | N/A     | N/A          |
| 2006/0030884 | 12/2005 | Yeung et al.       | N/A     | N/A          |
| 2006/0036271 | 12/2005 | Schomer et al.     | N/A     | N/A          |
| 2006/0052750 | 12/2005 | Lenker et al.      | N/A     | N/A          |
| 2007/0010798 | 12/2006 | Stoller et al.     | N/A     | N/A          |
| 2007/0135796 | 12/2006 | Gorodeski          | N/A     | N/A          |
| 2007/0179380 | 12/2006 | Grossman           | N/A     | N/A          |
| 2008/0045924 | 12/2007 | Cox et al.         | N/A     | N/A          |
| 2008/0097470 | 12/2007 | Gruber et al.      | N/A     | N/A          |
| 2008/0172050 | 12/2007 | Satake             | N/A     | N/A          |
| 2009/0156996 | 12/2008 | Milsom et al.      | N/A     | N/A          |
| 2009/0157069 | 12/2008 | Tom et al.         | N/A     | N/A          |
| 2009/0227893 | 12/2008 | Coonahan et al.    | N/A     | N/A          |
| 2010/0030256 | 12/2009 | Dubrul et al.      | N/A     | N/A          |
| 2010/0036197 | 12/2009 | Mesallum           | N/A     | N/A          |
| 2010/0160823 | 12/2009 | Parihar et al.     | N/A     | N/A          |
| 2010/0217250 | 12/2009 | Sampson            | N/A     | N/A          |
| 2010/0241153 | 12/2009 | Tilson et al.      | N/A     | N/A          |
| 2011/0066099 | 12/2010 | Hoskins            | N/A     | N/A          |
| 2012/0035471 | 12/2011 | Lee-sepsick et al. | N/A     | N/A          |
| 2012/0197245 | 12/2011 | Burnett et al.     | N/A     | N/A          |
| 2012/0305669 | 12/2011 | Meron et al.       | N/A     | N/A          |

|              |         |                  |     |     |
|--------------|---------|------------------|-----|-----|
| 2013/0123613 | 12/2012 | Trembly et al.   | N/A | N/A |
| 2013/0139828 | 12/2012 | Rousseau et al.  | N/A | N/A |
| 2013/0197392 | 12/2012 | Ritchart et al.  | N/A | N/A |
| 2014/0128732 | 12/2013 | Roy et al.       | N/A | N/A |
| 2014/0235943 | 12/2013 | Paris et al.     | N/A | N/A |
| 2014/0371597 | 12/2013 | Roy et al.       | N/A | N/A |
| 2015/0107598 | 12/2014 | Tal et al.       | N/A | N/A |
| 2015/0132045 | 12/2014 | Kinkelbur et al. | N/A | N/A |
| 2015/0133737 | 12/2014 | Bacich et al.    | N/A | N/A |
| 2015/0141917 | 12/2014 | Tilson et al.    | N/A | N/A |
| 2015/0142045 | 12/2014 | Bacich et al.    | N/A | N/A |
| 2015/0164313 | 12/2014 | Ouyang et al.    | N/A | N/A |
| 2015/0224280 | 12/2014 | Pinchuk et al.   | N/A | N/A |
| 2015/0305765 | 12/2014 | Fojtik et al.    | N/A | N/A |
| 2015/0343182 | 12/2014 | Vazales et al.   | N/A | N/A |
| 2015/0351729 | 12/2014 | Chin et al.      | N/A | N/A |
| 2016/0095584 | 12/2015 | Almeida et al.   | N/A | N/A |
| 2017/0209022 | 12/2016 | Molnar           | N/A | N/A |
| 2018/0028215 | 12/2017 | Cohen            | N/A | N/A |
| 2018/0104097 | 12/2017 | Bacich           | N/A | N/A |
| 2019/0142370 | 12/2018 | Roy et al.       | N/A | N/A |
| 2020/0179648 | 12/2019 | Bacich et al.    | N/A | N/A |
| 2020/0397478 | 12/2019 | Bacich et al.    | N/A | N/A |
| 2021/0205582 | 12/2020 | Bacich et al.    | N/A | N/A |
| 2021/0213251 | 12/2020 | Bacich et al.    | N/A | N/A |
| 2021/0267795 | 12/2020 | Bacich           | N/A | N/A |
| 2021/0308421 | 12/2020 | Bacich et al.    | N/A | N/A |
| 2022/0218947 | 12/2021 | Bacich et al.    | N/A | N/A |
| 2022/0257903 | 12/2021 | Bacich et al.    | N/A | N/A |
| 2023/0149207 | 12/2022 | Bacich et al.    | N/A | N/A |

#### FOREIGN PATENT DOCUMENTS

| Patent No.     | Application Date | Country | CPC |
|----------------|------------------|---------|-----|
| 206167152      | 12/2016          | CN      | N/A |
| 2021634        | 12/1970          | DE      | N/A |
| 2744418        | 12/2015          | EP      | N/A |
| 2950873        | 12/2018          | EP      | N/A |
| 2391815        | 12/2003          | GB      | N/A |
| H0859504       | 12/1995          | JP      | N/A |
| H10286222      | 12/1997          | JP      | N/A |
| 2022-541680    | 12/2021          | JP      | N/A |
| WO 2001/091652 | 12/2000          | WO      | N/A |
| WO 2003/053505 | 12/2002          | WO      | N/A |
| WO 2005/102184 | 12/2004          | WO      | N/A |
| WO 2007/022055 | 12/2006          | WO      | N/A |
| WO 2014/074522 | 12/2013          | WO      | N/A |
| WO 2015/070095 | 12/2014          | WO      | N/A |
| WO 2016/205431 | 12/2015          | WO      | N/A |
| WO 2019/046800 | 12/2018          | WO      | N/A |
| WO 2019/118520 | 12/2018          | WO      | N/A |

*Primary Examiner:* Hawthorne; Ophelia A

*Attorney, Agent or Firm:* Levine Bagade Han LLP

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 18/156,268 filed Jan. 18, 2023, which is a continuation of U.S. patent application Ser. No. 17/185,449 filed Feb. 25, 2021 (issued as U.S. Pat. No. 11,583,436), which is a divisional application of U.S. patent application Ser. No. 17/067,352, filed Oct. 9, 2020 (issued as U.S. Pat. No. 11,141,308), which claims priority to U.S. Provisional Patent Application No. 62/913,160, filed Oct. 9, 2019, the contents of which are incorporated by reference herein in their entirety.

### **BACKGROUND**

(1) The apparatuses and methods disclosed herein can have utility for everting catheters that are characterized with an inner catheter, outer catheter, and everting membrane that can be connected to both catheters. The inner catheter may contain an inner lumen to pass fluid or media, drugs or therapeutic agents, instruments or devices such as intrauterine uterine devices (IUDs), endoscopes, and other catheters.

(2) For physicians and medical professionals, accessing systems for vessels and bodily cavities in patients have typically used various guidewire and catheter technologies. In some cases, the process requires the insertion of a series of mandrels or wires to increase the lumen diameter for the eventual passage of a larger bore instrument within the vessel. This technique can be referred to as “Dottering” or in the case of accessing the cervical canal and uterus, physicians will use a series of increasing diameter mandrels known as Hegar dilators. In the techniques described above, the methods involved pushing an object, mandrel, or device through the vessel to gain access to a desired region in the body. The result of pushing an object, mandrel, or device creates shear forces on the lumen wall. In some cases, the shear forces can result in trauma, pain for the patient, or perforation.

(3) In contrast, another access technology that has been used in prior art is referred to as an everting catheter. Everting catheters utilize a traversing action in which a balloon is inverted and with the influence of hydraulic pressure created by a compressible or incompressible fluid or media, rolls inside out or everts with a propulsion force through the vessel. Everting balloons have been referred to as rolling or outrolling balloons, evaginating membranes, toposcopic catheters, or linear everting catheters such as those in U.S. Pat. Nos. 5,364,345; 5,372,247; 5,458,573; 5,472,419; 5,630,797; 5,902,286; 5,993,427; 6,039,721; 3,421,509; and 3,911,927; all of which are incorporated herein by reference in their entirety. These are categorized as everting balloons and are for traversing vessels, cavities, tubes, or ducts in a frictionless manner. In other words, an everting balloon can traverse a tube without imparting any shear forces on the wall being traversed. Because of this action and lack of shear forces, resultant trauma can be reduced and the risk of perforation reduced. In addition, as a result of the mechanism of travel through a vessel, material and substances in the proximal portion of the tube or vessel are not pushed or advanced forward to a more distal portion of the tube or vessel.

(4) In addition, as the everting catheter deploys inside out, uncontaminated or untouched balloon material is placed inside the vessel wall. In the inverted or undeployed state, the balloon and the IUD are housed inside the catheter body and cannot come into contact with the patient or

physician. As the balloon is pressurized and everted, the balloon material rolls inside out without contacting any element at the entrance outside of the vessel. For the delivery of IUDs, the action of the balloon material rolling inside out also prevents the IUD to contact any element at the vaginal wall, exocervix, endocervical canal, and depending upon the depth of insertion, the internal cervical os of the patient. Another advantage of an everting balloon catheter is that the method of access is more comfortable for the patient since the hydraulic forces “pull” the balloon membrane through the vessel or duct as opposed to a standard catheter that needs to be “pushed” into and through the vessel or duct. For the delivery of IUDs, the hydraulic forces “pull” the balloon membrane and IUD through the cervix and into the uterine cavity as opposed to a standard IUD catheter tube that needs to be “pushed” into and through the cervix and into the uterine cavity.

(5) For access to the uterine cavity with larger devices, the method typically used by physicians for accessing the cervical canal in women requires the use of multiple instruments of increasing diameter. The physician will use a small uterine sound or small diameter probe or Hegar device for gaining initial entry into the uterus via the cervix. Ever increasing sizes of Hegars are used to stretch the cervical muscles until the desired internal diameter is achieved for the insertion of a secondary instrument such as an endoscope or other device. This process can be particularly difficult in some nulliparous women who are seeking contraception with an IUD or women elect to use a hormonal IUD for alleviating abnormal bleeding. Post-menopausal women can also present with very small diameter cervical canals. A cervix could be difficult to traverse as a result of prior surgery, underlying stenosis, or other anatomical configuration or tortuosity that makes the passage of instruments or Hegar dilators difficult.

(6) There are some cervical dilators that provide radial expansion to open the cervical canal to a greater internal diameter without the insertion of multiple instruments. All of these devices are predicated on first crossing or traversing the cervical canal prior to the step of radial expansion. Once traversed through the cervical canal, these devices use either mechanical means or the expansion of a balloon dilation member that is concentric on the exterior of the dilator probe. If the cervical canal is particularly tight or narrow, a small diameter probe or mandrel may be required to first cross the cervix and access the uterine cavity. As mandrels or instruments get smaller in diameter, the likelihood of perforation or a false passage increases. In any case, these cervical dilators require passage or crossing by the initial probe prior to any further radial expansion being performed.

(7) Everting catheters have been described as dilatation catheters. Representative examples of dilating everting catheters include U.S. Pat. Nos. 5,364,345 and 4,863,440, both of which are incorporated by reference herein in their entireties.

(8) Everting catheters have also been described with additional elements such as a handle for controlling instruments within an everting catheter. A representative example is U.S. Pat. No. 5,346,498 which is incorporated by reference herein in its entirety. Everting balloon catheters can be constructed with an inner catheter with an internal lumen or through-lumen (or thru-lumen). The through-lumen can be used for the passage of instruments, media, materials, therapeutic agents, endoscope, guidewires, or other instruments or devices. Representative samples of everting catheters with through-lumens are in U.S. Pat. Nos. 5,374,247 and 5,458,573. In addition, everting catheters have been described with waists or a narrowing of the balloon diameter, such as in U.S. Pat. No. 5,074,845, which is incorporated by reference herein in its entirety.

(9) Everting catheters are particularly useful for accessing the uterine cavity where the endocervical canal may be stenotic, tortuous, or contain the presence of a C-section scar or other anatomical configuration that makes the passage of instruments difficult for the physician. This in turn can lead to an uncomfortable procedure for the patient.

(10) One common gynecological procedure is the placement of IUDs for women who are either seeking a non-permanent method of birth control or medication from an intrauterine device that elutes hormonal treatment for abnormal uterine bleeding, painful periods, or other medications that

may be placed by an implant in the uterine cavity. IUDs can contain copper and can be configured in numerous configurations. In all of these cases, the physician needs to place the device within the uterine cavity.

(11) For the placement of IUDs in the uterus, IUD inserters consist of fairly stiff tubes or cannula for insertion. The IUD implant itself can be configured in a “T-shape” or “Y-shape” in its natural, uncollapsed state in which the three arms of the “T” or “Y” are constructed as rigid members that can flex, but are not easily bent in a tight radius less than 0.500”. The “T” or “Y” configuration is needed to maintain the IUD within the uterine cavity during the normal activities of the woman and otherwise more forceful activities such as exercise, coughing, and the uterine contractions that occur with menses. In these situations, the “T” or “Y” shape is needed to prevent expulsion or migration from the uterine cavity since the arms of the “T” or “Y” are designed to keep the IUD near the patient's fundus with its rounded ends approximating the bilateral cornua of the uterine cavity. Not all IUDs are “T” or “Y” shaped and other configurations including circular or coiled shaped are known or available commercially.

(12) In clinical use during device placement, the endocervix may have multiple turns and curvatures that contain tight radii curves. For placement through the endocervix and to straighten the cervical canal to reduce the amount of curvature, the physician needs to grasp the cervix and maintain counter-traction on the cervix. Besides straightening the cervix, the counter-traction facilitates pushing the IUD inserter through the endocervical canal and into the uterine cavity. Misplacements, perforations, or the inability to place the IUD, are all known and recognized outcomes or adverse events with an IUD placement procedure. The stiffness of the cannula and the IUD implant itself also leads to patient discomfort during the placement procedure. This is particularly true for women who have stenotic cervices or who are nulliparous.

(13) Once the IUD is in the proper position in the patient, the IUD inserter can have a cannula that is attached to a handle that allows the physician to translate the IUD from out of the distal end of the cannula. The handle allows the physician to perform the placement procedure with one hand.

(14) Following the placement of the IUD in the uterine cavity, the IUD inserter is withdrawn from the patient. The retrieval suture or sutures of the IUD remains in the patient's endocervical canal when sliding the inserter out of the cervix. Once removed, the physician can trim the visible sutures extending from the exocervix. The IUD sutures are visible in the patient's vagina emanating from the exocervix and can be trimmed to length as indicated by the IUD manufacturer's labeling.

(15) Also, when delivering an IUD, instruments, device, and reproductive material such as an embryo, into the uterine cavity, the access system can push cervical mucus or fluids and materials from the vagina into the uterine cavity. There is a potential that these fluids and materials from the vagina could promote bacterial infection. The action of the unrolling balloon is designed to minimize this effect.

(16) In addition, access systems for the uterine cavity can create a vacuum effect when the access system is being withdrawn or removed from the uterine cavity. This vacuum effect can unintentionally remove the reproductive material from the uterine cavity in the situation of embryo transfer. In existing systems, when the transfer catheter is retracted from a second outer or guiding catheter (e.g., the “inner” catheter), the retraction produces vacuum pressure within the uterine cavity. This vacuum pressure is created in the uterine cavity by the removal and backward movement of the transfer catheter within the inner catheter. After the embryo transfer is completed, an embryologist may inspect the transfer catheter to verify that the embryos or reproductive material was indeed deposited in the uterus and not pulled back into the transfer catheter because of the vacuum effect. The same procedure may be done for the outer catheter once this catheter is removed. For IUD placement, having a system that can potentially reduce vacuum effect can lead to more reliable and exact IUD placement.

(17) Further, everting balloons describe an action in which a balloon is inverted and, with the influence of hydraulic pressure created by a compressible or incompressible fluid or media, rolls

inside out or everts with that propulsion force. Everting balloons have been referred to as rolling or outrolling balloons, evaginating membranes, toposcopic catheters, or linear everting balloons. These are all categorized as everting balloons due to their property of traversing vessels, cavities, tubes, or ducts in a substantially frictionless manner. Everting balloons can traverse a tube without imparting any significant shear forces on the wall being traversed. Because of this action and lack of shear forces, material and substances in the proximal portion of the tube or vessel are pushed or advanced forward to a more distal portion of the tube or vessel. For example for l everting balloons in the female reproductive tract, potentially infectious substances from the vagina, cervical os or exocervix, or the legs or other anatomy of the patient, and the hands of the physician during insertion or catheter preparation, are not in contact with the everted balloon that resides in the catheter system prior to deployment in the patient. The objective of keeping the everting balloon isolated from potentially uncleanly surfaces is to reduce post-procedural infections.

#### SUMMARY OF THE INVENTION

(18) An everting balloon system is disclosed. The everting balloon system can be used for IUD placement, delivery of instruments, devices, and endoscopes, and insemination, urinary incontinence, dilation of a body lumen, for access and sealing within a body cavity, or combinations thereof. The system can have automatic deployment and disengagement. The system can have a handle for insertion. The system can have a motorized air or fluid pump or pressurization source. The system can have inner and outer catheters that can automatically disengage upon everting.

(19) The everting balloon system can have an intubating base with a locking balloon that can activate upon pressurization. The system can be a compact, low profile unit used in vivo. The system can be single use and disposable. The system can be non-irritation and non-infection causing.

(20) The everting balloon system can be used for cervical access, dilation, and the delivery of IUDs. The everting balloon system can have a system handle mechanism that can enable a one-handed operating technique by the user. The one-handed operating technique can include advancement and pressurization of the everting balloon membrane within the control of the user with one hand.

(21) The everting balloon system can be used for the insertion of drug delivery devices, or insemination, and can seal the cervix for a duration of time for the deposition of drug agent or sperm and to allow for mobility for the patient. The everting balloon system can have a decoupling mechanism configured to decouple the outer catheter and inner catheter while maintaining hydraulic pressure in an everting balloon. The system can deflate and removal the everting balloon concurrently.

(22) The system can be used to place or deliver fallopian tube inserts (i.e., intratubal inserts, such as the Essure device from Bayer Corporation) in fallopian tubes. The system can access the intramural and isthmic portions of the fallopian tube. All or part of the everting catheter system can be loaded into a hysteroscope and placed with direct endoscopic visualization.

(23) The everting catheter system can be a selective fallopian tube catheter with a curved distal end section and angled ball tip. This configuration can be performed by ultrasound or radiographic visualization.

(24) One or more fallopian tube occluding devices (e.g., the Essure device) can be loaded into the everting balloon system, for example, in the through lumen of the inner catheter. Once fully everted and placed into the fallopian tube, the everting balloon system, such as the inner catheter, can be withdrawn from the fallopian tube while leaving the fallopian tube occluding device in the fallopian tube. Once the everting balloon system is withdrawn from the fallopian tube, the fallopian tube occluding can be deployed (e.g., device anchors such as coils can be extended, or a resilient porous matrix can expand to friction fit the tube lumen). Once the fallopian tube occluding device is deployed, a central guidewire can be removed from the fallopian tube. The procedure can be



repeated for the contralateral fallopian tube.

(25) The everting balloon system can be used to access the bladder, ureters, kidneys, or combinations thereof. Devices, tools, instrumentation, endoscopes, drugs, therapeutic agents, sampling devices (brushes, biopsy, and aspiration mechanisms), or combinations thereof can be delivered through the inner catheter lumen to the target site.

(26) Specialized everting catheter systems with specific instruments, tools, or functions built or placed within the everting catheter system are also disclosed herein. Examples of such tools or instruments are biopsy devices, cytology devices, drug delivery mechanisms, fluid delivery mechanisms, endoscopes, IUDs, or other tools to be delivered into a bodily cavity, a bodily space, a potential bodily space that is created by the everting balloon mechanism, or a bodily vessel. There are several advantages to having an IUD built or placed into the everting catheter system as the delivery mechanism. The everting balloon can be used to pull the IUD implant into the uterine cavity without requiring the physician or operator to push an inserter through the endocervix and into the uterine cavity. This is particularly useful for tortuous or tight cervixes. In addition, the everting membrane rolls inside-out through passageways in a frictionless manner without imparting shear forces on the inner lumen wall. The everting balloon works to protect the body passageway from the distal end profile of the IUD while pulling the IUD into the desired location.

(27) The IUD can be fixed to the everting catheter system and automatically extends beyond the distal end of the everting balloon by being pulled by the everting balloon into the uterine cavity. During the eversion process, the IUD can be shielded from the body tissue until it extends beyond the distal end of the everting balloon. In this process the IUD will not contact the vagina, exocervix, or other fluids, mucus, or tissue in the proximal region of the endocervix. Providing the IUD at a specific distance in the everting catheter system can provide the physician the ability to direct the IUD to an exact distance from the exocervix or specific location in the uterine cavity.

(28) An IUD placement procedure can be performed or delivered in particular locations in the uterine cavity.

(29) An everting membrane for IUD placement can be designed for one-handed placement.

(30) An everting membrane for IUD placement can be designed for one-handed placement with automatic negative pressure during the release of the IUD.

(31) An everting membrane for IUD placement can be designed for one-handed placement with automatic or manual irrigation through the central lumen during the release of the IUD. The automatic irrigation can facilitate device placement by releasing the IUD from the everting membrane. Irrigation through the central lumen prior to loading the IUD within an everting catheter, or the delivery and release of the IUD in the everting membrane, by increasing the lubricity or the IUD within the everting membrane so that the IUD can slide out of the everting membrane with reduced friction. Equipping the everting catheter for IUD delivery and placement with an irrigation function is especially useful since some IUDs contain hormonal drugs, coatings, or other therapeutic agents that can be tacky when interacting against the surface of certain polymers that are useful in catheter fabrication.

(32) The irrigation mechanism, whether done automatically or manually, can be used to facilitate device visualization in the uterine cavity using ultrasonography, fluoroscopy, or direct visualization with an endoscope through the central lumen of the IUD inserter. The injection of saline as an example with the irrigation mechanism through the central lumen can provide the physician a slightly distended uterine cavity in which ultrasonographic visualization of the IUD in the uterine cavity for confirmation of IUD placement.

(33) The IUD system can have a transfer mechanism to facilitate the loading of commercially available or second party IUDs in the everting catheter. Once loaded with the IUD, the everting catheter is ready for placement into the patient's uterus. The transfer mechanism includes a loading apparatus of retrograde loading the second-party IUD into the distal end of everting membrane and a snare for capturing and retracting the IUD sutures through the central lumen of the everting

catheter. The entire mechanism is contained within a flat stand that will fit on a standard procedure prep table. In operation, the loading mechanism can facilitate loading of a second party IUD within an everting catheter prior to delivery into a patient.

(34) An everting catheter system for an IUD placement procedure can be facilitated by an aspiration system for holding onto the device during the initial steps of device loading. The aspiration system can work in conjunction with the distal end opening of a pusher through the central lumen of the everting catheter to stabilize and pull the IUD into position with the everting membrane of the everting catheter system.

(35) An everting catheter system for an IUD placement procedure can utilize a translatable outer catheter with telescoping sections that provides selected insertion depths within the uterine cavity for IUD device placement. Telescoping sections in the outer catheter can independently change and select the insertion depth of the IUD placement without altering any other component of the everting catheter system.

(36) The distal end of the everting membrane at the location of the IUD can have an echogenic marker for increased ultrasound contrast, visibility, and detection within the patient's uterus or enhanced real time visualization of IUD placement.

(37) An IUD loading system can allow the user to load a separately supplied IUD into an everting catheter system. The loading system can include a cradle, split tube, and tray fixture to facilitate IUD loading into the everting catheter system.

(38) Another embodiment uses a derivation of the loading system within the manufacturing process during the construction of an integrated everting system with a pre-loaded IUD.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIGS. 1A through 1E are longitudinal cross-sectional views of the distal end of a variation of a method for using the everting balloon system.

(2) FIG. 2A illustrates a variation of the everting balloon system in a fully everted configuration.

(3) FIG. 2B is a cross-sectional view of a variation of the system handle.

(4) FIG. 3A illustrates a variation of the distal end of the everting balloon system with the dilating balloon in a less than fully inflated configuration.

(5) FIG. 3B illustrates a variation of the distal end of the everting balloon system with the dilating balloon in a fully inflated configuration.

(6) FIG. 4A illustrates a variation of the everting balloon system with a syringe in an attached, but not yet deployable configuration.

(7) FIG. 4B illustrates a variation of the everting balloon system with the syringe in an attached and deployable configuration.

(8) FIG. 4C illustrates a variation of the everting balloon system of FIG. 4B with the plunger driver shown in cut-away.

(9) FIG. 5A illustrates a length of a variation of the everting balloon system.

(10) FIG. 5B is a partial cross-sectional view of a variation of the system of FIG. 5A.

(11) FIGS. 5C and 5D are variations of side and perspective views of a portion of cross-section A-A.

(12) FIG. 5E is an exploded view of a variation of a portion of the system handle and the drive gears.

(13) FIG. 5F is a close-up view of a variation of the system handle at the ratchet handle axle.

(14) FIG. 6A is a cross-sectional view of a variation of the system handle.

(15) FIGS. 6B through 6D are side, top perspective and cross-sectional views, respectively, of a variation of the everting balloon system with the system handle of FIG. 6A.

- (16) FIGS. 7A and 7B are exploded and perspective views, respectively, of a variation of the everting balloon system.
- (17) FIG. 8A is a cross-section view of a variation of the three-way connector and adjacent elements in a configuration to deliver media pressure to the outer catheter, for example to the everting balloon.
- (18) FIG. 8B is a cross-section view of a variation of the three-way connector and adjacent elements in a configuration to deliver media pressure to the inner catheter, for example to the dilating balloon.
- (19) FIG. 9 is an exploded view of a variation of a transfer catheter.
- (20) FIGS. 10A through 10C illustrate a variation of method for delivering material to a target site, such as reproductive material delivered to a uterine cavity.
- (21) FIGS. 11A through 11C illustrate a variation of a method for delivering material to a target site, such as reproductive material delivered to a uterine cavity.
- (22) FIGS. 12A to 12E illustrate an everting catheter for performing an IUD placement procedure with an everting membrane.
- (23) FIGS. 13A to 13I illustrate in both side views and top views additional derivations built into the distal end of the everting membrane and inner catheter.
- (24) FIGS. 14A through 14D illustrate further embodiments demonstrating the advancement and release of an IUD within an everting membrane.
- (25) FIGS. 15A through 15D illustrate an automatic one-handed eversion mechanism for IUD placement.
- (26) FIGS. 16A to 16J illustrate a variation of an everting catheter that can deliver an IUD within the uterine cavity.
- (27) FIGS. 17A to 17I illustrate a variation of an everting catheter that can deliver an IUD within the uterine cavity.
- (28) FIGS. 18A to 18C illustrate mechanisms for automatically providing negative pressure during the IUD release step of the delivery process. In addition, irrigation through the central lumen can be provided separately or in conjunction with negative pressure to facilitate the IUD release step.
- (29) FIG. 19A illustrates an everting catheter system for delivering an IUD.
- (30) FIGS. 19B to 19D are close-up views of the everting catheter system.
- (31) FIG. 20A illustrates the everting catheter system after full eversion of the balloon in the process of delivering an IUD.
- (32) FIG. 20B is a close up view of the distal end of the everted balloon and IUD.
- (33) FIG. 20C is a close up view of the proximal portion of the everting catheter system after full eversion in the process of delivering an IUD.
- (34) FIGS. 21A to 21C illustrate the process of delivering an IUD within a simulated uterine cavity model.
- (35) FIGS. 22A to 22E illustrate a packaging configuration for the transit and loading of the everting catheter system for delivering an IUD.

#### DETAILED DESCRIPTION

(36) An everting balloon system 2 (also referred to as an everting catheter system) that can be used to traverse a vessel, such as the cervical canal is disclosed. The everting balloon system 2 can be used to access the uterine cavity via the cervix. The cervical canal is a single lumen vessel that can stretch or dilate. The everting balloon system 2 can have a control system that can be operated with one hand. The everting catheter system can also traverse other locations in the body of a patient or animal for the purposes of placement of a device within a bodily cavity or lumen.

(37) FIGS. 1A through 1E illustrate that an everting catheter system 2 can have a radially outer catheter 4, a balloon membrane 6, and a radially inner catheter 8. The inner catheter 8 can have an inner catheter lumen 10 (e.g., a through-lumen). The distal end of the inner catheter lumen 10 can be open or closed. The inner catheter 8 can have the inner catheter lumen 10 or be a solid rod or

flexible mandrel. The everting balloon system **2** can have a media volume **12**. The media volume **12** can be the contiguous open volume between the inner catheter **8** and outer catheter **4** that is proximal to the balloon membrane **6**. A radially outer terminal perimeter of the balloon membrane **6** can be attached to the distal terminal end of the outer catheter **4**. A radially inner terminal perimeter of the balloon membrane **6** can be attached to the distal terminal end of the inner catheter **8**. The everting balloon system **2** can be made without an inner catheter **8**, for example with the balloon membrane **6** extending proximally out of the working area to a control device (e.g., a pump).

(38) FIG. **1A** illustrates that the everting catheter system **2** can be in an unpressurized configuration. The media volume **12** can be uninflated and unpressurized. The balloon membrane **6** can be slack.

(39) FIG. **1B** illustrates that that everting catheter system **2** can be in a pressurized and uneverted configuration. A pressurization device, such as a pump, for example at the proximal end of the everting catheter system **2** can be in fluid communication with the media volume **12**. The pressurization device can deliver a fluid media, such as a pneumatic gas or hydraulic liquid media (e.g., saline, water, air, carbon dioxide, or combinations thereof), at a media pressure **14** to the media volume **12**. The media pressure **14** in the everting balloon **2** can be from about 2 to about 5 atmospheres of pressure when in the everted configuration and higher media pressures **14** from about 5 atmospheres to 10 atmospheres are possible, for example, to provide greater everting capability for more difficult or stenotic passageways in the body.

(40) The balloon membrane **6** can inflate and be in tension. The balloon membrane **6** can block the distal port of the inner catheter lumen **10**.

(41) FIG. **1C** illustrates that the everting catheter system can be in an inflated and partially everted configuration. The inner catheter **8** can be translated distally, as shown by arrow **16**, with respect to the outer catheter **4**, and out of the outer catheter **4**. The distal terminal end of the inner catheter **8** can be proximal of the distal terminal end of the balloon membrane **6**. The distal terminal end of the inner catheter **8** can be proximal or terminal of the distal terminal end of the outer catheter **4**. The balloon membrane **6** can block the distal port of the inner catheter lumen **10** or can be open allowing fluid communication between the inner catheter lumen **10** and the target site.

(42) FIG. **1D** illustrates that the everting catheter system can be in an inflated, fully everted, and fully distally extended configuration. The inner catheter **8** can be translated distally, as shown by arrow **16**, with respect to the outer catheter **4** until the distal terminal end of the inner catheter **8** is longitudinally beyond or co-terminal with the distal terminal end of the balloon membrane **6**. The distal port of the inner catheter lumen **10** can be unobstructedly accessible and in fluid communication with the target site.

(43) In the fully inflated configuration, the balloon membrane **6** can form an inflated everting balloon **18**. The everting balloon **18** can have a balloon outer diameter **20** and balloon length **22** in the inflated and fully everted configuration.

(44) The balloon outer diameter **20** can be from about 2 mm to about 20 mm, more narrowly from about 2 mm to about 7 mm, for example about 5 mm. The outer diameter can be constant or vary along the length of the everting balloon **18**. For example, for use in the cervical canal, the most proximal portion of the everting balloon outer diameter **20** could be configured with a smaller outer diameter than the remainder of the everting balloon membrane **24**. As an example, the first proximal portion of the everting balloon **18** can have a smaller balloon outer diameter **20** such as from about 2 mm to 4 mm for a length of from about 5 mm to about 10 mm from the distal terminal end of the outer catheter **4**, and the remainder of the length (e.g., from about 4 cm to about 7 cm along the everting balloon **18**) of the everting balloon **18** can have a balloon outer diameter **20** from about 4 mm to about 7 mm. The outer diameter of the proximal end of the everting balloon **18** can have a consistent balloon outer diameter **20**, for example for delivery in the cervix or urethra, of from about 3 mm to about 6 mm, and the distal-most outer about 2 cm to about 3 cm of the

everting balloon **18** can have a balloon outer diameter **20** from about 10 mm to about 20 mm, for example to create a seal with and anchor in the internal cervical os of the uterine cavity or the bladder.

(45) The exterior surface of the balloon membrane **6** can be configured with ridges, projections, bumps, grooves, and additional surface or mechanical features, or combinations thereof, for example for increased friction or holding power within the vessel, or the entrapment of bodily fluids, cells, or tissue.

(46) The everting balloon length **22** can be from about 2 cm to about 31 cm, more narrowly from about 2 cm to about 25 cm (e.g., for use in a male urethra), yet more narrowly from about 2 cm to about 12 cm for placement of IUDs, yet more narrowly from about 3 cm to about 6 cm for invitro fertilization, insemination procedures, or the delivery of instruments and endoscopes, for example about 4 cm, about 7 cm, about 15 cm and about 30 cm.

(47) FIG. 1E illustrates that the everting catheter system can be in an inflated and partially or fully everted configuration. A device or tool **26**, liquid, gas, or combinations thereof can be translated, as shown by the arrow **28**, through the inner catheter lumen **10**, out of the distal port of the inner catheter lumen **10** and into the target site. The tool **26** can be an IUD, a biopsy tool, a scope, a sonogram probe, a plug, a cauterization tool, or combinations thereof. Suction can be applied from the proximal end of the inner catheter lumen **10**, and to the target site, for example removing debris from the target site through the inner catheter lumen **10**.

(48) To retract and reposition or remove the balloon membrane **6**, the inner catheter **8** can be pulled proximally to pull the balloon membrane **6** back within the outer catheter **4**. The balloon membrane **6** can be deflated or have media pressure **14** reduced and the entire system can be withdrawn from the target site.

(49) FIG. 2 illustrates that the everting balloon system **2** can have a system handle **30**. The system handle **30** can have a system handle connector **32**. The system handle **30** can be attached to the outer catheter **4** and the inner catheter **8**, for example at the system handle connector **32**. The system handle connector **32** can be removably attached to the outer catheter **4**. For example, the outer and inner catheters **4**, **8** and balloons can be detached from the system handle **30** and replaced. The system handle **30** can be sterilizable. Media (e.g., liquid or gas) delivered by the system handle **30** can be filled into the system handle **30** before attaching or replacing the catheters and balloons.

(50) The system handle **30** can have a rigid system handle case **34** and a rigid pump lever **36** rotatably attached to the system handle **30** case at a pump lever axle **38**.

(51) The system handle **30** can have an inlet port **40**. The everting balloon system **2** can have a pressurization source. The pressurization source can have a flexible liquid reservoir **42** or fluid supply container or bag. The fluid bag can be filled with a hydraulic and/or pneumatic fluid.

(52) The inlet port **40** can be a female luer fitting and connection. The inlet port **40** can be in fluid communication through an inlet-reservoir channel **44** with the flexible reservoir **42**. The liquid reservoir **42** can be between the rigid pump lever **36** and a rigid system handle case **34**. The inlet port **40** can extend out of the proximal end of the system handle case **34**. The inlet port **40** can be configured to attach to a liquid source (e.g., a hose, tube, or supplemental reservoir configured to deliver the liquid through the inlet port **40** and to the liquid reservoir **42**). The inlet port **40** can have a proximal check valve or one-way valve configured to allow flow to the liquid reservoir **42** and prevent backflow (e.g., proximal flow from the liquid reservoir **42** and out the inlet port **40**).

(53) The liquid reservoir **40** can be in one-way (e.g., via a check valve) or two-way fluid communication with the media volume **12**.

(54) When the liquid reservoir **42** contains liquid, the pump lever **36** can rotate away from the system handle case **34**, as shown by pump lever rotation arrows **46**, as the liquid reservoir **42** inflates. The pump lever **36** can be rotated toward the system handle case **34** to compress the liquid reservoir **42**, for example, forcing liquid from the liquid reservoir **42** and into the media volume **12**.

of the everting balloon **18**.

(55) The pump lever **36** can provide a pumping (e.g., suction) action to supply aspiration to withdraw liquid from the media volume **12** of the everting balloon **18**. A spring within the lever can facilitate the pumping action of the lever to open the lever (not shown) for each compression.

(56) The system handle **30** can have an advancement slide **48**. The advancement slide **48** can be proximally and distally translatable, as shown by arrow **50**, with respect to the system handle case **34**. The advancement slide **48** can be configured to translate the inner catheter **16** with respect to the outer catheter **4**. For example, pushing the advancement slide **48** distally can push the inner catheter **8** distally with respect to the outer catheter **4** and evert the everting balloon **18**. Pulling the advancement slide **48** proximally can pull the inner catheter **8** proximally with respect to the outer catheter **4** and retract the everting balloon **18**. The advancement slide **48** can have gear wheels, ratchets with racks, and rotating advancement screws.

(57) The advancement button can be an advancing ratchet or a roller wheel that is geared into or with the inner catheter **8** to allow for translation of the inner catheter **16**.

(58) With one hand, the physician can advance the inner catheter **8**, evert the everting balloon **18**, traverse the cervical canal with the everting balloon **18**, and access the uterine catheter through the inner catheter lumen **10**.

(59) The fluid reservoir **42** can be pressurized prior to placement of the distal tip of the outer catheter **4** at the cervix. The fluid reservoir **42** can have a proximal check or one-way valve on the proximal portion of the handle. The proximal check valve is the connection point for the physician to pressurize the system. The distal portion of the fluid bag can be attached to a distal pressure check valve **52** that can open when pressure from the fluid bag is at or above a distal check valve limit pressure, for example about 1 atmosphere of pressure from the liquid reservoir, and then deliver liquid and pressure from the liquid reservoir **42** to fill and pressurize the media volume **12** of the catheters and everting balloon **18**. The distal pressure check valve **52** can be a one-way valve allowing hydraulic or pneumatic fluid or media to go from the fluid reservoir **42** to the media volume **12** of the catheters and everting balloon **18**. Higher and lower atmosphere pressure ratings from 1 atmosphere are also possible for the distal pressure check valve **52** such as from about 0.5 atmospheres to about 2 atmospheres.

(60) During pressurization of the fluid reservoir **42** (e.g., by pumping with the pump lever **36** or from the inlet port via the proximal check valve **54**), pressures greater than a reservoir limit pressure (e.g., 1 atmosphere) of the distal pressure check valve **52** can open the distal pressure check valve **52** and allow fluid media to flow from the liquid reservoir **42** into the media volume **12** of the catheters and everting balloon **18**. The pressurization in the media volume **12** of the catheters and everting balloon **18** can unroll and evert the everting balloon **18** under hydraulic force. Excess media can remain in the fluid reservoir **42** after the everting balloon **18** fully everts.

(61) The distal pressure valve **52** can be connected to a three-way connector **56** (e.g., Y-connector or T-connector) that has a hemostasis valve **58**, for example a Touhy-Borst valve. Thus the fluid reservoir **42** can stage or hold additional potential hydraulic pressure to be stored in the system for the user (e.g., physician) to use as needed by rotating the pump lever **46** without a change of hand position or the use of a second hand.

(62) The inner catheter **8** can extend through the three-way connector **56**. The inner catheter **8** can translate (i.e., advance and retract) through the three-way connector **56** while maintaining a seal (i.e., without the media volume **12** of the catheters or everting balloon **18** losing pressure). The inner catheter **8** (e.g., if a solid rod or mandrel) can be configured to withstand hydraulic pressures of up to about 5 atmospheres or up to about 10 atmospheres during the everting process and translational (e.g., advancement, retraction, tensile, compression, or combinations thereof) forces of up to about 2 pounds or up to about 5 pounds without deformation. As an example, during the everting process the inner catheter **8** with an inner catheter lumen **10** (e.g., a through lumen) could withstand media pressures **14**, tensile and compressive forces, and rotational forces as the everting

balloon membrane **6** traverses curved or tortuous anatomy, to allow for the passage of an instrument, catheter, media, or materials within the through lumen. Movement of the advancement button on the handle moves the inner catheter **8** within the three-way connector **56** and through the outer catheter **4**. The everting balloon **18** can then evert and roll out of the outer catheter **4** and traverse the target site (e.g., the cervical canal).

(63) After accessing the target site, for example, the user can activate the pressure release control **60** to release or reduce the pressure from the media volume **12** thereby deflating or reducing the outer diameter of the everting balloon **18**, and/or manually withdraw the everting balloon **18** and inner catheter **8** by retracting the advancement slide **48** or pulling the system handle **30** proximally, and therefore the remainder of the system.

(64) Once the biological lumen to be traversed (e.g., the cervical canal, or urethra) is traversed by the everted balloon **18**, the everting balloon system **2** can increase the pressure in the everting balloon **18**, for example increasing the diameter of the everting balloon **18**, or while maintaining a constant diameter everting balloon **18** (e.g., for a fiber-reinforced everting balloon **18** or a balloon membrane **6** constructed from a less distensible material). The pump lever **36** can be compressed to increase pressure in the fluid reservoir **42** builds and exits the distal pressure check valve **52**. The proximal check valve **54** can prevent or minimize the fluid media (e.g., pneumatic or hydraulic pressure) from leaking or bleeding in the proximal direction and out of the inlet port **40**.

(65) The user can rotate the pump lever **36**, for example increasing the pressure in the fluid reservoir **42**, the media volume **12**, and the everting balloon **18**. The balloon outer diameter can then increase, further pushing open the diameter of the biological lumen. For example, the everting balloon **18** can dilate the cervix and cervical canal. Tools such as endoscopes, instruments, Hegars, other devices to increase the diameter of the cervix further, or combinations thereof, can then be inserted into the dilated cervical canal concurrent with the everting balloon system **2** being located in the cervical canal or subsequent to the everting balloon system **2** being withdrawn from the cervical canal.

(66) The pump lever **36** can deliver tactile feedback to the user indicating the pressure of the everting balloon **18**. The everting balloon system **2** can have a pressure gauge indicating the pressure in the media volume **12**, such as in the liquid reservoir **42** and/or the media volume **12** in the catheters and everting balloon **18**.

(67) The system handle **30** can have a pressure release control **60**, such as a toggle lever or knob. The pressure release control **60** can release fluid from the liquid reservoir **42** and/or media volume **12** of the catheters and everting balloon **18**.

(68) The pressure release control **60** can be connected to the hemostasis valve **58**. The hemostasis valve **58** can have a seal or sealing gasket. The pressure release control **60** can be configured to open and close the sealing gasket by rotating the sealing cap, or open a connection to a separate drainage tube (not shown) in fluid communication with the media volume **12**.

(69) The pressure release control **60** can be on the handle **30** positioned by the user's thumb position, distal to and collinear with the movement of the advancement slide **48**. The pressure release control **60** can be operated by the same hand as the user is operating the advancement slide **48** and pump lever **36**.

(70) The pressure release control and handle can be used to advance and deliver an IUD with one hand by the user.

(71) The user can perform the following operations of the everting balloon system **2** with a single hand (e.g., without their other hand or another operator) without a change of hand position: a. pressurize the liquid reservoir **42**; b. position or place the distal end of the everting balloon system **2** at the patient's cervix; c. control the everting balloon system **2** position throughout use; d. advance the inner catheter **8** and balloon membrane **6**; e. increase the diameter of the everting balloon **18** by pumping additional hydraulic pressure from the fluid reservoir **42**; f. retract the inner catheter **8** and balloon membrane **6**; and g. activate the pressure release control **60** to remove or

release pressure from the everting catheter system.

(72) Structurally, the buttons and actuators to enable these functions can be positioned on the handle to allow for the operator to manipulate these features without a change of hand position or requiring the use of the other hand. For instance, advancement and retraction of the inner catheter **8** can be performed by a slide mechanism or gear wheels that are located on the upper side of the handle approximately 4 inches from the proximal end of the handle or handle grip. Levers and ratchet mechanisms can be located on the lower or underneath side of the handle at a distance of from about 2 inches to about 4 inches from the proximal end of the handle grip. Additional actuators can be placed on the lateral sides of the handle grip from about 3 inches to about 4 inches from the proximal end of the handle grip or on the upper or lower portions of the handle grip from about 3 inches to about 4 inches from the proximal end. The button and actuator position can be palpable for the operator without requiring visual confirmation, thereby allowing the user to maintain eye contact with the patient or visualization source such as an endoscopic monitor or ultrasound image.

(73) During the use of the everting balloon system **2**, the user can utilize their other hand for handling an ultrasonic probe, a tenaculum (e.g., if the cervix is difficult to access by anatomical reasons or is severely retroverted or anteverted), stabilizing the patient or other instruments, or combinations thereof.

(74) FIG. **3A** illustrates that the inner catheter **8** can be attached to a dilating balloon **62** or inner catheter balloon. The dilating balloon **62** can be radially inside of the everting balloon **18**. The distal end and the proximal end of the dilating balloon **62** can be attached and sealed to the inner catheter **8**. The inner catheter **8** can have a dilating balloon port **64** longitudinally within the dilating balloon **62**. The dilating balloon port **64** can be in fluid communication with a fluid pressure source at the proximal end of the everting balloon system **2**, for example in or attached to the system handle **30**. The dilating balloon **62** can be inflated and deflated through the dilating balloon port **64**.

(75) The dilating balloon **62** can be more, the same, or less compliant than the everting balloon **18**. The everting balloon **18** wall can be thicker, thinner, or the same thickness as the dilating balloon **62** wall. The everting balloon **18** can be made from one or more polymers including silicone, urethane, rubber, latex, polyethylene, polyolefin, irradiated polyolefin combined with ethylene vinyl acetate, co-polymers such as polyether block amide (PEBA, also known as Pebax), a fiber-reinforced polymer, PET, nylon, or combinations thereof. The dilating catheter can be made from any of the materials mentioned for the everting balloon **18**.

(76) The everting and/or dilating balloon membrane **6** can have a thickness from about 0.001 in to about 0.004 in.

(77) The everting and/or dilating balloon **18**, **62** can be internally coated with a lubricious material such as silicone oil, mineral oil, other lubricant, or combinations thereof. The lubricious coating can reduce the friction within the balloon during eversion.

(78) The exterior of the everting and/or dilating balloon **18**, **62** can be smooth, for example the balloon can be made by tubing extrusion. The balloons can be blow molded. For example, the exterior surface of the balloon can have ridges or other surface protrusions, for example to increase friction or holding forces in the target body lumen (e.g., cervical channel or urethra). The outer diameter of the balloons can vary dimensionally. For instance, the most distal portion of the everting balloon **18** can be manufactured with a larger outer diameter to accommodate larger vessel sizes or inflation that can extend into the bladder.

(79) During use, the everting balloon **18** can pull the inner catheter **8** into the endocervical canal. When the everting balloon **18** is deployed into the cervical channel, the dilating balloon **62** can be positioned in the cervical channel.

(80) FIG. **3B** illustrates that the dilating balloon **62** can be inflated by delivering pressurized fluid through the dilating balloon inflation port **64**. The dilating balloon **62** can expand inside of the



everting balloon **18**. The dilating balloon **62** can inflate to a dilating balloon diameter **66**.

(81) The dilating balloon **62** can have a predetermined or molded size and shape. For example, the dilating balloon **62** can have a dilating balloon diameter **66**. For example, the maximum dilating balloon diameter **66** or maximum everting balloon diameter can be from about 2 mm to about 12 mm, and for some applications, up to about 20 mm in diameter (e.g., for use in a cervix), and more narrowly from about 2 mm to about 10 mm (e.g., for use in a urethra), more narrowly from about 6 mm to about 12 mm, yet more narrowly from about 2 mm to about 7 mm (e.g., for use in a urethra), yet more narrowly from about 3 mm to about 4 mm (e.g., for use in a male urethra). The dilating balloon **62** can inflate to a preset outer diameter.

(82) (The dilating balloon outer diameter **66** can be equal to or less than the dilating diameter needed for the body lumen, such as the cervix.) The everting balloon **18** can have a maximum everting balloon diameter equal to or less than the maximum dilating balloon diameter **66**.

(83) The dilating balloon **62** can be inflated to the same or a higher pressure than the everting balloon **18**. For example, the dilating balloon **62** can have a dilating balloon pressure from about 4 atmospheres to about 12 atmospheres of pressure, and up to about 20 atmospheres of pressure, for example for disrupting a pathological stenosis or condition within a bodily lumen.

(84) When the dilating balloon **62** is inflated, the everting balloon **18** can stretch due to the expanding dilating balloon **62** to the dilating balloon diameter **66**. The inflation media within the everting balloon **18** can remain inside the balloon or be withdrawn before, during, and/or after inflation of the dilating balloon **62**. Due to the frictional forces of the everting balloon membrane **6** on the bodily lumen in the everted state, for example, the everting balloon membrane **6** can serve to maintain the position of the dilating balloon **62** during the dilation process without unintentional advancement or retraction of the system within the bodily lumen during the dilatation process.

(85) The dilating balloon **62** can inflate and tear or break the everting balloon **18** as the everting balloon diameter expands beyond the strain limit for the everting balloon **18**. The inflation media within the everting balloon **18** can remain inside the balloon or be withdrawn before, during, and/or after inflation of the dilating balloon **62**, for example exiting the everting balloon **18** can exit when the everting balloon **18** tears open.

(86) The everting balloon **18** can break or tear along an intentional line upon the inflation of the dilating catheter. For example, the everting balloon **18** can be torn by a mechanical instrument on or within the outer catheter **4**, a sharp implement on the proximal portion of the inner catheter **8** that becomes active upon full eversion and inflation of the dilating balloon **62**, and/or further advancement of the inner catheter **8** that disengages the attachment or bond between the everting balloon **18** and the inner catheter **8** on the distal end of the inner catheter **8**. The tearing or splitting of the everting balloon **18** can be done by weakening the everting balloon **18** with a mechanical indentation or seam on the balloon membrane **6** that splits upon reaching a specific strain limit, such as along a helical line, lateral line, longitudinal line, or combinations thereof. The everting balloon membrane **24** can be manufactured with increased longitudinal axial orientation of the molecular structure by tensioning or expanding the membrane along the longitudinal axis of the balloon during the balloon forming process which can promote a longitudinal break if the everting balloon membrane **24** splits or tears. A radial tear in the everting balloon **18** can be promoted by manufacturing the balloon membrane **6** with greater radial orientation of the molecular structure by radially expanding or tensioning the balloon membrane **6** during the balloon forming process.

(87) The system handle **30** can hold the inflation media to be delivered to and from the everting balloon **18** and the dilating balloon **62**. The inflation media can be in the liquid reservoir **42** (e.g., the fluid bag or a syringe piston). The inflation media can be delivered, for example via valves, to the dilation balloon after the inflation and eversion of the everting balloon **18**. The system handle **30** can have gear wheels or a ratchet configured to advance the inner catheter **8**. The outer catheter **4** can extend about 25 cm distal to the system handle **30**. The system handle **30** and actuators can inflate the everting balloon **18** and dilating balloon **62** from control with one hand.

(88) The dilating balloon **62** can be positioned into and dilate the cervix.

(89) FIGS. **4A** through **4C** illustrate that the inner catheter **8** can be in a fully retracted position inside of the outer catheter **4**.

(90) FIG. **4A** illustrates that the system handle **30** can have a pump lever **36**, such as a ratchet handle **68**, a syringe connector **70**, and a plunger drive plate **72**. The ratchet handle **68** can have a finger grip, trigger, lever, pump mechanism, or combinations thereof. The fluid reservoir can be a syringe **74**. The syringe **74** can have a volume from about 5 cc to about 20 cc, for example about 5 cc or about 20 cc. An open distal port of the syringe can be attached to and in fluid communication with the syringe connector **70**. The syringe connector **70** can have the distal pressure valve **52**. The syringe connector **70** can be rotatably attached to the system handle case **34**. The syringe **74** can have a plunger **76** longitudinally translatable with the remainder of the syringe **74**. The syringe **74** can be filled with any media disclosed herein, such as saline, air, gas, or combinations thereof. The liquid reservoir **42** can have two separate syringes **74**, each attached to and in fluid communication with the same or different syringe connectors **70**. For example, a first syringe can be in fluid communication with the everting balloon **18**, and the second syringe can be in fluid communication with the dilation balloon **62**.

(91) The syringe **74** can be locked to the syringe connector **70**.

(92) The outer catheter **4** can have an outer catheter distal tip **78**. The outer catheter distal tip **78** can be, for example, an atraumatic tip such as an acorn tip or stop. The outer catheter distal tip **78** can be configured to prevent insertion of the outer catheter **4** too far into the target biological lumen (e.g., the endocervix).

(93) The outer catheter distal tip **78** can have an outer catheter distal port **80**. The outer catheter distal port **80** can be large enough to allow the inner catheter **8** and balloons to pass through.

(94) FIG. **4B** illustrates that the syringe connector **70** and syringe **74** can rotate, as shown by the arrow, so the longitudinal axis of the syringe **74** can be parallel or collinear with the longitudinal axis of the outer catheter **4**. The syringe connector **70** can be angularly fixed with respect to the rest of the system handle **30**. The plunger drive plate **72** can be rotated and/or translated to contact or almost contact the proximal end of the syringe plunger **76**.

(95) FIG. **4C** illustrates that the system handle **30** can have a plunger driver **82**. The plunger driver **82** can have a linear rack or plunger drive screw **84**, plunger drive collar **86**, and plunger drive plate **72**. The ratchet handle **68** can be squeezed to rotate the plunger drive screw **84**, as shown by arrow **87**, or linear rack. The plunger drive screw **84** or linear rack can be configured to translate the plunger drive collar **86**. For example, the plunger drive collar **86** can have internal threads engaging with outer threads of the plunger drive screw **84**. The plunger drive collar **86** can be translatablely fixed to the plunger drive plate **72**. The plunger drive collar **86** and plunger drive plate **72** can translate distally with respect to the remainder of the syringe **74** when the ratchet handle **68** is squeezed. The plunger drive plate **72** can be in contact with and press the plunger **76** in a distal direction as shown by arrow.

(96) The ratchet handle **68** can have a ratchet to prevent reversing the direction of the plunger driver, for example to prevent proximal translation of the plunger **76**. A release lever can be rotated or deployed to release the ratchet mechanism for disengagement of the assembly, withdrawal of the system, or redeployment. The ratchet handle **68** can have no ratchet or a two-way ratchet, for example controlling the direction of the plunger driver **82**, for example to allow proximal and distal translation of the plunger **76**. The plunger drive plate **72** can be fixed to or touching but unfixed to the plunger **76**.

(97) Squeezing the ratchet handle **68** can depress the syringe plunger **94**. Depressing the syringe plunger **94** can force inflation media from the syringe **74** to the media volume **12** of the dilation and/or everting catheter **18**, for example pressurizing the respective balloons.

(98) FIGS. **5A** through **5F** illustrates that the system handle **30** can have a stop cock and check valve **88** extending from the three-way connector **56**. The stop cock and check valve **88** can be in

fluid communication with the media volume **12**. The stop cock and check valve **88** can be outside (as shown) or inside of the system handle case **34**. The stop cock and check valve **88** can be accessed to add media, remove media, or check the pressure of the media in the media volume **12**. (99) The system handle **30** can have one or more syringe detents **90**. The syringe detents **90** can removably attach to a portion of the syringe **74** to prevent or minimize longitudinal translation of the syringe **74** with respect to the system handle case **34**. The syringe detent **90** can be configured to allow the syringe **74** to slide in and out of the detent transverse to the longitudinal axis of the syringe **74**.

(100) The system handle case **34** can have a deflecting plate **92**. The outer and/or inner catheters **4**, **8** can press against the deflecting plate **92**. The deflecting plate **92** can alter or deflect the path of the outer and inner catheters **4**, **8** towards the longitudinally axial direction of the target site. The deflecting plate **92** can have a molded or formed groove, pins, plate, panel, or combinations thereof. The outer catheter **4** can be manufactured with a preset curve to accommodate the curved path within the system handle case **34**.

(101) The system handle case **34** can have a handle grip **96**. The inner catheter **8** can have a linear inner catheter grip length **98**. The inner catheter grip length **98** can be a length of the inner catheter **8** in the uneverted state in the handle grip **96**. The inner catheter grip length **98** can be about 12 cm of inner catheter **8** in the uneverted state, for example corresponding to an eversion length for the inner catheter grip length **98** of about 6 cm (e.g., about 50% of the inner catheter grip length **98**) of everted balloon membrane **24**. Alternatively, the inner catheter **8** can be configured to coil up on wheel, have telescoping segments, or have folding and unfolding segments, to reduce the amount of distance needed within a system handle case **34** to accommodate the length of inner catheter **8** in the uneverted state.

(102) The system handle **30** can have a reservoir-catheter channel **100**, for example in fluid communication with the distal end of the syringe **74** and the proximal end of the inner catheter **8**. The reservoir-catheter channel **100** can be a tube from the syringe connector **70** to the inner catheter **8**.

(103) The system handle **30** can have an access channel **102** extending from an external surface of the system handle connector **32** to an external surface of the system handle case **34**. The access channel **102** can proximally terminate at a proximal access port **104**.

(104) The inner catheter **8** can extend through the access channel **102**. One or more tools or fluids can be inserted through, and/or suction can be applied to, the proximal access port **104** and access channel **102** into and through or adjacent to the inner catheter **8**.

(105) The system handle **30** can have one or more drive gears **106**. The drive gears **106** can be on one or opposite sides of the access channel **102**. The drive gears **106** can encroach or impinge into the access channel **102**. The drive gears **106** can be rotatably attached to the system handle case **34** via drive gear axles **108**. The drive gears **106** can have toothed gear sections and drive gear grooves **124**. The inner catheter **8** can extend through the drive gear grooves **124**. The drive gears **106** can frictionally push and pull the inner catheter **8**. One or more of the drive gears **106** can extend and be exposed out of the system handle case **34**. For example, the exposed drive gears **106** can be rotated by pressing on the exposed drive gear **106** with the user's palm or digit (e.g., thumb). The exposed drive gear **106** can be interdigitally engaged with one or more non-exposed drive gears **106**. Rotating a first one of the drive gears **106** can rotate other drive gears **106** interdigitally engaged with the first drive gear **106**.

(106) The system handle case **34** can have a system handle case first lateral portion **110** and a system handle case second lateral portion **112**. The system handle **30** can be made by attaching the system handle case first lateral portion **110** to the system handle case second lateral portion **112**. Each drive gear axle **108** can be rotatably attached to the system handle case first lateral portion **110** and the system handle case second lateral portion **112**.

(107) The pump lever axle can be a ratchet handle axle **114**. The ratchet handle **68** can rotate

around the ratchet handle axle **114**.

(108) The system handle **30** can have a plunger drive rack **116**. The plunger drive rack **116** can be fixed to the plunger drive plate **72**. The plunger drive plate **72** can extend perpendicularly from the proximal end of the plunger drive rack **116**. A side of the plunger drive rack **116** facing toward the plunger drive plate **72** can have unidirectional or bidirectional drive teeth **118**.

(109) The system handle **30** can have a ratchet handle spring **120** compressed between the system handle case **34**, and/or the ratchet handle **68**, and/or a ratchet arm **122**. The ratchet handle spring **122** can reset the ratchet handle **68**, for example by rotating the ratchet handle **68** forward, after the ratchet handle **68** has been squeezed.

(110) The system handle **30** can have the ratchet arm **122** or actuating pawl. The ratchet arm **122** can be mechanically attached to the ratchet handle **68**, for example to the handle spring **120**. The ratchet arm **122** can be in a track limiting motion of the ratchet arm **122** to translation in the longitudinal direction with respect to the syringe **74**. The proximal terminal end of the ratchet arm **122** can be curved in a u-shape. The terminal end of the ratchet arm **122** can press against a ratchet tooth. The ratchet arm **122** can be configured to pull the plunger drive rack **116** distally when the ratchet handle **68** is squeezed. The ratchet arm **122** is configured to move proximally with respect to the plunger drive rack **116** when the ratchet handle **68** is returned to a reset position.

(111) The system handle **30** can have a locking pawl (not shown) can be spring-loaded between the system handle case **34** and the plunger drive rack **116**, for example, allowing distal translation of the plunger drive rack **116** and preventing proximal translation of the plunger drive rack **116** except when the locking pawl is manually released from the plunger drive rack **116** by the release lever **126**.

(112) The outer catheter **4** can have an outer catheter length **128**, as shown in FIG. 5B. The outer catheter length **128** can be from about 4 cm to about 35 cm, more narrowly from about 10 cm to about 24 cm, for example about 17 cm.

(113) FIGS. 6A through 6D illustrate that the system handle **30** can have an inner catheter drive tray **130** translatably attached to the system handle case **34**. A proximal length of the inner catheter **8** can extend proximally from the system handle case **34**. The proximal length of the inner catheter **8** can be in, on, or adjacent to the inner catheter drive tray **130**.

(114) The syringe **74** can have a syringe loading connector **132**, such as a luer connector, at the terminal distal or proximal end of the syringe **74** (e.g., the end further from the system handle case **34**). A delivery tube **133** or delivery device can be attached to the syringe loading connector **132** and pressurized media can be delivered through the syringe loading connector **132** into the syringe **74**.

(115) The delivery tube **133** or delivery device can be disconnected from the syringe loading connector **132** before deploying the everting balloon **18**, as shown in FIG. 6C. The delivery tube **133** can wrap inside the handle grip **96** and connect the syringe **74** and its pressurization media to the three-way connector **56** and the hemostasis valve **58** or inlet port **40** for the dilation balloon **62**.

(116) The proximal terminal end of the inner catheter **8** can be attached to the proximal access port **104**. The proximal end of the inner catheter drive tray **130** can have one or more access port detents **134**. The access port detents **134** can attach to the proximal access port **104**. The access port detents **134** can removably attach to a portion of the proximal access port **104** to prevent or minimize longitudinal translation of the proximal access port **104** with respect to the inner catheter drive tray **130**. The access port detent **134** can be configured to allow the proximal access port **104** to slide in and out of the access port detents **134** transverse to the longitudinal axis of the inner catheter drive tray **130**.

(117) The inner catheter drive tray **130** can be translated along the longitudinal axis of the inner catheter drive tray **130** to translate the inner catheter **8** (e.g., advance the inner catheter **8** into the target site). The inner catheter can deliver an IUD, instrument, device, endoscope, or a dilating balloon.

(118) The system handle case **34** can have a fluid connection between the syringe **74** and the outer catheter **4**, as disclosed herein.

(119) The ratchet arm **122** can extend away from the drive rack **116** to form a release lever **126**, as shown in FIG. **6A**. One or more other release levers **126** can extend from other locations on the system handle **30**, as shown in FIGS. **6B** and **6D**. The release lever **126** can be rotated to disengage the ratchet arm **122** from the drive rack **116**.

(120) The ratchet handle **68** can have a safety lock hole **136**. A safety lock having a cable or rod can removably extend through the safety lock hole **136**, for example to create an interference fit against the system handle case **34** and prevent rotation of the ratchet handle **68**, for example preventing unintentional or premature media delivery from the syringe **74**.

(121) The ratchet handle **68** can be laterally split into a catheter sub-handle **138** and a media sub-handle **140**. The catheter sub-handle **138** can be configured to control the advancement of the inner catheter drive tray **130**. The media sub-handle **140** can be configured to control the pressure of media delivery from the syringe **74**. The catheter sub-handle **138** can be attached to an inner catheter drive rack. The media sub-handle can be attached to a plunger drive rack.

(122) The ratchet handle **68** can control the syringe **74** for applying media pressure to the everting balloon **18** and dilating balloon **62**, and independently control the translational movement of the inner catheter **8**.

(123) FIGS. **7A** and **7B** illustrate that the inlet port **40** can have a female luer connector. The system handle connector **32** can have a female luer connector. The outer catheter distal tip **78** can have a soft rubber or polymerized acorn tip, for example, to assist in stabilizing the everting system **2** at the opening of the bodily lumen or preventing unintentional advancement of the outer catheter **4** within the bodily lumen.

(124) The reservoir-catheter channel **100** can extend from the three-way connector **56** and out of the system handle case **34**. The proximal terminal end of the reservoir-catheter channel **100** can be attached to a female luer connector and/or the distal pressure valve **52**. The distal pressure valve **52** and/or female luer connector can be connected to the liquid reservoir **42** (not shown).

(125) FIG. **8A** illustrates that the three-way connector **56** can have a hemostasis valve **58**. The three-way connector **56** can have or be a Touhy-Borst Y-connector. The inner catheter **8** can extend through the three-way connector **56**.

(126) The three-way connector **56** can have a distal gasket **142** between the reservoir-catheter channel **100** and the system handle connector **32**. The distal gasket **142** can have a cylindrical distal gasket port **144** extending through the radial middle of the distal gasket **142**. The distal gasket port **144** can have a distal gasket port diameter.

(127) The three-way connector **56** can have a proximal gasket **146** proximal to the distal gasket **142**. The proximal gasket **146** can be between the reservoir-catheter channel **100** and the proximal outlet through which the inner catheter **8** proximally exits the three-way connector **56**. The proximal gasket **146** can be more, the same, or less compliant than the distal gasket **142**. The proximal gasket **146** can have a cylindrical proximal gasket port **148** extending through the radial middle of the proximal gasket **146**. The proximal gasket **146** can have a proximal gasket port diameter.

(128) The inner catheter **8** can have an inner catheter small diameter length **150** and an inner catheter large diameter length **152** proximal to the inner catheter small diameter length **150**. The inner catheter **8** can have an inner catheter proximal inflation hole **154** at the distal end of the inner catheter large diameter length **152**. The inner catheter proximal inflation hole **154** can be in fluid communication with the open distal end of the inner catheter lumen **10** and/or the dilating balloon port **64**.

(129) Positive media pressure **14** or flow can be delivered, as shown by arrows, through the reservoir catheter channel **100** to the three-way connector **56**. The inner catheter large diameter length **152** can occlude, plug, and/or seal the proximal gasket port **148**. The positive media pressure

14 or flow can be delivered through the gap between the outer diameter of the inner catheter **8** (e.g., along the inner catheter small diameter length **150**) and the inner diameter of the distal gasket port **144** and to the media volume **12** between the outer catheter **4** and the inner catheter **8**, for example to the everting balloon **18**.

(130) FIG. **8B** illustrates that the inner catheter **8** can be translated distally, as shown by arrow, at least until the inner catheter large diameter length **152** moves into the distal gasket port **144**. The inner catheter large diameter length **152** can slide through the proximal gasket port **148**. The inner catheter large diameter length **152** can occlude, plug, and/or seal the distal gasket port **144** and/or against the distal gasket **142**. The media **155** flow from the reservoir-catheter channel **100** can be forced to flow into the inner catheter proximal inflation hole **154**. The media **155** can flow down the inner catheter lumen **10**, for example to the dilating balloon **62**.

(131) An exemplary procedure for delivering an IUD (not shown) or dilating a body lumen such as the cervical canal can include: 1. The syringe **74** can be loaded onto the system handle **30**. The system handle **30** can be a separate, reusable item in which the everting catheter and syringe filled with media **155** can be attached to the remainder of the system before use. Alternatively, the system handle **30** can come supplied to the end user preassembled with the remainder of the system and pre-filled, or combinations thereof. 2. The distal end of the everting balloon system **2** can be placed at the exocervix. 3. The ratchet handle **68** can be depressed. The first one to two clicks of the ratchet (i.e., as the locking pawl passes over ratchet teeth) can depress the syringe plunger **94** and pressurize the everting balloon **18**. The everting balloon **18** can be pressurized to 4 to 6 atmospheres. 4. The ratchet handle **68** can be depressed further (or released to rotationally reset and then depressed further). The next sets of clicks on the ratchet handle **68** can indicate advancement the inner catheter **8**. This can be accomplished by the ratchet mechanism rotating gear wheels on the inner catheter **8** and/or translating a linear rack to advance the inner catheter **8**. 5. The ratchet handle can be depressed further (or released to rotationally reset and then depressed further). The advancement of the inner catheter **8** can continue until the everting balloon is fully deployed and everted. The dilation balloon **62** can be positioned on the distal end of the inner catheter **8**. 6. The ratchet handle **68** can be depressed further. The next click of the ratchet can de-pressurize the everting balloon **18** or deliver an IUD (not shown). 7. The ratchet handle **68** can be depressed further. The next click of the ratchet can change the pressurization outlet of the syringe **74** from the everting balloon **18** to the dilation balloon **62** or this action can deliver an IUD (not shown). This can be accomplished, for example, by: a. rotating a valve with the ratchet mechanism, b. manually rotating the valve, and/or c. advancing the inner catheter **8** to where the inner catheter proximal inflation hole **154** or port is exposed to the inflation media, such as shown in FIGS. **8A** and **8B**. 8. The ratchet handle **68** can be depressed further. The next sets of clicks on the ratchet can indicate the inflation of the dilatation balloon **62**. 9. The dilatation balloon **62** may rupture the overlying everting balloon **18**. 10. The amount of force in the biological lumen dilatation can be governed by a pressure relief valve or by the amount of volume of media **155** that can be placed within the dilatation balloon **62**. The dilatation pressure can be monitored by a pressure gauge in or attached to the system handle case **34**. The dilation balloon **62** can dilate the cervix with from about 6 atmospheres to about 20 atmospheres. The dilation balloon **62** can initially deliver about 10 atmospheres to about 12 atmospheres with a reduction in pressure as the cervix dilates and the dilatation process is completed. The system can deliver a known volume of media **155** into the dilation balloon **62** irrespective of quantifying or measuring the media pressure **14**. 11. The dilatation process may be observed by ultrasound or radiographic imaging. 12. A pressure relief button on the system handle **30** can be activated to remove or reduce dilatation pressure in the media volume **12** in the inner catheter lumen **10**. 13. The syringe plunger **94** may be retracted to draw vacuum from the inner catheter lumen **10** and dilation balloon **62**, for example loosening the dilation balloon **62** from the cervix, and/or deflating the dilation balloon **62**, for example to facilitate removal of the everting balloon system **2** from the cervix. 14. The everting balloon system

2 can be re-pressurized, for example if additional dilatation force is desired in the cervix. For instance, if an additional stenosis in the cervix is visible, the dilatation balloon **62** can be repositioned and inflated in the additional stenosis area.

(132) The everting catheter system can access a bodily cavity (e.g., the uterine cavity or fallopian tubes) to deliver or introduce of tools (e.g., IUDs and instruments), reproductive (e.g., embryos, in vitro fertilization (IVF) or insemination products, such as hormones) media **155** or material, contrast media, dye, therapeutic agents, sclerosing agents to treat the endometrium, insufflation media, or combinations thereof to the cavity. For example, reproductive media can be delivered with a transfer catheter inserted through the inner catheter lumen **10** to the uterine cavity.

(133) FIG. **9** illustrates that a transfer catheter **156** or insemination catheter can have a transfer connector **158**, such as a female luer connector, a strain relief length **160**, and a transfer tube **162**. The transfer tube **162** can hold the reproductive media. The transfer tube **162** can have a proximal length having a proximal length diameter larger than a distal length diameter of a distal length of the transfer tube **162**. A delivery force, for example a positive fluid pressure, can be delivered through the transfer connector **158** and strain relief length **160** to push the contents of the transfer tube **162** into the target site.

(134) The transfer catheter **156** can attach to or inserted through the inlet port **40**. The transfer tube **162** can hold an embryo, for example for in vitro fertilization or IVF. The embryo transfer catheter **156** can deliver embryos through the system and to the uterine cavity. The transfer catheter **156** can hold spermatozoa and through the system and to the uterine cavity for intrauterine insemination procedures. The transfer catheter **156** can hold and deliver other materials the deposition of drugs, therapeutic agents, instruments, endoscopes, cytology brushes, other catheters, or combinations thereof through the system and into the uterine cavity. The transfer catheter **156** can be connected to a vacuum source for the aspiration of materials from the uterine cavity or other bodily cavities and lumens.

(135) The transfer catheter **156** and/or materials can be loaded in the inner catheter lumen **10** prior to everting the everting balloon **18** within the vessel or bodily cavity. For example in the case of delivery of reproductive material in the uterine cavity, the transfer catheter **156** can be loaded with washed and prepared semen in the transfer tube **162** and the transfer catheter **156** can be placed in the inner catheter lumen **10**.

(136) A guidewire can be inserted through the transfer catheter **156** and/or the remainder of the system, for example to direct the tube or system to the target site **164**. The guidewire can be used for recanalization.

(137) The inner catheter **8** can be extended and the everting balloon **18** can evert and unroll through the cervix and into the uterine cavity. Concurrently or subsequently, the transfer catheter **156** can be advanced through the inner catheter lumen **10** into the uterine cavity. Once fully everted or when the transfer catheter **156** becomes extended or exposed from the inner catheter **8** and beyond the everting balloon membrane **24**, the reproductive material **166** in the transfer catheter **156** can be deposited by a syringe **74**, squeeze bulb, piston, or other pressure system. A second delivery catheter, such as a second insemination, IVF, or drug delivery catheter can be concurrently inserted into the inlet port **40** or a second inlet port. The second delivery catheter can be deployed to the target site **164** concurrent with or subsequent to the transfer catheter **156**.

(138) The system handle **30** can have a lead-in area. The lead-in area can, for example, be without steps, edges, bumps, or restrictions that may impede or contact the distal opening of the transfer catheter **156** during passage, for example so that in the case of delivery of insemination material, the transfer catheter **156** can be easily loaded into the system handle **30**. An insemination syringe **74** or pump can be attached to the proximal transfer connector to deliver pressure to the transfer tube **162**, for example to expel the reproductive material **166** once the distal port of the transfer catheter **156** is positioned at the target site **164** (e.g., after the everting balloon **18** is fully deployed). The actuation of the insemination syringe or pump on a pre-loaded transfer catheter **156**

can be performed by the same hand that holds and operates the components of the everting catheter system.

(139) In addition, the transfer catheter **156** can be configured to be introduced into the proximal connector in the handle of the everting catheter system once the system is fully deployed.

(140) The user can perform any or all of the following while using the everting balloon system **2**, for example with a single hand: a. pressurize the everting catheter system; b. position the everting balloon system **2** at the patient's cervix; c. maintain the everting balloon system **2** position throughout the procedure; d. advance the inner catheter **8** and everting balloon **18**; e. once extended beyond the everting balloon membrane **24** or inner catheter **8**, present the transfer catheter **156** for deposition into the bodily cavity such as a uterine cavity f. retract the inner catheter **8** and everting balloon **18**; and/or g. activate (e.g., toggle) the pressure release lever to remove or release hydraulic or pneumatic pressure from the media volume **12**.

(141) FIGS. **10A** through **10C** illustrate that the distal end of the everting balloon can form a balloon check valve **168**. The length of the everting balloon **18** distal to the distal terminal end of the inner catheter **8** can radially contract to form a tight orifice that can be the balloon check valve **168**. The balloon check valve **168** can be an openable barrier that can block or interrupt fluid communication between the inner catheter lumen **10** and the target site **164**.

(142) The balloon membrane **6** can have from about 1 mm to about 3 mm of overlapping wall at the balloon check valve **168** closing off the inner catheter lumen **10**. The strength or closing pressure of the balloon check valve **168** can be modulated during use. For example the distance of overlap of balloon membrane **6** can be increased or decreased by controlling the amount of excursion available for the inner catheter **8** and everting balloon membrane **24**.

(143) FIG. **10B** illustrates that the distal end of the transfer catheter **156** can be advanced, as shown by arrow **170**, through the inner catheter lumen **10**, through the balloon check valve **168**, and to the target site **164**. The transfer catheter **156** can penetrate or push open the balloon check valve **168** when the transfer catheter **156** moves through the balloon check valve **168**. When the terminal distal end of the transfer catheter **156** is distal of the balloon check valve **168** and at the target site **164**, the reproductive material **166** loaded in the transfer catheter **156** can be delivered **172** through a distal port of the transfer catheter **156** and into the target site **164**, such as the uterine cavity.

(144) FIG. **10C** illustrates that the transfer catheter **156** can be retracted through the balloon check valve **168** and the inner catheter lumen **10** after the reproductive material is deposited at the target site **164**. The balloon check valve **168** can close as the transfer catheter **156** is retracted through the balloon check valve **168**. The balloon check valve **168** can maintain a seal between the inner catheter lumen **10** and the target site **164** when the transfer catheter advances **170** through, remains stationary within, and is retracted through the balloon check valve **168**.

(145) The reproductive material **166** can be isolated from vacuum effect or the retraction of reproductive material **166** from the target site **164** as a result of the vacuum forces created by the withdrawal of the transfer catheter **156** through the system once the deposition of reproductive material **166** is completed. The balloon check valve **168** can reduce or eliminate vacuum effect for embryo transfer.

(146) The balloon check valve **166** can be a tactile indicator for the physician when passing the transfer catheter **156** through the everting balloon system **2**. In transfer procedures, depending upon physician preference or patient anatomy, for example, the amount of insertion of the transfer catheter **156** through the distal end of the everting system can vary from patient to patient. As the distal end of the transfer catheter **156** passes through the balloon check valve **168**, the resistance created by the balloon check valve **168** can be felt by the physician on the proximal end of the transfer catheter **156**. Depending upon the length of balloon chosen to act as a balloon check valve **168**, the degree or amount of resistance can be modulated. In some procedural settings there may be a compromised ability to see the amount of insertion of the transfer catheter **156** into the everting balloon **18**, or physical depth indicia or markings on the proximal end of the transfer



catheter **156**. The compromised ability to see may be due to low light within the procedure room so that imaging and visualization of monitors can be enhanced. In addition, the physical relationship of the physician, embryologist, or other persons or equipment in the procedure room may compromise the ability to see easily the amount of insertion into the everting catheter. The tactile sensation of the resistance of the balloon check valve **168** can create a palpable indicator that the transfer catheter **156** is at the distal end of the everting balloon **18**.

(147) The everting balloon system **2** can be used to access and seal the uterine cavity, for example, for the deposition of reproductive material **172** for long duration intrauterine insemination.

(148) FIGS. **11A** through **11C** illustrate that the everting balloon membrane **24** can create a seal within the cervical canal (e.g., against the cervical canal walls **174**) as the everting balloon **18** traverses the cervical canal. FIG. **11A** illustrates that the everting balloon membrane **24** can unroll and advance along the cervical walls, as shown by arrows, as the balloon is pressurized and the inner catheter **8** is distally advanced. The outer catheter **4** can also seal against the cervical canal wall **174**. For example, the outer catheter **4** outer diameter can be equal to the everting balloon outer diameter.

(149) FIG. **11B** illustrates that the transfer catheter **156** can advance distally within the everting balloon **18** and the inner catheter lumen **10**. The transfer catheter **156** can deposit the reproductive material **166** (e.g., sperm) within the uterine cavity **176**.

(150) FIG. **11C** illustrates that the transfer catheter **156** and/or the inner catheter **8** can be retracted (e.g., from about 3 mm to about 10 mm) or inverted, as shown by arrows, to close the distal end of the inner catheter lumen **10**, as shown by arrows, with respect to the uterine cavity **176**. The distal opening of the balloon **178** can close, for example due to the pressure within the everting balloon **18** forcing the everting balloon **18** to form the balloon check valve **168**. The balloon check valve **168** can seal the cervical canal and the uterine cavity **176** from the inner catheter lumen **10**. The reproductive materials **166** can remain in the uterine cavity **176** without being expelled through the cervix.

(151) FIGS. **12A** to **12E** illustrate of an everting catheter for performing an IUD placement procedure. FIG. **12A** shows an everting catheter with an IUD contained in an everting catheter system **2** in the inverted membrane position. Everting membrane and IUD (not visible in this figure) are contained within outer catheter **4** with acorn tip **242** at the distal end. Acorn tip **242** can have an opening at the distal end (not visible). On the proximal end of outer catheter **4** there is a t-fitting or Y-fitting **244** which contains an x-ring gasket (not visible). Extension tubing and stopcock **248** supplies inflation or hydraulic energy to the everting catheter system. Hydraulic energy can be supplied by saline, air, a combination of saline and air, or gases such as CO<sub>2</sub>, contrast media, culture media, and other fluids. In operation, hydraulic energy can be in the range of 2 to 4 atmospheres, or 1 to 6 atmospheres. Inner catheter **8** is translatable within the outer catheter **4** to advance and retract the everting membrane (not visible). On the proximal end of the inner catheter **8** there is a proximal hub **246** that is designed to allow passage of the IUD suture **252**. Other embodiments may not require the IUD suture to be exposed from the inner catheter.

(152) FIG. **12B** shows the distal end of the everting catheter with IUD **254** visible in the everted membrane which is only partially everted from acorn tip **242**. IUD **254** can be in a collapsed condition within the membrane **6**. IUD suture **252** can be proximal to the IUD **254**. The IUD suture **252** can be within the central lumen of inner catheter **8**. IUD **254** can have rounded distal ends **256** and stem **258**. IUD **254** can have radio-opaque marker band **260**, copper or drug or hormone eluting section **262**, and other features.

(153) FIG. **12C** shows the advancement of the everting membrane **6** pulling IUD **254** through the distal end of outer catheter **4** and opening on acorn tip **242**. Eversion of the membrane can be performed in response to hydraulic energy or pressure within the everting catheter system **2** through the inflation tubing and stopcock (not shown). The everting membrane **6** responds to hydraulic energy to roll inside out. The advancement of the everting membrane **6** can be performed

by the user translating the inner catheter (not visible) or automatically in response to the hydraulic energy. The everting membrane can be dimensioned in a range of 1 mm to 5 mm in diameter for the endocervical canal or 4.0 to 4.5 mm in outer diameter when pressurized to 2 atmospheres. The everting membrane can have an outer diameter range of 2 mm to 7 mm, with a wall thickness of 0.001" to 0.004", or 0.0015". The everting membrane can be manufactured from irradiated polyolefin, polyurethane, Pebax, silicone, or other flexible membrane material. The everting membrane wall thickness could have a range of 0.002" to 0.010" depending upon the modulus of the membrane material.

(154) FIG. 12D shows the distal end of the outer catheter **4** and acorn tip **242** with everting membrane **6** in a further stage of eversion advancing IUD **254** through the distal end opening in acorn tip **242**. Rounded ends **256** of IUD **254** are in the initial stages of returning to its natural state as opposed to its collapsed state. In its natural state, IUD **254** can have a "T" or "Y" shape although other shapes and configurations are possible for intrauterine devices.

(155) FIG. 12E shows the completion of the eversion process with everting membrane **6** advanced further beyond the acorn tip **242** and fully exposing IUD **254** that can now be in its natural (i.e., unbiased or mechanically relaxed) state or "T" shape. Stem **258** and hormone or drug eluting section **262** are fully exposed from the distal end of membrane **6**. Certain IUDs are equipped with bands or rings of copper material as a spermicidal agent. IUD suture **252** can still be within the central lumen of membrane **6** and inner catheter (not visible). At full exposure outside of membrane **6**, IUD **254** can be at the insertion depth within the uterine cavity. The insertion depth of the IUD **254** within the uterine cavity can be determined or prescribed by the length of the membrane **6**, the amount of eversion performed by the user during the translation of the inner catheter **8**, which can vary depending upon the desired depth of insertion. In addition, the outer catheter **4** can be configured with telescoping tubes (not shown) that can change the membrane length and the insertion depth within the uterine cavity.

(156) FIGS. 13A to 13I illustrate additional derivations for an everting catheter system **2** for IUD placement. FIG. 13A shows everting catheter system **2** with IUD **254** in a collapsed state within the everting membrane **6** (not visible) within outer catheter **4**. Inner catheter **8** can be proximal to Y-fitting **244** and continues within outer catheter **4**. Everting membrane **6** can be connected to the distal end of inner catheter **8** and to the distal end of outer catheter **4**. Acorn tip **242** can be located at the distal end of outer catheter **4**. Everting membrane **6** can be pressurized by fluid, gas, or a combination of both through extension tubing and stopcock **248**. Within inner catheter **8** can be pusher **264** which can be proximal to inner catheter hub **246**. Pusher **264** can be a hollow tube with pusher hub **266** that can contain IUD suture **252** within its inner lumen.

(157) FIG. 13B shows in a side view acorn tip **242** with dashed lines indicating through lumen **276** within the acorn tip. Acorn tip **242** can be used to seat the everting catheter system **2** at the exocervix of the patient. Acorn tip **242** contains intubation tip **268** on the posterior surface that can be designed to gain purchase or intubate the opening of cervix with a rounded surface **269** on the anterior portion. Acorn tip **242** can have outer shoulders **270** to provide a stopping mechanism to avoid inadvertent insertion of the outer catheter **4** within the cervical canal of the patient. Distal end opening **272** can be configured to allow the everting membrane deliver the IUD (both not shown).

(158) FIGS. 13C and 13D show another type of acorn tip **242** with lower profile anterior surface **274** with outer shoulders **270** that are reduced in the anterior portion of circumference of acorn tip **242**. Lower profile anterior surface **274** provides the physician greater viewing angle of the exocervix when placing the everting catheter (not shown). The lower profile anterior surface can be used by the physician to gain better visualization of the exocervix while maintaining the functions of the acorn tip in regards to intubating the exocervix, gaining purchase, and providing a stopping mechanism from inadvertent advancement of the outer catheter into the cervical canal. Alternative acorn tip **242** contains an intubation tip **268** on its distal end on the posterior surface to facilitate initial device placement at the exocervix of the patient with ramp **271** leading to shoulder **270**.

Dashed lines indicate through lumen **276** with distal end opening **272**.

(159) Returning back to an alternative embodiment of everting catheter system **2**, FIG. **13E** shows IUD **254** being advanced by everting membrane **6** in response to the advancement of inner catheter **8** within outer catheter **4** using hydraulic energy supplied in extension tubing and stopcock **248**. In conjunction, pusher **264** can advance with everting membrane **6** with two strands of IUD suture **252** exiting pusher hub **266**.

(160) FIG. **13F** shows further advancement of IUD **254** with everting membrane **6** and translation of inner catheter **8** within outer catheter **4**. Rounded ends **256** are exposed distal at the end of the everting membrane **6** as the membrane everts inside out and pulls the IUD forward.

(161) FIG. **13G** shows IUD **254** released from everting membrane **6** with IUD fully in its natural state or “T” or “Y” shape. IUD suture **252** can be proximal to the IUD and runs through everting membrane **6**, pusher **264**, and inner catheter (not visible). To complete IUD release, pusher **264** advances IUD **254** beyond the distal end of everting membrane **6**.

(162) FIGS. **13H** and **13I** illustrate alternative embodiments of the distal end of pusher **264**. FIG. **13H** shows distal end of pusher **264** with pusher cup **278** with concave opening **280** to accept and hold the profile of the proximal end of IUD **254** (not shown). Pusher **264** can have through lumen with central axis **282**. Distal end pusher cup **278** facilitates the handling and loading of IUD **254** within an everting catheter (not shown).

(163) FIG. **13I** shows an alternative form of distal end of pusher **264** with through lumen and central axis **282** and with a split tube opening **284** at the distal end. Split tube opening **284** can be configured to open and accept and hold the proximal end of IUD **254** (not shown). Distal end split tube opening **284** facilitates the handling and loading of IUD **254** within an everting catheter (not shown).

(164) FIGS. **14A** and **14D** illustrate the advancement of IUD **254** within an everting membrane **6** from the collapsed state to the release of IUD **254** and return to its natural state or “T” shape. FIG. **14A** shows the everting membrane **6** advancing through acorn tip **242** pulling IUD **254** in a collapsed, low profile state within an everting catheter system **2**. Round ends **256** are compressed by the everting membrane **6** in response to the hydraulic energy supplied through extension tubing and stopcock (not visible).

(165) FIGS. **14B** and **14C** further illustrate the advancement of IUD **254** within an everting membrane **6** within an everting catheter system **2**. As IUD **254** is pulled forward by the everting membrane, IUD **254** can return to its natural state or a “T” or “Y” shape. FIG. **14B** shows the everting membrane **6** in a pressurized state via hydraulic energy. IUD suture **252** can be contained within the distal end of pusher **264** within split opening **284**.

(166) FIG. **14D** illustrates another embodiment of everting catheter system **2** in which the hydraulic energy can be removed by a pressure source **286** via extension tubing and stopcock **248**. Once hydraulic energy is removed from everting catheter system **2**, everting membrane **6** can no longer grip IUD **254** and pusher **264** can advance the proximal end of IUD beyond the distal opening of everting membrane. Pressure source **286** can be an inflation device as shown or other devices such as a syringe, a syringe and compliant tube, a pump, or a pressurized cannister or container.

(167) FIG. **15A** illustrates everting catheter system **2** equipped with a one-handed delivery mechanism. On the proximal end of everting catheter system **2**, housing **288** can be configured with rolling wheel **290** and outer catheter release button **292**. At the distal end, acorn tip **242** can be designed to engage the exocervix when placed in the patient for IUD delivery and placement. IUD **254** can be visible within outer catheter **4**. Extension tubing and stopcock **248** can be located on the posterior portion of housing **288**. Exiting the proximal portion of housing **288**, pusher **264** and pusher hub **266** can be visible with IUD suture **252** protruding the through lumen of pusher **264**.

(168) FIG. **15B** demonstrates the one-handed operating mechanism of everting catheter system **2** using housing **288**. The operator's thumb can be placed on rolling wheel **290** with outer catheter release button **292** in close proximity. IUD **254** can be visible within outer catheter **4** and pusher

**264** with pusher hub **266** can be visible exiting the proximal portion of the housing.

(169) FIG. **15C** shows a top view of the one-handed mechanism of everting catheter system **2** in which the inner catheter **8** can be visible in housing **288**. Also visible are inner catheter hub **246** with pusher **264** protruding from the proximal portion of the inner catheter hub. IUD suture **252** can be visible protruding from the proximal opening of pusher hub **266**. Also visible within housing **288** can be pusher stop **294** and gear wheel housing **296** under the thumb of the operator.

(170) FIG. **15D** illustrates further in a top view the one-handed operation of everting catheter system **2** during the advancement of everting membrane **6** pulling IUD **254** through acorn tip **242**. Rolling wheel **290** (partially visible under the thumb of the operator) can be used to advance inner catheter **8** which allows the everting membrane to advance. Advancement of the everting membrane **6** can be limited when inner catheter hub **246** reaches gear wheel housing **296**. As the inner catheter **8** can be advanced into the outer catheter **4**, inner catheter hub **246** reaches gear wheel housing **296** and advances pusher **264** until pusher hub **266** mechanically engages pusher stop **294**. In operation, the operator will actuate outer catheter release button **292** that will allow the outer catheter **4** and attached everting membrane **6** to retract while pusher **264** maintains in place in relation to housing **288** with pusher stop **294**. The distal end of pusher **264** thereby advances IUD **254** out of the distal end of everting membrane **6** and releasing IUD **254** in the uterine cavity. In operation, the operator will remove the entire everting catheter system **2** and having the IUD suture **252** threading out of pusher **264**.

(171) FIGS. **16A** to **16J** illustrate another embodiment of everting catheter system **2** with handle **30**. Protruding distal to handle **600** can be outer catheter **4** and protruding proximal to the handle can be pusher **264** with IUD sutures **252** exiting the pusher hub **266**. On the anterior portion of handle **600** can be inner catheter button **298** and outer catheter release button **292**. Protruding on the posterior portion of handle **600** can be extension tubing and stopcock **248** (partially visible).

(172) FIG. **16B** shows inner catheter button **298** being advanced within housing slot **308** on the anterior surface of housing **288**. Inner catheter button **298** is attached to the proximal end of inner catheter (not shown) and its advancement translates the inner catheter and everting membrane to deliver an IUD (not shown). In operation, inner catheter button **298** advances until it engages outer catheter release button **292** also on the anterior surface of housing **288**.

(173) FIG. **16C** shows the retraction of outer catheter release button **292** which performs the release of the IUD from the everting catheter (not shown).

(174) FIG. **16D** provides information on how housing **288** works with everting catheter system **2** to perform the advancement and release of the IUD (not shown). In FIG. **16D**, the anterior portion of housing **288** is removed showing the interior portions of the everting catheter system **2** including inner catheter hub **246**. Alternatively, inner catheter hub **246** can be eliminated by inner catheter button **298** or have both devices as shown. Also visible is pusher **264** and pusher hub **266** with IUD sutures **252** exiting the proximal portion of the pusher hub. Outer catheter release button **292** and inner catheter button **298** is also visible and at this position, the advancement of the everting membrane (not shown) is complete. Contained within the posterior portion of housing **288** are inflation tubing slot **300** and pusher engagement tabs **302** which is configured to mechanically hold pusher hub **266** at the completion of the eversion step. Also visible are housing holes **304** that are designed to snap the anterior and posterior sections of housing **288**.

(175) FIG. **16E** shows a cut-away view of the proximal portion of Y-fitting **244** with inner catheter **8** exiting the proximal of the Y-fitting. Extension tubing and stopcock **248** (stopcock not shown) is exiting posteriorly from Y-fitting **244** and through housing **288** through inflation tubing slot **300**. Outer tubing release button **292** is mechanically attached to Y-fitting **244** and can be retracted in housing **288** along inflation tubing slot **300**.

(176) FIG. **16F** shows the inflation tubing slot **300** on the posterior surface of housing **288** in another cut-away view. Extension tubing and stopcock **248** (stopcock not shown) is visible in inflation tubing slot **300**.

(177) FIG. 16G shows a cut-away view of the proximal portion of housing 288 and proximal hole 306. Cut away view of pusher 264 is visible exiting from the proximal portion of inner catheter hub 246. The internal track of the pusher engagement tabs 302 that progressively gets narrower as it extends from the proximal portion of housing 288 to the distal portion is visible on the internal posterior surface of housing 288. Pusher hub 266 can have a conical or tapered profile on its distal portion to travel through the pusher engagement tabs 302. The flat proximal portion of pusher hub 266 can serve as a mechanical detent in the proximal direction once the pusher hub 266 extends beyond the pusher engagement tabs 302.

(178) FIG. 16H shows the initial step of IUD delivery and placement with another cut-away view of the right-hand side of housing 288 with outer catheter 4 distal to Y-fitting 244 and attached to outer catheter release button 292. Also, on the anterior surface of the housing and in housing slot 308 is inner catheter button 298. Exiting proximal to inner catheter 8 and inner catheter button is pusher 264. Attached to the proximal end of pusher 264 is the pusher hub 266 with through lumen for IUD sutures 252.

(179) FIG. 16I shows in the same cut away view the range of advancement of inner catheter button 298 during the eversion step with everting catheter system 2 hydraulically pressurized through extension tubing and stopcock 248 (stopcock not shown). This embodiment shows an advancement of the inner catheter 8 within outer catheter 4 of 12.6 cm. This distance of advancement corresponds to an insertion depth within the uterine cavity of 6.3 cm. Other lengths of advancement are possible from 3 cm to 24 cm. In addition, the depth of insertion can be under the physician's control by stopping the eversion step at any point during the process.

(180) FIG. 16J shows the release step of the IUD delivery process with everting catheter system 2 in which outer catheter release button 292 is retracted bringing pusher 264 through inner catheter 8 to advance the IUD (not shown) through the everting membrane (not shown).

(181) FIGS. 17A to 17I illustrate further embodiments of an everting catheter that delivers an IUD. FIG. 17A shows everting catheter system 2 with housing 288 with pusher 264 and pusher luer hub 310 exiting proximal to the housing. Pusher luer hub 310 is configured to accept a syringe 74 or other irrigation source to provide fluid, saline, contrast media, sonographic media, drugs or therapeutic agents, or a gas or air through the central lumen of everting catheter system 2. Irrigation fluid or media can facilitate visual identification of the exocervix or the uterine cavity with ultrasonography or fluoroscopy.

(182) FIG. 17B shows everting catheter system 2 at the initial stage of the eversion process with anterior portion of housing 288 removed for identification of internal parts and mechanisms.

(183) FIG. 17C shows everting catheter system 2 with hydraulic energy is supplied through extension tubing and stopcock 248. Inner catheter button 298 is advanced to translate inner catheter 8 within outer catheter 4. Everting membrane 6 exits distal to acorn tip 242 and pulls IUD (not shown) and pusher 264 through the central lumen of everting catheter system 2. Pusher luer hub 310 is translated through proximal hole 306 of housing 288 and into the track of pusher engagement tabs 302.

(184) FIG. 17D shows the next step of the eversion process with inner catheter button 298 engaging outer catheter release button 292 and pusher luer hub 310 reaching mechanical detent of pusher engagement tabs 302.

(185) FIG. 17E shows the next step in the IUD delivery process with syringe 74 connected to extension tubing and stopcock 248 to draw negative pressure within everting catheter system 2. Negative pressure withdraws the hydraulic energy in the everting membrane 6.

(186) FIG. 17F shows the next step in the IUD delivery process with outer catheter release button 292 retracted and thereby retracting the outer catheter 4, everting membrane 6, and inner catheter 8 while maintaining the position of the pusher 264 relative to the housing 288. Pusher engagement tabs 302 prevent the pusher luer hub 310 from retracting and thereby maintaining the position relative to the housing 288.

(187) FIG. 17G shows a close-up photograph of the distal end of the everting membrane 6 with hydraulic energy removed from everting catheter system 2 and with distal end of pusher 264 extending beyond the distal opening of the everting membrane 6. Split tube opening 284 is at the distal end of pusher 264 and illustrates that the distal end of pusher 264 can exit everting membrane 6.

(188) FIG. 17H shows an alternative type of syringe 74 with plunger spring 314 on plunger 76. Engagement button 312 can translate within syringe housing 208 to lock onto ridges 316 on multiple locations on plunger 76. When depressed, engagement button 312 can lock plunger spring 314 in a compressed condition.

(189) FIG. 17I shows syringe 74 with engagement button 312 released allowing plunger spring 314 to expand and retract plunger 76 back to provide negative pressure within syringe 74 and an everting catheter system 2 (not shown).

(190) FIGS. 18A through 18C illustrate another embodiment of everting catheter system 2 that automatically provides negative pressure to remove hydraulic energy in the everting catheter at the step of releasing the IUD (not shown) during the delivery and placement procedure. FIG. 18A shows everting catheter system 2 with housing 288 and syringe 74 mounted or attached to the bottom posterior surface of the housing. Syringe 74 can have plunger spring 314 compressed and engagement button 312 locked into syringe housing 208. Syringe 74 is connected via inflation tubing 318 as a conduit for the hydraulic energy within everting catheter system 2.

(191) FIG. 18B shows the advancement of inner catheter button 298 in housing slot 308. Advancement of inner catheter button 298 translates inner catheter (not shown) within outer catheter 4 and advancing everting membrane and IUD (both not shown).

(192) FIG. 18C shows the next step in the IUD delivery and placement process. The depression of outer catheter release button 292 forces engagement button 312 to release plunger spring 314 and plunger 76 to create negative pressure in the everting catheter system 2 via inflation tubing 318. At this point the outer catheter release button can be retracted back along housing slot 308 to retract the outer catheter 4, everting membrane and inner catheter (not shown) while maintaining the position of pusher (not shown) and releasing the IUD from the everting membrane (both not shown).

(193) FIG. 19A illustrates an everting catheter system 2 for delivering an IUD in the inverted state. IUD 254 can be loaded in a collapsed condition within balloon membrane (not visible) and inner catheter 8. Inner catheter 8 can be within outer catheter 4. At the distal end of outer catheter 4, moveable flange can be a marker for insertion depth with indicia 402. The proximal end of outer catheter 4 there is a t-fitting 244 for pressurization of the everting balloon with x-ring valve (not shown) for the translation of inner catheter 8. Inner catheter 8 has proximal hub 246 that can be a luer connector, knob, or handle for the manipulation of inner catheter. Within the central lumen of inner catheter 8 is pusher 264 with lumen for IUD suture(s) 252. Pressurization of everting catheter system 2 can be performed by syringe 410 and syringe plunger 409 that can be connected by the user or physician to connector 413 that can be connected to compliant tube 412. Pinch clamp 411 can be used by the user or physician to close compliant tube 412 to maintain pressure within the everting balloon. Once pressurized, syringe 410 can be disconnected and removed from the everting catheter system 2 prior to insertion within the patient.

(194) FIGS. 19B to 19D are close-up views of different sections of everting catheter system 2. FIG. 19B is a close-up view of the distal end of outer catheter 4 with the initial portion of everting balloon 6 visible exiting the distal end outer catheter 4. The distal end opening of outer catheter 4 have an acorn tip or no acorn tip and a smooth, rounded, low profile distal tip. The distal end can have indicia 402 which denote 7 cm, 8 cm, 9 cm, and 10 cm markings for example, for showing the user (e.g., physician) an indication of insertion depth. Moveable flange 401 can be placed by the user (e.g., physician) to provide a visible and tactile indicator for insertion depth. Visible within outer catheter 4 can be IUD 254 in a collapsed, loaded, low profile state within the everting balloon

and inner catheter (not visible).

(195) FIG. 19C is a close-up view of the pressurization system for everting catheter system 2. Pressurization of the everting catheter 2 can be performed by syringe 410 filled with saline, sterile water, air, or an inert gas, or combination of gases and fluid media. Depression of syringe plunger 409 by the user or physician supplies hydraulic energy to the everting balloon. Syringe 409 can have a volume of 1 cc, 3 cc, 5 cc, or 10 cc, for example, 3 cc as shown. Other volumes are possible. Pressurization of the everting catheter system 2 can distend compliant tube 412. Compliant tube 412 can be made from silicone and/or other elastomeric materials, such as polyurethane, rubber, and TPE, or combinations thereof. Compliant tube 412 can maintain a near constant pressure within everting catheter system 2 during inversion and eversion. Compliant tube 412 can provide a mitigation from the user or physician inadvertently putting in too much pressure within the everting catheter system 2 since the silicone tube can continue to distend in response to the added hydraulic pressure. Pressurization amount can 1 to 4 atmospheres with 2 atmospheres as a nominal level. The amount of compliance within the silicone tube can depend upon the durometer of the material, the wall thickness of the tube, and the length of the tube available for distension. As shown for example, compliant tube 412 can be silicone with a durometer of 50 A, 6 cm in length, with an outer diameter of 4.75 mm and wall thickness of 1 mm. The pressurization system can be closed by the user with pinch clamp 411, for example to close the internal lumen of compliant tube 412 once pressurized by syringe 410. Other tubing closure devices can be used, such as stopcocks, gate valves, roller clamps, or combinations thereof. A one-way check valve or a luer-activated valve can be on compliant tube 412 instead of or in combination with connector 413 to allow for one-way pressurization without requiring the user to actuate a closure device to close and maintain pressure within compliant tube 412 and everting catheter system 2. Hydraulic pressure supplied by syringe 410 and syringe plunger 409 can be in fluid communication with everting catheter system 2 through t-fitting 244 with x-ring valve (not shown) maintaining pressure during eversion of balloon membrane and the translation of inner catheter 8 within outer catheter 4. Inner catheter 8 can be made from nylon, Pebax, polypropylene, polyethylene, or combinations thereof. Inner catheter 8 can extend from the distal end of the fully everted balloon to the proximal end of t-fitting 244 with an outer diameter of 4 mm and an inner diameter of 3 mm.

(196) FIG. 19D is a close-up view of the proximal portion of everting catheter system 2 and illustrates inner catheter 8 with proximal connector hub 246 with central through hole. Within the central through hole can be pusher 264 with pusher hub 266 with central through hole with IUD sutures 252. Proximal connector hub 246 and pusher hub 266 can be luer connectors to allow for the connection of syringes or tubing for the injection of fluid, saline, or gas media for distention of the uterine cavity for ultrasound, fluoroscopic, or endoscopic visualization. Proximal connector hub 246 and pusher hub 266 can be handles or knobs for manipulation of the catheters by the user or physician. Pusher 264 can be made from nylon, Pebax, polypropylene, polyethylene, or combinations thereof. Pusher 264 tubing can have an outer diameter of 2 mm and inner diameter of 1.25 mm and a length that approximates the entire length of everting catheter system 2, for example, to allow the user or physician to expel the IUD from inner catheter 8 during placement within the uterine cavity.

(197) FIG. 20A illustrates the everting catheter system 2 after full eversion of the balloon in the process of delivering an IUD. IUD 254 can be in a collapsed, loader state within inner catheter 8 and everting balloon 6. Outer catheter 4 can contain indicia markings 402 and depth insertion marker flange 401. Outer catheter 4 can be connected to t-fitting 244 with x-ring valve (not shown) and can be connected to compliant tube 412 with luer connector 413 and tubing pinch clamp 411 for hydraulic pressurization of everting catheter system 2. Immediately proximal to t-fitting 244 can be proximal connector hub 248 denoting full eversion of the everting balloon and full translation of inner catheter (not visible). Proximal to the proximal connector hub 248 is pusher 264 and pusher hub 266. Proximal to pusher hub 266 can be IUD sutures 252 seen beyond the

central lumen of the tubing.

(198) FIG. 20B is a close-up view of the distal end of the everting catheter system 2 with fully everted balloon 6 and IUD 254. Distal end of inner catheter (not visible) can be connected to everting balloon 6 and rounded distal ends 256 of IUD 254 can be immediately distal to the fully everted balloon 6. Visible through the everted balloon 6 and inner catheter can be portions of IUD 254 including copper wire 271, IUD stem hole 272, suture knot 273 and IUD sutures (not visible). Everting balloon 6 can be connected to outer catheter 4 with indicia markings 402. For example, everting balloon 6 can be 6 cm long to traverse the length of the cervix and which can be 3.5 cm in length from the exocervix to the internal cervical os. Different lengths of everting balloon 6 can be used to approximate the uterine lengths of different patients. Everting balloon can, for example, have an outer diameter of 4 mm in the pressurized state of 2 atmospheres and a wall thickness of 0.0015" thousandths of an inch. Everting balloon can be made from irradiated polyolefin, polyethylene, Pebax, polyurethane, other biocompatible materials that can create a hydraulic everting balloon, or combinations thereof.

(199) Distal end of inner catheter (not visible) can have an internal diameter that, for example, can allow for the collapsed IUD to fit within the tubing. For example, an internal diameter of 3 mm can allow the collapsed IUD to fit within the tubing but keep the rounded distal ends 256 protruding distal to the inner catheter (not visible) and the everting balloon 6. Distal end of pusher (not visible) can be just proximal to IUD stem hole 272 and suture knot 273. Distal end opening of everting balloon 6 can be connected to the distal end of the inner catheter (not visible). When inverted and pressurized, everting balloon 6 can collapse IUD 254 in a lower profile state that facilitates advancement through the cervical canal and into the uterine cavity. When inverted and pressurized, everting balloon 6 can collapse and compress the rounded distal ends 256 together to a low profile, for example, for advancement through the everting catheter system 2, the distal end opening of the outer catheter 4, and the cervical canal and into the uterine cavity.

(200) FIG. 20C is a close-up view of the proximal portion of the everting catheter system 2 after full eversion in the process of delivering an IUD 254. Outer catheter 4 can be connected to t-fitting 244 with x-ring (not visible) and is fluidly coupled to compliant tube 412 with tubing pinch clamp 411 shown in the closed condition with hydraulic pressurization within the everting catheter system 2. Proximal connector hub 248 can be seen immediately proximal to t-fitting 244, for example, denoting full eversion of the everting balloon (not shown) and full translation of the inner catheter (not visible). Within proximal connector hub 248 can be pusher 264 with pusher hub 266 on its proximal end with IUD sutures 252 seen exiting through the central lumen of pusher 264.

(201) FIGS. 21A to 21C illustrate the process of delivering an IUD within a simulated uterine cavity model 500 (standing in for a patient's uterine cavity and other respective anatomy for illustrative purposes) with metric scale 510 provided for reference. FIG. 21A illustrates the placement of IUD 254 within simulated uterine cavity model 500 with fundal portion 501 which simulates the cranial apex of the uterine cavity, and cornual regions 502 (denoting the patient's right fallopian tube os) and 503 (denoting the patient's left fallopian tube os). Simulated uterine cavity model can contain lower uterine segment 504 with simulated cervical canal 505 and simulated exocervix 506. Everting catheter system 2 can have everted balloon 6 fully everted with rounded distal ends 256 of IUD 254 approximating the fundus 501 of the uterine cavity and distal to the everted balloon 6. Pusher 264 can be proximal to IUD 254. Flange 401 can abut the exocervix 506 with an insertion depth of approximately 9 cm, for example.

(202) FIG. 21B illustrates a next (e.g., intermediate) step in the process of IUD placement with everting catheter system 2. Everting catheter system 2 can be retracted 1.5 cm as seen by flange 401 now being a distance, for example, of 1.5 cm from exocervix 506. In combination, IUD 254 can be expelled from the distal end of everting balloon 6 with pusher 264 and retraction of everting catheter system 2. IUD 254 can have rounded distal ends 256 extending outward towards cornual regions 502 and 503.



(203) FIG. 21C illustrates a next (e.g., final) step of IUD 254 placement with the everting catheter system (not shown) that can be completely removed from simulated uterine cavity model 500. Rounded distal ends 256 can remain in the cornual regions 502 and 503. IUD sutures 252 can be visible exiting the exocervix 506. The user or physician can trim the excess length of IUD sutures 252 depending upon the amount of excess IUD suture or type of IUD.

(204) FIGS. 22A to 22E illustrate a packaging configuration for the transit and loading of the everting catheter system 2 for delivering an IUD. Everting catheter system 2 can be placed onto pouch card 600 in the fully everted position with IUD 254 at the distal end of the everting balloon (not visible). Pouch card 600 and everting catheter system 2 can be placed into a sealed pouch (not shown) for sterilization, shipping, and eventual usage by a physician. Pouch card 600 can be made from clean laminated paper card stock, PETG, polypropylene, polyvinyl chloride, PET, or combinations thereof. Affixed to pouch card 600 can be protective tube 601 which can be, for example, 6.5 cm in length with an ID of 4 mm. Protective tube 601 can be sized in length to fit over the fully everted balloon (not visible) and leave IUD 254 in the open configuration with rounded distal ends 256 beyond the distal end of the protective tube 601. Protective tube 601 internal diameter can be sized to allow a non-pressurized everting balloon (not visible) to slide through the central lumen. When everting balloon (not visible) is pressurized, everting balloon outer diameter can contact the internal lumen of protective tube 601. Contacting the internal lumen when pressurized can, for example, allow the user or physician to easily retract the everting balloon and inner catheter for loading and preparation for use. Protective tube 601 can be made from nylon but can be made from polypropylene, PET, Pebax, and other tubing materials used in medical device packaging. T-fitting 244 and proximal connector hub (not visible) can be held in place by pouch tabs 602 with inner catheter (not visible) fully translated into outer catheter 4. Pusher 264, pusher hub 266, and IUD sutures 252 can extend proximal to everting catheter system 2.

(205) FIG. 22B is a close-up view of a variation of the distal portion of pouch card 600 and protective tube 601 with everting balloon (not visible) fully everted within protective tube 601. IUD 254 can be in an open configuration and can be positioned at the distal end of everting catheter system 2 with IUD sutures (not visible in this view) running through the entire length of the inner catheter and pusher of everting catheter system 2. Proximal end of protective tube 601 can be intubated by the distal end of outer catheter 4.

(206) FIG. 22C illustrates a step (e.g., unpacking, assembling, and pressurizing) in the preparation of everting catheter system 2. Pouch 603 can be peeled back halfway to expose the proximal portion of pouch card 600. The user or physician can connect syringe 410 to compliant tube 412 with pinch clamp 411 in the open position. The compliant tube can be rotated upwards or perpendicular to the surface or pouch card 600. The everting catheter system can be pressurized with 3 cc of saline.

(207) FIG. 22D shows the compliant tube 412 pressurized with pinch clamp 411 can be in the closed position with syringe disconnected and removed from luer connector 413. IUD sutures 252 can then pulled to retract IUD 254 within the distal end of the inner catheter (not visible) within protective tube 601.

(208) FIG. 22E is a close-up view of the distal portion of pouch card 600 with the IUD 254 that can be in the collapsed and loaded configuration inside the inner catheter (not visible) within protective tube 601. The everting balloon (not visible) can then be fully inverted with inner catheter (not visible) that can be fully translated back, for example, to remove the everting catheter system 2 from the protective tube 601 and pouch 603 in preparation for insertion into the patient.

(209) Any elements described herein as singular can be pluralized (i.e., anything described as “one” can be more than one). Any species element of a genus element can have the characteristics or elements of any other species element of that genus. The media delivered herein can be any of the fluids (e.g., liquid, gas, or combinations thereof) described herein. The patents and patent applications cited herein are all incorporated by reference herein in their entireties. Some elements

may be absent from individual figures for reasons of illustrative clarity. The above-described configurations, elements or complete assemblies and methods and their elements for carrying out the disclosure, and variations of aspects of the disclosure can be combined and modified with each other in any combination. All devices, apparatuses, systems, and methods described herein can be used for medical (e.g., diagnostic, therapeutic or rehabilitative) or non-medical purposes.

(210) U.S. Pat. No. 9,028,401, issued May 12, 2015; U.S. Pat. No. 9,101,391, issued Aug. 11, 2015; and U.S. Pat. No. 10,034,986, issued Jul. 31, 2018; and U.S. Published Application Nos. 2019/0009058, published Jan. 10, 2019; 2020/0206463, published Jul. 2, 2020; 2020/0297384, published Sep. 24, 2020; and 2020/0023162, published Jan. 23, 2020 which are all incorporated by reference herein in their entireties.

(211) Any elements described herein as singular can be pluralized (i.e., anything described as “one” can be more than one). Any species element of a genus element can have the characteristics or elements of any other species element of that genus. “Dilation” and “dilatation” are used interchangeably herein. The media **155** delivered herein can be any of the fluids (e.g., liquid, gas, or combinations thereof) described herein. The patents and patent applications cited herein are all incorporated by reference herein in their entireties. Some elements may be absent from individual figures for reasons of illustrative clarity. The above-described configurations, elements or complete assemblies and methods and their elements for carrying out the disclosure, and variations of aspects of the disclosure can be combined and modified with each other in any combination. All devices, apparatuses, systems, and methods described herein can be used for medical (e.g., diagnostic, therapeutic or rehabilitative) or non-medical purposes.

## Claims

1. A system for delivering a device into the reproductive tract of a female comprising: a first catheter having a lumen and a distal lumen port, wherein the first catheter has a retracted configuration and an extended configuration; an everting balloon attached to the first catheter, wherein at least a length of the everting balloon extends past a distal end of the first catheter when the first catheter is in the extended configuration; a second catheter slidably located in the first catheter; an IUD in the second catheter; and a third catheter radially outside of the first catheter.
2. The system of claim 1, further comprising an irrigant configured to flow through the first catheter.
3. The system of claim 2, wherein the irrigant comprises a therapeutic agent.
4. The system of claim 3, wherein the therapeutic agent comprises a cytotoxic agent.
5. The system of claim 4, wherein the therapeutic agent comprises an anticoagulant.
6. The system of claim 5, wherein the anticoagulant comprises heparin.
7. The system of claim 4, wherein the therapeutic agent comprises a sclerosing agent.
8. The system of claim 2, wherein the irrigant comprises a medication.
9. The system of claim 8, wherein the medication comprises an anesthetic agent.
10. The system of claim 9, wherein the anesthetic agent comprises a local anesthetic.
11. The system of claim 10, wherein the local anesthetic comprises lidocaine.
12. The system of claim 2, wherein the irrigant comprises an analgesic agent.
13. The system of claim 1, wherein the everting balloon is attached at a first end of the everting balloon to the third catheter, and wherein a second end of the everting balloon is attached to the first catheter.
14. A system for delivering a device into the reproductive tract of a female comprising: a first catheter having a lumen and a distal lumen port, wherein the first catheter has a retracted configuration and an extended configuration; an everting balloon attached to the first catheter, wherein at least a length of the everting balloon extends past a distal end of the first catheter when the first catheter is in the extended configuration; a second catheter slidably located in the first

catheter; an IUD in the second catheter; and a distal closure tip, wherein the distal closure tip is attached to the everting balloon, wherein the distal closure tip comprises a pressure releasing element.

15. The system of claim 14, further comprising an irrigant configured to flow through the first catheter.

16. The system of claim 15, wherein the irrigant comprises a medication.

17. The system of claim 16, wherein the medication comprises an anesthetic agent.

18. The system of claim 15, wherein the irrigant comprises an analgesic agent.

19. The system of claim 15, wherein the irrigant comprises a therapeutic agent.

20. The system of claim 14, wherein the distal closure tip is configured to detach the everting balloon from the first catheter and the second catheter.

---