

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416778
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Jun; Jae Woo et al.

Lens actuator and camera module including same

Abstract

A lens actuator includes: a lens barrel accommodating one or more lenses; and a driving unit to move the lens barrel along an optical axis direction. The driving unit includes a driving wire, at least a portion of which is extended in the optical axis direction, and a length of which is changed as voltage is applied thereto, and a driving transmission unit connected to the driving wire to move the lens barrel along the optical axis direction as the length of the driving wire is changed such that a distance by which the lens barrel is moved by the driving transmission unit is greater than an amount of change in the length of the driving wire.

Inventors:	Jun; Jae Woo (Suwon-si, KR), Choi; Yun Kyoung (Suwon-si, KR)
Applicant:	SAMSUNG ELECTRO-MECHANICS CO., LTD. (Suwon-si, KR)
Family ID:	1000008819297
Assignee:	Samsung Electro-Mechanics Co., Ltd. (Suwon-si, KR)
Appl. No.:	17/665713
Filed:	February 07, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220365311 A1	Nov. 17, 2022

Foreign Application Priority Data

KR	10-2021-0063381	May. 17, 2021
----	-----------------	---------------

Publication Classification

Int. Cl.: G02B7/09 (20210101); G02B7/10 (20210101); G03B3/10 (20210101)

U.S. Cl.:

CPC **G02B7/09** (20130101); **G02B7/102** (20130101); G03B3/10 (20130101)

Field of Classification Search

CPC: G02B (7/09); G02B (7/102); G02B (27/646); G03B (3/10); G03B (2205/0023); G03B (2205/003); G03B (2205/0046); G03B (2205/0069); G03B (2205/0084); G03B (5/00); G03B (13/36); G03B (30/00); G03B (5/04); G03B (17/12); G03B (2205/0015); H04N (23/55)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8848064	12/2013	Topliss	348/208.7	H04N 23/68
2002/0001467	12/2001	Tanaka	396/177	G03B 17/425
2009/0135395	12/2008	Melzer	355/67	G02B 7/023
2013/0028581	12/2012	Yeung	396/73	G02B 7/021
2014/0168793	12/2013	Fukino	N/A	N/A
2016/0044232	12/2015	Kim et al.	N/A	N/A
2018/0321504	12/2017	Hu et al.	N/A	N/A
2020/0409030	12/2019	Li	N/A	F03G 7/065

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103597394	12/2013	CN	N/A
2003-66309	12/2002	JP	N/A
2003-344903	12/2002	JP	N/A
2006-329111	12/2005	JP	N/A
2007-333792	12/2006	JP	N/A
2011-215351	12/2010	JP	N/A
2018194739	12/2017	JP	N/A
10-2007-0019893	12/2006	KR	N/A
10-2012-0052921	12/2011	KR	N/A
WO-2015045728	12/2014	WO	G02B 13/009

OTHER PUBLICATIONS

Korean Office Action issued on Apr. 21, 2023, in counterpart Korean Patent Application No. 10-2021-0063381 (5 pages in English, 4 pages in Korean). cited by applicant

Chinese Office Action Issued on Mar. 27, 2024, in Counterpart Chinese Patent Application No. 202210464821.5 (4 Pages in English, 7 Pages in Chinese). cited by applicant

Primary Examiner: Pham; Thomas K

Assistant Examiner: Jones; Jennifer A

Attorney, Agent or Firm: NSIP Law

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S)

(1) This application claims the benefit under 35 USC 119(a) of Korean Patent Application No. 10-2021-0063381 filed on May 17, 2021 in the Korean Intellectual Property Office, the entire disclosure of which is incorporated herein by reference for all purposes.

BACKGROUND

1. Field

(2) The following description relates to a lens actuator and a camera module including the same.

2. Description of Background

(3) A camera module has been basically used in a portable electronic device such as a tablet personal computer (PC) or a laptop computer as well as a smartphone, and an autofocus (AF) function, an optical image stabilization (OIS) function, a zoom function and the like have been added to a camera module for a mobile terminal.

(4) In addition, the camera module may include an actuator that directly moves a lens or indirectly moves a reflection module including the reflective member, for image stabilization. In general, the actuator may also move the lens or the reflection module using driving force generated by a magnet and a coil.

(5) Meanwhile, there has been increasing demand for high-definition and high-magnification captured using a small camera module such as the camera module for a mobile terminal. However, in the prior art, it is difficult to implement a zoom function with high magnification by driving a plurality of lens groups.

(6) In particular, when the plurality of lens groups are moved using the actuator including the magnet and the coil, it may be difficult for the camera module to have a small size due to sizes of the magnet and the coil, included in the actuator.

(7) In addition, when the plurality of lens groups are moved using the actuator including the magnet and the coil, the actuator may consume a large amount of power and it may be difficult to precisely control the plurality of lens groups.

SUMMARY

(8) This Summary is provided to introduce a selection of concepts in simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

(9) In one general aspect, a lens actuator includes: a lens barrel accommodating one or more lenses; and a driving unit configured to move the lens barrel along an optical axis direction. The driving unit includes: a driving wire, at least a portion of which is extended in the optical axis direction, and a length of which is changed as voltage is applied thereto; and a driving transmission unit connected to the driving wire and configured to move the lens barrel along the optical axis direction as the length of the driving wire is changed such that a distance the lens barrel is moved

by the driving transmission unit is greater than an amount of change in the length of the driving wire.

(10) As the voltage or current is applied to the driving wire, at least a portion of the driving wire may be contracted in the optical axis direction.

(11) The driving transmission unit may include: a crank gear connected to the driving wire and configured to rotate about a rotation axis crossing an optical axis; a pulley gear configured to rotate while meshing with the crank gear; and a guide wire connected to the pulley gear and configured to move as the pulley gear is rotated, and the lens barrel may be fixed to at least a portion of the guide wire.

(12) A first end of the crank gear may be connected to the driving wire, a second end of the crank gear may mesh with the pulley gear, and a distance from the first end of the crank gear to the rotation axis of the crank gear may be shorter than a distance from the second end of the crank gear to the rotation axis of the crank gear.

(13) The pulley gear may include a first wheel meshing with the second end of the crank gear and a second wheel to which the guide wire is connected, and an outer diameter of the second wheel may be greater than an outer diameter of the first wheel.

(14) The second end of the crank gear and an outer ring of the first wheel of the pulley gear may be teeth-coupled to each other.

(15) The driving wire may include a first driving wire configured to rotate the crank gear in a first direction as a length of the first driving wire is reduced and a second driving wire configured to rotate the crank gear in a second direction opposite to the first direction as a length of the second driving wire is reduced, and changes in the lengths of the first driving wire and the second driving wire may be controlled independently of each other.

(16) One or both of the first driving wire and the second driving wire may be made of a shape memory alloy, a length of which is changed when the voltage is applied thereto.

(17) The lens actuator may include a wire connection member connecting one or both of the first driving wire and the second driving wire to the crank gear, and the wire connection member may include a conductive material.

(18) The driving transmission unit may include: a crankshaft supporting the crank gear; and a crank fixation member disposed at an end of the crankshaft to support the crank gear so as not to be separated from the crankshaft.

(19) The driving transmission unit may include a sub-pulley gear spaced apart from the pulley gear in the optical axis direction, the guide wire may connect the pulley gear and the sub-pulley gear to each other, and the lens barrel may be connected to the guide wire between the pulley gear and the sub-pulley gear.

(20) A fixation groove, to which at least a portion of the guide wire is fixed, may be disposed in an outer circumferential surface of the pulley gear.

(21) The driving transmission unit may include a guide gear disposed between the pulley gear and the sub-pulley gear, and configured to guide at least a portion of the guide wire to be moved in a direction parallel to the optical axis direction.

(22) In another general aspect, a lens actuator may include: a lens barrel accommodating one or more lenses; and a driving unit configured to move the lens barrel in an optical axis direction. The driving unit includes a first driving wire and a second driving wire at least a portion of each of which is extended along the optical axis direction, and a length of each of which is changed as voltage is applied thereto, and a driving transmission unit configured to move the lens barrel in a first direction parallel to the optical axis direction as the length of the first driving wire is contracted, and to move the lens barrel in a second direction opposite to the first direction as the length of the second driving wire is contracted.

(23) The first driving wire and the second driving wire may be disposed opposite to each other in a direction crossing the optical axis direction.

(24) A camera module may include the plurality of lens actuators, and respective driving units included in each of the plurality of lens actuators may be controlled independently of each other.

(25) In another general aspect, a lens actuator includes: a lens barrel including one or more lenses; a driving wire configured to extend and contract in an optical axis direction as voltage is applied thereto; and a driving transmission connected to the driving wire and configured to move the lens barrel along the optical axis direction as the length of the driving wire is changed such that a distance the lens barrel is moved by the driving transmission unit is greater than an amount of change in the length of the driving wire. The driving transmission includes: a crank gear connected to the driving wire and configured to rotate about a rotation axis crossing an optical axis; and a pulley gear configured to rotate while meshing with the crank gear. A first end of the crank gear is connected to the driving wire, a second end of the crank gear is connected with the pulley gear, and a distance from the first end of the crank gear to the rotation axis of the crank gear is different than a distance from the second end of the crank gear to the rotation axis of the crank gear.

(26) The distance from the first end of the crank gear to the rotation axis of the crank gear may be less than the distance from the second end of the crank gear to the rotation axis of the crank gear.

(27) Other features and aspects will be apparent from the following detailed description, the drawings, and the claims.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a perspective view of a camera module.
- (2) FIG. 2 is an exploded perspective view of a camera module.
- (3) FIG. 3 is an exploded perspective view of a lens actuator.
- (4) FIGS. 4A and 4B are exemplary views each showing that a driving wire and a crank gear are coupled to each other.
- (5) FIG. 5 is a view showing that a portion of a driving transmission unit and a lens barrel are coupled to each other.
- (6) FIGS. 6A, 6B, 6C, and 6D are side views each showing a lens actuator positioned in the camera module.
- (7) FIG. 7 is an exemplary view showing that the plurality of lens actuators positioned in the camera module are coupled to each other.
- (8) FIGS. 8A and 8B are top views each showing that an upper cover is omitted from the camera module.
- (9) Throughout the drawings and the detailed description, the same reference numerals refer to the same elements. The drawings may not be to scale, and the relative size, proportions, and depictions of elements in the drawings may be exaggerated for clarity, illustration, and convenience.

DETAILED DESCRIPTION

- (10) The following detailed description is provided to assist the reader in gaining a comprehensive understanding of the methods, apparatuses, and/or systems described herein. However, various changes, modifications, and equivalents of the methods, apparatuses, and/or systems described herein will be apparent to one of ordinary skill in the art. The sequences of operations described herein are merely examples, and are not limited to those set forth herein, but may be changed as will be apparent to one of ordinary skill in the art, with the exception of operations necessarily occurring in a certain order. Also, descriptions of functions and constructions that would be well known to one of ordinary skill in the art may be omitted for increased clarity and conciseness.
- (11) The features described herein may be embodied in different forms, and are not to be construed as being limited to the examples described herein. Rather, the examples described herein have been provided so that this disclosure will be thorough and complete, and will fully convey the scope of

the disclosure to one of ordinary skill in the art.

(12) Herein, it is noted that use of the term “may” with respect to an example or embodiment, e.g., as to what an example or embodiment may include or implement, means that at least one example or embodiment exists in which such a feature is included or implemented while all examples and embodiments are not limited thereto.

(13) Throughout the specification, when an element, such as a layer, region, or substrate, is described as being “on,” “connected to,” or “coupled to” another element, it may be directly “on,” “connected to,” or “coupled to” the other element, or there may be one or more other elements intervening therebetween. In contrast, when an element is described as being “directly on,” “directly connected to,” or “directly coupled to” another element, there can be no other elements intervening therebetween.

(14) As used herein, the term “and/or” includes any one and any combination of any two or more of the associated listed items.

(15) Although terms such as “first,” “second,” and “third” may be used herein to describe various members, components, regions, layers, or sections, these members, components, regions, layers, or sections are not to be limited by these terms. Rather, these terms are only used to distinguish one member, component, region, layer, or section from another member, component, region, layer, or section. Thus, a first member, component, region, layer, or section referred to in examples described herein may also be referred to as a second member, component, region, layer, or section without departing from the teachings of the examples.

(16) Spatially relative terms such as “above,” “upper,” “below,” and “lower” may be used herein for ease of description to describe one element's relationship to another element as illustrated in the figures. Such spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, an element described as being “above” or “upper” relative to another element will then be “below” or “lower” relative to the other element. Thus, the term “above” encompasses both the above and below orientations depending on the spatial orientation of the device. The device may also be oriented in other ways (for example, rotated 90 degrees or at other orientations), and the spatially relative terms used herein are to be interpreted accordingly.

(17) The terminology used herein is for describing various examples only, and is not to be used to limit the disclosure. The articles “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. The terms “comprises,” “includes,” and “has” specify the presence of stated features, numbers, operations, members, elements, and/or combinations thereof, but do not preclude the presence or addition of one or more other features, numbers, operations, members, elements, and/or combinations thereof.

(18) Due to manufacturing techniques and/or tolerances, variations of the shapes illustrated in the drawings may occur. Thus, the examples described herein are not limited to the specific shapes illustrated in the drawings, but include changes in shape that occur during manufacturing.

(19) The features of the examples described herein may be combined in various ways as will be apparent after an understanding of the disclosure of this application. Further, although the examples described herein have a variety of configurations, other configurations are possible as will be apparent after an understanding of the disclosure of this application.

(20) The drawings may not be to scale, and the relative sizes, proportions, and depiction of elements in the drawings may be exaggerated for clarity, illustration, and convenience.

(21) Hereinafter, various examples will be described in detail with reference to the accompanying drawings.

(22) FIG. 1 is a perspective view of a camera module **10** according to an example; and FIG. 2 is an exploded perspective view of the camera module **10**.

(23) The camera module **10** may include a reflection module and one or more lens actuators **400** and **500** in an internal space of a housing **100** and an upper cover **800**, forming an appearance of

the camera module **10**.

(24) The camera module **10** may be positioned in a portable electronic device, such as a mobile communications terminal, a smartphone or a tablet personal computer (PC), to capture a subject outside the electronic device. To this end, the camera module **10** may include one or more lens actuators **400** and **500** in the housing **100**.

(25) When the camera module **10** includes the plurality of lens actuators **400** and **500**, an optical axis direction of the lens included in the plurality of lens actuators **400** and **500** positioned in the camera module **10** may be a direction (e.g., Z-axis direction) perpendicular to a thickness direction (e.g., Y-axis direction) of the camera module **10**. Therefore, the camera module **10** may not have an increased overall thickness even when having the plurality of lens actuators **400** and **500**, and may be easily accommodated in an internal space of the mobile communications terminal, tablet PC or the like.

(26) The lens actuators **400** and **500** may each include a driving unit adjusting positions of the plurality of lenses **433** (in FIG. 3 for example). The camera module **10** may use each driving unit of the lens actuators **400** and **500** to move the lens in the housing **100** or adjust a distance between the plurality of lenses, thereby performing an autofocus function, a zoom function and an image stabilization (OIS) function.

(27) As having a more complex structure, and the increasing number of lenses positioned in the housing **100**, the camera module **10** may require the driving unit which may precisely adjust the positions of the plurality of lenses. In particular, the plurality of stacked lenses is required to be accurately and quickly moved in the optical axis direction to perform the zoom function of high magnification, and a performance of the driving unit driving the lenses may thus be more important. However, a conventional lens actuator including a magnet and a coil is difficult to precisely control the plurality of lenses.

(28) In order to solve this problem, the various examples disclosed herein include the lens actuators **400** and **500** each including the driving unit which may accurately and quickly move the plurality of lenses, and the camera module **10** including the same. Hereinafter, the description describes the lens actuators **400** and **500** and a configuration of the camera module **10** including the same in detail with reference to FIG. 2.

(29) The camera module **10** may include a reflection module **200** which may change a propagation path of incident light, the one or more lens actuators **400** and **500** positioned adjacent to the reflection module **200**, and an image sensor module **600** positioned behind the lens actuators **400** and **500**. The reflection module **200**, the lens actuators **400** and **500** and the image sensor module **600** may be accommodated in the housing **100**, and may be electrically connected to a substrate **700**. The housing **100** may have an open top and may accommodate the reflection module **200** and the one or more lens actuators **400** and **500**. The upper cover **800** may cover the top of the housing **100** to protect the reflection module **200** accommodated in the housing **100**, and the one or more lens actuators **400** and **500** from an external environment. The upper cover **800** may include an opening **810** through which the incident light is incident, and the reflection module **200** may be disposed under the opening **810**. Therefore, the incident light incident in a height direction (e.g., Y-axis direction) of the housing **100** through the opening **810** of the upper cover **800** may change its propagation path through the reflection module **200** disposed under the opening **810**. A protection member **820**, which may protect the reflection module **200** from the external environment, may be positioned in the opening **810** of the upper cover **800**.

(30) The reflection module **200**, the lens actuators **400** and **500** and the image sensor module **600** may be sequentially arranged in the housing **100** from one side to the other side (for example, along the Z-axis direction). The housing **100** may have the internal space in which the reflection module **200**, the lens actuators **400** and **500** and the image sensor module **600** are inserted. The substrate **700**, which is electrically connected to each driving unit of the lens actuators **400** and **500** or the image sensor module **600**, may be attached to the inside or outside of the housing **100**. The housing

100 may be formed as one whole piece to insert all of the reflection module **200** and the lens actuators **400** and **500** in its internal space. However, the configuration is not limited thereto, and may have separate housings into which the reflection module **200** and the lens actuators **400** and **500** are respectively inserted, and which are interconnected to each other for example.

(31) The housing **100** may be covered by the upper cover **800** for its internal space not to be visible. The upper cover **800** may have the opening **810** in which the light is incident, and the light incident through the opening **810** may have its propagation direction changed by the reflection module **200** to be incident on the lens actuators **400** and **500**. The upper cover **800** may be one piece to cover the entire housing **100**, or may be formed as separate members respectively covering the reflection module **200** and the lens actuators **400** and **500**. The propagation path of the light incident through the opening in the thickness direction (e.g., Y-axis direction) of the camera module **10** may be changed to be in a direction approximately coinciding with the optical-axis direction (e.g., Z-axis direction) by the reflection module **200**.

(32) The reflection module **200** may change the propagation path of the incident light to be in the optical axis direction (e.g., Z-axis direction) of each of the lens actuators **400** and **500**. The reflection module **200** may include a reflection member **210** capable of changing the propagation path of the light, a reflection member holder **220** supporting the reflection member **210**, and a reflection module driving unit moving the reflection member holder **220**.

(33) The reflection member **210** may change the propagation path of the incident light by reflecting or refracting the same. For example, the reflection member **210** may be a prism having a reflection surface. The reflection member **210** may be accommodated in the reflection member holder **220** and moved based on the housing **100**. As the reflection member **210** is properly moved, the incident light incident in the height direction (e.g., Y-axis direction) of the housing **100** may have the propagation path changed in the optical-axis direction (e.g., Z-axis direction) of each of the lens actuators **400** and **500**.

(34) The reflection member holder **220** may support the reflection member **210** to be movable. The reflection member holder **220** may be rotated or moved based on the housing **100** by the reflection module driving unit. The reflection module driving unit may be electrically connected to the substrate **700**, and may receive energy from an external source to rotate or move the reflection member holder **220**. For example, as shown in FIG. 2, the reflection module driving unit may include a magnet **230** attached to the reflection member holder **220** and a coil **240** (or coils **240**) positioned in the housing **100** and electrically connected to the substrate **700**. When current or voltage is applied to the coil **240** of the reflection module driving unit, an electromagnetic force may be generated by interaction between the magnet **230** and the coil **240**, and the generated electromagnetic force may be used to rotate or move the reflection member holder **220**. However, the reflection module driving unit according to this configuration, shown in FIG. 2, is only an example, and may include a coil positioned on the reflection member holder **220** and a magnet positioned in the housing **100**.

(35) The reflection module **200** may properly rotate or move the reflection member **210**, thereby either changing the propagation path of the incident light to be in a direction coincide with the optical axis direction of each of the lens actuators **400** and **500**, or performing the image stabilization function in response to vibration outside the camera module **10**.

(36) The camera module **10** may include the one or more lens actuators **400** and **500** adjacent to the reflection module **200**. For example, as shown in FIG. 2, the camera module **10** may include the first lens actuator **400** and the second lens actuator **500**, positioned between the reflection module **200** and the image sensor module **600**. At least one of the first lens actuator **400** and the second lens actuator **500** may be moved in the optical axis direction (Z-axis direction). The lens actuators **400** and **500** may each be moved in the optical axis direction (Z-axis direction) by driving force generated by the driving unit. The movements of the lens actuators **400** and **500** are described below with reference to FIGS. 3 through 8. The camera module **10** may move at least one of the

plurality of lens actuators **400** and **500** in the optical axis direction (Z-axis direction) to perform the zoom function or the autofocus function.

(37) The camera module **10** may include one or more fixed lens units **300** to adjust a refraction degree of the incident light when performing the zoom function or the autofocus function. For example, as shown in FIG. 2, the camera module **10** may include the fixed lens unit **300** positioned between the reflection module **200** and the lens actuators **400** and **500** adjacent thereto. The fixed lens unit **300** may be fixedly positioned in the housing **100**. Accordingly, light emitted from the reflection module **200** may be incident on the image sensor module **600** through the fixed lens unit **300** and the one or more lens actuators **400** and **500**.

(38) The image sensor module **600** may be positioned behind the lens actuators **400** and **500**. The incident light passed through the lens actuators **400** and **500** may be incident on the image sensor module **600** to form an image. The image sensor module **600** may convert the incident light into an electrical signal.

(39) The camera module **10** may include the reflection module **200**, the one or more lens actuators **400** and **500**, and the substrate **700** electrically connected to the image sensor module **600**. The substrate **700** may be coupled to the housing **100** and electrically connected to the components of the camera module **10**. For example, the substrate **700** may transmit and receive the electrical signal including a control signal to the coil **240** of the reflection module driving unit or each driving unit of the lens actuators **400** and **500**.

(40) Each of the lens actuators **400** and **500** included in the camera module **10** may receive electrical energy from the substrate **700**, and may be moved in the optical axis direction (e.g., Z-axis direction), thereby performing the zoom function or the autofocus function.

(41) Hereinafter, a configuration of each of the lens actuators **400** and **500** according to the various examples is described in detail with reference to FIGS. 3 through 6. The description describes the detailed configuration of one lens actuator **400** (in FIG. 3 for example) with reference to FIGS. 3 through 6. However, this detailed configuration of the lens actuator **400** shown in FIGS. 3 through 6 may be applied to each of the plurality of lens actuators **400** and **500** shown in FIG. 2. For example, the first lens actuator **400** and the second lens actuator **500**, shown in FIG. 2 may each include a lens barrel **430** (in FIG. 3 for example) and the driving unit, shown in FIGS. 3 through 6.

(42) FIG. 3 is an exploded perspective view of the lens actuator **400**. The lens actuator **400** and the camera module, described with reference to FIG. 3, respectively correspond to the lens actuator **400** or **500** and the camera module **10**, described above with reference to FIGS. 1 and 2, and redundant descriptions thereof are thus omitted.

(43) The lens actuator **400** may include the lens barrel **430** accommodating the one or more lenses **433** and the driving unit connected to the lens barrel **430** and moving the lens barrel **430** based on the housing **100** in the optical axis direction (e.g., Z-axis direction).

(44) The lens barrel **430** may include the one or more lenses **433**. When the plurality of lenses is positioned in the one lens barrel **430**, the plurality of lenses may be aligned in the lens barrel **430** in the optical axis direction.

(45) The lens barrel **430** may be moved in the housing **100** in the optical axis direction (e.g., Z-axis direction). For example, as shown in FIG. 3, the lens barrel **430** may be positioned in the housing **100** and moved within a predetermined range in the optical axis direction (Z-axis direction).

(46) One or more guide rails **111** and **112** each guiding the movement of the lens barrel **430** may be positioned in the housing **100**. For example, the guide rails **111** and **112** may be extended from a bottom surface of the housing **100** in the optical axis direction (Z-axis direction). The one or more guide rails **111** and **112** may be positioned, and for example, as shown in FIG. 3, the plurality of guide rails **111** and **112** extended in the optical axis direction (Z-axis direction) may be positioned in parallel to each other by a predetermined distance in a width direction (e.g., the X-axis direction) of the housing **100**.

(47) The lens barrel **430** may be seated on the guide rails **111** and **112** and may be moved in the

optical axis direction (Z-axis direction). That is, the guide rails **111** and **112** may serve to guide the lens barrel **430** to be moved along a predetermined path in the optical axis direction (Z-axis direction). In addition, as the guide rails **111** and **112** are positioned thereon, a contact area between the lens barrel **430** and the bottom surface of the housing **100** may be reduced, thereby reducing a friction force between the lens barrel **430** and the housing **100** when the lens barrel **430** is moved. (48) A guide groove **432** accommodating at least a portion of each of the guide rails **111** and **112** may be positioned in a portion of a bottom surface of the lens barrel **430**, in which the lens barrel **430** and the guide rails **111** and **112** are in contact with each other. Accordingly, the lens barrel **430** may be moved in the optical axis direction (Z-axis direction) along the guide rails **111** and **112** while at least a portion of each of the guide rails **111** and **112** are accommodated in the guide groove **432**. As the guide groove **432** is positioned therein, the lens barrel **430** may be stably slid without being separated from the guide rails **111** and **112** even when an impact is applied from the outside of the lens actuator **400**.

(49) A friction reduction member (not shown) which may reduce the friction force may be further positioned between the guide groove **432** of the lens barrel **430** and the guide rails **111** and **112** of the housing **100**. For example, the friction reduction member (not shown) including at least one of a bush, a bearing, a roller and a ball member, made of a material which may reduce the friction force, may be positioned in the guide groove **432** of the lens barrel **430**.

(50) The driving unit may generate the driving force that moves the lens barrel **430** in the optical axis direction (Z-axis direction). The driving unit may include a driving wire **411** a length of which is changed and a driving transmission unit connected to the driving wire **411** and moving the lens barrel **430** using driving force generated from the driving wire **411**.

(51) The driving wire **411** may be made of a material a length of which is changed based on the control signal. For example, the driving wire **411** may be made of a shape memory alloy (SMA) material the length of which is changed when the current or the voltage is applied thereto. Both ends of the driving wire **411** may be electrically connected to the substrate **700** (in FIG. 2 for example), and may receive the current or the voltage from an external power source (not shown). That is, the driving wire **411** may be made of the conductive SMA material through which the current may flow, and one end and the other end of the driving wire **411** may respectively be connected to different portions of the substrate **700** in FIG. 2, to form a closed circuit leading to the power source (not shown). When the current or the voltage is applied to both ends of the driving wire **411** by the power source (not shown), an entire length of the driving wire **411** may be contracted or extended.

(52) One end of the driving wire **411** may be fixed to the housing **100**, and the other end thereof may be connected to the driving transmission unit. For example, as shown in FIG. 3, one end of the driving wire **411** may be coupled to a wire fixation member **412** and fixed to an inner surface of the housing **100**. The other end of the driving wire **411** may be connected to a crank gear **414** included in the driving transmission unit. A wire connection member **413** binding the crank gear **414** and the driving wire **411** to each other may be positioned at a portion in which the crank gear **414** and the driving wire **411** are connected to each other. The wire fixation member **412** and the wire connection member **413** may each be formed of a conductive material through which the current may flow.

(53) As the length of the driving wire **411** is changed, the other end of the driving wire **411**, connected to the crank gear **414** may rotate the crank gear **414**. For example, as shown in FIG. 3, the other end of the driving wire **411** may be fixed to the crank gear **414** by the wire connection member **413**, and may rotate the crank gear **414** about a constant rotation axis (e.g., rotation axis formed by a crankshaft **415a**) as the length of the driving wire **411** is contracted.

(54) The one or more driving wires **411** may be included in the driving unit. For example, as shown in FIG. 3, the plurality of driving wires **411** may be included in the driving unit, and each of the driving wires **411** may be made of a material the length of which is changed based on the control

signal. The plurality of driving wires **411** may each be coupled to a different portion of the crank gear **414**, and accordingly, as the length of each driving wire **411** is changed, the crank gear **414** may be rotated in a different direction. For example, as shown in FIG. 3, the two driving wires **411** may be coupled to the crank gear **414** with a rotational shaft of the crank gear **414** (e.g., rotational shaft formed by the crankshaft **415a**) interposed therebetween. Accordingly, the crank gear **414** may be rotated clockwise when any one of the driving wires **411** is contracted, and the crank gear **414** may perform a rotational motion counterclockwise when the other driving wire **411** is contracted. The rotational motion of the crank gear **414** based on the change in the length of the driving wire **411** is described below with reference to FIG. 4 or 6.

(55) The driving transmission unit may convert a force generated as the length of the driving wire **411** is contracted or extended into the driving force that moves the lens barrel **430**. The driving transmission unit may include the crank gear **414** connected to the driving wire **411**, a pulley gear **421** connected to the crank gear **414**, and a guide wire **423** connecting the pulley gear **421** and the lens barrel **430** to each other.

(56) The crank gear **414** may be connected to the driving wire **411** and may be rotated about the constant rotation axis based on whether the driving wire **411** is contracted or extended. The rotation axis of crank gear **414** may be in a direction (e.g., X-axis direction) crossing the optical axis direction (Z-axis direction). The crank gear **414** may be supported on the inner wall of the housing **100** to be rotated by the crankshaft **415a**. Therefore, the rotation axis of the crank gear **414** may be formed by the crankshaft **415a** supporting the crank gear **414** to be rotatable. A crank fixation member **415b** may be positioned at an end of the crankshaft **415a** to prevent the crank gear **414** from being separated from the crankshaft **415a**.

(57) The pulley gear **421** may be connected to the crank gear **414** and may be rotated about the constant rotation axis based on the rotation of the crank gear **414**. The rotation axis of the pulley gear **421** may be formed parallel to the rotation axis of the crank gear **414**. The pulley gear **421** may be supported on the inner wall of the housing **100** to be rotated by a pulley shaft **425a**. Therefore, the rotation axis of the pulley gear **421** may be formed by the pulley shaft **425a** supporting the pulley gear **421** to be rotatable. A pulley fixation member **425b** may be positioned at an end of the pulley shaft **425a** to prevent the pulley gear **421** from being separated from the pulley shaft **425a**. The guide wire **423** may be connected to the pulley gear **421**. For example, as shown in FIG. 3, the pulley gear **421** may include a first wheel **421a** connected to the crank gear **414** and a second wheel **421b** connected to the guide wire **423**. The first wheel **421a** and the second wheel **421b** may be integrally formed with each other and may be rotated together. Therefore, when the crank gear **414** rotates the first wheel **421a**, the second wheel **421b** may also be rotated together with the first wheel **421a**.

(58) A sub-pulley gear **422** may be positioned spaced apart from the pulley gear **421** in the optical axis direction (e.g., Z-axis direction), and may be supported on an inner surface of the housing **100** to be rotated by a sub-pulley shaft **427a**. A rotation axis of the sub-pulley gear **422** may be formed parallel to the rotation axis of the pulley gear **421** (e.g., rotation axis formed by the pulley shaft **425a**), and may be formed by the sub-pulley shaft **427a**. A sub-pulley fixation member **427b** may be positioned at an end of the sub-pulley shaft **427a** to prevent the sub-pulley gear **422** from being separated from the sub-pulley shaft **427a** during its rotation.

(59) The guide wire **423** may be connected to at least a portion of the pulley gear **421**, and may move the lens barrel **430** in the optical axis direction. The guide wire **423** may be connected to at least portions of the pulley gear **421** and the sub-pulley gear **422** by winding the same, and may be rotated between the pulley gear **421** and the sub-pulley gear **422** based on the rotation of the pulley gear **421**. For example, as shown in FIG. 3, the guide wire **423** may have a shape of a belt connecting the pulley gear **421** and the sub-pulley gear **422** spaced apart from each other in the optical axis direction (Z-axis direction), and may be rotated between the pulley gear **421** and the sub-pulley gear **422** based on the rotation of the pulley gear **421**.

(60) The lens barrel **430** may be connected to at least a portion of the guide wire **423**. For example, as shown in FIG. 3, the lens barrel **430** may be coupled to at least a portion of the guide wire **423** positioned between the pulley gear **421** and the sub-pulley gear **422**. A fixation clip **431** into which the guide wire **423** may be inserted may be positioned on a side surface of the lens barrel **430** to stably fix the lens barrel **430** to the guide wire **423**. The lens barrel **430** may be fixed to at least a portion of the guide wire **423**, and may be moved in the optical axis direction (Z-axis direction) together with the guide wire **423** as the guide wire **423** is rotated between the pulley gear **421** and the sub-pulley gear **422**.

(61) The driving unit may further include a guide gear **424** positioned between the pulley gear **421** and the sub-pulley gear **422**, and guiding at least a portion of the guide wire **423** to be rotated while maintaining its direction to be parallel to the optical axis direction. For example, as shown in FIG. 3, the guide gear **424** may be positioned between the pulley gear **421** and the sub-pulley gear **422**. The guide gear **424** may be in contact with at least a portion of the guide wire **423** connected to the pulley gear **421**, and may guide the guide wire **423** to be moved between the pulley gear **421** and the sub-pulley gear **422** while maintaining its direction to be parallel to the optical axis direction (Z-axis direction). At least a portion of the guide wire **423** to which the lens barrel **430** is connected may be moved in the direction parallel to the optical axis direction (Z-axis direction) by the guide of the guide gear **424**, and the lens barrel **430** connected to the guide wire **423** may also be stably moved in the optical axis direction (Z-axis direction). The guide gear **424** may be supported to be rotated by a guide gear shaft **426a** and may thus be positioned to be rotated about a rotation axis formed by the guide gear shaft **426a**. A guide gear fixation member **426b** may be positioned at an end of the guide gear shaft **426a** to prevent the guide gear **424** from being separated from the guide gear shaft **426a**.

(62) The guide gear **424** may be positioned to be rotated about the axis parallel to the rotation axis of the pulley gear **421**. For example, the rotation axes of the pulley gear **421**, sub-pulley gear **422** and guide gear **424** included in the driving unit may be formed parallel to one another.

(63) The driving unit of the lens actuator **400** may convert the force generated when the length of the driving wire **411** is contracted or extended (e.g., tension generated when the driving wire **411** is contracted) into the driving force that moves the lens barrel **430** using the driving transmission unit. Hereinafter, a configuration of the driving transmission unit is described in detail with reference to FIGS. 4A through 5.

(64) FIGS. 4A and 4B are views each showing that driving wires **411a** and **411b** and a crank gear **414**, included in the lens actuator, are coupled to each other. The lens actuator, and the driving wires **411a** and **411b** and the crank gear **414**, included therein, described with reference to FIGS. 4A and 4B respectively correspond to the lens actuators **400** and **500**, and the driving wire **411** and the crank gear **414**, included therein, described above with reference to FIGS. 2 and 3, and redundant descriptions thereof are thus omitted.

(65) The lens actuator may include the driving wires **411a** and **411b** and the driving transmission unit connected to the driving wires **411a** and **411b**. The driving transmission unit may include the crank gear **414** in contact with and connected to the driving wires **411a** and **411b**, the pulley gear **421** connected to the crank gear **414**, and the guide wire **423** (in FIG. 3 for example), connected to the pulley gear **421**. FIGS. 4A and 4B each show that the crank gear **414** included in the driving transmission unit is connected to the driving wires **411a** and **411b**. The one or more driving wires **411a** and **411b** may be included in the driving unit, and may be the first driving wire **411a** and the second driving wire **411b** each connected to a different portion of the crank gear **414** for example, as shown in FIG. 4A.

(66) The driving wires **411a** and **411b** may each be made of a material the length of which is changed. For example, at least one of the first driving wire **411a** and the second driving wire **411b** may include a shape memory alloy the length of which is changed when the current or the voltage is applied thereto.

(67) One end of each of the driving wires **411a** and **411b** may be connected to wire fixation members **412a** and **412b**, and may be fixed to the housing. For example, as shown in FIG. 4A, the first driving wire **411a** may be connected to the first wire fixation member **412a** and fixed to the housing, and the second driving wire **411b** may be connected to the second wire fixation member **412b** and fixed to the housing. The wire fixation members **412a** and **412b** may each be made of the conductive material, and the driving wires **411a** and **411b** may be electrically connected to the substrate **700** in FIG. 2 through the wire fixation members **412a** and **412b**. The first wire fixation member **412a** and the second wire fixation member **412b** may be electrically separated from each other. Accordingly, the current or the voltage may be applied to only one of the first driving wire **411a** and the second driving wire **411b**. Alternatively, magnitude of the voltage or an amount of the current, applied to the first driving wire **411a** and the second driving wire **411b** may be configured to be different from each other. Alternatively, time intervals during which the voltage is applied to the first driving wire **411a** and the second driving wire **411b** may be configured to be different from each other.

(68) The other end of each of the driving wires **411a** and **411b** may be connected to the crank gear **414**. Wire connection members **413a** and **413b**, which respectively bind the crank gear **414** and the driving wires **411a** and **411b** to each other, may each be positioned at a portion where the crank gear **414** and the driving wires **411a** and **411b** are connected to each other. The wire connection members **413a** and **413b** may connect at least one of the first driving wire **411a** and the second driving wire **411b** to the crank gear **414**. For example, as shown in FIG. 4A, the other end of each of the driving wires **411a** and **411b** may be in contact with and connected to the crank gear **414**, and the wire connection members **413a** and **413b** may respectively wrap and secure the ends of the driving wires **411a** and **411b** and crank gear **414**. The wire connection members **413a** and **413b** may be made of the conductive material through which the current may flow. The other end of each of the driving wires **411a** and **411b** may be electrically connected to the substrate **700** in FIG. 2 through a wire **416**. The wire may be in direct contact with and connected to the other end of each of the driving wires **411a** and **411b**, or may be connected to the wire connection members **413a** and **413b** respectively wrapping the driving wires **411a** and **411b**. As one end and the other end of each of the driving wires **411a** and **411b** are electrically connected to the substrate **700** in FIG. 2, respectively, a closed circuit may be formed from the power source through the driving wires **411a** and **411b**, and the current or the voltage may thus be applied to the driving wires **411a** and **411b**.

(69) The crank gear **414** may be connected to the driving wires **411a** and **411b** and may be positioned to be rotated about the constant rotation axis. For example, as shown in FIG. 4A, the crank gear **414** may be supported to be rotated by the crankshaft **415a**, and may thus be rotated about the rotation axis formed by the crankshaft **415a**. The crank fixation member **415b** that binds the crankshaft **415a** and crank gear **414** to each other may be positioned at the end of the crankshaft **415a** to prevent the crank gear **414** from being separated from the crankshaft **415a**.

(70) One end of the crank gear **414** may be connected to the driving wires **411a** and **411b**. In the following description, the one end of the crank gear **414** connected to the driving wires **411a** and **411b** is defined as a first connection portion. For example, as shown in FIG. 4A, the first driving wire **411a** and the second driving wire **411b** may be connected to the first connection portion of the crank gear **414**. Therefore, as each length of the driving wires **411a** and **411b** is changed, the ends of the driving wires **411a** and **411b** may each be moved in a direction in which each length of the driving wires **411a** and **411b** is changed. In this case, the first connection portion of the crank gear **414** connected to the ends of the driving wires **411a** and **411b** may also be moved in the direction in which each length of the driving wires **411a** and **411b** is changed, and as the first connection portion of the crank gear **414** is moved, the crank gear **414** may be rotated about the crankshaft **415a**. That is, as each length of the driving wires **411a** and **411b** is changed, the crank gear **414** connected to the driving wires **411a** and **411b** may be rotated about the crankshaft **415a**.

(71) The first driving wire **411a** and the second driving wire **411b** may be connected to the crank

gear **414** with the crankshaft **415a** therebetween. Therefore, a direction in which the crankshaft **415a** is rotated as the first driving wire **411a** is contracted and a direction in which the crankshaft **415a** is rotated as the second driving wire **411b** is contracted may be opposite to each other. For example, as shown in FIGS. 4A and 4B, the first driving wire **411a** and the second driving wire **411b** may be aligned parallel to each other with the crankshaft **415a** therebetween to be connected to the first connection portion of the crank gear **414**. Accordingly, the crank gear **414** may be rotated in a first direction when the first driving wire **411a** positioned above the crankshaft **415a** is contracted, and the crank gear **414** may be rotated in a second direction opposite to the first direction when the second driving wire **411b** positioned below the crankshaft **415a** is contracted. That is, the contraction of the first driving wire **411a** and the contraction of the second driving wire **411b** may generate a torque in the crank gear **414** in different directions. Therefore, the crank gear **414** may be rotated in a desired direction by selectively contracting either the first driving wire **411a** or the second driving wire **411b**.

(72) The other end of the crank gear **414** may mesh with the pulley gear **421** and rotate the pulley gear **421**. In the following description, the other end of the crank gear **414** meshing with the pulley gear **421** is defined as a second connection portion **414a**. The second connection portion **414a** and first connection portion of the crank gear **414** may be integrally formed with each other. Accordingly, when the first connection portion of the crank gear **414** is rotated about the crankshaft **415a**, the second connection portion **414a** may be rotated together. That is, as the driving wires **411a** and **411b** are contracted, the first connection portion and second connection portion **414a** of the crank gear **414** may be rotated in the same direction about the crankshaft **415a**, and the pulley gear **421** meshing with the second connection portion **414a** of the crank gear **414** may also be rotated.

(73) The second connection portion **414a** of the crank gear **414** may be positioned to mesh with the first wheel **421a** of the pulley gear **421**, and a friction member (not shown) or a fastening structure may be further formed on a surface on which the two components mesh with each other to increase friction force therebetween. For example, as shown in FIGS. 4A and 4B, teeth may be formed on the second connection portion **414a** of the crank gear **414**. Accordingly, teeth having a shape corresponding to a shape of the teeth of the second connection portion **414a** may be also formed on the first wheel **421a** of the pulley gear **421** meshing with the second connection portion **414a**. Therefore, the second connection portion **414a** of the crank gear **414** and the first wheel **421a** of the pulley gear **421** may be rotated together while having their teeth coupled to each other. However, the shape of the teeth shown in FIGS. 4A and 4B is only an example, and the teeth may have various specific shapes. A friction member (not shown) capable of increasing frictional force may be positioned on at least one of an outer ring of the second connection portion **414a** of the crank gear **414** and an outer ring of the first wheel **421a** of the pulley gear **421**.

(74) A distance from the crankshaft **415a** to the first connection portion of the crank gear **414** may be different from a distance from the crankshaft **415a** to the second connection portion **414a**. For example, it may be assumed that the distance from the crankshaft **415a** to the first connection portion is referred to as a first distance C1, and the distance from the crankshaft **415a** to the second connection portion **414a** is referred to as a second distance C2. In this case, as shown in FIG. 4B, the first distance C1 may be shorter than the second distance C2. When the second distance C2 is longer than the first distance C1, a distance in which the second connection portion **414a** is moved as the crank gear **414** is rotated may be longer than a distance in which the first connection portion is moved. That is, even when the first connection portion to which the driving wires **411a** and **411b** are connected is moved by an amount of the changes in the lengths of the driving wires **411a** and **411b**, the second connection portion **414a** may be moved more than the amount of the changes in the lengths of the driving wires **411a** and **411b**. Accordingly, a rotation amount (or a length of a rotation trajectory) of the pulley gear **421** meshing with the second connection portion **414a** may also be increased. That is, as the first distance C1 and second distance C2 of the crank gear **414** are

different from each other, each rotation amount of the crank gear **414** and the pulley gear **421** may be relatively large even when the amount of the changes in the lengths of the driving wires **411a** and **411b** is relatively small.

(75) Hereinafter, the description describes that the pulley gear **421** included in the driving transmission unit according to the exemplary embodiments is connected to the lens barrel **430** with reference to FIG. 5.

(76) FIG. 5 is a view showing that a portion of the driving transmission unit and the lens barrel **430** are coupled to each other. The lens actuator and the driving transmission unit, described with reference to FIG. 5, respectively correspond to the lens actuators **400** and **500** and the driving transmission unit, described above with reference to FIGS. 1 through 4B, and redundant descriptions thereof are thus omitted.

(77) The lens actuators **400** (in FIG. 3 for example) may each include the lens barrel **430** and the driving transmission unit moving the lens barrel **430**. The driving transmission unit may include the crank gear **414** rotated by being connected to the driving wires **411a** and **411b**, the pulley gear **421** rotated while meshing with the crank gear **414** and the guide wire **423** rotated by being wound around at least a portion of an outer circumferential surface of the pulley gear **421** as the pulley gear **421** is rotated. The lens barrel **430** may be fixed to the guide wire **423**, and accordingly, as the guide wire **423** is moved, the lens barrel **430** may also be moved in a direction in which the guide wire **423** is moved.

(78) The pulley gear **421** may be a disk-shaped gear member including the first wheel **421a** meshing with the crank gear **414** and the second wheel **421b** to which the guide wire **423** is connected. The first wheel **421a** and the second wheel **421b** may be integrally formed with each other, and the first wheel **421a** and the second wheel **421b** may thus have the same rotation angle.

(79) The second connection portion **414a** (in FIG. 4B) of the crank gear **414** (in FIG. 4B) may be connected to the first wheel **421a** of the pulley gear **421**, and a detailed description thereof is made with reference to FIGS. 4A and 4B.

(80) The guide wire **423** may be connected to at least a portion of an outer circumferential surface of the second wheel **421b** of the pulley gear **421**. Therefore, as the pulley gear **421** is rotated, the guide wire **423** may also be rotated. The guide wire **423** may be connected to both the pulley gear **421** and the sub-pulley gear **422** positioned spaced apart from the pulley gear **421** in the optical axis direction (e.g., Z-axis direction). For example, as shown in FIG. 5, the guide wire **423** may have the shape of a belt or chain connecting the pulley gear **421** and the sub-pulley gear **422** to each other. Accordingly, when the pulley gear **421** is rotated, the guide wire **423** and the sub-pulley gear **422** may also be rotated. The guide wire **423** may be made of a flexible material to wrap the pulley gear **421** and the sub-pulley gear **422**. Alternatively, the guide wire **423** may be made of a material which may not be stretched even when an external force is applied thereto to stably connect the pulley gear **421** and the sub-pulley gear **422** with each other.

(81) A fixation groove **421c** to which at least a portion of the guide wire **423** is fixed may be positioned in the outer circumferential surface of the pulley gear **421**. For example, as shown in FIG. 5, the fixation groove **421c** in which a portion of the guide wire **423** is inserted and fixed may be positioned in the outer circumferential surface of the second wheel **421b** of the pulley gear **421**. As at least a portion of the guide wire **423** is fixed in the fixation groove **421c**, the guide wire **423** may be rotated together with the pulley gear **421** on the outer circumferential surface of the pulley gear **421** without spinning.

(82) The guide gear **424** may be positioned between the pulley gear **421** and the sub-pulley gear **422** for at least a portion of the guide wire **423** to be moved in the optical axis direction (e.g., Z-axis direction). The guide gear **424** may be in contact with at least a portion of the guide wire **423** to guide the guide wire **423** to be moved in the optical axis direction (e.g., Z-axis direction). For example, as shown in FIG. 5, the guide gear **424** may be positioned between the pulley gear **421** and the sub-pulley gear **422**, and the guide gear **424** may be in contact with the guide wire **423** to

guide the guide wire **423** to be extended in the optical axis direction (e.g., Z-axis direction).

(83) A radius r_3 of the sub-pulley gear **422** may be smaller than a radius r_2 of the second wheel **421b** of the pulley gear **421**. Accordingly, it is possible to allow the pulley gear **421** and the sub-pulley gear **422** to be spaced apart from each other as much as possible while maintaining an overall length of the guide wire **423**, and to secure a maximum distance in which the lens barrel **430** may be moved between the pulley gear **421** and the sub-pulley gear **422**.

(84) The lens barrel **430** may be fixedly coupled to a portion of the guide wire **423**, where the guide wire **423** is extended in the optical axis direction (e.g., Z-axis direction). For example, as shown in FIG. 5, the lens barrel **430** may be fixed to a portion of the guide wire **423** extended between the guide gear **424** and the sub-pulley gear **422**. The fixation clip **431** may engage the lens barrel **430** and the guide wire **423** to each other to fix the lens barrel **430** to the guide wire **423**. Accordingly, the lens barrel **430** fixed to at least a portion of the guide wire **423** may be moved in the optical axis direction (e.g., Z-axis direction) together with the guide wire **423** as the pulley gear **421** is rotated.

(85) A radius r_1 of the first wheel **421a** of the pulley gear **421** may be smaller than the radius r_2 of the second wheel **421b**. That is, an outer diameter of the first wheel **421a** of the pulley gear **421** may be smaller than an outer diameter of the second wheel **421b**. Accordingly, while the first wheel **421a** and the second wheel **421b** are rotated at the same rotation angle in the pulley gear **421**, a length of an arc formed by a point on the outer circumferential surface of the second wheel **421b** may be longer than a length of an arc formed by a point on an outer circumferential surface of the first wheel **421a**. A length of a rotational trajectory of the first wheel **421a** may correspond to a length of a rotational trajectory of the crank gear **414** (in FIG. 4B) rotated while meshing with the first wheel **421a**, and a length of a rotation trajectory of the second wheel **421b** may thus be longer than the length of the rotation trajectory of the crank gear **414** (in FIG. 4B). That is, the first wheel **421a** and second wheel **421b** of the pulley gear **421** may have outer diameters designed different from each other, and a distance in which the guide wire **423** connected to the second wheel **421b** is moved may thus be greater than the length of the rotation trajectory of the crank gear **414** (in FIG. 4B). Accordingly, a distance in which the lens barrel **430** is moved by being connected to the guide wire **423** may be greater than the length of the rotation trajectory of the crank gear **414** (in FIG. 4B).

(86) The first distance C_1 (in FIG. 4B) and second distance C_2 (in FIG. 4B) of the crank gear **414** (in FIG. 4B) may be different from each other, thereby making the length of the rotation trajectory of the second connection portion **414a** (in FIG. 4B) of the crank gear **414** (in FIG. 4B) longer than the amount of the changes in the lengths of the driving wires **411a** and **411b** (in FIG. 4B), which is described above with reference to FIGS. 4A and 4B.

(87) As a result, in the driving transmission unit including the crank gear **414** and the pulley gear **421**, the driving force generated by the length changes of the driving wires **411a** and **411b** may be transmitted to the lens barrel **430** through the crank gear **414** having the first distance C_1 (in FIG. 4B) and the second distance C_2 (in FIG. 4B) different from each other, and the pulley gear **421** having the outer diameter of the first wheel **421a** and the outer diameter of the second wheel **421b**, different from each other, thereby making the distance in which the lens barrel **430** is moved greater than the amount of the changes in the lengths of the driving wires **411a** and **411b**.

(88) Hereinafter, the description describes that each of the lens actuators **400** and **500** (in FIG. 2 for example), according to the various examples is driven with reference to FIGS. 6A through 6D.

(89) FIGS. 6A, 6B, 6C, and 6D are all side views each showing the lens actuator **400** or **500** (in FIG. 2) positioned in the camera module **10** (in FIG. 2 for example). The lens actuator **400** or **500** (in FIG. 2) and the camera module **10** (in FIG. 2), described with reference to FIGS. 6A through 6D respectively correspond to the lens actuator **400** or **500** (in FIG. 2) and the camera module **10** (in FIG. 2), described above with reference to FIGS. 1 through 5, and redundant descriptions thereof are thus omitted.

(90) The lens actuators **400** and **500** (in FIG. 2) may each include the lens barrel **430** which may be

moved in the optical axis direction (e.g., Z-axis direction), the driving wires **411a** and **411b** each generating the driving force to move the lens barrel **430**, and the driving transmission unit transmitting the driving force generated by the driving wires **411a** and **411b** to the lens barrel **430**. The driving transmission unit may include the crank gear **414** rotated by being connected to the driving wires **411a** and **411b**, the pulley gear **421** rotated by being connected with the crank gear **414**, and the guide wire **423** connected to the pulley gear **421** and the lens barrel **430** to move the lens barrel **430** as the pulley gear **421** is rotated.

(91) In each of the lens actuators **400** and **500** (in FIG. 2), at least each portion of the driving wires **411a** and **411b** may be extended in the optical axis direction (e.g., Z-axis direction). The one or more driving wires **411a** and **411b** may be included in the driving unit. When the plurality of driving wires **411a** and **411b** are included in the driving unit, at least a portion of each of the one or more driving wires **411a** and **411b** may be extended in the optical axis direction (e.g., Z-axis direction). For example, as shown in FIG. 6A, at least a portion of each of the first driving wire **411a** and the second driving wire **411b**, connected to the crank gear **414**, may be extended in the optical axis direction (e.g., Z-axis direction).

(92) The first driving wire **411a** and the second driving wire **411b** may be disposed opposite to each other in the direction crossing the optical axis direction (e.g., Z-axis direction). For example, as shown in FIG. 6A, the first driving wire **411a** and the second driving wire **411b** may be disposed in parallel to be opposite to each other in the direction (e.g., Y-axis direction) crossing the optical axis direction (e.g., Z-axis direction).

(93) The driving wires **411a** and **411b** may each be made of a shape memory alloy the length or shape of which is changed as the voltage or the current is applied thereto. One end of each of the driving wires **411a** and **411b** may be electrically connected to the substrate **700** (in FIG. 2 for example) by the wire fixation members **412a** and **412b**, and the other end of each of the driving wires **411a** and **411b** may be electrically connected to the substrate **700** (in FIG. 2) through the wire **416**. One end and the other end of each of the driving wires **411a** and **411b** may be electrically connected to the substrate **700** (in FIG. 2), respectively. Therefore, when applying a predetermined voltage between one end and the other end of each of the driving wires **411a** and **411b**, the current may flow in the driving wires **411a** and **411b**, thereby contracting or extending the driving wires **411a** and **411b**. For example, when the voltage is applied to both the ends of each of the driving wires **411a** and **411b**, at least a portion of each of the driving wires **411a** and **411b** may be contracted in the optical axis direction to have a reduced length, and as each length of the driving wires **411a** and **411b** is reduced, the tension may be generated in each of the driving wires **411a** and **411b**.

(94) The force generated as the length of each of the driving wires **411a** and **411b** is changed may be transmitted to the lens barrel **430** through the driving transmission unit. The driving transmission unit may include the crank gear **414** connected to the driving wires **411a** and **411b**, the pulley gear **421** connected to the crank gear **414**, and the guide wire **423** connected to the pulley gear **421**, and the lens barrel **430** may be connected to the guide wire **423** and may be moved along the guide wire **423** in the optical axis direction (e.g., Z-axis direction). A detailed structure in which the driving wires **411a** and **411b** and the crank gear **414** are connected to each other is described above with reference to FIGS. 4A and 4B, and a detailed structure in which the pulley gear **421** and the lens barrel **430** are connected to each other is described above with reference to FIG. 5.

(95) Hereinafter, the description describes an operation of the driving unit based on the length changes of the driving wires **411a** and **411b**.

(96) FIGS. 6B through 6D are exemplary views showing that the lens barrel **430** is moved in the optical axis direction (e.g., Z-axis direction) as the driving wires **411a** and **411b** are contracted. FIGS. 6B and 6C each show that the lens barrel **430** is moved in one direction on an optical axis as the first driving wire **411a** is contracted, and FIG. 6D shows that the lens barrel **430** is moved in a direction opposite to the direction shown in FIG. 6C as the second driving wire **411b** is contracted.

As shown in FIGS. 6B through 6D, the lens barrel **430** may be moved in the optical axis direction (e.g., Z-axis direction) by contracting at least one of the first driving wire **411a** and the second driving wire **411b**.

(97) First, the description describes that each of the lens actuators **400** and **500** (in FIG. 2) is driven with reference to FIGS. 6B and 6C.

(98) The first driving wire **411a** may be made of the shape memory alloy the length of which is contracted when the current or the voltage is applied thereto. When the current or the voltage is applied to the first driving wire **411a** to contract the first driving wire **411a**, the end of the first driving wire **411a**, connected to the crank gear **414** may be moved in a direction in which the first driving wire **411a** is contracted. As the end of the first driving wire **411a** is moved, the crank gear **414** connected to the first driving wire **411a** may be rotated about the rotation axis formed by the crankshaft **415a**. For example, as shown in FIG. 6B, when the first driving wire **411a** is connected to crank gear **414** below the crankshaft **415a**, the force contracting the first driving wire **411a** may generate the torque in the crank gear **414** in a clockwise direction. Therefore, the force contracting the first driving wire **411a** may cause the crank gear **414** to be rotated about the crankshaft **415a** in the clockwise direction.

(99) As the crank gear **414** is rotated, the pulley gear **421** connected to the crank gear **414** may also be rotated. For example, as shown in FIG. 6B, the second connection portion **414a** of the crank gear **414** and the first wheel **421a** of the pulley gear **421** may mesh with each other while having their teeth coupled to each other, and as the crank gear **414** is rotated in the clockwise direction, the pulley gear **421** may also be rotated in a counterclockwise direction. That is, as the crank gear **414** is rotated, the pulley gear **421** may be rotated in a direction opposite to the direction in which the crank gear **414** is rotated.

(100) As the pulley gear **421** is rotated, the guide wire **423** connected to the second wheel **421b** of the pulley gear **421** may also be rotated. For example, as shown in FIG. 6B, the guide wire **423** may have a shape of a ring connected to the pulley gear **421** and the sub-pulley gear **422**, positioned spaced apart from each other in the optical axis direction (e.g., Z-axis direction), and as the pulley gear **421** is rotated in the counterclockwise direction, the guide wire **423** may perform a circular motion between the pulley gear **421** and the sub-pulley gear **422** in the counterclockwise direction. For the guide wire **423** to smoothly perform the circular motion, the sub-pulley gear **422** may be rotated in the same direction as a direction in which the guide wire **423** performs the circular motion. The guide gear **424** may be positioned between the pulley gear **421** and the sub-pulley gear **422** for at least a portion of the guide wire **423** may be moved in the direction parallel to the optical axis direction (e.g., Z-axis direction). The guide gear **424** may be in contact with the guide wire **423** performing the circular motion to guide at least a portion of the guide wire **423** to be moved in the optical axis direction (e.g., Z-axis direction).

(101) The guide wire **423** may be moved as the pulley gear **421** is rotated, and the lens barrel **430** fixedly connected to the guide wire **423** may thus be moved together with the guide wire **423**. For example, as shown in FIG. 6B, the lens barrel **430** may be fixed to at least a portion of the guide wire **423** and moved in the optical axis direction (e.g., Z-axis direction) as the guide wire **423** performs the circular motion.

(102) The driving unit may adjust the distance in which the lens barrel **430** is moved by adjusting the amount of the changes in the lengths of the driving wires **411a** and **411b**. For example, it is possible to adjust the amount of the change in the length of the first driving wire **411a** by adjusting the magnitude of the voltage or current applied to the driving wires **411a** and **411b** or adjusting time in which the same is applied thereto. It is thus possible to adjust the rotation amounts of the crank gear **414**, pulley gear **421** and guide wire **423** of the driving transmission unit connected to the driving wires **411a** and **411b**, thereby adjusting the distance in which the lens barrel **430** is moved. That is, as shown in FIGS. 6B and 6C, it is possible to increase the rotation amounts of the crank gear **414** and the pulley gear **421** by gradually contracting the first driving wire **411a**, thereby

moving the lens barrel **430** closer to the fixed lens unit **300**.

(103) Each length of the driving wires **411a** and **411b** may be continuously changed. The driving transmission unit connected to the driving wires **411a** and **411b** may thus continuously move the lens barrel **430** in the optical axis direction (e.g., Z-axis direction) in response to the continuous length changes of the driving wires **411a** and **411b**.

(104) The driving unit may include the second driving wire **411b** positioned at a position different from that of the first driving wire **411a**, and the second driving wire **411b** may be made of the shape memory alloy the length of which is contracted when the current or the voltage is applied thereto. As shown in FIG. 6D, when the second driving wire **411b** is contracted as the current or the voltage is applied thereto, the end of the second driving wire **411b**, connected to the crank gear **414** may be moved in the direction in which the second driving wire **411b** is contracted. As the end of the second driving wire **411b** is moved, the crank gear **414** connected to the second driving wire **411b** may be rotated about the rotation axis formed by the crankshaft **415a**. As the crank gear **414** is rotated, the pulley gear **421** and the guide wire **423** connected to the pulley gear **421** may be rotated, and as a result, the lens barrel **430** may be moved in the optical axis direction (e.g., Z-axis direction).

(105) The driving unit may be positioned for the two directions to be opposite to each other, the direction in which the lens barrel **430** is moved as the second driving wire **411b** is contracted and the direction in which the lens barrel **430** is moved as the first driving wire **411a** is contracted. For example, as shown in FIGS. 6C and 6D, the first driving wire **411a** and the second driving wire **411b** may be connected to the crank gear **414** with the crankshaft **415a** interposed therebetween. Accordingly, the force contracting the first driving wire **411a** and the force contracting the second driving wire **411b** may generate the torque in opposite directions based on the rotation axis of the crank gear **414** (rotation axis formed by the crankshaft **415a** for example). Accordingly, the two directions may be opposite to each other, the direction in which the crank gear **414**, the pulley gear **421** and the guide wire **423** are rotated as the first driving wire **411a** is contracted and the direction in which the crank gear **414**, the pulley gear **421** and the guide wire **423** are rotated as the second driving wire **411b** is contracted. That is, the force contracting the first driving wire **411a** and the force contracting the second driving wire **411b** may act on the lens barrel **430** through the driving transmission unit in the opposite directions, thereby moving the lens barrel **430** in the opposite directions. For example, as shown in FIG. 6C, as the first driving wire **411a** is contracted, the lens barrel **430** may be moved closer to the fixed lens unit **300**. To the contrary, as shown in FIG. 6D, as the length of the second driving wire **411b** is contracted, the lens barrel **430** may be moved away from the fixed lens unit **300**. That is, each of the lens actuators **400** and **500** (in FIG. 2) may selectively contract any one of the first driving wire **411a** and the second driving wire **411b** to move the lens barrel **430** in either direction of the optical axis.

(106) The camera module **10** according to the various examples may include the plurality of lens actuators **400** and **500**. Hereinafter, the description describes the camera module **10** including the plurality of lens actuators **400** and **500** with reference to FIGS. 7 through 8B.

(107) FIG. 7 is a view showing that the plurality of lens actuators **400** and **500**, positioned in the camera module **10**, are coupled to each other; and FIGS. 8A and 8B are top views each showing that an upper cover **800** (in FIG. 2 for example) is omitted from the camera module **10**.

(108) At least one of the plurality of lens actuators **400** and **500**, included in the camera module **10** described with reference to FIGS. 7 through 8B may correspond to the lens actuator **400** described with reference to FIGS. 3 through 6D. For example, the camera module **10** according to the example of FIG. 7 may be the camera module **10** including the same two lens actuators as the lens actuator **400** described with reference to FIGS. 3 through 6D. However, the camera module **10** shown in FIGS. 7 through 8B is only an example. The camera module **10** may include various numbers of the lens actuators, or may further include a lens actuator having a structure different from that of the lens actuator **400** described with reference to FIGS. 3 through 6D.

(109) For convenience of explanation, it may be assumed that all lens actuators described in the following description correspond to the lens actuator **400** described with reference to FIGS. **3** through **6D**. Accordingly, omitted is a description overlapping that of the lens actuator described with reference to FIGS. **3** through **6D**.

(110) The camera module **10** may include the reflection module **200**, the plurality of lens actuators **400** and **500**, and an image sensor module **600**. The plurality of lens actuators **400** and **500** may be the first lens actuator **400** and the second lens actuator **500**. For example, as shown in FIG. **7**, the first lens actuator **400** and the second lens actuator **500** may be accommodated between the reflection module **200** and the image sensor module **600**, in the housing **100** of the camera module **10**. The fixed lens unit **300** may be positioned between the reflection module **200** and the first lens actuator **400**, and the incident light directed from the reflection module **200** to the plurality of lens actuators **400** and **500** may thus be refracted in the fixed lens unit **300**. The housing **100**, the reflection module **200**, the fixed lens unit **300** and the image sensor module **600** may all correspond to the housing **100**, the reflection module **200**, the fixed lens unit **300** and the image sensor module **600** of the camera module **10** described with reference to FIG. **2**, respectively, and descriptions thereof are made above with reference to FIG. **2**.

(111) The first lens actuator **400** may include the lens barrel **430** accommodating one or more lenses **433** (in FIG. **3** for example) and moved in the optical axis direction (e.g., Z-axis direction), and the driving unit moving the lens barrel **430**. The driving unit of the first lens actuator **400** may include the driving wire **411** the length of which is changed when the voltage or the current is applied thereto, the crank gear **414** rotated in series by being connected to the driving wire **411**, the pulley gear **421**, the sub-pulley gear **422**, the guide gear **424** and the guide wire **423**. The crank gear **414**, the pulley gear **421**, the sub-pulley gear **422** and the guide gear **424** may respectively be supported by the crankshaft **415a**, the pulley shaft **425a**, the sub-pulley shaft **426a** and the guide gear shaft **427a** to be rotated on the inner surface of the housing **100**. The lens barrel **430** and the driving unit, included in the first lens actuator **400**, correspond to the lens barrel **430** and driving unit of the lens actuator **400**, described with reference to FIGS. **3** through **6D**, and redundant descriptions thereof are thus omitted.

(112) The second lens actuator **500** may include a lens barrel **530** accommodating one or more lenses and moved in the optical axis direction (e.g., Z-axis direction), and the driving unit moving the lens barrel **530**. The driving unit of the second lens actuator **500** may include a driving wire **511** a length of which is changed when the voltage or the current is applied thereto, a crank gear **514** rotated in series by being connected to the driving wire **511**, a pulley gear **521**, a sub-pulley gear **522**, a guide gear **524**, a guide wire **523**, and a wire fixation member **512**. The crank gear **514**, the pulley gear **521**, the sub-pulley gear **522** and the guide gear **524** may respectively be supported by a crankshaft **515a**, a pulley shaft **525a**, a sub-pulley shaft **526a** and a guide gear shaft **527a** to be rotated on the inner surface of the housing **100**. The lens barrel **530** and the driving unit, included in the second lens actuator **500**, correspond to the lens barrel **430** and driving unit of the lens actuator **400**, described with reference to FIGS. **3** through **6D**, and redundant descriptions thereof are thus omitted.

(113) The driving unit included in the first lens actuator **400** and the driving unit included in the second lens actuator **500** may respectively be positioned in different spaces in the housing **100**. For example, as shown in FIG. **7**, the driving unit included in the first lens actuator **400** may be positioned on a right inner surface of the housing based on the optical axis direction (e.g., Z-axis direction), and the driving unit included in the second lens actuator **500** may be positioned on a left inner surface of the housing. Accordingly, the driving units may respectively drive the lens barrels **400** and **500** without interfering each other.

(114) The lens barrel **430** included in the first lens actuator **400** and the lens barrel **530** included in the second lens actuator **500** may be aligned with each other for their optical axes to coincide with each other, and may thus be moved in the housing **100** in the same optical axis. The guide rails **111**

and **112** guiding the respective movement of the lens barrels **430** and **530** may be positioned in the housing **100**. In addition, the guide grooves **432** and **532** respectively accommodating the guide rails **111** and **112** may be positioned in the bottom surfaces of the lens barrels **430** and **530** to prevent the lens barrels **430** and **530** from being separated from the guide rails **111** and **112** by external impact, respectively. For example, as shown in FIG. 7, the first guide groove **432** may be positioned in the bottom surface of the lens barrel **430** included in the first lens actuator **400**, and the second guide groove **532** may be positioned on the bottom surface of the lens barrel **530** included in the second lens actuator **500**.

(115) The driving units respectively included in the first lens actuator **400** and the second lens actuator **500** may be controlled independently of each other. For example, in the camera module **10** shown in FIG. 7, different magnitudes of the voltages or the currents may respectively be applied to the driving wire **411** included in the first lens actuator **400** and the driving wire **511** included in the second lens actuator **500**. Alternatively, the same magnitude of the voltage or current may be applied to the driving wire **411** included in the first lens actuator **400** and the driving wire **511** included in the second lens actuator **500** for different times. Accordingly, the direction or distance in which the lens barrel **430** included in the first lens actuator **400** is moved may be different from the direction or distance in which the lens barrel **530** included in the second lens actuator **500** is moved.

(116) Hereinafter, the description describes that the plurality of lenses barrels **430** and **530** included in the camera module **10** are moved with reference to FIGS. **8A** and **8B**. FIGS. **8A** and **8B** are top views each showing that the upper cover is omitted from the camera module **10**, and the driving units included in the plurality of lens actuators **400** and **500** respectively move the plurality of lenses barrels **430** and **530**. For example, FIGS. **8A** and **8B** may be views showing that the arrangement of the plurality of lens barrels **430** and **530** at different times. In the following description, the lens barrel **430** included in the first lens actuator **400** is defined as the first lens barrel **430**, and the lens barrel **530** included in the second lens actuator **500** is defined as the second lens barrel **530**.

(117) The driving units included in the first lens actuator **400** and the second lens actuator **500** may be controlled independently of each other, and the first lens barrel **430** and the second lens barrel **530** may thus be moved independently of each other. For example, the driving unit of the first lens actuator **400** and the driving unit of the second lens actuator **500** may respectively move the first lens barrel **430** and the second lens barrel **530** away from the image sensor module **600** by different distances. Accordingly, two distances may be different from each other, i.e. a distance d_1 (in FIG. **8A** for example) between the first lens barrel **430** and the second lens barrel **530** before the lens barrels are moved and a distance d_2 (in FIG. **8B** for example) therebetween after the lens barrels are moved.

(118) However, FIGS. **8A** and **8B** show that the camera module **10** is moved, and the operation of the driving unit included in the camera module **10** is not limited thereto. For example, the driving unit of the first lens actuator **400** may move the first lens barrel **430** closer to the image sensor module **600**, and the driving unit of the second lens actuator **500** may simultaneously move the second lens barrel **530** away from the image sensor module **600**. Alternatively, while the driving unit of the first lens actuator **400** moves the first lens barrel **430**, the driving unit of the second lens actuator **500** may not be operated.

(119) In the various examples, the driving unit of the first lens actuator **400** and the driving unit of the second lens actuator **500** may continuously move the first lens barrel **430** and the second lens barrel **530** in the optical axis direction (e.g., Z-axis direction). Accordingly, the camera module **10** may perform the autofocus function.

(120) The driving unit of the first lens actuator **400** and the driving unit of the second lens actuator **500** may continuously adjust the distance between the first lens barrel **430** and the second lens barrel **530** or a distance between the second lens barrel **530** and the image sensor module **600**.

Accordingly, the camera module **10** may perform a continuous zoom function.

(121) As set forth above, the lens actuator and the camera module including the same may implement the autofocus function, the zoom function and the image stabilization function by moving the plurality of lenses in the optical axis direction.

(122) The lens actuator and the camera module including the same may move the plurality of lenses using the driving wire the length of which is changed, and the present disclosure may thus provide the lens actuator having a simple structure and high operational reliability and the camera module including the same.

(123) The lens actuator and the camera module including the same may move the plurality of lenses using the driving wire the length of which is changed, thereby reducing power consumed as the lens is moved.

(124) The lens actuator and the camera module including the same may move the plurality of lenses in the optical axis direction using a minute amount of the change in the length of the driving wire.

(125) The lens actuator and the camera module including the same may move the plurality of lenses using the driving wire the length of which is changed, thereby minimizing electromagnetic interference to another electronic component.

(126) The lens actuator and the camera module including the same may control the plurality of lenses precisely and quickly by adjusting the speed and amount of the change in the length of the driving wire.

(127) The lens actuator and the camera module including the same may continuously move the plurality of lenses, thus easily performing the continuous zoom function.

(128) While this disclosure includes specific examples, it will be apparent to one of ordinary skill in the art that various changes in form and details may be made in these examples without departing from the spirit and scope of the claims and their equivalents. The examples described herein are to be considered in a descriptive sense only, and not for purposes of limitation.

Descriptions of features or aspects in each example are to be considered as being applicable to similar features or aspects in other examples. Suitable results may be achieved if the described techniques are performed to have a different order, and/or if components in a described system, architecture, device, or circuit are combined in a different manner, and/or replaced or supplemented by other components or their equivalents. Therefore, the scope of the disclosure is defined not by the detailed description, but by the claims and their equivalents, and all variations within the scope of the claims and their equivalents are to be construed as being included in the disclosure.

Claims

1. A lens actuator comprising: a lens barrel accommodating one or more lenses; and a driving unit configured to move the lens barrel along an optical axis direction, wherein the driving unit comprises: a driving wire, at least a portion of which is extended in the optical axis direction, and a length of which is changed as voltage is applied thereto; and a driving transmission unit connected to the driving wire and configured to transfer changes in the length of the driving wire to the lens barrel along the optical axis direction as the length of the driving wire is changed such that a distance the lens barrel is moved by the driving transmission unit is greater than an amount of change in the length of the driving wire, and wherein the driving transmission unit, comprising a crank gear connected to the driving wire, is configured to rotate about a rotation axis crossing an optical axis based on contraction or extension of the driving wire.
2. The lens actuator of claim 1, wherein as the voltage is applied to the driving wire, at least a portion of the driving wire is contracted in the optical axis direction.
3. The lens actuator of claim 1, wherein the driving transmission unit further comprises: a pulley gear configured to rotate while meshing with the crank gear; and a guide wire connected to the

pulley gear and configured to move as the pulley gear is rotated, and the lens barrel is fixed to at least a portion of the guide wire.

4. The lens actuator of claim 3, wherein a first end of the crank gear is connected to the driving wire, a second end of the crank gear is connected with the pulley gear, and a distance from the first end of the crank gear to the rotation axis of the crank gear is shorter than a distance from the second end of the crank gear to the rotation axis of the crank gear.
5. The lens actuator of claim 4, wherein the pulley gear comprises: a first wheel connected with the second end of the crank gear; and a second wheel connected with the guide wire, and an outer diameter of the second wheel is greater than an outer diameter of the first wheel.
6. The lens actuator of claim 5, wherein the second end of the crank gear and an outer ring of the first wheel of the pulley gear are teeth-coupled to each other.
7. The lens actuator of claim 3, wherein the driving wire comprises: a first driving wire configured to rotate the crank gear in a first direction as a length of the first driving wire is reduced; and a second driving wire configured to rotate the crank gear in a second direction opposite to the first direction as a length of the second driving wire thereof is reduced, and changes in the lengths of the first driving wire and the second driving wire are controlled independently of each other.
8. The lens actuator of claim 7, wherein one or both of the first driving wire and the second driving wire is made of a shape memory alloy, a length of which is changed when the voltage is applied thereto.
9. The lens actuator of claim 7, further comprising a wire connection member connecting one or both of the first driving wire and the second driving wire to the crank gear, wherein the wire connection member comprises a conductive material.
10. The lens actuator of claim 3, wherein the driving transmission unit comprises: a crankshaft supporting the crank gear; and a crank fixation member disposed at an end of the crankshaft to support the crank gear so as not to be separated from the crankshaft.
11. The lens actuator of claim 3, wherein the driving transmission unit further comprises a sub-pulley gear spaced apart from the pulley gear in the optical axis direction, the guide wire is connected to both the pulley gear and the sub-pulley gear, and the lens barrel is connected to the guide wire between the pulley gear and the sub-pulley gear.
12. The lens actuator of claim 11, wherein the driving transmission unit further comprises a guide gear positioned between the pulley gear and the sub-pulley gear, and configured to guide at least a portion of the guide wire to be moved in a direction parallel to the optical axis direction.
13. The lens actuator of claim 3, wherein a fixation groove, to which at least a portion of the guide wire is fixed, is disposed in an outer circumferential surface of the pulley gear.
14. A lens actuator comprising: a lens barrel accommodating one or more lenses; and a driving unit configured to move the lens barrel along an optical axis direction, wherein the driving unit comprises: a first driving wire and a second driving wire at least a portion of each of which is configured to be extended along the optical axis direction, and a length of each of which is changed as voltage is applied thereto, and a driving transmission unit configured to transfer changes in the length of the first driving wire to the lens barrel in a first direction parallel to the optical axis direction as the length of the first driving wire is contracted, and to move the lens barrel in a second direction opposite to the first direction as the length of the second driving wire is contracted.
15. The lens actuator of claim 14, wherein the first driving wire and the second driving wire are disposed opposite to each other in a direction crossing the optical axis direction.
16. A camera module comprising one or more lens actuators of claim 14, wherein respective driving units included in each of the one or more lens actuators are controlled independently of each other.
17. A lens actuator comprising: a lens barrel comprising one or more lenses; a driving wire configured to extend and contract in an optical axis direction as voltage is applied thereto; and a driving transmission connected to the driving wire and configured to move the lens barrel along the

optical axis direction as the length of the driving wire is changed such that a distance the lens barrel is moved by the driving transmission unit is greater than an amount of change in the length of the driving wire, wherein the driving transmission comprises: a crank gear connected to the driving wire and configured to rotate about a rotation axis crossing an optical axis; and a pulley gear configured to rotate while meshing with the crank gear, and wherein a first end of the crank gear is connected to the driving wire, a second end of the crank gear is connected with the pulley gear, and a distance from the first end of the crank gear to the rotation axis of the crank gear is different than a distance from the second end of the crank gear to the rotation axis of the crank gear.

18. The lens actuator of claim 17, wherein the distance from the first end of the crank gear to the rotation axis of the crank gear is less than the distance from the second end of the crank gear to the rotation axis of the crank gear.
