

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416851
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Chen; Ya et al.

Lens mounting apparatus and projector

Abstract

A lens mounting apparatus includes a base including an opening, wherein a lens including a connection part is inserted and attached, an annular frame including a notch provided on a part of an outer periphery, a socket electrically connected to the connection part of the lens, and a first elastic member provided to urge the socket from the outer periphery toward a center of the annular frame. The annular frame is configured to fix the lens inserted and attached into the base by rotating the annular frame in one direction by a predetermined angle. When the annular frame does not fix the lens, the notch does not face the socket. When the annular frame fixes the lens, the notch faces the socket, and the socket is electrically connected to the connection part of the lens by an urging force of the first elastic member.

Inventors: Chen; Ya (Guangdong, CN), Chen; Chen (Guangdong, CN)

Applicant: Panasonic Intellectual Property Management Co., Ltd. (Osaka, JP)

Family ID: 1000008819428

Assignee: PANASONIC INTELLECTUAL PROPERTY MANAGEMENT CO., LTD.
(Osaka, JP)

Appl. No.: 17/555950

Filed: December 20, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220244482 A1	Aug. 04, 2022

Foreign Application Priority Data

CN	202110132784.3	Jan. 29, 2021
----	----------------	---------------

Publication Classification

Int. Cl.: G03B21/14 (20060101); G02B7/08 (20210101)

U.S. Cl.:

CPC G03B21/14 (20130101); G02B7/08 (20130101); G03B21/142 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2009/0015800	12/2008	Igarashi et al.	N/A	N/A
2012/0195587	12/2011	Hasuda et al.	N/A	N/A
2016/0087365	12/2015	Ohkubo et al.	N/A	N/A
2019/0094565	12/2018	Park	N/A	H04N 23/57
2019/0141224	12/2018	Park	N/A	H04N 23/55
2019/0265431	12/2018	Ichikawa	N/A	G02B 7/021

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2009-20445	12/2008	JP	N/A
2012-155290	12/2011	JP	N/A
2015-11961	12/2014	JP	N/A

Primary Examiner: Allen; Stephone B

Assistant Examiner: Washington; Tamara Y.

Attorney, Agent or Firm: Wenderoth, Lind & Ponack, L.L.P.

Background/Summary

BACKGROUND

1. Technical Field

(1) The present disclosure relates to a lens mounting apparatus and a projector including the lens mounting apparatus.

2. Description of the Related Art

(2) When a lens is mounted on a camera, a projector, or the like, it is necessary to electrically connect a lens contact of the lens and a socket contact of a socket mounted on the camera, the projector, or the like, and to fix the lens to the camera, the projector, or the like.

(3) As a lens mounting apparatus as described above, Unexamined Japanese Patent Publication No. 2012-155290 discloses the following configuration.

(4) In Unexamined Japanese Patent Publication No. 2012-155290, the lens contact and the socket

contact are electrically connected to each other by rotating the lens after the lens is inserted into the camera in order to electrically connect the lens contact and the socket contact favorably and prevent the lens from being erroneously mounted on the camera.

(5) Thus, the camera in Unexamined Japanese Patent Publication No. 2012-155290 has advantages that the socket has small dimensions and costs low.

(6) However, Unexamined Japanese Patent Publication No. 2012-155290 has the following technical problems.

(7) After the lens is inserted, the lens cannot be fixed to the camera without rotating the lens. Thus, mounting operation of the lens is inconvenient. In particular, with a lens having a large weight, elasticity of an elastic piece of a lens mount increases, a large force is required to rotate the lens, and the lens cannot be fixed firmly.

(8) An effective stroke of an elastic contact of the socket is small, and the elastic contact of the socket is easily deformed and lost when the lens is rotated, and thus a contact failure easily occurs.

(9) As the lens mounting apparatus as described above, in addition to a rotary mounting structure disclosed in Unexamined Japanese Patent Publication No. 2012-155290, a direct insertion mounting structure described below is also disclosed in the known art.

(10) Specifically, in the direct insertion lens mounting structure, after the lens is inserted into a camera, a projector, or the like, the lens is not rotated, and the lens contact and the socket contact are electrically connected directly.

(11) In this way, it is not necessary to rotate the lens after the insertion of the lens, and the lens mounting operation is convenient. After the lens is inserted, a contact failure rate at the contact decreases.

(12) However, the known art described above has the following technical problems.

(13) The socket, which has a large volume, makes an installation space of the lens mount narrow.

(14) The socket needs to freely move in a narrow space such that a position of the socket does not affect positioning of the lens, and thus the socket costs high.

SUMMARY

(15) The present disclosure has been made to solve the above-described technical problems, and an object of the present disclosure is to provide a lens mounting apparatus capable of reducing a volume of a socket, suppressing a contact failure of a socket contact, and improving mounting operability of a lens, and a projector including the lens mounting apparatus.

(16) In order to achieve the above object, a lens mounting apparatus of the present disclosure includes a base including an opening, wherein a lens including a connection part is inserted and attached into the opening of the base, an annular frame including a notch provided on a part of an outer periphery of the annular frame, a socket electrically connected to the connection part of the lens, and a first elastic member provided to urge the socket from the outer periphery toward a center of the annular frame. The annular frame is rotatably mounted on the base. The annular frame is configured to fix the lens inserted and attached into the base by rotating the annular frame in one direction by a predetermined angle. When the annular frame does not fix the lens, the notch does not face the socket. When the annular frame fixes the lens, the notch faces the socket, and the socket is electrically connected to the connection part of the lens by an urging force of the first elastic member.

(17) In the lens mounting apparatus of the present disclosure, the first elastic member is provided to urge the socket from the outer periphery toward the center, that is, the radial center of the annular frame. Thus, an effective stroke of the socket contact as the connection part of the socket increases, and a contact failure rate at the contact decreases.

(18) Further, since the socket contact of the socket and a lens contact as the connection part of the lens are not in contact with each other when the lens is inserted, the socket contact of the socket can be prevented from being deformed by receiving an impact.

(19) Furthermore, since the socket does not affect positioning of the lens, a position of the lens can

be determined appropriately.

(20) In addition, since the lens need not be rotated after the insertion of the lens, the mounting operation of the lens is convenient, and the mounting operability is improved particularly for a lens having a large weight.

(21) Finally, since the socket is movable radially, the socket has small dimensions and costs low.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an exploded perspective view of a lens mounting apparatus of the present disclosure;
- (2) FIG. 2 is a plan view of a lens mount in a base as viewed from a left side in FIG. 1;
- (3) FIG. 3 is views illustrating an installation state between a second elastic member and an annular frame in FIG. 1. Part (a) of FIG. 3 is a perspective view, and part (b) of FIG. 3 is a plan view of the second elastic member and the annular frame as viewed from the left side in FIG. 1;
- (4) FIG. 4 is views illustrating a state of a socket before the annular frame is rotated to fix a lens. Part (a) of FIG. 4 is a plan view of the annular frame and a body in the base as viewed from a right side in FIG. 1, and part (b) of FIG. 4 is a view illustrating a state in which a socket contact and a lens contact are not electrically connected;
- (5) FIG. 5 is a view illustrating a state of the socket after the annular frame is rotated to fix the lens. Part (a) of FIG. 5 is a plan view of the annular frame and the body in the base as viewed from the right side of FIG. 1, and part (b) of FIG. 5 is a view illustrating a state in which the socket contact and the lens contact are electrically connected;
- (6) FIG. 6A is a perspective view of the lens and the annular frame, and is a view illustrating a state after the annular frame is rotated to fix the lens;
- (7) FIG. 6B is a view illustrating a positional relationship between the second elastic member and a protrusion before the annular frame is rotated to fix the lens, and is a plan view of the annular frame and the body in the base as viewed from the right side in FIG. 1;
- (8) FIG. 7 is a schematic view illustrating that rotation of the annular frame causes the second elastic member to elastically abut on the protrusion of the lens sequentially to fix the lens;
- (9) FIG. 8A is a schematic view illustrating that the lens changes from a non-fixed state to a fixed state;
- (10) FIG. 8B is a schematic view illustrating a position change of the second elastic member before and after fixing the lens;
- (11) FIG. 9 is a schematic view illustrating that the lens changes from the fixed state to the non-fixed state;
- (12) FIG. 10 is a plan view illustrating a stopper provided in the body in the base and configured to limit a rotation angle of the annular frame;
- (13) FIG. 11 is a schematic view of a notch provided on a part of an outer periphery of the annular frame in each exemplary embodiment; and
- (14) FIG. 12 is a plan view of a main part of a projector of the present disclosure.

DETAILED DESCRIPTION

(15) Hereinafter, a structure and a function of each component of the present disclosure will be described in detail with reference to the drawings. In the following description, the same or corresponding members and structures are designated by the same reference numerals, and duplicated description will be omitted.

(16) As illustrated in FIG. 1, a lens mounting apparatus of the present disclosure includes base 1 having opening 1a into which lens 5 (see FIG. 6A described later) is inserted and attached, annular frame 2 provided with notch 2a formed by notching a part of an outer periphery, socket 3 electrically connected to lens contact 5a as a connection part of lens 5, and first elastic member (for

example, spring) **4** provided to urge socket **3** from an outer periphery toward a center, that is, a radial center of annular frame **2**. Here, lens **5** is a projection lens used in a projector described later. Note that illustration of the lens is omitted in FIG. **1**.

(17) Specifically, as illustrated in FIG. **1**, base **1** includes body **1b** and lens mount **1c**, and body **1b** and lens mount **1c** is provided with opening **1a** into which lens **5** is inserted and attached. Annular frame **2** is provided between body **1b** and lens mount **1c**, and recess **2b** through which protrusion **5b** (see FIGS. **6A** and **6B** described later) provided on an outer peripheral surface of lens **5** is inserted is formed on an inner periphery of annular frame **2**, and socket **3** is movably installed on body **1b**.

(18) Further, as illustrated in FIG. **2**, lens mount **1c** is provided with groove **1ca** accommodating protrusion **5b** inserted through recess **2b** of annular frame **2**.

(19) That is, in a state where socket **3** is not moved from the outer periphery toward the center, that is, the radial center of annular frame **2** by an elastic force of first elastic member **4**, lens **5** is inserted and attached into base **1** from body **1b** in FIG. **1** through opening **1a**. Protrusion **5b** provided on the outer peripheral surface of lens **5** is inserted through recess **2b** provided on the inner periphery of annular frame **2**, and then accommodated and engaged in groove **1ca** provided in lens mount **1c**, and thus lens **5** is smoothly mounted on base **1**. At this time, lens contact **5a** of lens **5** and socket contact **3a** of socket **3** face each other with a gap between lens contact **5a** and socket contact **3a**.

(20) In the present disclosure, annular frame **2** is rotatably mounted on base **1**, and rotates by a predetermined angle in one direction (for example, in a clockwise direction in part (a) of FIG. **4**) to fix lens **5** inserted and attached into base **1**.

(21) Specifically, as illustrated in FIGS. **1** and **3**, second elastic member (for example, elastic piece) **6** that elastically abuts on protrusion **5b** of lens **5** when the annular frame is rotated in one direction to urge lens **5** toward lens mount **1c** in base **1** and fix lens **5** is provided at a position separated from one end of recess **2b** of annular frame **2** by a predetermined distance.

(22) In FIG. **3**, first end **6a** as a fixed end of second elastic member **6** is fixed to a side surface of annular frame **2** facing body **1b** with a screw or the like, and second end **6b** as an elastic end of second elastic member **6** is inserted through a through hole provided in annular frame **2** and protrudes from a side surface of annular frame **2** facing lens mount **1c**. When annular frame **2** rotates in one direction, second end **6b** elastically abuts on protrusion **5b** of lens **5**, urges lens **5** toward lens mount **1c** in base **1**, and thus fixes lens **5**.

(23) Second elastic member **6** of the present disclosure is not limited to an exemplary embodiment described above, and for example, second elastic member **6** may be configured by fixing an elastic body to the side surface of annular frame **2** facing lens mount **1c** by means of adhesion, welding, or the like.

(24) Hereinafter, a change of a non-electrically connected state and an electrically connected state between socket contact **3a** and lens contact **5a** of the present disclosure will be described with reference to FIGS. **4** and **5**.

(25) As illustrated in part (a) of FIG. **4**, when annular frame **2** is rotated in the clockwise direction and lens **5** is not fixed, notch **2a** of annular frame **2** is at a position not facing socket **3**, and an arc of annular frame **2** abuts on socket **3** for socket **3** to compress first elastic member **4**. Accordingly, as illustrated in part (b) of FIG. **4**, socket contact **3a** and lens contact **5a** of lens **5** inserted and attached into base **1** face each other with a gap between socket contact **3a** and lens contact **5a**. That is, socket contact **3a** and lens contact **5a** are in the non-electrically connected state.

(26) Furthermore, as illustrated in part (a) of FIG. **5**, when annular frame **2** is rotated in the clockwise direction and second end **6b** of second elastic member **6** elastically abuts on protrusion **5b** of lens **5** to urge lens **5** toward lens mount **1c** of base **1** and fixes lens **5** as described above, notch **2a** rotationally moves to a position facing socket **3** in response to rotation of annular frame **2**, and first elastic member **4** extends to urge socket **3** from the outer periphery toward the center, that

is, the radial center of annular frame **2**. As a result, socket **3** moves toward the center by a biasing force of first elastic member **4** and comes in contact with lens contact **5a** of lens **5**. As illustrated in part (b) of FIG. 5, socket contact **3a** and lens contact **5a** of lens **5** inserted and attached into base **1** face each other without a gap between socket contact **3a** and lens contact **5a**. That is, socket contact **3a** and lens contact **5a** are in the electrically connected state.

(27) That is, in the present disclosure, socket contact **3a** and lens contact **5a** are in the non-electrically connected state when lens **5** is in a non-fixed state of not being fixed to base **1**, but socket contact **3a** and lens contact **5a** are in the electrically connected state when lens **5** is in a fixed state of being fixed to base **1**.

(28) Thus, in the lens mounting apparatus of the present disclosure, first elastic member **4** is provided to urge socket **3** from the outer periphery toward the center, that is, the radial center of annular frame **2**. That is, since socket **3** is radially movable by the biasing force of first elastic member **4**, an effective stroke of socket contact **3a** of socket **3** increases, and a contact failure rate at the contact decreases.

(29) Further, since socket contact **3a** of socket **3** and lens contact **5a** of lens **5** are not in contact with each other when lens **5** is inserted, socket contact **3a** of socket **3** can be prevented from being deformed by receiving an impact.

(30) Furthermore, since socket **3** does not affect positioning of lens **5**, a position of lens **5** can be determined appropriately.

(31) In addition, since lens **5** need not be rotated after the insertion of lens **5**, a mounting operation of lens **5** is convenient, and mounting operability is improved particularly for a lens having a large weight.

(32) Finally, since socket **3** is radially movable, the socket has small dimensions and costs low.

(33) Hereinafter, an exemplary embodiment in a case where lens **5** is fixed to base **1** using annular frame **2** of the present disclosure will be described with reference to FIGS. 6A to 8B. The “lens” herein means not a lens itself as an optical element but a lens module mounted on a lens-interchangeable camera or projector and having a metal contact (connection part) as illustrated in FIG. 6A.

(34) As described above, in the present disclosure, after lens **5** is inserted into base **1**, lens **5** is fixed to base **1** by rotating annular frame **2** without rotating lens **5**.

(35) Specifically, as described above, lens **5** is inserted and attached into base **1** from body **1b** in FIG. 1 through opening **1a**. FIG. 6A is a perspective view of an installation state between lens **5** and annular frame **2** after protrusion **5b** provided on the outer peripheral surface of lens **5** has inserted through recess **2b** provided on the inner periphery of annular frame **2**, and illustrates a state after annular frame **2** is rotated to fix lens **5**.

(36) On the other hand, FIG. 6B illustrates a positional relationship between second elastic member **6** and protrusion **5b** before annular frame **2** is rotated to fix lens **5**. FIG. 6B schematically illustrates only protrusion **5b** provided on the outer peripheral surface of lens **5**.

(37) More specifically, a plurality of protrusions **5b** of lens **5**, a plurality of recesses **2b** of annular frame **2**, and a plurality of second elastic members **6** are provided correspondingly. For example, as illustrated in FIG. 6B, three protrusions **5b** of lens **5**, three recesses **2b** of annular frame **2**, and three second elastic members **6** are provided correspondingly.

(38) A predetermined distance between one end (for example, an end downstream in the clockwise direction in FIG. 6B) of each recess **2b** and each corresponding second elastic member **6** (in the present exemplary embodiment, second end **6b** of each second elastic member **6**) is different. That is, distances **S1** to **S3** are different from each other.

(39) Preferably, as shown in FIG. 6B, distance **S1**, distance **S2**, and distance **S3** between second ends **6b** of second elastic members **6** and recesses **2b** sequentially increase in a counterclockwise direction. That is, the predetermined distance between one end of each recess **2b** and second end **6b** of each corresponding second elastic member **6** is set for second end **6b** of each second elastic

member **6** and each corresponding protrusion **5b** to elastically abut on each other sequentially when annular frame **2** is rotated in one direction (the clockwise direction). As a result, when annular frame **2** is rotated, second ends **6b** of three second elastic members **6** sequentially come into elastic contact with three protrusions **5b** instead of simultaneously coming into elastic contact with three protrusions **5b**. Therefore, a rapid increase in resistance received when annular frame **2** is rotated can be prevented, and this resistance can be gradually increased. Thus, annular frame **2** can be smoothly rotated and prevented from being deformed or displaced.

(40) FIG. **7** is a schematic view illustrating a state in which second end **6b** of each of second elastic members **6** and corresponding protrusion **5b** elastically abut on each other sequentially by rotating annular frame **2** in the clockwise direction from the state illustrated in FIG. **6B**, for example.

(41) As shown in FIG. **6B**, distance **S1**, distance **S2**, and distance **S3** between second ends **6b** of second elastic members **6** and recesses **2b** sequentially increase in the counterclockwise direction. Thus, when annular frame **2** is rotated in the clockwise direction, as shown in part (a) of FIG. **7**, first, second end **6b** of second elastic member **6** of a first group starts to elastically abut on corresponding protrusion **5b**, and then, as shown in part (b) of FIG. **7**, in response to the rotation of annular frame **2**, second end **6b** of second elastic member **6** of a second group starts to elastically abut on corresponding protrusion **5b**. Finally, in response to the rotation of annular frame **2**, as illustrated in part (c) of FIG. **7**, second end **6b** of second elastic member **6** of a third-group starts to elastically abut on corresponding protrusion **5b**. As a result, annular frame **2** can be smoothly rotated by a predetermined angle, and lens **5** can be fixed to base **1**. That is, distances **S1** to **S3** are set for the plurality of second elastic members **6** and the plurality of protrusions **5b** to elastically abut on each other sequentially.

(42) Note that, in the above description, rotating annular frame **2** to fix lens **5** means, for example, rotating annular frame **2** in one direction (in the above description, the direction is the clockwise direction, but may be the counterclockwise direction) by rotating operation lever **2c** (see FIGS. **1**, **3**, and the like) provided at a location different from a location where notch **2a** is formed on the outer periphery of annular frame **2**.

(43) Next, a change from the non-fixed state to the fixed state of lens **5** will be described with reference to FIGS. **8A** and **8B**. FIGS. **8A** and **8B** are overall perspective views of the lens mounting apparatus including lens **5** of the present disclosure.

(44) As described above, part (a) of FIG. **4**, part (a) of FIG. **5**, and FIG. **6B** are plan views of annular frame **2** and body **1b** of base **1** viewed from the right side in FIG. **1**, whereas FIGS. **8A** and **8B** are perspective views of base **1**, annular frame **2**, and the like viewed from the left side in FIG. **1**. Therefore, in FIGS. **8A** and **8B**, a rotation direction of annular frame **2** is the counterclockwise direction, unlike a rotation direction described above (that is, in the clockwise direction).

(45) FIG. **8A** is a schematic view of lens **5** changing from the non-fixed state to the fixed state.

(46) In FIG. **8A**, lens **5** changes from the non-fixed state to the fixed state by rotating operation lever **2c**, for example, in the counterclockwise direction. At the same time, socket contact **3a** of socket **3** and lens contact **5a** of lens **5** are electrically connected.

(47) FIG. **8B** is a partial perspective view illustrating a position change of second elastic member **6** when lens **5** is changed from the non-fixed state to the fixed state. In FIG. **8B**, lens **5** is not illustrated in order to describe the position change of elastic member **6**. As illustrated in FIG. **8B**, before lens **5** is fixed, second end **6b** of second elastic member **6** does not abut on protrusion **5b** of lens **5** provided in groove **1ca** of lens mount **1c**, but after lens **5** is fixed, second end **6b** of second elastic member **6** abuts on protrusion **5b** to fix lens **5**.

(48) Next, a change from the fixed state to the non-fixed state of lens **5** will be described with reference to FIG. **9**. Corresponding to FIG. **8A**, FIG. **9** is an overall perspective view of the lens mounting apparatus including lens **5** of the present disclosure.

(49) As described above, in FIG. **8A**, lens **5** changes from the non-fixed state to the fixed state by rotating operation lever **2c**, for example, in the counterclockwise direction.

(50) On the other hand, for example, when lens 5 is switched from the fixed state to the non-fixed state to remove lens 5, operation lever 2c only has to be rotated, for example, in the clockwise direction as illustrated in FIG. 9. As a result, lens 5 changes from the fixed state to the non-fixed state. At the same time, the electrical connection between socket contact 3a of socket 3 and lens contact 5a of lens 5 is also released.

(51) As described above, in the present disclosure, by rotating annular frame 2 by a predetermined angle in one direction (clockwise or counterclockwise direction), socket contact 3a and lens contact 5a are electrically connected to each other while lens 5 inserted and attached into base 1 is fixed. In addition, by rotating annular frame 2 by a predetermined angle in a direction opposite to one direction (counterclockwise or clockwise direction), the fixation of lens 5 inserted and attached into base 1 is released, and at the same time, the electrical connection between socket contact 3a and lens contact 5a is released.

(52) Further, stopper 1ba that limits a rotation angle of annular frame 2 of the present disclosure will be described with reference to FIG. 10.

(53) In FIG. 10, body 1b of base 1 is provided with stopper 1ba, and stopper 1ba is formed by providing a notch on an inner periphery of body 1b. As illustrated in FIGS. 1 and 3, projection 2d is provided at a location different from locations where notch 2a and operation lever 2c are provided on the outer periphery of annular frame 2. By inserting projection 2d into stopper 1ba, the rotation angle of annular frame 2 is limited to a predetermined angle at which projection 2d moves from one end to the other end in a circumferential direction of stopper 1ba.

(54) A circumferential length of stopper 1ba only has to be larger than a maximum distance between second end 6b of second elastic member 6 and recess 2b, for example, above-described distance S3. By setting the circumferential length of stopper 1ba, the predetermined angle at which annular frame 2 rotates can be freely set.

(55) FIG. 10 illustrates a case where stopper 1ba is provided on body 1b, but a position of stopper 1ba is not limited to this position, and of course, such a stopper may also be provided on lens mount 1c.

(56) Next, each exemplary embodiment of notch 2a provided in annular frame 2 will be described with reference to FIG. 11.

(57) Notch 2a of annular frame 2 illustrated in FIGS. 1, 3, and the like is a notch formed by linearly cutting out the outer periphery of annular frame 2 as illustrated in part (a) of FIG. 11, but may be a notch having a bent-line shape as illustrated in part (b) of FIG. 11 or a notch having an arcuate line shape as illustrated in part (c) of FIG. 11 other than the notch having a linear shape as illustrated in part (a) of FIG. 11. Further, as shown in FIG. 11(d), a linear notch can be provided between the inner periphery and the outer periphery of annular frame 2. In a case where socket 3 is provided in the notch as shown in part (d) of FIG. 11, when annular frame 2 rotates, socket 3 slides in the notch and moves radially.

(58) Each notch shown in part (a) to part (d) of FIG. 11 can electrically connect socket contact 3a and lens contact 5a or release the electrical connection between socket contact 3a and lens contact 5a.

(59) Finally, the projector of the present disclosure will be described with reference to FIG. 12.

(60) The projector of the present disclosure is an electronic device that modulates a light flux emitted from a light source device in response to an image signal and magnifies and projects a resultant light flux onto a projection surface such as a screen. The projector includes the above-described lens mounting apparatus, the light source device that emits the light flux, and optical modulator that modulates the light flux emitted from the light source device in response to the image signal.

(61) Specifically, as illustrated in FIG. 12, in the projector of the present disclosure, the light source device includes a laser light source that emits blue laser light. A part of the blue laser light from the laser light source excites yellow phosphor of a phosphor wheel as excitation light to emit yellow

fluorescence light, and yellow light is reflected from the phosphor wheel. The yellow light and the blue light of the blue laser light are synthesized at a constant ratio to become white light, and the white light is emitted from the light source device. The white light from the light source device is color-separated into red light, blue light, and green light by a dichroic mirror (not illustrated), and these red light, blue light, and green light are incident on the light modulator such as a liquid crystal panel. The light modulator modulates the red light, blue light, and green light in accordance with the image signal. The color lights modulated by the light modulator are synthesized by a light synthesizer (not illustrated) such as a prism and become projection image light. The projection image light is enlarged by the lens and then projected onto the projection surface.

(62) Note that, in FIG. 12, since the above-described lens is the projection lens (lens 5) mounted on the projector by the above-described lens mounting apparatus, in the projector, it is possible to reduce a volume of the socket, suppress a contact failure of the socket contact, and improve the mounting operability of the lens.

(63) The lens mounting apparatus and the projector of the present disclosure have been described above with reference to the specific exemplary embodiments illustrated in FIGS. 1 to 12.

(64) As is clear from the above description, an object of the present disclosure is to provide a lens mounting apparatus capable of reducing a volume of a socket, suppressing a contact failure of a socket contact, and improving mounting operability of a lens. In order to achieve this object, the lens mounting apparatus of the present disclosure includes base 1 having opening 1a into which lens 5 is inserted and attached, annular frame 2 provided with notch 2a formed by notching a part of an outer periphery, socket 3 electrically connected to lens contact 5a as a connection part of lens 5, and first elastic member 4 provided to urge socket 3 from the outer periphery of annular frame 2 toward the center. Annular frame 2 is rotatably mounted on base 1, and is rotated by a predetermined angle in one direction to fix lens 5 inserted and attached into base 1. When lens 5 is not fixed by annular frame 2, notch 2a is located at a position not facing socket 3, and when lens 5 is fixed by annular frame 2, notch 2a is located at a position facing socket 3, and socket 3 is electrically connected to lens contact 5a of lens 5 by the urging force of first elastic member 4.

(65) In the lens mounting apparatus of the present disclosure, since first elastic member 4 is provided to urge socket 3 from the outer periphery toward the center, that is, the radial center of annular frame 2, the effective stroke of socket contact 3a of socket 3 increases, and the contact failure rate at the contact decreases.

(66) Further, since socket contact 3a of socket 3 and lens contact 5a of lens 5 are not in contact with each other when lens 5 is inserted, socket contact 3a of socket 3 can be prevented from being deformed by receiving an impact.

(67) Furthermore, since socket 3 does not affect positioning of lens 5, a position of lens 5 can be determined appropriately.

(68) In addition, since lens 5 need not be rotated after the insertion of lens 5, a mounting operation of lens 5 is convenient, and mounting operability is improved particularly for a lens having a large weight.

(69) Finally, since socket 3 is radially movable, the socket has small dimensions and costs low.

(70) It is preferable that recess 2b through which protrusion 5b provided on the outer peripheral surface of lens 5 is inserted is formed on the inner periphery of annular frame 2, and second elastic member 6 that elastically abuts on protrusion 5b and urges lens 5 toward base 1 when annular frame 2 is rotated in one direction is provided at a position separated from one end of recess 2b of annular frame 2 by a predetermined distance.

(71) The plurality of protrusions 5b, the plurality of recesses 2b, and the plurality of second elastic members 6 are preferably provided correspondingly, and the predetermined distance between one end of each recess 2b and each corresponding second elastic member 6 is preferably different.

(72) Furthermore, the predetermined distance between one end of each recess 2b and each corresponding second elastic member 6 is preferably set for each second elastic member 6 and each

corresponding protrusion 5b to elastically abut on each other sequentially when annular frame 2 is rotated in one direction.

(73) As a result, a rapid increase in resistance received when annular frame 2 is rotated can be prevented, and this resistance can be gradually increased. Thus, annular frame 2 can be smoothly rotated and prevented from being deformed or displaced.

(74) It is preferable that base 1 includes body 1b and a lens mount 1c, annular frame 2 is provided between body 1b and lens mount 1c, lens 5 is inserted and attached into base 1 from body 1b, and second elastic member 6 elastically abuts on protrusion 5b and urges lens 5 toward lens mount 1c when annular frame 2 is rotated in one direction.

(75) As a result, gravity of lens 5 is received by body 1b, and the gravity of lens 5 substantially does not act on lens mount 1c. Therefore, lens mount 1c need not have high hardness and may include an inexpensive material, which leads to cost reduction.

(76) Lens mount 1c is preferably provided with groove 1ca accommodating protrusion 5b inserted through recess 2b.

(77) Consequently, lens 5 can easily be mounted on base 1 using groove 1ca.

(78) Base 1 is preferably provided with stopper 1ba that limits the rotation angle of annular frame 2 to a predetermined angle.

(79) Thus, by setting the circumferential length of stopper 1ba, the predetermined angle at which annular frame 2 rotates can be freely set.

(80) By rotating annular frame 2 by a predetermined angle in a direction opposite to the one direction, it is preferable that the fixation of lens 5 and the electrical connection between socket contact 3a of socket 3 and lens contact 5a of lens 5 can be released.

(81) Thus, lens 5 can be removed from base 1 by a simple operation of rotating annular frame 2 in a direction opposite to the one direction.

(82) Further, the present disclosure provides the projector including the above-described lens mounting apparatus.

(83) In the projector of the present disclosure, lens 5 is mounted by the above-described lens mounting apparatus, and thus effects similar to effects of the above-described lens mounting apparatus can be obtained.

(84) Although the present disclosure has sufficiently described the preferred exemplary embodiments with reference to the drawings as described above, those skilled in the art will obviously make appropriate modifications or changes on the basis of the above exemplary embodiments. Such modifications or changes are considered to be included in the scope of protection of the present disclosure unless deviating from the gist of the present disclosure.

Claims

1. A lens mounting apparatus comprising: a base including an opening, wherein a lens including a connection part is inserted and attached into the opening of the base; and a frame including a notch provided on a part of an outer periphery of the frame, wherein the frame is rotatably mounted on the base, the frame is configured to fix the lens inserted and attached into the base by rotating the frame in one direction by a predetermined angle, the frame includes a recess on an inner periphery of the frame, a protrusion provided on an outer peripheral surface of the lens is inserted through the recess of the frame, the lens mounting apparatus further comprises an elastic member at a position separated by a predetermined distance from one end of the recess of the frame, the elastic member elastically abutting on the protrusion and urging the lens toward the base when the frame is rotated in the one direction, a plurality of the protrusions, a plurality of the recesses, and a plurality of the elastic members are provided correspondingly, and a plurality of the predetermined distances are different from each other.

2. The lens mounting apparatus according to claim 1, wherein the plurality of predetermined

distances are set for the plurality of elastic members and the plurality of protrusions to elastically abut on each other sequentially when the frame is rotated in the one direction.

3. The lens mounting apparatus according to claim 1, wherein the base includes a body and a lens mount, the frame is provided between the body and the lens mount, the lens is inserted and attached into the base from the body, and the elastic member elastically abuts on the protrusion and urges the lens toward the lens mount when the frame is rotated in the one direction.

4. The lens mounting apparatus according to claim 3, wherein the lens mount includes a groove that accommodates the protrusion inserted through the recess.

5. The lens mounting apparatus according to claim 1, wherein the base includes a stopper that limits a rotation angle of the frame to the predetermined angle.

6. The lens mounting apparatus according to claim 1, further comprising a socket electronically connected to the connection part of the lens, wherein by rotating the frame by the predetermined angle in a direction opposite to the one direction, the frame is configured to release fixation of the lens and release an electrical connection between the socket and the connection part of the lens.

7. A projector comprising the lens mounting apparatus according to claim 1.

8. The lens mounting apparatus according to claim 1, further comprising: a socket electrically connected to the connection part of the lens; and a second elastic member provided to urge the socket from the outer periphery toward a center of the frame, wherein when the frame does not fix the lens, the notch does not face the socket, and when the frame fixes the lens, the notch faces the socket, and the socket is electrically connected to the connection part of the lens by an urging force of the second elastic member.
