

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409361
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Watson; Richard Yates

Low-profile balance board

Abstract

A balance board comprising a board, a first member, and a pivot interface. The board has a top side for applying active use resistance and active use effort, a bottom side, and an outer circumference. The first member consists of a base, a first side, a second side, and a pivot, the base having a width and the pivot having a second width, the first width greater than the second width. The first pivot interface comprises a roll section of the pivot and a first section of the bottom side of the board. The board and the first member have a low-height profile and a restricted roll in response to an active use resistance and an active use effort applied to the top side of the board. The pivot is rounded convex or bullnose shape. The base has a width 5 times greater than the width of the pivot's base.

Inventors:	Watson; Richard Yates (Park Ridge, IL)
Applicant:	Watson; Richard Yates (Park Ridge, IL)
Family ID:	92898768
Appl. No.:	18/387000
Filed:	November 03, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240325817 A1	Oct. 03, 2024

Related U.S. Application Data

us-provisional-application US 63492504 20230328

Publication Classification

Int. Cl.: A63B22/16 (20060101); A63B71/00 (20060101)

U.S. Cl.:

CPC A63B22/16 (20130101); A63B71/0054 (20130101);

Field of Classification Search

CPC: A63B (22/14); A63B (22/16); A63B (22/18)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2947009	12/1959	Mckenzie	359/872	A47C 21/00
3488049	12/1969	Sasser, Jr.	482/146	A63B 22/16
3561022	12/1970	James	482/142	A61H 1/0229
4822039	12/1988	Gonzales	482/130	A63B 21/04
5328421	12/1993	Stanalajczo	482/79	A63B 22/16
5755651	12/1997	Homyonfer	482/130	A63B 22/16
7252290	12/2006	Kaselitz	273/449	A63B 26/003
8888669	12/2013	Dunegan	482/141	A63B 23/1236
11369839	12/2021	Mrzlak	N/A	A63B 21/4034

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
20230116403	12/2022	KR	N/A

Primary Examiner: Moore; Zachary T

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application claims priority to U.S. Provisional Application No. 63/492,504, filed Mar. 28, 2023, the contents of which are incorporated herein by reference.

BACKGROUND

(1) The present disclosure relates to physical fitness equipment and, more particularly, balancing boards for improving balance or equilibrium, and safety measures for the elderly or inform.

(2) Aging brings about physiological changes that affect the body in various ways. These changes can cause bones to shrink in size and density, muscles to lose mass, strength, and flexibility, and the cognitive abilities of the brain to functionally diminish. These are factors that can affect a person's balance, stability, and coordination. Diminished balance, instability, and poor coordination are conditions that increase the chances of a person falling and injuring themselves. In some cases, these injuries can result in fractures, head trauma, and even death. According to www.nidcd.nih.gov website, falls are a leading cause of injury among older adults.

(3) Exercises performed using a balance board can be effective at countering diminished balance coordination. Using a balance board can improve balance and coordination, develop posture and core strength, rehabilitate, and prevent injuries, increase motor skills and cognitive skills, and

strengthen lower leg muscles. Balance boards available on the market may be effective for their intended purpose, but all lack critical safety features. As a result, exercising using one of these available balance boards can result in injury or injuries. And for the elderly, or those otherwise considered infirm, these types of injuries can be serious or even life threatening.

(4) As can be seen, there is a need for a balance board with improved safety measures.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. Like numerals having different letter suffixes may represent different instances of similar components. The drawings illustrate generally, by way of example, but not by way of limitation, various embodiments discussed in the present disclosure.

(2) FIG. 1 shows a top perspective view of a person using a low-profile balance board, the balance board comprising a board and one of a plurality of wedges for use with the board.

(3) FIG. 2A shows a bottom perspective view of the low-profile balance board.

(4) FIG. 2B shows a side view of wedge or member for use with a low-profile balance board.

(5) FIG. 3 is a side view of the low-profile balance board.

(6) FIG. 4 is a section view of the low-profile balance board, taken along line 4-4 in FIG. 3.

(7) FIG. 5A is a schematic diagram of the low-profile balance board.

(8) FIG. 5B is a front view of the low-profile balance board showing the movement (or swing or tipping) of the board on its pivot.

(9) FIG. 6 is an exploded view of the invention, illustrating the ability to interchangeably use variably sized wedges.

(10) FIG. 7 is a front view of the low-profile balance board, shown with a small wedge of select dimensions.

(11) FIG. 8 is a front view of the low-profile balance board, shown with a medium wedge of other select dimensions.

(12) FIG. 9 is a flow chart of a typical order of steps a person might follow when using the low-profile balance board.

(13) While embodiments of this disclosure have been depicted, such embodiments do not imply a limitation on the disclosure, and no such limitation should be inferred. The subject matter disclosed is capable of considerable modification, alteration, and equivalents in form and function, as will occur to those skilled in the pertinent art and having the benefit of this disclosure. The depicted and described embodiments of this disclosure are examples only, and not exhaustive of the scope of the disclosure.

DETAILED DESCRIPTION

(14) In the following description of various illustrative embodiments, reference is made to the accompanying drawings, which form a part hereof, and in which is shown, by way of illustration, various embodiments in which aspects of the disclosure may be practiced. It is to be understood that other embodiments may be utilized, and structural and functional modifications may be made, without departing from the scope of the present disclosure.

Overview

(15) As previously stated, the aging process brings about physiological changes to the body. As a result, a person's reflexes and reaction time tend to slow down.

(16) Falls among the elderly are a serious health issue that can cause injuries, death, and reduced quality of life. The risk of falling increases with age due to physical changes, health conditions, medications, environmental hazards, and other factors. According to the Centers for Disease Control and Prevention (CDC), one in four older adults reported falling, which equals about 36

million falls. Many of these falls require medical attention or a limitation in activity. It is also known that the risk of fall-related injuries and death increases with the height from which one falls. Additionally, the CDC has stated that more than 32,000 adults die from falls each year, or 88 adults per day. Injuries from falls and the fear of falling are a threat to the health and independence of older adults.

(17) It is important to take preventive measures to avoid falls among the elderly. Routine physical exercises are a great preventive measure. As previously stated, balance boards are great at countering diminished balance coordination. However, balance boards currently available on the market are dangerous when used ineffectively or not used properly or used carelessly. They can be particularly dangerous for the elderly, or infirm, who do not have the necessary reflexes and reaction time to use one of the commercially available balance boards as needed to benefit without significant risk of injury or death. As such, the elderly are much less likely to benefit from the benefits of this type of physical exercise device.

(18) Balance boards currently on the market have a platform (or board) set on top of, or coupled with, a pivot member. The balance board is set on ground surface and a person attempts to balance themselves and the platform as the pivot member rotates along the ground surface. The pivot member is configured to have a pivot with a large, rounded area that rolls along ground surface.

(19) A particular problem is that the platform sets too high from the ground, or stable surface. The platforms for some balance boards at level, or non-rotated, are over three and a quarter inch from the ground, and most are over five inches from the ground. Moreover, one of the body's ways to have awareness in balance is by proprioceptors. These sensory receptors are found in muscles, tendons and joints throughout the body. This low-profile board can achieve results in improved balance without the height problem of other balance boards.

(20) Another problem with currently available balance boards is the slow roll due to the large, rounded area of the pivot member. These are factors that can increase the chance of injury. The combination of height, slow roll, and size of the person can cause sudden changes in rotational velocity and motion. The higher the balance board is off the ground, the more pronounced the changes. Although for most these changes may not be disruptive, or even noticeable, to the elderly, or infirm, these sudden changes can be unmanageable and result in injury.

(21) Presented herein is a low-profile balance board having dimensioned safety measures that reduce the chance of injury while using the balance board. The low-profile balance board comprises a board, a first member, and a first pivot interface. The board has a top side for applying active use resistance and active use effort, a bottom side, and an outer circumference. The first member consists of a base, a first side, a second side, and a pivot. The first pivot interface comprises a top section of the pivot and a first section of the bottom side of the board. The board comprises a traverse (or horizontal) plane. The traverse (or horizontal) plane runs lengthwise to the board and has a fast roll, but a restricted roll due to a low-height profile that keeps the board stable and low to the ground.

(22) Also, presented herein is an article of manufacture comprising a board, a first member, and one or more additional members. The board comprises a top side for applying an active use resistance and an active use effort, a bottom side, and an outer circumference. The first member consists of a base, a first side, a second side, and a pivot between the first side and the second side. Each additional member consists of a base, a first side, a second side, and a pivot. The base, the first side, the second side, the pivot, or any combination thereof of each additional member has one or more dimensions distinct from the first member and other additional members. The article of manufacture further includes a first pivot interface. The first pivot interface further comprises a top section of the pivot and a first section of the bottom side of the board. The board comprises a traverse (or horizontal) plane. The traverse (or horizontal) plane runs lengthwise to the board and has a fast roll, but a restricted roll due to a low-height profile that keeps the board stable and low to the ground.

(23) Additionally, presented herein is a balance board comprising a board, a first member, and a first pivot interface. The board has a top side for applying active use resistance and an active use effort, a bottom side, and an outer circumference. The first member consists of a base, a first side, a second side, and a pivot between the first side and the second side. The base has a first width, and the pivot has a second width, the first width greater than the second width. The first pivot interface comprises a roll section (FIG. 2B) of the pivot and a first section of the bottom side of the board. The board and the first member have a low-height profile and a restricted roll in response to an active use resistance and an active use effort applied to the top side of the board.

(24) The first pivot interface comprises a surface, non-fixed contact. The balance board further comprises a second pivot interface, the second pivot interface comprising the top section of the pivot and a second section of the bottom side of the board, the second pivot interfaced achieved in response to movement (or swing or tipping) active resistance, movement (or swing or tipping) active effort, or both. The pivot (FIG. 2B) is rounded convex or bullnose shape. The base has a width 5 times greater than the width of the pivot's base. The first side and the second side have an angle of incline of 45 degrees. The balance board comprises a second member with two sides and a pivot, the second member having one or more dimensions different than the first member. The balance board further comprises one or more additional members with each having two sides and a pivot, the one or more additional members having one or more dimensions different than the first member and the second member.

(25) The low-profile balance board has many advantages over commercially available balance boards. The low-profile balance board has a board (or platform) and multiple (balancing) members of various sizes, e.g., large, medium, and small. The board proportionally has a much greater dimensional area than that of each member. The largest member has a total height under 1.5 inches, (unless this includes the board, which is then 2.0 inches). Each member includes a pivot with a rounded, smooth convex shape, a flat base that rests flat or parallel with a ground surface, and two inclined sides between the flat base and pivot, or base sides of the pivot. Additionally, the board and the member are in surface contact and not physically connected or fixed together, allowing the board to be easily manipulated during use.

(26) The unique oval size of the board gives the user the perception of being closer to the ground and the total height allows the board to be closer to the ground. Each of these can help the user stay focused and avoid injury. The rounded, smooth convex shape allows the board to easily roll and to do so without frictional forces disrupting the roll. Additionally, the rounded, smooth convex shape allows the board to be easily manipulated, e.g., to change positions of the board with respect to the member, while using the low-profile balance board. Further, the flat base, height, or both eliminate or minimizes the member from responding to rotational force or torque about its axis. Furthermore, the total height and rounded, smooth convex shape allows the board to have a fast roll, realistic simulated balance training situation, for an optimal workout.

(27) The low-profile balance board can be made of wood, metal, plastic, or any combination thereof. Members of low-profile balance board can be manufactured as a single piece member or a multipiece member.

Description

(28) FIG. 1 illustrates a top perspective view of person **280** using a low-profile balance board **100**, according to certain aspects of the present disclosure. Low-profile balance board **100** comprises a board **110**, top side **120** with outer circumference, (balancing) member **140**, and ground surface **260**.

(29) In use, person **280** places member **140** under board **110** at a desired location. While holding on to a non-movable object for additional safety, person **280** steps on low-profile balance board **100** and begins applying an active use resistance and an active use effort to balance themselves and board **110** on member **140**. Person **280**, while standing on board **110**, can change positions of board **110** with respect to member **140** to target a particular muscle group.

(30) FIGS. 2A and 2B illustrate a perspective view of a bottom side **122** of the low-profile balance board **100**, and a bottom-side view of member **140**, respectively, according to certain aspects of the present disclosure. Low-profile balance board **100** comprises board-pivot interface **180**. Board-pivot interface **180** comprises a top section (or roll area) of pivot **160** and a section of bottom side **122**. FIG. 3 illustrates a side view of low-profile balance board **100**, according to certain aspects of the present disclosure. FIG. 4 illustrates a section view of low-profile balance board **100**, taken along line 4-4 in FIG. 3, according to certain aspects of the present disclosure.

(31) In general, board **110** has a greater dimensional area than that of each member. As an example, board **110** can measure over 2 feet in length and a foot and a half in width. More particularly, board **110** can have a circumference of about 68 inches, a length of about 25 and $\frac{3}{4}$ inches, a width of about 17 inches, and a height (H) of about $\frac{3}{4}$ of an inch. Member **140** can have a base width of about 2 inches, length of about 12 inches, a height (h) of about 1 and a $\frac{1}{2}$ inches. Additionally, sides 1 and 2 can have a width of about 2 inches and an incline of about 45 degrees. The total height of low-profile balance board **100** in its level position is about 2 and $\frac{1}{4}$ inches. The total height of low-profile balance board **100** at its top roll height is about 3 and $\frac{3}{4}$ inches.

(32) FIG. 5A is a diagrammatic side view representation of low-profile balance board **100**, according to certain aspects of the present disclosure. FIG. 5B is a front view of low-profile balance board **100** showing the movement (or swing or tipping) of board **110** on its pivot **160**, according to certain aspects of the present disclosure.

(33) Pivot **160** can have a rounded or curved type smooth top surface. Pivot **160** can be a smooth, convex type layer or surface of pivot **160**. Pivot **160** can be described as a smooth, full bullnose type layer or surface of pivot **160**. The bullnose type layer or surface of pivot **160** and its dimensions with respect to board **110** allow pivot **160** to have a fast roll. The roll is restricted due to the height of the member **140**. The smoothness of the top surface of pivot **160** improves durability and reduces drag, allowing board **110** to glide or move more easily under load and create a realistic simulated balance training situation.

(34) Base of member **140** is relatively wide with respect to pivot **160**. This eliminates or minimizes member **140** from responding to rotational force or torque about its axes. This is a safety measure that keeps the traverse plane of board **110** relatively fixed with the ground plane of member **140** during use. This allows person **280** to concentrate on balancing board **110** and not on balancing and the rolling action of some commercially available products that use a cylinder, half-circle shape, or something similar, in place of member **140**.

(35) FIG. 6 is an exploded view of board **110** and first (large) member **140** with pivot **160**, member **140** having a first set of dimensions, second (medium) member **200** with pivot **210**, member **200** having a second set of dimensions, and third (small) member **230** with pivot **240**, member **230** having a third set of dimensions, according to some aspects of the present disclosure. FIG. 7 is a front view of low-profile balance board **100**, shown with board **110**, member **230** of select dimensions, and board-pivot interface **320**, according to some aspects of the present disclosure. FIG. 8 is a front view of low-profile balance board **100**, shown with board **110**, member **200** of other select dimensions, and board-pivot interface **310**, according to some aspects of the present disclosure.

(36) Board **110** can be manufactured to have an oval or oblong shape. Although other shapes are possible, the oval or oblong shape can provide sufficient lateral space that may be preferred for some users over a shape that has less lateral space. Board **110** can measure over 2 feet in length, a foot and a $\frac{1}{2}$ in width. Although other sizes are possible. During use, the size and shape of board **110** can give the user the impression board **110** is closer to the ground or that he or she is standing on a more robust or solid platform. For the elderly, this can help with relation, or perspective, and allow the user to focus on the task at hand. It also allows the user to find the stance that is most comfortable in performing an exercise routine, which also helps with relaxation. As previously provided, board **110** and member **140** have dimensions selected to improve balance board safety

while using the device for exercise routines, without compromising the quality and effectiveness of these routines.

(37) As previously stated, member **140** can have a base width of about 2 and ½ inches, length of about 12 inches, and a height (h) of about 1 and ½ inches. Member **200** is slightly shorter than member **140** at a little over an inch in height (h). Member **230** is slightly shorter than member **200** at around ¾ of an inch in height (h). A novice or someone not in good balance condition or physical fitness shape can start out using the smallest member, **230**, and work their way up to member **140**, the largest member. This wedge or member progression is important for variety and balance improvements.

(38) Board **110** and member **140** are not physically attached together or fixed to one another. Board **110** and member **140** have a surface, non-fixed contact. This allows the user to manipulate board **110** to various positions while using it to adjust an exercise routine to target other muscle groups.

(39) In use, see FIG. 9, person **280** can select from members **140**, **200**, and **230**, depending on the user's experience level. For a novice, member **230** (level 1) can be used. For an experienced user, member **140** (level 3) can be used. The selected member is placed under board **110** at a desired location. While holding on to a non-movable object for additional safety, person **280** steps on low-profile balance board **100** and begins applying an active use resistance and an active use effort to balance themselves and board **110** on the selected member. Person **280**, while standing on board **110**, can change positions of board **110** with respect to the selected member to target a particular muscle group.

(40) Board **110** and member **140**, **200**, or **230** can be configured for multi-use purposes. Instead of using board **110** and member **140**, **200**, or **230** as a balance board, board **110** and member **140**, **200**, or **230** can be configured for use as a low-profile board for plank exercises and other upper extremity exercises. Plank exercises can help strengthen the core muscles that surround the spine, abdominal viscera, and hip, as well as strengthen the cervical, shoulder and thoracic regions. Plank exercises can also help improve balance and increase motor coordination for the entire body.

(41) Board **110** can be manufactured using Baltic birch grade 3B plywood, a CNC (Computer Numerical Controlled) machining process, and a meticulous detailed sanding process. Board **110** can also include rubber edging **400** for protection and dampening of noise effect. Board **110** can include non-slip decals to the top and bottom surfaces of board **110** for safety and education purposes. Members **140**, **200**, and **230** can be cut from high-quality white oak and sanded for beveled fulcrum top and all edges sanded to avoid any sharp points. Decal stickers can be applied to member **140**, **200**, and **230** for identification and connection to board **110**.

(42) The above-disclosed embodiments have been presented for the purposes of illustration and to enable one of ordinary skill in the art to practice the disclosure, but the disclosure is not intended to be exhaustive or limited to the forms disclosed. Many insubstantial modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the disclosure. The scope of the claims is intended to broadly cover the disclosed embodiments and any such modification. Further, the following clauses represent additional embodiments of the disclosure and should be considered within the scope of the disclosure.

(43) Clause 1, a balance board having dimensioned safety measures, the balance board comprising: a board having a top side for applying an active use resistance and an active use effort, a bottom side, and an outer circumference; a first member consisting of a base, a first side, a second side, and a pivot; a first pivot interface comprising a top section of the pivot and a first section of the bottom side of the board; and wherein the board comprises a traverse plane, the traverse plane having a fast, restricted roll and low-height profile.

(44) Clause 2, the balance board of clause 1, wherein the first pivot interface comprises a surface, non-fixed contact.

(45) Clause 3, the balance board of any of the preceding clauses, further comprising a second pivot interface, the second pivot interface comprising the top section of the pivot and a second section of

the bottom side of the board, the second pivot interfaced achieved in response to movement (or swing or tipping) active resistance, movement (or swing or tipping) active effort, or both.

(46) Clause 4, the balance board of any of the preceding clauses, wherein the pivot is rounded convex or bullnose shape.

(47) Clause 5, the balance board of any of the preceding clauses, wherein the base comprises a first width and the pivot comprises a second width, the first width greater than the second width.

(48) Clause 6, the balance board of any of the preceding clauses, further comprising a second member with two sides and a pivot, the second member having one or more dimensions different than the first member.

(49) Clause 7, the balance board of any of the preceding clauses, further comprising one or more additional members with each having two sides and a pivot, the one or more additional members having one or more dimensions different than the first member and the second member.

(50) Clause 8, an article of manufacture having dimensioned safety measures, the article of manufacture comprising: a board having a top side for applying an active use resistance and an active use effort, a bottom side, and an outer circumference; a plurality of members comprising: a first member consisting of a base, a first side, a second side, and a pivot between the first side and the second side; one or more additional members, wherein each additional members consists of: a base, a first side, a second side, and a pivot; wherein the base, the first side, the second side, the pivot, or any combination thereof of each additional member has one or more dimensions distinct from the first member and other additional members; a first pivot interface comprising a top section of the pivot and a first section of the bottom side of the board; and wherein the board comprises a traverse plane, the traverse plane having a fast, restricted roll and low-height profile.

(51) Clause 9, the article of manufacture of any of the preceding clauses, wherein the first pivot interface comprises a surface, non-fixed contact.

(52) Clause 10, the article of manufacture of any of the preceding clauses, further comprising a second pivot interface, the second pivot interface comprising the top section of the pivot and a second section of the bottom side of the board, the second pivot interfaced achieved in response to movement (or swing or tipping) active resistance, movement (or swing or tipping) active effort, or both.

(53) Clause 11, the article of manufacture of any of the preceding clauses, wherein the pivot is rounded convex or bullnose shape.

(54) Clause 12, the article of manufacture of any of the preceding clauses, wherein the base of each member comprises a first width and the pivot comprises a second width, the first width greater than the second width.

(55) Clause 13, a balance board comprising: a board having a top side for applying an active use resistance and an active use effort, a bottom side, and an outer circumference; a first member consisting of a base, a first side, a second side, and a pivot between the first side and the second side, the base having a first width and the pivot having a second width, the first width greater than the second width; a first pivot interface comprising a roll section of the pivot and a first section of the bottom side of the board; and wherein the board and the first member have a low-height profile and a restricted roll in response to an active use resistance and an active use effort applied to the top side of the board.

(56) Clause 14, the balance board of any of the preceding clauses, wherein the first pivot interface comprises a surface, non-fixed contact.

(57) Clause 15, the balance board of any of the preceding clauses, further comprising a second pivot interface, the second pivot interface comprising the top section of the pivot and a second section of the bottom side of the board, the second pivot interfaced achieved in response to movement (or swing or tipping) active resistance, movement (or swing or tipping) active effort, or both.

(58) Clause 16, the balance board of any of the preceding clauses, wherein the pivot is rounded

convex or bullnose shape.

(59) Clause 17, the balance board of any of the preceding clauses, wherein the base has a width 5 times greater than the width of the pivot's base.

(60) Clause 18, the balance board of any of the preceding clauses, wherein a first side and the second side have an angle of incline of 45 degrees.

(61) Clause 19, the balance board of any of the preceding clauses, further comprising a second member with two sides and a pivot, the second member having one or more dimensions different than the first member.

(62) Clause 20, the balance board of any of the preceding clauses, further comprising one or more additional members with each having two sides and a pivot, the one or more additional members having one or more dimensions different than the first member and the second member.

(63) As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprise” and/or “comprising,” when used in this specification and/or the claims, specify the presence of stated features, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, steps, operations, elements, components, and/or groups thereof. In addition, the steps and components described in the above embodiments and figures are merely illustrative and do not imply that any particular step or component is a requirement of a claimed embodiment.

Claims

1. A balance board having dimensioned safety measures, the balance board comprising: a board having a top side for applying an active use resistance and an active use effort, a bottom side, and an outer circumference; a first member consisting of a base, a first side, a second side, and a pivot; a first pivot interface comprising a top section of the pivot and a first section of the bottom side of the board; and wherein the board comprises a traverse plane, the traverse plane having a fast, restricted roll and low-height profile; and a second member with two sides and a pivot, the second member having one or more dimensions different than the first member.
2. The balance board of claim 1, wherein the first pivot interface comprises a surface, non-fixed contact.
3. The balance board of claim 2, further comprising a second pivot interface, the second pivot interface comprising the top section of the pivot and a second section of the bottom side of the board, the second pivot interfaced achieved in response to rotational active resistance, rotational active effort, or both.
4. The balance board of claim 1, wherein the pivot is rounded convex or bullnose shape.
5. The balance board of claim 1, wherein the base comprises a first width and the pivot comprises a second width, the first width greater than the second width.
6. The balance board of claim 1, further comprising one or more additional members with each having two sides and a pivot, the one or more additional members having one or more dimensions different than the first member and the second member.
7. An article of manufacture having dimensioned safety measures, the article of manufacture comprising: a board having a top side for applying an active use resistance and an active use effort, a bottom side, and an outer circumference; a plurality of members comprising: a first member consisting of a base, a first side, a second side, and a pivot between the first side and the second side; one or more additional members, wherein each additional members consists of: a base, a first side, a second side, and a pivot; wherein the base, the first side, the second side, the pivot, or any combination thereof of each additional member has one or more dimensions distinct from the first member and other additional members; a first pivot interface comprising a top section of the pivot and a first section of the bottom side of the board; and wherein the board comprises a traverse

plane, the traverse plane having a fast, restricted roll and low-height profile.

8. The article of manufacture of claim 7, wherein the first pivot interface comprises a surface, non-fixed contact.

9. The article of manufacture of claim 8, further comprising a second pivot interface, the second pivot interface comprising the top section of the pivot and a second section of the bottom side of the board, the second pivot interfaced achieved in response to rotational active resistance, rotational active effort, or both.

10. The article of manufacture of claim 7, wherein the pivot is rounded convex or bullnose shape.

11. The article of manufacture of claim 7, wherein the base of each member comprises a first width and the pivot comprises a second width, the first width greater than the second width.

12. A balance board comprising: a board having a top side for applying an active use resistance and an active use effort, a bottom side, and an outer circumference; a first member consisting of a base, a first side, a second side, and a pivot between the first side and the second side, the base having a first width and the pivot having a second width, the first width greater than the second width; a first pivot interface comprising a roll section of the pivot and a first section of the bottom side of the board; and wherein the board and the first member have a low-height profile and a restricted roll in response to an active use resistance and an active use effort applied to the top side of the board; and one or more additional members with each having two sides and a pivot, the one or more additional members having one or more dimensions different than the first member and a second member.

13. The balance board of claim 12, wherein the first pivot interface comprises a surface, non-fixed contact.

14. The balance board of claim 13, further comprising a second pivot interface, the second pivot interface comprising the top section of the pivot and a second section of the bottom side of the board, the second pivot interfaced achieved in response to movement or swing or tipping active resistance, movement or swing or tipping active effort, or both.

15. The balance board of claim 12, wherein the pivot is rounded convex or bullnose shape.

16. The balance board of claim 12, wherein the base has a width 5 times greater than that of a base of the pivot.

17. The balance board of claim 12, wherein the first side and the second side have an angle of incline of about 45 degrees.

18. The balance board of claim 12, further comprising the second member with two sides and a pivot, the second member having one or more dimensions different than the first member.
