

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409484
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Stearne; Dwight et al.

Pipe bender alignment assembly

Abstract

A pipe bender alignment assembly includes a sleeve that is positionable around a pipe. A plurality of laser mounts is each attached to and extends outwardly from the sleeve and a plurality of laser emitters is mounted to a respective one of the plurality of laser mounts to emit a beam of laser light outwardly from the sleeve. The sleeve is rotatable on the pipe to align a respective one of the plurality of laser emitters with an alignment mark on a pipe bender to visually indicate that the pipe is precisely located in the pipe bender for accurately bending the pipe. A magnet is integrated into the sleeve for retaining the sleeve at a particular angle of rotating on the pipe.

Inventors:	Stearne; Dwight (Roseville, CA), Akens; Damien (Roseville, CA)
Applicant:	Stearne; Dwight (Roseville, CA); Akens; Damien (Roseville, CA)
Family ID:	92305560
Appl. No.:	18/111974
Filed:	February 21, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240278307 A1	Aug. 22, 2024

Publication Classification

Int. Cl.: **G01B3/56** (20060101); **B21D7/02** (20060101); **B21D7/16** (20060101); **G01B5/24** (20060101)

U.S. Cl.:

CPC **B21D7/16** (20130101); **B21D7/02** (20130101); **G01B3/56** (20130101); **G01B5/24** (20130101);

Field of Classification Search

CPC: B21D (7/16); B21D (7/02); B21D (7/063); G01B (3/56); G01B (5/24)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6124935	12/1999	Matthews	356/138	G01C 15/008
6708782	12/2003	Turney	175/45	E21B 7/067
6877236	12/2004	Williams	33/286	G01C 15/002
7155834	12/2006	Palumbo, III	33/645	G01C 15/002
7748127	12/2009	Cosimano	33/286	G01C 15/002
7886565	12/2010	Hainzinger	N/A	N/A
8893395	12/2013	Mickow	33/529	G01C 15/002
9080864	12/2014	McCarthy	N/A	G01C 15/004
9551145	12/2016	Aguilar	N/A	E04B 2/00
10309776	12/2018	Doeren	N/A	G01C 9/34
D939363	12/2020	Stellato	N/A	N/A
2007/0214666	12/2006	Kishi	33/281	G01C 15/004
2015/0033813	12/2014	Leclerc	N/A	N/A
2017/0343348	12/2016	Doeren	N/A	G01C 9/34
2020/0173778	12/2019	Smith	N/A	N/A
2020/0282505	12/2019	Benton	N/A	N/A
2021/0190494	12/2020	Lindberg	N/A	G01C 15/105
2021/0213507	12/2020	Heaird	N/A	N/A
2024/0278307	12/2023	Stearne	N/A	B21D 7/02
2024/0310166	12/2023	Goffredo	N/A	G01B 11/27

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO2013131179	12/2012	WO	N/A

Primary Examiner: Guadalupe-McCall; Yaritza

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) Not Applicable

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

(2) Not Applicable

THE NAMES OF THE PARTIES TO A JOINT RESEARCH AGREEMENT

(3) Not Applicable

INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC
OR AS A TEXT FILE VIA THE OFFICE ELECTRONIC FILING SYSTEM

(4) Not Applicable

STATEMENT REGARDING PRIOR DISCLOSURES BY THE INVENTOR OR JOINT

INVENTOR

(5) Not Applicable

BACKGROUND OF THE INVENTION

(1) Field of the Invention

(6) The disclosure relates to pipe bender devices and more particularly pertains to a new pipe bender device for precisely positioning a pipe in a pipe bender. The device includes a sleeve that is slidable on a pipe and a plurality of laser emitters integrated into the sleeve. The device includes a magnet integrated into the sleeve for retaining the sleeve at a selected spot on the pipe. The pipe is rotated to align a beam of laser light emitted from a respective laser emitter with an alignment mark on the pipe bender.

(2) Description of Related Art Including Information Disclosed Under 37 CFR 1.97 and 1.98

(7) The prior art relates to pipe bender devices including a pipe bender with a curved angled indicator. The prior art discloses a pipe bender that includes a curved saddle and a handle. The prior art discloses a pipe fitting device that comprises a plurality of pipe fittings that is each insertable into a leg of a pipe and a plurality of light emitters each integrated into a respective pipe fitting for emitting a beam of light to indicate where a junction with the leg of the pipe will intersect an adjacent pipe. The prior art discloses a laser guided conduit bender that includes a pipe bender and a laser pointer attached to the pipe bender.

BRIEF SUMMARY OF THE INVENTION

(8) An embodiment of the disclosure meets the needs presented above by generally comprising a sleeve that is positionable around a pipe. A plurality of laser mounts is each attached to and extends outwardly from the sleeve and a plurality of laser emitters is mounted to a respective one of the plurality of laser mounts to emit a beam of laser light outwardly from the sleeve. The sleeve is rotatable on the pipe thereby facilitating a respective one of the plurality of laser emitters to be aligned with an alignment mark on a pipe bender to visually indicate that the pipe is precisely located in the pipe bender for accurately bending the pipe. A magnet is integrated into the sleeve for retaining the sleeve at a particular angle of rotating on the pipe.

(9) There has thus been outlined, rather broadly, the more important features of the disclosure in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the disclosure that will be described hereinafter and which will form the subject matter of the claims appended hereto.

(10) The objects of the disclosure, along with the various features of novelty which characterize the disclosure, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

Description

BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWING(S)

(1) The disclosure will be better understood and objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:

(2) FIG. 1 is a front view of a pipe bender alignment assembly according to an embodiment of the disclosure.

(3) FIG. 2 is a top perspective view of an embodiment of the disclosure.

(4) FIG. 3 is a left side view of an embodiment of the disclosure.

(5) FIG. 4 is a top view of an embodiment of the disclosure.

(6) FIG. 5 is a left side cut-away view of an embodiment of the disclosure.

(7) FIG. 6 is a perspective in-use view of an embodiment of the disclosure.

DETAILED DESCRIPTION OF THE INVENTION

(8) With reference now to the drawings, and in particular to FIGS. **1** through **6** thereof, a new pipe bender device embodying the principles and concepts of an embodiment of the disclosure and generally designated by the reference numeral **10** will be described.

(9) As best illustrated in FIGS. **1** through **6**, the pipe bender alignment assembly **10** generally comprises a sleeve **12** that is positionable around a pipe **14**. The sleeve **12** has a first end **16**, a second end **18** and an outside wall **20** extending between the first end **16** and the second end **18**. The pipe **14** may be a metal conduit or other type of pipe that is commonly bent using a pipe bender **21**. The pipe bender **21** may be a mechanized pipe bender that has an alignment mark **22**. The sleeve **12** may have a length ranging between approximately 5.0 cm and 10.0 cm and a diameter ranging between approximately 2.0 cm and 3.0 cm.

(10) A plurality of laser mounts **24** is each attached to and extends outwardly from the sleeve **12** and each of the laser mounts **24** is positioned on the outside wall **20** of the sleeve **12**. Each of the plurality of laser mounts **24** includes a first surface **26** that is perpendicularly oriented with the outside wall **20** of the sleeve **12**. The first surface **26** of each of the plurality of laser mounts **24** is aligned with the first end **16** of the sleeve **12**. Each of the plurality of laser mounts **24** includes a second surface **28** sloping downwardly between the first surface **26** and the outside wall **20** of the sleeve **12**. The plurality of laser mounts **24** is evenly spaced apart from each other and is distributed around a full circumference of the outside wall **20**. Additionally, each of the plurality of laser mounts **24** is positioned on a respective quadrant of the first end **16** of the sleeve **12**.

(11) A plurality of laser emitters **30** is each mounted to a respective one of the plurality of laser mounts **24** to emit a beam of laser light **32** outwardly from the sleeve **12**. The sleeve **12** is rotatable on the pipe **14** thereby facilitating a respective one of the plurality of laser emitters **30** to be aligned with an alignment mark **22** on a pipe bender **21**. In this way the beam of laser light **32** emitted from the respective laser light emitter **30** visually indicates that the pipe **14** is precisely located in the pipe bender **21** for accurately bending the pipe **14**. Each of the laser emitters **30** is positioned on the first surface **26** of the respective laser mount **24**. Furthermore, each of the plurality of laser emitters **30** may comprise a light emitting diode or the like and each of the plurality of laser emitters **30** may emit red light.

(12) A control button **34** is movably integrated into the outside wall **20** of the sleeve **12** and the control button **34** is electrically coupled to the plurality of the laser emitters **30**. The control button **34** is positionable in an increasing position for increasing brightness of the plurality of laser emitters **30** toward a maximum brightness. Conversely, the control button **34** is positionable in a decreasing position for decreasing brightness of the plurality of laser emitters **30** toward a minimum brightness. The control button **34** is positioned closer to the first end **16** of the sleeve **12** than the second end **18** of the sleeve **12**.

(13) A magnet **36** is integrated into the sleeve **12** and the magnet **36** magnetically engages the pipe **14** for retaining the sleeve **12** at a particular angle of rotation on the pipe **14**. In this way the magnet **36** can assist with aligning the beam of laser light **32** with the alignment mark **22** on the pipe bender **21**. The magnet **36** is integrated into the outside wall **20** of the sleeve **12** and the magnet **36** is positioned closer to the second end **18** of the sleeve **12** than the control button **34**. A power supply **38** is integrated into the outside wall **20** of the sleeve **12**, the power supply **38** is electrically coupled to the control button **34** and the power supply **38** comprises at least one battery **40**.

(14) In use, the sleeve **12** is slid onto the pipe **14** and the control button **34** is manipulated to actuate the plurality of laser emitters **30** to the desired brightness. The sleeve **12** is rotated until a respective one of the laser mounts **24** is aligned with a mark that has been placed on the pipe **14** to establish a location of a bend. The pipe **14** is positioned in a pipe bender **21** and the pipe **14** is rotated until the beam of laser light **32** emitted by the laser light emitter in the respective laser mount is aligned with the alignment mark **22** on the pipe bender **21**. In this way the pipe **14** can be precisely positioned in the pipe bender **21** to perform accurate bends in the pipe **14**. Furthermore, a plurality of bends of

varying directions and can be precisely formed into the pipe **14** by repositioning the sleeve **12** and aligning the beam of laser light **32** with the alignment mark **22**.

(15) With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of an embodiment enabled by the disclosure, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by an embodiment of the disclosure.

(16) Therefore, the foregoing is considered as illustrative only of the principles of the disclosure. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the disclosure to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the disclosure. In this patent document, the word “comprising” is used in its non-limiting sense to mean that items following the word are included, but items not specifically mentioned are not excluded. A reference to an element by the indefinite article “a” does not exclude the possibility that more than one of the element is present, unless the context clearly requires that there be only one of the elements.

Claims

1. A pipe bender alignment assembly for facilitating a pipe to be precisely oriented in a pipe bender, said assembly comprising: a sleeve being positionable around a pipe; a plurality of laser mounts, each of said plurality of laser mounts being attached to and extending outwardly from said sleeve; a plurality of laser emitters, each of said plurality of laser emitters being mounted to a respective one of said plurality of laser mounts wherein each of said plurality of laser emitters is configured to emit a beam of laser light outwardly from said sleeve, said sleeve being rotatable on said pipe thereby facilitating a respective one of said plurality of laser emitters to be aligned with an alignment mark on a pipe bender wherein said beam of laser light emitted from said respective laser light emitter is configured to visually indicate that the pipe is precisely located in the pipe bender for accurately bending the pipe; and a magnet being integrated into said sleeve, said magnet magnetically engaging the pipe for retaining said sleeve at a particular angle of rotating on the pipe wherein said magnet is configured to assist with aligning the beam of laser light with the alignment mark on the pipe bender.

2. The assembly according to claim 1, wherein: said sleeve has a first end, a second end and an outside wall extending between said first end and said second end; each of said laser mounts is positioned on said outside wall of said sleeve, each of said plurality of laser mounts including a first surface being perpendicularly oriented with said outside wall of said sleeve, said first surface of each of said plurality of laser mounts being aligned with said first end of said sleeve, each of said plurality of laser mounts including a second surface sloping downwardly between said first surface and said outside wall of said sleeve; and each of said laser emitters is positioned on said first surface of said respective laser mount.

3. The assembly according to claim 2, wherein said plurality of laser mounts is evenly spaced apart from each other and being distributed around a full circumference of said outside wall, each of said plurality of laser mounts being positioned on a respective quadrant of said first end of said sleeve.

4. The assembly according to claim 2, further comprising a control button being movably integrated into said outside wall of said sleeve, said control button being electrically coupled to said plurality of said laser emitters, said control button being positionable in an increasing position for increasing brightness of said plurality of laser emitters toward a maximum brightness, said control button being positionable in a decreasing position for decreasing brightness of said plurality of laser emitters toward a minimum brightness, said control button being positioned closer to said first

end of said sleeve than said second end of said sleeve.

5. The assembly according to claim 4, wherein said magnet is integrated into said outside wall of said sleeve, said magnet being positioned closer to said second end of said sleeve than said control button.

6. The assembly according to claim 4, further comprising a power supply being integrated into said outside wall of said sleeve, said power supply being electrically coupled to said control button, said power supply comprising at least one battery.

7. A pipe bender alignment assembly for facilitating a pipe to be precisely oriented in a pipe bender, said assembly comprising: a sleeve being positionable around a pipe, said sleeve having a first end, a second end and an outside wall extending between said first end and said second end; a plurality of laser mounts, each of said plurality of laser mounts being attached to and extending outwardly from said sleeve, each of said laser mounts being positioned on said outside wall of said sleeve, each of said plurality of laser mounts including a first surface being perpendicularly oriented with said outside wall of said sleeve, said first surface of each of said plurality of laser mounts being aligned with said first end of said sleeve, each of said plurality of laser mounts including a second surface sloping downwardly between said first surface and said outside wall of said sleeve, said plurality of laser mounts being evenly spaced apart from each other and being distributed around a full circumference of said outside wall, each of said plurality of laser mounts being positioned on a respective quadrant of said first end of said sleeve; a plurality of laser emitters, each of said plurality of laser emitters being mounted to a respective one of said plurality of laser mounts wherein each of said plurality of laser emitters is configured to emit a beam of laser light outwardly from said sleeve, said sleeve being rotatable on said pipe thereby facilitating a respective one of said plurality of laser emitters to be aligned with an alignment mark on a pipe bender wherein said beam of laser light emitted from said respective laser light emitter is configured to visually indicate that the pipe is precisely located in the pipe bender for accurately bending the pipe, each of said laser emitters being positioned on said first surface of said respective laser mount; a control button being movably integrated into said outside wall of said sleeve, said control button being electrically coupled to said plurality of said laser emitters, said control button being positionable in an increasing position for increasing brightness of said plurality of laser emitters toward a maximum brightness, said control button being positionable in a decreasing position for decreasing brightness of said plurality of laser emitters toward a minimum brightness, said control button being positioned closer to said first end of said sleeve than said second end of said sleeve; a magnet being integrated into said sleeve, said magnet magnetically engaging the pipe for retaining said sleeve at a particular angle of rotating on the pipe wherein said magnet is configured to assist with aligning the beam of laser light with the alignment mark on the pipe bender, said magnet being integrated into said outside wall of said sleeve, said magnet being positioned closer to said second end of said sleeve than said control button; and a power supply being integrated into said outside wall of said sleeve, said power supply being electrically coupled to said control button, said power supply comprising at least one battery.
