

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409726
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Oka; Nobuyuki et al.

Vehicle differential and vehicle

Abstract

A vehicle differential includes: a pair of side gears arranged in a differential case; a plurality of friction plates arranged on an axially outer side of respective one of the side gears; and a pressing member that holds the plurality of friction plates together with respective one of the side gears. Each of the side gears has: a gear section that meshes with a pinion gear; and a cylindrical section s that extends from a radially inner portion of the gear section toward an axially side. outer An outer circumferential portion of the cylindrical section meshes with an inner circumferential portion of the pressing member via a helical spline.

Inventors:	Oka; Nobuyuki (Hiroshima, JP), Ohkawa; Yuzo (Hiroshima, JP)
Applicant:	Mazda Motor Corporation (Hiroshima, JP)
Family ID:	92882725
Assignee:	MAZDA MOTOR CORPORATION (Hiroshima, JP)
Appl. No.:	18/906192
Filed:	October 04, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250121680 A1	Apr. 17, 2025

Foreign Application Priority Data

JP	2023-177746	Oct. 13, 2023
----	-------------	---------------

Publication Classification

Int. Cl.: F16H48/22 (20060101); B60K17/16 (20060101); B60K17/348 (20060101); B60K23/04 (20060101)

U.S. Cl.:

CPC B60K17/20 (20130101); B60K17/348 (20130101); B60K23/04 (20130101); F16H48/22 (20130101)

Field of Classification Search

CPC: F16H (48/22); F16H (48/20); F16H (48/08)

USPC: 475/231; 475/234; 475/235; 475/236

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1361895	12/1919	Nogrady	475/234	F16H 48/22
1750981	12/1929	Wildhaber	475/241	F16H 48/22
2431272	12/1946	Mynssen	475/241	F16H 48/08
2545601	12/1950	Brubaker	475/231	F16H 48/08
2923174	12/1959	Gleasman	74/650	F16H 48/22
3457807	12/1968	Altmann	475/240	F16H 48/08
3523467	12/1969	Shachter	475/240	F16H 48/08
3815443	12/1973	McAninch	475/235	F16H 48/22
6283889	12/2000	Bordner	N/A	N/A
2017/0299036	12/2016	Zhao et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2944082	12/2009	FR	F16H 48/22
H09-49560	12/1996	JP	N/A
2003-130181	12/2002	JP	N/A
WO-2011105917	12/2010	WO	B60K 17/3465

OTHER PUBLICATIONS

Extended European Search Report issued Feb. 13, 2025 in European Patent Application No. 24201250.8. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) The present application claims priority to Japanese Patent Application 2023-177746, filed Oct. 13, 2023, the entire contents of which are incorporated herein by reference.

FIELD

(2) A technique disclosed herein relates to a vehicle differential and a vehicle.

DESCRIPTION OF THE RELATED ART

(3) Conventionally, a differential having a differential limiting mechanism has been considered.

(4) For example, the following differential is disclosed in Patent Literature 1. The differential includes: differential case that is rotationally driven by drive power of an engine; a differential gear mechanism that distributes rotation of the differential case to wheel sides via a pair of side gears; a cone clutch that is formed between the differential case and a clutch member, is engaged by receiving a meshing reaction force of the side gear, and thereby limits differential movement of the differential gear mechanism; and a cam mechanism that is provided between the clutch member and each of the side gears, actuates by receiving the drive power, and thereby presses the cone clutch.

(5) The differential in Patent Literature 1 employs a helical spline as the cam mechanism.

CITATION LIST

Patent Literature

(6) [Patent Literature 1] JPH09-49560A

SUMMARY

(7) From a perspective of improving travel performance, it has been considered to differentiate a differential limiting force, which limits differential movement of right and left drive wheels, during acceleration from that during deceleration. The following is disclosed in Patent Literature 1. During acceleration of a vehicle, the cone clutch is pressed against the differential case by the meshing reaction force from the pinion gear to the side gear and an outward meshing thrust reaction force from the helical spline. Meanwhile, during deceleration (braking) of the vehicle, a force to press the cone clutch against the differential case is reduced by an inward meshing thrust reaction force from the helical spline.

(8) However, when examining the differential described in Patent Literature 1, it may be seen that counteraction of the helical spline was not taken into consideration in the differential described in Patent Literature 1. That is, in the differential described in Patent Literature 1, in addition to the above-described force, an inward reaction force is added to the side gear due to the counteraction of the helical spline during the acceleration of the vehicle. Since the inward reaction force added to the side gear is equal to the above-described meshing thrust reaction force, the force to press the cone clutch only includes the meshing reaction force from the pinion gear to the side gear.

Meanwhile, during the deceleration of the vehicle, in addition to the above-described force, an outward reaction force is added to the side gear due to the counteraction of the helical spline, the force to press the cone clutch only includes the meshing reaction force from the pinion gear to the side gear. Thus, in the differential described in Patent Literature 1, the differential limiting force hardly varies during the acceleration and the deceleration.

(9) It is also considered to employ electronic control in order to adjust the differential limiting force. However, complication of the configuration of the differential and a cost increase thereof are

inevitable.

(10) A technique disclosed herein has been made in view of such points and therefore provides a differential capable of adjusting a differential limiting force with a simple configuration.

(11) In order to address the issues described above, a first aspect of a technique disclosed herein is directed to a vehicle differential that is mounted on a vehicle and configured to include: a differential case that receives drive power of a drive source and rotates; a pair of side gears arranged in the differential case in a coaxial manner with a rotation axis of the differential case; a pinion gear that meshes with both of the paired side gears; and a differential limiting mechanism provided to at least one side in a rotation axis direction, in which the differential limiting mechanism has: a plurality of friction plates arranged on an opposite side to the pinion gear, with respect to each of the side gears, in the rotation axis direction; and a pressing member arranged on an opposite side to each of the side gears, with interposing the plurality of friction plates, in the rotation axis direction to hold the plurality of friction plates together with respective one of the side gears, in which each of the side gears located on the one side in the rotation axis direction has: a gear section that meshes with the pinion gear; and a cylindrical section that extends from a radially inner portion of the gear section with respect to the rotation axis toward an opposite side to the pinion gear and a cylindrical axis of which is coaxial with the rotation axis, and in which an outer circumferential portion of the cylindrical section meshes with an inner circumferential portion of the pressing member via a helical spline.

(12) With this configuration, when the helical spline is subjected to a force in a direction in which the pressing member separates from the friction plates, the force in the direction away from the friction plates is input to each of the side gears due to counteraction from the helical spline. This reduces a force to hold the plurality of friction plates and further reduces a friction force applied between the plurality of friction plates. As a result, a differential limiting force is reduced.

Meanwhile, when the helical spline is subjected to a force in a direction in which the pressing member approaches the friction plates, the force in the direction approaching the friction plates is also input to each of the side gears due to the counteraction from the helical spline. This increases the force to hold the plurality of friction plates and further increases the friction force applied between the plurality of friction plates. As a result, the differential limiting force is increased. The direction of the force applied to the helical spline is opposite during acceleration and deceleration. Thus, a magnitude of the differential limiting force can be changed during the acceleration and the deceleration. In addition, the magnitude of the differential limiting force can be adjusted by adjusting an angle of the spline tooth of the helical spline. Thus, the magnitude of the differential limiting force can be adjusted easily. Therefore, the differential limiting force can be adjusted with the simple configuration.

(13) In the first aspect, a second aspect of the technique disclosed herein is configured that some of the plurality of friction plates are spline-fitted to the pressing member and that the rest of the plurality of friction plates are fixed to the differential case.

(14) With this configuration, in the cylindrical section of each of the side gears, an area available for the helical spline can be enlarged as much as possible. As a result, even when the cylindrical section is reduced in length in the rotation axis direction, a sufficiently large force can be input to each of the side gears via the helical spline. Therefore, the differential can have a compact configuration.

(15) In the first aspect, a third aspect of the technique disclosed herein is configured that some of the plurality of friction plates are spline-fitted to the cylindrical section and that the rest of the plurality of friction plates are fixed to the differential case.

(16) With this configuration, some of the friction plates are integrated with the side gears. Thus, a relatively large thrust load can be input. This can increase a range of the adjustable differential limiting force as wide as possible.

(17) In the first aspect, a fourth aspect of the technique disclosed herein is configured that the

differential limiting mechanism further has a disc spring that inputs a force directed toward the pressing member side in the rotation axis direction to the plurality of friction plates and that the gear section has a spring housing section that is provided in a portion on the friction plate side in the rotation axis direction and is recessed to an opposite side to the friction plates in the rotation axis direction to house the disc spring.

(18) With this configuration, the disc spring can apply initial torque to the friction plates. By arranging the disc spring in the spring housing section, it is possible to suppress enlargement of the differential in the rotation axis direction, which is caused by the disc spring. In other words, the differential can have a compact configuration while a mechanism to apply the initial torque is employed. In addition, by housing the disc spring in the spring housing section, the initial torque can be input to the friction plates in an independent manner of a meshing reaction force between the pinion gear and the side gear and a force via the helical spline. As a result, a magnitude of the initial torque can be set appropriately.

(19) A fifth aspect of the technique disclosed herein is configured that the differential limiting mechanism is arranged on each side in the rotation axis direction.

(20) With this configuration, since differential movement of each of the side gears can be limited, differential limiting capability can be exerted appropriately.

(21) In any one of the first to fifth aspects, a sixth aspect of the technique disclosed herein is configured that the vehicle is a rear-wheel-drive or all-wheel-drive vehicle and that the sixth aspect of the technique disclosed herein is used for differential control of a rear wheel of the vehicle.

(22) In particular, in the sixth aspect, a seventh aspect of the technique disclosed herein is configured that the helical spline is formed with a spline tooth such that a force in a direction away from the friction plates is input from the helical spline to each of the side gears during acceleration of the vehicle while a force in a direction approaching the friction plates is input from the helical spline to each of the side gears during deceleration of the vehicle.

(23) In other words, from a perspective of straight-travel stability of the vehicle, it is requested to increase stability of the vehicle in a yaw direction. During the acceleration of the vehicle, a rear portion of the vehicle is lowered, and a load applied to the rear wheels is increased. Thus, the stability of the rear portion of the vehicle in the yaw direction is high. Meanwhile, during the deceleration of the vehicle, the rear portion of the vehicle is raised, and the load applied to the rear wheels is reduced. Thus, the stability of the rear portion of the vehicle in the yaw direction is reduced. For this reason, it is requested to improve the stability of the rear portion of the vehicle in the yaw direction by increasing the differential limiting force to be larger during the deceleration of the vehicle than during the acceleration of the vehicle. In the above configuration, since the force in the direction away from the friction plates is input to each of the side gears during the acceleration, the differential limiting force is reduced. Meanwhile, since the force in the direction approaching the friction plates is input to each of the side gears during the deceleration, the differential limiting force is increased. Therefore, the differential limiting force can be adjusted appropriately during the acceleration of the vehicle and during the deceleration of the vehicle.

(24) An eighth aspect of the technique disclosed herein is directed to a vehicle. More specifically, the vehicle includes: a front drive unit that rotationally drives a front wheel; and a rear drive unit that can rotationally drive a rear wheel independently of the front drive unit and includes the vehicle differential according to the seventh aspect.

(25) With this configuration, since the differential limiting force on the rear wheels can be adjusted appropriately during the acceleration of the vehicle and during the deceleration of the vehicle, it is possible to improve straight-travel stability of the vehicle.

ADVANTAGES

(26) As it has been described so far, according to the technique disclosed herein, the differential capable of adjusting the differential limiting force with the simple configuration can be provided.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic view of a vehicle having a differential according to a first embodiment.
- (2) FIG. 2 is a cross-sectional view of the differential.
- (3) FIG. 3 is an enlarged view of an area III in FIG. 2.
- (4) FIG. 4 is a schematic view illustrating a force input to a friction plate during acceleration.
- (5) FIG. 5 is a schematic view illustrating a force input to the friction plate during deceleration.
- (6) FIG. 6 is a cross-sectional view of a differential according to a second embodiment.

DETAILED DESCRIPTION

(7) Hereinafter, exemplary embodiments are described in detail with reference to the drawings. In the following description, “up”, “down”, “front”, “rear”, “right”, and “left” are respectively defined with “up”, “down”, “front”, “rear”, “right”, and “left” directions seen from an occupant in a vehicle 1 being references.

First Embodiment

Overall Configuration of Vehicle

(8) FIG. 1 illustrates the vehicle 1 having a rear differential 30 according to this first embodiment. The vehicle 1 is a vehicle that is an electric car. The vehicle 1 is a vehicle as an all-wheel-drive vehicle in which both of front wheels 2 and rear wheels 3 are rotationally driven. The vehicle 1 enables independent rotation of each of the front wheels 2 and the rear wheels 3. A front drive unit 10 for causing the front wheels 2 to rotate is arranged in a front portion of the vehicle 1, and a rear drive unit 20 for causing the rear wheels 3 to rotate is arranged in a rear portion of the vehicle 1. The vehicle 1 does not include a shaft, such as a propeller shaft, that transmits drive power in a vehicle front-rear direction.

(9) The front drive unit 10 includes a front drive motor 11, a front reduction drive 12, and a front differential 13. The front drive motor 11 is a drive source for causing the front wheels 2 to rotate. The rotation of the front drive motor 11 is decelerated by the front reduction drive 12, which is then transmitted to the front differential 13. The front differential 13 is coupled to the right and left front wheels 2 via a front driveshaft 14. The front differential 13 differentiates movement of the right and left front wheels 2 according to a travel state of the vehicle 1.

(10) The rear drive unit 20 has a rear drive motor 21, a rear reduction drive 22, and the rear differential 30. Arrangement of the rear drive unit 20 is symmetrical to arrangement of the front drive unit 10 in the front-rear direction. The rear drive motor 21 is a drive source for causing the rear wheels 3 to rotate. The rotation of the rear drive motor 21 is decelerated by the rear reduction drive 22, which is then transmitted to the rear differential 30. The rear differential 30 is coupled to the right and left rear wheels 3 via a rear driveshaft 24. The rear differential 30 differentiates movement of the right and left rear wheels 3 according to the travel state of the vehicle 1.

(11) In this embodiment, a configuration of the rear differential 30 is particularly devised. Thus, hereinafter, the configuration of the rear differential 30 is described in detail.

Rear Differential

(12) FIG. 2 schematically illustrates the rear differential 30. The rear differential 30 includes: a differential case 31; a pinion shaft 32 that is fixed to the differential case 31; a pair of pinion gears 33, each of which rotates about the pinion shaft 32; and a pair of side gears 34, each of which meshes with the pinion gears 33.

(13) The differential case 31 rotates when receiving the drive power of the rear drive motor 21. The differential case 31 rotates about a rotation axis X when receiving the drive power from the rear reduction drive 22 via a final driven gear. The rotation axis X extends linearly in a vehicle width direction. In the following description, unless otherwise specified, an “axial direction” means an extending direction of the rotation axis X, and a “radial direction” means an orthogonal direction to

the rotation axis X.

(14) The pinion shaft **32** extends in the orthogonal direction to the rotation axis X. A center axis C of the pinion shaft **32** passes the rotation axis X and is orthogonal to the rotation axis X. When the differential case **31** rotates, the pinion shaft **32** rotates about the rotation axis X together with the differential case **31**.

(15) Each of the pinion gears **33** is arranged in the differential case **31**. Each of the pinion gears **33** is attached to the pinion shaft **32** in a manner to be rotatable about the pinion shaft **32**. One of the pinion gears **33** is arranged on a first end side of the pinion shaft **32**, and the other of the pinion gears **33** is arranged on a second end side of the pinion shaft **32** across the rotation axis X. When the differential case **31** rotates, each of the pinion gears **33** rotates about the rotation axis X together with the pinion shaft **32**. A rotation radius of the one pinion gear **33** about the rotation axis X is equal to a rotation radius of the other pinion gear **33** about the rotation axis X. Each of the pinion gears **33** meshes with both of the paired side gears **34**. A washer **33a** is arranged between each of the pinion gears **33** and the differential case **31** in the radial direction.

(16) Each of the side gears **34** has a cylindrical shape. A cylindrical axis of each of the side gears **34** is coaxial with the rotation axis X. That is, in the differential case **31**, each of the side gears **34** is arranged to be coaxial with the rotation axis X. One of the side gears **34** and the other of the side gears **34** are arranged to be mirror-symmetrical about a plane that passes the center axis C and is orthogonal to the rotation axis X.

(17) Each of the side gears **34** has: a gear section **34a** that meshes with the pinion gears **33**; and a cylindrical section **34b** that extends from a radially inner portion of the gear section **34a** toward an opposite side from the pinion gears **33** in the axial direction (hereinafter referred to as an axially outer side). The rear driveshaft **24** is fastened to each of an inner circumferential surface of each of the gear sections **34a** and an inner circumferential surface of each of the cylindrical sections **34b**. A spline of a helical spline is formed on an outer circumferential surface of each of the cylindrical sections **34b**. The cylindrical section **34b** of the right side gear **34** has first inner spline teeth **45a** of a first helical spline **45**. The first inner spline teeth **45a** are formed over the substantially entire cylindrical section **34b** of the right side gear **34**. The cylindrical section **34b** of the left side gear **34** has second inner spline teeth **46a** of a second helical spline **46**. The second inner spline teeth **46a** are formed over the substantially entire cylindrical section **34b** of the left side gear **34**.

(18) As illustrated in FIGS. 2 and 3, the rear differential **30** includes a differential limiting mechanism **40** that applies a differential limiting force to limit the differential movement of the right and left rear wheels **3**. Even in such a situation where one of the right and left rear wheels **3** idles, the differential limiting mechanism **40** transmits the force to the side gear **34**, which is connected to the other rear wheel **3**, and thereby causes the other wheel **3** to rotate. The differential limiting mechanism **40** is arranged on each side in the axial direction. The right differential limiting mechanism **40** includes: a plurality of friction plates **43**; a first pressing member **41** that presses the friction plates **43** from the axially outer side; and a pair of disc springs **44**, each of which presses the friction plates **43** from the pinion gears **33** side in the axial direction (hereinafter referred to as an axially inner side). The left differential limiting mechanism **40** includes: a plurality of friction plates **43**; a second pressing member **42** that presses the friction plates **43** from the axially outer side; and a pair of disc springs **44**, each of which presses the friction plates **43** from the axially inner side. Each of the differential limiting mechanisms **40** is arranged in the differential case **31**.

(19) The plurality of friction plates **43** has first friction plates **43a** relatively located radially outward and second friction plates **43b** relatively located radially inward. The first friction plates **43a** and the second friction plates **43b** are alternately aligned in the axial direction.

(20) The first friction plates **43a** are fixed to the differential case **31** in a manner not to make relative rotation about the rotation axis X. The first friction plates **43a** rotate with the differential case **31** about the rotation axis X. The first friction plates **43a** can move in the axial direction.

(21) As illustrated in FIG. 3, of the second friction plates **43b**, a thickness of a particular second

friction plate **43c** located at the innermost position in the axial direction is greater than thicknesses of the other second friction plates **43b**. The thickness of each of the second friction plates **43b** other than the particular second friction plate **43c** is each equal to a thickness of each of the first friction plates **43a**. The second friction plates **43b** including the particular second friction plate **43c** are spline-fitted to the first pressing member **41** and the second pressing member **42**. The second friction plates **43b** can move in the axial direction.

(22) In the differential case **31**, the first pressing member **41** is arranged on an opposite side to the right side gear **34**, with interposing the right friction plates **43**, in the axial direction, that is, on the right side of the right friction plates **43**. The first pressing member **41** has a cylindrical shape, a cylindrical axis of which is coaxial with the rotation axis X. The first pressing member **41** is not fixed to the differential case **31** and can rotate relative to the differential case **31**. The first pressing member **41** has: a disc-shaped first pressing section **41a** that presses the friction plates **43**; a first inner cylindrical section **41b** that extends axially inward (leftward herein) from a radially inner portion of the first pressing section **41a**; and a first outer cylindrical section **41c** that extends axially outward (rightward herein) from the radially inner portion of the first pressing section **41a**.

(23) The first pressing section **41a** is in contact with the first friction plate **43a** located on the far-right side. The first pressing section **41a** holds the right friction plates **43** with the left side gear **34**. A first spacer **41d** is arranged between a right surface of the first pressing section **41a** and the differential case **31**. The first spacer **41d** abuts an inner surface of the differential case **31**. Due to the first spacer **41d**, the first pressing section **41a** hardly moves axially outward. Thus, the first pressing member **41** hardly moves axially outward. The term “hardly moves axially outward” includes a case of no relative movement at all.

(24) The first inner cylindrical section **41b** extends linearly in the axial direction. A left end portion of the first inner cylindrical section **41b** is located on the right side of the gear section **34a** of the right side gear **34**. The second friction plates **43b** including the particular second friction plate **43c** are each spline-fitted to a radially outward portion of the first inner cylindrical section **41b**.

(25) The first outer cylindrical section **41c** extends linearly in the axial direction. The first outer cylindrical section **41c** is formed in the differential case **31** and housed in a first recessed section that is recessed rightward.

(26) The first pressing member **41** has first outer spline teeth **45b** of the first helical spline **45** on an inner circumferential surface. The first outer spline teeth **45b** are formed over the entire inner circumferential surface of the first pressing member **41** in the axial direction.

(27) In the differential case **31**, the second pressing member **42** is arranged on an opposite side to the left side gear **34**, with interposing the left friction plates **43**, in the axial direction, that is, on the left side of the left friction plates **43**. The second pressing member **42** has a cylindrical shape, a cylindrical axis of which is coaxial with the rotation axis X. The second pressing member **42** is not fixed to the differential case **31** and can rotate relative to the differential case **31**. The second pressing member **42** has: a disc-shaped second pressing section **42a** that presses the friction plates **43**; a second inner cylindrical section **42b** that extends axially inward (rightward herein) from a radially inner portion of the second pressing section **42a**; and a second outer cylindrical section **42c** that extends axially outward (leftward herein) from the radially inner portion of the second pressing section **42a**.

(28) The second pressing section **42a** is in contact with the second friction plate **43b** located on the far-left side. The second pressing section **42a** holds the left friction plates **43** with the left side gear **34**. A second spacer **42d** is arranged between a right surface of the second pressing section **42a** and the differential case **31**. The second spacer **42d** abuts the inner surface of the differential case **31**. Due to the second spacer **42d**, the second pressing section **42a** hardly moves axially outward. Thus, the second pressing member **42** hardly moves axially outward. The term “hardly moves axially outward” includes the case of no relative movement at all.

(29) The second inner cylindrical section **42b** extends linearly in the axial direction. A right end

portion of the second inner cylindrical section **42b** is located on the left side of the gear section **34a** of the left side gear **34**. The second friction plates **43b** including the particular second friction plate **43c** are each spline-fitted to a radially outward portion of the second inner cylindrical section **42b**. (30) The second outer cylindrical section **42c** extends linearly in the axial direction. The second outer cylindrical section **42c** is formed in the differential case **31** and housed in a second recessed section that is recessed leftward. An axial length of the second outer cylindrical section **42c** is longer than an axial length of the first outer cylindrical section **41c**. A radial thickness of the second outer cylindrical section **42c** is less than a radial thickness of the first outer cylindrical section **41c**. An axial length of the second recessed section is longer than an axial length of the first recessed section. A radial length of the second recessed section is shorter than a radial length of the first recessed section.

(31) The second pressing member **42** has second outer spline teeth **46b** of the second helical spline **46** on an inner circumferential surface. The second outer spline teeth **46b** are formed over the entire inner circumferential surface of the second pressing member **42** in the axial direction.

(32) As illustrated in FIG. 2 and FIG. 3, each of the disc springs **44** is housed in a spring housing section **34c** formed in the respective gear section **34a** of the respective side gear **34**. Each of the spring housing sections **34c** is provided in an axially outer portion of the respective gear section **34a** and recessed axially inward. Each of the disc springs **44** presses the respective particular second friction plate **43c** axially outward.

Operation of Differential Limiting Mechanism

(33) The differential limiting mechanisms **40** adjust the differential limiting force by adjusting respective ones of the spline teeth **45a**, **45b**, **46a**, **46b** of the first helical spline **45** and the second helical spline **46**. In this first embodiment, each of the spline teeth **45a**, **45b**, **46a**, **46b** is adjusted in a manner to increase the differential limiting force during deceleration of the vehicle **1** while reducing the differential limiting force during acceleration of the vehicle **1**. Hereinafter, operation of the differential limiting mechanisms **40** is described with reference to FIG. 4 and FIG. 5. Since the right differential limiting mechanism **40** and the left differential limiting mechanism **40** are bilaterally symmetrical only in terms of a force transmission direction, the operation of the right differential limiting mechanism **40** is described in detail below, and the operation of the left differential limiting mechanism **40** is not described in detail. It is assumed that the differential case **31** rotates clockwise when seen from the right side during forward travel of the vehicle **1**. In addition, in the following description, it is assumed that the vehicle **1** travels straight and the pinion gears **33** do not rotate about the pinion shaft **32**.

(34) FIG. 4 schematically illustrates the force input to the friction plates **43** during the acceleration of the vehicle **1**. First, when the vehicle **1** travels forward, the pinion gear **33** rotates with the differential case **31** about the rotation axis X, and a meshing reaction force **F1** is thereby generated by meshing of the side gear **34** with the pinion gear **33**. The meshing reaction force **F1** is a force that is directed axially outward. In addition, initial torque **F2** is generated from the disc spring **44**. The initial torque **F2** is a force that presses the particular second friction plate **43c** axially outward, but also acts on the side gear **34**.

(35) During the acceleration of the vehicle **1**, the side gear **34** is subjected to rotational torque in the same direction as a rotational direction during the forward travel. At this time, the first pressing member **41** is subjected to a meshing thrust force **F3**, which is directed axially outward, via the first helical spline **45**. The first pressing member **41** does not move axially outward relative to the differential case **31**. Thus, even when the meshing thrust force **F3** is generated, the first pressing member **41** hardly moves away from the friction plates **43**. Meanwhile, the side gear **34** is subjected to a meshing thrust reaction force **F4** directed axially inward due to counteraction from the first helical spline **45**. A magnitude of the meshing thrust reaction force **F4** is the same as a magnitude of the meshing thrust force **F3**.

(36) The friction plates **43** are subjected to the meshing reaction force **F1** and the meshing thrust

reaction force F_4 from the side gear **34**. Thus, when the axially outer side is a positive side, and the axially inner side is a negative side, a force F_A of the side gear **34** to press the friction plates **43** during the acceleration is as follows.

(37) $F_A = F_1 - F_4$

(38) FIG. 5 schematically illustrates the force input to the friction plates **43** during the deceleration of the vehicle **1**. Since the vehicle **1** travels forward, the meshing reaction force F_1 is generated, similar to the time of the acceleration.

(39) During the deceleration of the vehicle **1**, the side gear **34** is subjected to rotational torque in an opposite direction from the rotational direction during the forward travel. At this time, the first pressing member **41** is subjected to a meshing thrust force F_5 , which is directed axially inward, via the first helical spline **45**. Meanwhile, the side gear **34** is subjected to a meshing thrust reaction force F_6 directed axially outward due to the counteraction from the first helical spline **45**. A magnitude of the meshing thrust reaction force F_6 is the same as the magnitude of the meshing thrust reaction force F_6 .

(40) The friction plates **43** are subjected to the meshing reaction force F_1 and the meshing thrust reaction force F_6 from the side gear **34**. Thus, when the axially outer side is the positive side, and the axially inner side is the negative side, a force F_C of the side gear **34** to press the friction plates **43** during the deceleration is as follows.

(41) $F_C = F_1 + F_6$

(42) As described above, during the acceleration of the vehicle **1**, the force of the side gear **34** to press the friction plates **43** is smaller than that during the deceleration of the vehicle **1**. Since the first pressing member **41** and the second pressing member **42** hardly move axially outward, the force of the side gear **34** to press the friction plates **43** is input as is to the friction plates **43**. When the force input to the friction plates **43** becomes small, a dynamic friction force between each of the first friction plates **43a** and respective one of the second friction plates **43b** becomes small. Thus, the differential limiting force becomes small. On the contrary, when the force input to the friction plates **43** becomes large, the dynamic friction force between each of the first friction plates **43a** and respective one of the second friction plates **43b** becomes large. Thus, the differential limiting force becomes large. Therefore, the differential limiting mechanism **40** increases the differential limiting force during the deceleration of the vehicle **1** while reducing the differential limiting force during the acceleration of the vehicle **1**.

(43) In the left differential limiting mechanism **40**, the spline teeth **46a**, **46b** of the second helical spline **46** are arranged bilaterally symmetrical to the spline teeth **45a**, **45b** of the first helical spline **45**, and thus the force transmission direction thereof is bilaterally symmetrical. Sizes and angles of the spline teeth **46a**, **46b** of the second helical spline **46** are the same as those of the spline teeth **45a**, **45b** of the first helical spline **45**. Meshing thrust forces and meshing thrust reaction forces generated by the second helical spline **46** are the same as the meshing thrust forces F_3 , F_5 and the meshing thrust reaction forces F_4 , F_6 generated by the first helical spline **45**. The term “same” described herein includes not only a case of strict agreement but also a case where there is a difference to the extent that they can be regarded as substantially the same.

Effects of First Embodiment

(44) In this first embodiment, the rear differential **30** includes the differential limiting mechanisms **40** each having: the plurality of the friction plates **43**, each of which is arranged on the axially outer side of each of the side gears **34**; and respective one of the first pressing member **41** and the second pressing member **42**, which has the cylindrical shape coaxial with the rotation axis X , is arranged on the opposite side to the side gear **34**, with interposing the plurality of the friction plates **43**, in the axial direction, and holds the plurality of the friction plates **43** with the side gear **34**. The pair of the side gears **34** each have: the gear section **34a** that meshes with the pinion gears **33**; and the cylindrical section **34b** that extends axially outward from the radially inner portion of the gear section **34a**, and the cylindrical axis of which is coaxial with the rotation axis X . The outer

circumferential portion of the cylindrical section **34b** of one of the side gears **34** meshes with the inner circumferential portion of the first pressing member **41** via the first helical spline **45**, and the outer circumferential portion of the cylindrical section **34b** of the other side gear **34** meshes with the inner circumferential portion of the second pressing member **42** via the second helical spline **46**. When the first pressing member **41** and the second pressing member **42** are subjected to the force directed axially outward via the first helical spline **45** and the second helical spline **46**, respectively, the force directed axially inward is input to the side gears **34** due to the counteraction from the first helical spline **45** and the second helical spline **46**. This reduces a force to hold the plurality of the friction plates **43** and further reduces the friction force applied between the plurality of the friction plates **43**. As a result, the differential limiting force is reduced. Meanwhile, when the first pressing member **41** and the second pressing member **42** are subjected to the force directed axially inward via the first helical spline **45** and the second helical spline **46**, respectively, the force directed axially outward is input to the side gears **34** due to the counteraction from the first helical spline **45** and the second helical spline **46**. This increases the force to hold the plurality of the friction plates **43** and further increases the friction force applied between the plurality of the friction plates **43**. As a result, the differential limiting force is increased. The direction of the force applied to each of the first helical spline **45** and the second helical spline **46** is opposite during the acceleration and the deceleration of the vehicle **1**. Thus, the differential limiting force can be changed during the acceleration and the deceleration of the vehicle **1**. In addition, the magnitude of the differential limiting force can be adjusted by adjusting the angles of the spline teeth **45a**, **45b** of the first helical spline **45** and the spline teeth **46a**, **46b** of the second helical spline **46**. Thus, the magnitude of the differential limiting force can be adjusted easily. Therefore, the differential limiting force can be adjusted with the simple configuration.

(45) In particular, in this first embodiment, in the rear differential **30**, the first helical spline **45** and the second helical spline **46** are respectively formed with the spline teeth **45a**, **45b**, **46a**, **46b** such that the meshing thrust reaction force directed axially inward is input to each of the side gears **34** during the acceleration of the vehicle **1** while the meshing thrust reaction force directed axially outward is input to each of the side gears **34** during the deceleration of the vehicle **1**.

(46) That is, in this first embodiment, a shaft that transmits the drive power in the vehicle front-rear direction, such as a propeller shaft, is not provided in the vehicle **1**. Conventionally, straight-travel stability of the vehicle is improved by increasing the differential limiting force with such a shaft and thereby increasing stability of a rear portion of the vehicle in a yaw direction. When such a shaft is not provided as in the vehicle **1**, another mechanism is required to increase the stability in the yaw direction and thereby improve the straight-travel stability. During the acceleration of the vehicle **1**, the rear portion of the vehicle **1** is lowered, and a load applied to each of the rear wheels **3** is increased. Thus, the stability of the rear portion of the vehicle **1** in the yaw direction is high. Meanwhile, during the deceleration of the vehicle **1**, the rear portion of the vehicle **1** is raised, and the load applied to each of the rear wheels **3** is reduced. Thus, the stability of the rear portion of the vehicle **1** in the yaw direction is reduced. For this reason, it is requested to improve the stability of the rear portion of the vehicle **1** in the yaw direction by increasing the differential limiting force to be larger during the deceleration of the vehicle **1** than during the acceleration of the vehicle **1**. In this first embodiment, during the acceleration, the meshing thrust reaction force directed axially inward is input to each of the side gears **34**, and thus the differential limiting force is reduced. Meanwhile, during the deceleration, the meshing thrust reaction force directed axially outward is input to each of the side gears **34**, and thus the differential limiting force is increased. Accordingly, the differential limiting force is larger during the deceleration of the vehicle **1** than during the acceleration of the vehicle **1**. Therefore, the straight-travel stability of the vehicle **1** can be improved.

(47) In this first embodiment, the second friction plates **43b** of the plurality of the friction plates **43** are spline-fitted to either one of the first pressing member **41** and the second pressing member **42**,

and the first friction plates **43a** of the plurality of the friction plates **43** are fixed to the differential case **31**. Thus, in the cylindrical section **34b** of each of the side gears **34**, an area available for respective one of the first inner spline teeth **45a** and the second inner spline teeth **46a** can be enlarged as much as possible. As a result, even when the cylindrical section **34b** is reduced in length in the rotation axis direction, the sufficiently large meshing thrust reaction force can be input to each of the side gears **34** via respective one of the first helical spline **45** and the second helical spline **46**. Therefore, the rear differential **30** can have a compact configuration.

(48) In this first embodiment, the pair of the disc springs **44** is further provided to respectively input the force directed axially outward to the plurality of the friction plates **43**, and each of the gear sections **34a** has the spring housing section **34c** that is provided in the axially outer portion, recessed axially inward, and respectively houses the disc spring **44**. The disc spring **44** can apply the initial torque to the friction plates **43**. By arranging the disc spring **44** in the spring housing section **34c**, it is possible to suppress enlargement of the rear differential **30** in the rotation axis direction, which is caused by the disc springs **44**. In other words, the rear differential **30** can have a compact configuration while a mechanism to apply the initial torque is employed. In addition, by housing the disc spring **44** in the spring housing section **34c**, the initial torque can be input to the friction plates **43** in an independent manner of the meshing reaction force **F1** between the pinion gear **33** and the side gear **34** and the meshing thrust reaction force via respective one of the first helical spline **45** and the second helical spline **46**. As a result, a magnitude of the initial torque can be set appropriately.

Second Embodiment

(49) Hereinafter, a second embodiment is described in detail with reference to the drawings. In the following description, components in common with the components in the first embodiment are denoted by the same reference signs, and the detailed description thereon is not made.

Differential Limiting Mechanism

(50) In this second embodiment, a configuration of a differential limiting mechanism **240** in a rear differential **230** differs from that in the first embodiment.

(51) As illustrated in FIG. 6, in this second embodiment, side gears **234** each have spline teeth **234d** for spline-fitting to the second friction plates **43b**. The second friction plates **43b** are fitted to the spline teeth **234d**. The second friction plates **43b** have the same thickness. Similar to the first embodiment, the first friction plates **43a** are fixed to the differential case **31** in the manner not to make the relative rotation about the rotation axis **X**. The first friction plates **43a** rotate with the differential case **31** about the rotation axis **X**. The first friction plates **43a** have the same thickness.

(52) First inner spline teeth **245a** of a first helical spline **245** are provided in an axially outer portion of a right cylindrical section **234b** from the spline teeth **234d**. Second inner spline teeth **246a** of a second helical spline **246** are provided in an axially outer portion of a left cylindrical section **234b** from the spline teeth **234d**.

(53) A first pressing member **241** is not provided with a first inner cylindrical section and has a first pressing section **241a** and a first outer cylindrical section **241c**. First outer spline teeth **245b** of the first helical spline **245** are formed over an entire inner circumferential surface of the first pressing member **241** in the axial direction.

(54) A second pressing member **242** is not provided with a second inner cylindrical section and has a second pressing section **242a** and a second outer cylindrical section **242c**. Second outer spline teeth **246b** of the second helical spline **246** are formed over an entire inner circumferential surface of the second pressing member **242** in the axial direction.

(55) The disc spring **44** is located on the radially outer side of the spline teeth **234d** in a gear section **234a** of each of the side gears **234**.

(56) Similar to the first embodiment, the first helical spline **245** and the second helical spline **246** are respectively formed with the spline teeth **245a**, **245b**, **246a**, **246b** such that the force directed axially inward is input to each of the side gears **234** from respective one of the first helical spline

245 and the second helical spline **246** during the acceleration of the vehicle **1** while the force directed axially outward is input to each of the side gears **234** from respective one of the first helical spline **245** and the second helical spline **246** during the deceleration of the vehicle **1**. In addition, in this second embodiment, the first helical spline **245** and the second helical spline **246** each have a multiple-start thread structure with two starts or more.

Effects of Second Embodiment

(57) Also, in this second embodiment, similar to the first embodiment, it is possible to change the force applied to the friction plates **43** during the acceleration and the deceleration of the vehicle by the first helical spline **245** and the second helical spline **246**. Therefore, the differential limiting force can be adjusted with the simple configuration.

(58) With this configuration, the second friction plates **43b** are integrated with the side gears **234**. Thus, the relatively large meshing thrust reaction force can be input. This can increase a range of the adjustable differential limiting force as wide as possible.

Other Embodiments

(59) The technique disclosed herein is not limited to that in the above-described embodiment and can be substituted with another technique within the scope that does not depart from the gist of the claims.

(60) In the first and second embodiments described above, the differential limiting mechanisms **40**, **240** are provided on each side in the rotation axis direction. However, the differential limiting mechanisms **40**, **240** are not limited thereto and may be provided on one side in the rotation axis direction, that is, only one of the right and left sides.

(61) In the first and second embodiments described above, the differential limiting mechanisms **40**, **240** are mounted on the rear differentials **30**, **230**, respectively. However, the technique disclosed herein is not limited thereto. A differential limiting mechanism may be mounted on the front differential **13**. In this case, contrary to the rear differentials **30**, **230**, each of the spline teeth of a first helical spline and a second helical spline are formed such that the force directed axially outward is input to each of the side gears **34**, **234** from respective one of the first helical spline and the second helical spline during the acceleration of the vehicle while the force directed axially inward is input to each of the side gears **34**, **234** from respective one of the first helical spline and the second helical spline during the deceleration of the vehicle.

(62) In the above-described first embodiment, each of the side gears **34** has the spring housing section **34c** for housing the disc spring **44**. However, the technique disclosed herein is not limited thereto. Each of the side gears **34** may not have the spring housing section **34c**, and the disc spring **44** may be arranged between the axially outer portion of the gear section **34a** in each of the side gears **34** and the friction plates **43**.

(63) In the above-described first embodiment, the second friction plates **43b** are spline-fitted to the first inner cylindrical section **41b** of the first pressing member **41** and the second inner cylindrical section **42b** of the second pressing member **42**. However, the technique disclosed herein is not limited thereto. Comb teeth may be formed on the first inner cylindrical section **41b** and the second inner cylindrical section **42b** to hold the second friction plates **43b** on the comb teeth.

(64) The above-described embodiments are merely illustrative, and thus the scope of the present disclosure should not be interpreted in a restrictive manner. The scope of the present disclosure is defined by the claims, and all modifications and changes falling within equivalents of the claims fall within the scope of the present disclosure.

INDUSTRIAL APPLICABILITY

(65) The technique disclosed herein is useful for a vehicle differential and a vehicle having the vehicle differential.

REFERENCE SIGNS LIST

(66) **1**: vehicle **2**: front wheel **3**: rear wheel **10**: front drive unit **20**: rear drive unit **21**: rear drive motor (drive source) **30**: rear differential **31**: differential case **33**: pinion gear **34**: side gear **34a**:

gear section **34b**: cylindrical section **34c**: spring housing section **40**: differential limiting mechanism **41**: first pressing member **42**: second pressing member **43**: friction plate **44**: disc spring **45**: first helical spline **45a**: first inner spline tooth **45b**: first outer spline tooth **46**: second helical spline **46a**: second inner spline tooth **46b**: second outer spline tooth **230**: rear differential **234**: side gear **234a**: gear section **234b**: cylindrical section **240**: differential limiting mechanism **245**: first helical spline **245a**: first inner spline tooth **245b**: first outer spline tooth **246**: second helical spline **246a**: second inner spline tooth **246b**: second outer spline tooth X: rotation axis

Claims

1. A vehicle differential mounted on a vehicle, the vehicle differential comprising: a differential case that receives drive power of a drive source and rotates; a pair of side gears arranged in the differential case in a coaxial manner with a rotation axis of the differential case; a pinion gear that meshes with both side gears of the pair of side gears; and a differential limiting mechanism provided to at least one side in a rotation axis direction, wherein: the differential limiting mechanism has: a plurality of friction plates arranged on an opposite side to the pinion gear, with respect to at least one of the side gears, in the rotation axis direction; and a pressing member arranged on an opposite side to the at least one of the side gears and interposing the plurality of friction plates therebetween, in the rotation axis direction and holding the plurality of friction plates together with the at least one of the side gears, each of the side gears located on the one side in the rotation axis direction has: a gear section that meshes with the pinion gear; and a cylindrical section that extends from a radially inner portion of the gear section with respect to the rotation axis toward an opposite side to the pinion gear and a cylindrical axis of which is coaxial with the rotation axis, and an outer circumferential portion of the cylindrical section meshes with an inner circumferential portion of the pressing member via a helical spline.
2. The vehicle differential according to claim 1, wherein: some of the plurality of friction plates are spline-fitted to the pressing member, and the rest of the plurality of friction plates are fixed to the differential case.
3. The vehicle differential according to claim 2, wherein the differential limiting mechanism further has a disc spring that inputs a force directed toward the pressing member side in the rotation axis direction to the plurality of friction plates, and the gear section has a spring housing section that is provided in a portion on the friction plate side in the rotation axis direction and is recessed to an opposite side to the friction plates in the rotation axis direction to house the disc spring.
4. The vehicle differential according to claim 3, wherein the differential limiting mechanism is arranged on each side in the rotation axis direction.
5. The vehicle differential according to claim 4, wherein: the vehicle is a rear-wheel-drive vehicle or an all-wheel-drive vehicle, and the vehicle differential is a differential control of a rear wheel of the vehicle.
6. The vehicle differential according to claim 5, wherein the helical spline is formed with a spline tooth such that a force in a direction away from the friction plates is input from the helical spline to each of the side gears during acceleration of the vehicle while a force in a direction approaching the friction plates is input from the helical spline to each of the side gears during deceleration of the vehicle.
7. A vehicle, comprising: a front drive unit that rotationally drives a front wheel; and a rear drive unit that rotationally drives a rear wheel independently of the front drive unit and includes the vehicle differential according to claim 6.
8. The vehicle differential according to claim 2, wherein the differential limiting mechanism is arranged on each side in the rotation axis direction.
9. The vehicle differential according to claim 2, wherein: the vehicle is a rear-wheel-drive vehicle or an all-wheel-drive vehicle, and the vehicle differential is a differential control of a rear wheel of

the vehicle.

10. The vehicle differential according to claim 1, wherein: some of the plurality of friction plates are spline-fitted to the cylindrical section, and the rest of the plurality of friction plates are fixed to the differential case.

11. The vehicle differential according to claim 10, wherein: the differential limiting mechanism further has a disc spring that inputs a force directed toward the pressing member side in the rotation axis direction to the plurality of friction plates, and the gear section has a spring housing section that is provided in a portion on the friction plate side in the rotation axis direction and is recessed to an opposite side to the friction plates in the rotation axis direction to house the disc spring.

12. The vehicle differential according to claim 10, wherein the differential limiting mechanism is arranged on each side in the rotation axis direction.

13. The vehicle differential according to claim 10, wherein: the vehicle is a rear-wheel-drive vehicle or an all-wheel-drive vehicle, and the vehicle differential is a differential control of a rear wheel of the vehicle.

14. The vehicle differential according to claim 1, wherein: the differential limiting mechanism further has a disc spring that inputs a force directed toward the pressing member side in the rotation axis direction to the plurality of friction plates, and the gear section has a spring housing section that is provided in a portion on the friction plate side in the rotation axis direction and is recessed to an opposite side to the friction plates in the rotation axis direction to house the disc spring.

15. The vehicle differential according to claim 14, wherein the differential limiting mechanism is arranged on each side in the rotation axis direction.

16. The vehicle differential according to claim 14, wherein: the vehicle is a rear-wheel-drive vehicle or an all-wheel-drive vehicle, and the vehicle differential is a differential control of a rear wheel of the vehicle.

17. The vehicle differential according to claim 1, wherein the differential limiting mechanism is arranged on each side in the rotation axis direction.

18. The vehicle differential according to claim 17, wherein: the vehicle is a rear-wheel-drive vehicle or an all-wheel-drive vehicle, and the vehicle differential is a differential control of a rear wheel of the vehicle.

19. The vehicle differential according to claim 1, wherein: the vehicle is a rear-wheel-drive vehicle or an all-wheel-drive vehicle, and the vehicle differential is a differential control of a rear wheel of the vehicle.

20. The vehicle differential according to claim 19, wherein the helical spline is formed with a spline tooth such that a force in a direction away from the friction plates is input from the helical spline to the at least one of the side gears during acceleration of the vehicle while a force in a direction approaching the friction plates is input from the helical spline to the at least one of the side gears during deceleration of the vehicle.
