

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409784
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Juarez Espinoza; Jose Nicolas et al.

Vehicle having load floor holder

Abstract

A vehicle cargo storage system configured to be located in a floor of a vehicle, the vehicle cargo storage system includes a compartment configured to extend into and below the floor of the vehicle, and a cover movable between a closed position covering the compartment and providing a load floor and an upright open position to expose the compartment. The system also includes a retractable load floor holder comprising a protrusion coupled with an interior of the vehicle, the load floor holder having at least one bias arm and a side first surface and a rear second surface, wherein when the cargo floor cover is configured to move with force from the closed position to the upright open position to allow the cargo floor cover to slide along the side first surface of the protrusion and depress the protrusion, and is supported in the upright open position by the rear second surface.

Inventors: Juarez Espinoza; Jose Nicolas (Cuajimalpa de Morelos, MX), Villacres Mesias; Diego Fabricio (Cuajimalpa, MX), Martinez Huesca; Raul Rafael (Atizapan de Zaragoza, MX), Moctezuma Zamudio; Mariana (Huixquilucan de Degollado, MX), Toriz Vega; Jose Luis (Metepic, MX)

Applicant: Ford Global Technologies, LLC (Dearborn, MI)

Family ID: 92801911

Assignee: Ford Global Technologies, LLC (Dearborn, MI)

Appl. No.: 18/131494

Filed: April 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240336203 A1	Oct. 10, 2024

Publication Classification

Int. Cl.: B60R5/04 (20060101)

U.S. Cl.:

CPC B60R5/04 (20130101);

Field of Classification Search

CPC: B60R (5/044); B60R (5/045)

USPC: 296/37.14

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5685592	12/1996	Heinz	N/A	N/A
6955511	12/2004	Preta	N/A	N/A
7503610	12/2008	Karagitz et al.	N/A	N/A
7661742	12/2009	Medlar	296/37.16	B60R 5/04
9315156	12/2015	Nedelman	N/A	N/A
10196008	12/2018	Ranka et al.	N/A	N/A
2002/0096900	12/2001	Moore	N/A	N/A
2004/0129852	12/2003	Giampavolo	N/A	N/A
2010/0078956	12/2009	Aebker	296/37.13	B60R 5/04
2016/0096479	12/2015	Nedelman	N/A	N/A
2020/0122643	12/2019	Loew et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10261393	12/2003	DE	N/A
102011010458	12/2010	DE	B60R 5/044
102016222982	12/2017	DE	B60R 13/013
102017006581	12/2018	DE	B60R 5/04
102021106973	12/2021	DE	B60R 13/011
1258396	12/1997	EP	N/A
2095997	12/2008	EP	B60R 5/045
2522550	12/2011	EP	B60R 5/044
4488121	12/2024	EP	B60R 13/013
2934873	12/2022	ES	B60R 5/04
2941253	12/2022	ES	B60R 13/013
2982591	12/2023	ES	B60R 5/044
2611619	12/1987	FR	B60R 5/045
200431629	12/2005	KR	B60R 5/044
20070049896	12/2006	KR	B60R 5/045
101610582	12/2015	KR	B60J 5/108
20180046185	12/2017	KR	B60J 5/108
20240061144	12/2023	KR	B60R 5/044

Primary Examiner: Fuller; Robert E

Attorney, Agent or Firm: Price Heneveld LLP

Background/Summary

FIELD OF THE DISCLOSURE

(1) The present disclosure generally relates to vehicle storage systems, and more particularly relates to a retractable load floor holder for a vehicle cargo storage system.

BACKGROUND OF THE DISCLOSURE

(2) Motor vehicles are commonly equipped with storage compartments for storing cargo. For example, the rear cargo area of a vehicle may include a hidden storage compartment that extends in a recessed area below the cargo floor and has a removable load floor cover. Quite often, a spare tire or other items may be stored within the rear cargo area storage compartment. It would be desirable to provide for a cargo storage system that allows efficient access to the storage compartment.

SUMMARY OF THE DISCLOSURE

(3) According to a first aspect of the present disclosure, a vehicle cargo storage system configured to be located in a floor of a vehicle is provided. The vehicle cargo storage system includes a compartment configured to extend into and below the floor of the vehicle, and a cover movable between a closed position covering the compartment and providing a load floor and an upright open position to expose the compartment. The system also includes a retractable load floor holder comprising a protrusion coupled with an interior of the vehicle, the load floor holder having at least one bias arm and a side first surface and a rear second surface, wherein when the cargo floor cover is configured to move with force from the closed position to the upright open position to allow the cargo floor cover to slide along the side first surface of the protrusion and depress the protrusion to a retracted position, and is supported in the upright open position by the rear second surface with the protrusion in an extended position.

(4) Embodiments of the first aspect of the present disclosure can include any one or a combination of the following features: the at least one bias arm provides a bias force without a separate spring; the load floor holder is connected to an interior trim panel of the vehicle, wherein the protrusion extends through an opening in the trim panel; the compartment is located in a rear end of the vehicle; the at least one bias arm comprises a pair of first bias arms; the load floor holder comprises a pair of first arms configured to pivot about a pivot point as the protrusion moves between the extended position and the retracted position; the protrusion further comprises a cylindrical rod for engaging a hook in the interior of the vehicle; a second plurality of parallel arms parallel to the pair of first arms; the holder comprises a flange for engaging the interior; the protrusion comprises a unitary protrusion; and the retractable load floor holder comprises first and second load floor holders.

(5) According to a second aspect of the present disclosure, a retractable load floor holder for use in a vehicle cargo storage system that is configured to be located in a floor of a vehicle is provided. The load floor holder includes a unitary protrusion coupled with an interior panel of the vehicle, the protrusion having a side first surface and a second rear surface, and at least one bias arm extending from the protrusion. The system also includes a supporting base configured to engage the interior panel in the vehicle, wherein the first side surface of the protrusion is configured to be engaged by a cargo floor cover and depressed to a retracted position by the cargo floor cover as the cargo floor cover is rotated towards an upright position and a rear surface is configured to hold the cargo floor

cover in the upright position with the protrusion in an extended position.

(6) Embodiments of the second aspect of the present disclosure can include any one or a combination of the following features: the at least one bias arms provide a bias force without a separate spring; the load floor holder is connected to an interior trim panel of the vehicle; the compartment is located in a rear end of the vehicle; the at least one bias arm comprises a pair of first bias arms; the load floor holder comprises a pair of first arms are configured to pivot about a pivot point as the protrusion moves between the first position and second position; the protrusion further comprises a cylindrical rod for engaging a hook in the panel of the vehicle; a second plurality of parallel arms parallel to the pair of first arms; and the holder comprises a flange for engaging the interior.

(7) These and other features, advantages, and objects of the present disclosure will be further understood and appreciated by those skilled in the art by reference to the following specification, claims, and appended drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In the drawings:

(2) FIG. 1 is a rear perspective view of a motor vehicle having a cargo storage system shown having a load floor cover in a stowed position in a rear cargo area, according to a first embodiment;

(3) FIG. 1A is a rear perspective view of the motor vehicle having the cargo storage system shown supported on a retractable load floor holder in an open load floor cover position;

(4) FIG. 2 is an enlarged view of section II of FIG. 1A illustrating the load floor holder in an extended position;

(5) FIG. 2A is a cross-sectional view taken through line IIA-IIA of FIG. 2;

(6) FIG. 3 is an enlarged perspective view of the load floor holder in a retracted position;

(7) FIG. 3A is a cross-sectional view taken through line IIIA-IIIA of FIG. 3;

(8) FIG. 4 is a perspective view of the load floor holder in the first extended position;

(9) FIG. 5 is an exploded of the load floor holder and trim panel;

(10) FIG. 6A is an enlarged view of a portion of the load floor cover in a first cover position relative to the extended load floor holder;

(11) FIG. 6B is an enlarged view of the load floor cover at a rotated angle relative to the extended load floor holder;

(12) FIG. 6C is an enlarged view of the load floor cover engaging and forcing the load floor holder to the retracted position; and

(13) FIG. 6D is an enlarged view of the load floor cover supported on the load floor holder in an open cover position.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

(14) Reference will now be made in detail to the present preferred embodiments of the disclosure, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numerals will be used throughout the drawings to refer to the same or like parts. In the drawings, the depicted structural elements are not to scale and certain components are enlarged relative to the other components for purposes of emphasis and understanding.

(15) As required, detailed embodiments of the present disclosure are disclosed herein; however, it is to be understood that the disclosed embodiments are merely exemplary of the disclosure that may be embodied in various and alternative forms. The figures are not necessarily to a detailed design; some schematics may be exaggerated or minimized to show function overview. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a representative basis for teaching one skilled in the art to variously employ the present

disclosure.

(16) For purposes of description herein, the terms “upper,” “lower,” “right,” “left,” “rear,” “front,” “vertical,” “horizontal,” and derivatives thereof shall relate to the concepts as oriented in FIG. 1. However, it is to be understood that the concepts may assume various alternative orientations, except where expressly specified to the contrary. It is also to be understood that the specific devices and processes illustrated in the attached drawings, and described in the following specification are simply exemplary embodiments of the inventive concepts defined in the appended claims. Hence, specific dimensions and other physical characteristics relating to the embodiments disclosed herein are not to be considered as limiting, unless the claims expressly state otherwise.

(17) The present illustrated embodiments reside primarily in combinations of method steps and apparatus components related to a vehicle cargo storage system and load floor holder. Accordingly, the apparatus components and method steps have been represented, where appropriate, by conventional symbols in the drawings, showing only those specific details that are pertinent to understanding the embodiments of the present disclosure so as not to obscure the disclosure with details that will be readily apparent to those of ordinary skill in the art having the benefit of the description herein. Further, like numerals in the description and drawings represent like elements.

(18) As used herein, the term “and/or,” when used in a list of two or more items, means that any one of the listed items can be employed by itself, or any combination of two or more of the listed items, can be employed. For example, if a composition is described as containing components A, B, and/or C, the composition can contain A alone; B alone; C alone; A and B in combination; A and C in combination; B and C in combination; or A, B, and C in combination.

(19) In this document, relational terms, such as first and second, top and bottom, and the like, are used solely to distinguish one entity or action from another entity or action, without necessarily requiring or implying any actual such relationship or order between such entities or actions. The terms “comprises,” “comprising,” or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. An element preceded by “comprises . . . a” does not, without more constraints, preclude the existence of additional identical elements in the process, method, article, or apparatus that comprises the element.

(20) As used herein, the term “about” means that amounts, sizes, formulations, parameters, and other quantities and characteristics are not and need not be exact, but may be approximate and/or larger or smaller, as desired, reflecting tolerances, conversion factors, rounding off, measurement error and the like, and other factors known to those of skill in the art. When the term “about” is used in describing a value or an end-point of a range, the disclosure should be understood to include the specific value or end-point referred to. Whether or not a numerical value or end-point of a range in the specification recites “about,” the numerical value or end-point of a range is intended to include two embodiments: one modified by “about,” and one not modified by “about.” It will be further understood that the end-points of each of the ranges are significant both in relation to the other end-point, and independently of the other end-point.

(21) The terms “substantial,” “substantially,” and variations thereof as used herein are intended to note that a described feature is equal or approximately equal to a value or description. For example, a “substantially planar” surface is intended to denote a surface that is planar or approximately planar. Moreover, “substantially” is intended to denote that two values are equal or approximately equal. In some embodiments, “substantially” may denote values within about 10% of each other, such as within about 5% of each other, or within about 2% of each other.

(22) As used herein the terms “the,” “a,” or “an,” mean “at least one,” and should not be limited to “only one” unless explicitly indicated to the contrary. Thus, for example, reference to “a component” includes embodiments having two or more such components unless the context clearly indicates otherwise.

(23) Referring to FIGS. 1 and 1A, a wheeled automotive or motor vehicle **10** is generally illustrated configured with passenger seating for transporting one or more passengers, such as a driver of the vehicle and additional passengers, and for further transporting one or more items as cargo onboard the motor vehicle **10**. The motor vehicle **10** has a vehicle body **12** that generally defines a cabin interior **14**. The cabin interior **14** may contain various features and trim components. The cabin interior **14** is shown having an arrangement of passenger seats **16** which may include a front row of passenger seats and one or more rear rows of passenger seats, each configured to seat a passenger. The motor vehicle **10** shown herein, in one example, is a sport utility vehicle (SUV), however, it should be appreciated that the motor vehicle **10** may otherwise be configured as a van, a sedan, a truck or other motor vehicle having a cargo area configurable to include a cargo storage system.

(24) The motor vehicle **10** is shown as a wheeled motor vehicle having a plurality of wheel assemblies **18** on a chassis which generally supports the body **12**. At the rear end of the motor vehicle **10** is a rear door liftgate **26** which is generally configured to pivot about upper hinges between an open door position shown in FIG. 1 which exposes the cabin interior **14** via a rear opening **24** and a closed door position which closes the rear opening **24**. Located proximate to the rear of the motor vehicle **10** forward of the liftgate **26** and rearward of the passenger seats **16** is a rear cargo area **20** which has a cargo floor **22**. The cargo floor **22** may include a load floor cover **32** positionable over a compartment **70**. One or more items of cargo may be located in the compartment **70** and on top of the load floor cover **32** in rear cargo area **20**.

(25) The motor vehicle **10** includes a cargo storage system **30** located in the rear cargo area **20**. The storage cargo system **30** has a load floor lid or cover **32** that is movable to convert between a closed position shown in FIG. 1 and an open position shown in FIG. 1A. In the open position, the load floor cover **32** is rotated upward to an upright and a somewhat substantially vertical position rearward of the seats **16** and exposes the compartment **70** that is configured extending into and below a floor **22** of the vehicle to form a cargo storage compartment. As such, the load floor cover **32** in the closed position covers the storage compartment **70** and provides a generally horizontal load floor that extends substantially flush with the cargo floor **22** to support cargo placed on top thereof.

(26) The vehicle cargo storage system **30** includes a retractable load floor holder **40** located on each of the opposite lateral sides of the cargo area **20**. As such, a first retractable load floor holder **40** is located on one lateral side of the cargo area **20** and a second retractable load floor holder **40** is located on an opposite lateral side of the cargo area **20**. Each of the retractable load floor holders **40** are located within trim panels **34** of the vehicle **10** defining interior walls proximate to the cargo area **20**.

(27) Each retractable load floor holder **40** includes a unitary protrusion coupled with an interior wall of the vehicle, which is shown as the trim panel **34**. Each retractable load floor holder **40** in an extended position extends laterally inwards from the trim panel **34** towards the cabin interior. The retractable load floor holder **40** is biased to the extended position towards the cabin interior **14** and has a first angled surface that extends laterally inward to allow the load floor cover **32** to be rotated upward and to engage the first angled surface of the retractable load floor holder **40** which forcibly depresses or retracts the retractable load floor holder **40** to a retracted position and allow the load floor cover **32** to forcibly pass by until the load floor cover **32** extends upright beyond the retractable load floor holder **40**. In this upright position, the load floor cover **32** may be retained in the upright position leaning against a rear surface of the retractable load floor holders **40** as seen in FIG. 1A. As such, the load floor cover **32** may be rotated upwards and held in the upright position on opposite lateral sides by the pair of load floor holders **40**. To move the load floor cover **32** back to the horizontal closed position, the load floor cover **32** may be raised by a user and repositioned on top of the chamber **70** or a user may depress the retractable load floor holders **40** to allow the load floor cover **32** to rotate back down to the horizontal closed position.

(28) Referring to FIGS. 2-3A, one of the retractable load floor holders **40** is illustrated located

within a trim panel **34** of the cabin interior **14** of the vehicle **10**. The retractable load floor holder **40** includes the unitary protrusion having a first contact surface **44** configured extending inward towards the cabin interior at an angle α that is configured to be engaged by the load floor cover **32** as the load floor cover **32** moves from the horizontal closed position to the upright open position. The angle α may be in a range between about 5° and 85° , or more particularly between about 25° and 75° , for example, such that the surface acts as a cam surface. The retractable load floor holder **40** has a second rear contact surface **46** configured at an angle β and configured to hold or retain the load floor cover **32** in the upright open position. Angle β may be in the range of about 75° to 105° , for example. The unitary protrusion has a rod **42** that provides a head at a first end which is shown located within a hook **38** provided in the trim panel **34**. As such, the rod **42** may pivot within the hook **38** as the retractable load floor holder **40** is moved between extended and retracted positions. At an end opposite of the rod **42** is a flange **48** which is configured to engage a rear surface of the trim panel **34** to provide an end of travel limit to the extended position of the retractable load floor holder **40** as seen in FIG. 2A.

(29) The retractable load floor holder **40** is shown in the extended position in FIGS. 2 and 2A extending radially inward into the cabin interior from the trim panel **34**. The load floor holder **40** has a pair of first bias arms **50**, each of which includes a rod **52** at one end engaged within the hook **38** of the trim panel **34** and has a pivot point **54** at the opposite end. The first bias arms **50** provide a bias force to force the retractable load floor holder **40** towards the extended position so that flange **48** engages the rear surface of the trim panel **34** as shown in FIG. 2A. It should be appreciated that the unitary protrusion of the load floor holder **40** may be made of a polymeric material, such as plastic, which is flexible and has memory sufficient to apply a bias force when the bias arms **50** are bent and hence loaded.

(30) When the retractable load floor cover **32** is lifted at the rear end of the vehicle and rotated upward and passes along in contact with the first contact surface **44**, the retractable load floor holder **40** is forced laterally outward from the extended position shown in FIGS. 2 and 2A towards the retracted position shown in FIGS. 3 and 3A. In the retracted position, the load floor cover **32** is able to pass fully vehicle forward of the retractable load floor holder **40**. When this occurs, the bias force from the first bias arms **50** causes the retractable load floor holder **40** to extend back to the extended position to block the load floor cover **32** from rotating downward and to hold the load floor cover **32** in the upright open position resting on the second contact surface **46**.

(31) Referring to FIGS. 4 and 5, the retractable load floor holder **40** is further illustrated having the unitary body configured to fit within a generally rectangular opening **36** within trim panel **34**. The retractable load floor holder **40** is shown having the first bias arms **50** engaged at first rods **52** within hooks **38** which are integrally formed within the trim panel **34**. The retractable load floor holder **40** further includes a pair of second arms **60** which are attached to rods **42** and rods **42** are interconnected through a rod **62**. Rod **62** is connected at the same time to angled surface **44** at its extreme. Each of the second arms **60** engages the inner wall of the trim panel **34** surrounding opening **36** and allows the first bias arms **50** to pivot or rotate relative thereto to provide the loaded bias force.

(32) Referring to FIGS. 6A-6D, movement of the load floor cover **32** from the closed position to the extended open position is shown. As seen in FIG. 6A, the load floor cover **32** may rest upon the floor **22** to cover the storage compartment **70**. To access the storage compartment **70**, a user may lift the rear end of the load floor cover **32** upward such that the load floor cover **32** rotates up and comes into initial engagement with the first contact surface **44** of the load floor holder **40** as seen in FIG. 6B. As the load floor cover **32** continues to be rotated further upward as seen in FIG. 6C, the load floor cover **32** engages and depresses the load floor holder **40** such that the load floor holder **40** moves to the retracted position as the load floor cover **32** passes by the angled first contact surface **44**. Once the load floor cover **32** passes completely past the load floor holder **40**, the load floor holder **40** is bias forced to extend back outwards into the extended position as seen in FIG. 6D

in which the load floor cover **32** may rest upon and be supported by the rear second contact surface **46**. In this position, the load floor cover **32** may further be supported on a vehicle forward side by a support wall **80**, which is shown provided in the trim panel **34**. It should be appreciated that the support wall **80** may further be provided by another structure, such as the rear surface of the seat **16**, according to other examples. In the open position, the load floor lid **32** allows for access to the storage compartment **70**. To cover the storage compartment **70**, a user may lift the load floor cover **32** and reposition it on top of floor over the storage compartment **70** or may depress the load floor holders **40** to allow the load floor cover **32** to rotate back down to the horizontal closed cover position.

(33) Accordingly, the vehicle cargo storage system **30** and retractable load floor holder advantageously provide for a load floor holder **40** on a vehicle **10** that is easy to install and requires few components and does not require extra springs. The vehicle cargo storage system **30** and retractable load floor holder **40** may be employed at various locations on the vehicle **10** to provide for a cargo storage system.

(34) It is to be understood that variations and modifications can be made on the aforementioned structure without departing from the concepts of the present disclosure, and further it is to be understood that such concepts are intended to be covered by the following claims unless these claims by their language expressly state otherwise.

Claims

1. A vehicle cargo storage system configured to be located in a floor of a vehicle, the vehicle cargo storage system comprising: a compartment configured to extend into and below the floor of the vehicle; a cover movable between a closed position covering the compartment and providing a load floor and an upright open position to expose the compartment; and a retractable load floor holder comprising a protrusion coupled with an interior of the vehicle, the load floor holder having at least one bias arm and a side first surface and a rear second surface, wherein when the cargo floor cover is configured to move with force from the closed position to the upright open position to allow the cargo floor cover to slide along the side first surface of the protrusion and depress the protrusion to a retracted position, and is supported in the upright open position by the rear second surface with the protrusion in an extended position, and wherein the at least one bias arm comprises a pair of first bias arms each configured to pivot about a pivot point as the protrusion moves between the extended position and the retracted position.
2. The vehicle cargo storage system of claim 1, wherein the at least one bias arm provides a bias force without a separate spring.
3. The vehicle cargo storage system of claim 1, wherein the load floor holder is connected to an interior trim panel of the vehicle, wherein the protrusion extends through an opening in the trim panel.
4. The vehicle cargo storage system of claim 3, wherein the compartment is located in a rear end of the vehicle.
5. The vehicle cargo storage system of claim 1, wherein the protrusion further comprises a cylindrical rod for engaging a hook in the interior of the vehicle.
6. The vehicle cargo storage system of claim 5, wherein the retractable load floor holder further comprises a second plurality of parallel arms parallel to the pair of first bias arms in the retracted position.
7. The vehicle cargo storage system of claim 1, wherein the holder comprises a flange for engaging the interior.
8. The vehicle cargo storage system of claim 1, wherein the protrusion comprises a unitary protrusion.
9. The vehicle cargo storage system of claim 1, wherein the retractable load floor holder comprises

first and second load floor holders.

10. A retractable load floor holder for use in a vehicle cargo storage system that is configured to be located in a floor of a vehicle, the load floor holder comprising: a unitary protrusion coupled with an interior panel of the vehicle, the protrusion having a side first surface and a second rear surface; at least one bias arm extending from the protrusion; and a supporting base configured to engage the interior panel in the vehicle, wherein the first side surface of the protrusion is configured to be engaged by a cargo floor cover and depressed to a retracted position by the cargo floor cover as the cargo floor cover is rotated towards an upright position and a rear surface is configured to hold the cargo floor cover in the upright position with the protrusion in an extended position, and wherein the at least one bias arm comprises a pair of first bias arms each configured to pivot about a pivot point as the protrusion moves between the extended position and the retracted position.

11. The retractable load floor holder of claim 10, wherein the at least one bias arms provide a bias force without a separate spring.

12. The retractable load floor holder of claim 10, wherein the load floor holder is connected to an interior trim panel of the vehicle.

13. The retractable load floor holder of claim 12, wherein the compartment is located in a rear end of the vehicle.

14. The retractable load floor holder of claim 10, wherein the protrusion further comprises a cylindrical rod for engaging a hook in the panel of the vehicle.

15. The retractable load floor holder of claim 14, wherein the retractable load floor holder further comprises a second plurality of parallel arms parallel to the pair of first bias arms in the retracted position.

16. The retractable load floor holder of claim 10, wherein the holder comprises a flange for engaging the interior.
