

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent

12409856

Kind Code

B2

Date of Patent

September 09, 2025

Inventor(s)

Jafari; Rouhollah Sayed et al.

### Autonomous driving system for creating a planned route based on messages displayed by road signs

#### Abstract

An autonomous driving system for a vehicle includes one or more controllers that execute instructions to monitor image data captured by one or more cameras. In response to detecting a road sign in the image data, the controllers interpret a message displayed by the road sign. The controllers classify the message conveyed by the road sign into a sign application class based on a time frame when the message conveyed by the road sign is applicable. In response to determining the message conveyed by the road sign is classified as a future traffic condition encountered by the vehicle, the controllers identify lane segments having one or more updated lane attributes that are impacted by the message of the road sign and determine a planned route based on the one or more updated lane attributes of the lane segments impacted by the message displayed by the road sign.

**Inventors:** Jafari; Rouhollah Sayed (Troy, MI), Esna Ashari Esfahani; Alireza (Novi, MI)

**Applicant:** GM Global Technology Operations LLC (Detroit, MI)

**Family ID:** 92802078

**Assignee:** GM GLOBAL TECHNOLOGY OPERATIONS LLC (Detroit, MI)

**Appl. No.:** 18/295967

**Filed:** April 05, 2023

#### Prior Publication Data

**Document Identifier**

**Publication Date**

US 20240336281 A1

Oct. 10, 2024

#### Publication Classification

**Int. Cl.:** H04W4/44 (20180101); B60W50/00 (20060101); B60W60/00 (20200101); G06V20/56 (20220101); G06V20/58 (20220101)

## U.S. Cl.:

CPC     **B60W60/0011** (20200201); **B60W50/0097** (20130101); **G06V20/582** (20220101); **G06V20/588** (20220101); **H04W4/44** (20180201); B60W2420/403 (20130101); B60W2552/53 (20200201); B60W2555/60 (20200201); B60W2556/35 (20200201); B60W2556/40 (20200201); B60W2556/45 (20200201)

## Field of Classification Search

**CPC:**     B60W (60/0011); B60W (50/0097); B60W (2552/53); B60W (2556/40); B60W (2556/45); B60W (2555/60); B60W (2556/35); B60W (2420/403); H04W (4/44); G06V (20/582); G06V (20/588)

**USPC:**    701/23

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name | U.S. Cl. | CPC             |
|--------------|-------------|---------------|----------|-----------------|
| 10339398     | 12/2018     | Fotta         | N/A      | G06V 20/582     |
| 2018/0232967 | 12/2017     | Segawa        | N/A      | H04N 7/188      |
| 2019/0212163 | 12/2018     | Li            | N/A      | G01C<br>21/3837 |
| 2021/0012527 | 12/2020     | Shu           | N/A      | G06N 3/045      |
| 2022/0402520 | 12/2021     | Hetang        | N/A      | G01C<br>21/3602 |

### FOREIGN PATENT DOCUMENTS

| Patent No. | Application Date | Country | CPC             |
|------------|------------------|---------|-----------------|
| 2017807    | 12/2008          | EP      | G08G<br>1/09626 |

### OTHER PUBLICATIONS

Sign Classification, Jul. 3, 2015, Transportation Engineering Agency (Year: 2015). cited by examiner

---

*Primary Examiner:* Burgess; Ramya P

*Attorney, Agent or Firm:* Vivacqua Crane, PLLC

---

## Background/Summary

### INTRODUCTION

(1) The present disclosure relates to an autonomous driving system for a vehicle that creates a planned route based on interpreting messages displayed by a road sign, where the interpreted messages are indicative of future traffic conditions encountered by the vehicle.

(2) An autonomous vehicle executes various tasks such as, but not limited to, perception,

localization, mapping, path planning, decision making, and motion control. For example, an autonomous vehicle may include perception sensors such as a camera for collecting image data regarding the environment surrounding the vehicle. The autonomous vehicle may include a road sign interpretation system that relies on various algorithms for interpreting the information conveyed by a road sign. For example, scene text recognition (STR) algorithms and natural language processing algorithms may be used for semantic understanding of the text displayed by the road sign. In another approach, the road sign interpretation system may rely on perceptual hashing techniques to interpret the information conveyed by a road sign.

(3) Some types of road signs do not include specific text or symbols containing explicit instructions for the road vehicles to follow at the present time. Instead, some road signs are informative and contain information informing users of various traffic conditions that may occur in the future. That is, in other words, many road signs do not indicate which maneuver a vehicle is currently supposed to execute, and instead provide information about upcoming traffic conditions the vehicle may encounter ahead. Some examples of providing information regarding upcoming traffic conditions include, but are not limited to, a road sign indicating construction is ahead, a road sign including a left turn only lane marking, or a road sign indicating a road closure ahead.

(4) Additionally, some road signs may convey instructions that are to be carried out until some condition is fulfilled, or until the vehicle encounters the next relevant road sign. For example, a speed limit road sign is applicable until the vehicle encounters the next speed limit road sign while traveling. It is to be appreciated that the route planner of an autonomous driving system determines a lane-level route for a host vehicle to follow based on the information extracted from the road signs. However, it may be challenging for the route planner to utilize the information extracted from road signs that include information regarding upcoming traffic conditions, or that convey instructions that are to be carried out until some condition is satisfied when determining a planned route.

(5) Thus, while autonomous vehicles achieve their intended purpose, there is a need in the art for an improved approach for utilizing information determined by a road sign interpretation system when determining a planned route.

## SUMMARY

(6) According to several aspects, an autonomous driving system for a vehicle is disclosed, and includes one or more cameras capturing image data of a surrounding environment of the vehicle, where the surrounding environment includes a road sign. The autonomous driving system also includes one or more controllers in electronic communication with the one or more cameras, where the one or more controllers receive perception data and map data. The one or more controllers execute instructions to monitor the image data captured by the one or more cameras. In response to detecting the road sign in the image data, the one or more controllers interpret a message displayed by the road sign. The one or more controllers classify the message conveyed by the road sign into a sign application class based on a time frame when the message conveyed by the road sign is applicable. In response to determining the message conveyed by the road sign is classified as a future traffic condition encountered by the vehicle, the controllers identify lane segments having one or more updated lane attributes that are impacted by the message of the road sign, where the lane segments are part of a lane graph structure in the map data. The one or more controllers determine a planned route based on the one or more updated lane attributes of the lane segments impacted by the message displayed by the road sign.

(7) In another aspect, the controllers classify the message conveyed by the road sign into one of three sign application classes.

(8) In yet another aspect, the three sign application classes include a present class, an application ahead, an application until expired class.

(9) In an aspect, the application until expired class is indicative of future traffic conditions the vehicle encounters.

- (10) In another aspect, identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes analyzing regulation-based standards.
- (11) In yet another aspect, the regulation-based standards include maintenance work zone traffic control guidelines.
- (12) In an aspect, identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes identifying the lane segments preceding an upcoming road feature within the lane graph structure potentially impacted by the message displayed by the road sign.
- (13) In another aspect, identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes analyzing image data captured by the one or more cameras.
- (14) In yet another aspect, the image data includes visual cues in a surrounding environment of the vehicle indicating a lane attribute of at least one of the lane segments is potentially impacted by the message displayed by the road sign.
- (15) In an aspect, identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes analyzing vehicle-to-everything (V2X) data.
- (16) In another aspect, identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes fusing together results from analyzing the regulation-based standards, the map data, the perception data, and the V2X data.
- (17) In yet another aspect, the one or more controllers execute instructions to identify a location within the lane graph structure where the message conveyed by the road sign expires.
- (18) In an aspect, the one or more updated lane attributes indicate one of the following: when a particular lane segment is mapped or unmapped in the lane graph structure, the presence of construction, when the particular lane segment is authorized to be included in a selected route, and when the particular lane segment includes the same direction of travel as the vehicle.
- (19) In another aspect, a method of determining a planned route by an autonomous driving system for a vehicle is disclosed. The method includes monitoring, by one or more controllers, image data captured by one or more cameras, where the one or more cameras capture the image data of a surrounding environment of the vehicle that includes a road sign. In response to detecting the road sign in the image data, the method includes interpreting a message displayed by the road sign. The method also includes classifying the message conveyed by the road sign into a sign application class based on a time frame when the message conveyed by the road sign is applicable. In response to determining the message conveyed by the road sign is classified as a future traffic condition encountered by the vehicle, the method includes identifying lane segments having one or more updated lane attributes that are impacted by the message of the road sign, where the lane segments are part of a lane graph structure in map data. Finally, the method includes determining a planned route based on the one or more updated lane attributes of the lane segments impacted by the message displayed by the road sign.
- (20) In another aspect, an autonomous driving system for a vehicle is disclosed, and includes one or more cameras capturing image data of a surrounding environment of the vehicle, where the surrounding environment includes a road sign. The autonomous driving system also includes one or more controllers in electronic communication with the one or more cameras, where the one or more controllers receive perception data and map data. The one or more controllers execute instructions to monitor the image data captured by the one or more cameras. In response to detecting the road sign in the image data, the controllers interpret a message displayed by the road sign. The one or more controllers classify the message conveyed by the road sign into one of three sign application classes based on a time frame when the message conveyed by the road sign is applicable, where the three sign application classes include a present class, an application ahead, and an application until expired class. In response to determining the message conveyed by the road sign is classified as

either the application ahead or the application until expired class, the one or more controllers identify lane segments having one or more updated lane attributes that are impacted by the message of the road sign, where the lane segments are part of a lane graph structure in the map data. The one or more controllers determine a planned route based on the one or more updated lane attributes of the lane segments impacted by the message displayed by the road sign.

(21) In another aspect, identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes analyzing regulation-based standards.

(22) In yet another aspect, identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes identifying the lane segments preceding an upcoming road feature within the lane graph structure potentially impacted by the message displayed by the road sign.

(23) In an aspect, identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes analyzing image data captured by one or more cameras in electronic communication with the one or more controllers.

(24) In another aspect, identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes analyzing V2X data.

(25) In yet another aspect, identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes fusing together results from analyzing the regulation-based standards, the map data, the perception data, and the V2X data.

(26) Further areas of applicability will become apparent from the description provided herein. It should be understood that the description and specific examples are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) The drawings described herein are for illustration purposes only and are not intended to limit the scope of the present disclosure in any way.

(2) FIG. 1 is a schematic diagram of a vehicle including the disclosed autonomous driving system including one or more controllers, according to an exemplary embodiment;

(3) FIG. 2 is a block diagram illustrating the software architecture for converting road sign messages into a planned route by the one or more controllers shown in FIG. 1, according to an exemplary embodiment;

(4) FIG. 3 is a block diagram of a map association module that is part of the one or more controllers shown in FIG. 2, according to an exemplary embodiment;

(5) FIG. 4 illustrates a lane graph structure including a plurality of lane segments, according to an exemplary embodiment; and

(6) FIG. 5 is a process flow diagram illustrating a method for determining a planned route by the autonomous driving system illustrated in FIG. 1, according to an exemplary embodiment.

### DETAILED DESCRIPTION

(7) The following description is merely exemplary in nature and is not intended to limit the present disclosure, application, or uses.

(8) Referring to FIG. 1, an exemplary autonomous driving system **10** for a vehicle **12** is illustrated. It is to be appreciated that the vehicle **12** may be any type of vehicle such as, but not limited to, a sedan, truck, sport utility vehicle, van, or motor home. In one embodiment, the autonomous driving system **10** is part of an automated driving system (ADS) or an advanced driver assistance system (ADAS) for assisting a driver with steering, braking, and/or accelerating. The autonomous driving system **10** includes one or more controllers **20** in electronic communication with a plurality of perception sensors **22**. The plurality of perception sensors **22** includes one or more cameras **30**, an

inertial measurement unit (IMU) **32**, a global positioning system (GPS) **34**, radar **36**, and LIDAR **38**, however, is to be appreciated that additional sensors may be used as well. The one or more controllers **20** are also in wireless communication with one or more communication networks **24** to obtain map data and a vehicle-to-everything (V2X) communication network **26** to obtain information regarding one or more entities surrounding the vehicle **12**. The entities surrounding the vehicle **12** include, for example, other vehicles, infrastructure, and electronic devices located in the surrounding environment **14**. Some examples of infrastructure include traffic control devices, and some examples of electronic devices include smartphones.

(9) The one or more controllers **20** receive image data of a surrounding environment **14** of the vehicle **12** from the one or more cameras **30**. The one or more controllers **20** monitor the image data captured by the one or more cameras **30** for a road sign **16** located in the surrounding environment **14** of the vehicle **12**. The road sign **16** is erected at the side of or above a road to provide information to the road users and displays one or more messages **18**. The message **18** includes text, symbols, or both text and symbols to convey information to the road users. In an embodiment, the road sign **16** is informative and conveys information about upcoming traffic conditions the vehicle **12** encounters ahead or in the future. In the example as shown in FIG. **1**, the road sign **16** displays a message **18** that is a symbol indicating the right lane ends ahead, however, it is to be appreciated that FIG. **1** is merely exemplary in nature.

(10) FIG. **2** is a block diagram of the software architecture for converting road sign messages into the planned route by the one or more controllers **20** shown in FIG. **1**. The one or more controllers **20** include a localization module **50**, a perception module **52**, a sign interpretation module **54**, a classification module **56**, a memory update module **58**, a map association module **60**, a lane attribute update module **62**, and a route planning module **64**. Referring to both FIGS. **1** and **2**, the localization module **50** receives data from the perception sensors **22** and the map data from the network **24** and determines a current position of the vehicle **12** relative to the surrounding environment **14** based on the data from the perception sensors **22** and the map data. The perception module **52** receives the data from the plurality of perception sensors **22** and determines perception data based on the data received from plurality of perception sensors **22**.

(11) The sign interpretation module **54** of the one or more controllers **20** monitors the image data captured by the one or more cameras **30** for the road sign **16** located in the surrounding environment **14** of the vehicle **12**. In response to detecting the road sign **16** in the image data, the sign interpretation module **54** of the one or more controllers **20** interprets the message **18** displayed by the road sign **16** based on any number of techniques such as, for example, scene text recognition (STR) algorithms and natural language processing algorithms for semantic understanding of the text displayed by the road sign or, in the alternative, perceptual hashing techniques.

(12) The sign interpretation module **54** of the one or more controllers **20** sends the interpreted message **18** of the road sign **16** to the classification module **56**. The classification module **56** classifies the interpreted message **18** conveyed by the road sign **16** into a sign application class based on a time frame when the message **18** conveyed by the road sign **16** is applicable. As explained below, the message **18** conveyed by the road sign **16** is analyzed to determine an impact on attributes associated with specific lane segments **92** (FIG. **4**) of a lane graph structure **90** that is part of the map data in response to determining the message **18** conveyed by the road sign **16** is classified as being applicable to future traffic conditions encountered by the vehicle **12**.

(13) In an embodiment, the interpreted message **18** conveyed by the road sign **16** is classified into one of three sign application classes. The first sign application class is referred to as a present class, where the interpreted message **18** conveyed by the road sign **16** is applied at the current location where the vehicle **12** (FIG. **1**) is located. Some examples of road signs **16** that are applied at the current location where the vehicle **12** is located include, but are not limited to, stop signs and yield signs. The second sign application class is referred to as an application ahead, where the interpreted message **18** conveyed by the road sign **16** is indicative of future traffic conditions and is applied at

a location ahead of the current location where the vehicle **12** is located. In other words, the application ahead indicates the interpreted message **18** conveyed by the road sign **16** is to be applied in the future. Some examples of road signs **16** that are executed at a location ahead of the current location include, but are not limited to, road signs indicating road construction is located ahead and road signs indicating a lane is about to end. The third sign application class is referred to as an application until expired class, where the interpreted message **18** conveyed by the road sign **16** is applied until a predetermined condition no longer applies. It is to be appreciated that the application until expired class is indicative of future traffic conditions the vehicle **12** encounters. Some examples of road signs **16** that are applied until expired include, but are not limited to, road signs indicating the speed limit and do not pass road signs.

(14) The memory update module **58** receives the interpreted message **18** of the road sign **16** and the sign application class associated with the interpreted message **18**, and filters and updates the interpreted messages **18** that are sent to the map association module **60** based on the sign application class. Specifically, the memory update module **58** filters interpreted messages **18** that are classified as the present class and removes them from consideration by the map association module **60**. In response to determining the interpreted message **18** of the road sign **16** is classified as either the application ahead or the application until expired class, the memory update module **58** sends the interpreted message **18** of the road sign **16** to the map association module **60** and stores the interpreted message **18** of the road sign **16** in memory of the one or more controllers **20**.

(15) The map association module **60** receives the map data from the network **24**, the V2X data received over the network **26**, the interpreted message **18** of the road sign **16**, the current location of the vehicle **12** from the localization module **50**, and perception data from the perception module **52**. FIG. 3 is a block diagram of the map association module **60** shown in FIG. 2. The map association module **60** includes a regulation-based block **70**, a map-based block **72**, a perception-based block **74**, a V2X block **76**, a lane association block **78**, and an expiration block **80**. As explained below, the regulation-based block **70**, the map-based block **72**, the perception-based block **74**, and the V2X block **76** of the map association module **60** identify one or more lane segments **92** (FIG. 4) having one or more updated lane attributes **96** that are impacted by the message **18** of the road sign **16** stored in the memory of the one or more controllers **20** based on various sources of information.

(16) Referring to FIG. 4, the lane attributes **96** refer to characteristics of a particular lane segment **92**. In one non-limiting embodiment the lane attributes **96** indicate characteristics such as, for example, when a particular lane segment **92** is mapped or unmapped in the lane graph structure **90**, the presence of construction, when the particular lane segment **92** is authorized to be included in the selected route generated by the route planning module **64**, and when the particular lane segment **92** includes the same direction of travel as the vehicle **12**, however, it is to be appreciated that different or additional lane attributes may be included as well. In the example as shown in FIG. 4, the lane attribute **96** indicates the characteristics for lane segment 5, where the lane graph structure **90** illustrates lane segments 1-11. FIG. 4 illustrates four lane attributes **96A-96D**, where a "0" denotes an absence of the specific lane attribute **96** and a "1" denotes the presence of the specific lane attribute **96**. In the example as shown, the "0" for the lane attribute **96A** indicates the lane segment 5 is mapped in the lane graph structure **90**, the "1" for lane attribute **96B** indicates the presence of construction, the "0" for lane attribute **96C** indicates lane segment 5 is authorized to be on a selected route determined by the route planning module **64**, and the "0" for lane attribute **96D** indicates the direction of travel of lane segment 5 is the same as the vehicle **12**. FIG. 4 also illustrates three road signs **16A**, **16B**, and **16C**, where the first road sign **16A** includes the message "Road work ahead", the second road sign **16B** includes the message "Left lane closed ahead", and the third road sign **16C** includes the message "End road work".

(17) Referring to both FIGS. 3 and 4, the regulation-based block **70** of the map association module **60** provides information to identify one or more lane segments **92** having a lane attribute **96**

potentially impacted by the message **18** of the road sign **16** based on analyzing regulation-based standards. In an embodiment, the regulation-based standards include maintenance work zone traffic control guidelines, which dictate a construction distance measured between the road sign **16A** that indicates the presence of the construction site **98** and the location of the construction site **98**. It is to be appreciated that other types of regulation-based standards that indicate a set of rules that regulate the location where the road signs **16** are installed may be used as well. For example, other regulation-based standards may indicate the distance measured between a road sign and an intersection (e.g., a road sign displaying the message “right lane must turn right” is installed at a specific distance from an intersection). The maintenance work zone traffic control guidelines stipulate the construction distance measured between the first road sign **16A** informing the road users of the construction site **98** and the location of the construction site **98**, and in one non-limiting example may range from about 0.5 to about 1 mile (0.8 to 1.61 kilometers). In the present example, the regulation-based block **70** of the map association module **60** identifies the lane segments **92** located within the construction distance from the first road sign **16A**, which may include lane segments **3**, **4**, and **5**. As explained below, the lane association block **78** fuses together the output from the regulation-based block **70**, the map-based block **72**, the perception-based block **74**, and the V2X block **76** to identify the specific lane segments **92** having one or more lane attributes **96** that are impacted by the message **18** of the road sign **16** stored in the memory of the one or more controllers **20**.

(18) Referring to FIG. 3, the map-based block **72** of the map association module **60** identifies one or more lane segments having a lane attribute **96** potentially impacted by the message **18** of the road sign **16** based on analyzing the map data received from the network **24** (FIG. 1). For example, if the message **18** displayed by the road sign **16** displays “Right lane must turn right”, then the map-based block **72** analyzes the map data to identify the lane segments **92** preceding an upcoming road feature within the lane graph structure **90** potentially impacted by the message **18** displayed by the road sign **16**. Some examples of upcoming road features include, but are not limited to, exits, intersections, roundabouts, or parking locations. In the example as shown in FIG. 4, the upcoming road feature is a right exit, and the map-based block **72** would identify lane segment **6**, which precedes a right exit, as the lane segment **92** potentially impacted by the message “Right lane must turn right”.

(19) Referring to FIG. 3, the perception-based block **74** of the map association module **60** identifies one or more lane segments **92** having a lane attribute **96** potentially impacted by the message **18** displayed by the road sign **16** based on analyzing the perception data collected by the plurality of perception sensors **22** (FIG. 1). Specifically, the perception-based block operates by identifying clues that may aid in specifying where the message **18** displayed by the road sign **16** is applied. In an embodiment, the perception-based block **74** analyzes the image data captured by the one or more cameras **30** (FIG. 1), where the image data includes visual cues in the surrounding environment **14** of the vehicle **12** that indicate a lane attribute **96** of at least one of the lane segments **92** is potentially impacted by the message **18** displayed by the road sign **16**. In the example as shown in FIG. 4, the image data captured by the one or more cameras **30** indicate road construction cones **100** located at lane segment **5**. Furthermore, the image data also indicates traffic merging in lane segment **2** to avoid the road construction cones **100** located in lane segment **5**. Also, the image data include the message **18** displayed by the second road sign **16B** (i.e., “Left lane closed ahead”).

(20) Finally, the V2X block **76** of the map association module **60** identifies one or more lane segments **92** having a lane attribute **96** potentially impacted by the message **18** displayed by the road sign **16** based on analyzing V2X data received over the network **26** (FIG. 1). In the example as shown in FIG. 4, the V2X data indicates that surrounding vehicles report the location of the construction site **98**. For example, in one embodiment, the V2X data indicates the distance measured between the vehicle **12** (FIG. 1) and the construction site **98** is about 0.7 miles (1.13



kilometers), which includes lane segments **3**, **4** and **5**.

(21) The lane association block **78** of the map association module **60** fuses together the output from the regulation-based block **70**, the map-based block **72**, the perception-based block **74**, and the V2X block **76** to identify the lane segments **92** having one or more updated lane attributes **96** that are impacted by the message **18** of the road sign **16** stored in the memory of the one or more controllers **20**. In the example as shown in FIGS. **3** and **4**, the regulation-based block **70** of the map association module **60** identifies lane segments **3**, **4**, and **5** as being potentially impacted, and the perception-based block **74** and the V2X block **76** both indicate lane segment **5** as being potentially impacted. Therefore, in the present example, the lane association block **78** identifies lane segment **5** as having one or more updated lane attributes **96** impacted by the message **18** displayed by the road sign **16**. The lane association block **78** of the map association module **60** then transmits the lane segments **92** having one or more updated lane attributes **96** that are impacted by the message **18** to the lane attribute update module **62**.

(22) The expiration block **80** of the map association module **60** monitors the output from the regulation-based block **70**, the map-based block **72**, the perception-based block **74**, and the V2X block **76** to identify a location within the lane graph structure **90** where the message **18** of the road sign **16** stored in the memory of the one or more controllers **20** is no longer applicable or expires. In the example as shown in FIG. **4**, the expiration block **80** of the map association module **60** determines the message **18** displayed by the road sign **16A** (road work ahead) expires after lane segment **5**. This is because the perception data indicates the third road sign **16C** includes the message “End road work”. The perception data also indicates that the road construction cones **100** end after lane segment **5**. Furthermore, the perception data also indicates that traffic is present on road segment **8**. In response to determining the message **18** displayed by the road sign **16A** is no longer applicable, the expiration block **80** sends a notification to the memory update module **58** to remove the message **18** of the road sign **16A** from memory of the one or more controllers **20**.

(23) Referring to FIGS. **2** and **4**, the lane attribute update module **62** of the one or more controllers **20** receives the lane segments **92** having one or more updated lane attributes **96** that are impacted by the message **18** from the map association module **60**. The lane attribute update module **62** updates the lane attributes associated with the message **18** conveyed by road sign **16** for the lane segments **92** received from the map association module **60**. For example, in the embodiment shown in FIG. **4**, the lane attribute **96B** associated with construction status on lane segment **5** is updated to **1**.

(24) The route planning module **64** determines a planned route the vehicle **12** follows based on the lane segments **92** having one or more updated lane attributes **96** that are impacted by the message **18**. Specifically, in an embodiment, the planned route is a lane-level path the vehicle **12** follows. The route planning module **64** may include or exclude the lane segments **92** that are impacted by the message **18** displayed by the road sign **16** when determining the planned route. For example, in the embodiment as shown in FIG. **4**, the route planning module **64** may determine the planned route the vehicle **12** follows by avoiding travel along lane segment **5**. As another example, if the message **18** displayed by the road sign **16** reads “Right lane must turn right” but the planned route includes having the vehicle **12** travel in a straight direction along a road, then the route planning module **64** may include lane segment **6** (FIG. **4**), which precedes a right exit, when determining the planned route for the vehicle **12**. In response to determining the message **18** displayed by the road sign **16** is no longer applicable, the road sign **16** may be removed from the memory of the one or more controllers **20**. In the example as shown in FIG. **4**, once the road sign **16C** (End road work) is detected and the vehicle **12** passes the construction site **98**, the road sign **16C** is removed from the memory of the one or more controllers **20**. As another example, if the message **18** states “Right lane must turn right”, the road sign **18** will be removed from the memory as vehicle **12** passes an exit lane (lane segment **9**).

(25) FIG. **5** is an exemplary process flow diagram illustrating a method **200** for determining the

planned route the vehicle **12** follows based on the lane segments **92** that are impacted by the message **18** displayed by the road sign **16**. Referring generally to FIGS. **1-5**, the method **200** may begin at decision block **202**. In decision block **202**, the sign interpretation module **54** of the one or more controllers **20** continues to monitor the image data captured by the one or more cameras **30** for the road sign **16** located in the surrounding environment **14** of the vehicle **12** until detecting a road sign **16** in the image data. The method **200** may then proceed to block **204**.

(26) In block **204**, in response to detecting the road sign **16** in the image data, the sign interpretation module **54** of the one or more controllers **20** interpret the message **18** displayed by the road sign **16**. The method **200** may then proceed to block **206**.

(27) In block **206**, the classification module **56** classifies the message **18** conveyed by the road sign **16** into a sign application class based on a time frame when the message **18** conveyed by the road sign **16** is applicable. The method **200** may then proceed to block **208**.

(28) In block **208**, the memory update module **58** filters interpreted messages **18** that are classified as the present class and removes them from consideration by the map association module **60**. In response to determining the interpreted message **18** of the road sign **16** is classified as either the application ahead or the application until expired class, the memory update module **58** sends the interpreted message **18** of the road sign **16** to the map association module **60** and stores the interpreted message **18** of the road sign **16** in memory of the one or more controllers **20**. The method **200** may then proceed to block **210**.

(29) In block **210**, in response to determining the message **18** conveyed by the road sign **16** is classified as a future traffic condition encountered by the vehicle **12**, the map association module **60** identifies the lane segments **92**

(30) (FIG. **4**) having one or more updated lane attributes **96** impacted by the message **18** of the road sign **16**. The lane association block **78** of the map association module **60** fuses together the results from analyzing the regulation-based standards, the map data, the perception data, and the V2X data to identify the lane segments **92** having one or more lane attributes **96** impacted by the message **18** of the road sign **16**. The method **200** may then proceed to block **212**.

(31) In block **212**, the expiration block **80** of the map association module **60** continues to monitor the results from analyzing the regulation-based standards, the map data, the perception data, and the V2X data to identify a location within the lane graph structure **90** where the message **18** of the road sign **16** stored in the memory of the one or more controllers **20** expires. The method **200** may then proceed to decision block **214**.

(32) In decision block **214**, if the message **18** of road sign **16** is determined to be expired, then the method **200** proceeds to block **216**, where the road sign **16** stored in the memory of the one or more controllers **20** is removed. The method **200** may then terminate. Referring to decision block **214**, in response to determining the lane segments **92** identified by the map association module **60** are affected by the road sign **16** saved in the memory of the one or more controllers **20**, the method **200** proceeds to block **218**. In block **218**, the lane attribute update module **62** may then update the lane attributes associated with the message **18** displayed by the road sign **16** for the lane segments **92**, which are then sent to the route planning module **64**. The method **200** may proceed to block **220**.

(33) In block **220**, the route planning module **64** determines the planned route based on the lane segments **92** having one or more updated lane attributes **96** that are impacted by the message **18**. The method **200** may then terminate.

(34) Referring generally to the figures, the disclosed autonomous driving system provides various technical effects and benefits. Specifically, the disclosure provides an approach for utilizing information collected while interpreting road signs when determining a planned route for an autonomous vehicle. In particular, the autonomous driving system utilizes messages displayed by road signs that are classified as future traffic conditions encountered by the vehicle when determining the planned route for automated driving.

(35) The controllers may refer to, or be part of an electronic circuit, a combinational logic circuit, a

field programmable gate array (FPGA), a processor (shared, dedicated, or group) that executes code, or a combination of some or all of the above, such as in a system-on-chip. Additionally, the controllers may be microprocessor-based such as a computer having at least one processor, memory (RAM and/or ROM), and associated input and output buses. The processor may operate under the control of an operating system that resides in memory. The operating system may manage computer resources so that computer program code embodied as one or more computer software applications, such as an application residing in memory, may have instructions executed by the processor. In an alternative embodiment, the processor may execute the application directly, in which case the operating system may be omitted.

(36) The description of the present disclosure is merely exemplary in nature and variations that do not depart from the gist of the present disclosure are intended to be within the scope of the present disclosure. Such variations are not to be regarded as a departure from the spirit and scope of the present disclosure.

## Claims

1. An autonomous driving system for a vehicle, comprising: one or more cameras capturing image data of a surrounding environment of the vehicle, wherein the surrounding environment includes a road sign; and one or more controllers in electronic communication with the one or more cameras, wherein the one or more controllers receive perception data and map data, and wherein the one or more controllers execute instructions to: monitor the image data captured by the one or more cameras; in response to detecting the road sign in the image data, interpret a message displayed by the road sign; classify the message conveyed by the road sign into a sign application class based on a time frame when the message conveyed by the road sign is applicable, wherein the sign application class includes a present class, an application ahead class, an application until expired class, and wherein the present class applies the message conveyed by the road sign at a current location where the vehicle is located, the application ahead class is indicative of future traffic conditions and is applied at a location ahead of the current location where the vehicle is located, and the application until expired class is indicative of future traffic conditions the vehicle encounters; in response to determining the message conveyed by the road sign is classified as the present class, filter and remove the message from consideration; in response to determining the message conveyed by the road sign is classified as either the application ahead class or the application until expired class encountered by the vehicle, identify lane segments having one or more updated lane attributes that are impacted by the message of the road sign, wherein the lane segments are part of a lane graph structure in the map data; determine a planned route based on the one or more updated lane attributes of the lane segments impacted by the message displayed by the road sign; and follow, by the vehicle, the planned route determined by the autonomous driving system.

2. The autonomous driving system of claim 1, wherein identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes analyzing regulation-based standards.

3. The autonomous driving system of claim 2, wherein the regulation-based standards include maintenance work zone traffic control guidelines.

4. The autonomous driving system of claim 2, wherein identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes: identifying the lane segments preceding an upcoming road feature within the lane graph structure potentially impacted by the message displayed by the road sign.

5. The autonomous driving system of claim 2, wherein identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes: analyzing image data captured by the one or more cameras.

6. The autonomous driving system of claim 5, wherein the image data includes visual cues in a surrounding environment of the vehicle indicating a lane attribute of at least one of the lane segments is potentially impacted by the message displayed by the road sign.
7. The autonomous driving system of claim 5, wherein identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes analyzing vehicle-to-everything (V2X) data.
8. The autonomous driving system of claim 7, wherein identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes: fusing together results from analyzing the regulation-based standards, the map data, the perception data, and the V2X data.
9. The autonomous driving system of claim 5, wherein the one or more controllers execute instructions to: identify a location within the lane graph structure where the message conveyed by the road sign expires.
10. The autonomous driving system of claim 1, wherein the one or more updated lane attributes indicate one of the following: when a particular lane segment is mapped or unmapped in the lane graph structure, the presence of construction, when the particular lane segment is authorized to be included in a selected route, and when the particular lane segment includes the same direction of travel as the vehicle.
11. A method of determining a planned route by an autonomous driving system for a vehicle, the method comprising: monitoring, by one or more controllers, image data captured by one or more cameras, wherein the one or more cameras capture the image data of a surrounding environment of the vehicle that includes a road sign; in response to detecting the road sign in the image data, interpreting a message displayed by the road sign; classifying the message conveyed by the road sign into a sign application class based on a time frame when the message conveyed by the road sign is applicable, wherein the sign application class includes a present class, an application ahead class, an application until expired class, and wherein the present class applies the message conveyed by the road sign at a current location where the vehicle is located, the application ahead class is indicative of future traffic conditions and is applied at a location ahead of the current location where the vehicle is located, and the application until expired class is indicative of future traffic conditions the vehicle encounters; in response to determining the message conveyed by the road sign is classified as the present class, filtering and removing the message from consideration; in response to determining the message conveyed by the road sign is classified as either the application ahead class or the application until expired class encountered by the vehicle, identifying lane segments having one or more updated lane attributes that are impacted by the message of the road sign, wherein the lane segments are part of a lane graph structure in map data; determining a planned route based on the one or more updated lane attributes of the lane segments impacted by the message displayed by the road sign; and following, by the vehicle, the planned route determined by the autonomous driving system.
12. An autonomous driving system for a vehicle, comprising: one or more cameras capturing image data of a surrounding environment of the vehicle, wherein the surrounding environment includes a road sign; and one or more controllers in electronic communication with the one or more cameras, wherein the one or more controllers receive perception data and map data, and wherein the one or more controllers execute instructions to: monitor the image data captured by the one or more cameras; in response to detecting the road sign in the image data, interpret a message displayed by the road sign; classify the message conveyed by the road sign into one of three sign application classes based on a time frame when the message conveyed by the road sign is applicable, wherein the three sign application classes include a present class, an application ahead class, and an application until expired class, and wherein the present class applies the message conveyed by the road sign at a current location where the vehicle is located, the application ahead class is indicative of future traffic conditions and is applied at a location ahead of the current location where the

vehicle is located, and the application until expired class is indicative of future traffic conditions the vehicle encounters; in response to determining the message conveyed by the road sign is classified as the present class, filter and remove the message from consideration; in response to determining the message conveyed by the road sign is classified as either the application ahead or the application until expired class, identify lane segments having one or more updated lane attributes that are impacted by the message of the road sign, wherein the lane segments are part of a lane graph structure in the map data and the one or more updated lane attributes indicate one of the following: when a particular lane segment is mapped or unmapped in the lane graph structure, the presence of construction, when the particular lane segment is authorized to be included in a selected route, and when the particular lane segment includes the same direction of travel as the vehicle; determine a planned route based on the one or more updated lane attributes of the lane segments impacted by the message displayed by the road sign; and follow, by the vehicle, the planned route determined by the autonomous driving system.

13. The autonomous driving system of claim 12, wherein identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes analyzing regulation-based standards.

14. The autonomous driving system of claim 13, wherein identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes: identifying the lane segments preceding an upcoming road feature within the lane graph structure potentially impacted by the message displayed by the road sign.

15. The autonomous driving system of claim 14, wherein identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes: analyzing image data captured by one or more cameras in electronic communication with the one or more controllers.

16. The autonomous driving system of claim 15, wherein identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes analyzing V2X data.

17. The autonomous driving system of claim 16, wherein identifying the lane segments having the one or more updated lane attributes impacted by the message displayed by the road sign includes: fusing together results from analyzing the regulation-based standards, the map data, the perception data, and the V2X data.

---