

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410615
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Kelly; Scot Ryan

Extendable beam coupler

Abstract

A system for traversing an opening of a construction element the system including a elongated housing with two extendable elements configured to reside at least partially within the housing. The extendable elements may extend beyond the housing and may include flanges or ledges which may engage the ends of a construction element, which may be a wall, and thus allow the system to traverse the opening of a construction element, such as a window or door. A coupler may be utilized to connect to a more than one elongated housing element to provide for traversal across even larger openings. The system may allow a user to easily manipulate the system to fit a plurality of openings and reuse the system a countless number of times.

Inventors:	Kelly; Scot Ryan (Huntsville, UT)
Applicant:	Quick Headers, LLC (Ogden, UT)
Family ID:	92636085
Assignee:	Quick Headers, LLC (Ogden, UT)
Appl. No.:	18/117985
Filed:	March 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240301694 A1	Sep. 12, 2024

Publication Classification

Int. Cl.: E04C3/04 (20060101); E04C3/02 (20060101)

U.S. Cl.:

CPC **E04C3/04** (20130101); E04C2003/023 (20130101); E04C2003/0417 (20130101)

Field of Classification Search

CPC: E04C (3/04); E04C (3/005); E04C (2003/023); E04C (2003/0413); E04C (2003/0417);
E04C (2003/0465); E04C (2003/0473); E04G (11/54); E04G (11/56)

USPC: 52/204.2; 52/217; 52/632

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2796158	12/1956	Miles et al.	N/A	N/A
2949656	12/1959	Pleitgen et al.	N/A	N/A
2974762	12/1960	Hunnebeck	N/A	N/A
3124223	12/1963	Kisovec	52/261	E04G 11/56
3325957	12/1966	Joist	N/A	N/A
4121804	12/1977	O'Leary	N/A	N/A
4248024	12/1980	Dahlstrom	N/A	N/A
5459967	12/1994	Bodtker	N/A	N/A
7383665	12/2007	Frobosilo	N/A	N/A
7546718	12/2008	Vasta	52/645	E04G 21/1841
8261509	12/2011	Harkin	N/A	N/A
9103108	12/2014	Lin	N/A	N/A
11078667	12/2020	Kelly	N/A	E04C 3/07
2002/0074915	12/2001	Shih	N/A	N/A
2003/0093959	12/2002	Couture	N/A	N/A
2003/0213204	12/2002	Belanger	52/645	E04B 2/7457
2006/0010809	12/2005	Lafreniere	N/A	N/A
2007/0089374	12/2006	Vasta	52/204.2	E04C 3/07
2017/0073970	12/2016	Weber	N/A	N/A
2017/0159284	12/2016	Getz	N/A	N/A
2019/0048589	12/2018	Kelly	N/A	E04C 3/07
2020/0385988	12/2019	Kelly	N/A	E04C 3/005
2022/0018131	12/2021	Sessler	N/A	E04B 2/76

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
118007940	12/2023	CN	N/A
580600	12/1932	DE	N/A
840435	12/1948	DE	N/A
29516293	12/1994	DE	N/A
855048	12/1959	GB	N/A
2481908	12/2011	GB	E04B 5/12
20040021432	12/2003	KR	N/A
2003102321	12/2002	WO	N/A
WO-2004111361	12/2003	WO	E04C 3/005

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application incorporates by reference U.S. patent application Ser. No. 15/672,143 entitled EXTENDABLE BEAM filed Aug. 8, 2017, now U.S. Pat. No. 10,280,618.

TECHNICAL FIELD

(2) This disclosure relates generally to an extendable beam, methods, and systems for masonry or construction use in spanning and carrying a load of an opening. These systems relate more specifically to the use of a single beam over two vertical supports to create an opening, such as a window or doorway or other architectural element.

RELATED ART

(3) In masonry, forms are often used to create windows, doorways or openings. These forms can be called many different things such as frames, bucks, headers, girders, joists, and the like. These forms are often made of simple wood (e.g., 2×4s or 2×6s) and built to (hopefully) fit within the space needed. Many times the wood frames are not the right size and have to be cut, fit, worked, and reworked until the proper dimensions of the frame is made. After the frame is constructed, a mason or other construction worker may begin building the next layer of block over the frame, the frame maintaining the opening.

(4) These frames are costly and are typically limited to a one-time single use because of the opening size. Often installation and removal of these frames requires block repair and can interrupt a mason's job. A wood frame may also leave rough finishings and limit access through the opening while the frame is in place. Further, wood frames are not considered a very environmentally sensitive (or “green”) practice.

(5) Other devices include lintels. These lintels are supported by other support beams made of wood or metal that extend from the base of an opening to the lintel. These lintels may also include a single extendable portion that slides from a single side of the lintel so that the lintel may be used for different size openings. In one instance a lintel may include a first fixed shoulder that sits on one wall then a second extendable shoulder that sits on a different wall. The lintel rests on the two walls over an opening. These devices are only intended to telescope from a single side and may allow the lintel to nearly double its size.

SUMMARY

(6) This disclosure, at least in one aspect, relates to a system or device with a longitudinal housing, which may be comprised of steel, a steel alloy, other metals or alloys, or a strong structure capable of holding significant weight (i.e., carbon fiber). The housing may be elongated with a U-shaped or C-shaped cross-section. The housing may hold, or may be capable of encompassing, at least one extendable member. The at least one extendable member may be two extendable members that each extend from the housing in opposite directions.

(7) The housing may be forged, bent, milled, extruded or the like from a single piece of metal and may be forged with multiple bends (which bends may be 90°). The housing may also be welded with multiple pieces of metal at 90° angles or bends (or nearly 90° angles or bends) as well. The housing may include a first longitudinal wall that extends the length of the housing, a pair of second longitudinal walls that may be perpendicular to the first longitudinal wall and extend the length of the housing. A pair of third longitudinal walls, or pair of lips, that may be perpendicular to the pair of second longitudinal walls. The pair of lips may extend at least partially toward a

longitudinal axis of the housing and the pair of lips may be parallel or close to parallel to the first longitudinal wall. At least one cross support post may extend between the pair of lips across a void in the housing securing the one lip to the second lip. The cross support post may be welded, forged or the like.

(8) The system may comprise multiple configurations. In a first configuration the two extendable members may reside entirely within the housing. The two extendable members may be held within the housing by the pair of lips of the housing. Alternatively the two extendable members may be held by at least one support member which may be welded inside the housing. The at least one support member may be a plurality of support members. The plurality of support members may be secured, welded, formed, etc. to the pair of second longitudinal walls. The plurality of support members may be positioned opposite one another on the pair of second longitudinal walls. The plurality of support members may extend longitudinally at least partially along the pair of second longitudinal walls.

(9) Alternatively, a separate retention element may be used to maintain the two extendable members. For instance, apertures may be milled, premanufactured, or drilled into lateral, or side, walls of the housing and allow for passage of a pin or rod. A slot may also be milled, ore premanufactured, into the side walls of the extendable members. Such slots may allow for extension of the extendable members within a range to prevent the complete withdrawal of the extension member from the housing.

(10) The extendable members may be similar in shape and size and may be interchangeable. The extendable members may be forged or welded, and are separate from the housing. The extendable members may be substantially rectangular in shape and from one perspective may resemble a tray or open top box. Each extendable member may comprise a longitudinal axis, a first wall, a pair of second walls opposite each other, which may be parallel to each other, extending from the first wall at a 90° angle, and a pair of third walls opposite each other, and which may be parallel to each other, extending from the first wall at a 90° angle and connected to the pair of second walls.

(11) The pair of second walls may be different lengths extending from the first wall. The distal wall of the pair of second walls, may be shorter in length than the proximal wall. The proximal wall may be longer and may engage the plurality of support members of the housing to act as a stop such that the extendable members may not extend out of the housing beyond a predetermined or predesignated distance or amount. An extendable member flange, or tab, may extend distally from the distal wall of the pair of second walls. The extendable flange may be configured to engage a wall or support for the system to rest on.

(12) The pair of third walls may be substantially parallel and may be substantially the same length and width. The pair of third walls may provide a slide or guide to glide along the plurality of support members while the extendable members are manipulated at different positions relative to the housing.

(13) A second configuration may be both extendable members extending beyond the housing exposing each flange of each extendable member to engage the construction element (e.g., walls or supports) that traverses an opening of the construction element. In a third configuration at least one of the extendable members may extend at least partially beyond the housing, exposing at least one flange from the extendable member to engage a wall or support of the construction while the other extendable member only protrudes from the housing far enough to expose a flange to engage the construction element.

(14) Additionally, the extendable member may further include variable flanges extending from distal ends of the extendable members. Different angles of flanges with different depths are considered and may be utilized for different angles of intersecting walls.

(15) Disclosed systems may also include a coupler to couple, connect, or daisy-chain multiple housings and extendable members together. Such coupling allows the systems to traverse large openings of a structure. In a first configuration, the coupler may be substantially rectangular and

linear. In a second configuration, the coupler may include an angle, such as a 90° angle, allowing the coupler and the housings to traverse non-linear openings and/or corners of structures.

(16) The system may comprise or resemble a lintel or header and may be configured to traverse an opening of a structure, such as a door or window for a building that is being constructed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In the drawings:

- (2) FIG. 1 illustrates a side view of a system in a second configuration with a housing and two extendable members extended from the housing;
- (3) FIG. 2 illustrates a side view of the system of FIG. 1 in a first configuration with the two extendable members retracted within the housing;
- (4) FIG. 3 illustrates a bottom view of the system of FIG. 1 with a first extendable member and a second extendable member in the second configuration;
- (5) FIG. 4 illustrates a bottom perspective view of the system of FIG. 1 with a first extendable member and a second extendable member in the first configuration;
- (6) FIG. 5 illustrates a top view of the system of FIG. 1 in the second configuration;
- (7) FIG. 6 illustrates a top view of the system of FIG. 1 in the first configuration;
- (8) FIG. 7 illustrates a bottom perspective view of the system of FIG. 1 with a first extendable member and a second extendable member in the second configuration;
- (9) FIG. 8 illustrates a bottom perspective view of the system of FIG. 1 with a first extendable member and a second extendable member in the first configuration;
- (10) FIG. 9 illustrates the system of FIG. 1 traversing an opening of a construction element;
- (11) FIG. 10 illustrates a perspective view separate embodiment of the system of FIG. 1 with a pin, extendable members with slots and a window, with one extendable member at least partially extended;
- (12) FIG. 11 illustrates a perspective view of the system of FIG. 10 with two extendable members without slots within the housing;
- (13) FIG. 12 illustrates a perspective view of the system of FIG. 11 with the extendable members removed from the housing;
- (14) FIG. 13 illustrates a side view of the system of FIG. 11;
- (15) FIG. 14 illustrates a magnified partial perspective view of the system of FIG. 11;
- (16) FIG. 15 illustrates a perspective view of the housing of FIG. 10;
- (17) FIG. 16 illustrates a bottom view of the housing of FIG. 10;
- (18) FIG. 17 illustrates a lateral side view of the housing of FIG. 10;
- (19) FIG. 18 illustrates a longitudinal side view of the housing of FIG. 10;
- (20) FIG. 19 illustrates a perspective view of an alternate embodiment of an extendable member with slots and an angled flange;
- (21) FIG. 20 illustrates a bottom view of the extendable member of FIG. 19;
- (22) FIG. 21 illustrates a longitudinal side view of the extendable member of FIG. 19;
- (23) FIG. 22 illustrates a lateral side view of the extendable member of FIG. 19;
- (24) FIG. 23 illustrates a perspective view of an alternate embodiment of an extendable member with slots and with a different angled flange;
- (25) FIG. 24 illustrates a bottom view of the extendable member of FIG. 23;
- (26) FIG. 25 illustrates a longitudinal side view of the extendable member of FIG. 23;
- (27) FIG. 26 illustrates a lateral side view of the extendable member of FIG. 23;
- (28) FIG. 27 illustrates a perspective view of an alternate embodiment of an extendable member with slots and with a different angled flange;

(29) FIG. 28 illustrates a bottom view of the extendable member of FIG. 27;
(30) FIG. 29 illustrates a longitudinal side view of the extendable member of FIG. 27;
(31) FIG. 30 illustrates a lateral side view of the extendable member of FIG. 27;
(32) FIG. 31 illustrates a perspective view of an alternate embodiment of an extendable member without slots, but with an angled flange similar to FIG. 19;
(33) FIG. 32 illustrates a bottom view of the extendable member of FIG. 31;
(34) FIG. 33 illustrates a longitudinal side view of the extendable member of FIG. 31;
(35) FIG. 34 illustrates a lateral side view of the extendable member of FIG. 31;
(36) FIG. 35 illustrates a perspective view of an alternate embodiment of an extendable member without slots, but with an angled flange similar to FIG. 23;
(37) FIG. 36 illustrates a bottom view of the extendable member of FIG. 35;
(38) FIG. 37 illustrates a longitudinal side view of the extendable member of FIG. 35;
(39) FIG. 38 illustrates a lateral side view of the extendable member of FIG. 35;
(40) FIG. 39 illustrates a perspective view of an alternate embodiment of an extendable member without slots, but with an angled flange similar to FIG. 27;
(41) FIG. 40 illustrates a bottom view of the extendable member of FIG. 39;
(42) FIG. 41 illustrates a longitudinal side view of the extendable member of FIG. 39;
(43) FIG. 42 illustrates a lateral side view of the extendable member of FIG. 39;
(44) FIG. 43 illustrates a top view of another embodiment of an extendable member according to the present disclosure;
(45) FIG. 44 illustrates a side view of the extendable member of FIG. 43;
(46) FIG. 45 illustrates a top, unfolded view of the extendable member of FIG. 43;
(47) FIG. 46 illustrates an end view of the extendable member of FIG. 43;
(48) FIG. 47 illustrates a plan view and FIG. 48 illustrates a side view of another embodiment of a distal tip for an extendable member according to the present disclosure;
(49) FIG. 49 illustrates a top view of the extendable member of FIG. 43 including the distal tip of FIGS. 47 and 48;
(50) FIG. 50 illustrates a perspective view and FIG. 51 illustrates a side view of the extendable member of FIG. 49;
(51) FIG. 52 illustrates a perspective view of another embodiment of a housing according to the present disclosure;
(52) FIG. 53 illustrates a side view and FIG. 54 illustrates a top view of the housing of FIG. 52;
(53) FIG. 55 illustrates an end view of the housing of FIG. 52;
(54) FIG. 56 illustrates another side view of the housing of FIG. 52;
(55) FIG. 57 illustrates a top, unfolded view of the housing of FIG. 52;
(56) FIG. 58 illustrates an end view of the housing of FIG. 52;
(57) FIG. 59 illustrates another embodiment of a system in a second configuration with the housing of FIG. 52 and two extendable members of FIG. 45 partially extended from the housing;
(58) FIG. 60 illustrates a side view and FIG. 61 illustrates a top view of the system of FIG. 56;
(59) FIG. 62 illustrates an end view of the system of FIG. 59;
(60) FIG. 63 illustrates one embodiment of a coupler according to the present disclosure;
(61) FIG. 64 illustrates a top, unfolded view of the coupler of FIG. 63;
(62) FIG. 65 illustrates an end view of the coupler of FIG. 63;
(63) FIG. 66 illustrates another embodiment of a system including two housings of FIG. 51 each having the extendable member of FIG. 45 joined together by the coupler of FIG. 63; and
(64) FIG. 67 illustrates a side view of the system of FIG. 66.

DETAILED DESCRIPTION

(65) FIGS. 1 and 2 illustrate side views of at least one embodiment of device or system 10 which may be a horizontal support member, a lintel, a beam or the like. In the industry these systems may be referred to as “bucks” or “headers.” Other references to the system 10 may be a “frame” as well.

The system **10** may include a housing **12** which may be a single piece of metal, often steel, that is forged into a U-shaped or C-shaped configuration. The housing **12** may be manipulated with bends in the housing for optimum use by a mason (for purposes of this disclosure a “mason” may be a construction worker, mason, brick layer, stone layer, block layer or similar). The housing **12** may be a longitudinal member which may be substantially rectangular in shape from a plurality of views. A longitudinal axis **14** may extend the length of the housing (see, e.g., FIG. 3).

(66) The housing **12** may include a first wall **16**, which may be substantially planar, extending a length and a width of the housing **12**. The first wall **16** may be substantially flat and configured to allow other flat elements (i.e. bricks, blocks, etc.) to easily reside on the first wall **16**. The first wall **16** may include bends or curves toward each width end of the first wall **16**. A pair of second walls **18, 18'** may extend from the first wall **16**, or the bends of the first wall **16**, in a direction substantially perpendicular to the first wall **16**. Extending from the pair of second walls **18, 18'** are a pair of third walls **20, 20'** that may extend from separate bends in the second walls **18, 18'**. The pair of third walls **20, 20'** may extend toward each other and the longitudinal axis **14**, or midline, of the longitudinal housing **12**. A channel **25** may be positioned between the pair of third walls **20, 20'** and run the length of the housing **12**. The third walls **20, 20'** may be substantially parallel to the first wall **16**. The channel **25**, or passage or void, may run the length of the housing. A cross-sectional shape of the housing **12** may resemble a C-shape or U-shape.

(67) The housing **12** may include a first opening **24** toward one end of the housing **12** and a second opening **26** toward a second, opposing end of the housing **12** with the channel **25** running from the first opening **24** to the second opening **26**.

(68) The housing **12** may be comprised of a single piece of metal or steel, and may be forged of a single piece of metal. The single piece of metal can be forged with the bends in the walls as described earlier, which allows for greater strength of the housing **12** rather than welding the walls together at weld points. However, it will be appreciated that the system **10** may be welded together with multiple metal pieces. In the instance of welding, the “bends” may be sharper, more defined, and not as curved. Additionally, and/or alternatively, the welds may be ground or sanded down to form similar bends as though the housing **12** was forged from a single piece of metal.

(69) Referring to FIGS. 3 and 4, a cross-bar **28** may extend from the third walls **20, 20'** across the channel **25**. The cross-bar **28** may provide greater structural integrity to the system **10**, and specifically the housing **12**, to maintain the housing **12** shape and to allow the system **10** to carry heavier loads. More than one cross-bar **28** may be utilized and may be commensurate with a ratio of the length of the housing **12**. The cross-bar(s) **28** may be positioned within the housing **12** and/or across the channel **25** depending on the length of the housing **12**.

(70) A plurality of support members **30** may be positioned and secured to the housing **12** on the interior of the second walls **18, 18'** and within the channel **25**. Securing of the support members **30** may be accomplished by welding the pieces into place. The plurality of support members **30** may be positioned opposite one another on the pair of second walls **18, 18'** and at multiple locations along the pair of second walls **18, 18'**. For example, support members **30** may be secured at different longitudinal positions along the interior of the second walls **18, 18'**. The plurality of support members **30** may extend longitudinally at least partially along the pair of second walls **18, 18'**, provide additional support, and may operate as a guide or track for extendable members. The support members **30** may also be planar, or flat, with the plan of the support members running substantially parallel to the first wall **16** of the housing **12**.

(71) Referring to FIGS. 4 and 6, a first configuration **100** shows a first extendable member **32** and a second extendable member **31** in a retracted position within the channel **25**, wherein the first and second extendable members **32, 31** are positioned within the housing **12**. The first and second extendable members **32, 31** are configured to slide longitudinally within the channel **25** and along the support members **30**. The first and second extendable members **32, 31** may exit the first and second openings **24, 26**, respectively. The first extendable member **32** is configured to reversibly

slide away from the second extendable member **31** and vice versa.

(72) Referring to FIG. **3**, a second configuration **102** shows the first and second extendable members **32**, **31** protruding from and extending from the housing **12**. First extendable member **32** extends along the same longitudinal axis as the housing axis **14** and in the opposite direction of the second extendable member **31**.

(73) Referring to FIGS. **3** and **5**, the first extendable member **32** extends from the housing **12** in a longitudinal direction and along the same longitudinal axis **14** as the housing **12**. The first extendable member **32** is configured to fit at least partially within the housing **12** and may fit entirely within the housing **12**. The first extendable member **32** includes a body with a planar first wall **34** that may run substantially parallel to the first wall **16** of the housing. On the two lateral sides of the planar first wall **34**, two extendable member second walls **36**, **36'**, opposite each other, may extend from the planar first wall **34** at approximately 90°. The two extendable member second walls **36**, **36'** may engage the support members **30** with the walls **36**, **36'** gliding or sliding along the support members **30**. Alternatively, the two extendable member second walls **36**, **36'** may engage and glide or slide along the third walls **20**, **20'** of the housing **12**. It is to be understood that the second extendable member **31** similarly includes a planar first wall and two opposing extendable member second walls disposed on lateral sides of the planar first wall. Further, the second extendable member **31** may similarly engage the support members **30** and/or the third walls **20**, **20'** of the housing **12**.

(74) Referring to FIGS. **7** and **8**, the first extendable member **32** may be substantially rectangular in shape and, from one perspective, may resemble a tray or open top box. The first extendable member **32** may comprise a proximal wall **38** and a distal wall **40**, opposite each other, and which may be substantially parallel to each other. The proximal and distal walls **38**, **40** can extend from the first planar wall **34** at about a 90° angle and can be connected to the pair of extendable member second walls **36**, **36'**.

(75) The proximal wall **38** may extend further from the planar first wall **34** than the distal wall **40**. The proximal wall **38** may extend further than the extendable member second walls **36**, **36'** as well. The proximal wall **38** may provide a stop against a proximal end of the support members **30**, so that the first extendable member **32** does not extend too far out of the housing **12**. The distal wall **40** may include a distal tip **42** which may include a flange **44**, or tab, which extends longitudinally from the distal wall **40** in the same plane or parallel plane as the planar first wall **34**. The distal tip **42** may be integrated into the body of the first extendable member **32** or may be a separate piece that may be secured, or welded, to the distal wall **40**. The distal tip **42** may include a right angle piece, or elbow, that in one plane sits flush against the distal wall **40**. In a separate plane perpendicular to the one plane sitting flush against the distal wall **40**, the distal tip **42** may extend in a same plane, substantially the same plane, or a parallel plane to the first planar wall **34**, which extension may be the flange **44**. The flange **44** engages a construction element **50**, which may be a wall or support, and rests on that construction element **50** which holds up the system **10** (see, e.g., FIG. **9**).

(76) Each extendable member **32**, **31** may extend from the housing **12** at least as far as half of the length of the extendable members **32**, **31**. Each extendable member **32**, **31** may extend just far enough for the flange **44** to protrude from the housing **12** to engage one edge of an opening (see FIG. **9**). Each extendable member **32**, **31** may extend as far as required to traverse the opening with the appropriate length of housing **12**. The distance each extendable member **32**, **31** extends is roughly infinite because each member **32**, **31** can slide to any number of positions from the flange **44** extending until the extendable member **32**, **31** hits the stop or the support member **30**.

(77) The first extendable member **32** may be manufactured, or forged, from a single metal piece or it may be welded from multiple metal pieces. Additionally, the first extendable member **32** may complementarily fit within the housing **12**, such that the curved edges/corners of the housing **12** (e.g., between the first wall **16** and the second walls **18**, **18'**) may correspond to similar curvatures

in the first extendable member **32** (e.g., between the planar first wall **34** and the extendable member second walls **36**, **36'**). This complementary fit may allow for ease in sliding the first extendable member **32** out of the housing **12**, as well as retracting the first extendable member **32** back into the housing **12**.

(78) The second extendable member **31** may be substantially identical to the first extendable member **32**. The same elements are utilized in the second extendable member **31** with the same features other than the second extendable member **31** extends from the opposite side of the housing **12** and in an opposing direction than the first extendable member **32**.

(79) The extendable members **32**, **31** may extend from a fraction of one inch (e.g., $\frac{1}{4}$, $\frac{1}{2}$, $\frac{1}{3}$ inch) to up to 12 inches from the housing **12**. The length of the entire system **10** may vary from 1.5 feet (18 inches) up to 42 feet and perhaps even longer. The housing **12** may be the majority of the length of the system **10** while the extendable members **32**, **31** remain roughly the same size, regardless of the housing **12** size. However, it is contemplated that the extendable members size or length **32**, **31** may increase proportionately to the housing **12** size.

(80) Depending on the length of the system **10** utilized, for the system **10** to traverse an opening in a construction element **50**, posts, post shores, or props may be required to engage the system **10** at one or more locations. The posts may engage the system **10** on a bottom side, or within the channel **25** side of the housing **12** at strategic locations in the opening of the construction element **50**.

(81) Referring to FIG. **9**, one method of use for the system **10** includes identifying the system **10** (with the extendable members **31**, **32** in a first configuration within the housing **12**) that would easily fit within a construction element opening. The method of use can also include extending at least one of the extendable members **31**, **32** to expose at least one flange **44** to engage the edge of the opening. The method can also include positioning the system **10** across the opening, typically horizontally across the opening, and extending the other of the extendable members **31**, **32** to expose the other flange **44** to engage the opposite edge of the same opening. The system **10**, when extended across the opening, is in a second configuration.

(82) Referring to FIG. **10**, an alternate embodiment of a system **110** is depicted. The system **110** may include a housing **112** that is substantially similar to the housing **12** previously described herein.

(83) The housing **112** may include a first wall **116**, which may be substantially planar, extending a length and a width of the housing **112**. The first wall **116** may be substantially flat and configured to allow other flat elements (i.e. bricks, blocks, etc.) to easily reside on the first wall **116**. The first wall **16** may include bends or curves toward each width end of the first wall **116**. A pair of second walls **118**, **118'** may extend from the first wall **116**, or the bends of the first wall **16**, in a direction substantially perpendicular to the first wall **116**. Extending from the pair of second walls **118**, **118'** are a pair of third walls **120**, **120'** that may extend from separate bends in the second walls **118**, **118'**. The pair of third walls **120**, **120'** may extend toward each other and the longitudinal axis **114**, or midline, of the longitudinal housing **112**. A channel **125** may be positioned between the pair of third walls **120**, **120'** and run the length of the housing **112**. The third walls **120**, **120'** may be substantially parallel to the first wall **116**. The channel **125**, passage, or void, may run the length of the housing **112**. A cross-sectional shape of the housing **112** may resemble a C-shape or U-shape.

(84) The housing **112** may include a first opening **124** toward one end of the housing **112** and a second opening **126** toward a second end of the housing **112**, with the channel **125** running from the first opening **124** to the second opening **126**. A cross-bar **128** may extend from the pair of third walls **120**, **120'** across the channel **125**.

(85) Rather than support members **30**, this embodiment may include a pin **130**, or rod, which may pass through a pair of holes **152** in the housing **112**. The pair of holes **152** each pass through the pair of second walls **118**, **118'**, or side walls, as appropriate. The holes **152** may be axially aligned with one another (e.g., aligned on opposing side walls) to allow for easy passage of a pin **130**. The pin **130** may at least partially traverse the channel **125**. Additionally, and/or alternatively, the pin

130 may traverse the channel **125** entirely.

(86) Similar to the previous extendable members **31**, **32** a first extendable member **132** may be substantially rectangular in shape and, from one perspective, may resemble a tray or open top box. The first extendable member **132** includes a body with a planar first wall **134** that may run substantially parallel to the first wall **116** of the housing **112**. The first extendable member **132** may also comprise a proximal wall **138** and a distal wall **140**, opposite each other, and which may be substantially parallel to each other. Each wall **138**, **140** extends from the first planar wall **134** at about a 90° angle and is connected to the pair of extendable member second walls **136**, **136'**.

(87) The proximal wall **138** may extend further from the planar first wall **134** than the distal wall **140**. The proximal wall **138** may extend further than the extendable member second walls **136**, **136'** as well. That is, the proximal wall **138** may be taller than the distal wall **140** and/or the extendable member second walls **136**, **136'**. The proximal wall **138** may provide a stop against the pin **130** (as may be seen in FIGS. **11-14**) so that the first extendable member **132** does not extend too far out of the housing **112**. The distal wall **140** may include a distal tip **142** which may include a flange **144**, or tab, which extends longitudinally from the distal wall **140** in the same plane or parallel plane as the planar first wall **134**. The distal tip **142** may be integrated into the body of the first extendable member **132** or may be a separate piece that may be secured, or welded, to the distal wall **140**. The distal tip **142** may include a right angle piece, or elbow, that on one plane sits flush against the distal wall **140**. In a separate plane, perpendicular to the one plane sitting flush against the distal wall **140**, the distal tip **142** can extend in a same plane, substantially the same plane, or a parallel plane to the first planar wall **134**, which extension may be the flange **144**. The flange **144** engages the construction element **50** (see, e.g., FIG. **9**).

(88) A second extendable member **131** may be substantially similar and mirror image of the first extendable member **132** with the same elements and features. Each extendable member **132**, **131** may extend from the housing **112** at least as far as half of the length of the extendable members **132**, **131**. Each extendable member **132**, **131** may extend just far enough for the flange **144** to protrude from the housing **112** and to engage one edge of an opening (see FIG. **9**). Each extendable member **132**, **131** may extend as far as required to traverse an opening with the appropriate length of housing **112**. The distance each extendable member **132**, **131** extends is approximately infinite because each member **132**, **131** can slide to any number of positions. For example, each member **132**, **131** can slide from the flange **144** abutting the housing **112** and granularly extending until the extendable member **132**, **131** is prevented from extending further (e.g., by action of the proximal wall **138** hitting the pin **130**).

(89) Extendable member **132**, **131** may include slots **154**, or cutouts or elongated apertures, within the second walls **136**, **136'**, or side walls. The slots **154** may be elongated holes or apertures extending perpendicular to a plane of the second walls **136**, **136'**. The slots **154** may be axially aligned with each other and may pass through each of the second walls **136**, **136'** entirely. The slots **154** may allow for passage and/or movement of the pin **130**. The slots **154** may slidably receive the pin **130** so as to allow the elongated members **132**, **131** to freely slide into and out of the housing **112**. Likewise, the holes **152** may slidably receive the pin **130** and may engage the housing **112** as further described herein. The pin **130** may traverse the holes **152** and the slots **154**, and the pin **130** may be secured to the housing **112** with a nut **156** or bolt. Alternatively, the pin **130** may have a transverse aperture that allows for a separate rod to pass through the transverse aperture and secure the pin **130** to the housing. The pin **130** may resemble a screw with threads on at least one end that may engage a nut **156** on one side of the housing, such as on second wall **118**, with the head of the screw on the opposite side of the housing, such as on second wall **118'**. It will be appreciated that any number of methods and means of securing a rod, pin or screw is contemplated herein.

(90) The slots **154**, with the pin **130** passing therethrough, provides a maximum and minimum length of extension for the first extendable member **132**. A distal end **158** of the slot **154** may be engaged when the first extendable member **132** is retracted into the housing **112**, such as in the first

configuration **100**. A proximal end **160** of the slot **158** may be engaged when the first extendable member **132** is extended from the housing **112**, such as in the second configuration **102**, at a maximum distance. The slots **154** may allow for an infinite number of positions between the proximal end of the slot **160** and the distal end of the slot **158**.

(91) The first extendable member **132** may further include a window **162**, or opening, in the planar wall **134**. The window **162** may allow for the first extendable member **132** to be manufactured with less weight for easier use and manipulation. The window **162** may also provide a user with the ability to see through the first extendable member **132** to the traversed opening and the housing **112**.

(92) For ease in describing the system **110**, the first extendable member **132** may have been utilized and describe, though it will be appreciated that the second extendable member **131** may comprise the same features and elements, and may be a mirror image of the first extendable member **132** when positioned in the housing **112**.

(93) Referring to FIGS. **11-18**, a system **210** is depicted, where the housing **112** may be the housings **12**, **112** as previously described herein. Additionally, the extendable members **31**, **32** may be substantially as previously described herein with the addition of the window **162**. Rather than the system **10** which comprises support members **30**, this system **210** utilizes the same holes **152** and pin **130** from the previous embodiment **110**, wherein the pin **130** may act similarly as the support members **30** in maintaining the extendable members **31**, **32** in place. Additionally, the pin **130** engages with the proximal wall **38** to act as a stop, as previously described.

(94) In this embodiment, the pin **130** may provide the same strength and stability as the support members **30** but with far less weight allowing for easier manipulation of the system **110** or system **210**.

(95) FIGS. **19-22** illustrate additional views and details of an extendable members, which may be extendable members **31**, **32**, **131**, **132**. Though only one extendable member is illustrated, it is to be understood that the other, opposing extendable member is a mirror image, or substantially mirror image, of the illustrated and described extendable member. Referring to FIGS. **19-22**, the extendable member **132** may comprise an alternate flange **164** that may comprise an angle. The flange **164** may comprise the same elements as the previously disclosed embodiment of a flange **144**. The flange **164** may include an angle of about 11° (e.g., about 9° to about 13°) and may utilize such an angle to allow a user (which may be a mason) to stabilize the system (e.g., a system **10**, **110**, **210**) across an opening, where the opening may have an angled wall or an intersection of two walls that is angled. By providing an angled flange **164**, the entire flange **164** can rest on the angled wall with no exposure of the flange **164**.

(96) Referring to FIGS. **23-26**, the extendable member **132** may comprise an alternate flange **166** that may comprise an angle. A flange **166** may comprise the same elements as the previously disclosed embodiment of a flange **144**. The flange **166** may include an angle of about 22° (e.g., about 20° to about 25°) and may utilize such an angle to allow a user (which may be a mason) to stabilize the system across an opening that may have an angled wall or an intersection of two wells that is angled. By providing an angled flange **166** the entire flange may rest on the angled wall with no exposure of the flange **166**.

(97) Referring to FIGS. **27-30**, the extendable member **132** may comprise an alternate flange **168** that may comprise an angle. A flange **168** may comprise the same elements as the previously disclosed embodiment of a flange **144**. The flange **168** may include an angle of about 45° (e.g., about 43° to about 47°) and may utilize such an angle to allow a user (which may be a mason) to stabilize the system across an opening that may have an angled wall or an intersection of two wells that is angled. By providing an angled flange **168** the entire flange may rest on the angled wall with no exposure of the flange **168**.

(98) It will be appreciated that any number of angles is contemplated here and specifically between about 5° to 45° and the above examples are simply examples and not limiting herein. For example,

the angle may be about 6°, 10°, 15°, 20°, 25°, 30°, 35°, 44°, or an angle within a range defined by any two of the foregoing values.

(99) Referring to FIGS. **31-42** similar examples of angled flanges are provided utilizing the extendable members **32** described in the first embodiment of the system **10** with the exception of the window **162** also contemplated herein. Similar angles to the previous embodiments are shown with angles of 11°, 22° and 45° respectively. These embodiments may not include the slots **154** as these embodiments may be intended for use with the alternate system **210** but may also be utilized in the first described system **10**.

(100) The dimensions of the system may vary as well. The housing **12**, **112** may be anywhere from 2 feet (or roughly 0.6 meters) to 42 feet (or roughly 13 meters) in length. The width of the housing **12** may be 4 to 8 inches (or roughly 10 cm to 21 cm). The height of the housing **12** may be 2 to 4 inches (or roughly 5 cm to 11 cm). The length of the extendable members **31**, **32**, may vary but may be in the range of 12 to 18 inches (or roughly 30 cm to 46 cm), with the extendable members **31**, **32** being capable of extending 6 to 9 inches (or roughly 15 cm to 23 cm).

(101) A user may then use building materials, bricks, blocks, etc., to build across and on top of the system **10**, utilizing the system **10** to stabilize the building materials. The user may then remove the system **10** by simply retracting the extendable members **31**, **32** into the housing **12** at least enough to release the flange(s) from the edges of the construction element **50** opening.

(102) It will be appreciated that the housing **12**, **112**, or shell, may be comprised of 12-14 Gauge C Channel purlin which is a commonly used beam to extend over a roof or other constructive element. The extendable members **31**, **32**, **131**, **132** (or trays) may be one-quarter inch milled steel (it may also be cast, forged, extruded, welded, etc.). The pin **130**, or rod, may be comprised of steel, other metal or metal alloys that provide the strength and rigidity necessary for the functions described herein. Other metals and materials may be used with a similar construct and even wood, plastics and carbon-fiber are contemplated.

(103) FIGS. **43-46** illustrate another embodiment of a first extendable member **332** according to the present disclosure. As before, though only one extendable member **332** is illustrated, it is to be understood that the other, opposing extendable member **331** is a mirror image, or substantially mirror image, of the illustrated and described extendable member **332**. Similar to the previous extendable members **31**, **32** a first extendable member **332** may be substantially rectangular in shape and, from one perspective, may resemble a tray or open top box. The first extendable member **332** includes a body with a planar first wall **334** that may run substantially parallel to the first wall **316** of the housing **312** (see FIGS. **52-59**). The first extendable member **332** may also comprise a proximal wall **338** and a distal wall **340**, opposite each other, and which may be substantially parallel to each other. Each wall **338**, **340** extends from the first planar wall **334** at about a 90° angle and is connected to the pair of extendable member second walls **336**, **336'**.

(104) In some embodiments, the proximal wall **338** may extend further from the planar first wall **334** than the distal wall **340**. In some embodiments, the proximal wall **338** may extend further than the extendable member second walls **336**, **336'** as well. That is, the proximal wall **338** may be taller than the distal wall **340** and/or the extendable member second walls **136**, **136'**. The proximal wall **338** may provide a stop against the pin **330** (as may be seen in FIGS. **11-14** and **59**) so that the first extendable member **332** does not extend too far out of the housing **312**. The distal wall **340** may include a distal tip **342** which may include a flange **344**, or tab, which extends longitudinally from the distal wall **340** in the same plane or parallel plane as the planar first wall **334**. Alternatively, the flange **344** may be continuous with the planar first wall **334**.

(105) The distal tip **342** may be integrated into the body of the first extendable member **332** or may be a separate piece that may be secured, or welded, to the distal wall **340**. For example, referring to FIGS. **47-48**, the distal tip **342** may include a plurality of tabs **343** that may removably mate with or engage a plurality of corresponding notches or holes **341** in the extendable member **332**. The distal tip **342** may include a right-angle piece, or elbow, that on one plane sits flush against the

distal wall **340**. In a separate plane, perpendicular to the one plane sitting flush against the distal wall **340**, the distal tip **342** can extend in a same plane, substantially the same plane, or a parallel plane to the first planar wall **334**, which extension may be the flange **344**. The flange **344** engages the construction element **50** (see, e.g., FIG. **9**).

(106) As illustrated in FIGS. **49-51**, the distal tip **342** is received by the extendable member **332** at the distal wall **340**, where the distal tip **342** may also be the distal wall **340**. The tabs **343** of the distal tip **342** are received by holes **341** located at the distal end of the extendable member **332**. When mated with the holes **341**, the distal tip **342** may be substantially flush with the walls **336**, **336'** of the extendable member **332**.

(107) A second extendable member **331** may be substantially similar and a mirror image of the first extendable member **332** with the same elements and features. Each extendable member **332**, **331** may extend from the housing **312** at least as far as half of the length of the extendable members **332**, **331**. Each extendable member **332**, **331** may extend just far enough for the flange **344** to protrude from the housing **312** and to engage one edge of an opening (see FIG. **9**). Each extendable member **332**, **331** may extend as far as required to traverse an opening with the appropriate length of housing **312**. The distance each extendable member **332**, **331** extends is approximately infinite because each member **332**, **331** can slide to any number of positions. For example, each member **332**, **331** can slide from the flange **344** abutting the housing **312** and granularly extending until the extendable member **332**, **331** is prevented from extending further (e.g., by action of the proximal wall **338** hitting the pin **330**).

(108) Extendable member **332**, **331** may include raised notches **345** within the second walls **336**, **336'**, or side walls. The notches **345** may be positioned closer to the proximal wall **338** of the extendable members **332**, **331**. The raised notches **345** enhance the clearance and level attitude of the extendable member **332**, **331** when fully extended from the housing **312**. Further, the raised notches **345** allow a system **310** of the housing **312** and extendable members **332**, **331** (see FIG. **59**) to be installed and maintain a more level setting surface while traversing an opening in a structure (see FIG. **9**). Additionally, the raised notches **345** allow systems **310** to be effectively linked together to cross virtually any width opening. Still further, systems **310** can be mixed and matched to be utilized together in an infinite number of sizes based on the field requirement.

(109) Extendable member **332**, **331** may include slots **354**, or cutouts or elongated apertures, within the second walls **336**, **336'**, or side walls. The slots **354** may be elongated holes or apertures extending perpendicular to a plane of the second walls **336**, **336'**. The slots **354** may be axially aligned with each other and may pass through each of the second walls **336**, **336'** entirely. The slots **354** may allow for passage and/or movement of a pin **330**. In some embodiments, the pin **330** may include two (2) pins **330**, each received by a hole **352**, or housing hole, in the housing **312**, discussed more fully below with respect to FIG. **52**. The slots **354** may each slidably receive the pins **330** so as to allow the elongated members **332**, **331** to freely slide into and out of the housing **312**.

(110) Likewise, the holes **352** may slidably receive the pins **330** and may engage the housing **312** as further described herein. The pin **330** may traverse the holes **352** and the slots **354**, and the pin **330** may be secured to the housing **312** with a nut **356** or bolt. The pin **330** may resemble a screw with threads on at least one end that may engage a nut **356** on one side of the housing, such as on second wall **318**, with the head of the screw on the opposite side of the housing, such as on second wall **318'**. It will be appreciated that any number of methods and means of securing a rod, pin or screw is contemplated herein.

(111) Alternatively, in some embodiments, the pins **330** may resemble rivet nuts (also referred to as "rivnuts") and the holes **352** of the housing **312** may be ports to receive the rivnuts. The holes **352** may be positioned in or around the four (4) corners of the housing **312**, allowing the extendable members **332**, **331** to be directly attached or secured to the inside of the housing **312**. Such an arrangement allows the extendable members **332**, **331** to be secured and attached to the housing

312 with reduced drag or friction. Additionally, the arrangement allows the extendable members **332**, **331** to be fully retracted into the housing **312** at both ends of the housing **312**, which allows for the connection of multiple housings **312** together to span and cross any width or opening.

(112) For example, an eight-foot housing **312** can be combined with a twelve-foot housing **312** to cross a twenty-foot opening. Any other combinations tailored to specific sized openings are also considered by the present disclosure. This also allows multiple sized housings **312** to be combined “on the fly,” such as when changes in the field necessitates an opening size not anticipated in the original plan specifications.

(113) Inclusion of the pins **330** (e.g., rivnuts) also simplifies service or repair of a system **310** incorporating the housing **312**, the pins **330**, and the extendable member **332**, **331**. Specifically, the pins **330** received by the holes **352** can easily be ground down/off with any handheld grinder, allowing the extendable member **332**, **331** to be removed and quickly replaced. As damage to the extendable member **332**, **331** is the most common form of damage for disclosed systems **310**, quick and efficient removal and replacement enhances the overall longevity of the disclosed systems **310**.

(114) As discussed more fully below, inclusion of the pins **330** (e.g., rivnuts) allows multiple systems **310** to be quickly and efficiently connected together utilizing a coupler **322** (see FIGS. 63-67). Specifically, the coupler **322** simply and quickly connects any two housings **312** by bolting the coupler **322** into four holes **352** disposed, or positioned, about the corners of the housing **312**—two holes **352**, axially aligned, on a first housing **312** and two holes **352**, axially aligned, on a second housing **312**, where the ends of the housings **312** abut each other within the coupler **322**.

Connection of multiple housings **312** can be accomplished in a short time period, or time frame, even within minutes (e.g., 1, 5, 10, 15, 30 minutes etc.) rather than the hours typically associated with other steel fabricated or wood shoring systems.

(115) The slots **354** provide a maximum and minimum length of extension for the first extendable member **332**. A distal end **358** of the slot **354** may be engaged when the first extendable member **332** is retracted into the housing **312**, such as in the first configuration **100**. A proximal end **360** of the slot **354** may be engaged when the first extendable member **332** is extended from the housing **312**, such as in the second configuration **102**, at a maximum distance. The slots **354** may allow for an infinite number of positions between the proximal end of the slot **360** and the distal end of the slot **358**.

(116) The first extendable member **332** may further include a window **362**, or opening, in the planar wall **334**. The window **362** may allow for the first extendable member **332** to be manufactured with less weight for easier use and manipulation. The window **362** may also provide a user with the ability to see through the first extendable member **332** to the traversed opening and the housing **312**.

(117) For ease in describing the system **310**, the first extendable member **332** may have been utilized and describe, though it will be appreciated that the second extendable member **331** may comprise the same features and elements, and may be a mirror image of the first extendable member **332** when positioned in the housing **312**.

(118) FIGS. 52-58 illustrate another embodiment of a housing **312** according to the present disclosure. The housing **312** may include a first wall **316**, which may be substantially planar, extending a length and a width of the housing **312**. The first wall **316** may be substantially flat and configured to allow other flat elements (i.e. bricks, blocks, etc.) to easily reside on the first wall **316**. The first wall **316** may include bends or curves toward each width end of the first wall **316**. A pair of second walls **318**, **318'** may extend from the first wall **316**, or the bends of the first wall **316**, in a direction substantially perpendicular to the first wall **316**. Extending from the pair of second walls **318**, **318'** are a pair of third walls **320**, **320'** that may extend from separate bends in the second walls **318**, **318'**. The pair of third walls **320**, **320'** may extend toward each other and a longitudinal axis **314**, or midline, of the longitudinal housing **312**. A channel **325** may be positioned between the pair of third walls **320**, **320'** and run the length of the housing **312**. The

third walls **320**, **320'** may be substantially parallel to the first wall **316**. The channel **325**, passage, or void, may run the length of the housing **312**. A cross-sectional shape of the housing **312** may resemble a C-shape or U-shape.

(119) The housing **312** may include a first opening **324** toward one end of the housing **312** and a second opening **326** toward a second end of the housing **312**, with the channel **325** running from the first opening **324** to the second opening **326**. A plurality of cross-bars **328** may extend from the pair of third walls **320**, **320'** across the channel **325**.

(120) As discussed, this embodiment may include pins **330** which may pass through a pair of holes **352** in the housing **312**. The pair of holes **352** each pass through the pair of second walls **318**, **318'**, or side walls, as appropriate. The holes **352** may be axially aligned with one another (e.g., aligned on opposing side walls) to allow for easy passage of the pins **330**. The pins **330** may at least partially extend into the channel **325**, where the pins **330** will engage with the slots **354** of the extendable member **332**, **331**.

(121) FIGS. **59-62** illustrate another embodiment of a system **310** in a second configuration with the housing of FIG. **52** and two extendable members of FIG. **45** partially extended from the housing **312**. As before, the pins **330** maintain the position of the extendable member **332**, **331** within the channel **325** of the housing **325** while allowing the extendable member **332**, **331** to slide within the channel **325**. Specifically, the extendable member **332**, **331** slides between a first configuration, where the extendable member **332**, **331** is retracted within the channel **325**, to a second configuration, where the extendable member **332**, **331** is extended a distance from the channel **325**. When the pins **330** engage the distal end **358** of the slots **354** (see FIG. **50**), the extendable member **332**, **331** is “fully extended” from the channel **325**. When the pins **330** engage the proximal end **360** of the slots **354** (see FIG. **50**), the extendable member **332**, **331** is “fully retracted” within the channel **325**. In some embodiments, the distal tip **342** of the extendable member **332**, **331** is substantially flush with an end of the housing **312** and only the flange **344** extends from the housing **312**.

(122) The extendable members **332**, **331** may extend from a fraction of one inch (e.g., $\frac{1}{4}$, $\frac{1}{2}$, $\frac{1}{3}$ inch) to up to 12 inches from the housing **312**. The length of the entire system **310** may vary from 1.5 feet (18 inches) up to 42 feet and perhaps even longer. The housing **312** may be the majority of the length of the system **310** while the extendable members **332**, **331** remain roughly the same size, regardless of the housing **312** size. However, it is contemplated that the extendable members size or length **332**, **331** may increase proportionately to the housing **312** size.

(123) Depending on the length of the system **310** utilized, for the system **310** to traverse an opening in a construction element **50**, posts, post shores, or props may be required to engage the system **310** at one or more locations. The posts may engage the system **310** on a bottom side, or within the channel **325** side of the housing **312** at strategic locations in the opening of the construction element **50**. As discussed below, posts, or support beams, may engage a coupler **322** via holes **337**, or coupler holes, in a first wall **327** of the coupler **322**. The first wall **327** may comprise an inner channel surface **364** and an outer planar surface **366**.

(124) FIGS. **63-65** illustrate one embodiment of a coupler **322** according to the present disclosure. As illustrated, the coupler **322** includes a first wall **327**, which may be substantially planar, extending a length and a width of the coupler **322**. The first wall **327** may be substantially flat and configured to allow other flat elements (i.e., housings **312**) to easily reside on the first wall **327**. A pair of second walls **329**, **329'** may extend from the first wall **327** in a direction non-parallel, or substantially perpendicular, to the first wall **327**. The first wall **327** together with the second walls **329**, **329'** define a channel **323**, or coupler channel. A pair of holes or ports **335**, or coupler ports, are defined in each second wall **329**, **329'**. A pair of coupler holes **337** are defined in the first wall **327**. The pairs of coupler ports **335** may be axially aligned with each other and may be disposed within the walls **329**, **329'** such that they are also axially aligned with housing holes **352** on one end of the housing **312**. Such alignment of the pairs of ports **335** and housing holes **352** allows the

coupler **322** to be bolted or otherwise secured to one end of the housing **312**. For example, the pairs of ports **335** and the housing holes **352** may receive rivnuts that secure the coupler **322** to one end of the housing **312**.

(125) The disposition of the coupler ports **335** around the coupler **322** allows the coupler **322** to be aligned with the housing holes **352** of two housings **312**. That is, a first housing **312** can be aligned and secured to the coupler **322** via alignment of the housing holes **352** and the coupler ports **335**. A second housing can be similarly aligned and secured to the coupler **322**, where the second housing **312** will abut the first housing **312** within the coupler **322**. As shown in FIG. **65**, the coupler **322** may have a C-shaped or U-shaped cross-section to receive the housings **312**.

(126) FIGS. **66-67** illustrate another embodiment, or use, of a system **310** including two housings **312** joined together by the coupler **322**. The housings **312** are received within the channel **323** of the coupler **322**. Additionally, the housings **312** oriented such that the channel **325** faces the coupler channel **323** and such that when the system **310** is in position the outer planar surface **366**, of the coupler **322**, faces down, or substantially downward, such that a support beams, or posts, may engage the coupler holes **337** from the outer planar surface **366**. The ports **335** of the coupler **322** align with housing holes **352** of each housing **312** to secure the housings **312** to the coupler **322**.

Due to the orientation of the housing holes **352** and ports **335**, the housings **312** can be quickly and simply joined together via the coupler **322**. The housings **312** abut each other at a substantial mid-point or center of the coupler **322**. The coupler **322** is sized and shaped to receive any length of housing **312**. The coupler holes **337** defined in the first wall **327** of the coupler **322** may be for receiving a post or other support structure as the system **310** traverses an opening of a structure.

(127) Alternatively, the coupler **322** may be positioned such that the coupler channel **323** receives the housings **312** first planar wall **334** (as one example) against the inner channel surface **364**. The inner channel **364**, may face downward, or substantially downward, when engaging each of the housings **312**.

(128) The coupler **322** may be comprised of a single piece of metal or steel, and may be forged of a single piece of metal. The single piece of metal can be forged with the bends in the walls as described earlier, which allows for greater strength of the coupler **322** rather than welding the walls together at weld points. However, it will be appreciated that the system **310** may be welded together with multiple metal pieces. In the instance of welding, the “bends” may be sharper, more defined, and not as curved. Additionally, and/or alternatively, the welds may be ground or sanded down to form similar bends as though the housing **12** was forged from a single piece of metal.

(129) A width of the coupler **322** may be sized such that the coupler **322** can receive and be secured to a housing **312**. Thus, the width of the coupler **322** may correspond to a width of the housing **312**. In some embodiments, the width of the coupler **322** may range from approximately 5 to 12 inches, such as 6, 7, 8, 10 inches or a width within a range defined by any two of the foregoing values.

Similarly, a length of the coupler **322** may be sized such that the coupler **322** adequately receives and secures two housings **312** together. In some embodiments, the length of the coupler **322** ranges from 18 inches (or 1.5 feet) to 30 inches (or 2.5 feet), such as 20, 23, 25, 28 inches or a length within a range defined by any two of the foregoing values. A height of the coupler **322** may correspond to a height of the housings **312**, such that the housings **312** are substantially flush with the coupler **322** when received by the coupler **322**. In some embodiments, the height of the coupler **322** may range from approximately 2 to 8 inches, such as 3, 5, 7 inches or a height within a range defined by any two of the foregoing values.

(130) The ports **335** may be disposed at approximately a middle or center of the walls **329**, **329'**. For example, a height of the walls **329**, **329'** may be about 2.5 inches, with the ports **335** disposed about 1.2 inches from the first wall **327**. In some embodiments, the ports **335** are disposed approximately 1.5 inches above the first wall **327**. The disposition of the ports **335** may correspond to the placement and disposition of the holes **352** within the housing **312**. The coupler holes **337** in the first wall **327** of the coupler **322** may be horizontally and/or vertically offset from each other. In

some embodiments, the coupler holes **337** are offset from each other by about 2 to 4 inches, such as about 3.5 inches.

(131) Additionally, the coupler **322** may alternatively have a 90 degree bend in the center. The bend may allow for two housings **312** to be attached, connected or engaged at 90 degrees and may traverse a 90 degree opening thus allowing for an opening on a corner of a building. While 90 degrees may be the most frequently used, it is contemplated that any angled opening or corner is considered herein from 0 to 180 degrees.

(132) Although the foregoing disclosure provides many specifics, these should not be construed as limiting the scope of any of the ensuing claims. Other embodiments may be devised which do not depart from the scopes of the claims. Features from different embodiments may be employed in combination. The scope of each claim is, therefore, indicated and limited only by its plain language and the full scope of available legal equivalents to its elements.

Claims

1. A system for traversing an opening, comprising: a first elongated frame; a second elongated frame; a coupler for receiving and coupling the first elongated frame and the second elongated frame, the coupler comprising: a first coupler wall with a substantially planar surface; a pair of second coupler walls extending non-parallel from the first coupler wall, the space between the pair of second coupler walls defining a coupler channel configured to receive the first elongated frame and the second elongated frame; a first set of coupler ports axially aligned within the second coupler walls; and a second set of coupler ports, spaced apart from the first set of coupler ports, axially aligned within the second coupler walls; wherein the coupler channel is oriented substantially upward with the first elongated frame and second elongated frame residing within the coupler channel when the system traverses an opening; and the first elongated frame comprising: a first planar surface; a first longitudinal wall extending substantially perpendicular from the first planar surface, and a second longitudinal wall, opposite the first longitudinal wall, extending substantially perpendicular from the first planar surface, the first and second longitudinal walls forming a channel; a third longitudinal wall extending substantially perpendicular from the first longitudinal wall at least partially across the channel; a fourth longitudinal wall extending substantially perpendicular from the second longitudinal wall at least partially across the channel; a first hole extending through a first longitudinal wall and a second hole extending through a second longitudinal wall axially aligned with the first hole and through the longitudinal walls; a first extendable member configured to extend longitudinally beyond the first elongated frame, the first extendable member comprising: a second planar surface substantially parallel to the first planar surface; a first lateral wall extending substantially perpendicular to the second planar surface and a second lateral wall opposite the first lateral wall extending substantially perpendicular to the second planar surface; a first pin passing at least partially through the first hole and the second hole, wherein the first pin is secured to the first elongated frame and the first lateral wall and second lateral wall are configured to run along the first pin; a distal wall extending from the second planar surface, substantially perpendicular to the first and second lateral walls; a proximal wall substantially parallel and opposite the distal wall, wherein the proximal wall extending further from the second planar surface than the distal wall and lateral walls; and a flange extending longitudinal and in the same plane as the second planar surface.

2. The system of claim 1, wherein the second elongated frame comprises: a third planar surface; a second elongated frame first longitudinal wall extending substantially perpendicular from the third planar surface, and a second elongated frame second longitudinal wall, opposite the second elongated frame first longitudinal wall, extending substantially perpendicular from the third planar surface, the second elongated frame first longitudinal wall and the second elongated frame second longitudinal wall forming a channel; and a second extendable member configured to extend

longitudinally beyond the second elongated frame opposite the first extendable member.

3. The system of claim 2, further comprising: a first configuration wherein the first and second extendable members are positioned within the first elongated frame and second elongated frame respectively; and a second configuration wherein the first and second extendable members are extended at least partially outside the first elongated frame and second elongated frame respectively.

4. The system of claim 1, wherein the coupler channel extends across the width of the pair of coupler walls and is configured to flushly receive the pair of longitudinal walls of the first elongated frame.

5. The system of claim 1, where the channel of the first elongated frame faces substantially downward when residing within the coupler channel when the system traverses an opening.

6. The system of claim 1, wherein the first elongated frame comprises a third hole and a fourth hole toward an opposite end from the first extendable member; wherein the third hole and fourth hole are axially aligned.

7. The system of claim 6, wherein the first set of ports axially align with the third hole and fourth hole are axially aligned-when the first elongated frame resides within the coupler.

8. The system of claim 6, wherein a second pin passes at least partially through the third hole and the fourth hole as well as the first set of ports and is secured to the coupler.

9. The system of claim 1, wherein the coupler further comprises at least one coupler hole extending through the first coupler wall configured to engage at least one support beam.

10. A system for traversing an opening, comprising: a first elongated frame; a second elongated frame; a coupler for receiving and coupling the first elongated frame and the second elongated frame, the coupler comprising: a first coupler wall with a substantially planar surface; a pair of second coupler walls extending non-parallel from the first coupler wall, the space between the pair of second coupler walls defining a coupler channel configured to receive the first elongated frame and the second elongated frame; a first set of coupler ports axially aligned within the second coupler walls; and a second set of coupler ports, spaced apart from the first set of coupler ports, axially aligned within the second coupler walls; and the first elongated frame comprising: a first planar surface; a first longitudinal wall extending substantially perpendicular from the first planar surface, and a second longitudinal wall, opposite the first longitudinal wall, extending substantially perpendicular from the first planar surface, the first and second longitudinal walls forming a channel; at least one crossbar extending from the first longitudinal wall to the second longitudinal wall across the channel; a first hole extending through a first longitudinal wall and a second hole extending through a second longitudinal wall axially aligned with the first hole and through the longitudinal walls; a first extendable member configured to extend longitudinally beyond the first elongated frame, the first extendable member comprising: a second planar surface substantially parallel to the first planar surface; a first lateral wall extending substantially perpendicular to the second planar surface and a second lateral wall opposite the first lateral wall extending substantially perpendicular to the second planar surface; a pair of axially aligned elongated holes passing through the first lateral wall and second lateral wall, the elongated holes extending a substantial length of the first lateral wall and second lateral wall; wherein a first pin passes at least partially through the first hole and the second hole and the pair of elongated holes and is secured to the first elongated frame, wherein the first extendable member is configured to freely slide longitudinally along the elongated holes wherein the elongated holes engage the first pin to provide a stop for the first extendable member; a distal wall extending from the second planar surface, substantially perpendicular to the first and second lateral walls; a proximal wall substantially parallel and opposite the distal wall; and a flange extending longitudinal and in the same plane as the second planar surface.

11. The system of claim 10, wherein the second elongated frame comprises: a third planar surface; a second elongated frame first longitudinal wall extending substantially perpendicular from the

third planar surface, and a second elongated frame second longitudinal wall, opposite the second elongated frame first longitudinal wall, extending substantially perpendicular from the third planar surface, the second elongated frame first longitudinal wall and the second elongated frame second longitudinal wall forming a channel; and a second extendable member configured to extend longitudinally beyond the second elongated frame opposite the first extendable member.

12. The system of claim 11, further comprising: a first configuration wherein the first and second extendable members are positioned within the first elongated frame and second elongated frame respectively; and a second configuration wherein the first and second extendable members are extended at least partially outside the first elongated frame and second elongated frame respectively.

13. The system of claim 10, wherein the coupler channel extends across the width of the pair of coupler walls and is configured to flushly receive the pair of longitudinal walls of the first elongated frame.

14. The system of claim 10, where the coupler channel is oriented substantially upward when receiving the first elongated frame and the second elongated frame when the system traverses an opening.

15. The system of claim 10, wherein the first elongated frame comprises a third hole and a fourth hole toward an opposite end from the first extendable member; wherein the third hole and fourth hole are axially aligned.

16. The system of claim 15, wherein the first set of ports axially align with the third hole and fourth hole are axially aligned when the first elongated frame resides within the coupler.

17. The system of claim 15, wherein a second pin passes at least partially through the third hole and the fourth hole as well as the first set of ports and is secured to the coupler.

18. The system of claim 10, wherein the coupler further comprises at least one coupler hole extending through the first coupler wall configured to engage at least one support beam.
