

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410835
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Patil; Pravin Ganpati et al.

Lubricant draining bearing assemblies

Abstract

Lubricant draining bearing assemblies are disclosed. An example apparatus includes a first race, a second race, roller bearings positioned between the first race and the second race, and a cage positioned around the roller bearings between the first race and the second race, the cage including a first radial surface, a second radial surface, and an axial surface, the first radial surface facing the first race, the second radial surface facing the second race, the axial surface facing away from the roller bearings, the cage including at least one conduit extending between the first radial surface and at least one of the second radial surface or the axial surface, the conduit defining a flow path for a fluid out of a cavity between the first race, the roller bearings, and the cage.

Inventors: Patil; Pravin Ganpati (Bengaluru, IN), Ganiger; Ravindra Shankar (Bengaluru, IN), Potnuru; Santosh Kumar (Bengaluru, IN), Prasad; Santosh Kumar (Bengaluru, IN), Sangli; Pradeep Hemant (Bengaluru, IN), Kumar; Rajesh (Bengaluru, IN), Hopper; Mark L. (West Chester, OH)

Applicant: General Electric Company (Schenectady, NY)

Family ID: 92716868

Assignee: GENERAL ELECTRIC COMPANY (Evendale, OH)

Appl. No.: 18/313145

Filed: May 05, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240318688 A1	Sep. 26, 2024

Foreign Application Priority Data

IN	202311018804	Mar. 20, 2023
----	--------------	---------------

Publication Classification

Int. Cl.: F16C33/46 (20060101); F16C33/66 (20060101)

U.S. Cl.:

CPC F16C33/4623 (20130101); F16C33/6681 (20130101); F16C2360/23 (20130101)

Field of Classification Search

CPC: F16C (33/4605); F16C (33/4623); F16C (33/4629); F16C (33/4635); F16C (33/6681); F16C (2360/23); F01D (25/16); F01D (25/18)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2838348	12/1957	Clarence	384/466	F16C 33/6681
5749660	12/1997	Dusserre-Telmon et al.	N/A	N/A
8197142	12/2011	Murata et al.	N/A	N/A
8562224	12/2012	Duffy	N/A	N/A
8672555	12/2013	Gardelle et al.	N/A	N/A
8979383	12/2014	Carter et al.	N/A	N/A
9022661	12/2014	Hayashi	384/470	F16C 33/6681
9033581	12/2014	Carter et al.	N/A	N/A
9841056	12/2016	Snow et al.	N/A	N/A
9957839	12/2017	Antunes et al.	N/A	N/A
2013/0087413	12/2012	Carter	384/470	F16C 33/3843

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
09151946	12/1996	JP	F16C 33/4605
H11336767	12/1998	JP	N/A
2012041940	12/2011	JP	F16C 33/4623

OTHER PUBLICATIONS

Machine Translation of JP-09151946-A (Year: 1997). cited by examiner

Machine Translation of JP-H11336767-A (Year: 1999). cited by examiner

Machine Translation of JP-2012041940-A (Year: 2012). cited by examiner

Primary Examiner: Waits; Alan B

Attorney, Agent or Firm: Venable LLP

Background/Summary

RELATED APPLICATION

(1) This patent claims the benefit of Indian Provisional Patent Application No. 202311018804, which was filed on Mar. 20, 2023. Indian Provisional Patent Application No. 202311018804 is hereby incorporated herein by reference in its entirety. Priority to Indian Provisional Patent Application No. 202311018804 is hereby claimed.

FIELD OF THE DISCLOSURE

(2) This disclosure relates generally to bearings and, more particularly, to lubricant draining bearing assemblies.

BACKGROUND

(3) A turbine engine generally includes a fan and a core section arranged in flow communication with one another. The turbine engine includes bearing assemblies to facilitate rotation between relative parts. The bearing assemblies are lubricated to facilitate rotation of the bearing elements.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) A full and enabling disclosure of the presently described technology, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which makes reference to the appended figures, in which:
- (2) FIG. 1 is a schematic, cross-sectional view of a turbine engine, taken along a centerline axis of the turbine engine, according to the present disclosure.
- (3) FIG. 2A is a schematic, cross-sectional view of a bearing assembly for the turbine engine of FIG. 1.
- (4) FIG. 2B is another schematic, cross-sectional view of a bearing assembly for the turbine engine of FIG. 1.
- (5) FIG. 3 is a schematic, cross-sectional view of the bearing assembly of FIG. 2B, taken along the section line 3-3 of FIG. 2B.
- (6) FIG. 4 is a schematic of a flow path of an example lubricant drain of the bearing assembly of FIG. 2B.
- (7) FIG. 5 is a schematic, axial cross-sectional view of a bearing assembly representative of the bearing assembly of FIG. 2A and/or the bearing assembly of FIG. 2B.
- (8) FIG. 6 is a schematic, axial cross-sectional view of another bearing assembly representative of the bearing assembly of FIG. 2A and/or the bearing assembly of FIG. 2B.
- (9) FIG. 7 is a schematic, axial cross-sectional view of another bearing assembly representative of the bearing assembly of FIG. 2A and/or the bearing assembly of FIG. 2B.
- (10) FIG. 8 is a schematic, circumferential cross-sectional view of the bearing assembly of FIGS. 6 and/or 7 taken along the section line 8-8 in FIGS. 6 and/or 7.
- (11) FIG. 9 is a partial perspective view of the bearing assembly of FIG. 8.
- (12) FIG. 10 is another view of the bearing assembly of FIG. 8.
- (13) FIG. 11 is a schematic, circumferential cross-sectional view of another bearing assembly representative of the bearing assembly of FIG. 2A and/or the bearing assembly of FIG. 2B.
- (14) FIG. 12 is a schematic, axial cross-sectional view of the bearing assembly of FIG. 11, taken along the section line 12-12 of FIG. 11.
- (15) FIG. 13 is a schematic, axial cross-sectional view of another bearing assembly representative of the bearing assembly of FIG. 2A and/or the bearing assembly of FIG. 2B.
- (16) FIG. 14 is a schematic, circumferential cross-sectional view of another bearing assembly representative of the bearing assembly of FIG. 2A and/or the bearing assembly of FIG. 2B.
- (17) FIG. 15 is a schematic, circumferential cross-sectional view of another bearing assembly representative of the bearing assembly of FIG. 2A and/or the bearing assembly of FIG. 2B.

- (18) FIG. 16 is a schematic, axial cross-sectional view of a configuration of a bearing cage of the bearing assembly of FIG. 15, taken along the section line 16-16 of FIG. 15.
- (19) FIG. 17 is a schematic, axial cross-sectional view of another configuration of a bearing cage of the bearing assembly of FIG. 15.
- (20) FIG. 18 is a partial perspective view of a bearing cage utilized in the bearing assemblies of FIGS. 12-15.
- (21) FIG. 19A is a partial perspective view of another bearing assembly representative of the bearing assembly of FIG. 2A and/or the bearing assembly of FIG. 2B.
- (22) FIG. 19B is a partial perspective view of another bearing assembly representative of the bearing assembly of FIG. 2A and/or the bearing assembly of FIG. 2B.
- (23) FIG. 20 is a schematic, circumferential cross-sectional view of the bearing assemblies of FIGS. 19A and 19B.
- (24) FIG. 21A is another schematic, circumferential cross-sectional view of the bearing assemblies of FIGS. 19A and 19B.
- (25) FIG. 21B is another schematic, circumferential cross-sectional view of the bearing assemblies of FIGS. 19A and 19B.
- (26) FIG. 21C is another schematic, circumferential cross-sectional view of the bearing assemblies of FIGS. 19A and 19B.
- (27) FIG. 21D is another schematic, circumferential cross-sectional view of the bearing assemblies of FIGS. 19A and 19B.
- (28) FIG. 22A is a schematic, axial cross-sectional view of the bearing assembly of FIG. 2B.
- (29) FIG. 22B is another schematic, axial cross-sectional view of the bearing assembly of FIG. 2B.
- (30) FIG. 23 is a schematic, circumferential cross-sectional view of another bearing assembly representative of the bearing assembly of FIG. 2A and/or the bearing assembly of FIG. 2B.
- (31) FIG. 24 is a schematic, circumferential cross-sectional view of another bearing assembly representative of the bearing assembly of FIG. 2A and/or the bearing assembly of FIG. 2B.
- (32) FIG. 25 is a schematic, axial cross-sectional view of another bearing assembly representative of the bearing assembly of FIG. 2A and/or the bearing assembly of FIG. 2B.
- (33) FIG. 26A is a schematic, axial view of another bearing assembly representative of the bearing assembly of FIG. 2A and/or the bearing assembly of FIG. 2B.
- (34) FIG. 26B is a schematic, radial cross-sectional view of the bearing assembly of FIG. 26A.
- (35) In general, the same reference numbers will be used throughout the drawings and accompanying written description to refer to the same or like parts. The figures are not substantially to scale.

DETAILED DESCRIPTION

- (36) As used herein, connection references (e.g., attached, coupled, connected, fixed, joined, etc.) may include intermediate members between the elements referenced by the connection reference and/or relative movement between those elements unless otherwise indicated. As such, connection references do not necessarily infer that two elements are directly connected and/or in fixed relation to each other. As used herein, stating that any part is in “contact” with another part is defined to mean that there is no intermediate part between the two parts.
- (37) Unless specifically stated otherwise, descriptors such as “first,” “second,” “third,” etc., are used herein without imputing or otherwise indicating any meaning of priority, physical order, arrangement in a list, and/or ordering in any way, but are merely used as labels and/or arbitrary names to distinguish elements for ease of understanding the disclosed examples. In some examples, the descriptor “first” may be used to refer to an element in the detailed description, while the same element may be referred to in a claim with a different descriptor such as “second” or “third.” In such instances, it should be understood that such descriptors are used merely for identifying those elements distinctly that might, for example, otherwise share a same name.
- (38) As used herein, “approximately” and “about” modify their subjects/values to recognize the

potential presence of variations that occur in real world applications. For example, “approximately” and “about” may modify dimensions that may not be exact due to manufacturing tolerances and/or other real world imperfections as will be understood by persons of ordinary skill in the art. For example, “approximately” and “about” may indicate such dimensions may be within a tolerance range of $\pm 10\%$ unless otherwise specified in the below description.

(39) “Including” and “comprising” (and all forms and tenses thereof) are used herein to be open ended terms. Thus, whenever a claim employs any form of “include” or “comprise” (e.g., comprises, includes, comprising, including, having, etc.) as a preamble or within a claim recitation of any kind, it is to be understood that additional elements, terms, etc., may be present without falling outside the scope of the corresponding claim or recitation. As used herein, when the phrase “at least” is used as the transition term in, for example, a preamble of a claim, it is open-ended in the same manner as the term “comprising” and “including” are open ended. The term “and/or” when used, for example, in a form such as A, B, and/or C refers to any combination or subset of A, B, C such as (1) A alone, (2) B alone, (3) C alone, (4) A with B, (5) A with C, (6) B with C, or (7) A with B and with C. As used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. Similarly, as used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. As used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. Similarly, as used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B.

(40) As used herein, singular references (e.g., “a”, “an”, “first”, “second”, etc.) do not exclude a plurality. The term “a” or “an” object, as used herein, refers to one or more of that object. The terms “a” (or “an”), “one or more”, and “at least one” are used interchangeably herein.

Furthermore, although individually listed, a plurality of means, elements or method actions may be implemented by, e.g., the same entity or object. Additionally, although individual features may be included in different examples or claims, these may possibly be combined, and the inclusion in different examples or claims does not imply that a combination of features is not feasible and/or advantageous.

(41) The terms “upstream” and “downstream” refer to the relative direction with respect to fluid flow in a fluid pathway. For example, “upstream” refers to the direction from which the fluid flows, and “downstream” refers to the direction to which the fluid flows.

(42) The terms “forward” and “aft” refer to relative positions within a turbine engine or vehicle, and refer to the normal operational attitude of the turbine engine or vehicle. For example, with regard to a turbine engine, forward refers to a position closer to an engine inlet and aft refers to a position closer to an engine nozzle or exhaust.

(43) As used herein, the terms “low,” “mid” (or “mid-level”), and “high,” or their respective comparative degrees (e.g., “lower” and “higher,” when applicable), when used with compressor, turbine, shaft, fan, or turbine engine components, each refers to relative pressures, relative speeds, relative temperatures, and/or relative power outputs within an engine unless otherwise specified. For example, a “low power” setting defines the engine configured to operate at a power output lower than a “high power” setting of the engine, and a “mid-level power” setting defines the engine configured to operate at a power output higher than a “low power” setting and lower than a “high power” setting. The terms “low,” “mid” (or “mid-level”) or “high” in such terms may additionally,

or alternatively, be understood as relative to minimum allowable speeds, pressures, or temperatures, or minimum or maximum allowable speeds, pressures, or temperatures relative to normal, desired, steady state, etc., operation of the engine.

(44) As used herein, the terms “axial” and “axially” refer to directions and orientations that extend substantially parallel to a centerline of the turbine engine and/or a bearing assembly. Moreover, the terms “radial” and “radially” refer to directions and orientations that extend substantially perpendicular to the centerline (e.g., a rotational axis) of the turbine engine and/or the bearing assembly. In addition, as used herein, the terms “circumferential” and “circumferentially” refer to directions and orientations that extend arcuately about the centerline of the turbine engine and/or the bearing assembly.

(45) As used herein, the terms “roller bearing” and “rolling element” encompasses spherical roller bearings, cylindrical roller bearings, tapered roller bearings, and the like.

(46) During engine operation, as described below, the low pressure shaft and the high pressure shaft rotate at high speeds and experience high axial loading. The high speeds and loads generate high bearing temperatures (e.g., greater than about 1000 British thermal units (BTUs)/minute) in the bearings that facilitate rotation of the shafts. That is, as the speed and/or the load on the shaft increases, the temperature of the bearing increases as well. The higher bearing temperatures require increased amounts of lubricant (e.g., oil) to cool the bearings and the hardware located in and around a sump area (e.g., the forward cavity and the aft cavity surrounding the bearing assembly). The requirement for more lubricant impacts heat load management of the engine because, for example, the required lubricant defines the lubricant line sizing and the heat exchanger sizing, among other components. Higher lubricant volumes required to cool the bearing assemblies also leads to increases in viscous heat generation in the bearings.

(47) In order to maintain low temperatures and/or lower the temperatures at the bearings, while not increasing lubricant volumes, the lubricant drains of the present disclosure are provided in the bearing assemblies to remove lubricant from the bearing assemblies and allow for continuous and/or predetermined flows of lubricant into and out of the bearing assembly. As a result, heat can be continuously or constantly taken from the bearing assembly and drained to one or more sumps or cavities in the system. By draining the lubricant from the bearing assemblies, the temperature of the bearings may be reduced, which enables smaller lubricant lines and/or heat exchangers to be associated with the bearing assemblies. Lubricant drains also reduce the viscous heat generation in the bearings by reducing the residence time of the lubricant within the bearing assembly.

(48) Disclosed bearing assemblies include an inner race (e.g., an inner ring), an outer race (e.g., an outer ring), roller bearings positioned between the inner race and the outer race, and a bearing cage positioned around the roller bearings. The bearing cage includes one or more conduits that define a flow path to drain a portion of the lubricant that is positioned in a cavity defined between adjacent roller bearings, the inner race, and the bearing cage. A first orifice of the conduit (e.g., an inlet, an outlet) is defined in an inner radial surface of the bearing cage and faces the cavity or cage landings of the inner race. A second orifice (e.g., an inlet, an outlet) of the conduit is defined in an outer radial surface or an outer axial surface of the bearing cage. The conduit may convey the lubricant itself or another fluid (e.g., air) that helps move the lubricant out of the cavity to another area of the bearing assembly or out of the bearing assembly.

(49) An inner radial surface of the bearing cage and/or the cage landings of the inner race may include different heights or depths to control the flow of the lubricant. For example, different depths of the bearing cage between the cage landings in the axial direction adjust a size of the cavity and, thus, the amount of lubricant that remains in the cavity. Additionally or alternatively, the cage may include grooves that guide the lubricant from the cavity to a circumferential portion between the cage landing and the bearing cage where the lubricant can enter the conduit to be moved to a different area of the bearing assembly or out of the bearing assembly.

(50) A size and/or a shape of the conduit helps control a rate at which the lubricant is drained from

the cavity. For example, the conduit may include a taper to create a pressure difference that pulls the lubricant through the conduit or pulls air through the conduit to facilitate removal of the lubricant from the cavity. Additionally or alternatively, the cross-sectional area may correlate with a desired rate at which the lubricant is to be drained from the cavity.

(51) The bearing assemblies drain lubricant to reduce residence time of the oil in the cavity and, in turn, reduce the viscous and frictional heat generation encountered by the lubricant. The reduced residence time allows for a faster turnover of the lubricant in the cavity, which allows the lubricant within the cavity to remain below a temperature threshold. The bearing assemblies of the present disclosure reduce the heat generated by the bearing by about twenty percent to about thirty percent, inclusive of the end points. The bearing assemblies of the present disclosure allow for increased shaft speeds, reduced oil supply to the bearings, reduced heat exchanger sizing, reduced lubricant supply line sizing, etc., as compared to bearing assemblies without such lubricant drains.

(52) FIG. 1 shows a schematic cross-sectional view of a gas turbine engine **10**. The gas turbine engine **10** defines an axial direction A extending parallel to a longitudinal, centerline axis **12** of the gas turbine engine **10**, a radial direction R, and a circumferential direction C extending about the axial direction A. The gas turbine engine **10** includes a fan section **14** and a core turbine engine **16** disposed downstream from the fan section **14**.

(53) The core turbine engine **16** depicted in the example of FIG. 1 includes an outer casing **18** that defines an annular inlet **20**. The core turbine engine **16** includes, in serial flow relationship, a compressor section including a low pressure (LP) compressor **22** and a high pressure (HP) compressor **24**, a combustion section **26**, a turbine section including a high pressure (HP) turbine **28** and a low pressure (LP) turbine **30**, and a jet exhaust nozzle section **32**. A high pressure (HP) shaft **34** drivingly connects the HP turbine **28** to the HP compressor **24**. A low pressure (LP) shaft **36** drivingly connects the LP turbine **30** to the LP compressor **22**. Accordingly, the LP shaft **36** and the HP shaft **34** are each rotary components, rotating about the longitudinal, centerline axis **12** in the circumferential direction C during operation of the gas turbine engine **10**.

(54) In order to support such rotary components, the gas turbine engine **10** includes a plurality of bearing assemblies **80** attached to various structural components within the gas turbine engine **10**. For example, the bearing assemblies **80** may be located to facilitate rotation of the LP shaft **36** and the HP shaft **34**. The bearing assemblies **80** may additionally, or alternatively, be located at any desired location along the LP shaft **36** and the HP shaft **34**. The bearing assemblies **80** may be used in combination with oil-lubricated bearing assemblies, as will be discussed in more detail herein.

(55) Referring still to FIG. 1, the fan section **14** includes a fan **38** having a plurality of fan blades **40** spaced apart and coupled to a disk **42**. The disk **42** is covered by a hub **48**. As depicted, the fan blades **40** extend radially outwardly from the disk **42** generally along the radial direction R. Each fan blade **40** is rotatable relative to the disk **42** about a pitch axis P because the fan blades **40** are operatively coupled to a pitch change mechanism **44**. The fan blades **40**, the disk **42**, and the pitch change mechanism **44** are together rotatable about the longitudinal, centerline axis **12** by the LP shaft **36** across a power gearbox **46**. The power gearbox **46** includes a plurality of gears for adjusting the rotational speed of the fan **38** relative to the LP shaft **36**. More particularly, the fan section **14** includes a fan shaft rotatable by the LP shaft **36** across the power gearbox **46**.

Accordingly, the fan shaft may also be considered to be a rotary component and is similarly supported by a bearing assembly **80**.

(56) The fan section **14** includes an annular fan casing or outer nacelle **50** that circumferentially surrounds the fan **38** and/or at least a portion of the core turbine engine **16**. The outer nacelle **50** is supported relative to the core turbine engine **16** by a plurality of circumferentially-spaced outlet guide vanes **52**. A downstream section **54** of the outer nacelle **50** extends over an outer portion of the core turbine engine **16** and defines a bypass airflow passage **56** between the downstream section **54** and the outer portion of the core turbine engine **16**.

(57) During operation of the gas turbine engine **10**, a volume of air **58** enters the gas turbine engine

10 through an inlet **60** of the outer nacelle **50** and/or the fan section **14**. As the volume of air **58** passes across the fan blades **40**, a first portion of air **62** of the air **58** is directed or routed into the bypass airflow passage **56** and a second portion of air **64** of the air **58** is directed or routed into a core air flow path **37**, or, more specifically, into the LP compressor **22**. The ratio between the first portion of air **62** and the second portion of air **64** is known as a bypass ratio. The pressure of the second portion of air **64** is then increased as it is routed through the high pressure (HP) compressor **24** and into the combustion section **26**, where it is mixed with fuel and burned to generate combustion gases **66**.

(58) The combustion gases **66** are routed through the HP turbine **28** where a portion of thermal and/or kinetic energy from the combustion gases **66** is extracted via sequential stages of HP turbine stator vanes **68** that are coupled to the outer casing **18** and HP turbine rotor blades **70** that are coupled to the HP shaft **34**, thus, causing the HP shaft **34** to rotate, thereby supporting operation of the HP compressor **24**. The combustion gases **66** are then routed through the LP turbine **30** where a second portion of thermal and kinetic energy is extracted from the combustion gases **66** via sequential stages of LP turbine stator vanes **72** that are coupled to the outer casing **18** and LP turbine rotor blades **74** that are coupled to the LP shaft **36**, thus, causing the LP shaft **36** to rotate, thereby supporting operation of the LP compressor **22** and/or rotation of the fan **38**.

(59) The combustion gases **66** are subsequently routed through the jet exhaust nozzle section **32** of the core turbine engine **16** to provide propulsive thrust. Simultaneously, the pressure of the first portion of air **62** is substantially increased as the first portion of air **62** is routed through the bypass airflow passage **56** before the first portion of air **62** is exhausted from a fan nozzle exhaust section **76** of the gas turbine engine **10**, also providing propulsive thrust. The HP turbine **28**, the LP turbine **30**, and the jet exhaust nozzle section **32** at least partially define a hot gas path **78** for routing the combustion gases **66** through the core turbine engine **16**.

(60) Although depicted and described in conjunction with the gas turbine engine **10** of FIG. **1**, aspects of the present disclosure may be incorporated into any other suitable gas turbine engine. For example, aspects of the present disclosure may be incorporated into a turbo fan engine (e.g., similar to the gas turbine engine **10** of FIG. **1**), a turboprop engine, a turboshaft engine, a turbojet engine, and/or a turbine generator.

(61) The gas turbine engine **10** depicted in FIG. **1** is by way of example only. In other examples, the gas turbine engine **10** may have a different configuration. For example, the fan **38** may be configured differently (e.g., as a fixed pitch fan) and further may be supported using another fan frame configuration. Moreover, in other examples, another number and/or configuration of compressors, turbines, shafts, or a combination thereof may be provided. In still other examples, aspects of the present disclosure may be incorporated into another turbine engine, such as turbofan engines, propfan engines, turbojet engines, turboprop, and/or turboshaft engines. Further, in still other examples, aspects of the present disclosure may be incorporated into another turbomachine, including, without limitation, a steam turbine, a centrifugal compressor, a turbocharger, stationary turbomachinery, other power generation turbomachines, or other rotating equipment.

(62) FIGS. **2A-2B** illustrate bearing assemblies **100**, **200** including a cage **102** that facilitates lubricant drainage from cavities defined between adjacent roller bearings, an inner race **104**, and the cage **102**. The bearing assembly **100** of FIG. **2A** and/or the bearing assembly **200** of FIG. **2B** can implement the bearing assembly **80** of FIG. **1**. In FIGS. **2A-2B**, the bearing assemblies **100**, **200** support rotation of a shaft **106** (e.g., the HP shaft **34** and/or the LP shaft **36** of FIG. **1**) with respect to another component **108**, such as another component of the gas turbine engine **10** of FIG. **1**.

(63) Referring now to FIG. **2A**, the bearing assembly **100** includes a roller bearing **110** (also referred to herein as a rolling element) positioned between the inner race **104** (e.g., an inner ring), and an outer race **112** (e.g., an outer ring) in a bearing housing **114**. The roller bearing **110** is one of a plurality of roller bearings spaced apart in a circumferential direction defined by the bearing

assembly **100**. The cage **102** is positioned around the roller bearing **110**, as well as the other roller bearings, between the inner race **104** and the outer race **112**. Specifically, the cage **102** includes a slot in which the roller bearing **110** is positioned and other, separate slots for the remainder of the plurality of roller bearings to maintain a separation between the roller bearings and evenly distribute the load that the roller bearings support. Accordingly, the slots defined by the cage **102** are defined intermittently in the circumferential direction between axial surfaces **116** (e.g., outer side surfaces) of the cage **102** to maintain relative positions of the roller bearings, such as the roller bearing **110**.

(64) The bearing assembly **100** may be coupled to the component **108** with a bearing housing **120**. In some examples, the bearing housing **120** includes a damper housing **122**. In such examples, the damper housing **122** is positioned radially outward of the bearing assembly **100** to provide a squeeze film damper (SFD) at the bearing assembly **100**. The bearing assembly **100** is supplied with a lubricant, such as oil, between the inner race **104** and the outer race **112** to facilitate rotation of the roller bearing **110**, the inner race **104**, and the cage **102**. For example, one or more lubricant passageways provide lubricant onto a riding surface of the roller bearing **110** defined by the inner race **104**, as discussed in further detail below.

(65) The cage **102** includes and/or forms lubricant drains to facilitate movement of the lubricant and/or removal of the lubricant from the bearing assembly **100**. Specifically, the lubricant drains of the cage **102** guide the lubricant out of cavities defined between adjacent roller bearings (e.g., the roller bearing **110** and another roller bearing adjacent to the roller bearing **110** in the circumferential direction), the inner race **104**, and the cage **102**. The lubricant drains of the cage **102** may be uniformly or nonuniformly spaced around the circumference of the cage **102**. For example, the lubricant drains are configured to cause the lubricant to flow to a different area of the bearing assembly **100** (e.g., onto a riding surface of the outer race **112**) and/or out of the bearing assembly **100** and into a sump **124** proximate axial surfaces of the bearing assembly **100** (e.g., axial surfaces **116**). Specifically, the lubricant drains of the cage **102** cause the lubricant to flow out of the bearing assembly **100** through one or more of the axial surface(s) **116**, between the cage **102** and the inner race **104**, and/or between the cage **102** and the outer race **112**. As a result, the cage **102** helps the lubricant maintain flow and reduces churning of the lubricant in the cavities that would otherwise lead to increased viscous and frictional heat generation.

(66) The sump **124** is in fluid connection with a lubricant treatment system (not shown). The lubricant treatment system may include a heat exchanger to maintain the temperature of the lubricant within a certain range. For example, the lubricant may generate and/or absorb heat in the bearing assembly **100** during operations, and the heat exchanger absorbs the heat from the lubricant to maintain certain material properties (e.g., a viscosity) of the lubricant. Advantageously, by reducing the heat generated and/or absorbed by the lubricant in the bearing assembly **100**, the lubricant drains of the cage **102** enable a size of the heat exchanger and/or other components (e.g., a supply line) of the lubricant treatment system to be reduced. After being treated by the heat exchanger, the lubricant is recirculated to the bearing assembly **100**. Specifically, the lubricant is fed into the bearing assembly **100** through one or more conduits in the inner race **104**. Although, it should be understood that the lubricant may be provided to the bearing assembly **100** in a variety of ways. The lubricant drains of the cage **102** are illustrated and discussed in further detail below.

(67) Referring now to FIG. 2B, the bearing assembly **200** is positioned in another example bearing housing **202** and includes another example outer race **204**. The outer race **204** includes at least a portion of a lubricant drain **206** that may be used in combination with the lubricant drain of the cage **102**, which will be discussed in further detail below. The lubricant drain **206** defines a passage that includes one or more holes **208**, a groove **210**, and one or more slots **212**. The one or more holes **208** are located in the outer race **204**. Each hole **208** extends radially outward from a hole inlet **208a** to a hole outlet **208b**. The hole **208** extends radially outward from an inner surface **204a** of the outer race **204** to an outer surface **204b** of the outer race **204**. Although a single hole **208** is

shown in FIG. 2B, multiple holes **208** may be provided in the outer race **204**. The holes **208** may be uniformly or nonuniformly spaced around the circumference of the outer race **204**.

(68) The groove **210** is located in the bearing housing **202**. The groove **210** is a groove formed in an inner surface **202a** of the bearing housing **202**. The groove **210** is an annular groove extending around the inner surface **202a** about the centerline axis **12** (FIG. 1). The one or more slots **212** are located in the bearing housing **202**. The one or more slots **212** are slots formed in the inner surface **202a** of the bearing housing **202**. Each slot **212** extends axially from an aft end to a forward end. Each slot **212** extends axially from a slot inlet **212a** to a slot outlet **212b**. Although a single slot **212** is shown in FIG. 2, multiple slots **212** may be provided in the bearing housing **202**. The slots **212** may be uniformly or nonuniformly spaced around the circumference of the bearing housing **202**.

(69) FIG. 3 illustrates a partial cross-sectional view of the bearing assembly **200** of FIG. 2B and the lubricant drain **206** taken through the section line 3-3 of FIG. 2B. As shown in FIG. 3, the hole **208** is inclined in a circumferential direction from the hole inlet **208a** to the hole outlet **208b**. Thus, the hole **208** extends radially outward (as shown in FIG. 2) and extends at an angle in the circumferential direction (FIG. 3). Although the circumferential incline is shown at an angle of about forty-five degrees with respect to the centerline axis **12** (FIG. 1), other angles are contemplated.

(70) FIG. 4 illustrates a plan view of the inner surface **202a** of the bearing housing **202**. As mentioned, the groove **210** is an annular groove that extends around the inner surface **202a**. The groove **210** may extend three-hundred and sixty degrees (360°) about the centerline axis **12** (FIG. 1) such that the groove **210** is circular in shape in a forward view or an aft end view. The slots **212** extend at an angle in the circumferential direction from the slot inlet **212a** to the slot outlet **212b**. Although the circumferential incline is shown at an angle of about forty-five degrees with respect to the centerline axis **12** (FIG. 1), other angles are contemplated. For example, the angle may be between about zero degrees and about eighty degrees with respect to the centerline axis **12**.

(71) As shown in FIG. 3, each hole outlet **208b** is offset circumferentially from an adjacent hole inlet **208a**. In some examples, the hole outlet **208b** and the hole inlet **208a** may be circumferentially aligned. Accordingly, and referring to FIGS. 2B, 3, and 4, the lubricant drain **206** allows for lubricant to flow through the outer race **204** and to the sump **124**. Due to the radial constraint of the bearing housing **202** (FIG. 2), the lubricant drain **206** changes direction to deposit lubricant in the sump **124**. The overall trajectory of the lubricant drain **206** is in the axial direction and the radial direction. That is, the inlet (e.g., hole inlet **208a**) of the lubricant drain **206** is radially inward and axially aft (also referred to as axially downstream) of the outlet (e.g., slot outlet **212b**) of the lubricant drain **206**. Thus, the passage defined by the lubricant drain **206** is a multi-directional passage. That is, the passage has a radially and circumferentially extending portion (e.g., hole **208**), a circumferentially extending, annular portion (e.g., groove **210**), and an axial and circumferentially extending portion (e.g., slot **212**).

(72) During operation, and referring to FIGS. 2A, 2B, 3, and 4, the lubricant is provided to the bearing assemblies **100**, **200**. The lubricant facilitates rotation of the roller bearing **110**. To enable lubricant to continually flow through the bearing assembly **100**, **200** and/or to allow used lubricant to flow from the bearing assembly **100**, **200**, the lubricant drain defined by the cage **102** and/or the lubricant drain **206** enables the lubricant to flow from the bearing assemblies **100**, **200** to the sump **124** (FIGS. 2A and 2B). Referring to FIG. 2A, the lubricant exits the bearing assembly **100** at least one of (a) between the inner race **104** and the cage **102**, (b) through one or more of the axial surface(s) **116** of the cage **102**, and/or (c) between the cage **102** and the outer race **112**. Referring to FIG. 2B, the lubricant exits the bearing assembly **200** through the hole inlet **208a**, travels through the hole **208** to the hole outlet **208b**. From the hole outlet **208b**, the lubricant enters the annular groove **210**. Once in the annular groove **210**, the lubricant may exit through one or more of the slots **212** and into the sump **124**.

(73) FIG. 5 is a schematic, axial cross-sectional view of a bearing assembly **500** including a cage

502 (e.g., a bearing cage) that may be utilized in the bearing assemblies **100, 200** of FIGS. 2A and/or 2B. Accordingly, the cage **502** of FIG. 5 is a representation of the cage **102** of FIGS. 2A-2B. As shown in FIG. 5, the cage **502** includes a first slot **504**, a second slot **506**, and an axial segment **508** (e.g., a portion of the cage **502** that extends in an axial direction A defined by the bearing assembly **100, 200**) between the first slot **504** and the second slot **506**. A first roller bearing **510** (e.g., the roller bearing **110** of FIGS. 2A, 2B, and 3) is positioned in the first slot **504**. A second roller bearing **512** is positioned in the second slot **506**. The first roller bearing **510** is adjacent to the second roller bearing **512**, and the first slot **504** is adjacent to the second slot **506**. During operation, the first roller bearing **510** is a leading roller bearing that is followed by the second roller bearing (e.g., a trailing roller bearing).

(74) The axial segment **508** of the cage **502** includes a conduit **514**. A lengthwise span of the conduit **514** is positioned between the roller bearings **510, 512** (e.g., between the slots **504, 506**) in a circumferential direction C defined by the bearing assembly **500**. The conduit **514** includes an inlet **516** defined at an inner radial surface **518** of the cage **502**. Further, the conduit **514** includes an outlet **520** defined at an outer radial surface **522** of the cage **502**. Accordingly, the conduit **514** extends in a radial direction R defined by the bearing assembly **500**. Furthermore, the inlet **516** and the outlet **520** are aligned in the same position in the circumferential direction C defined by the bearing assembly **500** (e.g., in the same geometric degree about the axial centerline of the bearing assembly **500** (e.g., the centerline axis **12** (FIG. 1)). Additionally, the inlet **516** and the outlet **520** are aligned in the same position in the axial direction A defined by the bearing assembly **500**. In some examples, the inlet **516** and the outlet **520** are offset in the circumferential direction C and/or the axial direction A, as discussed in further detail below. Accordingly, the conduit **514** may be oblique relative to the circumferential direction C, the axial direction A, and/or the radial direction R. The bearing assembly **500** may include more than one of the conduit **514** in the axial segment **508** spaced apart in the axial direction A. The cage **502** may include a plurality of the conduit **514** positioned intermittently in the circumferential direction C in respective axial segments, such as the axial segment **508**, between adjacent roller bearings, such as the roller bearings **510, 512**.

(75) Lubricant is positioned in a cavity **524** defined between the inner radial surface **518** of the cage **502**, the roller bearings **510, 512**, and an inner race of the bearing assembly **500** (e.g., the inner race **104** of FIGS. 2A-2B and 3). During operation, the lubricant in the cavity **524** encounters a centrifugal force from the cage **502**, the roller bearings **510, 512**, and the inner race. The centrifugal force causes the lubricant to enter the conduit **514** via the inlet **516** and, in turn, exit the conduit **514** via the outlet **520**. Additional lubricant being injected into the cavity **524** may also cause the lubricant to enter the conduit **514**. Accordingly, the conduit **514** prevents the lubricant from being trapped in the cavity **524** and generating heat via friction and/or churning, which leads to viscous heat. After exiting the conduit **514**, the lubricant helps facilitate rotation of the roller bearings **510, 512** along an outer race (e.g., the outer race **204** of FIG. 2B) and/or exits the bearing assembly **500** between the cage **502** and the outer race and/or through the outer race (e.g., through the hole **208**, the groove **210**, and the slot **212** of FIG. 2B).

(76) After exiting the bearing assembly **500**, the lubricant passes through a lubricant treatment system, which cools the lubricant to maintain certain material properties before returning the lubricant to the bearing assembly **500**. As discussed above, the conduit **514** reduces a temperature change (e.g., increase) that the lubricant encounters in the bearing assembly **500** during operation such that the size of components in, and/or a power consumption associated with, the lubricant treatment system can be reduced and/or material properties of the lubricant can be maintained for an extended period to enable the bearing assembly to operate with a reduced amount of the lubricant.

(77) The conduit **514** and other conduits disclosed herein that carry lubricant include a cross-sectional diameter of approximately 30-50 mils. However, the conduit **514** and the other conduits disclosed herein that carry lubricant may have another cross-sectional diameter based on the

desired flow rate of the lubricant and/or the amount of lubricant to be maintained in a cavity (e.g., the cavity **524**) defined between a cage (e.g., the cage **502**), an inner race (e.g., the inner race **104**), and adjacent roller bearings (e.g., the roller bearings **510**, **512**). Further, the conduit **514** and the other conduits disclosed herein that carry lubricant may have a varied cross-sectional area that narrows from an inlet (e.g., the inlet **516**) to an outlet (e.g., the outlet **520**) to create a higher pressure at the inlet and a lower pressure at the outlet that pulls the lubricant through the conduits. Moreover, the conduit **514** and other conduits disclosed herein that carry lubricant may have a circular cross-sectional area, an elliptical cross-sectional area, or another shaped cross-sectional area to convey the lubricant between the associated inlet and outlet.

(78) FIG. **6** is a schematic, axial cross-sectional view of another bearing assembly **600** including another cage **602** that may be utilized in the bearing assemblies **100**, **200** of FIGS. **2A** and/or **2B**. Accordingly, the cage **602** of FIG. **6** is a representation of the cage **102** of FIGS. **2A-2B**. As shown in FIG. **6**, the cage **602** includes the first slot **504** in which the first roller bearing **510** is positioned and the second slot **506** in which the second roller bearing **512** is positioned. Further, the cage **602** includes an axial segment **604**. The axial segment **604** includes an inner radial surface **606** and an outer radial surface **608**. Further, the axial segment **604** includes a weir **610** (e.g., a protrusion, a projection, a protuberance, etc.) defined at the inner radial surface **606**. A cavity **611** is defined between the roller bearings **510**, **512**, the inner radial surface **606** of the cage **602**, and an inner race (e.g., the inner race **104** of FIGS. **2A-2B** and **3**).

(79) The weir **610** extends inward in a radial direction **R** defined by the bearing assembly **600** (e.g., towards an axial centerline of the bearing assembly **600** (e.g., the centerline axis **12** (FIG. **1**))). Accordingly, the weir **610** defines a first radial height **H1** (e.g., a first radial depth) of the inner radial surface **606** of the cage **602** (e.g., a distance between the inner radial surface **606** and the outer radial surface **608**). Further, the inner radial surface **606** includes a first portion **612** between the weir **610** and the first slot **504** and a second portion **614** between the weir **610** and the second slot **506** in the circumferential direction **C** defined by the bearing assembly **600**. As such, the first portion **612** and the second portion **614** are on opposite sides of the weir **610** in the circumferential direction **C**. The first portion **612** and the second portion **614** define a second radial height **H2** (e.g., a second radial depth) of the inner radial surface **606** of the cage **602** (e.g., a distance between the inner radial surface **606** and the outer radial surface **608**) that is smaller than the first radial height **H1**. That is, the first radial height **H1** extends closer than the second radial height **H2** to a rotational axis of the cage **602** and/or the inner race (e.g., the inner race **104** of FIGS. **2A-2B** and **3**)).

Accordingly, the weir **610** protrudes further into the cavity **611** than the first portion **612** and the second portion **614** of the inner radial surface **606**. The weir **610** also includes a first inclined surface **622** that extends between a portion of the weir **610** that defines the first radial height **H1** and the first portion **612** of the inner radial surface **606**. Similarly, the weir **610** includes a second inclined surface **624** that extends between the portion of the weir **610** that defines the first radial height **H1** and the second portion **614** of the inner radial surface **606**. As such, the first inclined surface **622** and the second inclined surface **624** define a radial height increase from the second height **H2** to the first height **H1**.

(80) The cage **602** includes a conduit **616**, similar to the conduit **514** (FIG. **5**), that is in fluid connection with the cavity **611** via an inlet **618** defined in the weir **610** of the inner radial surface **606**. The cage **602** also includes an outlet **620** of the conduit **616** in the outer radial surface **608**. In FIG. **6**, the conduit **616** extends in the radial direction **R**. Furthermore, the inlet **618** and the outlet **620** are aligned in the same position in the circumferential direction **C** defined by the bearing assembly **600** (e.g., in the same geometric degree about the axial centerline of the bearing assembly **600** (e.g., the centerline axis **12** (FIG. **1**))). Additionally, the inlet **618** and the outlet **620** are aligned in the same position in the axial direction **A** defined by the bearing assembly **600**. As such, a first axial-radial plane **P1** defined by the conduit **616** intersects the axial centerline of the bearing assembly **600**. In some examples, the inlet **618** and the outlet **620** are offset in the circumferential

direction C and/or the axial direction A, as discussed in further detail below. Accordingly, the conduit **616** may be oblique relative to the circumferential direction C, the axial direction A, and/or the radial direction R. The bearing assembly **600** may include more than one of the conduit **616** spaced apart in the axial direction A.

(81) During operation, the conduit **616** reduces shear forces (e.g., churning) encountered by the lubricant and, thus, reduces the viscous heat generation. Additionally, the weir **610** controls the amount of lubricant that remains in the cavity **611** to lubricate the roller bearings **510**, **512** for rotation along the inner race (e.g., the inner race **104** of FIGS. 2A-2B). For example, the weir **610** increases the amount of lubricant that there is adjacent the first portion **612** and the second portion **614** (e.g., adjacent the roller bearings **510**, **512**, on opposite sides of the weir **610**) before the lubricant enters the conduit **616** via the inlet **618**. That is, the weir **610** creates two pockets of lubricant adjacent the first portion **612** and the second portion **614** that fill before the lubricant exits the cavity **611** such that a volume of the lubricant is maintained in the pockets for lubrication of the roller bearings **510**, **512**. Accordingly, the weir **610** enables the conduit **616** to drain the lubricant from the cavity **611** while also maintaining a certain amount of lubricant in the cavity **611** to lubricate the roller bearings **510**, **512**. Moreover, a height of the weir **610** is based on the volume of the lubricant that is to remain in the pockets for a particular bearing assembly. For example, the height of the weir **610** is based on a size and/or maximum rotational velocity of the roller bearings **510**, **512**, a shear strength of the cage **602**, properties of the lubricant, and/or thermal characteristics in the particular bearing assembly. Similarly, the slope of the first inclined surface **622** and/or the second inclined surface **624** and/or a circumferential location of transition between the first and second portions **612**, **614** and the inclined surfaces **622**, **624** is defined based on the volume of the lubricant that is to remain the pockets, the size and/or maximum rotational velocity of the roller bearings **510**, **512**, the shear strength of the cage **602**, the properties of the lubricant, and/or the thermal characteristics associated with the particular bearing assembly, as discussed further in association with FIG. 7. Therefore, although the weir **610** has a particular cross-sectional size, shape, and position in FIG. 6, it should be understood that the protrusion of the weir **610** into the cavity **611** may have a different size, shape, and/or position to control the amount of lubricant that remains in the cavity **611** during operation.

(82) FIG. 7 is a schematic, axial cross-sectional view of another bearing assembly **700** including another bearing cage **702** that may be utilized in the bearing assemblies **100**, **200** of FIGS. 2A and/or 2B. Accordingly, the cage **702** of FIG. 7 is a representation of the cage **102** of FIGS. 2A-2B. The cage **702** of FIG. 7 includes another weir **704** defined in an inner radial surface **706** of an axial segment **708** of the cage **702**. Specifically, the inner radial surface **706** defines a gradual change from the first radial height H1 of the weir **704** and the second radial height H2 of the inner radial surface **706** defined proximate the slots **504**, **506**. That is, the cage **702** includes an approximately constant slope along the inner radial surface **706** between the first radial height H1 and the slots **504**, **506**. In particular, the weir **704** includes a first inclined surface **710** that extends from the first slot **504** to a first circumferential edge **712** of a level portion **714** of the weir **704**. Similarly, the weir **704** includes a second inclined surface **716** that extends from the second slot **506** to a second circumferential edge **718** of the level portion **714**. The approximately constant slope between the respective slots **504**, **506** and the respective edges **712**, **718** of the level portion **714** reduces a drag force encountered by the weir **704** during a rotation of the cage **702**.

(83) The cage **702** includes a conduit **720** that extends from the inner radial surface **706** to an outer radial surface **726**, similar to the conduit **616** of FIG. 6. Accordingly, the bearing assembly **700** may include more than one of the conduit **720** in the axial segment **708** spaced apart in the axial direction A. Lubricant in a cavity **711** defined between the cage **702**, an inner race (e.g., the inner race **104** of FIGS. 2A-2B and/or 3), and the adjacent roller bearings **510**, **512** enters the conduit **720** via an inlet **722** defined in the level portion **714** of the weir **704**. Further, the lubricant exits the conduit **720** via an outlet **724** defined in the outer radial surface **726** of the axial segment **708**.

Similar to the conduit **616** of FIG. 6, a mid-portion of the conduit **720** is defined by the first axial-radial plane **P1**, which intersects the axial centerline of the bearing assembly (e.g., the centerline axis **12** (FIG. 1). Alternatively, the inlet **722** and the outlet **724** may be offset in the circumferential direction **C** and/or the axial direction **A**, as discussed in further detail below.

(84) Although the level portion **714** of the weir **704** in FIG. 7 has a larger width than the conduit **720** in the circumferential direction **C**, it should be understood that the level portion **714** may have approximately the same width in the circumferential direction **C** as the conduit **720**. Alternatively, the weir **704** may not include the level portion **714** and may be defined by the first and second inclined surfaces **710**, **716**, which either extend to the inlet **722** of the conduit **720** or meet at a shared edge aligned with the conduit in the circumferential direction **C**. In such examples, the shared edge may have a third height (not shown) that is greater than the first height and extends radially inward of the inlet **722** defined in the inner radial surface **706**.

(85) FIG. 8 illustrates a partial cross-sectional view of a bearing assembly **800** taken through the **8-8** section line (e.g., through the first axial-radial plane **P1**) of FIGS. 6 and/or 7. Accordingly, the bearing assembly **800** includes a cage **802**, which corresponds to the cage **602** of FIG. 6 or the cage **702** of FIG. 7. Moreover, the cage **802** is a representation of the cage **102** of FIGS. 2A-2B.

(86) As shown in FIG. 8, the bearing assembly **800** also includes an inner race **804** (e.g., the inner race **104** of FIGS. 2A-2B) and an outer race **806** (e.g., the outer race **112** of FIG. 2A, the outer race **204** of FIG. 2B). The roller bearing **512** is in contact with, and rolls along, an outer radial surface **810** of the inner race **804** (e.g., a first roller bearing riding surface, an inner raceway track, etc.) and an inner radial surface **812** of the outer race **806** (e.g., a second roller bearing riding surface, an outer raceway track, etc.) during operation. Furthermore, the inner race **804** includes cage landings **814** (e.g., shoulders, berms, axial walls, etc.) on opposite axial sides of the roller bearing **512**.

(87) The cage **802** is an inner race-guided cage such that circumferential segments **816** of the cage **802** are supported by the cage landings **814**. The circumferential segments **816** of the cage **802** are positioned on opposite axial sides of the roller bearing **512** and span along the circumferential direction **C** defined by the bearing assembly **800**. The cage **802** also includes an axial segment **818** between the circumferential segments **816** in the axial direction **A**. Accordingly, the axial segment **818** is aligned with the roller bearing **512** in the axial direction **A**. Moreover, the cage **802** includes a plurality of the axial segment **818** positioned intermittently in the circumferential direction **C** between adjacent roller bearings.

(88) An inner radial surface **820** of the axial segment **818** includes a weir **822** that extends between the cage landings **814** in the radial direction **R**. As shown in FIG. 8, the weir **822** includes the first radial height **H1**, and the circumferential segments **816** of the cage **802** include the second radial height **H2**. Moreover, the cage landings **814** are separated from the outer radial surface **810** of the cage **802** by a third distance **H3** (e.g., a third radial depth), which is less than the first radial height **H1** and greater than the second radial height **H2**. Although FIG. 8 shows a portion of the inner radial surface **820** of the axial segment **818** as approximately flat in the axial direction **A** on opposite axial sides of the weir **822** (e.g., between the weir **822** and the cage landings **814**), it should be understood that the weir **822** may extend approximately to the cage landings **814** in the axial direction **A**.

(89) The cage **802** also includes conduits **824** (e.g., the conduit **616** of FIG. 6, the conduit **720** of FIG. 7) to transport lubricant out of a cavity **826** defined between the roller bearing **512**, an adjacent roller bearing (e.g., the roller bearing **510** of FIGS. 5-7), the inner race **804**, and the cage **802**. Specifically, the lubricant enters the conduits **824** via inlets **828** defined on the weir **822** and exits the conduits **824** via outlets **830** defined on an outer radial surface **832** of the cage **802**. After exiting the conduits **824**, the lubricant may provide lubrication between the roller bearing **512** and the outer race **806** and/or exit the bearing assembly **800** and enter a sump (e.g., the sump **124** of FIGS. 2A and/or 2B) in fluid connection with a system that recirculates the lubricant to the bearing assembly **800**.

(90) In some examples, portions of the weir **822** between the inlets **828** of the conduits **824** in the axial direction A extend closer to the outer radial surface **810** of the inner race **804** than the inlets **828** of the conduits **824** to help the lubricant that is inside the cavity **826** remain adjacent to the roller bearing **512** or another roller bearing on an opposite side of the cavity **826** (e.g., the roller bearing **510**). The conduits **824** include a cross-sectional diameter of approximately 30-50 mils. However, the conduits **824** may have another cross-sectional diameter based on the desired flow rate of the lubricant and/or the amount of lubricant to be maintained in the cavity **826**. Further, the conduits **824** may have a varied cross-sectional area that narrows from the inlets **828** to the outlets **830** to create a higher pressure at the inlets **828** and a lower pressure at the outlets **830** that pulls the lubricant through the conduits **824**. Although three conduits **824** are shown in FIG. 8, it should be understood that the cage **802** may include one or more of the conduits **824**.

(91) FIG. 9 is a partial perspective view of the bearing assembly **800** of FIG. 8. As shown in FIG. 9, the outlets **830** are defined in the outer radial surface **832** of the axial segment **818** of the cage **802**. As such, lengthwise spans of the conduits **824** are positioned between the adjacent roller bearings **510**, **512** in the circumferential direction C defined by the bearing assembly **800**. Although the outlets **830** of FIG. 9 have a circular cross-sectional shape, the outlets **830** and, more generally, the conduits **824** may have any other cross-sectional shape, such as an elliptical cross-sectional shape, to help transport the lubricant out of the cavity **826** at a desired rate.

(92) FIG. 10 is another view (e.g., a radially outward view) of the inner radial surface **820** of the bearing assembly **800** of FIG. 8. As shown in FIG. 10, the inlets **828** of the conduits **824** are defined in the weir **822** of the inner radial surface **820**. The weir **822** may be tapered from a first thickness T1 to a second thickness T2 where the inlets **828** are defined.

(93) The weir **822** may be integral part of the cage **802** (e.g., formed integrally with the rest of the cage **802**). Alternatively, the weir **822** may be a separate part that is inserted into a slot defined in the axial segment **818** of the cage **802** and coupled to the cage **802**. For example, when the weir **822** is defined by a separate, insertable part initially, the slot for the insertable part can be drilled or cut into the axial segment **818** of the cage **802** via laser drilling. Further, an outer radial portion of the insertable part can be inserted through the slot at the inner radial surface **820** of the cage **802** and pushed through to be flush with the outer radial surface **832** (FIGS. 8-9). Furthermore, the weir **822** can be defined by an inner radial portion of the insertable part that extends past an inner radial end of the slot when the outer radial portion of the insertable part is flush with the outer radial surface **832**. As such, the inner radial portion of the insertable part is positioned between the roller bearings **510**, **512** in the circumferential direction C. The first thickness T1 may exceed a size of the slot through which the outer radial portion of the insertable part is inserted to prevent the insertable part from extending through the slot further than desired or specified. When the portion of the inserted part defining the first thickness T1 contacts the inner radial surface **820** of the axial segment **818**, the inserted part can be coupled to the cage **802**, such as via a press fit, welding, or another coupling operation. The second thickness T2 may correspond with the size of the slot such that the conduits **824** in the insertable part extend through the slot from the inner radial surface **820** to the outer radial surface **832** (FIG. 8). As such, the height of the weir **822** (e.g., the first height H1 (FIG. 8)) can be defined by the height of the insertable part between the first thickness T1 and the second thickness T2. Accordingly, different insertable parts may have different sizes to enable different lubricant draining and/or cage drains to be provided by the weir **822**. Thus, an insertable part having a certain size may be selected based on characteristics of the operation of the bearing assembly **800**.

(94) FIG. 11 illustrates a partial cross-sectional view of another bearing assembly **1100** including another cage **1102** that may be utilized in the bearing assembly **100** of FIG. 2A and/or the bearing assembly **200** of FIG. 2B. Accordingly, the cage **1102** is a representation of the cage **102** of FIGS. 2A-2B. The bearing assembly **1100** includes the inner race **804**, the outer race **806**, the roller bearing **512** positioned between the inner race **804** and the outer race **806**, and the cage **1102**

positioned around the roller bearing **512** between the inner race **804** and the outer race **806**. As discussed, during operation, the roller bearing **512** is in contact with, and rolls along, the outer radial surface **810** of the inner race **804** and the inner radial surface **812** of the outer race **806**. The inner race **804** also includes the cage landings **814**. The roller bearing **512** is positioned between the cage landings **814** in the axial direction A.

(95) The cage **1102** includes another weir **1104** protruding from an inner radial surface **1106** of an axial segment **1108** of the cage **1102**. The cage **1102** also includes conduits **1110** extending between inlets **1112** defined in the weir **1104** and outlets **1114** defined in outer axial surfaces **1116** of the cage **1102** (e.g., surfaces facing an environment external to the bearing assembly **1100** (e.g., the sump **124** (FIGS. 2A-2B)) in the axial direction A). Accordingly, the inlets **1112** are offset from the outlets **1114** in the axial direction A defined by the bearing assembly **1100**. That is, the conduits **1110** are angled in the first axial-radial plane P1 (FIGS. 6-7) and respective lengthwise spans of the conduits **1110** define a second axial-radial plane P2 and a third axial-radial plane P3, respectively. As shown in FIG. 11, the second axial-radial plane P2 and the third axial-radial plane P3 intersect in a cavity **1118** defined between the roller bearing **512**, an adjacent roller bearing (e.g., the roller bearing **510** (FIG. 5)), the inner race **804**, and the cage **1102**. As such, the conduits **1110** are oblique relative to the axial direction A and the radial direction R defined by the bearing assembly **1100**.

During operation, lubricant in the cavity **1118** flows through the conduits **1110** and exits the bearing assembly **1100**. In turn, the lubricant can enter a sump (e.g., the sump **124** (FIGS. 2A and 2B)) in fluid connection with a system that recirculates the lubricant to the bearing assembly **1100**.

(96) FIG. 12 illustrates a partial cross-sectional view of the bearing assembly **1100** of FIG. 11 taken through the 12-12 section line of FIG. 11 with the inner race **804** and the outer race **806** removed. Although the conduits **1110** would not be visible from the viewpoint through the 12-12 section line of FIG. 11, a perimeter of the conduits **1110** is shown by a dashed line for purposes of explanation. As shown in FIG. 12, the outlets **1114** of the conduits **1110** are defined in the outer axial surfaces **1116** of the cage **1102**. As a result, the lubricant that flows through the conduits **1110** exits the bearing assembly **1100**. As also shown in FIG. 12, the inlets **1112** and the outlets **1114** are aligned in the same position in the circumferential direction C defined by the bearing assembly **1100** (e.g., in the same geometric degree about the axial centerline of the bearing assembly **1100** (e.g., the centerline axis **12** (FIG. 1)). Alternatively, the conduit **1110** may be oblique relative to the circumferential direction C such that the outlet **1114** trails the inlet **1112** in a direction of rotation of the cage **1102**.

(97) FIG. 13 is a schematic, axial cross-sectional view of another bearing assembly **1300** including another bearing cage **1302** that may be utilized in the bearing assemblies **100**, **200** of FIGS. 2A and/or 2B. Accordingly, the cage **1302** of FIG. 13 is a representation of the cage **102** of FIGS. 2A-2B. As shown in FIG. 13, the cage **1302** includes an indentation **1304** (e.g., a scoop, a notch, a groove, etc.) in an inner radial surface **1306** of an axial segment **1308** of the cage **1302**. In FIG. 13, the indentation **1304** includes curvature. Alternatively, the indentation **1304** may be defined by another cut-out geometry (e.g., a triangular cut-out, a trapezoidal cut-out, a rectangular cut-out, etc.).

(98) The cage **1302** also includes a conduit **1310** in the axial segment **1308**. The conduit **1310** is fluidly coupled to a cavity **1312** defined between the roller bearings **510**, **512**, the inner race **804**, and the cage **1302** via an inlet **1314**. In particular, the inlet **1314** is defined in the indentation **1304** at the inner radial surface **1306** of the cage **1302**. An outlet **1316** of the conduit **1310** is defined in an outer radial surface **1318** of the axial segment **1308**. The bearing assembly **1300** may include more than one of the conduit **1310** spaced apart in the axial direction A.

(99) In FIG. 13, the outlet **1316** is offset from the inlet **1314** in the circumferential direction C. In particular, the outlet **1316** trails the inlet **1314** in a direction of rotation **1320** of the cage **1302** and the inner race **804**. As such, a fourth axial-radial plane P4 defined by a lengthwise span of the conduit **1310** does not intersect the axial centerline of the bearing assembly **1300** (e.g., the

centerline axis **12** (FIG. **1**). Alternatively, the outlet **1316** and the inlet **1314** may be aligned in the circumferential direction **C** and occupy an axial-radial plane that intersects the axial centerline of the bearing assembly **1300**, as discussed further in association with FIG. **14**.

(100) The indentation **1304** has a fourth height **H4** (e.g., a fourth radial depth, a distance between the outer radial surface **1318** and the indentation **1304**). Portions of the inner radial surface **1306** on opposite sides of the indentation **1304** in the circumferential direction **C** have the second height **H2**, which is greater than the fourth height **H4**. That is, the second height **H2** extends closer than the fourth height **H4** to a rotational axis of the cage **1302** and/or the inner race **804**. During operation, lubricant in the cavity **1312** encounters a centrifugal force from the rotation of the inner race **804** and/or the cage **1302**. Additionally, the lubricant may encounter a tangential force from the first roller bearing **510** and/or the second roller bearing **512**. In particular, the lubricant in the cavity **1312** of FIG. **13** encounters a tangential force from the first roller bearing **510** that drives the lubricant towards the inner radial surface **1306** of the cage **1302** as the roller bearings **510**, **512** rotate counter-clockwise. Similarly, lubricant in a cavity on an opposite side of the second roller bearing **512** may encounter a tangential force from the second roller bearing **512**. As the centrifugal and/or tangential forces drive the lubricant in the cavity **1312** radially outwards, the lubricant fills the indentation **1304** and enters the conduit **1310** via the inlet **1314**. The indentation **1304** provides an increased area for collection and draining of the lubricant. As such, the indentation **1304** enables the lubricant to drain out of the cavity **1312** at a faster rate. A portion of the indentation **1304** around the inlet **1314** may have an increased depth in the cage **1302** (e.g., extend further radially outwards) than other areas of the indentation **1304** to help guide the lubricant that is in the indentation **1304** towards the inlet **1314**.

(101) The lubricant exits the conduit **1310** via the outlet **1316** at the outer radial surface **1318** of the cage **1302**. During operation, the circumferentially offset position of the outlet **1316** relative to the inlet **1314** enables the rotational inertia of the lubricant to help move the lubricant through the conduit **1310** in addition to the centrifugal force from the rotation of the cage **1302**. After exiting the conduit **1310**, the lubricant can provide lubrication between the roller bearing **510** and the outer race **806** (not shown) and/or exit the bearing assembly **1300** between the cage **1302** and the outer race **806** and/or through the outer race **806** (e.g., the outer race **204** of FIG. **2B**).

(102) FIG. **14** is a schematic, circumferential cross-sectional view of another bearing assembly **1400** including another bearing cage **1402** that may be utilized in the bearing assemblies **100**, **200** of FIGS. **2A** and/or **2B**. Accordingly, the cage **1402** of FIG. **14** is a representation of the cage **102** of FIGS. **2A-2B**. As shown in FIG. **14**, the cage **1402** includes the indentation **1304** in an inner radial surface **1404** of an axial segment **1406** of the cage **1402**. The cage **1402** also includes conduits **1408** in the axial segment **1406** that are fluidly coupled to the cavity **1312** via inlets **1410**. Outlets **1412** of the conduits **1408** are defined in an outer radial surface **1414** of the axial segment **1406**.

(103) In FIG. **14**, the outlets **1412** and the inlets **1410** of the respective conduits **1408** are aligned (e.g., in a same position) in the circumferential direction **C** defined by the bearing assembly **1400**. Additionally, the outlets **1412** and the inlets **1410** of the respective conduits **1408** are aligned in the axial direction **A**. As such, the first axial-radial plane **P1** (FIGS. **6-7**) defined by the conduits **1408** intersects an axial centerline of the bearing assembly **1400** (e.g., the centerline axis **12** (FIG. **1**)). At least a portion of the indentation **1304** has the fourth radial height **H4** between the inner radial surface **1404** and the outer radial surface, and circumferential segments **1416** of the cage **1402** have the second radial height **H2**. Moreover, the cage landings **814** are separated from the outer radial surface **1414** of the cage **1402** by the third radial distance **H3**, which is greater than the fourth radial height **H4** and the second radial height **H2**.

(104) The bearing assembly **1400** of FIG. **14** operates similar to the bearing assembly **1300** of FIG. **13**. However, the conduits **1408** are not offset in the circumferential direction **C** like the conduit **1310** of FIG. **13**. Advantageously, the indentation **1304** helps guide the lubricant in the cavity **1312**

into the conduits **1408**. Further, portions of the indentation **1304** positioned around the inlets **1410** may have an increased depth into the cage **1402** (e.g., extend further radially outwards than other areas of the indentation **1304**) such that the centrifugal force continually moves the lubricant in the indentation **1304** towards the inlets **1410**.

(105) FIG. **15** is a schematic, circumferential cross-sectional view of another bearing assembly **1500** including another bearing cage **1502** that may be utilized in the bearing assemblies **100**, **200** of FIGS. **2A** and/or **2B**. Accordingly, the cage **1502** of FIG. **15** is a representation of the cage **102** of FIGS. **2A-2B**. As shown in FIG. **15**, the cage **1502** includes the indentation **1304** in an inner radial surface **1504** of an axial segment **1506**. The cage **1502** also includes conduits **1508** in the axial segment **1506**. The conduits **1508** are fluidly coupled to the cavity **1312** via inlets **1510**. Outlets **1512** of the conduits **1508** are defined in outer axial surfaces **1514** of the cage **1502**. Accordingly, the conduits **1508** extend from the axial segment **1506** through circumferential segments **1516** to the outer axial surfaces **1514**. As such, the outlets **1512** and the inlets **1510** of the conduits **1508** are offset (e.g., not aligned, in a different position) in an axial direction **A** defined by the bearing assembly **1500**. As such, the conduits **1508** are oblique relative to the axial direction **A**. The outlets **1512** and the inlets **1510** are aligned in a same position in the circumferential direction **C** defined by the bearing assembly **1500**. Alternatively, the outlets **1512** may also be offset from the inlets **1510** in the circumferential direction **C** similar to the conduit **1310** in the bearing assembly **1300** of FIG. **13**, as discussed further in association with FIG. **17**.

(106) The indentation **1304** collects lubricant in the cavity **1312** that moves radially outward as a result of centrifugal and tangential forces encountered during operation of the bearing assembly **1500**. As discussed, the indentation **1304** helps guide the lubricant into the conduits **1508**. Further, the lubricant exits the conduits **1508** via the outlets **1512**. Thus, the lubricant is directed out of the bearing assembly **1500** via the conduits **1508**. In turn, the lubricant can be discarded and/or flow through a thermal treatment and recirculation system (not shown) that returns the lubricant to the bearing assembly **1500**. As a result, the bearing cage **1502** minimizes or otherwise reduces viscous and frictional heat generation from the lubricant by preventing the lubricant from building up in the cavity **1312**.

(107) FIG. **16** illustrates a partial cross-sectional view of the bearing assembly **1500** of FIG. **15** taken through the **16-16** section line of FIG. **15**. Although the conduits **1508** would not be visible from the viewpoint through the **16-16** section line of FIG. **15**, a perimeter of the conduits **1110** is shown by a dashed line for purposes of explanation. As shown in FIG. **16**, the outlets **1512** of the conduits **1508** are defined in the outer axial surfaces **1514** of the cage **1502**. As a result, the lubricant that flows through the conduits **1508** is discarded from the bearing assembly **1500**. As also shown in FIG. **16**, the inlets **1510** and the outlets **1512** of the conduits **1508** are aligned in the same position in the circumferential direction **C** defined by the bearing assembly **1500**. As such, the conduits **1508** are positioned in the first axial-radial plane **P1**, which intersects the axial centerline of the bearing assembly **1500** (e.g., the centerline axis **12** (FIG. **1**)).

(108) In FIG. **16**, a center portion of the cross-sectional area of the inlets **1510** trails a peak depth of the indentation **1304** in the inner radial surface **1504** in the direction of rotation **1320**. As a result, the cross-sectional areas of the inlets **1510** are positioned in a trailing portion of the indentation **1304** such that the rotational inertia of the lubricant causes the lubricant to move towards the inlets **1510** at a faster rate. As also shown in FIG. **16**, a lengthwise span of the conduits **1508** is positioned between the roller bearings **510**, **512** in the circumferential direction **C**.

(109) FIG. **17** is a schematic, axial cross-sectional view of another bearing assembly **1700** including another bearing cage **1702**. The cage **1702** of FIG. **17** is another example implementation of the cage **102** of FIGS. **2A-2B**. As shown in FIG. **17**, the cage **1702** includes the indentation **1304** in an inner radial surface **1704** of an axial segment **1706**. As also shown in FIG. **17**, the cage **1702** includes a conduit **1708**. An inlet **1710** of the conduit **1708** is defined in the indentation **1304**, and an outlet **1712** of the conduit **1708** is defined in an outer axial surface **1714** of the cage **1702**.

(110) In FIG. 17, the outlet 1712 is offset from the inlet 1710 in the circumferential direction C defined by the bearing assembly 1700. In particular, the outlet 1712 trails the inlet 1710 in the direction of rotation 1320 of the cage 1702 and the inner race 804. As such, the lengthwise span of the conduit 1708 is positioned in the second axial-radial plane P2, which does not intersect the axial centerline of the bearing assembly 1700 (e.g., the centerline axis 12 (FIG. 1)). During operation, the circumferentially offset position of the outlet 1712 relative to the inlet 1710 enables a rotational inertia of the lubricant to help move the lubricant through the conduit 1708 in addition to the centrifugal force from the rotation of the cage 1702.

(111) FIG. 18 is another view (e.g., a radially outward view) of the bearing assembly 1700 of FIG. 17. Although FIG. 18 is described with reference to the bearing assembly 1700 of FIG. 17, at least some of FIG. 18 and the related description also communicates details associated with the indentation 1304 in the bearing assemblies 1300, 1400, 1500 of FIGS. 13-16. As shown in FIG. 18, the indentations 1304 are positioned in the axial segments 1706 between adjacent roller bearings 510, 512, 1802. As also shown in FIG. 18, the inlets 1710 of the conduits 1708 (FIG. 17) are defined in the indentations 1304. Further, the conduits 1708 extend to the outer axial surfaces 1714 of the cage 1702 where the outlets 1712 (FIG. 17) are defined.

(112) In the illustrated example of FIG. 18, the inlets 1710 include a circular cross-sectional shape (elliptical cross-sectional shape of inlets 1710 in FIG. 18 is due to the position of the inlets 1710 in the indentation 1304 and the partial perspective shown by FIG. 18). Accordingly, the conduits 1708 and the outlets 1712 also include the circular cross-sectional geometry. Alternatively, the inlets 1710, the outlets 1712, and the conduits 1708 may include an elliptical cross-sectional shape. For example, the cross-sectional shape of the conduits 1708 and the associated inlets 1710 and outlets 1712 is defined based on desired and/or predefined flow characteristics for the lubricant being directed out of the cavity 1312. Thus, the cross-sectional shape of the conduits 1708 and the associated inlets 1710 and outlets 1712 help maintain a desired and/or predefined amount of lubricant in the cavity 1312 while also directing lubricant out of the cavity 1312 to reduce the heat that the lubricant generates and/or collects (e.g., by about 20% compared to known bearing assemblies) during operation.

(113) FIG. 19A is another view (e.g., a radially outward view, a schematic view) of another example bearing assembly 1900 including a cage 1902 that may be utilized in the bearing assemblies 100, 200 of FIGS. 2A and/or 2B. In particular, FIG. 19A illustrates an inner radial surface 1904 of the cage 1902. The inner radial surface 1904 of the cage includes grooves 1906 (e.g., slots, indents, raised portions, etc.) and support surfaces 1908 that extend radially inward of the grooves 1906 (e.g., closer to an axial centerline of the bearing assembly 1900 (e.g., the centerline axis 12 (FIG. 1))).

(114) First portions 1910 of the support surfaces 1908 are positioned around perimeters of respective slots 1912 in which roller bearings 510, 512, 1802, 1914 are positioned. Second portions 1916 of the support surfaces 1908 are positioned around outer axial edges 1918 of circumferential segments 1920 of the cage 1902. In particular, the circumferential segments 1920 of the cage 1902 are defined on opposite axial sides of the roller bearings 510, 512, 1802, 1914 and span in the circumferential direction C defined by the bearing assembly 1900. As such, outer axial surfaces of the second portions 1916 of the support surfaces 1908 define a portion of outer axial surfaces 1919 of the cage 1902. Further, third portions 1922 of the support surfaces 1908 are positioned intermittently between the first portions 1910 and the second portions 1916. In particular, the third portions 1922 of the support surfaces 1908 are positioned in the circumferential segments 1920 and connect to the first portions 1910 and the second portions 1916. The third portions 1922 of the support surfaces 1908 enable axial portions 1924 of the grooves 1906 (e.g., portions of the grooves 1906 in the axial segments of the cage 1902) to be contiguous with circumferential portions 1926 of the grooves 1906 (e.g., portions of the grooves 1906 in the circumferential segments 1920). In FIG. 19A, segments of the circumferential portions 1926 of the grooves 1906 are defined

intermittently and separated by the third portions **1922** of the support surfaces **1908**. Alternatively, the circumferential portions **1926** may be contiguous around an inner circumference defined by the circumferential segments **1920** of the cage **1902**, as discussed in association with FIG. **19B**.

(115) The grooves **1906** define passageways for lubricant to flow out of a cavity defined between adjacent roller bearings **510**, **512**, **1802**, **1914**, the inner race **804** (not shown) and the cage **1902** (e.g., the cavity **524** of FIGS. **5-6**, the cavity **826** of FIGS. **8** and **11**, the cavity **1312** of FIGS. **13-15**). In particular, during operation, the centrifugal force and/or tangential force encountered by the lubricant moves the lubricant into the axial portions **1924** of the grooves **1906**. Filling of the axial portions **1924** causes the lubricant to flow into the circumferential portions **1926** of the grooves **1906**. Further, inlets of conduits are defined in surfaces of the circumferential portions **1926** of the grooves **1906** such that the lubricant enters the conduits. Outlets of the conduits are defined in an outer radial surface and/or the outer axial surfaces **1919** of the cage **1902**. As such, the grooves **1906** and the conduits in fluid connection with the grooves **1906** enable the lubricant to exit the bearing assembly **1900** to prevent the lubricant from generating and/or encountering additional viscous and/or frictional heat that may otherwise alter material properties associated with the lubricant.

(116) Furthermore, the support surfaces **1908** support and/or guide movement of the cage **1902** and the roller bearings **510**, **512**, **1802**, **1914** along the inner race **804**. In particular, the support surfaces **1908** contact, or are positioned closer to, the cage landings **814** of the inner race **804** (FIG. **8**) to help support a radial load of the cage **1902**. When the support surfaces **1908** are not in direct contact with the cage landings **814** of the inner race **804**, a thin layer of lubricant or another fluid (e.g., air) is positioned between the inner race **804** and the support surfaces **1908** to transfer loads between the inner race **804** and the support surfaces **1908**. The first portions **1910** of the support surfaces **1908** may include weirs (e.g., the weir **610** (FIG. **6**), the weir **704** (FIG. **7**), the weir **822** (FIGS. **8** and/or **10**), the weir **1104** (FIGS. **11** and/or **12**)) proximate the roller bearings **510**, **512**, **1802**, **1914** to maintain a certain amount of the lubricant on or near a surface of the roller bearings **510**, **512**, **1802**, **1914**. Additionally, the second portions **1916** of the support surfaces **1908** may be positioned around outer axial surfaces of the inner race **804** to maintain an alignment of the cage **1902** and the roller bearings **510**, **512**, **1802**, **1914** relative to the inner race **804**.

(117) FIG. **19B** is another view (e.g., a radially outward view, a schematic view) of another example bearing assembly **1950** including a cage **1952** that may be utilized in the bearing assemblies **100**, **200** of FIGS. **2A** and/or **2B**. In particular, FIG. **19B** illustrates an inner radial surface **1954** of the cage **1952** similar to FIG. **19A**. The cage **1952** includes support surfaces **1956** and grooves **1958**. In particular, the support surfaces **1956** include the first portion **1910** positioned around the slots **1912** and the second portion **1916** positioned around the outer axial edges **1918** of the circumferential segments **1920** of the cage **1952**. That is, the support surfaces **1956** of FIG. **19B** do not include the third portion **1922** of the support surfaces **1908** of FIG. **19A**. The grooves **1958** include the axial portions **1924** and circumferential portions **1960**. The circumferential portions **1960** are contiguous with the axial portions **1924** and extend around a circumference of the inner radial surface **1954** on opposite axial sides of the roller bearings **510**, **512**, **1802**, **1914**.

(118) FIG. **20** illustrates a cross-sectional view of a bearing assembly **2000** representative of the bearing assemblies **1900**, **1950** taken through the 20-20 section line of FIGS. **19A** and **19B**. As shown in FIG. **20**, the bearing assembly **2000** includes a cage **2002** (e.g., the cage **1902** of FIG. **19A**, the cage **1952** of FIG. **19B**), the inner race **804**, the outer race **806**, and the roller bearing **1914** positioned in one of the slots **1912** of the cage **2002**, which is shown by a dashed line as it would be positioned in this view. The cage **2002** includes support surfaces **2004** (e.g., the support surfaces **1908** of FIG. **19A**, the support surfaces **1956** of FIG. **19B**) and grooves **2006** (e.g., the grooves **1906** of FIG. **19A**, the grooves **1958** of FIG. **19B**). The slots **1912** are positioned adjacent to the support surfaces **2004** and connect the grooves **2006** on opposite axial sides of the roller bearing **1914**. As shown in FIG. **20**, the support surfaces **2004** include the first portion **1910** and the second

portion **1916**. The support surfaces **2004** may also include the third portion **1922** (FIG. **19A**). The first portion **1910** of the support surfaces **2004** extends past axial ends **2005**, **2007** of the roller bearing **1914** and is positioned over inner axial portions **2009** of the cage landings **814** of the inner race **804**. A portion of the first portion **1910** of the support surfaces **2004** may have the first height **H1**, while the cage landings **814** are separated from an outer radial surface **2014** of the cage **2002** by the third distance **H3** (FIG. **8**) and extend between the cage landings **814** in the axial direction **A**. That is, the first portion **1910** of the support surfaces **2004** may include a weir (e.g., the weir **610** (FIG. **6**), the weir **704** (FIG. **7**), the weir **822** (FIGS. **8** and/or **10**), the weir **1104** (FIGS. **11** and/or **12**)) to maintain lubricant proximate the roller bearing **1914**.

(119) The grooves **2006** include the axial portions **1924** (FIGS. **19A** and **19B**) and circumferential portions **2008** (e.g., the circumferential portions **1926** of FIG. **19A**, the circumferential portions **1960** of FIG. **19B**). The axial portions **1924** are positioned on a circumferential side of the first portion **1910** of the support surfaces **2004** opposite the slot **1912** in which the roller bearing **1914** is positioned. The circumferential portions **2008** are contiguous with at least one of the axial portions **1924** and extend in the circumferential direction **C** between the first portion **1910** and the second portion **1916** of the support surfaces **2004** in the axial direction **A**.

(120) As also shown in FIG. **20**, the bearing assembly **2000** includes a lubricant spout **2010** that provides lubricant to a cavity **2012** defined between the roller bearing **1914**, the roller bearing **1802** (FIGS. **18**, **19A**, and **19B**), the inner race **804**, and the cage **2002**. The bearing assembly **2000**, and other bearing assemblies described herein, may include any number of the lubricant spouts extending through the inner race **804** and positioned intermittently in the circumferential direction **C**.

(121) During operation, the lubricant in the cavity **2012** is driven into the axial portion **1924** (FIGS. **19A** and **19B**) of the grooves **2006** between the roller bearings **1914**, **1802** (FIGS. **18**, **19A**, and **19B**). The lubricant in the axial portion **1924** of the grooves **2006** flows in an axial direction **A** into the circumferential portions **2008**. For example, the lubricant in the axial portion **1924** of the grooves **2006** flows in the axial direction **A** as a result of a rotational inertia of the lubricant and/or the cavity **2012** receiving more lubricant via the lubricant spout **2010**. Additionally or alternatively, the first portion **1910** of the support surfaces **1908** can include a bend in the circumferential direction **C** that causes the lubricant to flow in axial directions **A** towards the respective circumferential portions **2008** of the grooves **2006** as a result of a rotational inertia associated with the lubricant. Additionally or alternatively, a mid-axial section of the axial portions **1924** can extend closer to the axis about which the cage **2002** rotates than outer axial sections of the axial portions **1924** to cause the lubricant to flow towards the circumferential portions **2008**. Further, conduits (not shown in this view) in fluid connection with the circumferential portions **2008** of the grooves **2006** transport the lubricant to the outer radial surface **2014** and/or outer axial surfaces **2016** of the cage **2002**. In some examples, inlets of conduits may also be defined in the axial portion **1924** of the groove **2006**, similar to the conduits **1110** (FIGS. **11-12**), the conduit **1310** (FIG. **13**), the conduits **1408** (FIG. **14**), the conduits **1508** (FIGS. **15-16**), and/or the conduits **1708** (FIG. **17**).

(122) FIG. **21A** illustrates a first example cross-sectional view of the bearing assembly **2000** (e.g., the bearing assemblies **1900**, **1950** of FIGS. **19A** and/or **19B**) taken through the **21-21** section line of FIGS. **19A** and **19B**. As shown in FIG. **21A**, the cage **2002** includes conduits **2102** extending between the circumferential portions **2008** of the grooves **2006** and the outer axial surfaces **2016**. As a result, the lubricant can enter the conduits **2102** via inlets **2104** defined in the circumferential portions **2008** of the grooves **2006**. Further, the lubricant can exit the conduits **2102** and, more generally, the bearing assembly **2000** via outlets **2106** defined in the outer axial surfaces **2016**. Thus, the outlets **2106** are offset from the inlets **2104** in the axial direction **A**. Accordingly, the conduits **2102** are oblique relative to the axial direction **A** and the radial direction **R**. The inlets **2104** and the outlets **2106** may additionally or alternatively be offset in the circumferential

direction C. Additionally, the conduits **2102** are aligned with the roller bearing **512** in circumferential direction C defined by the bearing assembly **2000**. After flowing through the outlets **2106**, the lubricant can flow through a lubricant treatment system and/or flow through one or more conduits that return the lubricant to the bearing assembly **2000** (e.g., via the lubricant spout **2010**). (123) FIG. **21B** illustrates another example cross-sectional view of the bearing assembly **2000** (e.g., the bearing assemblies **1900**, **1950** of FIGS. **19A** and/or **19B**) taken through the **21-21** section line of FIGS. **19A** and **19B**. As shown in FIG. **21B**, the cage **2002** includes conduits **2112** extending between the circumferential portions **2008** of the grooves **2006** and the outer radial surface **2014**. As a result, the lubricant can enter the conduits **2112** via inlets **2114** defined in the circumferential portions **2008** of the grooves **2006**, and the lubricant can exit the conduits **2112** via outlets **2116** defined in the outer radial surface **2014**. Thus, the outlets **2116** are aligned with the inlets **2114** in the axial direction A. Additionally, the conduits **2112** are aligned with the roller bearing **512** in circumferential direction C defined by the bearing assembly **2000**. After flowing through the outlets **2106**, the lubricant can exit the bearing assembly **2000** and/or provide lubrication between the outer race **806** and the roller bearing **512**.

(124) FIG. **21C** illustrates another example cross-sectional view of the bearing assembly **2000** (e.g., the bearing assemblies **1900**, **1950** of FIGS. **19A** and/or **19B**) taken through the **21-21** section line of FIGS. **19A** and **19B**. As shown in FIG. **21C**, the cage **2002** includes conduits **2122** extending between the circumferential portions **2008** of the grooves **2006** and the outer radial surface **2014**. Inlets **2124** of the conduits **2122** are offset from outlets **2126** of the conduits **2122** in the axial direction A. In particular, the inlets **2124** are positioned closer than the outlets **2126** to the roller bearing **512** in the axial direction A. As a result, the conduits **2122** carry the lubricant radially outward and away from the roller bearing **512** in the axial direction A. In some examples, the conduits **2122** cause a first portion of the lubricant that flows through the outlet **2126** to exit the bearing assembly **2000** and cause a second portion of the lubricant that flows through the outlet **2126** to provide lubrication between the outer race **806** and the roller bearing **512**. In some such examples, the first portion of the lubricant is greater than the second portion of the lubricant.

(125) FIG. **21D** illustrates another example cross-sectional view of the bearing assembly **2000** (e.g., the bearing assemblies **1900**, **1950** of FIGS. **19A** and/or **19B**) taken through the **21-21** section line of FIGS. **19A** and **19B**. As shown in FIG. **21D**, the cage **2002** includes conduits **2132** extending between the circumferential portions **2008** of the grooves **2006** and the outer radial surface **2014**. Inlets **2134** of the conduits **2132** are offset from outlets **2136** of the conduits **2132** in the axial direction A. In particular, the outlets **2136** are positioned closer than the inlets **2134** to the roller bearing **512** in the axial direction A. As a result, the conduits **2132** carry the lubricant radially outward and towards the roller bearing **512** in the axial direction A. In some examples, the conduits **2132** cause a first portion of the lubricant that flows through the outlet **2136** to exit the bearing assembly **2000** and cause a second portion of the lubricant that flows through the outlet **2136** to provide lubrication between the outer race **806** and the roller bearing **512**. In some such examples, the second portion of the lubricant is greater than the first portion of the lubricant.

(126) FIGS. **22A-22B** illustrate example cross-sectional views of the bearing assembly **2000** (e.g., the bearing assemblies **1900**, **1950** of FIGS. **19A** and/or **19B**) taken through the **22-22** section line of FIG. **20**. In particular, in FIG. **22A**, the cross-section of the bearing assembly **2000** is representative of the bearing assembly **1900** of FIG. **19A** and includes the third portion **1922** of the support surfaces **1908**. In FIG. **22B**, the cross-section of the bearing assembly **2000** is representative of the bearing assembly **1950** of FIG. **19B** and does not include the third portion **1922** of the support surfaces **1908**.

(127) As shown in FIGS. **22A-22B**, the cage **2002** includes a conduit **2202** extending between the circumferential portions **2008** of the grooves **2006** and the outer radial surface **2014**. An inlet **2204** of the conduit **2202** is offset relative to an outlet **2206** of the conduit **2202** in the circumferential direction C. As such, the conduit **2202** is oblique in the radial direction R. In particular, the outlet

2206 trails the inlet **2204** in a direction of rotation **2207** of the cage **2002** (e.g., a clockwise rotation, the direction of rotation **1320** (FIG. 13)). As a result, the rotational inertia of the lubricant helps the lubricant flow into and through the conduit **2202** at a faster rate. The outlet **2206** may also be offset from the inlet **2204** in the axial direction A.

(128) In FIGS. 22A-22B, the inlet **2204** is aligned with the roller bearing **512** in the circumferential direction C, and the outlet **2206** is positioned between the roller bearing **512** and a trailing roller bearing (e.g., the roller bearing **510** (FIGS. 19A-19B)) in the circumferential direction C.

Alternatively, the inlet **2204** and the outlet **2206** may both be positioned between the roller bearings **510**, **512**, or the inlet **2204** may be positioned between the roller bearings **512**, **1802** and the outlet may be aligned with the roller bearing **512** in the circumferential direction C.

(129) During operation, a centrifugal force on and/or a rotational inertia of the lubricant in the circumferential portion **2008** of the grooves **2006** pushes the lubricant through the inlet **2204** into the conduit **2202**. As shown in FIG. 22A, a leading edge **2208** of the third portion **1922** of the support surfaces **1908** is aligned with (e.g., flush with) a trailing portion **2210** of the inlet **2204**. As such, the leading edge **2208** may help guide the lubricant radially outwards from the circumferential portion **2008** of the grooves **2006** into the conduit **2202**.

(130) FIG. 23 is a schematic, circumferential cross-sectional view of another bearing assembly **2300** including a cage **2302** that may be utilized in the bearing assembly **100** of FIG. 2A and/or the bearing assembly **200** of FIG. 2B. Accordingly, the cage **2302** is representative of the cage **102** of FIGS. 2A-2B. As shown in FIG. 23, the bearing assembly **2300** also includes the roller bearing **512** positioned between an inner race **2304** and the outer race **806**. Lubricant is positioned in a cavity **2306** between the cage **2302**, the inner race **2304**, the roller bearing **512**, and an adjacent roller bearing (e.g., the roller bearing **510** (FIG. 5)).

(131) The inner race **2304** also includes a cage landing **2308** (e.g., a shoulder, a raised axial end, a rim, etc.). The cage landing **2308** includes a first portion **2310** proximate the cavity **2306** and a second portion **2312** bordering (e.g., on an axial side of) the first portion **2310** opposite the cavity **2306**. The second portion **2312** of the cage landing **2308** extends to an outer axial surface **2314** of the inner race **2304**. The first portion **2310** of the cage landing **2308** is approximately level in the axial direction A. The second portion **2312** of the cage landing **2308** is angled to define an increasing separation between the cage **2302** and the inner race **2304** towards the outer axial surface **2314**. That is, the bearing assembly **2300** includes a first separation between the first portion **2310** of the cage landing **2308** and an inner radial surface **2326** of the cage **2302**. Further, the bearing assembly **2300** includes a second separation between the second portion **2312** of the cage landing **2308** and the inner radial surface of the cage **2302** at an end of the cage landing **2308** (e.g., adjacent to the outer axial surface **2314**) that is greater than the first separation. A plurality of the second portion **2312** are defined intermittently in the circumferential direction C. As a result, outer axial portions of the cage **2302** are supported between adjacent second portions **2312**.

Moreover, the second portion **2312** of the cage landing **2308** defines an approximately constant adjustment (e.g., slope) between the first separation and the second separation. Thus, the first portion **2310** and the second portion **2312** of the cage landing **2308** form an angle that is greater than 180 degrees (°) across a transition point **2315** from the first portion **2310** to the second portion **2312**. Accordingly, the second portion **2312** of the cage landing **2308** is oblique relative to the axial direction A.

(132) In FIG. 23, the cage **2302** includes a tapered conduit **2316** positioned in a circumferential portion **2318** of the cage **2302**. In particular, the circumferential portion **2318** of the cage **2302** is aligned with the cage landing **2308** in the axial direction A. An inlet **2320** of the tapered conduit **2316** is defined at an outer radial surface **2322** of the cage **2302**. Alternatively, the inlet **2320** of the tapered conduit **2316** may be defined in an outer axial surface **2323** of the cage **2302**. An outlet **2324** of the tapered conduit **2316** is defined at the inner radial surface **2326**. The outlet **2324** of the tapered conduit **2316** and the second portion **2312** of the cage landing **2308** are aligned in the axial

direction A. The inlet **2320** and the outlet **2324** are also aligned in the axial direction A. Additionally, the inlet **2320** and the outlet **2324** are aligned in the circumferential direction C and positioned between the roller bearing **512** and an adjacent roller bearing (e.g., the roller bearing **510** (FIG. 5)) in the circumferential direction C. Alternatively, the inlet **2320** and the outlet **2324** may be offset in the axial direction A and/or the circumferential direction C, as discussed in further detail below.

(133) The inlet **2320** includes a first cross-sectional area, and the outlet **2324** includes a second cross-sectional area smaller than the first cross-sectional area. Moreover, the change in cross-sectional area between the inlet **2320** and the outlet **2324** is approximately constant. During operation, the tapered conduit **2316** encounters a first fluid pressure **P1** proximate the inlet **2320** and a second fluid pressure **P2** less than the first fluid pressure **P1** proximate the outlet **2324**. The difference between the first fluid pressure **P1** at the inlet **2320** and the second fluid pressure **P2** at the outlet **2324** causes a fluid (e.g., air) in a region radially outward of the cage **2302** to flow radially inward toward the cage landing **2308**. Furthermore, the cavity **2306** includes the first fluid pressure **P1** or another fluid pressure that is greater than the second fluid pressure **P2**.

(134) As shown in FIG. 23, the transition point **2315** is positioned between the outlet **2324** of the tapered conduit **2316** and the cavity **2306** in the axial direction A. The transition point **2315** between the first portion **2310** and the second portion **2312** of the cage landing **2308** also defines an area of transition between the first pressure **P1** and the second pressure **P2**. As such, a pressure between the second portion **2312** of the cage landing **2308** and the cage **2302** is less than a pressure between the first portion **2310** of the cage landing **2308** and the cage **2302**. As a result, the pressure difference causes the lubricant in the cavity **2306** to flow out of the cavity **2306** towards the lower pressure between the second portion **2312** of the cage landing **2308** and the cage **2302**. Further, the fluid exiting the tapered conduit **2316** proximate the second portion **2312** of the cage landing **2308** helps drive the lubricant out of the bearing assembly **2300**. In turn, the lubricant can be discarded and/or flow through a thermal treatment and/or recirculation system that returns the lubricant to the bearing assembly **2300**. Thus, the bearing assembly **2300** prevents the lubricant from being trapped in the cavity **2306** and continuously encountering and/or generating viscous and/or frictional heat. A size, shape, and/or position of the tapered conduit **2316**, the angle defined by the first and second portions **2310**, **2312** of the cage landing **2308**, and/or a distance between the transition point **2315** and the outlet **2324** may be adjusted based on a rate at which the lubricant is to exit the cavity **2306**.

(135) FIG. 24 is a schematic, circumferential cross-sectional view of another bearing assembly **2400** including a cage **2402** that may be utilized in the bearing assembly **100** of FIG. 2A and/or the bearing assembly **200** of FIG. 2B (e.g., the cage **102** of FIGS. 2A-2B). As shown in FIG. 24, the cage **2402** includes a tapered conduit **2404** extending between an inlet **2406** defined in an outer radial surface **2408** of the cage **2402** and an outlet **2410** defined in an inner radial surface **2412** of the cage **2402**. In FIG. 24, the inlet **2406** and the outlet **2410** are aligned in the circumferential direction C and offset in the axial direction A. In particular, the outlet **2410** is defined between the inlet **2406** and the roller bearing **512** in the axial direction A.

(136) In FIG. 24, the bearing assembly **2400** also includes an inner race **2414** and a cavity **2416** defined between the inner race **2414**, the cage **2402**, the roller bearing **512**, and an adjacent roller bearing (e.g., the roller bearing **510** (FIG. 5)). The inner race **2414** includes a cage landing **2418** aligned with at least a portion of the tapered conduit **2404** in the axial direction A. The cage landing **2418** includes a first portion **2420** and a second portion **2422**. A first axial end of the first portion **2420** borders the cavity **2416** and a second axial end of the first portion **2420** borders the second portion **2422**. Similar to the first and second portions **2310**, **2312** of the cage landing **2308** of FIG. 23, the first portion **2420** is approximately level in the axial direction A and the second portion **2422** is angled to increase a distance between the cage **2402** and the cage landing **2418** away from the first portion **2420** in the axial direction A. That is, the second portion **2422** includes a sharper

height increase than the first portion **2420**. A transition point **2424** in the cage landing **2418** between the first portion **2420** and the second portion **2422** (e.g., the second axial end of the first portion **2420**) is closer than the outlet **2410** to the cavity **2416** in the axial direction A. Additionally, similar to the second portion **2312** of the cage landing **2308** of FIG. 23, a plurality of the second portion **2422** are defined intermittently in the circumferential direction C.

(137) During operation, a pressure difference between the inlet **2406** and the outlet **2410** causes a fluid (e.g., air) to flow from an outer radial and/or axial area of the cage **2402** to an area between the cage **2402** and the second portion **2422** of the cage landing **2418**. Additionally, the pressure difference between the cavity **2416** and the area between the cage **2402** and the second portion **2422** of the cage landing **2418** causes the lubricant in the cavity to flow between the cage **2402** and the cage landing **2418**. The fluid flowing through the outlet **2410** helps drive the lubricant out of the area between the cage **2402** and the second portion **2422** of the cage landing **2418** such that the lubricant can be discarded and/or undergo thermal treatment before returning to the bearing assembly **2400**.

(138) FIG. 25 is a schematic, axial cross-sectional view of another bearing assembly **2500** including another cage **2502** that may be utilized in the bearing assembly **100** of FIG. 2A and/or the bearing assembly **200** of FIG. 2B (e.g., the cage **102** of FIGS. 2A-2B). As shown in FIG. 25, the cage **2502** includes another tapered conduit **2504** having an inlet **2506** defined in an outer radial surface **2508** of the cage **2502** and an outlet **2510** defined in an inner radial surface **2512** of the cage **2502**. The inlet **2506** and the outlet **2510** are offset in the circumferential direction C. In particular, the inlet **2506** defines a leading portion (e.g., a leading end) of the tapered conduit **2504** in a direction of rotation **2514** of the cage **2502**. Accordingly, the outlet **2510** defines a trailing portion (e.g., a trailing end) of the tapered conduit **2504** in the direction of rotation **2514**.

(139) In FIG. 25, the inlet **2506** is positioned between the roller bearings **510**, **512** in the circumferential direction C. The outlet **2510** is aligned with the roller bearing **512** in the circumferential direction C. In some examples, the outlet **2510** is positioned between the roller bearings **510**, **512** in the circumferential direction C. Additionally or alternatively, the inlet **2506** may be aligned with the roller bearing **510** in the circumferential direction C.

(140) During operation, the reduction in cross-sectional area from the inlet **2506** to the outlet **2510** in the tapered conduit **2504** forms a pressure difference that causes fluid (e.g., air) that is flowing along the outer radial surface **2508** to flow through the tapered conduit **2504** to the inner radial surface **2512**. After exiting the tapered conduit **2504**, the fluid encounters the lubricant in a slanted portion of a cage landing **2516** (e.g., the second portion **2312** of FIG. 23, the second portion **2422** of FIG. 24). As a result, a mixture of the fluid and the lubricant exits the bearing assembly **2500** between the cage **2502** and the cage landing **2516**.

(141) FIGS. 26A-26B illustrate another bearing assembly **2600** including another cage **2602** that may be utilized in the bearing assembly **100** of FIG. 2A and/or the bearing assembly **200** of FIG. 2B (e.g., the cage **102** of FIGS. 2A-2B). In particular, FIG. 26A is a schematic, axial cross-sectional view of the bearing assembly **2600**. FIG. 26B is a partial perspective view of a radial cross-sectional view of the bearing assembly **2600**.

(142) The cage **2602** includes a tapered conduit **2604** extending between an inlet **2606** defined in an outer axial surface **2608** of the cage **2602** and an outlet **2610** defined in an inner radial surface **2612** of the cage **2602**. The inlet **2606** includes a first cross-sectional area, and the outlet **2610** includes a second cross-sectional area smaller than the first cross-sectional area. The cross-sectional area in the tapered conduit **2604** gradually changes between the first cross-sectional area and the second cross-sectional area to form a pressure differential that pulls fluid (e.g., air) at the outer axial surface **2608** to the inner radial surface **2612**. In turn, the fluid encounters the lubricant between the inner radial surface **2612** and a slanted portion of a cage landing (e.g., the second portion **2312** of the cage landing **2308** of FIG. 23, the second portion **2422** of the cage landing **2418** of FIG. 24). As a result, a mixture of the fluid and the lubricant exits the bearing assembly

2600 between the cage **2602** and the cage landing **2516**.

(143) In some examples, the bearing assembly includes first means for guiding. For example, the first means for guiding is implemented by the inner race **104, 804, 2304, 2414**.

(144) In some examples, the bearing assembly includes second means for guiding. For example, the second means for guiding is implemented by the outer race **112, 204, 806**.

(145) In some examples, the bearing assembly includes means for rolling between the first means for guiding and the second means for guiding. For example, the means for rolling is implemented by the roller bearings **510, 512, 1802, 1914**.

(146) In some examples, the bearing assembly includes means for containing the means for rolling. For example, the means for containing is implemented by the cage **502, 602, 702, 802, 1102, 1302, 1402, 1502, 1702, 1902, 2002, 2302, 2402, 2502, 2602**.

(147) In some examples, the bearing assembly includes means for transporting oil out of a cavity between a first means for rolling, a second means for rolling the inner race, and the means for containing. For example, the means for transporting is implemented by the conduit **514** (FIG. 5), the conduit **616** (FIG. 6), the conduit **720** (FIG. 7), the conduits **824** (FIGS. 8-10), the conduits **1110** (FIGS. 11-12), the conduit **1310** (FIG. 13), the conduits **1408** (FIG. 14), the conduits **1508** (FIG. 15), the conduits **1708** (FIG. 17), the grooves **1906, 2006** (FIGS. 19A-19B, 20) and the conduits **2102, 2112, 2122, 2132, 2202** (FIGS. 21A-21D, 22A-22B), and/or the tapered conduits **2316, 2404, 2504, 2604** (FIGS. 23, 24, 25, 26A-26B) and the cage landings **2308, 2418** (FIGS. 23 and 24).

(148) In some examples, the cage includes means for maintaining at least a portion of the oil in the cavity. For example, the means for maintaining is implemented by the weir **610** (FIG. 6), the weir **704** (FIG. 7), the weir **822** (FIGS. 8 and 10), and/or the weir **1104** (FIGS. 11-12).

(149) In some examples, the cage includes means for collecting at least a portion of the oil at an end of the means for transporting. For example, the means for collecting is implemented by the indentation **1304** (FIGS. 13-18) and the grooves **1906, 2006** (FIGS. 19A-19B, 20, 21A-21D, and 22A-B).

(150) From the foregoing, it will be appreciated that systems, methods, apparatus, and articles of manufacture have been disclosed that drain lubricant out of a cavity defined between adjacent roller bearings, an inner race, and a bearing cage to reduce heat viscous and/or frictional heat generated by the lubricant during operation. As a result, the lubricant may help cool the bearing assembly. Further, by draining the lubricant from the bearing assemblies, the temperature of the bearings may be reduced, which enables smaller lubricant lines and/or heat exchangers to be associated with the bearing assemblies.

(151) Lubricant draining bearing assemblies are disclosed herein. Further aspects of the present disclosure are provided by the subject matter of the following clauses:

(152) An apparatus comprising a first race, a second race, roller bearings positioned between the first race and the second race to enable the first race to rotate relative to the second race, and a cage positioned around the roller bearings between the first race and the second race, the cage including a first radial surface, a second radial surface, and an axial surface, the first radial surface facing the first race, the second radial surface facing the second race, the axial surface facing away from the roller bearings, the cage including at least one conduit extending between the first radial surface and at least one of the second radial surface or the axial surface, the conduit defining a flow path for a fluid out of a cavity between the first race, the roller bearings, and the cage.

(153) A bearing assembly comprising an inner race, an outer race, roller bearings positioned between the inner race and the outer race, and a cage positioned around the roller bearings between the inner race and the outer race, the cage including a conduit to enable a fluid to flow out of a cavity defined between the inner race, the roller bearings, and the cage, the cage including an inner radial surface, the inner radial surface including a first portion having a first depth and a second portion having a second depth different from the first depth.

- (154) A bearing assembly comprising first means for guiding, second means for guiding, means for rolling between the first means for guiding and the second means for guiding, and means for containing the means for rolling, the means for containing including means for transporting lubricant out of a cavity between the means for rolling, the first means for guiding, and the means for containing.
- (155) An apparatus comprising an inner race, an outer race, roller bearings positioned between the inner race and the outer race, and a cage positioned around the roller bearings between the inner race and the outer race, a first portion of the cage defined between the roller bearings in the axial direction, a second portion of the cage defined outside of the roller bearings in the axial direction, the cage including an inner radial surface, an outer axial surface, and an outer radial surface, the cage including a conduit extending from the inner radial surface in the second portion of the cage to the outer axial surface or the outer radial surface.
- (156) A bearing assembly comprising an inner race, an outer race, roller bearings positioned between the inner race and the outer race, and a cage positioned around the roller bearings between the inner race and the outer race, the cage including an inner radial surface, an outer radial surface, and a side surface facing an axial direction defined by the bearing assembly, the cage including a conduit having an outlet in the inner radial surface and an inlet in the outer radial surface or the side surface, the conduit tapered to define a first cross-sectional area proximate the inner radial surface and a second cross-sectional area proximate the outer radial surface or the side surface, the second cross-sectional area greater than the first cross-sectional area.
- (157) A bearing assembly comprising an inner race, an outer race, roller bearings positioned between the inner race and the outer race, and a cage positioned around the roller bearings between the inner race and the outer race, the cage including an inner radial surface, an outer radial surface, and a side surface facing an axial direction defined by the bearing assembly, the cage including a tapered conduit extending between (a) the inner radial surface and (b) the outer radial surface or the side surface.
- (158) The apparatus of any preceding clause, wherein the first radial surface includes a first portion having a first height and a second portion having a second height different from the first height.
- (159) The apparatus of any preceding clause, wherein the first height extends closer to a rotational axis of the first race than the second height, and wherein the first portion includes an inlet that fluidly couples the cavity to the conduit.
- (160) The apparatus of any preceding clause, wherein the first race includes cage landings on opposite sides of the roller bearings in an axial direction, and wherein the first portion of the first radial surface is positioned between the cage landings in the axial direction.
- (161) The apparatus of any preceding clause, wherein the first height extends closer to a rotational axis of the first race than the second height, and wherein the second portion includes an inlet that fluidly couples the cavity to the conduit.
- (162) The apparatus of any preceding clause, wherein the first race includes cage landings on opposite sides of the roller bearings in an axial direction, and wherein the second portion of the first radial surface is positioned between the cage landings in the axial direction.
- (163) The apparatus of any preceding clause, wherein the roller bearings are adjacent roller bearings, wherein a lengthwise span of the conduit is positioned between the adjacent roller bearings in a circumferential direction.
- (164) The apparatus of any preceding clause, wherein the roller bearings include a leading roller bearing adjacent to a trailing roller bearing, wherein the conduit defines an inlet in the first radial surface and an outlet in the second radial surface or the axial surface, and wherein the outlet is positioned closer than the inlet to the trailing roller bearing in a circumferential direction.
- (165) The apparatus of any preceding clause, wherein the conduit carries the fluid out of the cavity.
- (166) The apparatus of any preceding clause, wherein the conduit is substantially perpendicular to an axis around which the first race rotates.

(167) The apparatus of any preceding clause, wherein the conduit is oblique relative to at least one of a radial direction or an axial direction.

(168) The bearing assembly of any preceding clause, wherein the first depth extends closer to a rotational axis of the cage than the second depth, wherein the inner race includes cage landings on opposite sides of the roller bearings in an axial direction defined by the bearing assembly, wherein the first portion is positioned between the cage landings in the axial direction, and wherein the second portion is at least partially aligned with the cage landings in the axial direction.

(169) The bearing assembly of any preceding clause, wherein the second depth extends closer to a rotational axis of the cage than the first depth, wherein the inner race includes cage landings on opposite sides of the roller bearings in an axial direction defined by the bearing assembly, wherein the first portion is positioned between the cage landings, and wherein the second portion is at least partially aligned with the cage landings in the axial direction.

(170) The bearing assembly of any preceding clause, wherein the cage includes an outer radial surface and an outer axial surface, wherein the conduit includes an inlet defined in the inner radial surface and an outlet defined in the outer radial surface or the outer axial surface.

(171) The bearing assembly of any preceding clause, wherein the roller bearings are adjacent roller bearings, wherein the conduit includes an inlet and an outlet in the cage between the adjacent roller bearings in a circumferential direction defined by the bearing assembly.

(172) The bearing assembly of any preceding clause, wherein the inlet and the outlet are offset in a circumferential direction defined by the bearing assembly.

(173) The bearing assembly of any preceding clause, wherein the inlet and the outlet are offset in an axial direction defined by the bearing assembly.

(174) The bearing assembly of any preceding clause, wherein the means for containing includes means for maintaining at least a portion of the lubricant in the cavity.

(175) The bearing assembly of any preceding clause, wherein the means for containing includes means for collecting at least a portion of the lubricant at an end of the means for transporting.

(176) The apparatus of any preceding clause, wherein the roller bearings include a first roller bearing, and wherein the first radial surface includes an edge proximate the first roller bearing, wherein the second portion of the first radial surface includes a first section and a second section, the second section between the first section and the edge, wherein the first section includes a sharper height increase than the second section.

(177) The apparatus of any preceding clause, wherein the roller bearings include a first roller bearing, and wherein the first radial surface includes an edge proximate the first roller bearing, wherein the second portion of the first radial surface defines an approximately constant height increase extending from the edge to the first portion of the first radial surface.

(178) The apparatus of any preceding clause, wherein the cage includes a main body and an insert positioned in a void in the main body, wherein the insert defines the first portion of the first radial surface and the main body defines the second portion of the first radial surface.

(179) The apparatus of any preceding clause, wherein the cage includes an axial groove defined in the inner radial surface in the first portion of the cage and extending in the axial direction, and a circumferential groove defined in the inner radial surface in the second portion of the cage and extending in a circumferential direction, wherein an end of the axial groove is in fluid communication with the circumferential groove, and wherein the conduit is in fluid communication with the circumferential groove.

(180) The apparatus of any preceding clause, wherein the roller bearings include a first roller bearing, a second roller bearing, and a third roller bearing, wherein the axial groove includes a first axial groove between the first roller bearing and the second roller bearing, and a second axial groove between the second roller bearing and the third roller bearing, and wherein the circumferential groove is in fluid communication with the first axial groove and the second axial groove.

(181) The apparatus of any preceding clause, wherein the roller bearings include a first roller bearing, a second roller bearing, and a third roller bearing, wherein the axial groove includes a first axial groove between the first roller bearing and the second roller bearing, and a second axial groove between the second roller bearing and the third roller bearing, wherein the circumferential groove includes a first circumferential groove in fluid communication with the first axial groove and a second circumferential groove in fluid communication with the second axial groove, and wherein the inner radial surface of the second portion includes a radially inward extension that separates the first circumferential groove from the second circumferential.

(182) The apparatus of any preceding clause, wherein the axial groove includes a passageway between radially inward extensions, and wherein the radially inward extensions are positioned around the roller bearings.

(183) The apparatus of any preceding clause, wherein the inner race includes landings on opposite sides of an inner raceway track in contact with the roller bearings, wherein the radially inward extensions define a first separation between the cage and the landings, and wherein the circumferential groove defines a second separation between the cage and the landings, the second separation greater than the first separation.

(184) The apparatus of any preceding clause, wherein the conduit includes an inlet defined in the inner radial surface and an outlet defined in the outer radial surface.

(185) The apparatus of any preceding clause, wherein the inlet is aligned with the outlet in the axial direction.

(186) The apparatus of any preceding clause, wherein the inlet is positioned closer to the roller bearing than the outlet in the axial direction.

(187) The apparatus of any preceding clause, wherein the outlet is positioned closer to the roller bearing than the inlet in the axial direction.

(188) The apparatus of any preceding clause, wherein the outlet is positioned rearward of the inlet in a direction of rotation of the cage.

(189) The apparatus of any preceding clause, wherein the conduit includes an inlet defined in the inner radial surface and an outlet defined in the outer axial surface.

(190) The apparatus of any preceding clause, wherein the outlet is positioned rearward of the inlet in a direction of rotation of the cage.

(191) The bearing assembly of any preceding clause, wherein the inner race includes a track and a landing, wherein the roller bearings roll along the track adjacent the landing, and wherein an outer radial surface of the landing or the inner radial surface of the cage includes an angled portion to increase a separation between the outer radial surface of the landing and the inner radial surface of the cage away from the roller bearings.

(192) The bearing assembly of any preceding clause, wherein the landing includes the angled portion and a support portion adjacent to the angled portion, the support portion positioned between the angled portion and the roller bearing.

(193) The bearing assembly of any preceding clause, wherein a transition in the landing from the support portion to the angled portion is defined between the outlet of the conduit and the roller bearings in the axial direction.

(194) The bearing assembly of any preceding clause, wherein the conduit and the angled portion causes a pressure difference that pulls fluid through the conduit, and wherein the pressure difference pulls the fluid and lubricant from a cavity between the roller bearings, the cage, and the inner race in the axial direction between the cage and the landing.

(195) The bearing assembly of any preceding clause, wherein a first area defined between the cage and the inner race at the angled portion forms a first pressure, and wherein a second area between the cage and the outer race forms a second pressure, wherein a third area between the roller bearings, the cage, and the inner race forms a third pressure, the second pressure and the third pressure greater than the first pressure.

(196) The bearing assembly of any preceding clause, wherein the outlet of the conduit is in a leading position relative to the inlet in a direction of rotation of the cage.

(197) The assembly of any preceding clause, wherein the roller bearings include a first roller bearing and a second roller bearing, wherein the outlet of the conduit is aligned with the first roller bearing in a circumferential direction defined by the bearing assembly, and wherein the inlet of the conduit is aligned between the first roller bearing and the second roller bearing in the circumferential direction.

(198) The bearing assembly of any preceding clause, wherein the roller bearings include a first roller bearing and a second roller bearing, wherein the outlet of the conduit is aligned with the first roller bearing in a circumferential direction defined by the bearing assembly, and wherein the inlet of the conduit is aligned with the second roller bearing in the circumferential direction.

(199) The bearing assembly of any preceding clause, wherein the inlet and the outlet are offset in a radial direction, an axial direction, and a circumferential direction defined by the bearing assembly.

(200) The apparatus of any preceding clause, wherein the conduit carries the fluid out of the cavity.

(201) The apparatus of any preceding clause, wherein the first height extends closer to a surface of the first race that contacts the roller bearings than the second height, and wherein the first portion includes an inlet that fluidly couples the cavity to the conduit.

(202) The apparatus of any preceding clause, wherein at least one of the inlet or the outlet includes a circular cross-sectional area.

(203) The apparatus of any preceding clause, wherein at least one of the inlet or the outlet includes an elliptical cross-sectional area.

(204) The apparatus of any preceding clause, wherein the conduit is tapered.

(205) The apparatus of any preceding clause, wherein the conduit includes a first cross-sectional area at the inlet and a second cross-sectional area at the outlet, and wherein the first cross-sectional area is greater than the second cross-sectional area.

(206) The apparatus of any preceding clause, wherein the first height of the first radial surface defines a weir extending past an outer radial surface of the inner race.

(207) The apparatus of any preceding clause, wherein the first height of the first radial surface defines an indent that is farther than the second height from an outer radial surface of the inner race.

(208) The apparatus of any preceding clause, wherein the first height defines an extension into the cavity.

(209) The apparatus of any preceding clause, wherein the first height defines an indent that increases a size of the cavity.

(210) The foregoing examples of bearing assemblies can be used with rolling roller bearings to enable a shaft to rotate relative to a stationary part. Although each example bearing assembly disclosed above has certain features, it should be understood that it is not necessary for a particular feature of one example bearing assembly to be used exclusively with that example. Instead, any of the features described above and/or depicted in the drawings can be combined with any of the examples, in addition to or in substitution for any of the other features of those examples. Features of one example are not mutually exclusive to features of another example. Instead, the scope of this disclosure encompasses any combination of any of the features discussed above and/or depicted in the figures.

(211) The following claims are hereby incorporated into this Detailed Description by this reference. Although certain example systems, methods, apparatus, and articles of manufacture have been disclosed herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all systems, methods, apparatus, and articles of manufacture fairly falling within the scope of the claims of this patent.

Claims

1. An apparatus comprising: an inner race; an outer race; roller bearings positioned between the inner race and the outer race, wherein the roller bearings include a leading roller bearing adjacent to a trailing roller bearing; and a cage positioned around the roller bearings between the inner race and the outer race, a cavity defined between the inner race, the roller bearings, and the cage, the cage including an inner radial surface, an outer radial surface, and an axial surface, the inner radial surface facing the inner race, the outer radial surface facing the outer race, the axial surface facing away from the roller bearings, the cage including at least one conduit extending between the inner radial surface and at least one of the outer radial surface or the axial surface, the conduit defining a flow path for a fluid out of the cavity, wherein a lengthwise span of the conduit is positioned between the leading roller bearing and the trailing roller bearing in a circumferential direction, wherein the conduit defines an inlet in the inner radial surface and an outlet in the outer radial surface or the axial surface, and wherein the outlet is positioned closer than the inlet to the trailing roller bearing in a circumferential direction.
2. The apparatus of claim 1, wherein the inner radial surface includes a first portion having a first height and a second portion having a second height different from the first height.
3. The apparatus of claim 2, wherein the first height extends closer than the second height to a rotational axis of the inner race, and wherein the first portion includes an inlet that fluidly couples the cavity to the conduit.
4. The apparatus of claim 3, wherein the inner race includes cage landings on opposite sides of the roller bearings in an axial direction, and wherein the first portion of the inner radial surface is positioned between the cage landings in the axial direction.
5. The apparatus of claim 4, wherein the second portion is positioned between the cage landings on opposite sides of the first portion in the circumferential direction.
6. The apparatus of claim 5, wherein the second portion includes an inclined surface that defines a transition from the first height to the second height.
7. The apparatus of claim 2, wherein the first height extends closer than the second height to a rotational axis of the inner race, and wherein the second portion includes an inlet that fluidly couples the cavity to the conduit.
8. The apparatus of claim 7, wherein the inner race includes cage landings on opposite sides of the roller bearings in an axial direction, and wherein the second portion of the inner radial surface is positioned between the cage landings in the axial direction.
9. The apparatus of claim 2, wherein the second height extends closer than the first height to a rotational axis of the inner race, and wherein the first portion includes an inlet that fluidly couples to the cavity.
10. The apparatus of claim 1, wherein the conduit carries the fluid out of the cavity.
11. The apparatus of claim 1, wherein the conduit is oblique relative to at least one of a radial direction or an axial direction.
12. The apparatus of claim 1, wherein the inlet and the outlet are offset in an axial direction.
13. A bearing assembly comprising: an inner race; an outer race; adjacent roller bearings positioned between the inner race and the outer race; and a cage positioned around the roller bearings between the inner race and the outer race, the cage including a conduit to transport a fluid to flow out of a cavity defined between the inner race, the roller bearings, and the cage, the cage including an inner radial surface, the inner radial surface including a first portion having a first depth and a second portion having a second depth different from the first depth, wherein the conduit includes an inlet and an outlet in the cage between the adjacent roller bearings in a circumferential direction defined by the bearing assembly, wherein the inlet and the outlet are offset in at least one of the circumferential direction or an axial direction defined by the bearing assembly.

14. The bearing assembly of claim 13, wherein the first depth extends closer than the second depth to a rotational axis of the cage, wherein the inner race includes cage landings on opposite sides of the roller bearings in an axial direction defined by the bearing assembly, wherein the first portion is positioned between the cage landings in the axial direction, and wherein the second portion is at least partially aligned with the cage landings in the axial direction.
15. The bearing assembly of claim 13, wherein the second depth extends closer than the first depth to a rotational axis of the cage, wherein the inner race includes cage landings on opposite sides of the roller bearings in an axial direction defined by the bearing assembly, wherein the first portion is positioned between the cage landings, and wherein the second portion is at least partially aligned with the cage landings in the axial direction.
16. The bearing assembly of claim 13, wherein the cage includes an outer radial surface and an outer axial surface, wherein the conduit includes an inlet defined in the inner radial surface and an outlet defined in the outer radial surface or the outer axial surface.
17. The bearing assembly of claim 13, wherein the inner race includes cage landings on opposite sides of the roller bearings in an axial direction defined by the bearing assembly, wherein the first portion and the second portion are positioned between the cage landings in an axial direction defined by the bearing assembly, and wherein the second portion is positioned on a first side of the first portion in the circumferential direction and a second side of the first portion in the circumferential direction opposite the first side.
18. A bearing assembly comprising: first means for guiding; second means for guiding; means for rolling between the first means for guiding and the second means for guiding, the means for rolling including first means for rolling adjacent second means for rolling; and means for containing the means for rolling, the means for containing including means for transporting lubricant out of a cavity between the means for rolling, the first means for guiding, and the means for containing, wherein the means for transporting directs the lubricant at least one of (i) from a first axial location to a second axial location different than the first axial location or (ii) from a first circumferential location to a second circumferential location different than the first circumferential location, wherein the first axial location, the second axial location, the first circumferential location, and the second circumferential location are positioned between the first means for rolling and the second means for rolling in a circumferential direction defined by the bearing assembly.
19. The bearing assembly of claim 18, wherein the means for containing includes means for maintaining at least a portion of the lubricant in the cavity.
20. The bearing assembly of claim 18, wherein the means for containing includes means for collecting at least a portion of the lubricant at an end of the means for transporting.
-