

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413407
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Kong; Xiaoyu et al.

Ciphers to protect keystrokes

Abstract

Encrypting keystroke data on a computing device involves receiving a key identifier (ID) from a keyboard device, creating a keystroke cipher segment comprising a primary authentication code and the key ID, and encrypting the keystroke cipher segment to generate an encrypted keystroke cipher segment. The keystroke cipher segment is included within a keystroke message and transmitted from the keyboard device driver to a window event handler via an input/output (I/O) message channel native to an operating system running on the computing device. The encrypted keystroke cipher segment is decrypted to identify the key ID, which is transmitted to a first application for further processing.

Inventors: Kong; Xiaoyu (Beijing, CN), Wang; Zhiyuan (Beijing, CN), Yun; Yiqun (Beijing, CN), Zhou; Zhanglin (Beijing, CN), Yu; Yang (Beijing, CN)

Applicant: Omnissa, LLC (Mountain View, CA)

Family ID: 92896272

Assignee: Omnissa, LLC (Mountain View, CA)

Appl. No.: 18/311879

Filed: May 03, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240333502 A1	Oct. 03, 2024

Foreign Application Priority Data

WO	PCT/CN2023/085332	Mar. 31, 2023
----	-------------------	---------------

Publication Classification

Int. Cl.: H04L9/14 (20060101); G06F21/83 (20130101); H04L9/08 (20060101)

U.S. Cl.:

CPC H04L9/14 (20130101); G06F21/83 (20130101); H04L9/0825 (20130101);

Field of Classification Search

CPC: H04L (9/14); H04L (9/0825); G06F (21/83)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11550922	12/2022	Soman et al.	N/A	N/A
12032726	12/2023	Tas	N/A	G06F 21/83
2007/0182714	12/2006	Pemmaraju	N/A	N/A
2009/0296928	12/2008	Matsumoto et al.	N/A	N/A
2010/0195825	12/2009	Cini	N/A	N/A
2012/0079282	12/2011	Lowenstein et al.	N/A	N/A
2016/0371472	12/2015	Walsh	N/A	N/A
2017/0104597	12/2016	Negi et al.	N/A	N/A
2017/0286141	12/2016	Adler et al.	N/A	N/A
2018/0026947	12/2017	Haworth et al.	N/A	N/A
2019/0370013	12/2018	Katchapalayam	N/A	N/A
2020/0104538	12/2019	Summers	N/A	G06F 21/606
2021/0034743	12/2020	Tan	N/A	G06F 21/568
2021/0216644	12/2020	Soman et al.	N/A	N/A
2022/0092221	12/2021	Scillieri	N/A	H04L 63/0428
2022/0245287	12/2021	Fernandez	N/A	H04W 12/50

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2002-0048313	12/2001	KR	N/A
2004-0009575	12/2003	KR	N/A
2018078212	12/2017	WO	N/A

OTHER PUBLICATIONS

Unknown, "WM_SETFOCUS message", <https://docs.microsoft.com/en-us/windows/desktop/inputdev/wm-setfocus>, May 30, 2018; retrieved on Feb. 9, 2023, 2 pages. cited by applicant

Unknown, "Virtual-Key Codes", <https://docs.microsoft.com/en-us/windows/desktop/inputdev/virtual-key-codes>, May 31, 2018; retrieved on Feb. 9, 2023, 19 pages. cited by applicant

Unknown, "Window Messages", <https://docs.microsoft.com/en-us/windows/desktop/learnwin32/window-messages>, May 31, 2018; retrieved on Mar. 2, 2020. cited by applicant

Unknown, "WM_KEYDOWN message", <https://docs.microsoft.com/en-us/windows/desktop/inputdev/wm-keydown>, May 30, 2018; retrieved on Feb. 9, 2023, 3 pages. cited by applicant

Unknown, "WM_KILLFOCUS message", <https://docs.microsoft.com/en-us/windows/desktop/inputdev/wm-killfocus>, May 31, 2018; retrieved on Feb. 9, 2023, 2 pages. cited by applicant

Ogelsby, R., "A look at the VMware Horizon key logger blocker—Ron's Cool Feature of the Week", <https://blogs.vmware.com/euc/2022/01/a-look-at-the-vmware-horizon-key-logger-blocker-rons-cool-feature-of-the-week.html>, VMware, Jan. 27, 2022, 9 pages. cited by applicant

Hex-Rays, "IDA Pro", <https://hex-rays.com/ida-pro/>, Hex-Rays, Copyright 2023, retrieved on Feb. 8, 2023, 12 pages. cited by applicant

Hex-Rays, "IDA Freeware", <https://hex-rays.com/ida-free/>, Hex-Rays, Copyright 2023, retrieved on Feb. 8, 2023, 8 pages. cited by applicant

Hex-Rays, "Interactive Operation", <https://hex-rays.com/ida-free/>, Hex-Rays, Copyright 2023, retrieved on Feb. 8, 2023, 9 pages. cited by applicant

Unknown, "CryptMT. The Cryptographic Mersenne Twister", <http://www.math.sci.hiroshima-u.ac.jp/m-mat/MT/CRYPTMT/index.html>, Japan Society for the Promotion of Science, retrieved on Feb. 8, 2023, 2 pages. cited by applicant

Unknown, "CryptMT", <https://en.wikipedia.org/wiki/CryptMT>, Wikipedia, retrieved on Feb. 8, 2023, 1 page. cited by applicant

Unknown, "Advanced Encryption Standard", https://en.wikipedia.org/wiki/Advanced_Encryption_Standard, Wikipedia, retrieved on Feb. 8, 2023, 14 pages. cited by applicant

Unknown, "AES implementations", https://en.wikipedia.org/wiki/AES_implementations, Wikipedia, retrieved on Feb. 8, 2023, 6 pages. cited by applicant

Unknown, "Keyboard_Input_Data structure (ntddkbd.h)", https://learn.microsoft.com/en-US/windows/win32/api/ntddkbd/ns-ntddkbd-keyboard_input_data, Microsoft, Aug. 3, 2021, Retrieved on Feb. 9, 2023. cited by applicant

Unknown, "Block cipher mode of operation", https://en.wikipedia.org/wiki/Block_cipher_mode_of_operation, Wikipedia, retrieved on Feb. 9, 2023, 20 pages. cited by applicant

Unknown, "Stream Cipher", https://en.wikipedia.org/wiki/Stream_cipher, Wikipedia, retrieved on Feb. 9, 2023, 7 pages. cited by applicant

Unknown, "Block cipher", https://en.wikipedia.org/wiki/Block_cipher, Wikipedia, retrieved on Feb. 9, 2023, 16 pages. cited by applicant

Unknown, "GDES", <https://en.wikipedia.org/wiki/GDES>, Wikipedia, retrieved on Feb. 9, 2023, 1 page. cited by applicant

Unknown, "Lucifer (cipher)", [https://en.wikipedia.org/wiki/Lucifer_\(cipher\)](https://en.wikipedia.org/wiki/Lucifer_(cipher)), Wikipedia, retrieved on Feb. 9, 2023, 2 pages. cited by applicant

Unknown, "Madryga", <https://en.wikipedia.org/wiki/Madryga>, Wikipedia, retrieved on Feb. 9, 2023, 2 pages. cited by applicant

Unknown, "Simon (cipher)", [https://en.wikipedia.org/wiki/Simon_\(cipher\)](https://en.wikipedia.org/wiki/Simon_(cipher)), Wikipedia, retrieved on Feb. 9, 2023, 6 pages. cited by applicant

Unknown, "Speck (cipher)", [https://en.wikipedia.org/wiki/Speck_\(cipher\)](https://en.wikipedia.org/wiki/Speck_(cipher)), Wikipedia, retrieved on Feb. 9, 2023, 7 pages. cited by applicant

Unknown, "Chosen-plaintext attack", https://en.wikipedia.org/wiki/Chosen-plaintext_attack, Wikipedia, retrieved on Feb. 9, 2023, 4 pages. cited by applicant

Unknown, "Chosen-ciphertext attack", https://en.wikipedia.org/wiki/Chosen-ciphertext_attack, Wikipedia, retrieved on Feb. 9, 2023, 3 pages. cited by applicant

Unknown, "Interactive Operation", Hex-Rays, copyright 2023, retrieved Mar. 26, 2023, <https://www.hex-rays.com/products/decompiler/manual/interactive.shtml>, 8 pages. cited by applicant

Primary Examiner: Gadalla; Hany S.

Attorney, Agent or Firm: Kim & Stewart LLP

Background/Summary

CROSS REFERENCE TO RELATED

(1) This application claims the benefit of priority of Chinese Patent Application No. PCT/CN2023/085332, filed Mar. 31, 2023, entitled "Ciphers to Protect Keystrokes", the entirety of which is incorporated herein by reference.

BACKGROUND

(2) Key logging is a process involving the capture of keystrokes made by a user via an input device, such as a physical keyboard. Software-based keyloggers are computer programs designed to record keyboard input without interrupting the input/output (I/O) flow between the input device and the application(s) that receive the input stream. Such keyloggers have been developed for various reputable uses, such as troubleshooting of technical problems with computers and their use within enterprise environments or monitoring computer usage in family settings. However, many nefarious uses of such keyloggers are possible. For example, keyloggers have been maliciously installed unbeknownst to users to steal passwords, credit card numbers, personal information, or otherwise illegally spy on users.

SUMMARY

(3) This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

(4) Aspects of the disclosure provide solutions for encrypting keystroke data. Solutions include: receiving, by a keyboard device driver of the computing device, a key identifier (ID) from a keyboard device, the key ID representing a keystroke event occurring on the computing device via the keyboard device; creating a keystroke cipher segment comprising a primary authentication code and the key ID; encrypting the keystroke cipher segment to generate an encrypted keystroke cipher segment; creating a keystroke message comprising at least the encrypted keystroke cipher segment; transmitting the keystroke message from the keyboard device driver to a window event handler via an input/output (I/O) message channel native to an operating system running on the computing device, the window event handler being responsible for providing keystroke data to applications running on the operating system; receiving the keystroke message at the window event handler; decrypting the encrypted keystroke cipher segment, thereby identifying the key ID; and transmitting the key ID to a first application.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present description will be better understood from the following detailed description read in the light of the accompanying drawings, wherein:

(2) FIG. 1 illustrates an example architecture that advantageously provides encryption and

decryption of keystroke data;

(3) FIG. 2 illustrates an example data flow of a keystroke message through a native keystroke I/O message channel, such as the example shown in FIG. 1;

(4) FIG. 3A and FIG. 3B illustrate a flowchart of exemplary operations associated with an example architecture, such as that shown in FIG. 1;

(5) FIG. 4A and FIG. 4B illustrate a flowchart of exemplary operations associated with example architecture, such as that shown in FIG. 1; and

(6) FIG. 5 illustrates a block diagram of an example computing apparatus that may be used as a component of an example architecture, such as that shown in FIG. 1.

(7) Any of the figures may be combined into a single example or embodiment.

DETAILED DESCRIPTION

(8) Solutions encrypt at least portions of I/O from a physical or virtual input device and through portions of an I/O message stream such that traditional software-based keyloggers cannot snoop plaintext keystroke data coming from the input device. An encryptor (e.g., encryption module, engine, component, or the like) is installed and used at the device driver level that allows the device driver to encrypt key identifiers (or “key IDs”) in a very short cipher. This cipher segment is embedded within a keystroke message and sent, for example in a keystroke I/O message channel native to an underlying operating system of the computing device, from the device driver to a window event manager (e.g., a window procedure under Windows, a window event handling function under Linux or macOS, or the like) that is tasked with providing the keystroke data to whichever active window is currently receiving I/O from the input device. A decryptor (e.g., decryption module, engine, component, or the like) is installed and used by this window event handler **122** to decrypt the cipher segment, revealing the plaintext keystroke data, which is then passed onto the active window (e.g., for display, further processing, etc.).

(9) Aspects of the disclosure improve the functioning of the computer by protecting plaintext keystroke data from being snooped by software-based keyloggers as keystroke messages transit the native keystroke I/O message channel. These techniques limit network traffic on the native I/O message channel by utilizing native I/O message channel protocols and fields for the cipher segment. This both allows the feature to work within existing message sizes, thus not increasing the network packet size of I/O messages, as well as limits the scope of changes to the operating system to enable such features. Thus, aspects of the disclosure provide a practical, useful result to solve a technical problem in the domain of computing.

(10) FIG. 1 illustrates an example architecture **100** that advantageously provides encryption and decryption of keystroke data. Architecture **100** uses a computing device **104** in conjunction with a keyboard device **106** which may be implemented on one or more computing apparatus **518** of FIG. 5. A keystroke encryptor **114** encrypts keystrokes **108** (e.g., scan codes, virtual-key codes, or the like), thus encrypting the keystrokes **108** as the keystroke data is passed through a keystroke I/O message channel **126**, such as a channel native to, or otherwise part of, an operating system **110** of the computing device. In the example shown in FIG. 1, the operating system **110** is a version of MICROSOFT WINDOWS (Microsoft Corporation, Redmond, Washington). In other examples, the client operating system **110** is another operating system such as another desktop or server-based operating system (e.g., MACOS (Apple Inc., Cupertino, California), CHROMEOS (Google LLC, Mountain View, California), Unix, Linux, or the like) or a mobile operating system (e.g., Android, IOS (Apple, Inc.), CHROMEOS, or the like).

(11) In operation, a user **102** operates the keyboard device **106** as an input device to the computing device **104**. In some examples, the computing device **104** is a desktop or laptop computer and the keyboard device is a physical keyboard device, such as a QWERTY keyboard device or a French AZERTY keyboard device connected via a wired or wireless connection with the computing device **104**. In other examples, the computing device **104** is a mobile computing device and the keyboard device **106** is a virtual keyboard device (e.g., a keyboard displayed on a touch screen of a mobile

device).

(12) Each time a key on the keyboard device **106** is pressed (and, in some configurations, released) by the user **102**, the keyboard device **106** transmits keystroke data (e.g., keystrokes **108**, in the form of scan codes or the like generated by the keyboard device **106**) to a keyboard device driver **112** of the client operating system **110**. Each keystroke **108** can include a scan code, a unique value that identifies which particular key was pressed or released during a given input event (e.g., independent of an active keyboard layout being used by the client operating system **110**).

(13) In conventional architectures, the keyboard device driver **112** interprets the scan code and converts the scan code to a virtual-key code, a device-independent value defined by the computing device **104** that identifies a particular purpose of each key. The keyboard device driver **112** then creates a keystroke message that includes the scan code (in plaintext form) and transmits that message through the keystroke I/O message channel **126**. This message channel **126** includes a system message queue **116**, a thread message queue **118**, and a thread message loop **120** that are collectively configured to deliver keystroke messages to applications **130** running on the computing device **104** via a window event handler **122** (e.g., window procedure under Microsoft Windows, a window event handling function under Linux or macOS, or the like). However, keyloggers can inspect keystroke messages as the messages pass through the channel **126**, and thus the plaintext keystroke data is vulnerable to being read and inspected in such conventional architectures.

(14) In contrast, the keyboard device driver **112** includes a keystroke encryptor **114** that is configured to encrypt the keystroke data as the keystroke message transits the keystroke I/O message channel **126** through to the window event handler **122**, where a keystroke decryptor **124** is configured to decrypt the keystroke data before the window event handler **122** passes each keystroke on to some particular application **130**. More specifically, a key identifier (e.g., a particular scan code or virtual-key code of a particular keystroke **108**) is included in a cipher segment that is encrypted by the encryptor **114**. This cipher segment (in encrypted form) is included as one field of a keystroke message, and another field that typically includes the plaintext key identifier is left empty (e.g., does not include the plaintext key identifier). As such, the cipher segment accompanies the keystroke message through the message channel **126** in an encrypted form, and any keylogger operating between the keyboard device driver **112** and the window event handler **122** can at best read an empty key identifier field of the message or an encrypted cipher segment.

(15) Upon arrival at the window event handler **122**, the keystroke decryptor **124** decrypts the cipher segment embedded in the keystroke message, thus identifying the key identifier (in plaintext). The window event handler **122** passes the plaintext key identifier to the application **130** as an input event to be processed by the application **130**.

(16) The application **130** may be any application, including virtualized and non-virtualized. In some examples, the application **130** is a virtual machine (VM) client that is configured to connect and communicate with a virtual machine **146** of a virtual machine system **140**. The virtual machine system **140** provides a virtualization architecture that comprises of a set of compute nodes **144**, where each compute node hosts multiple objects, which may be virtual machines **146** (e.g., VMs, such as base objects, linked clones, and independent clones), containers, applications, or any compute entity (e.g., computing instance or virtualized computing instance) supported by a virtualization platform **142**.

(17) FIG. 2 illustrates an example data flow **200** of a keystroke message **210** through the native keystroke I/O message channel **126** shown in FIG. 1. A keystroke **108** is received by the keystroke encryptor **114**. In some examples, the keystroke **108** includes a key identifier comprising a scan code (e.g., an 8-bit integer generated by the keyboard device **106** of FIG. 1). In some examples, the key identifier comprises a virtual-key code (e.g., an 8-bit integer that is the results of a mapping of a scan code to the virtual-key code by the keyboard device driver **112**). The keyboard device driver

112 generates a keystroke message **210** for each keystroke **108** that is received. In this example, the keystroke encryptor **114** generates and encrypts a keystroke cipher segment **240** that is embedded within the keystroke message **210** before the keystroke message **210** is sent through the message channel **126**.

(18) In the example shown in FIG. 2, the message channel **126** is a keystroke I/O message channel **126** native to certain versions of the Windows operating system. As such, the keystroke message **210** includes several predefined fields as a part of a message protocol for the message channel **126**, including a Unit ID field **212** (as a USHORT of 2 bytes), a MakeCode field **214** (USHORT), a Flags field **216** (USHORT), a Reserved field **218** (USHORT), and an ExtraInformation field **220** (as a ULONG of 4 bytes) (e.g., as defined by a “KEYBOARD_INPUT_DATA” object or structure). The MakeCode field **214** typically includes the key identifier (in plaintext) in unencrypted implementations. In encrypted implementations described herein, the MakeCode field **214** is intentionally left empty (zero value) and the key identifier is embedded as a key ID field **234** within a keystroke cipher segment **240** and that keystroke cipher segment is encrypted and included as the ExtraInformation field **220**. The ExtraInformation field **220** thus represents a data channel between the keyboard device driver **112** and the window event handler **122** that is used to pass the key ID **234** in an encrypted state.

(19) More specifically, and in a first example implementation, the keystroke encryptor **114** creates a 32-bit (4 bytes) keystroke cipher segment (or just “cipher segment”) **240** that includes a random buffer field (or just “random buffer”) **230** of 12 bits, a primary authentication code field (or just “primary auth code”) **232** of 12 bits, and a key ID field (or just “key ID”) **234** of 8 bits. The key ID **234**, as mentioned above, is the plaintext key identifier received in the keystroke **108** (e.g., a scan code or virtual-key code mapped from the scan code). The random buffer **230** is a random 12 bits of data used to pad the size of the cipher segment **240** to be 32 bits (4 bytes), the size of the ExtraInformation field **220**. The primary auth code **232** is a random number generated and shared between the encryptor **114** and the decryptor **124** as a part of shared cipher parameters **202** (SHARED_AUTH_CODE). As such, in this first example implementation, the primary auth code **232** is consistently used for all keystroke messages **210** between the encryptor **114** and the decryptor **124** (until the shared cipher parameters **202** are reset and renegotiated). This first example implementation is referred to herein as a “static authentication code” implementation. The primary auth code **232** is used by the decryptor **124** to authenticate that the keystroke message **210** was properly generated by the encryptor **114**. While the random buffer field **230** and primary auth code field **232** are set to 12 bits in size in the example implementation, it should be understood that other widths between these two fields are possible (from 24 total bits), where more bits to the random buffer field **230** makes the cipher more secure against certain types of attacks (e.g., chosen-plaintext attack), and where more bits to the primary auth code field **232** provides a greater chance to detect faked ciphertext. Further, the fields **230**, **233**, **234** of the cipher segment **240** can be in any arbitrary order.

(20) In a second example implementation, the primary auth code **232** differs from the first example implementation. This second example implementation is referred to herein as a “dynamic authentication code” implementation. More specifically, the primary auth code **232** is a 12-bit value that is generated for each particular keystroke message **210** in this second implementation. To create the primary auth code **232**, the encryptor **114** creates a hash segment **250**, a 32-bit value that includes a zeros field **252** of 4 bits, a shared auth code field **254** of 12 bits, a tag field (or just “tag”) **256** of 8 bits, and a key ID field **258** of 8 bits. The zeros field is set to all zeros. The shared auth code field **254** is the shared authentication code, SHARED_AUTH_CODE, from the shared cipher parameters **202**. The tag field **256** is an 8-bit value that is used to help verify whether the MakeCode field **214** of the keystroke message **210** has been tampered with or otherwise changed between encryption and decryption. The encryptor **114** selects a tag value for the tag field **256** (e.g., a random 8-bit value, an incrementing value, or the like). This tag value is also included as the

MakeCode field **214** in the keystroke message **210** (in plaintext, zero padded). The encryptor **114** hashes the hash segment (e.g., using “triple32” hash function, or any other hash method that takes 32 bits as input and produces 32 bit hash values) to generate a 32-bit hash **260**. This 32-bit hash **260** is converted into a 16-bit hash **262** (e.g., using XOR-folding). The lower 12 bits **264** of the 16-bit hash **262** are then used as the primary auth code **232** within the keystroke cipher segment **240** prior to encryption. The fields **252**, **254**, **256**, **258** of the hash segment **250** can be in any arbitrary order.

(21) In operation, the encryptor **114** creates the keystroke cipher segment **240** with either the first or second implementations as described above. The encryptor **114** then encrypts the cipher segment **240** using an encryption algorithm that can support encryption of a 4-byte message. In example implementations, the encryptor **114** uses Simon32 to encrypt the cipher segment **240**. Simon32 is a variant of the Simon family of lightweight block ciphers made publicly available by the National Security Agency (NSA) and that supports 32-bit blocks. In other implementations, another block cipher that supports 32-bit blocks is used, such as RC5, Skip32, Spec32, or the like. The encrypted cipher segment **240** is included as the ExtraInformation field **220** of the keystroke message **210**. As discussed above, the MakeCode field is empty in the static auth code implementation and is set to the tag value in the dynamic auth code implementation.

(22) Upon receipt of the keystroke message **210**, the decryptor **124** extracts the encrypted cipher segment **240** from the ExtraInformation field **220**, and optionally the tag value from the MakeCode field **214**. The decryptor **124** then decrypts the encrypted cipher segment **240** (using the shared cipher parameters). In the first example embodiment, if the decrypted primary auth code **232** matches the SHARED_AUTH_CODE from the shared cipher parameters **202**, then the message **210** is determined to be authentic, and thus the key ID **234** is extracted and passed along by the window event handler **122** to the active application **130**. In the second example embodiment, the decryptor **124** verifies the message **210** by recreating the hash segment **250**. In recreating the hash segment **250**, zeros field is created with all zeros, the SHARED_AUTH_CODE is used for the shared auth code field **254**, the value from the MakeCode field **214** of the message **210** is used as the tag field **256**, and the unencrypted key ID field **234** of the cipher segment **240** is used as the key ID field **258**. The resulting 32-bit hash **260** is converted to a 16-bit hash **262**, and the lower 12 bits **264** are then compared to the primary auth code **232** from the unencrypted cipher segment **240**. If these values match, then the message **210** is considered authentic (properly decrypted and a verified untampered MakeCode field), and thus the unencrypted key ID **234** is similarly extracted and passed along to the active application **130**.

(23) In example implementations, the shared cipher parameters **202** include a VERSION_NUMBER indicating a version of the encryption system, a KEY_GENERATION value indicating a counter identifying how many times the encryption system has regenerated, reset, or recreated some of these parameters, a KEY_ARRAY array of 32 64-bit keys (under Simon32) used by the encryption algorithm to perform encryption and decryption, a NUM_ROUNDS value of a random integer between 16 and 32, and a SHARED_AUTH_CODE whose use is described above. Other shared cipher parameters **202** may be included. The encryptor **114** and decryptor **124** share these cipher parameters **202** via some separate communications channel and periodically regenerate, reset, or recreate some of these parameters **202**. For example, a reset event is initiated or performed by either of the encryptor **114** and decryptor **124** after a predetermined period of time (e.g., reset event automatically initiated every five minutes) or after a predetermined number of encryptions (e.g., reset event automatically initiated after every 1024 encryptions, as tracked internally by the encryptor), where quicker resets yields stronger security, but at a cost of computational processing.

(24) In some implementations, the decryptor **124** maintains both a current set of cipher parameters **202** and a previous set of cipher parameters. There may be situations in which a new set of cipher parameters **202** may have been created and shared but some messages **210** that had been encrypted

with the previous version of cipher parameters **202** may still be inbound to the decryptor **124**. As such, if a decryption attempt fails with the current parameters **202**, then the decryptor **124** may attempt to decrypt with the prior set of parameters **202**, and only then may reject a message **210** if neither set of parameters **202** successfully authenticates the message **210**.

(25) FIG. 3A and FIG. 3B illustrate a flowchart **300** of exemplary operations associated with architecture **100** shown in FIG. 1. In some examples, the operations of flowchart **300** are performed by the keystroke encryptor **114** executing on the computing device **104** of FIG. 1 or the computing apparatus **518** of FIG. 5. Referring now to FIG. 3A, flowchart **300** commences with the encryptor **114** resetting a set of shared cipher parameters at operation **310**, such as the shared cipher parameters **202** of FIG. 2. Resetting the shared cipher parameters at operation **310** includes creating a new key array at operation **312**. In an example implementation, the keystroke encryptor **114** uses Simon32 encryption algorithm during encryption and decryption operations. This encryption algorithm uses a set of N=32 64-bit keys stored as KEY_ARRAY[]. Each key of the KEY_ARRAY[] is configured as a 64-bit value randomly generated by the encryptor **114** for implementations using Simon32. Other encryption algorithms may use keys of different key length. The encryptor **114** also randomly generates a NUM_ROUNDS value at operation **314**, which is created as an integer value between 16 and 32. In other implementations, the range of NUM_ROUNDS can have a lower minimum or maximum (for faster encryption, but at a reduced encryption strength) or a higher minimum or maximum (for slower encryption, but at a higher encryption strength). The number of keys in the KEY_ARRAY[] is configured to be the maximum of the range of NUM_ROUNDS. A SHARED_AUTH_CODE is also randomly generated at operation **316**. The SHARED_AUTH_CODE is a 12-bit value that is used as an authentication code for messages passed between the encryptor **114** and the decryptor **124**. At operation **318**, a KEY_GENERATION counter is incremented. This KEY_GENERATION counter tracks how many times the cipher parameters **202** have been recreated and resynchronized between the encryptor **114** and decryptor **124**. At operation **320**, the encryptor **114** shares the new set of cipher parameters with the decryptor **124**. While the example flowchart **300** describes the operation **310** as being performed by the encryptor **114**, it should be understood that this operation **310** can alternatively be performed by the decryptor **124** or by some other coordination application (not shown).

(26) At operation **330**, the encryptor **114** receives a new keystroke **108** from the keyboard device **106**. The keystroke data included in keystroke **108** includes a key identifier associated with a key press or release event that has occurred on the keyboard device. This key ID may be a scan code or a virtual-key code. For each new keystroke **108** received at operation **330**, the encryptor **114** assembles a cipher segment **240** that will be included in a new keystroke message **210** to be sent to the decryptor **124**. Initially, the encryptor **114** assembles a cipher segment **240** at operation **340**. Assembling the cipher segment **240** includes inserting the key ID into the key ID field **234** of the cipher segment **240** at operation **342**. At operation **344**, the encryptor **114** randomly generates a 12-bit random value and includes this value as the random buffer field **230** of the cipher segment **240**.

(27) At decision operation **346**, the encryptor **114** determines whether to use static authentication codes or dynamic authentication codes, which can be a configuration setting shared between the encryptor **114** and decryptor **124**. When the encryptor **114** is configured to use static authentication codes, the cipher segment assembly of operation **340** continues to operation **348** and inserts the SHARED_AUTH_CODE into the primary auth code field **232** of the cipher segment **240**. When the encryptor **114** is configured to use dynamic authentication codes, the cipher segment assembly of operation **340** continues to operations **350-356**, which generates a 12-bit dynamic authentication code for use as the primary authentication code field **232**. More specifically, at operation **350**, the encryptor **114** assembles a 32-bit hash segment **250**. This hash segment assembly includes inserting the key ID as the key ID field **258**, the SHARED_AUTH_CODE as the shared auth code field **254**, an 8-bit tag value as the tag field **256**, and 4 bits of zero padding in the zeros field **252**. At operation

352, the encryptor **114** computes a 32-bit hash **260** by hashing the hash segment **250** using a hash function such as “triple32.” At operation **354**, the 32-bit hash **260** is reduced to a 16-bit hash **262** by performing XOR-folding (or another reduction method) on the 32-bit hash **260**. At operation **356**, the encryptor **114** inserts the 12 least significant bits of the 16-bit hash **262** into the primary auth code field **232** of the cipher segment **240**. As such, the assembly of the cipher segment of operation **340** is complete, though currently in an unencrypted, plaintext state.

(28) At operation **360**, the encryptor **114** encrypts the cipher segment **240**. This encryption operation **360** is illustrated in greater detail in FIG. 3B. Referring now to FIG. 3B, at operation **370**, the encryptor **114** initializes a round counter “I=0.” This round counter, I, is used to track a number of rounds of encryption that have been performed on the cipher segment **240**. At operation **372**, the encryptor **114** begins a loop that causes N=NUM_ROUNDS of encryption of the cipher segment **240**. Since NUM_ROUNDS is some random value between 16 and 32, this loop of operations **374-378** will be performed between 16 and 32 times, transforming the initially-plaintext cipher segment **240** into an encrypted cipher segment. At operation **374**, and at each iteration I=0 to (N-1), the current cipher segment **240** is encrypted using key[I] of the KEY_ARRAY[] using Simon32 encryption. As such, each operation **374** inputs a 32-bit current cipher segment and outputs a 32-bit encrypted cipher segment, which becomes the new current cipher segment **240**. At operation **376**, the round counter/is incremented. At decision operation **378**, the encryptor **114** determines whether the loop began at operation **372** is complete, namely whether I=(N-1). If the loop is not yet complete, the encryptor **114** returns to operation **374** for another iteration.

(29) When the primary encryption loop of operations **372-378** is complete, the cipher segment **240** has been completely encrypted. The encryptor **114** may perform one or more dummy encryption operations (to protect against side channel attacks). These dummy encryption operations of a dummy encryption loop **380-386** do not operate on the encrypted cipher segment **240**. Rather, the dummy encryption operations may be performed on a dummy 32-bit segment, thus performing encryption processing but not altering the already-encrypted cipher segment **240**. More specifically, at operation **380**, the encryptor **114** begins the dummy encryption loop by determining a number of rounds (32-NUM_ROUNDS) to loop. If the primary encryption loop **372-378** already performed 32 encryption operations on the cipher segment **240** (I=32-1), then no dummy encryption operations are needed, and thus the encryptor **114** skips down to operation **388**. Otherwise, if there is at least one dummy encryption operation to be performed (1<32-1), then at operation **382**, the encryptor **114** performs an encryption operation on the dummy segment using key[I], similar to operation **374**. At operation **384**, the round counter/is incremented. At decision operation **386**, the encryptor **114** determines whether the dummy encryption loop **380-386** is complete, namely whether I=32-1. If the loop is not yet complete, the encryptor **114** returns to operation **382** for another iteration of dummy encryption. When the dummy encryption loop **380-386** is complete, the encryptor **114** has completed 32 rounds of encryption, of which (NUM_ROUNDS) were performed on the cipher segment **240**, yielding the encrypted cipher segment, and (32-NUM_ROUNDS) were performed on the dummy segment. At operation **388**, the encryptor **114** provides the encrypted cipher segment **240** (now in encrypted text) as the output of operation **360**.

(30) Referring again to FIG. 3A, once the encrypted cipher segment **240** has been generated, the encryptor **114** assembles a keystroke message **210** at operation **362**. Assembling the keystroke message **210** includes inserting the 32-bit encrypted cipher segment **240** into the ExtraInformation field **220**. Further, the encryptor **114** also modifies the MakeCode field **214**. In static auth code implementations, the MakeCode field is erased (all zero-bits) or is otherwise overwritten with a random value. In dynamic auth code implementations, the tag value used in the tag field **254** is inserted as the value of the MakeCode field. In such dynamic auth code implementations, the tag value will be read from the MakeCode field and used to authenticate the dynamic authentication code, as discussed in greater detail below. The other fields of the keystroke message **210** may be populated with other data, but remain unchanged by the encryptor **114**, as they do not impact the

encryption and decryption operations described herein. At operation **364**, the assembled keystroke message **210** is transmitted through the message channel **126**, bound for the decryptor **124**.

(31) At decision operation **366**, the encryptor **114** determines whether to reset the shared cipher parameters **202** between the encryptor **114** and decryptor **124**. For example, the encryptor **114** is configured to reset the cipher parameters **202** when a predetermined amount of time has passed since the last reset (e.g., a reset every five minutes), or after a predetermined number of keystroke messages **210** have been encrypted (e.g., a reset after every 1,024 encrypted keystroke messages **210**). In some implementations, the decryptor **124** is configured to trigger a reset if a predetermined number of encrypted keystroke messages **210** fail to be properly decrypted and authenticated (e.g., reset after three failed decryptions). While the examples provided herein describe the encryptor **114** performing the computation operations of the reset operation **310**, it should be understood that any or all of those operations **310** may be performed by the decryptor **124**, and either or both of the encryptor **114** and decryptor **124** may be configured to trigger a reset operation **310**. When a reset is triggered, the encryptor **114** re-performs operation **310** and associated sub-operations **312-320**, thereby causing a new set of cipher parameters **202** to be shared between the encryptor **114** and decryptor **124**. Otherwise, the encryptor **114** returns to operation **330** to receive and process the next keystroke **108**.

(32) FIG. **4A** and FIG. **4B** illustrate a flowchart **400** of exemplary operations associated with architecture **100** shown in FIG. **1**. In some examples, the operations of flowchart **400** are performed by the keystroke decryptor **124** executing on the computing device **104** of FIG. **1** or the computing apparatus **518** of FIG. **5**. Referring now to FIG. **4A**, flowchart **400** commences with the decryptor **124** receiving the shared cipher parameters **202** at operation **410**. In the example implementation, the decryptor **124** keeps two copies of cipher parameters, a current set and a prior set (not separately shown). At operation **412**, when a reset is triggered, the decryptor **124** copies the current cipher parameters **202** into a prior cipher parameters, thereby retaining the last version of cipher parameters. At operation **414**, the decryptor **124** also receives new cipher parameters and uses these new cipher parameters as the current cipher parameters **202**.

(33) At operation **420**, the decryptor **124** receives a new keystroke message **210** from the message channel **126**. At operation **422**, the encrypted cipher segment **240** is extracted from the ExtraInformation field **220** of the keystroke message **210**. At operation **424**, the decryptor **124** decrypts the encrypted cipher segment **240**. This decryption operation **424** is illustrated in greater detail in FIG. **4B**.

(34) Referring now to FIG. **4B**, at operation **470**, the decryptor **124** initializes a round counter “ $I=32-1$.” This round counter, I , is similarly used to track a number of rounds of decryption that have been performed, either on the cipher segment **240** or on a dummy segment, for a total of 32 decryption operations. The decryptor **124** may perform one or more dummy decryption operations (to protect against side channel attacks). These dummy decryption operations of a dummy encryption loop **472-478** do not operate on the encrypted cipher segment **240**. Rather, the dummy decryption operations may be performed on a dummy 32-bit segment, thus performing decryption processing but not altering the encrypted cipher segment **240**. More specifically, at operation **472**, the decryptor **124** begins a loop that causes $N=32-\text{NUM_ROUNDS}$ of decryption of the dummy segment. Since NUM_ROUNDS is some random value between 16 and 32, this loop of dummy decryption operations **474-478** will be performed between 0 and 16 times. At operation **474**, and at each iteration $\neq (32-1)$ to $(32-\text{NUM_ROUNDS}-1)$, the dummy segment is decrypted using $\text{key}[I]$ of the $\text{KEY_ARRAY}[]$ using Simon32 encryption. At operation **476**, the round counter I is decremented. At decision operation **478**, the decryptor **124** determines whether the loop began at operation **472** is complete, namely whether $I < 32 - \text{NUM_ROUNDS} - 1$. If the loop is not yet complete, the decryptor **124** returns to operation **374** for another iteration.

(35) When the dummy decryption loop of operations **472-478** is complete, the decryptor **124** begins to decrypt the encrypted cipher segment **240**. More specifically, at operation **480**, the

decryptor **124** begins the cipher segment decryption loop by determining a number of rounds ($N = \text{NUM_ROUNDS}$) to loop. At operation **482**, and at each iteration $= (32 - \text{NUM_ROUNDS} - 1)$ to 0 , the encrypted cipher segment **240** is decrypted using $\text{key}[I]$ of the $\text{KEY_ARRAY}[]$ using Simon32 encryption. At operation **484**, the round counter is decremented. At decision operation **486**, the decryptor **124** determines whether the dummy encryption loop **480-486** is complete, namely whether $I < 0$. If the loop is not yet complete, the decryptor **124** returns to operation **482** for another iteration of cipher segment decryption. When the cipher segment decryption loop **480-486** is complete, the decryptor **124** has completed 32 rounds of decryption, of which (NUM_ROUNDS) were performed on the cipher segment **240**, yielding the decrypted cipher segment, and $(32 - \text{NUM_ROUNDS})$ were performed on the dummy segment. At operation **488**, the decryptor **124** provides the decrypted cipher segment **240** (now in plaintext) as the output of operation **424**.

(36) Referring again to FIG. 4A, once the decrypted cipher segment **240** has been generated, the decryptor **124** extracts the key ID from the key ID field **234** of the decrypted cipher segment **240** at operation **426**. At operation **430**, the decryptor **124** verifies the integrity of the keystroke message **210** using the decrypted cipher segment. Verifying the message integrity includes extracting the primary auth code from the decrypted cipher segment **240** at operation **432**. At decision operation **434**, the decryptor **124** branches based on the type of auth code in use. When static auth codes are being used, the decryptor **124** compares the primary auth code **232** to the SHARED_AUTH_CODE of the current cipher parameters **202** at operation **436**. When dynamic auth codes are being used, the integrity verification of operation **430** continues to operations **440-446**, which generates a 12-bit dynamic authentication code for use in authenticating the keystroke message **210**. More specifically, at operation **440**, the decryptor **124** assembles a 32-bit hash segment similar to the hash segment **250** shown in FIG. 2. This hash segment assembly includes inserting the key ID extracted from the key ID field **234** of the decrypted cipher segment **240** as the key ID field **258**, inserting the SHARED_AUTH_CODE as the shared auth code field **254**, inserting the 8-bit tag value (extracted from the MakeCode field **214** of the keystroke message **210**) as the tag field **256**, and 4 bits of zero padding in the zeros field **252**. At operation **442**, the decryptor **124** computes a 32-bit hash **260** by hashing the hash segment **250** using a hash function such as "triple32." At operation **444**, the 32-bit hash **260** is reduced to a 16-bit hash **262** by performing XOR-folding (or other reduction method) on the 32-bit hash **260**. At operation **446**, the decryptor **124** compares the 12 least significant bits of the 16-bit hash **262** to the primary auth code field **232** of the unencrypted cipher segment **240**.

(37) At decision operation **450**, the decryptor **124** thus determines whether the keystroke message **210** is authentic, namely whether the primary auth code matches the SHARED_AUTH_CODE (in static auth code implementations) or whether the primary auth code matches the 12 LSBs of the 16-bit hash **262** (in dynamic auth code implementations). When the keystroke message **210** is determined to be authentic, the decryptor **124** returns the key ID from the key ID field **234** of the decrypted cipher segment **240** to the window event handler **122** for submission to the application **130** at operation **452**. When the keystroke message **210** is determined to not be authentic, then the decryptor **124** may attempt to decrypt the encrypted cipher segment **240** using the prior set of cipher parameters (as retained in operation **412**). As such, at decision operation **460**, the decryptor **124** returns to repeat operations **424-450**, but using the prior set of cipher parameters to decrypt the encrypted cipher segment **240** (rather than the current set). Such a retry allows the decryptor **124** to potentially catch and successfully decrypt keystroke messages that had been generated before the latest reset, but that had not yet been received and processed by the decryptor **124** (when the prior cipher parameters were then the current cipher parameters).

(38) If, at decision operation **460**, it is determined that a retry was already attempted and failed with the prior cipher parameters, then the decryptor **124** rejects the keystroke message **210** at operation **462**. At decision operation **454**, the decryptor **124** determines whether a reset has been triggered (either by the decryptor **124** or by the encryptor **114**). In some implementations, a failure of a

predetermined number of keystroke messages **210** during decryption causes the decryptor **124** to initiate a reset. If a reset has been triggered, the decryptor **124** returns to operation **410** to receive new cipher parameters. Otherwise, the decryptor **124** returns to operation **420** and prepares to receive the next keystroke message **210** for decryption.

Additional Examples

(39) An example method of encrypting keystroke data comprises: receiving, by a keyboard device driver of the computing device, a key identifier (ID) from a keyboard device, the key ID representing a keystroke event occurring on the computing device via the keyboard device; creating a keystroke cipher segment comprising a primary authentication code and the key ID; encrypting the keystroke cipher segment to generate an encrypted keystroke cipher segment; creating a keystroke message comprising at least the encrypted keystroke cipher segment; transmitting the keystroke message from the keyboard device driver to a window event handler via an input/output (I/O) message channel native to an operating system running on the computing device, the window event handler being responsible for providing keystroke data to applications running on the operating system; receiving the keystroke message at the window event handler; decrypting the encrypted keystroke cipher segment, thereby identifying the key ID; and transmitting the key ID to a first application.

(40) An example computer system comprises: a keyboard device; a processor; and a non-transitory computer readable medium having stored thereon program code executable by the processor, the program code causing the processor to: receive, by a keyboard device driver managing the keyboard device, a key identifier (ID) from the keyboard device, the key ID representing a keystroke event occurring on the computing device via the keyboard device; create a keystroke cipher segment comprising a primary authentication code and the key ID; encrypt the keystroke cipher segment to generate an encrypted keystroke cipher segment; create a keystroke message comprising at least the encrypted keystroke cipher segment; transmit the keystroke message from the keyboard device driver to a window event handler via an input/output (I/O) message channel native to an operating system running on the computer system, the window event handler being responsible for providing keystroke data to applications running on the operating system; receive the keystroke message at the window event handler; decrypt the encrypted keystroke cipher segment, thereby identifying the key ID; and transmit the key ID to a first application.

(41) An example non-transitory computer storage medium has stored thereon program code executable by a processor, the program code embodying a method comprising: receiving, by a keyboard device driver, a key identifier (ID) from a keyboard device, the key ID representing a keystroke event occurring on the computing device via the keyboard device; creating a keystroke cipher segment comprising a primary authentication code and the key ID; encrypting the keystroke cipher segment to generate an encrypted keystroke cipher segment; creating a keystroke message comprising at least the encrypted keystroke cipher segment; transmitting the keystroke message from the keyboard device driver to a window event handler via an input/output (I/O) message channel native to an operating system, the window event handler being responsible for providing keystroke data to applications running on the operating system; receiving the keystroke message at the window event handler; decrypting the encrypted keystroke cipher segment, thereby identifying the key ID; and transmitting the key ID to a first application.

(42) Another example computer system comprises: a processor; and a non-transitory computer readable medium having stored thereon program code executable by the processor, the program code causing the processor to perform a method disclosed herein. Another example non-transitory computer storage medium has stored thereon program code executable by a processor, the program code embodying a method disclosed herein.

(43) Alternatively, or in addition to the other examples described herein, examples include any combination of the following: installing and executing a keystroke encryption module in conjunction with a keyboard device driver; installing and executing a keystroke decryption module

in conjunction with a window event handler; resetting shared cipher parameters; creating new key arrays for Simon32 encryption (or other 32 bits block encryption algorithms); randomly generating a number between 16 and 32 to run Simon32 encryption (or other 32 bits block encryption algorithms) that number of times; incrementing a counter configured to count a number of times keys have been generated; sharing cipher parameters between partner encryption module and decryption module; receiving a new keystroke that includes keystroke data; receiving keystroke data that includes one or more of a scan code and a virtual-key code; inserting one or more of a key identifier, a randomly generated value, and an authentication code in a plaintext cipher segment; assembling a hash segment that includes one or more of: any number of zeros, an authentication code, a tag value, and a key identifier; hashing a data segment using triple32 (or other hash algorithms that give a 32 bits result); XOR-folding a data segment (or other folding method); using a number of least significant bits of a data segment as an authentication code; encrypting a cipher segment; embedding an encrypted cipher segment as any field in a keystroke message; transmitting a keystroke message through a keystroke I/O message channel native to an operating system; performing one or more dummy encryption operations; retaining two or more copies of the most recent cipher parameters; receiving a key identifier (ID) from a keyboard device, the key ID representing a keystroke event occurring on the computing device via the keyboard device; creating a keystroke cipher segment comprising a primary authentication code and a key ID; encrypting a keystroke cipher segment to generate an encrypted keystroke cipher segment; creating a keystroke message comprising at least an encrypted keystroke cipher segment; transmitting a keystroke message from a keyboard device driver to a window event handler via an input/output (I/O) message channel native to an operating system running on the computing device; an operating system including one of Microsoft Windows, Apple MacOS, Google ChromeOS, Apple iOS, linux, unix; a window event handler that is responsible for providing keystroke data to applications running on the operating system; receiving a keystroke message at the window event handler; decrypting one or more portions of the encrypted keystroke cipher segment at the window event handler; transmitting a key ID to a first application; storing an encrypted keystroke cipher segment in a preexisting field provided by a I/O message channel; a preexisting field provided by an I/O message channel (e.g., an ExtraInformation field defined by a keyboard input data object); a preexisting field is four bytes in size; an encrypted keystroke cipher segment is four bytes in size; encrypting a keystroke cipher segment is performed by an encryption module integrated with the keyboard device driver; encrypting the keystroke cipher segment using Simon32 encryption algorithm; a primary authentication code includes a shared authentication code that is known by both an encryption module configured to perform the encrypting of the keystroke cipher segment and a decryption module configured to perform the decrypting of the encrypted keystroke cipher segment, the method further comprising authenticating the keystroke message by the decryption module using the shared authentication code.

Exemplary Operating Environment

(44) The present disclosure is operable with a computing device (computing apparatus) according to an embodiment shown as a functional block diagram **500** in FIG. **5**. In an embodiment, components of a computing apparatus **518** is implemented as part of an electronic device according to one or more embodiments described in this specification. The computing apparatus **518** comprises one or more processors **519** which may be microprocessors, controllers, or any other suitable type of processors for processing computer executable instructions to control the operation of the electronic device. Alternatively, or in addition, the processor **519** is any technology capable of executing logic or instructions, such as a hardcoded machine. Platform software comprising an operating system **520** or any other suitable platform software may be provided on the computing apparatus **518** to enable application software **521** to be executed on the device. According to an embodiment, the operations described herein are accomplished by software, hardware, and/or firmware.

(45) Computer executable instructions may be provided using any computer-readable medium (e.g., any non-transitory computer storage medium) or media that are accessible by the computing apparatus **518**. Computer-readable media may include, for example, computer storage media such as a memory **522** and communications media. Computer storage media, such as a memory **522**, include volatile and non-volatile, removable, and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, program modules or the like. Computer storage media include, but are not limited to, hard disks, RAM, ROM, EPROM, EEPROM, NVMe devices, persistent memory, phase change memory, flash memory or other memory technology, compact disc (CD, CD-ROM), digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage, shingled disk storage or other magnetic storage devices, or any other non-transmission medium (e., non-transitory) that can be used to store information for access by a computing apparatus. In contrast, communication media may embody computer readable instructions, data structures, program modules, or the like in a modulated data signal, such as a carrier wave, or other transport mechanism. As defined herein, computer storage media do not include communication media. Therefore, a computer storage medium should not be interpreted to be a propagating signal per se. Propagated signals per se are not examples of computer storage media. Although the computer storage medium (the memory **522**) is shown within the computing apparatus **518**, it will be appreciated by a person skilled in the art, that the storage may be distributed or located remotely and accessed via a network or other communication link (e.g. using a communication interface **523**). Computer storage media are tangible, non-transitory, and are mutually exclusive to communication media.

(46) The computing apparatus **518** may comprise an input/output controller **524** configured to output information to one or more output devices **525**, for example a display or a speaker, which may be separate from or integral to the electronic device. The input/output controller **524** may also be configured to receive and process an input from one or more input devices **526**, for example, a keyboard, a microphone, or a touchpad. In one embodiment, the output device **525** may also act as the input device. An example of such a device is a touch sensitive display. The input/output controller **524** may also output data to devices other than the output device, e.g. a locally connected printing device. In some embodiments, a user provides input to the input device(s) **526** and/or receive output from the output device(s) **525**.

(47) The functionality described herein can be performed, at least in part, by one or more hardware logic components. According to an embodiment, the computing apparatus **518** is configured by the program code when executed by the processor **519** to execute the embodiments of the operations and functionality described. Alternatively, or in addition, the functionality described herein can be performed, at least in part, by one or more hardware logic components. For example, and without limitation, illustrative types of hardware logic components that can be used include Field-programmable Gate Arrays (FPGAs), Application-specific Integrated Circuits (ASICs), Program-specific Standard Products (ASSPs), System-on-a-chip systems (SOCs), Complex Programmable Logic Devices (CPLDs), Graphics Processing Units (GPUs).

(48) Although described in connection with an exemplary computing system environment, examples of the disclosure are operative with numerous other general purpose or special purpose computing system environments or configurations. Examples of well-known computing systems, environments, and/or configurations that may be suitable for use with aspects of the disclosure include, but are not limited to, mobile computing devices, personal computers, server computers, hand-held or laptop devices, multiprocessor systems, gaming consoles, microprocessor-based systems, set top boxes, programmable consumer electronics, mobile telephones, network PCs, minicomputers, mainframe computers, distributed computing environments that include any of the above systems or devices.

(49) Examples of the disclosure may be described in the general context of computer-executable

instructions, such as program modules, executed by one or more computers or other devices. The computer-executable instructions may be organized into one or more computer-executable components or modules. Generally, program modules include, but are not limited to, routines, programs, objects, components, and data structures that perform particular tasks or implement particular abstract data types. Aspects of the disclosure may be implemented with any number and organization of such components or modules. For example, aspects of the disclosure are not limited to the specific computer-executable instructions or the specific components or modules illustrated in the figures and described herein. Other examples of the disclosure include different computer-executable instructions or components having more or less functionality than illustrated and described herein.

(50) Aspects of the disclosure transform a general-purpose computer into a special purpose computing device when programmed to execute the instructions described herein. The detailed description provided above in connection with the appended drawings is intended as a description of a number of embodiments and is not intended to represent the only forms in which the embodiments may be constructed, implemented, or utilized. Although these embodiments may be described and illustrated herein as being implemented in devices such as a server, computing devices, or the like, this is only an exemplary implementation and not a limitation. As those skilled in the art will appreciate, the present embodiments are suitable for application in a variety of different types of computing devices, for example, PCs, servers, laptop computers, tablet computers, etc.

(51) The term “computing device” and the like are used herein to refer to any device with processing capability such that it can execute instructions. Those skilled in the art will realize that such processing capabilities are incorporated into many different devices and therefore the terms “computer”, “server”, and “computing device” each may include PCs, servers, laptop computers, mobile telephones (including smart phones), tablet computers, and many other devices. Any range or device value given herein may be extended or altered without losing the effect sought, as will be apparent to the skilled person. Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

(52) While no personally identifiable information is tracked by aspects of the disclosure, examples may have been described with reference to data monitored and/or collected from the users. In some examples, notice may be provided to the users of the collection of the data (e.g., via a dialog box or preference setting) and users are given the opportunity to give or deny consent for the monitoring and/or collection. The consent may take the form of opt-in consent or opt-out consent.

(53) The order of execution or performance of the operations in examples of the disclosure illustrated and described herein is not essential, unless otherwise specified. That is, the operations may be performed in any order, unless otherwise specified, and examples of the disclosure may include additional or fewer operations than those disclosed herein. For example, it is contemplated that executing or performing a particular operation before, contemporaneously with, or after another operation is within the scope of aspects of the disclosure. It will be understood that the benefits and advantages described above may relate to one embodiment or may relate to several embodiments. When introducing elements of aspects of the disclosure or the examples thereof, the articles “a,” “an,” and “the” are intended to mean that there are one or more of the elements. The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements. The term “exemplary” is intended to mean “an example of.”

(54) Having described aspects of the disclosure in detail, it will be apparent that modifications and variations are possible without departing from the scope of aspects of the disclosure as defined in

the appended claims. As various changes may be made in the above constructions, products, and methods without departing from the scope of aspects of the disclosure, it is intended that all matter contained in the above description and shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

Claims

1. A computer-implemented method of encrypting keystroke data in a computing device, the method comprising: receiving, by a keyboard device driver of the computing device, a key identifier (ID) from a keyboard device, the key ID representing a keystroke event occurring on the computing device via the keyboard device; creating a keystroke cipher segment comprising a random number, a primary authentication code and the key ID; encrypting the keystroke cipher segment resulting in an encrypted keystroke cipher segment; transmitting the encrypted keystroke cipher segment in a keystroke message from the keyboard device driver to a window event handler via an input/output (I/O) message channel of an operating system running on the computing device, the window event handler being responsible for providing keystroke data to applications running on the operating system; receiving the keystroke message at the window event handler; decrypting the encrypted keystroke cipher segment, thereby identifying the key ID; and transmitting the key ID to a first application for further processing.
2. The computer-implemented method of claim 1, further comprising creating the keystroke message including storing the encrypted keystroke cipher segment in a preexisting field provided by the I/O message channel.
3. The computer-implemented method of claim 2, wherein the preexisting field provided by the I/O message channel is an ExtraInformation field defined by a keyboard input data object.
4. The computer-implemented method of claim 2, further comprising regenerating the random number and the primary authentication code for another key ID.
5. The computer-implemented method of claim 1, wherein encrypting the keystroke cipher segment is performed by an encryptor integrated with the keyboard device driver.
6. The computer-implemented method of claim 1, wherein encrypting the keystroke cipher segment includes encrypting the keystroke cipher segment with a random quantity of encryption rounds using a different key in each of the encryption rounds.
7. The computer-implemented method of claim 1, wherein the primary authentication code includes a shared authentication code that is known by both an encryptor configured to perform the encrypting of the keystroke cipher segment and a decryptor configured to perform the decrypting of the encrypted keystroke cipher segment, the method further comprising authenticating the keystroke message by the decryptor using the shared authentication code.
8. A computer system comprising: a keyboard device; a processor; and a non-transitory computer readable medium having stored thereon program code executable by the processor, the program code causing the processor to: receive, by a keyboard device driver managing the keyboard device, a key identifier (ID) from the keyboard device, the key ID representing a keystroke event occurring via the keyboard device; create a keystroke cipher segment comprising a random number, a primary authentication code and the key ID; encrypt the keystroke cipher segment resulting in an encrypted keystroke cipher segment; transmit the encrypted keystroke cipher segment in a keystroke message from the keyboard device driver to a window event handler via an input/output (I/O) message channel of an operating system running on the computer system, the window event handler being responsible for providing keystroke data to applications running on the operating system; receive the keystroke message at the window event handler; decrypt the encrypted keystroke cipher segment, thereby identifying the key ID; and transmit the key ID to a first application for further processing.
9. The computer system of claim 8, wherein the program code further causes the processor to create

the keystroke message including storing the encrypted keystroke cipher segment in a preexisting field provided by the I/O message channel.

10. The computer system of claim 9, wherein the preexisting field provided by the I/O message channel is an ExtraInformation field defined by a keyboard input data object.

11. The computer system of claim 9, wherein the program code further causes the processor to regenerate the random number and the primary authentication code for another key ID.

12. The computer system of claim 8, wherein encrypting the keystroke cipher segment is performed by an encryptor integrated with the keyboard device driver.

13. The computer system of claim 8, wherein encrypting the keystroke cipher segment includes encrypting the keystroke cipher segment with a random quantity of encryption rounds using a different key in each of the encryption rounds.

14. The computer system of claim 8, wherein the primary authentication code includes a shared authentication code that is known by both an encryptor configured to perform the encrypting of the keystroke cipher segment and a decryptor configured to perform the decrypting of the encrypted keystroke cipher segment, the program code further causing the processor to authenticate the keystroke message by the decryptor using the shared authentication code.

15. A non-transitory computer storage medium having stored thereon program code executable by a processor, the program code embodying a method comprising: receiving, by a keyboard device driver, a key identifier (ID) from a keyboard device, the key ID representing a keystroke event occurring on a computing device via the keyboard device; creating a keystroke cipher segment comprising a random number, a primary authentication code and the key ID; encrypting the keystroke cipher segment resulting in an encrypted keystroke cipher segment; transmitting the encrypted keystroke cipher segment in a keystroke message from the keyboard device driver to a window event handler via an input/output (I/O) message channel of an operating system, the window event handler being responsible for providing keystroke data to applications running on the operating system; receiving the keystroke message at the window event handler; decrypting the encrypted keystroke cipher segment, thereby identifying the key ID; and transmitting the key ID to a first application for further processing.

16. The non-transitory computer storage medium of claim 15, wherein the method further comprises creating the keystroke message including storing the encrypted keystroke cipher segment in a preexisting field provided by the I/O message channel.

17. The non-transitory computer storage medium of claim 16, wherein the preexisting field provided by the I/O message channel is an ExtraInformation field defined by a keyboard input data object.

18. The non-transitory computer storage medium of claim 15, wherein encrypting the keystroke cipher segment is performed by an encryptor integrated with the keyboard device driver.

19. The non-transitory computer storage medium of claim 15, wherein encrypting the keystroke cipher segment includes encrypting the keystroke cipher segment with a random quantity of encryption rounds using a different key in each of the encryption rounds.

20. The non-transitory computer storage medium of claim 15, wherein the primary authentication code includes a shared authentication code that is known by both an encryptor configured to perform the encrypting of the keystroke cipher segment and a decryptor configured to perform the decrypting of the encrypted keystroke cipher segment, the method further comprising authenticating the keystroke message by the decryptor using the shared authentication code.
