

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413485
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Groff; Montgomery Nelson

System and method to generate optimized spectrum administration service (SAS) configuration commands

Abstract

An apparatus comprises a memory and a processor communicatively coupled to one another. The memory may be configured to store a data lake and multiple existing spectrum administration service (SAS) configuration commands. The processor may be configured to perform first SAS operations in accordance with the existing SAS configuration commands, collect multiple channel parameters from one or more communication channels configured to provide connectivity between user equipment and a core network, store the channel parameters in the data lake, monitor the channel parameters in the data lake, and generate optimized SAS configuration commands based at least in part upon the channel parameters. Further, the processor is configured to compare the optimized SAS configuration commands to the existing SAS configuration commands and perform second SAS operations in accordance with the optimized SAS configuration commands.

Inventors:	Groff; Montgomery Nelson (Denver, CO)
Applicant:	DISH Wireless L.L.C. (Englewood, CO)
Family ID:	92538753
Assignee:	DISH Wireless L.L.C. (Englewood, CO)
Appl. No.:	18/447411
Filed:	August 10, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250055768 A1	Feb. 13, 2025

Publication Classification

Int. Cl.: H04L41/40 (20220101); H04L41/16 (20220101); H04W24/02 (20090101)

U.S. Cl.:

CPC **H04L41/40** (20220501); **H04L41/16** (20130101); **H04W24/02** (20130101);

Field of Classification Search

CPC: H04L (41/40); H04L (41/16); H04W (24/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7920472	12/2010	Porat	370/398	H04L 47/762
10177998	12/2018	Parandehgheibi et al.	N/A	N/A
10572226	12/2019	Biskup et al.	N/A	N/A
10756949	12/2019	Kulshreshtha et al.	N/A	N/A
11082487	12/2020	Jain et al.	N/A	N/A
11119980	12/2020	Szczepanik et al.	N/A	N/A
11157629	12/2020	Shenoy et al.	N/A	N/A
11178182	12/2020	Saxena et al.	N/A	N/A
11233821	12/2021	Yadav et al.	N/A	N/A
11240153	12/2021	Vasseur et al.	N/A	N/A
11321337	12/2021	Nucci et al.	N/A	N/A
2019/0378073	12/2018	Lopez et al.	N/A	N/A
2020/0027052	12/2019	Aiyer	N/A	N/A
2020/0211141	12/2019	Argyle et al.	N/A	N/A
2020/0372576	12/2019	Sundaram et al.	N/A	N/A
2020/0394455	12/2019	Lee et al.	N/A	N/A
2021/0076223	12/2020	Taneja	N/A	G06N 20/00
2022/0007374	12/2021	Sevindik	N/A	H04W 16/22
2022/0021652	12/2021	Moghe et al.	N/A	N/A
2022/0075889	12/2021	Friedman	N/A	N/A
2022/0076165	12/2021	Minkin et al.	N/A	N/A
2022/0150760	12/2021	Balasubramanian	N/A	H04L 43/0876
2022/0182128	12/2021	Taneja et al.	N/A	N/A
2022/0209971	12/2021	Doshi et al.	N/A	N/A
2022/0215028	12/2021	Nanda et al.	N/A	N/A
2022/0383417	12/2021	Cummings	N/A	N/A
2023/0062655	12/2022	Wan et al.	N/A	N/A
2023/0164756	12/2022	Vankayala	370/329	H04W 72/121
2023/0199820	12/2022	Balasubramanian	370/329	H04W 28/0862
2023/0370865	12/2022	Reeves	N/A	H04W 24/02
2024/0394149	12/2023	Ambaljeri	N/A	G06F 16/2358
2025/0008346	12/2024	Singh	N/A	G06N 20/00

OTHER PUBLICATIONS

Data Lakes, Databricks, retrieved Sep. 7, 2024 from <<https://databricks.com/discover/data-lakes/introduction>>, Evidenced by the Wayback machine Jul. 31, 2022, p. 1-4 (Year: 2022). cited by examiner

Definition of “monitoring”, Oxford Dictionary, <https://www.oed.com/dictionary/monitor_v?tab=meaning_and_use#36265198>, 1944, p. 1-5 (Year: 1944). cited by examiner
World Wide Technology, CBRS Technology Overview, Aug. 11, 2020, Retrieved from
<<https://www.wwt.com/video/cbrs-technology-overview>>, p. 1-16 (Year: 2020). cited by examiner
PCT International Search Report and Written Opinion of the International Searching Authority, or
the Declaration for International Application No. PCT/US2024/041042, mailed Nov. 22, 2024
(Nov. 22, 2024), 17 pages. cited by applicant

Primary Examiner: Dollinger; Tonia L

Assistant Examiner: Cousins; Joseph M

Attorney, Agent or Firm: Baker Botts L.L.P.

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates generally to optimization of Spectrum Administration Service (SAS) operations in a communication system, and more specifically to a system and a method to generate optimized SAS configuration commands.

BACKGROUND

(2) In some wireless communications systems, a Spectrum Access System (SAS) is a frequency coordination system that manages the Citizens Broadband Radio Service (CBRS) spectrum in the 3.5 gigahertz (GHz) band. The SAS manages spectrum sharing on a dynamic, as-needed basis across three tiers. The SAS may provide priority to a top tier, while preventing interference to lower tiers. The three tiers in the CBRS band comprise Incumbent Access licenses, Priority Access licenses (PALs), and General Authorized Access licenses (GAA). The Federal Communications Commission (FCC) requires the use of a SAS administrator to coordinate and manage operations of the three tiers to prevent interference to higher priority users. The SAS dynamically manages spectra for all three tiers with first priority for incumbents, second priority for PALs and third priority for GAA users.

SUMMARY OF THE DISCLOSURE

(3) In one or more embodiments, the system and the method disclosed herein generate optimized Spectrum Administration Service (SAS) configuration commands. In particular, the system and the method may implement one or more existing SAS configuration commands to route and assign spectra of certain communication channels to one or more connected devices. In performing one or more SAS operations (e.g., routing operations and spectra assigning operations), multiple channel parameters are determined from the communication channels during the SAS operations. In some embodiments, the channel parameters are dynamically stored in a data lake. At this stage, a machine learning algorithm is executed to monitor, analyze, and structure the channel parameters in the data lake. A channel optimization controller may be configured to generate the optimized SAS configuration commands based at least in part upon outputs from the machine learning algorithm. In some embodiments, a SAS administrator may monitor activity on one, some, or all Citizen Broadband Radio Service (CBRS) channels to obtain the channel parameters. The optimized SAS configuration commands may dynamically modify some of the communication channels that are affected by interference (e.g., low quality of service and performance) by automatically moving CBRS channels to the best frequency available in a given area.

(4) In one or more embodiments, the system and the method described herein are integrated into a

practical application to perform SAS operations based at least in part upon optimized SAS configuration commands. In particular, the system and the method are integrated into a practical application of dynamically updating the SAS operations to account for current and historical changes to the CBRS channels. For example, the system and the method may generate optimized SAS configuration commands that are performed to correct interference identified in one of the CBRS channels over time based at least in part on one or more conditions. The conditions may comprise determining a traffic level in a given CBRS channel at a time of day and routing modifications to ease tension in the given CBRS channel. The system and the method may train the machine learning algorithm with the conditions and the routing modifications. In a future event, based at least in part on the training, the system and the method may implement the machine learning algorithm to preemptively provide the routing modifications as soon as the conditions are identified.

(5) In addition, the system and method described herein are integrated into a technical advantage of increasing processing speeds in a computer system, because processors associated with the system and the method comprise a machine learning algorithm that actively generate insights for any identified channel parameters. In the machine learning algorithm, the system and the method may provide the optimized SAS configuration commands based on some or all raw data obtained from the CBRS channels. As the machine learning algorithm is trained to account for many of the situations and conditions occurring in the CBRS channels, multiple optimized SAS configuration commands are generated to relieve stress conditions in communication networks during the SAS operations. As a result, processing speed during SAS operations is improved because the system and the method comprise optimized SAS configuration commands that may preventively set conditions during the SAS operations to prevent stress in the networks and reduce traffic. Under these improvements, the system and the method provide a practical application of maintaining operations in the network for longer periods of time by reducing downtime caused by heavy traffic conditions in the networks.

(6) In one or more embodiments, the system and the method may be performed by an apparatus, such as a server, communicatively coupled to multiple network components in a core network, one or more base stations in a radio access network, and one or more user equipment. Further, the system may be a wireless communication system, that comprises the apparatus. In addition, the system and the method may be performed as part of a process performed by the apparatus communicatively coupled to the network components in the core network. As a non-limiting example, the apparatus may comprise a memory and a processor communicatively coupled to one another. The memory may be configured to store a data lake comprising one or more channel parameters, a machine learning algorithm configured to analyze and structure the channel parameters in the data lake, and multiple existing SAS configuration commands. The processor may be configured to perform first SAS operations in accordance with the existing SAS configuration commands, collect multiple channel parameters from multiple communication channels configured to provide connectivity between user equipment and a core network, store the channel parameters in the data lake, monitor the channel parameters in the data lake in response to executing the machine learning algorithm, and generate optimized SAS configuration commands based at least in part upon the channel parameters. The optimized SAS configuration commands comprising being possible updates to the existing SAS configuration commands. Further, the processor is configured to compare the optimized SAS configuration commands to the existing SAS configuration commands, determine whether the optimized SAS configuration commands comprise commands that are different to those comprised in the existing SAS configuration commands, and perform second SAS operations in accordance with the optimized SAS configuration commands in response to determining that the optimized SAS configuration commands comprise commands that are different to those comprised in the existing SAS configuration commands.

(7) Certain embodiments of this disclosure may comprise some, all, or none of these advantages. These advantages and other features will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings and claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) For a more complete understanding of this disclosure, reference is now made to the following brief description, taken in connection with the accompanying drawings and detailed description, wherein like reference numerals represent like parts.

(2) FIG. 1 illustrates an example communication system in accordance with one or more embodiments;

(3) FIG. 2 illustrates examples of one or more monitoring operations performed in conjunction with the example communication system of FIG. 1; and

(4) FIG. 3 illustrates an example flowchart of a method to generate optimized Spectrum Administration Service (SAS) configuration commands in conjunction with the operational flow of FIG. 2.

DETAILED DESCRIPTION

(5) In one or more embodiments, a Spectrum Administration Service (SAS) is a frequency coordination system that manages Citizens Broadband Radio Service (CBRS) spectrum in the 3.5 gigahertz (GHz) band. As described above, this disclosure provides various systems and methods to generate optimized SAS configuration commands. FIG. 1 illustrates a communication system **100** in which a server **102** performs one or more SAS operations based on historical configuration commands derived from the CBRS spectrum. FIG. 2 illustrates monitoring operations **200** performed by the communication system **100** of FIG. 1. FIG. 3 illustrates a process **300** performed by the communication system **100** of FIG. 1.

(6) Communication System Overview

(7) FIG. 1 illustrates a diagram of a communication system **100** (e.g., a wireless communication system) that comprises a server **102** configured to generate optimized SAS configuration commands, in accordance with one or more embodiments. In the communication system **100** of FIG. 1, the server **102** may be communicatively coupled to one or more data networks **104**, a core network **106**, and a radio access network (RAN) **108**. In FIG. 1, the server is communicatively coupled to multiple user equipment **110A-110G** (collectively, user equipment **110**) via the RAN **108** via multiple corresponding communication links **112A-112G** (collectively, communication links **112**) established between each user equipment **110** and the RAN **108**. As represented by a user equipment **110G**, the user equipment **110** may be operated or attended to by one or more users **114**. In the example of FIG. 1, the server **102** may be communicatively coupled to multiple additional devices in the communication system **100**. While FIG. 1 shows the server **102** connected directly to the one or more data networks **104**, the server **102** may be located inside the core network **106** as part of one or more of the network components (e.g., any of the network components **116A-116G**) in the core network **106**.

(8) In one or more embodiments, the communication system **100** comprises the user equipment **110**, the RAN **108**, the core network **106**, the one or more data networks **104**, and the server **102**. In some embodiments, the communication system **100** may comprise a Fifth Generation (5G) mobile network or wireless communication system, utilizing high frequency bands (e.g., 24 Gigahertz (GHz), 39 GHz, and the like) or lower frequency bands such (e.g., Sub 6 GHz). In this regard, the communication system **100** may comprise a large number of antennas. In some embodiments, the communication system may perform one or more monitoring operations associated with the 5G New Radio (NR) protocols described in reference to the Third Generation Partnership Project

(3GPP). As part of the 5G NR protocols, the communication system **100** may perform one or more millimeter (mm) wave technology operations to improve bandwidth or latency in wireless communications.

(9) In some embodiments, the communication system **100** may be configured to partially or completely enable communications via one or more various radio access technologies (RATs), wireless communication technologies, or telecommunication standards, such as Global System for Mobiles (GSM) (e.g., Second Generation (2G) mobile networks), Universal Mobile Telecommunications System (UMTS) (e.g., Third Generation (3G) mobile networks), Long Term Evolution (LTE) of mobile networks, LTE-Advanced (LTE-A) mobile networks, 5G NR mobile networks, or Sixth Generation (6G) mobile networks.

(10) Communication System Components

(11) Server

(12) The server **102** is generally any device or apparatus that is configured to process data, communicate with the data networks **104**, one or more network components **116A-116G** (collectively, network components **116**) in the core network **106**, the RAN **108**, and the user equipment **110**. The server **102** may be configured to monitor, track data, control routing of signal, and control operations of certain electronic components in the communication system **100**, associated databases, associated systems, and the like, via one or more interfaces. The server **102** is generally configured to oversee operations of the server processing engine **120**. The operations of the server processing engine **120** are described further below. In some embodiments, the server **102** comprises a server processor **122**, one or more server Input (I)/Output (O) interfaces **124**, a channel optimization controller **126** configured to generate one or more optimized SAS configuration commands **128**, and a server memory **130** communicatively coupled to one another. The server **102** may be configured as shown, or in any other configuration. As described above, the server **102** may be located in one of the network components **116** located in the core network **106** and may be configured to perform one or more network functions (NFs) associated with monitoring operations **200** described in reference to FIG. 2.

(13) The server processor **122** may comprise one or more processors operably coupled to and in signal communication with the one or more server I/O interfaces **124**, the channel optimization controller **126**, and the server memory **130**. The server processor **122** is any electronic circuitry, including, but not limited to, state machines, one or more central processing unit (CPU) chips, logic units, cores (e.g., a multi-core processor), field-programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), or digital signal processors (DSPs). The server processor **122** may be a programmable logic device, a microcontroller, a microprocessor, or any suitable combination of the preceding. The one or more processors in the server processor **122** are configured to process data and may be implemented in hardware or software executed by hardware. For example, the server processor **122** may be an 8-bit, a 16-bit, a 32-bit, a 64-bit, or any other suitable architecture. The server processor **122** may comprise an arithmetic logic unit (ALU) to perform arithmetic and logic operations, processor registers that supply operands to the ALU, and store the results of ALU operations, and a control unit that fetches software instructions such as server instructions **132** from the server memory **130** and executes the server instructions **132** by directing the coordinated operations of the ALU, registers and other components via the server processing engine **120**. The server processor **122** may be configured to execute various instructions. For example, the server processor **122** may be configured to execute the server instructions **132** to perform functions or perform operations disclosed herein, such as some or all of those described with respect to FIGS. 1-3. In some embodiments, the functions described herein are implemented using logic units, FPGAs, ASICs, DSPs, or any other suitable hardware or electronic circuitry.

(14) In one or more embodiments, the server I/O interfaces **124** may be hardware configured to perform one or more monitoring operations **200** described in reference to FIG. 2. The server I/O

interfaces **124** may comprise one or more antennas as part of a transceiver, a receiver, or a transmitter for communicating using one or more wireless communication protocols or technologies. In some embodiments, the server I/O interfaces **124** may be configured to communicate using, for example, NR or LTE using at least some shared radio components. In other embodiments, the server I/O interfaces **124** may be configured to communicate using single or shared radio frequency (RF) bands. The RF bands may be coupled to a single antenna, or may be coupled to multiple antennas (e.g., for a multiple-input multiple output (MIMO) configuration) to perform wireless communications. The server I/O interfaces **124** may be configured to comprise one or more peripherals such as a network interface, one or more administrator interfaces, and one or more displays.

(15) The server network interfaces that may be part of the server I/O interfaces **124** may be any suitable hardware or software (e.g., executed by hardware) to facilitate any suitable type of communication in wireless or wired connections. These connections may comprise, but not be limited to, all or a portion of network connections coupled to additional network components **116** in the core network **106**, the RAN **108**, the user equipment **110**, the Internet, an Intranet, a private network, a public network, a peer-to-peer network, the public switched telephone network, a cellular network, a local area network (LAN), a metropolitan area network (MAN), a wide area network (WAN), and a satellite network. The server network interface may be configured to support any suitable type of communication protocol.

(16) The one or more administrator interfaces that may be part of the server I/O interfaces **124** may be user interfaces configured to provide access and control to of the server **102** to one or more users (e.g., the user **114**) or electronic devices. The one or more users may access the server memory **130** upon confirming one or more access credentials to demonstrate that access or control to the server **102** may be modified. In some embodiments, the one or more administrator interfaces may be configured to provide hardware and software resources to the one or more users. Examples of user devices comprise, but are not limited to, a laptop, a computer, a smartphone, a tablet, a smart device, an Internet-of-Things (IoT) device, a simulated reality device, an augmented reality device, or any other suitable type of device. The administrator interfaces may enable access to one or more graphical user interfaces (GUIs) via an image generator display (e.g., one or more displays), a touchscreen, a touchpad, multiple keys, multiple buttons, a mouse, or any other suitable type of hardware that allow users to view data or to provide inputs into the server **102**. The server **102** may be configured to allow users to send requests to one or more user equipment **110**.

(17) In the example of FIG. **1**, the one or more displays that may be part of the server I/O interfaces **124** may be configured to display a two-dimensional (2D) or three-dimensional (3D) representation of a service. Examples of the representations may comprise, but are not limited to, a graphical or simulated representation of an application, diagram, tables, or any other suitable type of data information or representation. In some embodiments, the one or more displays may be configured to present visual information to one or more users (not shown). The one or more displays may be configured to present visual information to the one or more users updated in real-time. The one or more displays may be a wearable optical display (e.g., glasses or a head-mounted display (HMD)) configured to reflect projected images and enable user to see through the one or more displays. For example, the one or more displays may comprise display units, one or more lenses, one or more semi-transparent mirrors embedded in an eye glass structure, a visor structure, or a helmet structure. Examples of display units comprise, but are not limited to, a cathode ray tube (CRT) display, a liquid crystal display (LCD), a liquid crystal on silicon (LCOS) display, a light emitting diode (LED) display, an organic LED (OLED) display, an active-matrix OLED (AMOLED) display, a projector display, or any other suitable type of display. In another embodiment, the one or more displays are a graphical display on the server **102**. For example, the graphical display may be a tablet display or a smartphone display configured to display the data representations.

(18) In some embodiments, the channel optimization controller **126** may be any combination of a

baseband processor, analog RF signal processing circuitry (e.g., including filters, mixers, oscillators, amplifiers, and the like), or digital processing circuitry (e.g., for digital modulation as well as other digital processing). For example, the channel optimization controller **126** may be configured to allocate power, frequency, and sensing resources during wireless monitoring operations **200** described in reference to FIG. 2. In some embodiments, the channel optimization controller **126** may be configured to generate one or more of optimized SAS configuration commands **128**.

(19) The server memory **130** may be volatile or non-volatile and may comprise a read-only memory (ROM), random-access memory (RAM), ternary content-addressable memory (TCAM), dynamic random-access memory (DRAM), and static random-access memory (SRAM). The server memory **130** may be implemented using one or more disks, tape drives, solid-state drives, and/or the like. The server memory **130** is operable to store the server instructions **132**, one or more configuration scripts **134**, one or more existing SAS configuration commands **136**, one or more service directories **138**, a data lake **140** comprising one or more determined channel parameters **142**, a machine learning algorithm **144**, multiple artificial intelligence commands **146**, one or more CBRS logs **148**, and one or more tier lists **152** comprising multiple distribution tiers **154A-154C** (collectively, tiers **154**). In the server memory **130**, the server instructions **132** may comprise commands and controls for operating one or more specific NFs in the core network **106** when executed by the server processing engine **120** of the server processor **122**.

(20) In one or more embodiments, the one or more configuration scripts **134** are configured to instruct one or more network components **116** in the core network **106** to establish one or more SAS configuration commands **136** or one of the optimized SAS configuration commands **128** to perform the SAS operations. The one or more configuration scripts **134** enable automation of the routing and configuration of network components **116** in the core network **106**. In this regard, the one or more configuration scripts **134** may reconfigure multiple cloud-NFs (CNFs) that establish initial communication sessions with at least one NRF in a communication path comprising one or more additional network components **116**. In this regard, the one or more configuration scripts **134** instruct routing and configuration of communication procedures based on static routing commands to restore restores services in the core network **106**.

(21) In one or more embodiments, the SAS configuration commands **136** are configured to establish one or more communication sessions between the network components **116** in the core network **106** and the user equipment **110**. Each configuration command of the SAS configuration commands **136** may be configured to provide control information to perform one or more of the SAS operations. Further, the SAS configuration commands **136** may be routing and configuration information for reinstating or reestablishing communication sessions. The SAS configuration commands **136** may be dynamically or periodically updated from the network components **116** in the core network **106**. In one or more embodiments, the optimized SAS configuration commands **128** are configured to establish one or more optimized communication sessions between the network components **116** in the core network **106** and the user equipment **110**. Each configuration command of the optimized SAS configuration commands **128** may be configured to provide control information to perform one or more of the SAS operations based at least in part upon the analyzed data from the data lake **140**. Further, the optimized SAS configuration commands **128** may be routing and configuration information for reinstating or reestablishing communication sessions. The optimized SAS configuration commands **128** may be dynamically or periodically updated from the network components **116** in the core network **106**. In some embodiments, the optimized SAS configuration commands **128** may comprise possible updates to the existing SAS configuration commands **136**.

(22) The service directories **138** may be configured to store service-specific information and/or user-specific information. The service directories **138** may enable the server **102** to confirm user credentials to access one or more network components (e.g., one of the network components **116**

configured to perform one or more NFs in the core network **106**. The service directories **138** may be configured to store provider-specific information. The service directories **138** may enable the server **102** to validate credentials associated with a specific provider (e.g., one of the CNFs) against corresponding user-specific information in the service directories **138**.

(23) In some embodiments, the data lake **140** is a storage repository configured to store large amount of structured, semi-structured, and unstructured data. In some embodiments, the data lake **140** is configured to store every type of data in its native format without fixed limits. The data lake **140** may be updated periodically or dynamically (e.g., updated in real-time). In some embodiments, the data lake **140** may be located in the server memory **130** or located at a remote location different from a location of the server **102**. The data lake **140** may be configured to store one or more of the channel parameters **142** in a corresponding raw format preselected in accordance with one or more rules or policies.

(24) In one or more embodiments, the machine learning algorithm **144** may be configured to converts the data stored by the data lake **140** to generate structured data for further analysis. Further, the machine learning algorithm **144** may be configured to interpret and transform the channel parameters **142** into structured data sets and subsequently stored as files or tables. The machine learning algorithm **144** may cleanse, normalize raw data, and derive intermediate data to generate uniform data in terms of encoding, format, and data types. The machine learning algorithm **144** may be executed to run user queries and advanced analytical tools on the structured data. The machine learning algorithm **144** may be configured to generate the one or more artificial intelligence commands **146** based on current channel parameters **142** and the existing SAS configuration commands **136**. In turn, the channel optimization controller **126** may be configured to generate the optimized SAS configuration commands **128** based on the outputs of the machine learning algorithm **144**. The artificial intelligence commands **146** may be parameters that modify routing of resources in the CBRS channels to be allocated in the communication network. The artificial intelligence commands **146** may be combined with the existing SAS configuration commands **136** to create the optimized SAS configuration commands **128**.

(25) In some embodiments, the CBRS logs **148** may comprise the incumbent lists **150** and the tier lists **152**. The CBRS logs **148** may comprise information listing the resources of the CBRS channels available for SAS management. The incumbent lists **150** may comprise lists of electronic devices (e.g., the user equipment **110**) that are configured to receive resources allocated from the server **102**. The tier lists **152** comprise one or more priority levels for each of the electronic devices. In one or more embodiments, a SAS manages spectrum sharing on a dynamic, as-needed basis across three tiers **154**. The SAS may provide priority to a top tier **154A**, while preventing interference to lower tiers. The three tiers **154** shown in the CBRS band comprise Incumbent Access licenses, Priority Access licenses (PALs), and General Authorized Access licenses (GAA). In some embodiments, the server **102** may dynamically manage spectra for all three tiers **154** with first priority for incumbents in a first tier **154A**, second priority for PALs in a second tier **154B**, and third priority for GAA users in a third tier **154C**. In some embodiments, to use the CBRS spectrum, the server **102** may use the CBRS logs **148** to assign one or more resources and deploy corresponding CBRS access points. For example, one of the user equipment **110** may request use of the CBRS channels via a connection request. In turn, the server **102** (e.g., acting as at least a part of the SAS administrator) may receive connectivity data in the request indicating latitude, longitude, and height into a SAS database (e.g., the server memory **130**). In some embodiments, the server **102** (e.g., the SAS administrator) may determine whether the requested spectrum is available. The server **102** may then assign spectrum channels and grant authority for CBRS Devices (CBSDs) to operate in the channel in accordance with the priority level (e.g., depending in the tiers **154**) assigned to each CBSD. In this regard, the server **102** may authorize allocation of appropriate transmission power levels and allocation of channel resources.

(26) User Equipment

(27) In one or more embodiments, each of the user equipment **110** (e.g., the user equipment **110A** and a user equipment **110G** representative of the user equipment **110A-110G**) may be any computing device configured to communicate with other devices, such as the server **102**, other network components **116** in the core network **106**, databases, and the like in the communication system **100**. Each of the user equipment **110** may be configured to perform specific functions described herein and interact with one or more network components **116** in the core network **106** via one or more base stations **160**. Examples of user equipment **110** comprise, but are not limited to, a laptop, a computer, a smartphone, a tablet, a smart device, an IoT device, a simulated reality device, an augmented reality device, or any other suitable type of device.

(28) In one or more embodiments, referring to the user equipment **110A** as a non-limiting example of the user equipment **110**, the user equipment **110A** may comprise a user equipment (UE) network interface **170**, a UE I/O interface **172**, a UE processor **174** configured to execute a UE processing engine **176**, and a UE memory **178** comprising one or more UE instructions **180**. The UE network interface **170** may be any suitable hardware or software (e.g., executed by hardware) to facilitate any suitable type of communication in wireless or wired connections. These connections may comprise, but not be limited to, all or a portion of network connections coupled to additional network components **116** in the core network **106**, the RAN **108**, the Internet, an Intranet, a private network, a public network, a peer-to-peer network, the public switched telephone network, a cellular network, a local area network (LAN), a metropolitan area network (MAN), a wide area network (WAN), and a satellite network. The UE network interface **170** may be configured to support any suitable type of communication protocol.

(29) The UE I/O interface **172** may be hardware configured to perform one or more monitoring operations **200** described in reference to FIG. 2. The UE I/O interface **172** may comprise one or more antennas as part of a transceiver, a receiver, or a transmitter for communicating using one or more wireless communication protocols or technologies. In some embodiments, the UE I/O interface **172** may be configured to communicate using, for example, 5G NR or LTE using at least some shared radio components. In other embodiments, the UE I/O interface **172** may be configured to communicate using single or shared RF bands. The RF bands may be coupled to a single antenna, or may be coupled to multiple antennas (e.g., for a MIMO configuration) to perform wireless communications. In some embodiments, the user equipment **110A** may comprise capabilities for voice communication, mobile broadband services (e.g., video streaming, navigation, and the like), or other types of applications. In this regard, the UE I/O interface **172** of the user equipment **110A** may communicate using machine-to-machine (M2M) communication, such as machine-type communication (MTC), or another type of M2M communication.

(30) In some embodiments, the user equipment **110A** is communicatively coupled to one or more of the base stations **160** via one or more communication links **112** (e.g., the communication link **112A** and the communication link **112G** representative of the communication links **112**). The user equipment **110A** may be a device with cellular communication capability such as a mobile phone, a hand-held device, a computer, a laptop, a tablet, a smart watch or other wearable device, or virtually any type of wireless device. In some applications, the user equipment **110** may be referred to as a UE, UE device, or terminal.

(31) The UE processor **174** may comprise one or more processors operably coupled to and in signal communication with the UE network interface **170**, the UE I/O interface **172**, and the UE memory **178**. The UE processor **174** is any electronic circuitry, including, but not limited to, state machines, one or more CPU chips, logic units, cores (e.g., a multi-core processor), FPGAs, ASICs, or DSPs. The UE processor **174** may be a programmable logic device, a microcontroller, a microprocessor, or any suitable combination of the preceding. The one or more processors in the UE processor **174** are configured to process data and may be implemented in hardware or software executed by hardware. For example, the UE processor **174** may be an 8-bit, a 16-bit, a 32-bit, a 64-bit, or any other suitable architecture. The UE processor **174** comprises an ALU to perform arithmetic and

logic operations, processor registers that supply operands to the ALU, and store the results of ALU operations, and a control unit that fetches software instructions such as the UE instructions **180** from the UE memory **178** and executes the UE instructions **180** by directing the coordinated operations of the ALU, registers, and other components via the UE processing engine **176**. The UE processor **174** may be configured to execute various instructions. For example, the UE processor **174** may be configured to execute the UE instructions **180** to implement functions or perform operations disclosed herein, such as some or all of those described with respect to FIGS. **1-3**. In some embodiments, the functions described herein are implemented using logic units, FPGAs, ASICs, DSPs, or any other suitable hardware or electronic circuitry.

(32) Radio Access Network

(33) In one or more embodiments, the RAN **108** enables the user equipment **110** to access one or more services in the core network **106**. The one or more services may be a mobile telephone service, a Short Message Service (SMS) message service, a Multimedia Message Service (MMS) message service, an Internet access, cloud computing, or other types of data services. The RAN **108** may comprise the base stations **160** in signal communication with the user equipment **110** via the one or more communication links **112**. Each of the base stations **160** may service the user equipment **110**. In some embodiments, while multiple base stations **160** are shown connected to multiple user equipment **110** via the communication link **112**, one or more additional base stations **160** may be connected to one or more additional user equipment **110** via one or more additional communication links **112**. For example, the base station **160A-110G** may exchange connectivity signals with the user equipment **110A** via the communication link **112A**. In another example, the base station **160G** may exchange connectivity signals with the user equipment **110G** via the communication link **112G**. In yet another example, the base stations **160** may service some user equipment **110** located within a geographic area serviced by one of the base stations **160**.

(34) In one or more embodiments, referring to the base station **160A** as a non-limiting example of the base station **160**, the base station **160A** may comprise a base station (BS) network interface **182**, a BS I/O interface **184**, a BS processor **186**, and a BS memory **188**. The BS network interface **182** may be any suitable hardware or software (e.g., executed by hardware) to facilitate any suitable type of communication in wireless or wired connections between the core network **106** and the user equipment **110**. These connections may comprise, but not be limited to, all or a portion of network connections coupled to additional network components **116** in the core network **106**, other base stations **160**, the user equipment **110**, the Internet, an Intranet, a private network, a public network, a peer-to-peer network, the public switched telephone network, a cellular network, a LAN, a MAN, a WAN, and a satellite network. The BS network interface **182** may be configured to support any suitable type of communication protocol.

(35) The BS I/O interface **184** may be hardware configured to perform one or more monitoring operations **200** described in reference to FIG. **2**. The BS I/O interface **184** may comprise one or more antennas as part of a transceiver, a receiver, or a transmitter for communicating using one or more wireless communication protocols or technologies. In some embodiments, the BS I/O interface **184** may be configured to communicate using, for example, 5G NR or LTE using at least some shared radio components. In other embodiments, the BS I/O interface **184** may be configured to communicate using single or shared RF bands. The RF bands may be coupled to a single antenna, or may be coupled to multiple antennas (e.g., for a MIMO configuration) to perform wireless communications. In some embodiments, the base station **160A** may allocate resources in accordance with one or more routing and configuration operations obtained from the core network **106**. In some embodiments, resources may be allocated to enable capabilities in the user equipment **110** for voice communication, mobile broadband services (e.g., video streaming, navigation, and the like), or other types of applications.

(36) In some embodiments, the base station **160A** is communicatively coupled to one or more of the user equipment **110** via the one or more communication links **112**. In some applications, the

base stations **160A** may be referred to as BS, evolved Node B (eNodeB or eNB), a next generation Node B, gNodeB, gNB, or terminal.

(37) The BS processor **186** may comprise one or more processors operably coupled to and in signal communication with the BS network interface **182**, the BS I/O interface **184**, and the BS memory **188**. The BS processor **186** is any electronic circuitry, including, but not limited to, state machines, one or more CPU chips, logic units, cores (e.g., a multi-core processor), FPGAs, ASICs, or DSPs. The BS processor **186** may be a programmable logic device, a microcontroller, a microprocessor, or any suitable combination of the preceding. The one or more processors in the BS processor **186** are configured to process data and may be implemented in hardware or software executed by hardware. For example, the BS processor **186** may be an 8-bit, a 16-bit, a 32-bit, a 64-bit, or any other suitable architecture. The BS processor **186** comprises an ALU to perform arithmetic and logic operations, processor registers that supply operands to the ALU, and store the results of ALU operations, and a control unit that fetches software instructions (not shown) from the BS memory **188** and executes the software instructions by directing the coordinated operations of the ALU, registers, and other components via a processing engine (not shown) in the BS processor **186**. The BS processor **186** may be configured to execute various instructions. For example, the BS processor **186** may be configured to execute the software instructions to implement functions or perform operations disclosed herein, such as some or all of those described with respect to FIGS. **1-3**. In some embodiments, the functions described herein are implemented using logic units, FPGAs, ASICs, DSPs, or any other suitable hardware or electronic circuitry.

(38) Core Network

(39) The core network **106** may be a network configured to manage communication sessions for the user equipment **110**. In one or more embodiments, the core network **106** may establish connections between user equipment **110** and a particular data network **104** in accordance with one or more communication protocols. In the example of FIG. **1**, the core network **106** comprises one or more network components configured to perform one or more NFs. In some embodiments, the core network **106** enables the user equipment **110** to communicate with the server **102**, or another type of device, located in a particular data network **104** or in signal communication with a particular data network **104**. The core network **106** may implement a communication method that does not require the establishment of a specific communication protocol connection between the user equipment **110** and one or more of the data networks **104**. The core network **106** may include one or more types of network devices (not shown), which may perform different NFs.

(40) In some embodiments, the core network **106** may include a 5G NR or an LTE access network (e.g., an evolved packet core (EPC) network) among others. In this regard, the core network **106** may comprise one or more logical networks implemented via wireless connections or wired connections. Each logical network may comprise an end-to-end virtual network with dedicated power, storage, or computation resources. Each logical network may be configured to perform a specific application comprising individual policies, rules, or priorities. Further, each logical network may be associated with a particular Quality of Service (QoS) class, type of service, or particular user associated with one or more of the user equipment **110**. For example, a logical network may be a Mobile Private Network (MPN) configured for a particular organization. In this example, when the user equipment **110A** is configured and activated by a wireless network associated with the RAN **108**, the user equipment **110A** may be configured to connect to one or more particular network slices (i.e., logical networks) in the core network **106**. Any logical networks or slices that may be configured for the user equipment **110A** may be configured using a network component (e.g., one of the network components **116** (e.g., the network component **116A**, the network component **116B**, and the network component **116G** representing the network component **116A-116G**) of FIG. **1**.

(41) In one or more embodiments, each of the network components **116** may comprise a component processor **192** configured to perform one or more similar operations to those described in reference

to the BS processor **186** and the UE processor **174**. In other embodiments, each of the network components **116** may comprise a component memory **194** configured to perform one or more similar operations to those described in reference to the BS memory **188** and the UE memory **178**.

(42) Data Networks

(43) In the example system **100** of FIG. **1**, the data networks **104** may facilitate communication within the communication system **100**. This disclosure contemplates that the data networks **104** may be any suitable network operable to facilitate communication between the server **102**, the core network **106**, the RAN **108**, and the user equipment **110**. The data networks **104** may include any interconnecting system capable of transmitting audio, video, signals, data, messages, or any combination of the preceding. The data networks **104** may include all or a portion of a LAN, a WAN, an overlay network, a software-defined network (SDN), a virtual private network (VPN), a packet data network (e.g., the Internet), a mobile telephone network (e.g., cellular networks, such as 4G or 5G), a Plain Old Telephone (POT) network, a wireless data network (e.g., WiFi, WiGig, WiMax, and the like), a Long Term Evolution (LTE) network, a Universal Mobile Telecommunications System (UMTS) network, a peer-to-peer (P2P) network, a Bluetooth network, a Near Field Communication network, a Zigbee network, or any other suitable network, operable to facilitate communication between the components of the communication system **100**. In other embodiments, the communication system **100** may not have all of these components or may comprise other elements instead of, or in addition to, those above.

(44) Monitoring Operations

(45) FIG. **2** illustrates one or more communication operations **200** in accordance with one or more embodiments. The communication operations **200** may be performed by the server **102**. In the non-limiting example of FIG. **2**, the server **102** may be communicatively coupled to the data lake **140**. The data lake **140** may be configured to be stored in the server memory **130**. The data lake **140** may be configured to be a standalone database in a location remote to the server **102**. In the example of FIG. **2**, the server **102** is connected to the CBRS channels **202** in the CBRS spectrum via the connection **204** and the data lake **140** via the connection **206**. The connection **204** and the connection **206** may be internal or external to the server **102** as part of one of the server I/O interfaces **124**.

(46) In one or more embodiments, the channel parameters **142** comprise a channel connectivity registry **210** comprising connectivity interruptions **212** and connectivity success rates **214**, dynamic routing information **216**, static routing information **218**, and one or more channel communication frequency bands **220**. The connectivity interruptions **212** may be communication interruptions in the communication channels **202** over a predefined time duration. The connectivity success rates **214** may be a percentage of successful communication transactions in the communication channels **202** over the predefined time duration. The dynamic routing information **216** may be routing information that is continuously or dynamically changed in the channels **202** during one or more predefined time periods. The static routing information **218** may be routing information that remains relatively unchanged (e.g., when compared to the dynamic routing information **216**) in the channels **202** during one or more predefined time periods. The one or more channel communication frequency bands **220** may be information comprising resources corresponding to the managed portions of the channels **202** that are controlled by the server **102**.

(47) Example Process to Generate Optimized SAS Configuration Commands

(48) FIG. **3** illustrate respective example flowchart of the process **300**, in accordance with one or more embodiments. Modifications, additions, or omissions may be made to the process **300**. The process **300** may include more, fewer, or other operations than those shown above. For example, operations may be performed in parallel or in any suitable order. While at times discussed as the server **102**, one or more of the network components **116**, one or more of the base stations **160**, components of any of thereof, or any suitable system or components of the security system **100** may perform one or more operations of the process **300**. For example, one or more operations of

the process **300** may be implemented, at least in part, in the form of server instructions **132** of FIG. **1**, stored on non-transitory, tangible, machine-readable media (e.g., server memory **130** of FIG. **1** operating as a non-transitory computer readable medium) that when run by one or more processors (e.g., the server processor **122** of FIG. **1**) may cause the one or more processors to perform operations described in operations **302-322**.

(49) FIG. **3** illustrates an example flowchart of the process **300** to generate the optimized SAS configuration commands **128**, in accordance with one or more embodiments. In one or more embodiments, the process **300** comprises implementing the one or more existing SAS configuration commands **136** to route and assign spectra of certain communication channels **202** to one or more connected devices (e.g., one of the base stations **160** or the one or more user equipment **110**). In performing one or more SAS operations (e.g., routing operations and spectra assigning operations), multiple channel parameters **142** are determined from the communication channels **202** during the SAS operations. In some embodiments, the channel parameters **142** are dynamically stored in the data lakes **140**. At this stage, the machine learning algorithm **144** is executed to monitor, analyze, and structure the channel parameters **142** in the data lake **140**. In this regard, the channel optimization controller **126** may be configured to generate the optimized SAS configuration commands **128** based at least in part upon outputs from the machine learning algorithm **144**. In some embodiments, the communication channels **202** may be CBRS channels. In other embodiments, a SAS administrator may monitor activity on one, some, or all the CBRS channels to obtain the channel parameters **142**. The optimized SAS configuration commands **128** may enable the server **102** to dynamically modify some of the channels **202** that are affected by interference (e.g., low quality of service and performance) by automatically moving CBRS channels to the best frequency available in a given area.

(50) The process **300** starts at operation **302**, where the server **102** performs SAS operations in the communication system **100** (e.g., as part of a communication network) in accordance with the existing SAS configuration commands **136**. At operation **304**, the server **102** collects the channel parameters **142** from the one or more communication channels **202**. In some embodiments, the channel parameters **142** are collected from the communication channels **202** over a predefined (e.g., preconfigured or configured) time duration. In other embodiments, the channel parameters **142** are collected from the communication channels **202** continuously or periodically over the predefined time duration. In yet other embodiments, the server **102** may store the one or more channel parameters **142** in the data lake **140** automatically in response to collecting the one or more channel parameters **142** from the communication channels **202** over the predefined time duration. At operation **306**, the server **102** stores the channel parameters **142** in one or more data lakes **140**. At operation **308**, the server **102** monitor the channel parameters **142** based at least in part upon execution of the machine learning algorithm **144**. The machine learning algorithm **144** may organize and analyze the information stored in the data lakes **140**. At operation **310**, the server **102** may manage routing and assignment of resources for the channels **202** following the SAS operations. At operation **312**, the server **102** may generate optimized SAS configuration commands **128** based on the analysis performed by executing the machine learning algorithm **144**. In this regard, the machine learning algorithm **144** may output the one or more artificial intelligence commands **136** to implement the optimized SAS configuration commands **128**.

(51) The process **300** continues at operation **320**, where the server **102** may determine whether the optimized SAS configuration commands **128** are different from the existing SAS configuration commands **136**. In this regard, the server **102** may compare the optimized SAS configuration commands **128** to the existing SAS configuration commands **136**. If the server **102** determines that the optimized SAS configuration commands **128** comprise commands that are not different (e.g., same commands) to those comprised in the plurality of existing SAS configuration commands (i.e., NO), the process **300** returns to operation **302**. In this case, at operation **302**, the server **102** performs new SAS operations in the communication system **100** using the existing SAS

configuration commands **136**. In response, if the server **102** determines that the optimized SAS configuration commands **128** comprise commands that are different to those comprised in the existing SAS configuration commands **136** (i.e., YES), the process **300** proceeds to operation **322**. In this case, the process **300** may conclude at operation **322**, where the server **102** performs new SAS operations in the communication system **100** using the optimized SAS configuration commands **128**.

Scope Of The Disclosure

(52) While several embodiments have been provided in the present disclosure, it should be understood that the disclosed systems and methods might be embodied in many other specific forms without departing from the spirit or scope of the present disclosure. The present examples are to be considered as illustrative and not restrictive, and the intention is not to be limited to the details given herein. For example, the various elements or components may be combined or integrated with another system or certain features may be omitted, or not implemented.

(53) In addition, techniques, systems, subsystems, and methods described and illustrated in the various embodiments as discrete or separate may be combined or integrated with other systems, modules, techniques, or methods without departing from the scope of the present disclosure. Other items shown or discussed as coupled or directly coupled or communicating with each other may be indirectly coupled or communicating through some interface, device, or intermediate component whether electrically, mechanically, or otherwise. Other examples of changes, substitutions, and alterations are ascertainable by one skilled in the art and could be made without departing from the spirit and scope disclosed herein.

(54) To aid the Patent Office, and any readers of any patent issued on this application in interpreting the claims appended hereto, applicants note that they do not intend any of the appended claims to invoke 35 U.S.C. § 112 (f) as it exists on the date of filing hereof unless the words “means for” or “step for” are explicitly used in the particular claim.

Claims

1. A method, comprising: performing a first plurality of spectrum administration service (SAS) operations in accordance with existing SAS configuration commands during a first time duration, wherein: the first plurality of SAS operations is configured to establish one or more communication sessions between a plurality of network components in a core network and a plurality of user equipment; the existing SAS configuration commands are configured to provide control information to perform a first plurality of SAS operations; the first plurality of SAS operations is associated with controlling access between the plurality of user equipment and one or more Citizens Broadband Radio Service (CBRS) channels; and the one or more CBRS channels are communication channels configured to provide connectivity between the plurality of user equipment and the core network; collecting a plurality of channel parameters, the plurality of channel parameters comprising unstructured data associated with the first plurality of SAS operations and the one or more CBRS channels; storing the plurality of channel parameters in a data lake comprising the plurality of channel parameters; transforming, using a machine learning algorithm, the unstructured data of the plurality of channel parameters into structured data in the data lake, the structured data being representative of a plurality of conditions in the one or more CBRS channels during the first time duration; generating, using the machine learning algorithm, a plurality of routing modifications based at least in part upon the plurality of channel parameters and the existing SAS configuration commands, the routing modifications being configured to modify routing of resources in the plurality of CBRS channels to be allocated in a communication network; generating, using the machine learning algorithm, a plurality of optimized SAS configuration commands based at least in part upon the plurality of routing modifications, the existing SAS configuration commands, a transformed version of the unstructured data representative of a

plurality of conditions in the one or more CBRS channels during the first time duration, the optimized SAS configuration commands comprising possible updates to the plurality of existing SAS configuration commands, and the routing modifications; comparing, using the machine learning algorithm, the plurality of optimized SAS configuration commands to the plurality of existing SAS configuration commands; determining, using the machine learning algorithm, that the plurality of optimized SAS configuration commands comprise one or more commands that are different to those comprised in the plurality of existing SAS configuration commands; and in response to determining that the plurality of optimized SAS configuration commands comprise commands that are different to those comprised in the plurality of existing SAS configuration commands, training the machine learning algorithm using input data comprising the structured data representative of the plurality of conditions in the one or more CBRS channels during the first time duration, and the routing modifications; and performing a second plurality of SAS operations associated with the one or more CBRS channel in accordance with the optimized SAS configuration commands during a second time duration, the second time duration being different from the first time duration.

2. The method of claim 1, further comprising: in response to determining that the plurality of optimized SAS configuration commands comprise same commands to those comprised in the plurality of existing SAS configuration commands, performing the second plurality of SAS operations in accordance with the existing SAS configuration commands.

3. The method of claim 1, wherein: the plurality of channel parameters from the plurality of communication channels is collected over a predefined time duration during the first time duration.

4. The method of claim 3, wherein: the plurality of channel parameters is stored in the data lake automatically in response to collecting the plurality of channel parameters over the predefined time duration.

5. The method of claim 1, wherein: the plurality of channel parameters comprises a channel connectivity registry comprising connectivity interruptions and connectivity success rates, dynamic routing information, static routing information, a plurality of channel communication frequency bands.

6. The method of claim 5, wherein: the connectivity interruptions comprise communication interruptions in the one or more CBRS channels over a predefined time duration during the first time duration.

7. The method of claim 5, wherein: the connectivity success rates comprise a percentage of successful communication transactions in the one or more CBRS channels over a predefined time duration.

8. A non-transitory computer readable medium storing instructions that when executed by a processor cause the processor to: perform a first plurality of spectrum administration service (SAS) operations in accordance with existing SAS configuration commands during a first time duration, wherein: the first plurality of SAS operations is configured to establish one or more communication sessions between a plurality of network components in a core network and a plurality of user equipment; the existing SAS configuration commands are configured to provide control information to perform a first plurality of SAS operation; the first plurality of SAS operations is associated with controlling access between the plurality of user equipment and one or more Citizen Broadband Radio Service (CBRS) channels; and the one or more CBRS channels are communication channels configured to provide connectivity between the plurality of user equipment and the core network; collect a plurality of channel parameters, the plurality of channel parameters comprising unstructured data associated with the first plurality of SAS operations and the one or more CBRS channels; store the plurality of channel parameters in a data lake comprising the plurality of channel parameters; transform, using a machine learning algorithm, the unstructured data of the plurality of channel parameters into structured data in the data lake, the structured data being representative of a plurality of conditions in the one or more CBRS channels

during the first time duration; generate, using the machine learning algorithm, a plurality of routing modifications based at least in part upon the plurality of channel parameters and the existing SAS configuration commands, the routing modifications being configured to modify routing of resources in the plurality of CBRS channels to be allocated in a communication network; generate, using the machine learning algorithm, a plurality of optimized SAS configuration commands based at least in part upon the plurality of routing modifications, the existing SAS configuration commands, a transformed version of the unstructured data representative of a plurality of conditions in the one or more CBRS channels during the first time duration, the optimized SAS configuration commands comprising possible updates to the plurality of existing SAS configuration commands, and the routing modifications; compare, using the machine learning algorithm, the plurality of optimized SAS configuration commands to the plurality of existing SAS configuration commands; determine, using the machine learning algorithm, the plurality of optimized SAS configuration commands to the plurality of existing SAS configuration commands; and in response to determining that the plurality of optimized SAS configuration commands comprise commands that are different to those comprised in the plurality of existing SAS configuration commands, training the machine learning algorithm using input data comprising the structured data representative of the plurality of conditions in the one or more CBRS channels during the first time duration, and the routing modifications; and perform a second plurality of SAS operations associated with the one or more CBRS channel in accordance with the optimized SAS configuration commands during a second time duration, the second time duration being different from the first time duration.

9. The non-transitory computer readable medium of claim 8, wherein the processor is further caused to: in response to determining that the plurality of optimized SAS configuration commands comprise same commands to those comprised in the plurality of existing SAS configuration commands, performing the second plurality of SAS operations in accordance with the existing SAS configuration commands.

10. The non-transitory computer readable medium of claim 8, wherein: the plurality of channel parameters from the plurality of communication channels is collected over a predefined time duration during the first time duration.

11. The non-transitory computer readable medium of claim 10, wherein: the plurality of channel parameters is stored in the data lake automatically in response to collecting the plurality of channel parameters over the predefined time duration.

12. The non-transitory computer readable medium of claim 8, wherein: the plurality of channel parameters comprises a channel connectivity registry comprising connectivity interruptions and connectivity success rates, dynamic routing information, static routing information, a plurality of channel communication frequency bands.

13. The non-transitory computer readable medium of claim 12, wherein: the connectivity interruptions comprise communication interruptions in the one or more CBRS channels over a predefined time duration during the first time duration; and the connectivity success rates comprise a percentage of successful communication transactions in the one or more CBRS channels over the predefined time duration.

14. An apparatus, comprising: a memory, comprising: a data lake comprising one or more channel parameters that are stored as structured data, semi-structured data, or unstructured data; a machine learning algorithm configured to analyze and structure the one or more channel parameters in the data lake; and a plurality of existing spectrum administration service (SAS) configuration commands configured to establish one or more communication sessions between a plurality of network components in a core network and a plurality of user equipment, the existing SAS configuration commands being configured to provide control information to perform a first plurality of SAS operation; and a processor communicatively coupled to the memory and configured to: perform the first plurality of SAS operations in accordance with the existing SAS

configuration commands during a first time duration, wherein: the first plurality of SAS operations is associated with controlling access between the plurality of user equipment and one or more Citizens Broadband Radio Service (CBRS) channels; and the one or more CBRS channels are communication channels configured to provide connectivity between the plurality of user equipment and the core network; collect a plurality of channel parameters, the plurality of channel parameters comprising unstructured data associated with the first plurality of SAS operations and the one or more CBRS channels; store the plurality of channel parameters in the data lake; transform, using the machine learning algorithm, the unstructured data of the plurality of channel parameters into structured data in the data lake, the structured data being representative of a plurality of conditions in the one or more CBRS channels during the first time duration; generate, using the machine learning algorithm, a plurality of routing modifications based at least in part upon the plurality of channel parameters and the existing SAS configuration commands, the routing modifications being configured to modify routing of resources in the plurality of CBRS channels to be allocated in a communication network; generate, using the machine learning algorithm, a plurality of optimized SAS configuration commands based at least in part upon the plurality of routing modifications, the existing SAS configuration commands, a transformed version of the unstructured data representative of a plurality of conditions in the one or more CBRS channels during the first time duration, the optimized SAS configuration commands comprising possible updates to the plurality of existing SAS configuration commands, and the routing modifications; compare, using the machine learning algorithm, the plurality of optimized SAS configuration commands to the plurality of existing SAS configuration commands; determine, using the machine learning algorithm, that the plurality of optimized SAS configuration commands comprise one or more commands that are different to those comprised in the plurality of existing SAS configuration commands; and in response to determining that the plurality of optimized SAS configuration commands comprise commands that are different to those comprised in the plurality of existing SAS configuration commands, train the machine learning algorithm using input data comprising the structured data representative of the plurality of conditions in the one or more CBRS channels during the first time duration, and the routing modifications; and perform a second plurality of SAS operations associated with the one or more CBRS channels in accordance with the optimized SAS configuration commands during a second time duration, the second time duration being different from the first time duration.

15. The apparatus of claim 14, wherein the processor is further configured to: in response to determining that the plurality of optimized SAS configuration commands comprise same commands to those comprised in the plurality of existing SAS configuration commands, perform the second plurality of SAS operations in accordance with the existing SAS configuration commands.

16. The apparatus of claim 14, wherein: the plurality of channel parameters from the plurality of communication channels is collected over a predefined time duration during the first time duration.

17. The apparatus of claim 16, wherein: the processor is further configured to store the one or more channel parameters in the data lake automatically in response to collecting the one or more channel parameters from the plurality of communication channels over the predefined time duration.

18. The apparatus of claim 14, wherein: the one or more channel parameters comprise a channel connectivity registry comprising connectivity interruptions and connectivity success rates, dynamic routing information, static routing information, a plurality of channel communication frequency bands.

19. The apparatus of claim 18, wherein: the connectivity interruptions comprise communication interruptions in the one or more CBRS channels over a predefined time duration during the first time duration.

20. The apparatus of claim 18, wherein: the connectivity success rates comprise a percentage of

successful communication transactions in the one or more CBRS channels over a predefined time duration.
