

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413517
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Jaiswal; Rajesh Kumar et al.

Host authentication using a non-addressable domain controller

Abstract

A data management system (DMS) may support authentication of a host using a non-addressable domain controller within a network. The DMS may obtain a list of domain controllers within the network and create an account at a domain controller on the list via a virtual machine instantiated within the network and used to create a tunnel between the DMS and the virtual machine. The DMS may receive, via a port, a packet from a host within the network and route the packet, using a demultiplexer configured to monitor the port, to a storage entity. The storage entity may transmit, via the port to the domain controller, a request to authenticate the host, the request bypassing the demultiplexer that is configured not to monitor the port when the storage entity operates in a client mode. The DMS may receive an indication of whether the host is authenticated from the domain controller.

Inventors:	Jaiswal; Rajesh Kumar (Bangalore, IN), Luo; Jiangbin (Cupertino, CA)
Applicant:	Rubrik, Inc. (Palo Alto, CA)
Family ID:	92635012
Assignee:	Rubrik, Inc. (Palo Alto, CA)
Appl. No.:	18/119237
Filed:	March 08, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240305566 A1	Sep. 12, 2024

Publication Classification

Int. Cl.: H04L45/76 (20220101); G06F9/455 (20180101); H04L9/40 (20220101); H04L12/46 (20060101); H04L43/50 (20220101); H04L45/745 (20220101); H04L61/5007

U.S. Cl.:

CPC **H04L45/76** (20220501); **G06F9/45558** (20130101); **H04L12/4633** (20130101);
H04L43/50 (20130101); **H04L45/745** (20130101); **H04L61/5007** (20220501);
H04L63/029 (20130101); **H04L63/08** (20130101); G06F2009/45595 (20130101)

Field of Classification Search

CPC: H04L (45/76); H04L (61/5007); H04L (12/4633); H04L (43/50); H04L (45/745); H04L
(63/029); H04L (63/018); G06F (9/45558)

USPC: 370/250

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2015/0089331	12/2014	Skerry	714/799	G06F 11/2289
2021/0028987	12/2020	Krivenok	N/A	H04L 67/1097
2023/0308475	12/2022	Pane	N/A	H04L 63/0435
2023/0336375	12/2022	Sparkman, III	N/A	H04L 63/166

Primary Examiner: Mejia; Anthony

Attorney, Agent or Firm: Holland & Hart LLP

Background/Summary**FIELD OF TECHNOLOGY**

(1) The present disclosure relates generally to data management, including techniques for host authentication using a non-addressable domain controller.

BACKGROUND

(2) A data management system (DMS) may be employed to manage data associated with one or more computing systems. The data may be generated, stored, or otherwise used by the one or more computing systems, examples of which may include servers, databases, virtual machines, cloud computing systems, file systems (e.g., network-attached storage (NAS) systems), or other data storage or processing systems. The DMS may provide data backup, data recovery, data classification, or other types of data management services for data of the one or more computing systems. Improved data management may offer improved performance with respect to reliability, speed, efficiency, scalability, security, or ease-of-use, among other possible aspects of performance.

Description**BRIEF DESCRIPTION OF THE DRAWINGS**

(1) FIGS. 1, 2, and 3 illustrate examples of computing environments that support host authentication using a non-addressable domain controller in accordance with aspects of the present

disclosure.

(2) FIG. 4 illustrates an example of a process flow that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure.

(3) FIG. 5 illustrates a block diagram of an apparatus that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure.

(4) FIG. 6 illustrates a block diagram of a storage manager that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure.

(5) FIG. 7 illustrates a diagram of a system including a device that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure.

(6) FIGS. 8 through 10 illustrate flowcharts showing methods that support host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure.

DETAILED DESCRIPTION

(7) A data management system (DMS) may provide data management services (e.g., backup and recovery services) for data of a computing system. For example, the DMS may facilitate the capture (e.g., generation or ingestion) and storage of snapshots of the computing system (e.g., a computing object of the computing system such as a virtual machine, a database, a filesystem, a virtual disk, a virtual desktop, or other type of computing system or storage system), and the snapshots support later recovery (e.g., restoration) of the computing object.

(8) The DMS may provide data management services to non-addressable (e.g., not directly addressable) computing entities. For example, some computing entities, such as hosts (among others), may be within a private network such that the DMS is unable to directly address the host. For instance, communications (e.g., packets) between the DMS and a computing entity may include internet protocol (IP) addresses to correctly route the communications. However, a non-addressable host within a private network may be associated with an IP address that is not directly reachable by the DMS. That is, the DMS may be unable to reach the host using the IP address (e.g., direct network routes between the DMS and the host may be non-existent or blocked). In cases where the DMS is unable to directly access a non-addressable host of a network (e.g., a private network), a virtual machine may be instantiated (e.g., installed) in the network to support DMS operations. For example, the virtual machine, which may be referred to as an envoy virtual machine, may create a tunnel (e.g., transport layer security TLS tunnel) between itself and the DMS to support communications between the host within the network and the DMS.

(9) When a host attempts to access (e.g., start a connection with, send packets to) a storage entity (e.g., a server) of the DMS that is used to back up the host, the DMS may attempt to authenticate the host, which may include the DMS sending (e.g., issuing, transmitting) an authentication request to a domain controller within the network that includes the host. The domain controller may, in response to receiving an authentication request from the DMS, verify whether the DMS is authorized to issue the authentication request. Whether the DMS is authorized may depend on whether an account (e.g., a machine account) for the DMS was previously created at the domain controller. However, if a host is non-addressable (e.g., reside within a private network) and an envoy virtual machine and associated tunnel are used for communications between the host and the DMS, various issues may arise with respect to the DMS requesting the domain controller to authenticate the host.

(10) For example, a domain name system (DNS) server may include a list of available domain controllers associated with the host (e.g., associated with a domain to which the host belongs) that the DMS may access to request authentication of the host. However, the DNS server and the domain controllers may themselves be non-addressable by the DMS (e.g., may reside within the private network). As such, the DMS may be unable to obtain the list of available domain controllers from the DNS and be unable to create an account at a domain controller to support later authentication requests. Additionally, even if the DMS were able to create a machine account at the domain controller for the host, the DMS may still be unable to successfully send authentication

requests to the domain controller via the tunnel. For example, communications via the tunnel may be routed through a demultiplexing component (e.g., an “Nginx” server) within the DMS such that the communications may be routed to the correct entities. For inbound traffic to the DMS, the demultiplexing component may route packets from respective hosts to corresponding storage entities of the DMS acting as servers by mapping host internet protocol (IP) addresses associated with the packets to the corresponding storage entities. However, outbound traffic from different storage entities acting as clients to establish a connection with an external entity may all appear as generally coming from the DMS (rather than a specific storage entity). As such, the demultiplexing component may be unable to determine with which corresponding storage entity a connection is to be established and hence the connection attempt may fail (e.g., be dropped by the demultiplexing component).

(11) To support creation of an account at a non-addressable domain controller, the DMS may utilize the envoy virtual machine to obtain the list of available domain controllers. For example, because the virtual machine is instantiated within (e.g., resides within, is located within) the network, the virtual machine may obtain the list of available domain controllers, such as from the non-addressable DNS server. The virtual machine may transmit the list of available domain controllers to the DMS via the tunnel, and the DMS may use the list to access one of the domain controllers.

(12) To support the transmission of outgoing traffic to the domain controller, such as to create the account at the domain controller or request authentication of a host, the DMS may configure the demultiplexing component to differentiate between incoming and outgoing traffic via the tunnel for the purposes of routing the traffic. For example, traffic communicated between the DMS and a given host within the network may be communicated according to a communication protocol, such as a server message block (SMB) protocol, among others. Such traffic may be communicated via a port of the DMS allocated for the communication of the traffic (e.g., a port 445 corresponding to the SMB protocol, which may have a port number 445). The DMS may configure the demultiplexing component such that, if a storage entity operates in a server mode to receive packets (e.g., connection requests) via the port, the demultiplexing component may monitor (e.g., listen to) the port and route the packets to the storage entity. The DMS may also configure the demultiplexing component such that, if the storage entity operates in a client mode to transmit packets (e.g., connection requests such as to support account creation and authentication requests) via the port, the demultiplexing component may not monitor (e.g., not listen, refrain from monitoring, refrain from intercepting, be disabled from monitoring) the port, and as such, the packets may bypass the demultiplexing component. As a result, outgoing traffic from the storage entity via the port will not be intercepted and dropped by the demultiplexing component. Instead, a connection may be established between the storage entity and the domain controller such that traffic is routed between them without interception by the demultiplexing component. The DMS may create an account at the domain controller, request authentication of a host within the network, or both, via the connection established.

(13) FIG. 1 illustrates an example of a computing environment **100** that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure. The computing environment **100** may include a computing system **105**, a DMS **110**, and one or more computing devices **115**, which may be in communication with one another via a network **120**. The computing system **105** may generate, store, process, modify, or otherwise use associated data, and the DMS **110** may provide one or more data management services for the computing system **105**. For example, the DMS **110** may provide a data backup service, a data recovery service, a data classification service, a data transfer or replication service, one or more other data management services, or any combination thereof for data associated with the computing system **105**.

(14) The network **120** may allow the one or more computing devices **115**, the computing system **105**, and the DMS **110** to communicate (e.g., exchange information) with one another. The network

120 may include aspects of one or more wired networks (e.g., the Internet), one or more wireless networks (e.g., cellular networks), or any combination thereof. The network **120** may include aspects of one or more public networks or private networks, as well as secured or unsecured networks, or any combination thereof. The network **120** also may include any quantity of communications links and any quantity of hubs, bridges, routers, switches, ports or other physical or logical network components.

(15) A computing device **115** may be used to input information to or receive information from the computing system **105**, the DMS **110**, or both. For example, a user of the computing device **115** may provide user inputs via the computing device **115**, which may result in commands, data, or any combination thereof being communicated via the network **120** to the computing system **105**, the DMS **110**, or both. Additionally or alternatively, a computing device **115** may output (e.g., display) data or other information received from the computing system **105**, the DMS **110**, or both. A user of a computing device **115** may, for example, use the computing device **115** to interact with one or more user interfaces (e.g., graphical user interfaces (GUIs)) to operate or otherwise interact with the computing system **105**, the DMS **110**, or both. Though one computing device **115** is shown in FIG. 1, it is to be understood that the computing environment **100** may include any quantity of computing devices **115**.

(16) A computing device **115** may be a stationary device (e.g., a desktop computer or access point) or a mobile device (e.g., a laptop computer, tablet computer, or cellular phone). In some examples, a computing device **115** may be a commercial computing device, such as a server or collection of servers. And in some examples, a computing device **115** may be a virtual device (e.g., a virtual machine). Though shown as a separate device in the example computing environment of FIG. 1, it is to be understood that in some cases a computing device **115** may be included in (e.g., may be a component of) the computing system **105** or the DMS **110**.

(17) The computing system **105** may include one or more servers **125** and may provide (e.g., to the one or more computing devices **115**) local or remote access to applications, databases, or files stored within the computing system **105**. The computing system **105** may further include one or more data storage devices **130**. Though one server **125** and one data storage device **130** are shown in FIG. 1, it is to be understood that the computing system **105** may include any quantity of servers **125** and any quantity of data storage devices **130**, which may be in communication with one another and collectively perform one or more functions ascribed herein to the server **125** and data storage device **130**.

(18) A data storage device **130** may include one or more hardware storage devices operable to store data, such as one or more hard disk drives (HDDs), magnetic tape drives, solid-state drives (SSDs), storage area network (SAN) storage devices, or network-attached storage (NAS) devices. In some cases, a data storage device **130** may comprise a tiered data storage infrastructure (or a portion of a tiered data storage infrastructure). A tiered data storage infrastructure may allow for the movement of data across different tiers of the data storage infrastructure between higher-cost, higher-performance storage devices (e.g., SSDs and HDDs) and relatively lower-cost, lower-performance storage devices (e.g., magnetic tape drives). In some examples, a data storage device **130** may be a database (e.g., a relational database), and a server **125** may host (e.g., provide a database management system for) the database.

(19) A server **125** may allow a client (e.g., a computing device **115**) to download information or files (e.g., executable, text, application, audio, image, or video files) from the computing system **105**, to upload such information or files to the computing system **105**, or to perform a search query related to particular information stored by the computing system **105**. In some examples, a server **125** may act as an application server or a file server. In general, a server **125** may refer to one or more hardware devices that act as the host in a client-server relationship or a software process that shares a resource with or performs work for one or more clients.

(20) A server **125** may include a network interface **140**, processor **145**, memory **150**, disk **155**, and

computing system manager **160**. The network interface **140** may enable the server **125** to connect to and exchange information via the network **120** (e.g., using one or more network protocols). The network interface **140** may include one or more wireless network interfaces, one or more wired network interfaces, or any combination thereof. The processor **145** may execute computer-readable instructions stored in the memory **150** in order to cause the server **125** to perform functions ascribed herein to the server **125**. The processor **145** may include one or more processing units, such as one or more central processing units (CPUs), one or more graphics processing units (GPUs), or any combination thereof. The memory **150** may comprise one or more types of memory (e.g., random access memory (RAM), static random access memory (SRAM), dynamic random access memory (DRAM), read-only memory ((ROM), electrically erasable programmable read-only memory (EEPROM), Flash, etc.). Disk **155** may include one or more HDDs, one or more SSDs, or any combination thereof. Memory **150** and disk **155** may comprise hardware storage devices. The computing system manager **160** may manage the computing system **105** or aspects thereof (e.g., based on instructions stored in the memory **150** and executed by the processor **145**) to perform functions ascribed herein to the computing system **105**. In some examples, the network interface **140**, processor **145**, memory **150**, and disk **155** may be included in a hardware layer of a server **125**, and the computing system manager **160** may be included in a software layer of the server **125**. In some cases, the computing system manager **160** may be distributed across (e.g., implemented by) multiple servers **125** within the computing system **105**.

(21) In some examples, the computing system **105** or aspects thereof may be implemented within one or more cloud computing environments, which may alternatively be referred to as cloud environments. Cloud computing may refer to Internet-based computing, wherein shared resources, software, and/or information may be provided to one or more computing devices on-demand via the Internet. A cloud environment may be provided by a cloud platform, where the cloud platform may include physical hardware components (e.g., servers) and software components (e.g., operating system) that implement the cloud environment. A cloud environment may implement the computing system **105** or aspects thereof through Software-as-a-Service (SaaS) or Infrastructure-as-a-Service (IaaS) services provided by the cloud environment. SaaS may refer to a software distribution model in which applications are hosted by a service provider and made available to one or more client devices over a network (e.g., to one or more computing devices **115** over the network **120**). IaaS may refer to a service in which physical computing resources are used to instantiate one or more virtual machines, the resources of which are made available to one or more client devices over a network (e.g., to one or more computing devices **115** over the network **120**).

(22) In some examples, the computing system **105** or aspects thereof may implement or be implemented by one or more virtual machines. The one or more virtual machines may run various applications, such as a database server, an application server, or a web server. For example, a server **125** may be used to host (e.g., create, manage) one or more virtual machines, and the computing system manager **160** may manage a virtualized infrastructure within the computing system **105** and perform management operations associated with the virtualized infrastructure. The computing system manager **160** may manage the provisioning of virtual machines running within the virtualized infrastructure and provide an interface to a computing device **115** interacting with the virtualized infrastructure. For example, the computing system manager **160** may be or include a hypervisor and may perform various virtual machine-related tasks, such as cloning virtual machines, creating new virtual machines, monitoring the state of virtual machines, moving virtual machines between physical hosts for load balancing purposes, and facilitating backups of virtual machines. In some examples, the virtual machines, the hypervisor, or both, may virtualize and make available resources of the disk **155**, the memory, the processor **145**, the network interface **140**, the data storage device **130**, or any combination thereof in support of running the various applications. Storage resources (e.g., the disk **155**, the memory **150**, or the data storage device **130**) that are virtualized may be accessed by applications as a virtual disk.

(23) The DMS **110** may provide one or more data management services for data associated with the computing system **105** and may include DMS manager **190** and any quantity of storage nodes **185**. The DMS manager **190** may manage operation of the DMS **110**, including the storage nodes **185**. Though illustrated as a separate entity within the DMS **110**, the DMS manager **190** may in some cases be implemented (e.g., as a software application) by one or more of the storage nodes **185**. In some examples, the storage nodes **185** may be included in a hardware layer of the DMS **110**, and the DMS manager **190** may be included in a software layer of the DMS **110**. In the example illustrated in FIG. **1**, the DMS **110** is separate from the computing system **105** but in communication with the computing system **105** via the network **120**. It is to be understood, however, that in some examples at least some aspects of the DMS **110** may be located within computing system **105**. For example, one or more servers **125**, one or more data storage devices **130**, and at least some aspects of the DMS **110** may be implemented within the same cloud environment or within the same data center.

(24) Storage nodes **185** of the DMS **110** may include respective network interfaces **165**, processors **170**, memories **175**, and disks **180**. The network interfaces **165** may enable the storage nodes **185** to connect to one another, to the network **120**, or both. A network interface **165** may include one or more wireless network interfaces, one or more wired network interfaces, or any combination thereof. The processor **170** of a storage node **185** may execute computer-readable instructions stored in the memory **175** of the storage node **185** in order to cause the storage node **185** to perform processes described herein as performed by the storage node **185**. A processor **170** may include one or more processing units, such as one or more CPUs, one or more GPUs, or any combination thereof. The memory **150** may comprise one or more types of memory (e.g., RAM, SRAM, DRAM, ROM, EEPROM, Flash, etc.). A disk **180** may include one or more HDDs, one or more SDDs, or any combination thereof. Memories **175** and disks **180** may comprise hardware storage devices. Collectively, the storage nodes **185** may in some cases be referred to as a storage cluster or as a cluster of storage nodes **185**.

(25) The DMS **110** may provide a backup and recovery service for the computing system **105**. For example, the DMS **110** may manage the extraction and storage of snapshots **135** associated with different point-in-time versions of one or more target computing objects within the computing system **105**. A snapshot **135** of a computing object (e.g., a virtual machine, a database, a filesystem, a virtual disk, a virtual desktop, or other type of computing system or storage system) may be a file (or set of files) that represents a state of the computing object (e.g., the data thereof) as of a particular point in time. A snapshot **135** may also be used to restore (e.g., recover) the corresponding computing object as of the particular point in time corresponding to the snapshot **135**. A computing object of which a snapshot **135** may be generated may be referred to as snappable. Snapshots **135** may be generated at different times (e.g., periodically or on some other scheduled or configured basis) in order to represent the state of the computing system **105** or aspects thereof as of those different times. In some examples, a snapshot **135** may include metadata that defines a state of the computing object as of a particular point in time. For example, a snapshot **135** may include metadata associated with (e.g., that defines a state of) some or all data blocks included in (e.g., stored by or otherwise included in) the computing object. Snapshots **135** (e.g., collectively) may capture changes in the data blocks over time. Snapshots **135** generated for the target computing objects within the computing system **105** may be stored in one or more storage locations (e.g., the disk **155**, memory **150**, the data storage device **130**) of the computing system **105**, in the alternative or in addition to being stored within the DMS **110**, as described below:

(26) To obtain a snapshot **135** of a target computing object associated with the computing system **105** (e.g., of the entirety of the computing system **105** or some portion thereof, such as one or more databases, virtual machines, or filesystems within the computing system **105**), the DMS manager **190** may transmit a snapshot request to the computing system manager **160**. In response to the snapshot request, the computing system manager **160** may set the target computing object into a

frozen state (e.g., a read-only state). Setting the target computing object into a frozen state may allow a point-in-time snapshot **135** of the target computing object to be stored or transferred.

(27) In some examples, the computing system **105** may generate the snapshot **135** based on the frozen state of the computing object. For example, the computing system **105** may execute an agent of the DMS **110** (e.g., the agent may be software installed at and executed by one or more servers **125**), and the agent may cause the computing system **105** to generate the snapshot **135** and transfer the snapshot to the DMS **110** in response to the request from the DMS **110**. In some examples, the computing system manager **160** may cause the computing system **105** to transfer, to the DMS **110**, data that represents the frozen state of the target computing object, and the DMS **110** may generate a snapshot **135** of the target computing object based on the corresponding data received from the computing system **105**.

(28) Once the DMS **110** receives, generates, or otherwise obtains a snapshot **135**, the DMS **110** may store the snapshot **135** at one or more of the storage nodes **185**. The DMS **110** may store a snapshot **135** at multiple storage nodes **185**, for example, for improved reliability. Additionally or alternatively, snapshots **135** may be stored in some other location connected with the network **120**. For example, the DMS **110** may store more recent snapshots **135** at the storage nodes **185**, and the DMS **110** may transfer less recent snapshots **135** via the network **120** to a cloud environment (which may include or be separate from the computing system **105**) for storage at the cloud environment, a magnetic tape storage device, or another storage system separate from the DMS **110**.

(29) Updates made to a target computing object that has been set into a frozen state may be written by the computing system **105** to a separate file (e.g., an update file) or other entity within the computing system **105** while the target computing object is in the frozen state. After the snapshot **135** (or associated data) of the target computing object has been transferred to the DMS **110**, the computing system manager **160** may release the target computing object from the frozen state, and any corresponding updates written to the separate file or other entity may be merged into the target computing object.

(30) In response to a restore command (e.g., from a computing device **115** or the computing system **105**), the DMS **110** may restore a target version (e.g., corresponding to a particular point in time) of a computing object based on a corresponding snapshot **135** of the computing object. In some examples, the corresponding snapshot **135** may be used to restore the target version based on data of the computing object as stored at the computing system **105** (e.g., based on information included in the corresponding snapshot **135** and other information stored at the computing system **105**, the computing object may be restored to its state as of the particular point in time). Additionally or alternatively, the corresponding snapshot **135** may be used to restore the data of the target version based on data of the computing object as included in one or more backup copies of the computing object (e.g., file-level backup copies or image-level backup copies). Such backup copies of the computing object may be generated in conjunction with or according to a separate schedule than the snapshots **135**. For example, the target version of the computing object may be restored based on the information in a snapshot **135** and based on information included in a backup copy of the target object generated prior to the time corresponding to the target version. Backup copies of the computing object may be stored at the DMS **110** (e.g., in the storage nodes **185**) or in some other location connected with the network **120** (e.g., in a cloud environment, which in some cases may be separate from the computing system **105**).

(31) In some examples, the DMS **110** may restore the target version of the computing object and transfer the data of the restored computing object to the computing system **105**. And in some examples, the DMS **110** may transfer one or more snapshots **135** to the computing system **105**, and restoration of the target version of the computing object may occur at the computing system **105** (e.g., as managed by an agent of the DMS **110**, where the agent may be installed and operate at the computing system **105**).

(32) In response to a mount command (e.g., from a computing device **115** or the computing system **105**), the DMS **110** may instantiate data associated with a point-in-time version of a computing object based on a snapshot **135** corresponding to the computing object (e.g., along with data included in a backup copy of the computing object) and the point-in-time. The DMS **110** may then allow the computing system **105** to read or modify the instantiated data (e.g., without transferring the instantiated data to the computing system). In some examples, the DMS **110** may instantiate (e.g., virtually mount) some or all of the data associated with the point-in-time version of the computing object for access by the computing system **105**, the DMS **110**, or the computing device **115**.

(33) In some examples, the DMS **110** may store different types of snapshots, including for the same computing object. For example, the DMS **110** may store both base snapshots **135** and incremental snapshots **135**. A base snapshot **135** may represent the entirety of the state of the corresponding computing object as of a point in time corresponding to the base snapshot **135**. An incremental snapshot **135** may represent the changes to the state—which may be referred to as the delta-of the corresponding computing object that have occurred between an earlier or later point in time corresponding to another snapshot **135** (e.g., another base snapshot **135** or incremental snapshot **135**) of the computing object and the incremental snapshot **135**. In some cases, some incremental snapshots **135** may be forward-incremental snapshots **135** and other incremental snapshots **135** may be reverse-incremental snapshots **135**. To generate a full snapshot **135** of a computing object using a forward-incremental snapshot **135**, the information of the forward-incremental snapshot **135** may be combined with (e.g., applied to) the information of an earlier base snapshot **135** of the computing object along with the information of any intervening forward-incremental snapshots **135**, where the earlier base snapshot **135** may include a base snapshot **135** and one or more reverse-incremental or forward-incremental snapshots **135**. To generate a full snapshot **135** of a computing object using a reverse-incremental snapshot **135**, the information of the reverse-incremental snapshot **135** may be combined with (e.g., applied to) the information of a later base snapshot **135** of the computing object along with the information of any intervening reverse-incremental snapshots **135**.

(34) In some examples, the DMS **110** may provide a data classification service, a malware detection service, a data transfer or replication service, backup verification service, or any combination thereof, among other possible data management services for data associated with the computing system **105**. For example, the DMS **110** may analyze data included in one or more computing objects of the computing system **105**, metadata for one or more computing objects of the computing system **105**, or any combination thereof, and based on such analysis, the DMS **110** may identify locations within the computing system **105** that include data of one or more target data types (e.g., sensitive data, such as data subject to privacy regulations or otherwise of particular interest) and output related information (e.g., for display to a user via a computing device **115**). Additionally or alternatively, the DMS **110** may detect whether aspects of the computing system **105** have been impacted by malware (e.g., ransomware). Additionally or alternatively, the DMS **110** may relocate data or create copies of data based on using one or more snapshots **135** to restore the associated computing object within its original location or at a new location (e.g., a new location within a different computing system **105**). Additionally or alternatively, the DMS **110** may analyze backup data to ensure that the underlying data (e.g., user data or metadata) has not been corrupted. The DMS **110** may perform such data classification, malware detection, data transfer or replication, or backup verification, for example, based on data included in snapshots **135** or backup copies of the computing system **105**, rather than live contents of the computing system **105**, which may beneficially avoid adversely affecting (e.g., infecting, loading, etc.) the computing system **105**.

(35) In some examples, the computing system **105** may be included in a network that is separate from a network within which the DMS **110** is located. In some cases, the computing system **105** (e.g., components of the computing system **105**) may be associated with an IP address that is not

directly reachable by the DMS **110**, and thus the DMS **110** may be unable to reach the computing system **105** using the IP address. Here, an envoy virtual machine associated with (e.g., that is considered a part of) the DMS **110** may be instantiated within the network that includes the computing system **105**, and the envoy virtual machine may create a tunnel between the networks (e.g., between the envoy virtual machine and the DMS), such that packets may be communicated between the DMS **110** and computing system **105** via the tunnel.

(36) In accordance with examples described herein, the DMS **110** may support authentication of the computing system **105** in response to the computing system **105** requesting to establish a connection with the DMS. For example, the network that includes the computing system **105** may include one or more non-addressable domain controllers (e.g., domain controllers having IP addresses that are not directly reachable by and/or unknown to the DMS **110**). Because the envoy virtual machine is instantiated within (e.g., resides within, is located within) the network, the virtual machine may obtain a list of the one or more non-addressable domain controllers, such as from a non-addressable DNS server, and transmit the list to the DMS **110** via the tunnel. The DMS **110** may use the list to create an account at a domain controller on the list such that the DMS **110** may subsequently send authentication requests to the domain controller. To support creation of the account and transmission of the authentication requests, the DMS **110** may configure a demultiplexer of the DMS **110** to not monitor (e.g., exclude monitoring of) a port via which a packet (e.g., a connection request) from the DMS **110** to the domain controller is communicated. As such, the packet may not be intercepted by the demultiplexer, which may lead to dropping of the packet, and instead a connection between the DMS **110** and the domain controller may be established to support account creation and authentication of non-addressable hosts.

(37) FIG. 2 illustrates an example of a computing environment **200** that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure. The computing environment **200** may implement or be implemented by aspects of the computing environment **100** described with reference to FIG. 1. For example, the computing environment **200** may include a DMS **210**, which may be an example of a DMS **110** described herein, including with reference to FIG. 1. The computing environment **200** may support the creation of an account (e.g., a machine account) for the DMS **210** at a non-addressable domain controller **240** such that authentication of a non-addressable host **235** may be supported (e.g., as described with reference to FIGS. 3 and 4).

(38) The computing environment **200** may include a network **205**. The network **205** may include various computing entities that are backed up by the DMS **210**. For example, the network **205** may include one or more hosts **235** (although a single host **235** is depicted in the example of FIG. 2), which may be examples of one or more components of a computing system **105**, such as including aspects of a server **125**, a data storage device **130**, or a combination thereof. In some examples, a host **235** may be a computing entity, such as a hypervisor, that provides underlying hardware resources, such as processing power, memory, network, and storage during virtualization. In some examples, the host **235** may be a bare-metal hypervisor installed directly on the hardware of a physical machine, between the hardware and the operating system. In some examples, the host **235** may be an example of a VMWare host, such as an ESX host or an ESXi host.

(39) The DMS **210** may include various storage entities that are used to back up respective hosts **235**. For example, the DMS **210** may include a server **220** that is used to back up the host **235**. For instance, packets transmitted by the host **235** may be routed to the server **220** that backs up the host **235**. The DMS **210** may also include a client **225** that supports the DMS **210** establishing a connection with an entity external to the DMS **210**, such as entities within the network **205** (e.g., the host **235**, a domain controller **240**). In some examples, the server **220** and the client **225** may be included in a same storage entity. In some examples, the server **220** and the client **225** may be the same storage entity that supports operating as the server **220** and the client **225**. For example, communications with the server **220**) may correspond to the storage entity operating in a server

mode, and communications with the client **225** may correspond to the storage entity operating in a client mode. In some examples, the server **220** and the client **225** may be respective examples of or included in a storage node **185** described with reference to FIG. **1**. In some examples, the DMS **210** may include a node **215**, which may be an example of a storage node **185**.

(40) The DMS **210** may support protecting and managing a variety of workloads that rely on various communication protocols, such as an SMB protocol, for backup and/or restore functionality. To secure (e.g., protect) access to the DMS **210** (such as by the host **235**), the DMS **210** may support authentication of clients (e.g., an entity attempting to establish a connection with another entity, such as the host **235**) trying to access the DMS **210** (e.g., the server **220**, which may be referred to as an SMB share). In some examples, the DMS **210** may support active directory-based authentication of hosts **235**, which may include accessing a domain controller **240**. For example, the network **205** may include the domain controller **240**, which may be an example of a server responsible for managing network and identity security requests, such as by authenticating whether a given user (e.g., host **235**) is authorized to access the resources in a given domain **230**. The domain controller **240** may authenticate and validate users on the network **205**, including group policies, user credentials, and computer names to determine and validate user access. The server **220** and the client **225** may be associated with a domain **230** (e.g., identified by a domain name). Accordingly, by accessing the domain controller **240**, the DMS **210** may determine whether the host **235** is authorized (e.g., permitted) to access the domain **230** (e.g., the server **220**).

(41) However, the domain controller **240** may be non-addressable from the perspective of the DMS **210**. That is, the domain controller **240** may have an IP address (e.g., a private IP address) that is not directly reachable by (e.g., and unknown to) the DMS **210**, which may result in various obstacles preventing the DMS **210** from accessing the domain controller **240** to authenticate the host **235**. For example, prior to requesting the domain controller **240** to authenticate the host **235**, the DMS **210** (e.g., the node **215**, the client **225**) may create an account **285** for the DMS **210** (e.g., the node **215**, the client **225**) at the domain controller **240**, which may be an example of a machine account. Creation of the account **285** may indicate that the DMS **210** is authorized to access the domain controller **240**, such as to request authentication of the host **235**. However, because the domain controller **240** may be non-addressable and the IP address of the domain controller **240** may be unknown to the DMS **210**, the DMS **210** may be unable to initiate the establishment of a connection with the domain controller **240** to create the account **285** at the domain controller **240**.

(42) For example, in some cases, the DMS **210** may obtain the IP address of the domain controller **240** by accessing a DNS server **247**, which may include a database of the IP addresses of the available domain controllers **240** within the network **205**. However, the DNS server **247** may also be included in the network **205** and may be non-addressable from the perspective of the DMS **210**. Accordingly, the DMS **210** may be unable to access the DNS server **247** to obtain the IP address of the domain controller **240** and may thus be unable to access the domain controller **240**. Further, in some cases, even if the IP address were obtained from the DNS server **247**, the IP address may be a private IP address of the DMS **210**, which may not be directly reachable by the DMS **210**.

(43) To support communications between the DMS **210** and entities within the network **205**, a virtual machine **245** may be instantiated within the network **205**. The virtual machine **245** may be an envoy virtual machine that is configured to create a tunnel **265** between the virtual machine **245** and the DMS **210** (e.g., the node **215**) via which communications between the DMS **210** (e.g., the node **215**, the server **220**, the client **225**) and the network **205** (e.g., the host **235**, the domain controller **240**) may be communicated. Communications (e.g., messages, packets) between the DMS **210** network **205** via the tunnel **265** may be routed via (e.g., through) various entities. In some examples, the tunnel **265** may be created between software processes **255** at the virtual machine **245** and the node **215**. For example, the virtual machine **245** may use (e.g., implement, execute, run) a software process **255-a**, and the node **215** may use a software process **255-b**. In some examples, the software processes **255** may support packet forwarding from various sockets

via a single secure tunnel, such as the tunnel **265**, which may be a TLS tunnel. For example, the software processes **255** may implement TLS tunneling to forward packets via the tunnel **265**. In some examples, the software processes **255** may be referred to as TLS tunneling processes.

(44) Additionally, in some cases, the communications may be routed through respective translators **260** (e.g., a network address translator (NAT) devices) associated with the node **215** and the network **205** (e.g., a translator **260-a** associated with the network **205**, a translator **260-b** associated with the node **215**). The translators **260** may be configured to translate IP addresses (e.g., source IP addresses, destination IP addresses) included in the communications from private IP addresses to public IP addresses (e.g., and vice versa). For example, the translator **260-a** may translate private IP addresses of the host **235** and the domain controller **240** to a public IP address of the network **205**, and vice versa. The translator **260-b** may translate private IP addresses of the server **220** or client **225** to a public IP address of the DMS **210** (e.g., the node **215**), and vice versa.

(45) The DMS **210** may utilize the virtual machine **245** to create the account **285** at the non-addressable domain controller **240**. For example, because the virtual machine **245** is instantiated (e.g., resides, is located) within the network **205**, the virtual machine **245** may be able to obtain a list of one or more domain controllers **240** within the network **205** that are available for accessing by the DMS **210**. For instance, the virtual machine **245** may access the DNS server **247** to obtain the IP addresses (e.g., the private IP addresses) of the one or more domain controllers **240**, which may include the domain controller **240**. In some examples, the virtual machine **245** may obtain the list of domain controllers **240** in response to a request from the DMS **210**. For example, the DMS **210** (e.g., the node **215**, the client **225**) may transmit a list request **270** to the virtual machine **245** via the tunnel **265** that requests for the virtual machine **245** to obtain the and transmit the list to the DMS **210**. In some examples, the virtual machine **245** may be configured to obtain and transmit the list to the DMS **210** after instantiation within the network **205** (e.g., without an explicit request from the DMS **210**). The virtual machine **245** may transmit the list to the DMS **210** (e.g., the node **215**, the client **225**) via a list message **275**. In some examples, the list message **275** may include the private IP addresses of the one or more domain controllers **240** included in the list (e.g., the list may be a list of the private IP addresses).

(46) Because the DMS **210** obtains the list of domain controllers **240** via the virtual machine **245**, the DMS **210** may refrain from accessing (e.g., attempting to access) the DNS server **247**. For example, the virtual machine **245** may access the DNS server **247** instead of the DMS **210** such that directly accessing the DNS server **247** by the DMS **210** may be unnecessary. In some examples, the DMS **210** may maintain an up-to-date list of the domain controllers **240** via the virtual machine **245**. For example, the DMS **210** may use (e.g., execute, run, maintain) a background job to maintain the list of domain controllers **240** up-to-date, such as if there is a change to which domain controllers **240** within the network **205** are available.

(47) The DMS **210** may use the list of domain controllers **240** received via the list message **275** to create the account **285** at the domain controller **240**. For example, the DMS **210** may select the domain controller **240** from the list of domain controllers **240** at which to create the account **285**. To support transmission of a packet to the selected domain controller **240**, the DMS **210** may allocate a virtual IP address **290** to the domain controller **240**. For example, the list of domain controllers **240** may include the private IP address of the domain controller **240**, which may be unknown to the DMS **210** prior to the list being obtained. However, the private IP address may be private and may thus not be directly reachable by the DMS **210**. But the private IP address of the domain controller **240** may be reachable by the virtual machine **245**.

(48) Allocation of the virtual IP address **290** to the domain controller **240** may enable the virtual machine **245** to route an account message **280**, transmitted by the DMS **210** (e.g., the node **215**, the client **225**), to the domain controller **240**, where the account message **280** requests (e.g., supports) the creation of the account **285** at the domain controller **240**. For example, after (e.g., in response to) obtaining the list of domain controllers **240**, the DMS **210** may allocate a respective

virtual IP address **290** to each domain controller **240**) included in the list. The virtual IP address **290** may indicate to which domain controller **240** the virtual machine **245** is to route (e.g., forward) the account message **280**. For example, the account message **280**), as received at the software process **255-b**, may include the virtual IP address **290** allocated to the domain controller, such as being the destination IP address of the account message **280**) or being included in addition to the destination IP address of the account message **280**) (e.g., which may be the IP address of the network **205**).

(49) In some examples, the virtual IP address **290** may be allocated from a loopback address space. For example, the loopback address space may be a reserved IP address (e.g., that starts from 127.0.0.0 and ends at 127.255.255.255) that enables the DMS **210** (e.g., the node **215**) to send and receive its own packets. In some examples, the virtual IP address **290** may be an IP address within the loopback address space such that a loopback interface may be used to forward the account message **280** while identifying the corresponding domain controller **240**).

(50) The software process **255-b** may forward the account message **280** to the virtual machine **245** via the tunnel **265**. The account message **280**, as communicated via the tunnel **265**, may include an identifier **295** associated with the domain controller **240**. In some examples, the identifier **295** may be the virtual IP address **290**. In some examples, the identifier **295** may be some other identifier associated with the domain controller **240** that the software process **255-b** may bind (e.g., add, insert, append) to the account message **280**) based on the virtual IP address **290** included in the account message **280** as received at the software process **255-b**. The virtual machine **245** may include a mapping (e.g., a routing configuration) that maps the identifier **295** to the private IP address of the domain controller **240** (e.g., maps the virtual IP address **290** to the private IP address of the domain controller **240**, maps the identifier bound to the account message **280** to the private IP address of the domain controller **240**). Accordingly, using the mapping, the virtual machine **245** may route the account message **280**) to the domain controller **240**. The domain controller **240**) may create the account **285** for the DMS **210** based on (e.g., in response to) receiving the account message **280**. In this way, the DMS **210** may support the creation of the account **285** at the non-addressable domain controller **240** such that the DMS **210** may subsequently be authorized to request authentication of the host **235**, as described with reference to FIGS. **3** and **4**.

(51) In some examples, the DMS **210** (e.g., the node **215**, the client **225**) may transmit a packet, using the virtual IP address allocated to the domain controller **240**, requesting to establish a connection with the domain controller **240** prior to the transmission of the account message **280**), and the DMS **210** may transmit the account message **280** via the established connection (e.g., without inclusion of the virtual IP address **290**). In some examples, the account message **280** may include or be an implicit request to establish the connection with the domain controller **240**. In some examples, the domain controller **240**) may transmit a packet to the DMS **210** (e.g., the node **215**, the client **225**) indicating a confirmation of the creation of the account **285** at the domain controller **240**).

(52) In some examples, communication of the list request **270**), the list message **275**, the account message **280**), or a combination thereof, may bypass a demultiplexer **346**, as described with reference to FIG. **3** in reference to the communication of an authentication request **350**) and an authentication message **352**.

(53) FIG. **3** illustrates an example of a computing environment **300** that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure. The computing environment **300** may implement or be implemented by aspects of the computing environments **100** and **200** described with reference to FIGS. **1** and **2**. For example, the computing environment **300** may include a DMS **310**, which may be an example of a DMS **110** or **210** described herein, including with reference to FIGS. **1** and **2**. The computing environment **300** may support the authentication of and establishment of a connection with a non-addressable host **328** using a non-addressable domain controller **330**.

(54) The computing environment **300** may include a network **305**, which may be an example of a network **205** described with reference to FIG. 2. The network **305** may include the host **328** and the domain controller **330**, which may be examples of a host **235** and a domain controller **240** described with reference to FIG. 2. The DMS **310** may include a node **315**, which may be an example of a node **215**. The node **315** may include one or more servers **320** (e.g., a server **320-a** and **320-b**) and one or more clients **322** (e.g., a client **322-a** and **322-b**), which may be examples of a server **220** and a client **225**, respectively. For example, in the example of FIG. 3, the server **320-a** and the client **322-a** may be associated with a domain **326-a** (e.g., a domain **230**) and the server **320-b** and the client **322-b** may be associated with a domain **326-b** (e.g., a domain **230**).

(55) A virtual machine **334** may be instantiated within the network **305** to support communications between the network **305** and the DMS **310**, as described with reference to the virtual machine **245** of FIG. 2. For example, the virtual machine **334** may create a tunnel **342** (e.g., a tunnel **265**) between the DMS **310** and the network **305**, such as between a software process **338-a** at the virtual machine **334** and a software process **338-b** at the node **315**, which may be examples of the software processes **255**. As described with reference to FIG. 2, the DMS **310** may obtain a list of domain controllers **330** within the network **305** and use the list of domain controllers **330** to create an account **332** (e.g., an account **285**) at the domain controller **330** for the DMS **310** (e.g., the node **315**, the client **322-a**). Additionally, as described with reference to FIG. 2, the DMS **310** may allocate (e.g., assign) a virtual IP address **354** to the domain controller **330** for use in transmitting packets to the domain controller **330**.

(56) The host **328** may attempt to establish a connection with the server **320-a** that is used to back up the host **328**. For example, the host **328** may transmit a packet **348** to the DMS **310** that is associated with a request to establish the connection with server **320-a**. For instance, the packet **348** may explicitly request to establish the connection with the server **220-a**. Additionally or alternatively, the packet **348** may include other information, such as information associated with a snapshot **135** or a restore command (among other types of information), which, in some cases, may function as an implicit request to establish the connection (e.g., if the request is excluded from the packet **348**).

(57) The packet **348** may be routed via various entities to be received at the corresponding server **320-a**. For example, the host **328** may access (e.g., establish a connection with, communicate with) the server **320-a** by connecting to an IP address (e.g., a live-mountable IP address) associated with the DMS **310** (e.g., the node **315** where the server **320-a** is running), where the IP address may be included in (e.g., exposed to the host **328** by) the virtual machine **334**. That is, to transmit a packet **348** to the server **320-a**, the host **328** may transmit (e.g., send, forward) the packet **348** to the virtual machine **334**, and the packet **348** may include a destination IP address of the IP address associated with the DMS **310**. The virtual machine **334** may receive the packet **348** via a port **336**, which may be an example of a network file system (NFS) listening port (e.g., a port having a port number of 2049) or an SMB port (e.g., a port having a port number 445), among other ports via which the virtual machine **334** may receive the packet **348**. The virtual machine **334** may transmit (e.g., forward) the packet **348** to the node **315** via the tunnel **342** using the software process **338-a**. The packet **348** may also be routed via a translator **340-a** associated with the network **305** and a translator **340-b** associated with the DMS **310**, which may be examples of the translators **260-a** and **260-b**, respectively.

(58) The node **315** may use the software process **338-b** to determine a port of the node **315** to which to forward the packet **348**. For example, the node **315** may include various ports (e.g., virtual points of a network connection) via which different types of traffic may be received. Ports may support the differentiation between different types of traffic, and each port may be reserved for one or more communication protocols. In some examples, communications between the server **320-a** and the hosts **328** and between the client **322-a** and the domain controller **330** may be communicated according to (e.g., using) an SMB protocol (among other possible communication

protocols). The software process **338-b** may identify the communication protocol according to which the packet **348** is communicated (e.g., the SMB protocol) and may forward the packet to a port **344** corresponding to the communication protocol. In some examples, the port **344** have a port number of 445.

(59) The node **315** may include a demultiplexer **346** that is configured to monitor for packets **348** received via the port **344** (e.g., listen to SMB connections at the port **344**) and to route (e.g., forward) the packets **348** to a corresponding server **320** (e.g., the server **320-a**) based on a source IP address of the packet **348**. For example, the destination IP address of the packet **348** may be the IP address associated with the DMS **310** (e.g., the IP address of the node **315**) but may not be specific to the server **320-a** for which the packet **348** is intended. As such, routing to the proper server **320** may be unsupported using the destination IP address alone. Instead, to route the packet **348** to the proper server **320**, the demultiplexer **346** may include a routing configuration that maps respective source IP addresses to respective domains **326**. The hosts **328** may be associated with a respective domain **326** (e.g., the domain **326-a**) such that traffic from a respective host **328** may be routed to the corresponding server **320-a** via the demultiplexer **346** and in accordance with the routing configuration.

(60) As part of forwarding (e.g., routing) the packet **348** to the port **344**, the source IP address of the packet **348** may be dropped. For example, after the packet is received at the node **315**, the software process **338-b** may drop the IP address (e.g., an IP address of the network **305**, such as a private or public IP address of the network **305**) included as the source IP address of the packet **348** (e.g., in conjunction with forwarding the packet **348** to the port **344**). To support routing of the packet **348** to the server **320-a**, the DMS **310** may allocate a virtual IP address to the host **328** (e.g., a virtual IP address having an IP address within the loopback address space such that the packet **348** may be forwarded on a loopback interface). For example, the DMS **310** may allocate the virtual IP address to the host **328** and generate the routing configuration such that it maps virtual IP addresses to respective domains **326**. After the source IP address of the packet **348** is dropped, the software process **338-b** may set the source IP address of the packet **348** to be the virtual IP address allocated to the host, for example, based on an identifier of the host **328** included in the packet **348** (e.g., which may be or be used to identify the virtual IP address). Accordingly, when the packet **348** is received (e.g., intercepted) by the demultiplexer **346**, the demultiplexer **346** may route the packet **348** to the server **320-a** in accordance with the routing configuration and the setting of the source IP address to be the virtual IP address. In some examples, the demultiplexer **346** may be an example of an Nginx server, and the routing configuration may be an example of a Nginx configuration file (e.g., an nginx.config file).

(61) The DMS **310** may support authentication of whether the host **328** is authorized (e.g., permitted) to access the server **320-a** before establishing the connection with the host **328**. For example, in response to receiving the packet **348**, the DMS **310** may attempt to establish a connection with the domain controller **330** to request for the domain controller **330** to authenticate the host **328** (e.g., indicate whether the host **328** is authorized to access the server **320-a**). For instance, the client **322-a** may transmit an authentication request **350** to the domain controller **330** that requests the domain controller **330** to authenticate the host **328**. In some cases, however, the authentication request **350** (e.g., or a prior packet requesting to establish the connection with the domain controller **330**, for example, if the authentication request **350**) is transmitted after the connection is established) may be intercepted by the demultiplexer **346** and dropped.

(62) For example, connection requests initiated within the DMS **310** from different domains **326** may include the same source IP address. Additionally, the connection requests may be communicated via the port **344** (e.g., port number 445 due to be communicated in accordance with the SMB protocol), which the demultiplexer **346** may be configured to monitor. As such, the demultiplexer **346** may be configured to intercept packets communicated via the port **344** to support route the packets to a corresponding destination. However, because the packets from

different domains **326** include the same source IP address (e.g., an IP address associated with the node **315**), the routing configuration may exclude a mapping from the source IP address of the packet, as such a mapping would be unable to distinguish between different clients **322** that sent the packet. Accordingly, the authentication request **350** transmitted by the client **322-a** may be intercepted by the demultiplexer **346** and dropped, as it may be unclear with which client **322** the connection is to be established. As such, the DMS **310** may be unable to connect with the domain controller **330** to request authentication of the host **328** in response to the packet **348**.

(63) To support establishing a connection with the domain controller **330** (e.g., such as to transmit the authentication request **350** and an account message **280**, among other purposes), connection requests received from outside of the DMS **310** (e.g., from within the network **305**) may be distinguished from connection requests initiated from within the DMS **310** by the demultiplexer **346**. For example, a storage entity that backs up the host **328** may operate as the server **320-a** and the client **322-a**. The storage entity may operate in a server mode if operating as the server **320-a** and may operate in a client mode if operating as the client **322-a**. That is, if the storage entity operates as the server **320-a** to receive a connection request from the host **328** (e.g., receive the packet **348**) via the port **344**, the storage entity may be said to operate in the server mode. Similarly, if the storage entity operates as the client **322-a** to transmit (e.g., initiate) a connection request (e.g., the authentication request **350**), an account message **280**) with the domain controller **330**, the storage entity may be said to operate in the client mode.

(64) The DMS **310** may configure the demultiplexer **346** to monitor (e.g., listen to) the port **344** when (e.g., if) the storage entity operates in the server mode such that the packet **348** may be properly routed to the server **320-a**. The DMS **310** may also configure the demultiplexer **346** to not monitor (e.g., not listen to, refrain from monitoring, be disabled) the port **344** when the storage entity operates in the client mode. As such, the packets transmitted by the client **322-a** (e.g., the authentication request **350**, the account message **280**) may not be intercepted by the demultiplexer **346**, which may prevent dropping of these packets by the demultiplexer **346**. That is, the packets transmitted by the client **322-a** may bypass the demultiplexer **346** to avoid being intercepted and dropped by the demultiplexer **346**.

(65) As described with reference to FIG. 2, the packets transmitted by the client **322-a** may include a virtual IP address **354** (e.g., a virtual IP address **290**) allocated to the domain controller **330** to support reaching the domain controller **330** (e.g., routing of the packets to the domain controller **330** by the virtual machine **334**). For example, these packets, as communicated via the tunnel **342**, may include an identifier **356** (e.g., an identifier **295**) associated with the domain controller **330**. In some examples, the identifier **356** may be the virtual IP address **354** or be some other identifier associated with the domain controller **330** that the software process **338-b** may bind (e.g., add, insert, append) to the packets based on the virtual IP address **354** included in the packets as received at the software process **338-b**. The virtual machine **334** may use a mapping (e.g., a routing configuration) that maps the identifier **356** to a private IP address of the domain controller **330** to route these packets to the domain controller **330**.

(66) In some examples, the DMS **310** may configure the demultiplexer **346** to monitor or not monitor the port **344** based on a virtual interface (e.g., a virtual IP address) used to communicate a packet. For example, the node **315** may be associated with (e.g., allocated) a first virtual IP address at which the node **315** receives packets via the tunnel **342**. The DMS **310** may configure the demultiplexer **346** to intercept and route packets received via the tunnel **342** using the virtual IP address associated with the node **315**. For example, the software process **338-b** may set (e.g., bind) the first virtual IP address as a destination IP address of packets received via the tunnel **342** (such as to support a loopback-to-loopback connection), and the DMS **310** may configure the demultiplexer **346** to monitor the port **344** for packets having the first virtual IP address as the destination IP address. The DMS **310** may configure the demultiplexer to refrain from intercepting

packets communicated (e.g., transmitted from within the node **315**, such as from the client **322-a**) using the virtual IP address allocated to the domain controller **330**.

(67) The domain controller **330** may authenticate the host **328** in response to the authentication request **350**. For example, the domain controller **330** may receive the authentication request **350** and determine whether the host **328** is authorized to access the server **320-a** (e.g., the domain **326-a**). The domain controller **330** may transmit an authentication message **352** to the client **322-a** that indicates whether the host **328** is authorized to access the server **320-a**. If the host **328** is authorized to access the server **320-a** (e.g., if the host **328** is authenticated), the DMS **310** (e.g., the server **320-a**) may establish the connection between the server **320-a** and the host **328** via which additional packets may be communicated. If the host **328** is not authorized to access the server **320-a**, the DMS **310** may drop the connection (e.g., refrain from establishing the connection). In the example of FIG. 3, the authentication message **352** may indicate an authentication of the host **328**, and the DMS **310** (e.g., the server **320-a**) may establish the connection with the host **328**.

(68) The authentication message **352** may be communicated via the same path as the authentication request **350** (e.g., but in the reverse direction). As such, the authentication message **352** may similarly bypass the demultiplexer **346** as it is routed to the client **322-a** based on being in response to the authentication request **350**. For example, the authentication message **352** may be communicated via the virtual interface with the domain controller **330** (e.g., using the virtual IP address allocated to the domain controller **330**).

(69) As shown in the example of FIG. 3, the DMS **310** may also support communication with a host **358** and a domain controller **360**. The host **358** and the domain controller **360** may be directly addressable by the DMS **310**. That is, the host **358** and the domain controller **360** may have IP addresses that are directly reachable by the DMS **310**. The server **320-b** and the client **322-b** may be used to provide backup, recovery, and authentication services for the host **358** and the domain **326-b**. Because the IP addresses may be directly reachable by the DMS **310**, communications between the host **358** and the server **320-b** and between the client **322-b** and the domain controller **360** may be communicated without the usage of virtual IP addresses (e.g., using the directly reachable IP addresses).

(70) In an example, such as the example of FIG. 3, the node **315** may be configured to provide backup and recovery services to the network **305** having one client host (e.g., the host **328**). The host **328** within the network **305** may be a part of the domain **326-a** having a single domain controller (e.g., the domain controller **330**), and connectivity between the node **315** and the network **305** may be through the tunnel **365**. The node **315** may also be configured to provide backup and recovery services to the host **358** having direct connectivity with the node **315**. The host **358** may be a part of the domain **326-b** having a single domain controller (e.g., the domain controller **360**). In this example, an example routing configuration of the demultiplexer **346** may be as follows:

(71) TABLE-US-00001 geo \$remote_addr \$backend { 127.128.1.35 Domain1.com;
10.0.178.124 Domain2.com; } upstream Domain1.com { server 127.0.0.138:1445; } upstream
Domain2.com { server 127.0.0.139:1445; } server { listen 10.0.39.214:445; proxy_timeout
7d; proxy_pass \$backend; } server { listen 127.128.2.0:445; proxy_timeout 7d;
proxy_pass \$backend; }

(72) The routing configuration may include a mapping for a virtual IP address 127.128.1.35 of (e.g., allocated to) the host **328** to the Domain1.com, which may be the domain **326-a**. The routing configuration may also include a mapping for an IP address 10.0.178.124 of the host **358** to the Domain2.com, which may be the domain **326-b**. The routing configuration may also map the Domain1.com to a server having the address 127.0.0.138:1445 (e.g., the server **320-a**) and map the Domain2.com to a server having the address server 127.0.0.139:1445 (e.g., the server **320-b**). Accordingly, in accordance with the routing configuration, the demultiplexer **346** may route a packet having the virtual IP address 127.128.1.35 set as the source IP address to the server 127.0.0.138:1445 and route a packet having the IP address 10.0.178.124 set as the source IP

address to the server 127.0.0.139:1445

(73) The routing configuration may also indicate for which interfaces (e.g., IP addresses) the demultiplexer **346** is configured to listen to the port **344**. For example, the routing configuration may indicate that the demultiplexer is configured to intercept and route packets communicated via the port having port number 445 (e.g., the port **344**) for all public interfaces of the node **315** and for virtual interfaces of the node **315** via which packets are received via the tunnel **342**. Virtual interfaces of (e.g., virtual IP addresses allocated to) non-addressable domain controllers may be excluded from the listening configuration. In the example of the routing configuration above, the demultiplexer **346** may be configured to intercept and route packets communicated via port 445 that have the IP addresses 10.0.39.214 and 127.128.2.0, which may correspond to a public interface of the node **315** and a virtual interface (e.g., private interface) of the node **315**, respectively. As such, packets having different virtual IP addresses, such as the virtual IP address **354** allocated to the domain controller **330**, may not be intercepted by the demultiplexer **346** based on the routing configuration indicating that the demultiplexer **346** is not configured to listen to the port **344** for that virtual interface.

(74) In some examples, the software process **338-b** may bind the IP address 127.128.2.0 to packets received via the tunnel **342** before (e.g., as part of) forwarding the packet to port 445. In some examples, the virtual IP address allocated to the node **315** as the virtual interface may be allocated statically to avoid conflicts (e.g., allocation of same virtual IP addresses) with virtual IP addresses allocated to hosts **328** and domain controllers **330**).

(75) FIG. 4 illustrates an example of a process flow **400** that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure. The process flow **400** may implement or be implemented by aspects of the computing environments described with reference to FIGS. 1 through 3. For example, the process flow **400** may be implemented by a network **405** and a DMS **410**. The network **405** and the DMS **410** may be examples of the corresponding networks and systems described with reference to FIGS. 1 through 3. The DMS **410** may include a server **415**, a client **420**, and a demultiplexer **425** (among other components, software entities, or a combination thereof), which may be examples of the corresponding aspects described with reference to FIGS. 2 and 3. The network may include **405** may include a virtual machine **430**, a host **435**, and a domain controller **440**, which may be examples of the corresponding aspects described with reference to FIGS. 2 and 3.

(76) In the following description of the process flow **400**, the operations between the network **405** and the DMS **410** may be performed in a different order than the example order shown, or the operations performed by the network **405** and the DMS **410** may be performed in different orders or at different times. Some operations may also be omitted from the process flow **400**, and other operations may be added to the process flow **400**. Further, although some operations or signaling may be shown to occur at different times for discussion purposes, these operations may actually occur at the same time.

(77) At **442**, the virtual machine **430** may create a tunnel (e.g., a tunnel **265** or **342**) to support communications between the network **405** and the DMS **410**. For example, the tunnel may be a TLS tunnel via which the host **435** may communicate packets with the DMS **410** (e.g., the server **415**) and via which the client **420** may communicate packets with the domain controller **440**. In some examples, the tunnel may be between the virtual machine **430** and the DMS **410**, such as between software processes at the virtual machine **430** and the DMS **410** that support multiplexing and demultiplexing various network data flows (e.g., to corresponding ports).

(78) At **444**, the DMS **410** may transmit a list request to the virtual machine **430** via the tunnel. For example, the list request may request for the virtual machine **430** to obtain and transmit a list of one or more domain controllers **440** within the network **405** that are available for access by the DMS **410** (e.g., the client **420**).

(79) At **446**, the virtual machine **430** may transmit a list message to the DMS **410** via the tunnel

that indicates the list of one or more domain controllers **440**, including the domain controller **440**. In some examples, the virtual machine may transmit the list message in response to the list request. In some examples, the virtual machine **430** may transmit the list message after (e.g., in response to) being instantiated within the network **405**, such as without receiving the list request. In some examples, the virtual machine **430** may obtain the list from a DNS server within the network **405** that is not directly reachable by the DMS **410**.

(80) At **448**, the DMS **410** may create an account (e.g., a machine account) at the domain controller **440** for the DMS **410** such that the DMS **410** may be authorized (e.g., permitted) to request authentication of the host **435** by the domain controller **440**. For example, the DMS **410** (e.g., the client **420**) may transmit an account message to the domain controller **440** via the tunnel that requests to create the account for the DMS **410** at the domain controller **440**. The DMS **410** may transmit the account message such that it bypasses the demultiplexer **425**, for example, based on the demultiplexer being configured to not monitor a port via which the account message is transmitted when the DMS **410** is operating in a client mode (e.g., as the client **420**, such as the account message being transmitted by the client **420**).

(81) At **450**, the host **435** may transmit a packet intended for the server **415**. For example, the packet may be associated with a request to establish a connection with the server **415**. The host **435** may transmit the packet to the virtual machine **430**.

(82) At **452**, the virtual machine **430** may forward the packet to the DMS **410** via the tunnel. For example, the virtual machine **430** may forward the packet to the software process at the DMS **410**.

(83) At **454**, the software process at the DMS **410** may forward the packet to the port that may be monitored by the demultiplexer **425**. The software process may bind a virtual IP address allocated to the host **435** to the packet as the source IP address of the packet.

(84) At **456**, the demultiplexer **425** may route the packet to the server **415**. For example, the demultiplexer **425** may intercept the packet forwarded to the port and route the packet to the server **415** in accordance with the virtual IP address allocated to the host **435** and corresponding to the server **415**.

(85) At **458**, the DMS **410** may initiate an authentication of the host **435**. For example, the client **420** may transmit an authentication request intended for the domain controller **440** requesting for the domain controller to authenticate the host **435** (e.g., verify whether the host **435** is authorized to access the server **415**). The authentication request may be transmitted via the port to the software process at the DMS **410** and to the virtual machine **430** via the tunnel. The authentication request may bypass the demultiplexer **425** based on the demultiplexer being configured to not monitor the port when DMS **410** is operating in the client mode.

(86) At **460**, the virtual machine **430** may forward the authentication request to the domain controller **440**, for example, by mapping an identifier associated with the domain controller **440** and included in the authentication request to a private IP address of the domain controller **440**.

(87) At **462**, the domain controller **440** may transmit an authentication message to the client **420** indicating whether the host **435** is authenticated. The authentication message may be routed via a same path (e.g., but in reverse order) as the authentication request, thus bypassing demultiplexer **425**. In the example of FIG. 4, the authentication message may indicate that the host **435** is authenticated.

(88) At **464**, the server **415** (e.g., the DMS **410**) may establish the connection with the host **435** based on the host **435** being authenticated by the domain controller **440**.

(89) FIG. 5 illustrates a block diagram **500** of a system **505** that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure. In some examples, the system **505** may be an example of aspects of one or more components described with reference to FIGS. 1 through, such as a DMS **110**, **210**, **310**, or **410**. The system **505** may include an input interface **510**, an output interface **515**, and a storage manager **520**. The system **505** may also include one or more processors. Each of these components may be in communication with one

another (e.g., via one or more buses, communications links, communications interfaces, or any combination thereof).

(90) The input interface **510** may manage input signaling for the system **505**. For example, the input interface **510** may receive input signaling (e.g., messages, packets, data, instructions, commands, or any other form of encoded information) from other systems or devices. The input interface **510** may send signaling corresponding to (e.g., representative of or otherwise based on) such input signaling to other components of the system **505** for processing. For example, the input interface **510** may transmit such corresponding signaling to the storage manager **520** to support host authentication using a non-addressable domain controller. In some cases, the input interface **510** may be a component of a network interface **725** as described with reference to FIG. 7.

(91) The output interface **515** may manage output signaling for the system **505**. For example, the output interface **515** may receive signaling from other components of the system **505**, such as the storage manager **520**, and may transmit such output signaling corresponding to (e.g., representative of or otherwise based on) such signaling to other systems or devices. In some cases, the output interface **515** may be a component of a network interface **725** as described with reference to FIG. 7.

(92) For example, the storage manager **520** may include a packet reception component **525**, a routing component **530**, a packet transmission component **535**, a connection component **540**, or any combination thereof. In some examples, the storage manager **520**, or various components thereof, may be configured to perform various operations (e.g., receiving, monitoring, transmitting) using or otherwise in cooperation with the input interface **510**, the output interface **515**, or both. For example, the storage manager **520** may receive information from the input interface **510**, send information to the output interface **515**, or be integrated in combination with the input interface **510**, the output interface **515**, or both to receive information, transmit information, or perform various other operations as described herein.

(93) The storage manager **520** may support data management in accordance with examples as disclosed herein. The packet reception component **525** may be configured as or otherwise support a means for receiving a first packet at a DMS (e.g., the system **505**), where the first packet is from a host that is within a network that includes one or more hosts for which the DMS is configured to provide backup and recovery services, and where the first packet is associated with a request to establish, via a port at which the first packet is received, a connection between the host and a storage entity within the DMS that is used to back up the host. The routing component **530** may be configured as or otherwise support a means for routing the first packet to the storage entity using a demultiplexer of the DMS that is configured to monitor the port when the storage entity operates to receive packets in a server mode via the port, the demultiplexer configured to identify the storage entity based on an IP address associated with the host. The packet transmission component **535** may be configured as or otherwise support a means for transmitting, from the storage entity based on receiving the first packet, a second packet to a domain controller within the network, where the second packet requests that the domain controller authenticate the host, and where the second packet bypasses the demultiplexer based on the demultiplexer being configured not to monitor the port when the storage entity operates to transmit packets in a client mode via the port. The packet reception component **525** may be configured as or otherwise support a means for receiving, at the storage entity from the domain controller, a third packet that indicates an authentication of the host, where the third packet bypasses the demultiplexer based on being in response to the second packet. The connection component **540** may be configured as or otherwise support a means for establishing the connection between the storage entity and the host based on the authentication of the host indicated by the third packet.

(94) FIG. 6 illustrates a block diagram **600** of a storage manager **620** that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure. The storage manager **620** may be an example of aspects of a storage manager or a storage manager **520**, or both, as described herein. The storage manager **620**, or various

components thereof, may be an example of means for performing various aspects of host authentication using a non-addressable domain controller as described herein. For example, the storage manager **620** may include a packet reception component **625**, a routing component **630**, a packet transmission component **635**, a connection component **640**, a tunnel component **645**, an IP address allocation component **650**, a list component **655**, an account component **660**, or any combination thereof. Each of these components may communicate, directly or indirectly, with one another (e.g., via one or more buses, communications links, communications interfaces, or any combination thereof).

(95) The storage manager **620** may support data management in accordance with examples as disclosed herein. The packet reception component **625** may be configured as or otherwise support a means for receiving a first packet at a DMS, where the first packet is from a host that is within a network that includes one or more hosts for which the DMS is configured to provide backup and recovery services, and where the first packet is associated with a request to establish, via a port at which the first packet is received, a connection between the host and a storage entity within the DMS that is used to back up the host. The routing component **630**) may be configured as or otherwise support a means for routing the first packet to the storage entity using a demultiplexer of the DMS that is configured to monitor the port when the storage entity operates to receive packets in a server mode via the port, the demultiplexer configured to identify the storage entity based on an IP address associated with the host. The packet transmission component **635** may be configured as or otherwise support a means for transmitting, from the storage entity based on receiving the first packet, a second packet to a domain controller within the network, where the second packet requests that the domain controller authenticate the host, and where the second packet bypasses the demultiplexer based on the demultiplexer being configured not to monitor the port when the storage entity operates to transmit packets in a client mode via the port. In some examples, the packet reception component **625** may be configured as or otherwise support a means for receiving, at the storage entity from the domain controller, a third packet that indicates an authentication of the host, where the third packet bypasses the demultiplexer based on being in response to the second packet. The connection component **640** may be configured as or otherwise support a means for establishing the connection between the storage entity and the host based on the authentication of the host indicated by the third packet.

(96) In some examples, the tunnel component **645** may be configured as or otherwise support a means for instantiating, within the network, a virtual machine configured to create a tunnel for communications between the DMS and the one or more hosts. In some examples, the routing component **630** may be configured as or otherwise support a means for configuring the demultiplexer not to monitor the port when the storage entity operates to transmit packets in the client mode based on the packets being transmitted via the tunnel.

(97) In some examples, the IP address allocation component **650** may be configured as or otherwise support a means for allocating a virtual IP address to the domain controller, the virtual IP address different than a private IP address of the domain controller, where the second packet is transmitted to the domain controller using the virtual IP address.

(98) In some examples, the tunnel component **645** may be configured as or otherwise support a means for instantiating, within the network, a virtual machine configured to create a tunnel for communications between the DMS and the one or more hosts. In some examples, the list component **655** may be configured as or otherwise support a means for obtaining, via the virtual machine, a list of one or more domain controllers within the network, where the one or more listed domain controllers are associated with authenticating the one or more hosts. In some examples, the account component **660** may be configured as or otherwise support a means for creating, before transmitting the second packet, an account for the DMS at the domain controller based on the domain controller being included in the one or more listed domain controllers, where the third packet is received from the domain controller based on the account created at the domain

controller.

(99) In some examples, the list component **655** may be configured as or otherwise support a means for transmitting, to the virtual machine, a fourth packet requesting the list of one or more domain controllers, where the list of one or more domain controllers is obtained via the virtual machine in response to the fourth packet.

(100) In some examples, the list component **655** may be configured as or otherwise support a means for maintaining, via the virtual machine, an up-to-date list of the one or more domain controllers within the network.

(101) In some examples, the list component **655** may be configured as or otherwise support a means for refraining from accessing a DNS server within the network to obtain the list of one or more domain controllers, the refraining based on obtaining the list of one or more domain controllers via the virtual machine.

(102) In some examples, the domain controller is associated with an IP address that, based on the domain controller being within the network, is unknown to the DMS prior to the list of one or more domain controllers being obtained. In some examples, the IP address associated with the domain controller is not directly reachable by the DMS. In some examples, the second packet is transmitted to the domain controller based on obtaining the list of one or more domain controllers.

(103) In some examples, the storage entity operating to transmit packets in the client mode includes the storage entity transmitting packets to request to establish a respective connection between the storage entity and a respective entity within the network.

(104) In some examples, the storage entity operating to receive packets in the server mode includes the storage entity receiving packets to request to establish a respective connection between the storage entity and a respective entity within the network.

(105) FIG. 7 illustrates a block diagram **700** of a system **705** that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure. The system **705** may be an example of or include the components of a system **505** as described herein. The system **705** may include components for data management, including components such as a storage manager **720**, an input information **710**, an output information **715**, a network interface **725**, a memory **730**, a processor **735**, and a storage **740**. These components may be in electronic communication or otherwise coupled with each other (e.g., operatively, communicatively, functionally, electronically, electrically: via one or more buses, communications links, communications interfaces, or any combination thereof). Additionally, the components of the system **705** may include corresponding physical components or may be implemented as corresponding virtual components (e.g., components of one or more virtual machines). In some examples, the system **705** may be an example of aspects of one or more components described with reference to FIGS. 1 through 4, such as a DMS **110**, **210**, **310**, or **410**.

(106) The network interface **725** may enable the system **705** to exchange information (e.g., input information **710**, output information **715**, or both) with other systems or devices (not shown). For example, the network interface **725** may enable the system **705** to connect to a network (e.g., a network **120** as described herein). The network interface **725** may include one or more wireless network interfaces, one or more wired network interfaces, or any combination thereof. In some examples, the network interface **725** may be an example of may be an example of aspects of one or more components described with reference to FIG. 1, such as one or more network interfaces **165**.

(107) Memory **730** may include RAM, ROM, or both. The memory **730** may store computer-readable, computer-executable software including instructions that, when executed, cause the processor **735** to perform various functions described herein. In some cases, the memory **730** may contain, among other things, a basic input/output system (BIOS), which may control basic hardware or software operation such as the interaction with peripheral components or devices. In some cases, the memory **730**) may be an example of aspects of one or more components described with reference to FIG. 1, such as one or more memories **175**.

(108) The processor **735** may include an intelligent hardware device, (e.g., a general-purpose processor, a DSP, a CPU, a microcontroller, an ASIC, a field programmable gate array (FPGA), a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). The processor **735** may be configured to execute computer-readable instructions stored in a memory **730** to perform various functions (e.g., functions or tasks supporting host authentication using a non-addressable domain controller). Though a single processor **735** is depicted in the example of FIG. 7, it is to be understood that the system **705** may include any quantity of one or more of processors **735** and that a group of processors **735** may collectively perform one or more functions ascribed herein to a processor, such as the processor **735**. In some cases, the processor **735** may be an example of aspects of one or more components described with reference to FIG. 1, such as one or more processors **170**.

(109) Storage **740** may be configured to store data that is generated, processed, stored, or otherwise used by the system **705**. In some cases, the storage **740** may include one or more HDDs, one or more SSDs, or both. In some examples, the storage **740** may be an example of a single database, a distributed database, multiple distributed databases, a data store, a data lake, or an emergency backup database. In some examples, the storage **740** may be an example of one or more components described with reference to FIG. 1, such as one or more network disks **180**.

(110) The storage manager **720** may support data management in accordance with examples as disclosed herein. For example, the storage manager **720** may be configured as or otherwise support a means for receiving a first packet at a DMS (e.g., the system **705**), where the first packet is from a host that is within a network that includes one or more hosts for which the DMS is configured to provide backup and recovery services, and where the first packet is associated with a request to establish, via a port at which the first packet is received, a connection between the host and a storage entity within the DMS that is used to back up the host. The storage manager **720** may be configured as or otherwise support a means for routing the first packet to the storage entity using a demultiplexer of the DMS that is configured to monitor the port when the storage entity operates to receive packets in a server mode via the port, the demultiplexer configured to identify the storage entity based on an IP address associated with the host. The storage manager **720** may be configured as or otherwise support a means for transmitting, from the storage entity based on receiving the first packet, a second packet to a domain controller within the network, where the second packet requests that the domain controller authenticate the host, and where the second packet bypasses the demultiplexer based on the demultiplexer being configured not to monitor the port when the storage entity operates to transmit packets in a client mode via the port. The storage manager **720** may be configured as or otherwise support a means for receiving, at the storage entity from the domain controller, a third packet that indicates an authentication of the host, where the third packet bypasses the demultiplexer based on being in response to the second packet. The storage manager **720** may be configured as or otherwise support a means for establishing the connection between the storage entity and the host based on the authentication of the host indicated by the third packet.

(111) By including or configuring the storage manager **720** in accordance with examples as described herein, the system **705** may support techniques for host authentication using a non-addressable domain controller, which may provide one or more benefits such as, for example, backup and recovery services for non-addressable hosts, authentication of non-addressable hosts, increased security of backup and recovery services by supporting the authentication of non-addressable hosts, and backup and recovery services for additional types of network configurations (e.g., networks including non-addressable hosts and domain controllers), among other possibilities.

(112) FIG. 8 illustrates a flowchart showing a method **800** that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure. The operations of the method **800** may be implemented by a DMS or its components as described herein. For example, the operations of the method **800** may be performed by a DMS as described with reference to FIGS. 1 through 7. In some examples, a DMS may execute a set of instructions to

control the functional elements of the DMS to perform the described functions. Additionally, or alternatively, the DMS may perform aspects of the described functions using special-purpose hardware.

(113) At **805**, the method may include receiving a first packet at a DMS, where the first packet is from a host that is within a network that includes one or more hosts for which the DMS is configured to provide backup and recovery services, and where the first packet is associated with a request to establish, via a port at which the first packet is received, a connection between the host and a storage entity within the DMS that is used to back up the host. The operations of **805** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **805** may be performed by a packet reception component **625** as described with reference to FIG. 6.

(114) At **810**, the method may include routing the first packet to the storage entity using a demultiplexer of the DMS that is configured to monitor the port when the storage entity operates to receive packets in a server mode via the port, the demultiplexer configured to identify the storage entity based on an IP address associated with the host. The operations of **810** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **810** may be performed by a routing component **630** as described with reference to FIG. 6.

(115) At **815**, the method may include transmitting, from the storage entity based on receiving the first packet, a second packet to a domain controller within the network, where the second packet requests that the domain controller authenticate the host, and where the second packet bypasses the demultiplexer based on the demultiplexer being configured not to monitor the port when the storage entity operates to transmit packets in a client mode via the port. The operations of **815** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **815** may be performed by a packet transmission component **635** as described with reference to FIG. 6.

(116) At **820**, the method may include receiving, at the storage entity from the domain controller, a third packet that indicates an authentication of the host, where the third packet bypasses the demultiplexer based on being in response to the second packet. The operations of **820** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **820** may be performed by a packet reception component **625** as described with reference to FIG. 6.

(117) At **825**, the method may include establishing the connection between the storage entity and the host based on the authentication of the host indicated by the third packet. The operations of **825** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **825** may be performed by a connection component **640** as described with reference to FIG. 6.

(118) FIG. 9 illustrates a flowchart showing a method **900** that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure. The operations of the method **900** may be implemented by a DMS or its components as described herein. For example, the operations of the method **900** may be performed by a DMS as described with reference to FIGS. 1 through 7. In some examples, a DMS may execute a set of instructions to control the functional elements of the DMS to perform the described functions. Additionally, or alternatively, the DMS may perform aspects of the described functions using special-purpose hardware.

(119) At **905**, the method may include instantiating, within a network that includes one or more hosts for which a DMS is configured to provide backup and recovery services, a virtual machine configured to create a tunnel for communications between the DMS and the one or more hosts. The operations of **905** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **905** may be performed by a tunnel component **645** as described with reference to FIG. 6.

(120) At **910**, the method may include receiving a first packet at the DMS, where the first packet is from a host that is within the network, and where the first packet is associated with a request to establish, via a port at which the first packet is received, a connection between the host and a storage entity within the DMS that is used to back up the host. The operations of **910** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **910** may be performed by a packet reception component **625** as described with reference to FIG. 6.

(121) At **915**, the method may include routing the first packet to the storage entity using a demultiplexer of the DMS that is configured to monitor the port when the storage entity operates to receive packets in a server mode via the port, the demultiplexer configured to identify the storage entity based on an IP address associated with the host. The operations of **915** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **915** may be performed by a routing component **630** as described with reference to FIG. 6.

(122) At **920**, the method may include configuring the demultiplexer not to monitor the port when the storage entity operates to transmit packets in a client mode via the port based on the packets being transmitted via the tunnel. The operations of **920** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **920** may be performed by a routing component **630** as described with reference to FIG. 6.

(123) At **925**, the method may include transmitting, from the storage entity based on receiving the first packet, a second packet to a domain controller within the network, where the second packet requests that the domain controller authenticate the host, and where the second packet bypasses the demultiplexer based on the demultiplexer being configured not to monitor the port when the storage entity operates to transmit packets in the client mode. The operations of **925** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **925** may be performed by a packet transmission component **635** as described with reference to FIG. 6.

(124) At **930**, the method may include receiving, at the storage entity from the domain controller, a third packet that indicates an authentication of the host, where the third packet bypasses the demultiplexer based on being in response to the second packet. The operations of **930** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **930** may be performed by a packet reception component **625** as described with reference to FIG. 6.

(125) At **935**, the method may include establishing the connection between the storage entity and the host based on the authentication of the host indicated by the third packet. The operations of **935** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **935** may be performed by a connection component **640**) as described with reference to FIG. 6.

(126) FIG. 10 illustrates a flowchart showing a method **1000** that supports host authentication using a non-addressable domain controller in accordance with aspects of the present disclosure. The operations of the method **1000** may be implemented by a DMS or its components as described herein. For example, the operations of the method **1000** may be performed by a DMS as described with reference to FIGS. 1 through 7. In some examples, a DMS may execute a set of instructions to control the functional elements of the DMS to perform the described functions. Additionally, or alternatively, the DMS may perform aspects of the described functions using special-purpose hardware.

(127) At **1005**, the method may include instantiating, within a network that includes one or more hosts for which a DMS is configured to provide backup and recovery services, a virtual machine configured to create a tunnel for communications between the DMS and the one or more hosts. The operations of **1005** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1005** may be performed by a tunnel component **645** as

described with reference to FIG. 6.

(128) At **1010**, the method may include obtaining, via the virtual machine, a list of one or more domain controllers within the network, where the one or more listed domain controllers are associated with authenticating the one or more hosts. The operations of **1010** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1010** may be performed by a list component **655** as described with reference to FIG. 6.

(129) At **1015**, the method may include creating, an account for the DMS at the domain controller based on the domain controller being included in the one or more listed domain controllers. The operations of **1015** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1015** may be performed by an account component **660** as described with reference to FIG. 6.

(130) At **1020**, the method may include receiving a first packet at a DMS, where the first packet is from a host within the network, and where the first packet is associated with a request to establish, via a port at which the first packet is received, a connection between the host and a storage entity within the DMS that is used to back up the host. The operations of **1020** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1020** may be performed by a packet reception component **625** as described with reference to FIG. 6.

(131) At **1025**, the method may include routing the first packet to the storage entity using a demultiplexer of the DMS that is configured to monitor the port when the storage entity operates to receive packets in a server mode via the port, the demultiplexer configured to identify the storage entity based on an IP address associated with the host. The operations of **1025** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1025** may be performed by a routing component **630** as described with reference to FIG. 6.

(132) At **1030**, the method may include transmitting, from the storage entity based on receiving the first packet and after creating the account, a second packet to a domain controller within the network, where the second packet requests that the domain controller authenticate the host, and where the second packet bypasses the demultiplexer based on the demultiplexer being configured not to monitor the port when the storage entity operates to transmit packets in a client mode via the port. The operations of **1030** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1030** may be performed by a packet transmission component **635** as described with reference to FIG. 6.

(133) At **1035**, the method may include receiving, at the storage entity from the domain controller and based on the account created at the domain controller, a third packet that indicates an authentication of the host, where the third packet bypasses the demultiplexer based on being in response to the second packet. The operations of **1035** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1035** may be performed by a packet reception component **625** as described with reference to FIG. 6.

(134) At **1040**, the method may include establishing the connection between the storage entity and the host based on the authentication of the host indicated by the third packet. The operations of **1040** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1040** may be performed by a connection component **640**) as described with reference to FIG. 6.

(135) A method for data management is described. The method may include receiving a first packet at a DMS, where the first packet is from a host that is within a network that includes one or more hosts for which the DMS is configured to provide backup and recovery services, and where the first packet is associated with a request to establish, via a port at which the first packet is received, a connection between the host and a storage entity within the DMS that is used to back up the host, routing the first packet to the storage entity using a demultiplexer of the DMS that is configured to monitor the port when the storage entity operates to receive packets in a server mode via the port, the demultiplexer configured to identify the storage entity based on an IP address associated with

the host, transmitting, from the storage entity based on receiving the first packet, a second packet to a domain controller within the network, where the second packet requests that the domain controller authenticate the host, and where the second packet bypasses the demultiplexer based on the demultiplexer being configured not to monitor the port when the storage entity operates to transmit packets in a client mode via the port, receiving, at the storage entity from the domain controller, a third packet that indicates an authentication of the host, where the third packet bypasses the demultiplexer based on being in response to the second packet, and establishing the connection between the storage entity and the host based on the authentication of the host indicated by the third packet.

(136) An apparatus for data management is described. The apparatus may include at least one processor, memory coupled with the at least one processor, and instructions stored in the memory. The instructions may be executable by the at least one processor to cause the apparatus to receive a first packet at a DMS, where the first packet is from a host that is within a network that includes one or more hosts for which the DMS is configured to provide backup and recovery services, and where the first packet is associated with a request to establish, via a port at which the first packet is received, a connection between the host and a storage entity within the DMS that is used to back up the host, route the first packet to the storage entity using a demultiplexer of the DMS that is configured to monitor the port when the storage entity operates to receive packets in a server mode via the port, the demultiplexer configured to identify the storage entity based on an IP address associated with the host, transmit, from the storage entity based on receiving the first packet, a second packet to a domain controller within the network, where the second packet requests that the domain controller authenticate the host, and where the second packet bypasses the demultiplexer based on the demultiplexer being configured not to monitor the port when the storage entity operates to transmit packets in a client mode via the port, receive, at the storage entity from the domain controller, a third packet that indicates an authentication of the host, where the third packet bypasses the demultiplexer based on being in response to the second packet, and establish the connection between the storage entity and the host based on the authentication of the host indicated by the third packet.

(137) Another apparatus for data management is described. The apparatus may include means for receiving a first packet at a DMS, where the first packet is from a host that is within a network that includes one or more hosts for which the DMS is configured to provide backup and recovery services, and where the first packet is associated with a request to establish, via a port at which the first packet is received, a connection between the host and a storage entity within the DMS that is used to back up the host, means for routing the first packet to the storage entity using a demultiplexer of the DMS that is configured to monitor the port when the storage entity operates to receive packets in a server mode via the port, the demultiplexer configured to identify the storage entity based on an IP address associated with the host, means for transmitting, from the storage entity based on receiving the first packet, a second packet to a domain controller within the network, where the second packet requests that the domain controller authenticate the host, and where the second packet bypasses the demultiplexer based on the demultiplexer being configured not to monitor the port when the storage entity operates to transmit packets in a client mode via the port, means for receiving, at the storage entity from the domain controller, a third packet that indicates an authentication of the host, where the third packet bypasses the demultiplexer based on being in response to the second packet, and means for establishing the connection between the storage entity and the host based on the authentication of the host indicated by the third packet.

(138) A non-transitory computer-readable medium storing code for data management is described. The code may include instructions executable by at least one processor to receive a first packet at a DMS, where the first packet is from a host that is within a network that includes one or more hosts for which the DMS is configured to provide backup and recovery services, and where the first packet is associated with a request to establish, via a port at which the first packet is received, a

connection between the host and a storage entity within the DMS that is used to back up the host, route the first packet to the storage entity using a demultiplexer of the DMS that is configured to monitor the port when the storage entity operates to receive packets in a server mode via the port, the demultiplexer configured to identify the storage entity based on an IP address associated with the host, transmit, from the storage entity based on receiving the first packet, a second packet to a domain controller within the network, where the second packet requests that the domain controller authenticate the host, and where the second packet bypasses the demultiplexer based on the demultiplexer being configured not to monitor the port when the storage entity operates to transmit packets in a client mode via the port, receive, at the storage entity from the domain controller, a third packet that indicates an authentication of the host, where the third packet bypasses the demultiplexer based on being in response to the second packet, and establish the connection between the storage entity and the host based on the authentication of the host indicated by the third packet.

(139) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for instantiating, within the network, a virtual machine configured to create a tunnel for communications between the DMS and the one or more hosts and configuring the demultiplexer not to monitor the port when the storage entity operates to transmit packets in the client mode based on the packets being transmitted via the tunnel.

(140) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for allocating a virtual IP address to the domain controller, the virtual IP address different than a private IP address of the domain controller, where the second packet may be transmitted to the domain controller using the virtual IP address.

(141) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for instantiating, within the network, a virtual machine configured to create a tunnel for communications between the DMS and the one or more hosts, obtaining, via the virtual machine, a list of one or more domain controllers within the network, where the one or more listed domain controllers may be associated with authenticating the one or more hosts, and creating, before transmitting the second packet, an account for the DMS at the domain controller based on the domain controller being included in the one or more listed domain controllers, where the third packet may be received from the domain controller based on the account created at the domain controller.

(142) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, to the virtual machine, a fourth packet requesting the list of one or more domain controllers, where the list of one or more domain controllers may be obtained via the virtual machine in response to the fourth packet.

(143) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for maintaining, via the virtual machine, an up-to-date list of the one or more domain controllers within the network.

(144) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for refraining from accessing a DNS server within the network to obtain the list of one or more domain controllers, the refraining based on obtaining the list of one or more domain controllers via the virtual machine.

(145) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the domain controller may be associated with an IP address that, based on the domain controller being within the network, may be unknown to the DMS prior to the list of one or more domain controllers being obtained and the second packet may be transmitted to the domain controller based on obtaining the list of one or more domain controllers. In some examples of the

method, apparatuses, and non-transitory computer-readable medium described herein, the IP address associated with the domain controller may not be directly reachable by the DMS.

(146) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the storage entity operating to transmit packets in the client mode includes the storage entity transmitting packets to request to establish a respective connection between the storage entity and a respective entity within the network.

(147) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the storage entity operating to receive packets in the server mode includes the storage entity receiving packets to request to establish a respective connection between the storage entity and a respective entity within the network.

(148) It should be noted that the methods described above describe possible implementations, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible. Furthermore, aspects from two or more of the methods may be combined.

(149) The description set forth herein, in connection with the appended drawings, describes example configurations and does not represent all the examples that may be implemented or that are within the scope of the claims. The term “exemplary” used herein means “serving as an example, instance, or illustration,” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form in order to avoid obscuring the concepts of the described examples.

(150) In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If just the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

(151) Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

(152) The various illustrative blocks and modules described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a DSP, an ASIC, an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

(153) The functions described herein may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software, functions described above can be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations. Further, a system as used herein may be a

collection of devices, a single device, or aspects within a single device.

(154) Also, as used herein, including in the claims, “or” as used in a list of items (for example, a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an exemplary step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

(155) Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A non-transitory storage medium may be any available medium that can be accessed by a general purpose or special purpose computer. By way of example, and not limitation, non-transitory computer-readable media can comprise RAM, ROM, EEPROM, compact disk (CD) ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other non-transitory medium that can be used to carry or store desired program code means in the form of instructions or data structures and that can be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of medium. Disk and disc, as used herein, include CD, laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers.

Combinations of the above are also included within the scope of computer-readable media.

(156) The description herein is provided to enable a person skilled in the art to make or use the disclosure. Various modifications to the disclosure will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

Claims

1. A method for data management, comprising: receiving a first packet at a data management system, wherein the first packet is from a host that is within a network that includes one or more hosts for which the data management system is configured to provide backup and recovery services, and wherein the first packet is associated with a request to establish, via a port at which the first packet is received, a connection between the host and a storage entity within the data management system that is used to back up the host; routing the first packet to the storage entity using a demultiplexer of the data management system that is configured to monitor the port when the storage entity operates to receive packets in a server mode via the port, the demultiplexer configured to identify the storage entity based at least in part on an internet protocol address associated with the host; transmitting, from the storage entity based at least in part on receiving the first packet, a second packet to a domain controller within the network, wherein the second packet requests that the domain controller authenticate the host, and wherein the second packet bypasses the demultiplexer based at least in part on the demultiplexer being configured not to monitor the port when the storage entity operates to transmit packets in a client mode via the port; receiving, at the storage entity from the domain controller, a third packet that indicates an authentication of the

host, wherein the third packet bypasses the demultiplexer based at least in part on being in response to the second packet; and establishing the connection between the storage entity and the host based at least in part on the authentication of the host indicated by the third packet.

2. The method of claim 1, further comprising: instantiating, within the network, a virtual machine configured to create a tunnel for communications between the data management system and the one or more hosts; and configuring the demultiplexer not to monitor the port when the storage entity operates to transmit packets in the client mode based at least in part on the packets being transmitted via the tunnel.

3. The method of claim 1, further comprising: allocating a virtual internet protocol address to the domain controller, the virtual internet protocol address different than a private internet protocol address of the domain controller, wherein the second packet is transmitted to the domain controller using the virtual internet protocol address.

4. The method of claim 1, further comprising: instantiating, within the network, a virtual machine configured to create a tunnel for communications between the data management system and the one or more hosts; obtaining, via the virtual machine, a list of one or more domain controllers within the network, wherein the one or more listed domain controllers are associated with authenticating the one or more hosts; and creating, before transmitting the second packet, an account for the data management system at the domain controller based at least in part on the domain controller being included in the one or more listed domain controllers, wherein the third packet is received from the domain controller based at least in part on the account created at the domain controller.

5. The method of claim 4, further comprising: transmitting, to the virtual machine, a fourth packet requesting the list of one or more domain controllers, wherein the list of one or more domain controllers is obtained via the virtual machine in response to the fourth packet.

6. The method of claim 4, further comprising: maintaining, via the virtual machine, an up-to-date list of the one or more domain controllers within the network.

7. The method of claim 4, further comprising: refraining from accessing a domain name system (DNS) server within the network to obtain the list of one or more domain controllers, the refraining based at least in part on obtaining the list of one or more domain controllers via the virtual machine.

8. The method of claim 4, wherein: the domain controller is associated with an internet protocol address that, based at least in part on the domain controller being within the network, is unknown to the data management system prior to the list of one or more domain controllers being obtained, and the second packet is transmitted to the domain controller based at least in part on obtaining the list of one or more domain controllers.

9. The method of claim 1, wherein the storage entity operating to transmit packets in the client mode comprises the storage entity transmitting packets to request to establish a respective connection between the storage entity and a respective entity within the network.

10. The method of claim 1, wherein the storage entity operating to receive packets in the server mode comprises the storage entity receiving packets to request to establish a respective connection between the storage entity and a respective entity within the network.

11. An apparatus for data management, comprising: at least one processor; memory coupled with the at least one processor; and instructions stored in the memory and executable by the at least one processor to cause the apparatus to: receive a first packet at a data management system, wherein the first packet is from a host that is within a network that includes one or more hosts for which the data management system is configured to provide backup and recovery services, and wherein the first packet is associated with a request to establish, via a port at which the first packet is received, a connection between the host and a storage entity within the data management system that is used to back up the host; route the first packet to the storage entity using a demultiplexer of the data management system that is configured to monitor the port when the storage entity operates to receive packets in a server mode via the port, the demultiplexer configured to identify the storage

entity based at least in part on an internet protocol address associated with the host; transmit, from the storage entity based at least in part on receiving the first packet, a second packet to a domain controller within the network, wherein the second packet requests that the domain controller authenticate the host, and wherein the second packet bypasses the demultiplexer based at least in part on the demultiplexer being configured not to monitor the port when the storage entity operates to transmit packets in a client mode via the port; receive, at the storage entity from the domain controller, a third packet that indicates an authentication of the host, wherein the third packet bypasses the demultiplexer based at least in part on being in response to the second packet; and establish the connection between the storage entity and the host based at least in part on the authentication of the host indicated by the third packet.

12. The apparatus of claim 11, wherein the instructions are further executable by the at least one processor to cause the apparatus to: instantiate, within the network, a virtual machine configured to create a tunnel for communications between the data management system and the one or more hosts; and configure the demultiplexer not to monitor the port when the storage entity operates to transmit packets in the client mode based at least in part on the packets being transmitted via the tunnel.

13. The apparatus of claim 11, wherein the instructions are further executable by the at least one processor to cause the apparatus to: allocate a virtual internet protocol address to the domain controller, the virtual internet protocol address different than a private internet protocol address of the domain controller, wherein the second packet is transmitted to the domain controller using the virtual internet protocol address.

14. The apparatus of claim 11, wherein the instructions are further executable by the at least one processor to cause the apparatus to: instantiate, within the network, a virtual machine configured to create a tunnel for communications between the data management system and the one or more hosts; obtain, via the virtual machine, a list of one or more domain controllers within the network, wherein the one or more listed domain controllers are associated with authenticating the one or more hosts; and create, before transmitting the second packet, an account for the data management system at the domain controller based at least in part on the domain controller being included in the one or more listed domain controllers, wherein the instructions are executable by the at least one processor to cause the apparatus to receive the third packet from the domain controller based at least in part on the account created at the domain controller.

15. The apparatus of claim 14, wherein the instructions are further executable by the at least one processor to cause the apparatus to: transmit, to the virtual machine, a fourth packet requesting the list of one or more domain controllers, wherein the list of one or more domain controllers is obtained via the virtual machine in response to the fourth packet.

16. The apparatus of claim 14, wherein the instructions are further executable by the at least one processor to cause the apparatus to: maintain, via the virtual machine, an up-to-date list of the one or more domain controllers within the network.

17. The apparatus of claim 14, wherein the instructions are further executable by the at least one processor to cause the apparatus to: refrain from accessing a domain name system (DNS) server within the network to obtain the list of one or more domain controllers, the refraining based at least in part on obtaining the list of one or more domain controllers via the virtual machine.

18. The apparatus of claim 14, wherein: the domain controller is associated with an internet protocol address that, based at least in part on the domain controller being within the network, is unknown to the data management system prior to the list of one or more domain controllers being obtained, and instructions are executable by the at least one processor to cause the apparatus to transmit the second packet to the domain controller based at least in part on obtaining the list of one or more domain controllers.

19. The apparatus of claim 11, wherein: to operate transmit packets in the client mode, the storage entity is operable to transmit packets to request to establish a respective connection between the

storage entity and a respective entity within the network, and to operate to receive packets in the server mode, the storage entity is operable to receive packets to request to establish the respective connection between the storage entity and the respective entity within the network.

20. A non-transitory computer-readable medium storing code for data management, the code comprising instructions executable by at least one processor to: receive a first packet at a data management system, wherein the first packet is from a host that is within a network that includes one or more hosts for which the data management system is configured to provide backup and recovery services, and wherein the first packet is associated with a request to establish, via a port at which the first packet is received, a connection between the host and a storage entity within the data management system that is used to back up the host; route the first packet to the storage entity using a demultiplexer of the data management system that is configured to monitor the port when the storage entity operates to receive packets in a server mode via the port, the demultiplexer configured to identify the storage entity based at least in part on an internet protocol address associated with the host; transmit, from the storage entity based at least in part on receiving the first packet, a second packet to a domain controller within the network, wherein the second packet requests that the domain controller authenticate the host, and wherein the second packet bypasses the demultiplexer based at least in part on the demultiplexer being configured not to monitor the port when the storage entity operates to transmit packets in a client mode via the port; receive, at the storage entity from the domain controller, a third packet that indicates an authentication of the host, wherein the third packet bypasses the demultiplexer based at least in part on being in response to the second packet; and establish the connection between the storage entity and the host based at least in part on the authentication of the host indicated by the third packet.
